FCC Part 15C
Measurement and Test Report

For

Shenzhen Gulf Asiamac Enterprise Co., Limited

FCC ID:2AQKG-B28S

FCC Rule(s):	FCC Part 15.249
Product Description:	Bluetooth speaker
Model:	B28S,BT460,BT200,BT450,TG116,TG117,SPK13GO,SPK12GO,I77,E5000,E6000,BT20
Brand:	Asiamac
Report No.:	BST0114357
Tested Date:	July. 21-August 01, 2018
Issued Date:	August 02, 2018
Tested By:	Messi Wang / Engineer
Reviewed By:	Lisa. Li / EMC Manager
Approved & Authorized By:	Mike mo / PSQ Manager
Prepared By:	

BSL Testing Co.,LTD.
NO. 24, ZH Park, Nantou, Shenzhen, 518000 China
Tel: 400-882-9628 Fax: 86- 755-26508703

TABLE OF CONTENTS

1. GENERAL INFORMATION....3
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)....3
1.2 TEST STANDARDS....4
1.3 TEST METHODOLOGY....4
1.4 TEST FACILITY....4
1.5 EUT SETUP AND TEST MODE....5
1.6 MEASUREMENT UNCERTAINTY....6
1.7 TEST EQUIPMENT LIST AND DETAILS....7
2. SUMMARY OF TEST RESULTS....8
3. ANTENNA REQUIREMENTS....9
3.1 STANDARD APPLICABLE....9
3.2 TEST RESULT....9
4. RADIATED EMISSIONS....10
4.1 STANDARD APPLICABLE....10
4.2 TEST PROCEDURE....10
4.3 CORRECTED AMPLITUDE & MARGIN CALCULATION....12
4.4 ENVIRONMENTAL CONDITIONS....12
4.5 SUMMARY OF TEST RESULTS/PLOTS....12
5. OUT OF BAND EMISSIONS....17
5.1 STANDARD APPLICABLE....17
5.2 TEST PROCEDURE....17
5.3 ENVIRONMENTAL CONDITIONS....17
5.4 SUMMARY OF TEST RESULTS/PLOTS....17
6. EMISSION BANDWIDTH....21
6.1 STANDARD APPLICABLE....21
6.2 TEST PROCEDURE....21
6.3 ENVIRONMENTAL CONDITIONS....21
6.4 SUMMARY OF TEST RESULTS/PLOTS....22
7. CONDUCTED EMISSIONS....28
7.1 TEST PROCEDURE....28
7.2 BASIC TEST SETUP BLOCK DIAGRAM....28
7.3 ENVIRONMENTAL CONDITIONS....28
7.4 TEST RECEIVER SETUP....29
7.5 SUMMARY OF TEST RESULTS/PLOTS....29
7.6 CONDUCTED EMISSIONS TEST DATA....29

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant:	Shenzhen Gulf Asiamac Enterprise Co., Limited
Address of applicant:	B12 Building, Yintian industrial park,Xixiang Town,Baoan district,Shenzhen,Guangdong,China
Manufacturer:	Shenzhen Gulf Asiamac Enterprise Co., Limited
Address of manufacturer:	B12 Building, Yintian industrial park,Xixiang Town,Baoan district,Shenzhen,Guangdong,China

General Description of EUT	
Product Name:	Bluetooth speaker
Trade Name:	Asiamac
Model No.:	B28S
Adding Model(s):	BT460,BT200,BT450,TG116,TG117,SPK13GO,SPK 12GO,I77,E5000,E6000,BT20
Rated Voltage:	DC 3.7V from battery and DC 5V from USB
Power Adapter Model:	N/A
Note: The test data is gathered from a production sample, provided by the manufacturer.	

Technical Characteristics of EUT	
Frequency Range:	2402-2480MHz
Data Rate:	1Mbps, 2Mbps, 3Mbps
Modulation:	GFSK, Pi/4 QDPSK, 8DPSK
Quantity of Channels:	79
Channel Separation:	1MHz
Antenna Type:	PCB
Antenna Gain:	1.2dBi
Lowest Internal Frequency of EUT:	26MHz

1.2 Test Standards

The following report is prepared on behalf of the Shenzhen Gulf Asiamac Enterprise Co., Limited in accordance with FCC Part 15, Subpart B, Subpart C, and section 15.107, 15.203, 15.205, 15.207, 15.209 and 15.249 of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Part 15, Subpart C, and section 15.107,15.203, 15.205, 15.207, 15.209 and 15.249 of the Federal Communication Commissions rules.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which results in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard for Testing Unlicensed Wireless Devices, and ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

1.4 Test Facility

BSL Testing Co.,LTD.
NO. 24, ZH Park, Nantou, Shenzhen, 518000 China
Designation Number : CN1217
Test Firm Registration Number: 866035

1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	Low Channel	2402MHz
TM2	Middle Channel	2442MHz
TM3	High Channel	2480MHz
TM4	Hopping	2402-2480MHz

Modulation Configure			
Modulation	Packet	Packet Type	Packet Size
GFSK	DH1	4	27
	DH3	11	183
	DH5	15	339
Pi/4 DQPSK	2DH1	20	54
	2DH3	26	367
	2DH5	30	679
8DPSK	3DH1	24	83
	3DH3	27	552
	3DH5	31	1021
Normal mode: the Bluetooth has been tested on the modulation of GFSK, (Pi/4)DQPSK and 8DPSK, compliance test and record the worst case.			

Special Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
Notebook	Lenovo	E23	EB12648265
USB	ESR	S01	19682904994

1.6 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
RF Output Power	Conducted	±0.42dB
Occupied Bandwidth	Conducted	±1.5%
Conducted Spurious Emission	Conducted	±2.17dB
Conducted Emissions	Conducted	±2.88dB
Transmitter Spurious Emissions	Radiated	±5.1dB

1.7 Test Equipment List and Details

Description	Manufacturer	Model	Serial No.	Cal Date	Due. Date
Communication Tester	Rohde & Schwarz	CMW500	100358	2017-10-21	2018-10-20
Spectrum Analyzer	R&S	FSP40	100550	2017-10-21	2018-10-20
Test Receiver	R&S	ESCI7	US47140102	2017-10-21	2018-10-20
Signal Generator	HP	83630B	3844A01028	2017-10-22	2018-10-21
Test Receiver	R&S	ESPI-3	100180	2017-10-21	2018-10-20
Amplifier	Agilent	8449B	4035A00116	2017-10-22	2018-10-21
Amplifier	HP	8447E	2945A02770	2017-10-22	2018-10-21
Signal Generator	IFR	2023A	202307/242	2017-10-22	2018-10-21
Broadband Antenna	SCHAFFNER	2774	2774	2017-10-17	2018-10-16
Biconical and log periodic antennas	ELECTRO-METRICS	EM-6917B-1	171	2017-10-17	2018-10-16
Horn Antenna	R&S	HF906	100253	2017-10-17	2018-10-16
Horn Antenna	EM	EM-6961	6462	2017-10-17	2018-10-16
LISN	R&S	ESH3-Z5	100196	2017-10-17	2018-10-16
LISN	COM-POWER	LI-115	02027	2017-10-17	2018-10-16
3m Semi-Anechoic Chamber	Chengyu Electron	9 (L)*6 (W)* 6 (H)	BSL086	2017-10-21	2018-10-20
Horn Antenna	A-INFOMW	LB-180400KF	BSL088	2017-10-21	2018-10-20

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§ 15.203	Antenna Requirement	PASS
§15.205	Restricted Band of Operation	PASS
§ 15.207(a)	Conducted Emission	PASS
§ 15.209(a)(f)	Radiated Spurious Emissions	PASS
§15.249(a)	Field Strength of Emissions	PASS
§15.249(d)	Out of Band Emission	PASS
§15.215 (c)	Emission Bandwidth	PASS

Note: PASS: applicable, N/A: not applicable.

3. Antenna Requirements

3.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.2 Test Result

This product has a PCB antenna, fulfill the requirement of this section.

4. Radiated Emissions

4.1 Standard Applicable

According to §15.249(a), the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental Frequency	Field strength of fundamental (milli-volts/meter)	Field strength of Harmonics (micro-volts/meter)
902-928 MHz	50	500
2400-2483.5 MHz	50	500
5725-5875 MHz	50	500
24.0-24.25 GHz	250	2500

(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

4.2 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.205 15.249(a) and FCC Part 15.209 Limit.
The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.
The spacing between the peripherals was 10 cm.





Frequency :9kHz-30MHz	Frequency :30MHz-1GHz	Frequency :Above 1GHz
RBW=10KHz,	RBW=120KHz,	RBW=1MHz,
VBW =30KHz	VBW=300KHz	VBW=3MHz(Peak), 10Hz(AV)
Sweep time= Auto	Sweep time= Auto	Sweep time= Auto
Trace = max hold	Trace = max hold	Trace = max hold
Detector function = peak	Detector function = peak, QP	Detector function = peak, AV

4.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

Corr. Ampl. = Indicated Reading + Ant. Factor + Cable Loss – Ampl. Gain

The "**Margin**" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dBμV means the emission is 6dBμV below the maximum limit. The equation for margin calculation is as follows:

Margin = Corr. Ampl. – FCC Part 15C Limit

4.4 Environmental Conditions

Temperature:	24 °C
Relative Humidity:	60 %
ATM Pressure:	1012 mbar

4.5 Summary of Test Results/Plots

According to the data below, the FCC Part 15.205, 15.209 and 15.249 standards, and had the worst cases.

Note:
1. Worst-case radiated emission below 1GHz is GFSK (CH Low) mode.
2. Worst-case radiated emission above 1GHz is (Pi/4)DQPSK (CH Low, Middle, High) mode.

Plot of Radiated Emissions Test Data (30MHz to 1GHz): GFSK (CH Low) mode:

Test Specification: Horizontal



No.	Mk.	Freq.	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	*	34.8823	33.87	40.00	-6.13	QP			
2		49.1865	33.80	40.00	-6.20	QP			
3		75.4462	29.69	40.00	-10.31	QP			
4		111.7377	29.86	43.50	-13.64	QP			
5		206.3976	30.28	43.50	-13.22	QP			
6		356.6757	31.34	46.00	-14.66	QP			

Test Specification: *Vertical*



No.	Mk.	Freq.	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		37.6798	28.84	40.00	-11.16	QP			
2	*	51.4806	34.77	40.00	-5.23	QP			
3		75.4462	25.69	40.00	-14.31	QP			
4		118.1860	35.39	43.50	-8.11	QP			
5		180.0165	26.02	43.50	-17.48	QP			
6		345.5951	32.01	46.00	-13.99	QP			

Spurious Emissions Above 1GHz :(Pi/4)DQPSK (CH Low, Middle, High) mode.

Frequency	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel-2402MHz					
2402	94.97	114	-19.03	H	PK
2402	81.98	94	-12.02	H	AV
4804	57.31	74	-16.69	H	PK
4804	46.11	54	-7.89	H	AV
7206	58.21	74	-15.79	H	PK
7206	43.2	54	-10.8	H	AV
2402	93.91	114	-20.09	V	PK
2402	80.97	94	-13.03	V	AV
4804	56.36	74	-17.64	V	PK
4804	45.33	54	-8.67	V	AV
7206	60.38	74	-13.62	V	PK
7206	44.42	54	-9.58	V	AV
Middle Channel-2442MHz					
2442	93.54	114	-20.46	H	PK
2442	79.6	94	-14.4	H	AV
4884	54.23	74	-19.77	H	PK
4884	43.13	54	-10.87	H	AV
7326	57.26	74	-16.74	H	PK
7326	42.15	54	-11.85	H	AV
2442	93.64	114	-20.36	V	PK
2442	79.62	94	-14.38	V	AV
4884	57.55	74	-16.45	V	PK
4884	46.44	54	-7.56	V	AV
7326	60.45	74	-13.55	V	PK
7326	45.48	54	-8.52	V	AV

Frequency	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	H/V	
2480	93.33	114	-20.67	H	PK
2480	80.81	94	-13.19	H	AV
4960	60.34	74	-13.66	H	PK
4960	45.62	54	-8.38	H	AV
7440	52.51	74	-21.49	H	PK
7440	43.22	54	-10.78	H	AV
2480	91.65	114	-22.35	V	PK
2480	78.59	94	-15.41	V	AV
4960	55.07	74	-18.93	V	PK
4960	41.91	54	-12.09	V	AV
7440	59.49	74	-14.51	V	PK
7440	44.32	54	-9.68	V	AV

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, which above 5th Harmonics are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
The measurements greater than 20dB below the limit from 9kHz to 30MHz..

5. Out of Band Emissions

5.1 Standard Applicable

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

5.2 Test Procedure

As the radiation test, set the Lowest and Highest Transmitting Channel, observed the outside band of 2400MHz to 2483.5MHz, than mark the higher-level emission for comparing with the FCC rules.

5.3 Environmental Conditions

Temperature:	24 °C
Relative Humidity:	60 %
ATM Pressure:	1012 mbar

5.4 Summary of Test Results/Plots

Note: We pre-scan all mode, the worst data is DH1, 2DH1, 3DH1.

The edge emissions are below the FCC 15.209 Limits or complies with the 15.249 requirements.

Please refer to the test plots as below.

Worst mode: GFSK (DH1)

Lowest:



Date: 1.AUG.2018 09:41:20

Highest:



Date: 1.AUG.2018 09:54:43

Worst mode: Pi/4 QDPSK (2DH1)

Lowest:



Date: 1.AUG.2018 09:48:42

Highest:



Date: 1.AUG.2018 09:56:41

Worst mode: 8DPSK (3DH1)

Lowest:



Date: 1.AUG.2018 09:51:24

Highest:



Date: 1.AUG.2018 09:58:10

6. Emission Bandwidth

6.1 Standard Applicable

According to 15.215 (c), intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

6.2 Test Procedure

According to the ANSI 63.10-2013, the emission bandwidth test method as follows.

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
Set span = 1MHz, centered on a transmitting channel
RBW ≥1% 20dB Bandwidth, VBW ≥RBW
Sweep = auto
Detector function = peak
Trace = max hold
All the trace to stabilize, use the marker-to-peak function to set the marker to the peak of the emission, use the marker-delta function to measure and record the 20dB down and 99% bandwidth of the emission.

6.3 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	53%
ATM Pressure:	1018 mbar

6.4 Summary of Test Results/Plots

Worst mode: GFSK (DH1)

Channel	Frequency MHz	20dB Bandwidth kHz
Low Channel	2402	906
Middle Channel	2442	900
High Channel	2480	900

Worst mode: Pi/4 QDPSK (2DH1)

Channel	Frequency MHz	20dB Bandwidth kHz
Low Channel	2402	1128
Middle Channel	2442	1128
High Channel	2480	1128

Worst mode: 8DPSK (3DH1)

Channel	Frequency MHz	20dB Bandwidth kHz
Low Channel	2402	1152
Middle Channel	2442	1158
High Channel	2480	1164

Please refer to the following test plots

Worst mode: GFSK (DH1)

Low Channel:



Date: 1.AUG.2018 10:18:20

Middle Channel:



Date: 1.AUG.2018 10:09:57

High Channel:



Date: 1.AUG.2018 10:08:08

Worst mode: Pi/4 QDPSK (2DH1)

Low Channel:



Date: 1.AUG.2018 10:25:53

Middle Channel:



Date: 1.AUG.2018 10:12:45

High Channel:



Date: 1.AUG.2018 10:06:22

Worst mode: 8DPSK (3DH1)

Low Channel:



Date: 1.AUG.2018 10:28:09

Middle Channel:



Date: 1.AUG.2018 10:15:36

High Channel:



Date: 1.AUG.2018 10:04:01

7. Conducted Emissions

7.1 Test Procedure

The setup of EUT is according with per ANSI C63.4-2014 measurement procedure. The specification used was with the FCC Part 15.207 Limit.
The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.
The spacing between the peripherals was 10 cm.

7.2 Basic Test Setup Block Diagram



7.3 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52%
ATM Pressure:	1012 mbar

7.4 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency..... 150 kHz
Stop Frequency..... 30 MHz
Sweep Speed..... Auto
IF Bandwidth..... 10 kHz
Quasi-Peak Adapter Bandwidth..... 9 kHz
Quasi-Peak Adapter Mode.....Normal

7.5 Summary of Test Results/Plots

According to the data in section 7.7, the EUT complied with the FCC Part 15.207 Conducted margin for this device.

7.6 Conducted Emissions Test Data



No.	Mk.	Freq.	Measure-ment	Limit	Over		
		MHz	dBuV	dBuV	dB	Detector	Comment
1		0.1806	35.59	64.45	-28.86	QP	
2		0.1806	22.91	54.45	-31.54	AVG	
3		0.2938	37.86	60.41	-22.55	QP	
4		0.2938	24.08	50.41	-26.33	AVG	
5	*	1.7660	45.42	56.00	-10.58	QP	
6		1.7660	32.89	46.00	-13.11	AVG	
7		6.4579	44.19	60.00	-15.81	QP	
8		6.4579	29.58	50.00	-20.42	AVG	
9		9.5259	43.23	60.00	-16.77	QP	
10		9.5259	28.39	50.00	-21.61	AVG	
11		25.0100	46.07	60.00	-13.93	QP	
12		25.0100	33.28	50.00	-16.72	AVG	

No.	Mk.	Freq.	Measure-ment	Limit	Over		
		MHz	dBuV	dBuV	dB	Detector	Comment
1		0.2938	39.36	60.41	-21.05	QP	
2		0.2938	26.07	50.41	-24.34	AVG	
3		0.6380	35.76	56.00	-20.24	QP	
4		0.6380	22.21	46.00	-23.79	AVG	
5	*	1.5780	44.58	56.00	-11.42	QP	
6		1.5780	31.07	46.00	-14.93	AVG	
7		6.6619	42.50	60.00	-17.50	QP	
8		6.6619	30.58	50.00	-19.42	AVG	
9		12.5457	46.34	60.00	-13.66	QP	
10		12.5457	32.40	50.00	-17.60	AVG	
11		26.8180	46.42	60.00	-13.58	QP	
12		26.8180	34.56	50.00	-15.44	AVG	

******* END OF REPORT *******