



FCC CFR47 Part 15 Subpart C ISED RSS-247 Certification Test Report

For the

Product	: SMART DIGITAL DOOR LOCK
Model	: PDS-100
FCC ID	: 2AQMR-PDS100
IC	: 24126-PDS100
Applicant	: PHILIA TECHNOLOGY Co., Ltd.
FCC Rule	: CFR 47 Part 15 Subpart C
ISED Rule	: RSS-247 Issue 2

We hereby certify that the above product has been tested by us with the listed rules and found in compliance with the regulation. The test data and results are issued on the test report no. **TR-W1808-003**

Signature

A handwritten signature in black ink, appearing to read 'Choi, Yeong-min', written over a horizontal line.

Choi, Yeong-min / Technical Manager

Date: 2018-08-06

Test Laboratory: ENG Co., Ltd.

It shall not be reproduced except in full, without the written approval of the ENG Co., Ltd. This document may be altered or revised by the ENG Co., Ltd. personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.

Report No.: TR-W1808-003

ENG Co., Ltd. 135-60 Gyeongchung-daero, Gyeongju-eup, Gyeongju-si, Gyeonggi-do, Korea 464-942

Report Form_01 (Rev.0)

FCC/ISED CERTIFICATION TEST REPORT

Project Number : EA1806C-107
Test Report Number : TR-W1808-003
Type of Equipment : SMART DIGITAL DOOR LOCK
Model Name : PDS-100
FCC ID : 2AQMR-PDS100
ISED Cert. Number : 24126-PDS100
Multiple Model Name : N/A
Applicant : PHILIA TECHNOLOGY Co., Ltd.
Address : A-904 Digital Empire, #387, Simin-daero, Dongan-gu, Anyang-si, Gyeonggi-do, KOREA
Manufacturer : PHILIA TECHNOLOGY Co., Ltd.
Address : A-904 Digital Empire, #387, Simin-daero, Dongan-gu, Anyang-si, Gyeonggi-do, KOREA
Regulation : FCC Part 15 Subpart C Section 15.247, ISED RSS-247 Issue2
Total page of Report : 44 Pages
Date of Receipt : 2018-06-19
Date of Issue : 2018-08-06
Test Result : PASS

This test report only contains the result of a single test of the sample supplied for the examination.
 It is not a generally valid assessment of the features of the respective products of the mass-production.

Prepared by	Song, In-young / Senior Engineer		2018-08-06
		Signature	Date
Reviewed by	Choi, Yeong-min / Technical Manager		2018-08-06
		Signature	Date

CONTENTS

Page

1. TEST SUMMARY	4
2. EUT (EQUIPMENT UNDER TEST) INFORMATION	6
3. TEST CONDITION	8
4. ANTENNA REQUIREMENT	10
4.1 ANTENNA DESCRIPTION	10
4.2 CONCLUSION	10
5. TEST RESULT	11
5.1 6 DB BANDWIDTH	11
5.2 99 % BANDWIDTH	14
5.3 MAXIMUM PEAK OUTPUT POWER	17
5.4 PEAK POWER SPECTRAL DENSITY	20
5.5 OUT OF BAND EMISSION	23
5.6 RADIATED EMISSION	28
APPENDIX I – TEST INSTRUMENTATION	44

Release Control Record

Issue Report No.	Issued Date	Details/Revisions
TR-W1808-003	2018-08-06	Initial Release
-	-	-

1. TEST SUMMARY

1.1 Regulations and results

The sample submitted for evaluation (Referred to below as the EUT) has been tested in accordance with the following regulations or standards.

FCC Reference Section	ISED Reference Section	Description	P	F	N.T.	Note
15.247(a)(2)	RSS-247 5.2 a)	6 dB Bandwidth Occupied Bandwidth	P			
15.247(b)(3)	RSS-247 5.4 d)	Maximum peak output power	P			
15.247(e)	RSS-247 5.2 b)	Power spectral density	P			
15.247(d)	RSS-247 5.5	Band Edge Conducted spurious emission	P			
15.205(a) 15.209(a)	RSS 247 5.5 RSS-GEN 8.9	Radiated spurious emissions	P			
15.207(a)	RSS GEN 8.8	AC power line conducted emissions			N.T.	Note 1

Remark:

P means Passed

F means Failed

N.T. means Not Tested

Note1. The EUT is operated by battery only. (used manganese dry cell as type AA)

1.2 Test Methodology

The tests mentioned in clause 1.1 in this test report were performed according to FCC CFR 47 Part 2, CFR 47 Part 15 and ANSI C63.10-2013, and RSS-Gen Issue 4, KDB 558074 D01DTS Meas. Guidance v04: Measurement Procedure PK is used for power measurement.

1.3 Additions, deviations, exclusions from standards

No additions, deviations or exclusions have been made from standard.

1.4 Purpose of the test

The test was performed to determine whether the equipment under test fulfills the requirements of the regulation stated in FCC Part 15 Subpart C Section 15.247, RGG-Gen and RSS-247

1.5 Test Facility

The measurement facilities are located at 135-60 Gyeongchung-daero, Gonjam-eup, Gwangju-si, Gyeonggi-do 12813, Korea. Description details of test facilities were submitted to the FCC and IC, designated by the RRA (Radio Research Agency), and accredited by Korea and accredited by KOLAS (Korea Laboratory Accreditation Scheme) in Korea according to the requirement of ISO 17025.

Laboratory Qualification	Registration No.	Mark
FCC	KR0160	
ISED(Canada)	IC 12721A	
RRA	KR0160	
Korean Agency for Technology and Standards	KT733	

2. EUT (Equipment Under Test) INFORMATION

2.1 General Description

The PHILIA TECHNOLOGY Co., Ltd., Model PDS-100 (referred to as the EUT in this report) is a SMART DIGITAL DOOR LOCK. The EUT is a device for transferring Bluetooth signal to an Smart phone through wireless communication. The product specification described herein was obtained from product data sheet or user's manual.

Operating Frequency	2 402 ~ 2 480 MHz
Max. RF Output Power	-4.71 dBm
Modulation Types	Bluetooth Low Energy
Number of Channels	40 CH
Channel Bandwidth	2 MHz
Generated or used Freq. in EUT	32.768 kHz, 13.56 MHz, 16 MHz, 32 MHz
Type of Antenna	☒ Integrated Type ☐ Dedicated Type
Antenna Gain	-7.45 dBi
Operating Temperature	-25 °C ~ + 50 °C
Normal Test Voltage	DC 6.0 V
Electrical Rating	DC 6.0 V
Test SW Version	nRFgo Studio Version: 1.21.2.10
RF power setting in TEST SW	N/A
Software Version	1.0
Hardware Version	1.0

2.2 Available channel number and frequency

Operating Mode: Bluetooth LE, 2 MHz Channel Spacing					
Channel	Frequency(MHz)	Channel	Frequency(MHz)	Channel	Frequency(MHz)
0	2 402	14	2 430	28	2 458
1	2 404	15	2 432	29	2 460
2	2 406	16	2 434	30	2 462
3	2 408	17	2 436	31	2 464
4	2 410	18	2 438	32	2 466
5	2 412	19	2 440	33	2 468
6	2 414	20	2 442	34	2 470
7	2 416	21	2 444	35	2 472
8	2 418	22	2 446	36	2 474
9	2 420	23	2 448	37	2 476
10	2 422	24	2 450	38	2 478
11	2 424	25	2 452	39	2 480
12	2 426	26	2 454		
13	2 428	27	2 456		

2.3 Additional Model

None

3. TEST CONDITION

3.1 Equipment Used During Test

The following peripheral devices and/or interface cables were connected during the measurement:

Description	Model No.	Serial No.	Manufacturer.
SMART DIGITAL DOOR LOCK (EUT)	PDS-100	N/A	PHILIA TECHNOLOGY Co., Ltd.
Test Jig	FT232	N/A	N/A
Notebook PC	E5470	ZU10190-15008	DELL
Adapter for Notebook PC	LA65NM130	N/A	DELL

3.2 Mode of operation during the test

Software used to control the EUT for staying in continuous transmitting mode is programmed.

The used modulation type for the testing is GFSK.


3.3 Preliminary Testing for Worst case configuration

For finding worst case configuration and operating mode, preliminary testing was performed and radiated emission and conducted emission tests were performed with the EUT set to transmit and receive at the channel with the highest output power as worst case scenario. Since the EUT is a fixed type device, all spurious emission tests were performed in one axis direction.


3.3.1 Test Channel and Frequency

Operating Mode	Test Channel	Frequency
Bluetooth Low Energy	Low Channel	2 402 MHz
	Middle Channel	2 440 MHz
	High Channel	2 480 MHz


3.3 Test Setup Drawing (Radiated Test below 1 GHz)



(Radiated Test above 1 GHz)



(Conducted Test)



3.4 EUT Modifications

- No EMC Relevant Modifications were performed by this test laboratory.

4. ANTENNA REQUIREMENT

According to FCC CFR 47 Part 15 section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provision of this section.

4.1 Antenna Description

Frequency Band (GHz)	Antenna Type	Max Peak Gain (dBi)	Connector Type
2.4	PCB Pattern Antenna	-7.45	-

4.2 Conclusion

The antenna connector type of the EUT is PCB Pattern Antenna, so the EUT met the requirement.

5. TEST RESULT

5.1 6 dB Bandwidth

5.1.1 Limit


The minimum 6 dB bandwidth shall be at least 500 kHz acc to Section 15.247 (a) (2), and RSS-247 5.2 (a).

5.1.2 Method of Measurement



Reference to KDB 558074 D01 DTS Meas Guidance v04: 8.1 Option 1

The transmitter output is connected to a spectrum analyzer with the RBW set to 100 kHz, VBW $\geq 3 \times$ RBW, peak detector and max hold.

5.1.3 Test Data

Date of Test	2018-07-09	Temperature	(24.2 $\pm$ 1.0) °C
		Relative humidity	(65.1 $\pm$ 3.0) % R.H.
Test Result	PASS	Tested by	Do-heon Kim 
Operating Mode: Bluetooth LE			
Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)
Low	2 402	0.66	0.5
Middle	2 440	0.66	
High	2 480	0.66	

5.1.4 Test Plots




Operating Mode: Bluetooth LE (High Channel)

MultiView Spectrum

Ref Level 10.00 dBm
Att 20 dB
TDF
RBW 100 kHz
VBW 300 kHz
Mode Auto FFT
SWT 41.71 μ s (~8.1 ms)

1 Frequency Sweep



2 Marker Table

Type	Ref	Trc	X-Value	Y-Value	Function	Function Result
M1	1	1	2.480042 GHz	-9.03 dBm	ndB	6.0 dB
T1	1	1	2.4797093 GHz	-15.01 dBm	ndB down BW	659.30 kHz
T2	1	1	2.4803686 GHz	-14.93 dBm	Q Factor	3761.4

Measuring... 09.07.2018 13:35:19

Date: 9 JUL 2018 13:35:19

5.2 99 % Bandwidth

5.2.1 Limit

Not applicable. For reporting purpose only.


5.2.2 Method of Measurement

The transmitter output is connected to the spectrum analyzer. The RBW is set to 1 % to 5 % of the OBW.


The span is set to capture all products of the modulation process, including the emission skirts.

The VBW is set to 3 times the RBW. The sweep time is coupled and peak detection and max hold mode is used. The spectrum analyzer internal 99% bandwidth function is utilized.

5.2.3 Test Data

Date of Test	2018-07-09	Temperature	(24.2 ± 1.0) °C
		Relative humidity	(65.1 ± 3.0) % R.H.
Test Result	PASS	Tested by	Do-heon Kim 
Operational Mode: Bluetooth LE			
Channel	Frequency (MHz)		99 % Bandwidth (MHz)
Low	2 402		1.01
Middle	2 440		1.01
High	2 480		1.02

5.2.4 Test Plots




Operating Mode: Bluetooth LE (High Channel)

MultiView Spectrum

Ref Level 10.00 dBm
Att 20 dB
TDF
RBW 30 kHz
VBW 100 kHz
SWT 140 μ s (~7.0 ms)
Mode Auto FFT

1 Occupied Bandwidth



2 Marker Table						
Type	Ref	Trc	X-Value	Y-Value	Function	Function Result
M1		1	2.480048 GHz	-9.22 dBm	Occ Bw	1.018916392 MHz
T1		1	2.4795407 GHz	-26.39 dBm	Occ Bw Centroid	2.480050157 GHz
T2		1	2.48055962 GHz	-27.55 dBm	Occ Bw Freq Offset	50.156900519 kHz

Date: 9 JUL 2018 13:36:00

Measuring... 09.07.2018 13:36:01

5.3 Maximum Peak Output Power

5.3.1 Limit

Acc. To section 15.247 and RSS-247 5.4 d), For system using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt, based on the use of antennas with directional gains that do not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

5.3.2 Method of Measurement

Reference to KDB 558074 D01 DTS Meas Guidance v04: 9.1.1 RBW $\geq$ DTS bandwidth



The cable assembly insertion loss was entered as an offset in the spectrum analyzer to allow for direct reading of power.

5.3.3 Test Data for Output Power


Date of Test		2018-07-09	Temperature	(24.2 ± 1.0) °C
			Relative humidity	(65.1 ± 3.0) % R.H.
Test Result		PASS	Tested by	Do-heon Kim 
Operating Mode: Bluetooth LE				
Channel	Frequency (MHz)	Measured Value (dBm)	Limit (dBm)	Margin (dB)
Low	2 402	-4.71	30	34.71
Middle	2 440	-6.21		36.21
High	2 480	-8.62		38.62

Remark. Margin = Limit – Measured Value

5.3.4 Test Plots



Operating Mode: Bluetooth LE (High Channel)



Date: 9 JUL 2018 13:40:01

5.4 Peak Power Spectral Density

5.4.1 Limit


Acc. To section 15.247 and RSS-247 5.2 b), the power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

5.4.2 Method of Measurement

Reference to KDB 558074 D01 DTS Meas Guidance v04: 10.2 Method PKPSD (peak PSD).


The transmitter output is connected to a spectrum analyzer with the RBW set from 3 kHz to 100 kHz,
VBW $\geq$ 3 X RBW, peak detector and max hold.

5.4.3 Test Data


Date of Test	2018-07-09	Temperature	(24.2 ± 1.0) °C	
		Relative humidity	(65.1 ± 3.0) % R.H.	
Test Result	PASS	Tested by	Do-heon Kim 	
Operating Mode: Bluetooth LE				
Channel	Frequency (MHz)	Measured Value (dBm)	Limit (dBm)	Margin (dB)
Low	2 402	-18.13	8	26.13
Middle	2 440	-19.55		27.55
High	2 480	-21.41		29.41

Remark. Margin = Limit – Measured Value

5.4.4 Test Plots



Operating Mode: Bluetooth LE (High Channel)



Date: 9 JUL 2018 14:23:57

5.5 Out of Band Emission


5.5.1 Limit

Acc. To section 15.247(d) and RSS-247 5.5, In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in 15.209(a) is not required. In addition, radiated emission which in the restricted band, as define in section §15.205(a), must also comply the radiated emission limits specified in section §15.209(a) (see section §15.205(c))


5.5.2 Method of Measurement

Reference to KDB 558074 D01 DTS Meas Guidance v04: 11.0 Emissions in non-restricted frequency bands. The transmitter output is connected to a spectrum analyzer with the RBW set to 100 kHz, VBW $\geq 3 \times$ RBW, peak detector and max hold. Measurements utilizing these settings are made of the in-band reference level, band-edge (where measurements to the general radiated limits will not be made) and out-of-band emissions.


5.5.3 Test Data for Operating mode: Bluetooth LE

Date of Test	2018-07-09	Temperature	(24.2 ± 1.0) °C
		Relative humidity	(65.1 ± 3.0) % R.H.
Test Result	PASS	Tested by	Do-heon Kim 


Band-edge and Restricted band – Low channel




Band-edge and Restricted band – High channel




Non-restricted band – Low Channel (1)




Non-restricted band – Low Channel (2)




Non-restricted band – Middle Channel (1)



Non-restricted band – Middle Channel (2)




Non-restricted band – High Channel (1)



Date: 9 JUL 2018 14:11:41

Non-restricted band – High Channel (2)



Date: 9 JUL 2018 14:13:23

5.6 Radiated Emission

5.6.1 Limit

Acc. To section 15.205, 15.209, and RSS-Gen 8.9, following table shall be applied.

Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m
30 – 88	100	40
88 – 216	150	43.5
216 – 960	200	46
Above 960	500	24

5.6.2 Method of Measurement

Reference to KDB 558074 D01 DTS Meas Guidance v04: 12.1 Radiated emission measurements.

The radiated emissions measurements were on 3 m, semi-anechoic chamber. The EUT and other support equipment were placed on a non-conductive table 80 cm for below 1 GHz and 1.5 m for above 1 GHz above the ground plane. The interconnecting cables from outside test site were inserted into ferrite clamps at the point where the cables reach the turntable.

The frequency spectrum from 30 MHz to 25 GHz was scanned and emission levels maximized at each frequency recorded. The system was rotated 360°, and the antenna was varied in height between 1.0 m and 4.0 m in order to determine the maximum emission levels. This procedure was performed for both horizontal and vertical polarization of the receiving antenna.

For measurement below 1 GHz, the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For peak emission measurements above 1 GHz the resolution bandwidth is set to 1 MHz; the video bandwidth is set to 3 MHz and for average measurement, resolution bandwidth is set to 1 MHz; and the video bandwidth is set to 10 Hz, when duty cycle is more than 98 %. If duty cycle is less than 98 %, the video bandwidth is set to $\geq 1/T$, where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

For measurements above 1 GHz the resolution bandwidth is set to 1 MHz; the video bandwidth is set to 3 MHz. The spectrum from 30 MHz to 25 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in each applicable band.

5.6.3 Test Site Requirement for KDB 414788 D01

Acc. to KDB 414788 D01 Radiated Test Site v01, Semi Anechoic Chamber (SAC) shall be verified test results below 30 MHz with Open Area Test Site (OATS), so we compared test results between the measurements from our SAC and an OATS and found test results almost same, so we ***declare test result for below 30 MHz from our SAC is valid and met the requirement acc. to KDB 414788 D01 Radiated Test Site v01.***

5.6.4 Measurement Uncertainty

Measurement uncertainties were not taken into account and following uncertainty levels have been estimated for tests performed on the apparatus. The measurement uncertainties are given with at least 95 % confidence.

Frequency Range	Uncertainty	Frequency Range	Uncertainty
9 kHz ~ 30 MHz	± 2.1 dB	30 MHz ~ 1 GHz	± 4.8 dB
1 GHz ~ 18 GHz	± 5.0 dB	18 GHz ~25 GHz	± 5.3 dB

5.6.5 Sample Calculated Example

At 80 MHz

Limit = 40.0 dBuV/m

Result = Receiver reading value + Antenna Factor + Cable Loss – Pre-amplifier gain = 30 dBuV/m


Margin = Limit – Result = 40 – 30 = 10

so the EUT has 10.0 dB margin at 80 MHz

5.6.6 Test Data

Date of Test	2018-07-20	Temperature	(22.6 ± 2.7) °C			
		Relative humidity	(50.4 ± 5.9) % R.H.			
Measurement Frequency Range		9 kHz ~ 25 GHz				
Test Result	PASS	Tested By		Do-heon Kim 		
Frequency range	Detector Mode	Resolution BW	Video BW	Video Filtering	Measurement distance	
Below 30 MHz	Peak or Q.P.	9 kHz	100 kHz	-	3 m	
30 MHz ~ 1 000 MHz	Peak or Q.P.	100 kHz	300 kHz	-	3 m	
Above 1 GHz	Peak	1 MHz	3 MHz		3 m	
	Average	1 MHz	3 MHz		3 m	


5.6.6.1 Test Data below 30 MHz



Tabulated Test Data – Low / Middle / High Channel

Frequency (MHz)	Receiver Reading (dBuV)	Detector Mode	Pol.	Ant. Factor (dB/m)	Corr. Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Azimuth (Degree)
* Spurious emissions that 20 dB below the limits didn't be recorded										

5.6.6.2 Test Data from 30 MHz to 1 GHz



Note: “H” means Horizontal polarity, “V” means Vertical polarity.

GFSK lowest channel is worst case configuration.


Quasi-peak measurements are omitted because the peak data meets the limit.

5.6.6.3 Test Data above 1 GHz

5.6.6.3.1 Duty Cycle

Date of Test	2018-07-20	Temperature	(22.6 ± 2.7) °C
		Relative humidity	(50.4 ± 5.9) % R.H.
Measurement Distance	3 m	Tested By	Do-heon Kim 
Detector Mode	Resolution BW	Video BW	Sweep Time
PEAK	1 MHz	3 MHz	Auto
AVERAGE	1 MHz	3 MHz	Auto

Graphical Test Data



Date: 9 JUL 2018 14:26:33


Tabulated Test Data

Operating Mode	On Time (µs)	On + Off Time (µs)	Duty Cycle (%)	Duty Factor (dB)
Bluetooth LE	420.0	624.0	67.31	1.72


5.6.6.3.2 Test Data for Band edge (Restricted band)

Graphical Test Data – Low Channel (Peak)

Horizontal



Vertical




Tabulated Test Data – Low Channel

Freq. (MHz)	Detector Mode	Pol.	Receiver Reading (dBuV/m)	Duty Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Azimuth (Deg)
2 349.7	Peak	H	52.31	-	52.31	74.00	21.69	200	30
2 349.8	Peak	V	52.24	-	52.24	74.00	21.76	200	20


NOTE: “H” means Horizontal polarity, “V” means Vertical polarity.

Graphical Test Data – Low Channel (Average)

Horizontal



Vertical



Tabulated Test Data – Low Channel


Freq. (MHz)	Detector Mode	Pol.	Receiver Reading (dBuV/m)	Duty Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Azimuth (Deg)
2 349.7	Average	H	44.48	1.72	46.20	54.00	7.80	200	30
2 349.7	Average	V	44.35	1.72	46.07	54.00	7.93	200	20

NOTE: “H” means Horizontal polarity, “V” means Vertical polarity.


Result = Receiver Reading + Duty Factor

Graphical Test Data – High Channel (Peak)

Horizontal



Vertical




Tabulated Test Data – High Channel

Freq. (MHz)	Detector Mode	Pol.	Receiver Reading (dBuV/m)	Duty Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Azimuth (Deg)
2 496.2	Peak	H	49.45	-	49.45	74.00	24.55	190	30
2 496.2	Peak	V	46.40	-	46.40	74.00	27.60	200	20


NOTE: "H" means Horizontal polarity, "V" means Vertical polarity.

Graphical Test Data – High Channel (Average)

Horizontal



Vertical



Tabulated Test Data – High Channel


Freq. (MHz)	Detector Mode	Pol.	Receiver Reading (dBuV/m)	Duty Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Azimuth (Deg)
2 496.3	Average	H	49.01	1.72	50.73	54.00	3.27	190	30
2 496.2	Average	V	45.95	1.72	47.67	54.00	6.33	200	20

NOTE: “H” means Horizontal polarity, “V” means Vertical polarity.

Result = Receiver Reading + Duty Factor

5.6.6.4 Test Data for Harmonic & Spurious emission (1 GHz to 18 GHz)

5.6.6.4.1 Operating mode: Bluetooth LE




Note. "H" means Horizontal polarity, "V" means Vertical polarity.

Corr. Factor (dB) = Pre-amplifier gain - Cable Loss

Result = Receiver Reading + Antenna Factor - Corr. Factor + Duty factor

Margin = Limit - Result

Graphical Test Data – Low Channel (Average)



Freq. (MHz)	Detector Mode	Pol.	Receiver Reading (dBuV)	Ant. Factor (dB/m)	Corr. Factor (dB)	Duty Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Azimuth (Deg)
Tabulated Test Data – Low Channel											
4 808	Average	H	50.6	32.3	37.6	1.72	47.02	54.00	6.98	100	48
7 205	Average	H	36.8	35.7	36.2	1.72	38.02	54.00	15.98	100	282
9 602	Average	H	37.9	37.4	35.2	1.72	41.82	54.00	12.18	200	83

Except above frequencies, no emissions were detected above the noise floor which was at least 20 dB below the specification limit.


Note. "H" means Horizontal polarity, "V" means Vertical polarity.

Corr. Factor (dB) = Pre-amplifier gain - Cable Loss

Result = Receiver Reading + Antenna Factor - Corr. Factor + Duty factor

Margin = Limit – Result

Graphical Test Data – Middle Channel (Peak)



Freq. (MHz)	Detector Mode	Pol.	Receiver Reading (dBuV)	Ant. Factor (dB/m)	Corr. Factor (dB)	Duty Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Azimuth (Deg)
Tabulated Test Data – Middle Channel											
* Spurious emissions that 20 dB below the limits didn't be recorded											


Note. "H" means Horizontal polarity, "V" means Vertical polarity.

Corr. Factor (dB) = Pre-amplifier gain - Cable Loss

Result = Receiver Reading + Antenna Factor - Corr. Factor + Duty factor

Margin = Limit – Result

Graphical Test Data – Middle Channel (Average)



Freq. (MHz)	Detector Mode	Pol.	Receiver Reading (dBuV)	Ant. Factor (dB/m)	Corr. Factor (dB)	Duty Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Azimuth (Deg)
Tabulated Test Data – Middle Channel											
2 462	Average	H	41.7	29.1	38.5	1.72	34.02	54.00	19.98	200	0
4 876	Average	H	48.8	32.5	37.3	1.72	45.72	54.00	8.28	100	42
7 324	Average	H	36.6	35.8	36.2	1.72	37.92	54.00	16.08	100	42
9 755	Average	H	38.0	37.3	35.5	1.72	41.52	54.00	12.48	200	0


Except above frequencies, no emissions were detected above the noise floor which was at least 20 dB below the specification limit.

Note. "H" means Horizontal polarity, "V" means Vertical polarity.

Corr. Factor (dB) = Pre-amplifier gain - Cable Loss

Result = Receiver Reading + Antenna Factor - Corr. Factor + Duty factor

Margin = Limit – Result




Note. "H" means Horizontal polarity, "V" means Vertical polarity.

Corr. Factor (dB) = Pre-amplifier gain - Cable Loss

Result = Receiver Reading + Antenna Factor - Corr. Factor + Duty factor

Margin = Limit – Result

Graphical Test Data – High Channel (Average)



Freq. (MHz)	Detector Mode	Pol.	Receiver Reading (dBuV)	Ant. Factor (dB/m)	Corr. Factor (dB)	Duty Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Azimuth (Deg)
Tabulated Test Data – High Channel											
4 961	Average	H	51.0	32.6	37.4	1.72	47.92	54.00	6.08	100	0
7 443	Average	H	36.8	36.0	36.3	1.72	38.22	54.00	15.78	100	45
9 925	Average	H	33.6	37.2	35.7	1.72	36.82	54.00	17.18	150	359

Except above frequencies, no emissions were detected above the noise floor which was at least 20 dB below the specification limit.


Note. "H" means Horizontal polarity, "V" means Vertical polarity.

Corr. Factor (dB) = Pre-amplifier gain - Cable Loss

Result = Receiver Reading + Antenna Factor - Corr. Factor + Duty factor

Margin = Limit – Result

5.6.6.5 Test Data for Harmonic & Spurious emission (18 GHz to 25 GHz)



Note. "H" means Horizontal polarity, "V" means Vertical polarity.

Corr. Factor (dB) = Pre-amplifier gain - Cable Loss

Result = Receiver Reading + Antenna Factor - Corr. Factor + Duty factor

Margin = Limit - Result

Appendix I – Test Instrumentation

Description	Model No.	Serial No.	Manufacturer.	Due for Cal Date
Signal & Spectrum Analyzer	FSW 43	100578	Rohde & Schwarz	2019-04-26
Attenuator	56-10	58769	WEINSCHTEL	2019-01-22
Test Receiver	ESU 26	100303	Rohde & Schwarz	2019-01-18
Loop Antenna	HFH2-Z2	100341	Rohde & Schwarz	2019-04-21
TRILOG Broadband Antenna	VULB9163	9163.799	Schwarzbeck	2019-09-14
Horn Antenna	HF 907	102426	Rohde & Schwarz	2018-11-25
Horn Antenna	BBHA 9170	BBHA 9170 #783	Schwarzbeck	2018-11-28
Attenuator	6dB	272.4110.50	Rohde & Schwarz	2019-01-18
Pre-Amplifier	310N	344015	Sonoma Instrument	2019-01-18
Pre-Amplifier	SCU 18D	19006450	Rohde & Schwarz	2019-04-24
Pre-Amplifier	CBL18265035	28706	CERNEX	2019-03-29
Turn Table	DT3000-3t	1310814	INNCO SYSTEM	N/A
Antenna Master	MA4000-EP	4600814	INNCO SYSTEM	N/A
Antenna Master	MA4000-XP-ET	-	INNCO SYSTEM	N/A
Camera Controller	HDCon4102	6531445048	PONTIS	N/A
CO3000 Controller	Co3000-4Port	CO3000/806/ 34130814/L	INNCO SYSTEM	N/A
CO3000 Controller	Co3000-4Port	CO3000/807/ 34130814/L	INNCO SYSTEM	N/A

The measuring equipment utilized to perform the tests documented in this test report has been calibrated in accordance with manufacturer's recommendations, and is traceable to recognized national standards.