

MPE Test Report

Report No.: WVK-ESH-P21051909B-14

FCC ID: 2AQOB-LWF1V2

Product: WIFI CEILING SPEAKER V2

Model: LWF1V2, LWF1V2/IP

Received Date: May.25, 2021

Test Date: May.28, 2021 to Jun.22, 2021

Issued Date: Jul.14, 2021

Applicant: Lithe Audio Ltd.

Address: Unit 4 IO Centre, Salbrook Road Industrial Estate, Salbrook Road, Salfords, Redhill, Surrey, RH1 5GJ. UK

Manufacturer: Lithe Audio Ltd.

Address: Unit 4 IO Centre, Salbrook Road Industrial Estate, Salbrook Road, Salfords, Redhill, Surrey, RH1 5GJ. UK

Issued By: BUREAU VERITAS ADT (Shanghai) Corporation

Lab Address: No. 829, Xinzhuang Road, Shanghai, P.R.China (201612)



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.



Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 General Description of EUT	5
3 RF Exposure	9
3.1 Limits For Maximum Permissible Exposure (MPE)	9
3.2 MPE Calculation Formula.....	9
3.3 Calculation Result of Maximum Permissible Exposure.....	10



Release Control Record

Issue No.	Description	Date Issued
WVK-ESH-P21051909B-14	Original release	Jul.14, 2021



1 Certificate of Conformity

Product: WIFI CEILING SPEAKER V2

Brand: LITHEAUDIO

Test Model: LWF1V2, LWF1V2/IP

Applicant: Lithe Audio Ltd.

Test Date: May.28, 2021 to Jun.22, 2021

Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D01 General RF Exposure Guidance v06

IEEE C95.1-1992

The above equipment has been tested by **BUREAU VERITAS ADT (Shanghai) Corporation**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :

Yuan ZHANG
Project Engineer

, **Date:**

Jul.14, 2021

Approved by :

Daniel SUN
EMC Lab Manager

, **Date:**

Jul.14, 2021

2 General Description of EUT

BLE

Product	WIFI CEILING SPEAKER V2
Brand	LITHEAUDIO
Test Model	LWF1V2, LWF1V2/IP
Power Rating	100-240V~, 50/60Hz, 2.0A for adapter; 24.0Vdc for WI-FI CEILING SPEAKERS
Modulation Type	GFSK
Modulation Technology	Bluetooth Low Energy 4.0
Operating Frequency	2402MHz ~ 2480MHz
Number of Channel	40
Output Power	5.61dBm
Antenna Type	PCB Antenna
Antenna Connector	--
Antenna Gain	3.5dBi

Note:

1. For more details, please refer to the User's manual of the EUT.
2. The EUT contains the wireless module of model LS9AD-AC11DBT-GV (FCC ID: 2ADBM-LS9ADAC11DBT) supports BT/WIFI function.
3. The wireless module can't support MIMO mode. 2.4G and 5 GHz bands can't operate simultaneously.

BT

Product	WIFI CEILING SPEAKER V2
Brand	LITHEAUDIO
Test Model	LWF1V2, LWF1V2/IP
Power Rating	100-240V~, 50/60Hz, 2.0A for adapter; 24.0Vdc for WI-FI CEILING SPEAKERS
Modulation Type	GFSK, $\pi/4$ -DQPSK, 8DPSK
Modulation Technology	BT-EDR, FHSS
Operating Frequency	2402MHz ~ 2480MHz
Number of Channel	79
Output Power	7.55dBm
Antenna Type	PCB antenna
Antenna Connector	--
Antenna Gain	3.5dBi

Note:

1. For more details, please refer to the User's manual of the EUT.
2. The EUT contains the wireless module of model LS9AD-AC11DBT-GV (FCC ID: 2ADBM-LS9ADAC11DBT) supports BT/WIFI function.
3. The wireless module can't support MIMO mode. 2.4G and 5 GHz bands can't operate simultaneously.

WIFI 2.4G

Product	WIFI CEILING SPEAKER V2
Brand	LITHEAUDIO
Test Model	LWF1V2, LWF1V2/IP
Power Rating	100-240V~, 50/60Hz, 2.0A for adapter; 24.0Vdc for WI-FI CEILING SPEAKERS
Modulation Type	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
Modulation Technology	DSSS, OFDM
Operating Frequency	2412~2462MHz
Number of Channel	11b/g/n(HT20):11;11n(HT40):7
Output Power	15.07dBm
Antenna Type	PCB Antenna
Antenna Connector	--
Antenna Gain	Ant1:3.5dBi, Ant2:3.5dBi

Note:

1. For more details, please refer to the User's manual of the EUT.
2. The EUT contains the wireless module of model LS9AD-AC11DBT-GV (FCC ID: 2ADBM-LS9ADAC11DBT) supports BT/WIFI function.
3. The wireless module can't support MIMO mode. 2.4G and 5 GHz bands can't operate simultaneously.

WIFI 5G

Product	WIFI CEILING SPEAKER V2
Brand	LITHEAUDIO
Test Model	LWF1V2, LWF1V2/IP
Power Rating	100-240V~, 50/60Hz, 2.0A for adapter; 24.0Vdc for WI-FI CEILING SPEAKERS
Modulation Type	OFDM
Modulation Technology	802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK), 802.11n: OFDM (BPSK, QPSK, 16QAM, 64QAM), 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM)
Operating Frequency	5150 ~ 5250MHz, 5250 ~ 5350MHz, 5470 ~ 5725MHz
Number of Channel	See clause 3.2
Output Power	13.11dBm
Antenna Type	PCB Antenna
Antenna Connector	--
Antenna Gain	Ant1:5.9dBi, Ant2:5.9dBi

Note:

1. For more details, please refer to the User's manual of the EUT.
2. The EUT contains the wireless module of model LS9AD-AC11DBT-GV (FCC ID: 2ADBM-LS9ADAC11DBT) supports BT/WIFI function.
3. The wireless module can't support MIMO mode. 2.4G and 5 GHz bands can't operate simultaneously.

3 RF Exposure

3.1 Limits For Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
300-1,500	-	-	F/1500	30
1,500-100,000	-	-	1.0	30

F = Frequency in MHz

3.2 MPE Calculation Formula

Power density (S) is calculated according to the formula:

$$S = PG / (4\pi R^2)$$

Where S = power density in mW/cm²

P = transmit power in mW

G = numeric gain of transmit antenna (numeric gain=Log-1(dB antenna gain/10))

R = distance (cm)

The antenna of this product, under normal use condition, is at least 20cm from the body of the user. So the device is classified as Mobile Device.

3.3 Calculation Result of Maximum Permissible Exposure

Frequency Band (MHz)	Max. Conducted Output power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
BLE					
2402-2480	5.61	3.5	20	0.001622	1
BT					
2402-2480	7.55	3.5	20	0.002535	1
WIFI 2.4GHz					
2412-2462	15.07	3.5	20	0.014320	1
WIFI 5GHz					
5150-5725	13.11	5.9	20	0.015847	1

Conclusion:

The calculation result of MPE is less than the limit.

--- END ---