



## FCC PART 95

## TEST REPORT

For

### Quanzhou Dongkun Electronics Technology Co., Ltd

4/F,Building 1,Unit 2,Optoelectronics-information, Industry Base,Nan'an, Quanzhou, Fujian, China

**FCC ID: 2AQPM-DK-408**

**Report Type:**

Original Report

**Product Name:**

Walkie Talkie

**Report Number:** 2507S03015E-RF-01

**Report Date:** 2025-05-06

**Reviewed By:** Ash Lin

**Approved By:** Miles Chen

**Prepared By:** Bay Area Compliance Laboratories Corp. (Xiamen)  
Unit 102, No. 902 Meifeng South Road, Binhai West  
Avenue, Science and Technology Innovation Park, Torch  
High tech Zone XiaMen  
Tel: +86-592-3200111  
[www.baclcorp.com.cn](http://www.baclcorp.com.cn)

## **TABLE OF CONTENTS**

|                                                                                      |           |
|--------------------------------------------------------------------------------------|-----------|
| <b>REPORT REVISION HISTORY .....</b>                                                 | <b>4</b>  |
| <b>GENERAL INFORMATION.....</b>                                                      | <b>5</b>  |
| PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....                             | 5         |
| ★ ANTENNA INFORMATION .....                                                          | 5         |
| OBJECTIVE .....                                                                      | 5         |
| TEST METHODOLOGY .....                                                               | 5         |
| MEASUREMENT UNCERTAINTY.....                                                         | 6         |
| TEST FACILITY .....                                                                  | 6         |
| <b>SYSTEM TEST CONFIGURATION.....</b>                                                | <b>7</b>  |
| TEST MODE AND VOLTAGE.....                                                           | 7         |
| DESCRIPTION OF TEST CONFIGURATION .....                                              | 7         |
| EQUIPMENT MODIFICATIONS .....                                                        | 7         |
| SUPPORT EQUIPMENT LIST AND DETAILS .....                                             | 7         |
| EXTERNAL I/O CABLE.....                                                              | 7         |
| BLOCK DIAGRAM OF TEST SETUP .....                                                    | 8         |
| <b>SUMMARY OF TEST RESULTS .....</b>                                                 | <b>10</b> |
| <b>TEST EQUIPMENT LIST .....</b>                                                     | <b>11</b> |
| <b>FCC §2.1046, §95.567 – FRS TRANSMIT POWER .....</b>                               | <b>12</b> |
| APPLICABLE STANDARD .....                                                            | 12        |
| EUT SETUP BLOCK DIAGRAM .....                                                        | 12        |
| TEST PROCEDURE .....                                                                 | 12        |
| TEST DATA .....                                                                      | 13        |
| <b>FCC §2.1047, §95.575 – FRS MODULATION LIMITS .....</b>                            | <b>15</b> |
| APPLICABLE STANDARD .....                                                            | 15        |
| TEST SETUP BLOCK DIAGRAM .....                                                       | 15        |
| TEST PROCEDURE .....                                                                 | 15        |
| TEST DATA .....                                                                      | 16        |
| <b>FCC §2.1049, §95.573, §95.579 - AUTHOURIZED BANDWIDTH AND EMISSION MASK .....</b> | <b>23</b> |
| APPLICABLE STANDARD .....                                                            | 23        |
| EUT SETUP BLOCK DIAGRAM .....                                                        | 23        |
| TEST PROCEDURE .....                                                                 | 24        |
| TEST DATA .....                                                                      | 25        |
| <b>FCC §2.1053 &amp; §95.579 - RADIATED SPURIOUS EMISSION .....</b>                  | <b>28</b> |
| APPLICABLE STANDARD .....                                                            | 28        |
| TEST PROSEDURE:.....                                                                 | 28        |
| EUT SETUP BLOCK DIAGRAM .....                                                        | 30        |
| TEST DATA .....                                                                      | 31        |
| <b>FCC§2.1055 (d), §95.565 – FRS FREQUENCY ACCURACY .....</b>                        | <b>33</b> |
| APPLICABLE STANDARD .....                                                            | 33        |
| EUT SETUP BLOCK DIAGRAM .....                                                        | 33        |
| TEST PROCEDURE .....                                                                 | 33        |
| TEST DATA .....                                                                      | 34        |
| <b>§95.571 – FRS EMISSION TYPES .....</b>                                            | <b>35</b> |
| APPLICABLE STANDARD .....                                                            | 35        |
| JUDGEMENT .....                                                                      | 35        |
| <b>§95.587 – FRS ADDITIONAL REQUIREMENT .....</b>                                    | <b>36</b> |

|                                     |           |
|-------------------------------------|-----------|
| APPLICABLE STANDARD .....           | 36        |
| JUDGMENT .....                      | 36        |
| <b>EUT PHOTOGRAPHS .....</b>        | <b>37</b> |
| <b>TEST SETUP PHOTOGRAPHS .....</b> | <b>38</b> |

## REPORT REVISION HISTORY

| Number of Revisions | Report No.        | Version | Issue Date | Description     |
|---------------------|-------------------|---------|------------|-----------------|
| 0                   | 2507S03015E-RF-01 | R1V1    | 2025-05-06 | Initial Release |

## GENERAL INFORMATION

### Product Description for Equipment under Test (EUT)

|                                                                                                                                                                                                                                                                                                                                                                                                                                        |         |                                                                  |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|------------------------------------------------------------------|
| Applicant:                                                                                                                                                                                                                                                                                                                                                                                                                             |         | Quanzhou Dongkun Electronics Technology Co., Ltd                 |
| Product Name:                                                                                                                                                                                                                                                                                                                                                                                                                          |         | Walkie Talkie                                                    |
| Tested Model:                                                                                                                                                                                                                                                                                                                                                                                                                          |         | DK-408                                                           |
| Multiple Model(s):                                                                                                                                                                                                                                                                                                                                                                                                                     |         | DK-418, DK-428, DK-438, DK-458, DK-468                           |
| Power Supply:                                                                                                                                                                                                                                                                                                                                                                                                                          |         | DC 5V from adapter or DC3.7V from battery                        |
| Adapter Information                                                                                                                                                                                                                                                                                                                                                                                                                    | Model:  | DOO77                                                            |
|                                                                                                                                                                                                                                                                                                                                                                                                                                        | Input:  | AC 100-240V, 50/60Hz, 0.15A                                      |
|                                                                                                                                                                                                                                                                                                                                                                                                                                        | Output: | DC 5V, 1000mA                                                    |
| Maximum Output Power (ERP):                                                                                                                                                                                                                                                                                                                                                                                                            |         | 462.5500-462.7250MHz: 32.87dBm<br>467.5625-467.7125MHz: 26.41dBm |
| Operation Frequency:                                                                                                                                                                                                                                                                                                                                                                                                                   |         | 462.5500-462.7250MHz<br>467.5625-467.7125MHz                     |
| Modulation Mode:                                                                                                                                                                                                                                                                                                                                                                                                                       |         | FM                                                               |
| Channel Spacing:                                                                                                                                                                                                                                                                                                                                                                                                                       |         | 12.5kHz                                                          |
| Emission Designator:                                                                                                                                                                                                                                                                                                                                                                                                                   |         | 11K0F3E                                                          |
| EUT Received Status:                                                                                                                                                                                                                                                                                                                                                                                                                   |         | Good                                                             |
| <i>Note:</i><br>1. The model difference is model name and appearance, but the internal structure is the same. Therefore, only the DK-408 model is chosen for testing; please refer to declaration letter for more details.<br>2. All measurement and test data in this report was gathered from production sample serial number: 31R3-7 (Assigned by the BACL (Xiamen). The EUT supplied by the applicant was received on 2025-04-21). |         |                                                                  |

### ★Antenna Information

| Antenna Manufacturer                                           | Antenna Type | Antenna Connector | Input Impedance (Ohm) | Antenna Gain /Frequency Range |
|----------------------------------------------------------------|--------------|-------------------|-----------------------|-------------------------------|
| Shenzhen Saiwei Communication Technology Co., LTD              | Spring       | Integral          | 50                    | 2.15 dBi (0 dBd) / 400-470MHz |
| <i>Note: The Antenna information is provided by applicant.</i> |              |                   |                       |                               |

### Objective

This test report is prepared for *Quanzhou Dongkun Electronics Technology Co., Ltd* in accordance with Part 2 and Part 95, Subpart B of the Federal Communication Commissions rules.

### Test Methodology

All tests and measurements indicated in this document were performed in accordance with Part 95 Subpart B of the Federal Communication Commissions rules with ANSI C63.26:2015, American National Standard for Compliance Testing of Transmitters Used in Licensed Radio Services.

## Measurement Uncertainty

| Item                          |              | $U_{lab}$             |
|-------------------------------|--------------|-----------------------|
| Unwanted Emissions, radiated  | 30MHz~200MHz | 3.47dB                |
|                               | 200MHz~1GHz  | 4.86dB                |
|                               | 1GHz~6GHz    | 4.88dB                |
| Occupied Channel Bandwidth    |              | 2%                    |
| RF output power, conducted    |              | $\pm 1.49$ dB         |
| Unwanted Emissions, conducted |              | $\pm 2.92$ dB         |
| Radiated RF power             |              | $\pm 3.66$ dB         |
| Audio Frequency               |              | 3.96%                 |
| Modulation Limiting           |              | 1.01%                 |
| Frequency Error(RF Frequency) |              | $0.085 \times 10^6$   |
| Temperature                   |              | $\pm 1^\circ\text{C}$ |
| Humidity                      |              | $\pm 5\%$             |
| Voltage (DC)                  |              | $\pm 0.4\%$           |

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

## Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Xiamen) to collect test data is located on Unit 102, No. 902 Meifeng South Road, Binhai West Avenue, Science and Technology Innovation Park, Torch High tech Zone XiaMen.

Bay Area Compliance Laboratories Corp. (Xiamen) Lab is accredited to ISO/IEC 17025 by A2LA (Certificate Number: 7134.01) and the lab has been recognized as the FCC accredited lab under the KDB 974614 D01, the FCC Designation No. : CN1384.

## SYSTEM TEST CONFIGURATION

### Test Mode and Voltage

| The system was configured for testing in a typical mode (as normally used by a typical user). |                      |
|-----------------------------------------------------------------------------------------------|----------------------|
| Test mode:                                                                                    | Transmitting         |
| Test voltage:                                                                                 | DC 3.7V from Battery |

### Description of Test Configuration

The EUT was configured for testing in an engineering mode which was provided by the manufacturer.

Test channel list as below, EUT was tested with channel 4 and 11.

| Channel Number | Frequency (MHz) | Channel Number | Frequency (MHz) |
|----------------|-----------------|----------------|-----------------|
| 1              | 462.5625        | 12             | 467.6625        |
| 2              | 462.5875        | 13             | 467.6875        |
| 3              | 462.6125        | 14             | 467.7125        |
| 4              | <b>462.6375</b> | 15             | 462.5500        |
| 5              | 462.6625        | 16             | 462.5750        |
| 6              | 462.6875        | 17             | 462.6000        |
| 7              | 462.7125        | 18             | 462.6250        |
| 8              | 467.5625        | 19             | 462.6500        |
| 9              | 467.5875        | 20             | 462.6750        |
| 10             | 467.6125        | 21             | 462.7000        |
| 11             | <b>467.6375</b> | 22             | 462.7250        |

### Equipment Modifications

No modification was made to the EUT tested.

### Support Equipment List and Details


| Manufacturer | Description | Model | Serial Number |
|--------------|-------------|-------|---------------|
| /            | /           | /     | /             |

### External I/O Cable


| Cable Description | Length(m) | From Port | To |
|-------------------|-----------|-----------|----|
| /                 | /         | /         | /  |

## Block Diagram of Test Setup

For Radiated Emissions(Below 1GHz):



For Radiated Emissions(Above 1GHz):



For RF Conducted:



**SUMMARY OF TEST RESULTS**

| <b>FCC Rules</b>          | <b>Description of Test</b>           | <b>Results</b> |
|---------------------------|--------------------------------------|----------------|
| §2.1046, §95.567          | FRS Transmit Power                   | Compliant      |
| §2.1047, §95.575          | FRS Modulation Limits                | Compliant      |
| §2.1049, §95.573, §95.579 | Authorized Bandwidth & Emission Mask | Compliant      |
| §2.1053, §95.579          | Radiated Spurious Emission           | Compliant      |
| §2.1055(d), §95.565       | FRS Frequency Accuracy               | Compliant      |
| §95.587                   | FRS Additional Requirement           | Compliant      |
| §95.571                   | FRS Emission Types                   | Compliant      |

**TEST EQUIPMENT LIST**

| Test Equipment                                          | Manufacturer              | Model              | Serial Number | Calibration Date | Calibration Due Date |
|---------------------------------------------------------|---------------------------|--------------------|---------------|------------------|----------------------|
| <b>Radiated Emissions</b>                               |                           |                    |               |                  |                      |
| Hybrid Antenna                                          | Sunol Sciences            | JB6                | A122022-5     | 2023/07/27       | 2026/07/26           |
| Amplifier                                               | Sonoma                    | 310B               | 120903        | 2025/02/20       | 2026/02/19           |
| EMI Test Receiver                                       | Rohde & Schwarz           | ESR                | 103103        | 2025/02/20       | 2026/02/19           |
| Coaxial Cable                                           | XINHANGWEIBO              | XH400T-N-4M        | CC002         | 2025/02/20       | 2026/02/19           |
| Coaxial Cable                                           | XINHANGWEIBO              | XH460B-N-2M        | CC006         | 2025/02/20       | 2026/02/19           |
| Coaxial Cable                                           | XINHANGWEIBO              | XH460B-N-12M       | CC007         | 2025/02/20       | 2026/02/19           |
| Spectrum Analyzer                                       | Rohde & Schwarz           | FSU                | 100405        | 2025/02/20       | 2026/02/19           |
| Horn Antenna                                            | EMCO                      | 3115               | 9002-3355     | 2024/11/19       | 2027/11/18           |
| Preamplifier                                            | GLOBAL                    | 1313-A100M18G      | 4121301       | 2025/01/16       | 2026/01/15           |
| Coaxial Cable                                           | XINHANGWEIBO              | XH800A-N-6M        | CC003         | 2025/02/20       | 2026/02/19           |
| Coaxial Cable                                           | XINHANGWEIBO              | XH800A-N-1M        | CC005         | 2025/02/20       | 2026/02/19           |
| Dipole Antenna                                          | COM-POWER                 | 3121C              | 9209-860      | N/A              | N/A                  |
| Double Ridge Guide<br>Horn Antenna                      | A.H.Systems               | SAS-571            | 1980          | 2023/07/28       | 2026/07/27           |
| Microwave Analog<br>Signal Generator                    | Agilent                   | N5181A             | MY48180319    | 2025/02/20       | 2026/02/19           |
| Band Elimination<br>Filter                              | HX Microwave              | HXLBQ-<br>DZA266LC | 24031602-2    | 2025/02/20       | 2026/02/19           |
| <b>RF Conducted Test</b>                                |                           |                    |               |                  |                      |
| Spectrum Analyzer                                       | Rohde & Schwarz           | FSU 26             | 200199        | 2025/02/20       | 2026/02/19           |
| Coaxial Cable                                           | WEIHE                     | WH316              | RFCC002       | Each time        | Each time            |
| Attenuator                                              | Electronic<br>Corporation | 300-WA-FFN-30      | 1172435       | 2025/02/20       | 2026/02/19           |
| DC Power Supply                                         | MAISHENG                  | MS-606DS           | 1027453694    | N/A              | N/A                  |
| Multimeter                                              | deli                      | DL8490             | 23930192      | 2025/02/20       | 2026/02/19           |
| RF Communications<br>test set                           | HP                        | 8920A              | 3524A07202    | 2024/04/26       | 2025/04/25           |
| constant temperature<br>and humidity testing<br>machine | BACL                      | BTH-150            | 30211         | 2025/02/20       | 2026/02/19           |

**Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Xiamen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).


## FCC §2.1046, §95.567 – FRS TRANSMIT POWER

### Applicable Standard

According to FCC §95.567

Each FRS transmitter type must be designed such that the effective radiated power (ERP) on channels 8 through 14 does not exceed 0.5 Watts and the ERP on channels 1 through 7 and 15 through 22 does not exceed 2.0 Watts.

### EUT Setup Block Diagram



Note: The Insertion Loss of the RF cable, Attenuators was offset into the Spectrum Analyzer.

### Test Procedure

C63.26-2015, Clause 5.2.3.3

This procedure can be used to measure the peak power in either a CW-like or noise-like narrowband RF signal. The measurement instrument must have a RBW that is greater than or equal to the OBW of the signal to be measured and a  $VBW \geq 3 \times RBW$ .

- Set the  $RBW \geq OBW$ .
- Set  $VBW \geq 3 \times RBW$ .
- Set  $span \geq 2 \times OBW$ .
- Sweep time  $\geq 10 \times (\text{number of points in sweep}) \times (\text{transmission symbol period})$ .
- Detector = peak.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the peak amplitude level

**ERP=Conducted Output Power+ Antenna Gain (dBd)**

# Test Data

|                   |              |                       |           |
|-------------------|--------------|-----------------------|-----------|
| <b>Test Mode:</b> | Transmitting | <b>Test Engineer:</b> | Lucas Lin |
| <b>Test Date:</b> | 2025-04-23   | <b>Test Result:</b>   | Pass      |


## Environment Conditions:

|                      |      |                              |    |                        |       |
|----------------------|------|------------------------------|----|------------------------|-------|
| Temperature:<br>(°C) | 23.1 | Relative<br>Humidity:<br>(%) | 58 | ATM Pressure:<br>(kPa) | 100.1 |
|----------------------|------|------------------------------|----|------------------------|-------|

Please refer to below plots:


| Test Frequency<br>(MHz) | Conducted Output<br>power<br>(dBm) | Antenna Gain<br>(dBd) | ERP<br>(dBm) | ERP Limit<br>(dBm) |
|-------------------------|------------------------------------|-----------------------|--------------|--------------------|
| 462.6375                | 32.87                              | 0                     | 32.87        | ≤33                |
| 467.6375                | 26.41                              | 0                     | 26.41        | ≤27                |

## 462.6375MHz



Project No.:2507S03015E-RF Tester:Lucas Lin  
Date: 23.APR.2025 09:54:52

# 467.6375MHz



Project No.:2507S03015E-RF Tester:Lucas Lin  
 Date: 23.APR.2025 09:45:28


## FCC §2.1047, §95.575 – FRS MODULATION LIMITS

### Applicable Standard

Per FCC §2.1047 and §95.575:

Each FRS transmitter type must be designed such that the peak frequency deviation does not exceed 2.5 kHz, and the highest audio frequency contributing substantially to modulation must not exceed 3.125 kHz.

### Test Setup Block Diagram



### Modulation limiting Test and Audio frequency response Test

### Test Procedure

#### C63.26-2015, Clause 5.3.2 Modulation limiting test methodology

Modulation limiting is the ability of a transmitter circuit to limit the transmitter from producing deviations in excess of a rated system deviation.

- Connect the equipment as illustrated in Figure 1.
- Adjust the transmitter per the manufacturer's procedure for full rated system deviation.
- Set the test receiver to measure peak positive deviation. Set the audio bandwidth for  $\leq 0.25$  Hz to  $\geq 15000$  Hz. Turn the de-emphasis function off.
- Apply a 1000 Hz modulating signal to the transmitter from the audio frequency generator, and adjust the level to obtain 60% of full rated system deviation. This is the 0 dB reference level.
- Increase the level from the audio generator by 20 dB in 5 dB increments recording the deviation as measured from the test receiver in each step. Verify that the audio level used to make the OBW measurement is included in the sweep.
- Repeat for step e) at 300 Hz, 2500 Hz and 3000 Hz at a minimum using the 0 dB reference level obtained in step d).
- Set the test receiver to measure peak negative deviation and repeat step d) through step f).
- The values recorded in step f) and step g) are the modulation limiting.
- Plot the data set as a percentage of deviation relative to the 0 dB reference point versus input voltage.

#### C63.26-2015, Clause 5.3.3.2 Audio frequency response test methodology—Constant Input

- Connect the equipment as illustrated in Figure 3.
- Set the test receiver to measure peak positive deviation. Set the audio bandwidth for  $\leq 50$  Hz to  $\geq$

15000Hz. Turn the de-emphasis function off.

c) Adjust the transmitter per the manufacturer's procedure for full rated system deviation.

d) Apply a 1000 Hz tone and adjust the audio frequency generator to produce 20% of the rated system deviation.

e) Set the test receiver to measure rms deviation and record the deviation reading as DEVREF.

f) Set the audio frequency generator to the desired test frequency between 300 Hz and 3000 Hz.

### Test Data

|                   |              |                       |           |
|-------------------|--------------|-----------------------|-----------|
| <b>Test Mode:</b> | Transmitting | <b>Test Engineer:</b> | Lucas Lin |
| <b>Test Date:</b> | 205-04-24    | <b>Test Result:</b>   | Pass      |


| Enviroment Conditions: |      |                              |    |                        |       |
|------------------------|------|------------------------------|----|------------------------|-------|
| Temperature:<br>(°C)   | 22.8 | Relative<br>Humidity:<br>(%) | 59 | ATM Pressure:<br>(kPa) | 100.1 |

Please refer to below table:

## Modulation Limiting


PK+

| FM 12.5kHz             | Carrier Frequency: 462.6375MHz |       |       |       |             |
|------------------------|--------------------------------|-------|-------|-------|-------------|
| Audio Input Level (dB) | Deviation (kHz)                |       |       |       | Limit (kHz) |
|                        | 0.3                            | 1.0   | 2.5   | 3.0   |             |
| 20                     | 1.053                          | 2.422 | 2.323 | 2.249 | 2.5         |
| 15                     | 0.916                          | 2.251 | 2.313 | 2.251 | 2.5         |
| 10                     | 0.778                          | 2.181 | 2.309 | 2.255 | 2.5         |
| 5                      | 0.712                          | 2.106 | 2.298 | 2.247 | 2.5         |
| 0                      | 0.439                          | 1.500 | 2.232 | 2.195 | 2.5         |




PK-

| FM 12.5kHz             | Carrier Frequency: 462.6375MHz |       |       |       |             |
|------------------------|--------------------------------|-------|-------|-------|-------------|
| Audio Input Level (dB) | Deviation (kHz)                |       |       |       | Limit (kHz) |
|                        | 0.3                            | 1.0   | 2.5   | 3.0   |             |
| 20                     | 1.005                          | 2.383 | 2.455 | 2.363 | 2.5         |
| 15                     | 0.843                          | 2.298 | 2.447 | 2.362 | 2.5         |
| 10                     | 0.789                          | 2.167 | 2.435 | 2.366 | 2.5         |
| 5                      | 0.661                          | 2.101 | 2.422 | 2.350 | 2.5         |
| 0                      | 0.373                          | 1.500 | 2.313 | 2.263 | 2.5         |




## PK+

| FM 12.5kHz             | Carrier Frequency: 467.6375MHz |       |       |       |             |
|------------------------|--------------------------------|-------|-------|-------|-------------|
| Audio Input Level (dB) | Deviation (kHz)                |       |       |       | Limit (kHz) |
|                        | 0.3                            | 1.0   | 2.5   | 3.0   |             |
| 20                     | 1.035                          | 2.412 | 2.309 | 2.229 | 2.5         |
| 15                     | 0.916                          | 2.256 | 2.301 | 2.236 | 2.5         |
| 10                     | 0.788                          | 2.182 | 2.293 | 2.235 | 2.5         |
| 5                      | 0.706                          | 2.108 | 2.281 | 2.234 | 2.5         |
| 0                      | 0.433                          | 1.500 | 2.211 | 2.173 | 2.5         |




## PK-

| FM 12.5kHz             | Carrier Frequency: 467.6375MHz |       |       |       |             |
|------------------------|--------------------------------|-------|-------|-------|-------------|
| Audio Input Level (dB) | Deviation (kHz)                |       |       |       | Limit (kHz) |
|                        | 0.3                            | 1.0   | 2.5   | 3.0   |             |
| 20                     | 1.039                          | 2.443 | 2.466 | 2.383 | 2.5         |
| 15                     | 0.918                          | 2.313 | 2.459 | 2.387 | 2.5         |
| 10                     | 0.788                          | 2.203 | 2.449 | 2.392 | 2.5         |
| 5                      | 0.709                          | 2.127 | 2.440 | 2.391 | 2.5         |
| 0                      | 0.431                          | 1.500 | 2.361 | 2.322 | 2.5         |




**Audio Frequency Response****Carrier Frequency: 462.6375MHz**

| Audio Frequency | Response Attenuation |
|-----------------|----------------------|
| Hz              | dB                   |
| 300             | -11.09               |
| 400             | -7.63                |
| 500             | -5.74                |
| 600             | -4.23                |
| 700             | -2.98                |
| 800             | -1.86                |
| 900             | -0.87                |
| 1000            | 0.00                 |
| 1200            | 1.64                 |
| 1400            | 2.98                 |
| 1600            | 4.14                 |
| 1800            | 5.18                 |
| 2000            | 6.08                 |
| 2200            | 6.88                 |
| 2400            | 7.56                 |
| 2600            | 8.15                 |
| 2800            | 8.61                 |
| 3000            | 8.83                 |
| 3125            | 8.75                 |



Carrier Frequency: 467.6375MHz



---

**FCC §2.1049, §95.573, §95.579 - AUTHORIZED BANDWIDTH AND EMISSION MASK**

---

**Applicable Standard**

According to §95.573

Each FRS transmitter type must be designed such that the occupied bandwidth does not exceed 12.5 kHz.

According to §95.579

Each FRS transmitter type must be designed to satisfy the applicable unwanted emissions limits in this paragraph.

(a) Attenuation requirements. The power of unwanted emissions must be attenuated below the carrier power output in Watts (P) by at least:


(1) 25 dB (decibels) in the frequency band 6.25 kHz to 12.5 kHz removed from the channel center frequency.

(2) 35 dB in the frequency band 12.5 kHz to 31.25 kHz removed from the channel center frequency.

(3)  $43 + 10 \log (P)$  dB in any frequency band removed from the channel center frequency by more than 31.25 kHz.

(b) Measurement bandwidths. The power of unwanted emissions in the frequency bands specified in paragraphs (a) (1) and (2) of this section is measured with a reference bandwidth of 300 Hz. The power of unwanted emissions in the frequency range specified in paragraph (a) (3) is measured with a reference bandwidth of at least 30 kHz.

(c) Measurement conditions. The requirements in this section apply to each FRS transmitter type both with and without the connection of permitted attachments, such as an external speaker, microphone and/or power cord.

**EUT Setup Block Diagram**

Note: The Insertion Loss of the RF cable, Attenuators was offset into the Spectrum Analyzer.

## Test Procedure

C63.26-2015, Clause 5.4.4

The OBW is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission.

The following procedure shall be used for measuring (99%) power bandwidth:

a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be set wide enough to capture all modulation products including the emission skirts (typically a span of  $1.5 \times \text{OBW}$  is sufficient).

b) The nominal IF filter 3 dB bandwidth (RBW) shall be in the range of 1% to 5% of the anticipated OBW, and the VBW shall be set  $\geq 3 \times \text{RBW}$ .

c) Set the reference level of the instrument as required to prevent the signal amplitude from exceeding the maximum spectrum analyzer input mixer level for linear operation. See guidance provided in 4.2.3.

NOTE—Step a), step b), and step c) may require iteration to adjust within the specified tolerances.

d) Set the detection mode to peak, and the trace mode to max-hold.

e) If the instrument does not have a 99% OBW function, recover the trace data points and sum directly in linear power terms. Place the recovered amplitude data points, beginning at the lowest frequency, in a running sum until 0.5% of the total is reached. Record that frequency as the lower OBW frequency. Repeat the process until 99.5% of the total is reached and record that frequency as the upper OBW frequency. The 99% power OBW can be determined by computing the difference these two frequencies.

f) The OBW shall be reported and plot(s) of the measuring instrument display shall be provided with the test report. The frequency and amplitude axis and scale shall be clearly labeled. Tabular data can be reported in addition to the plot(s).

According to ANSI C63.26-2015 Section 5.7.3:

f) See Annex I for example emission mask plots.

**Test Data**

|                   |              |                       |           |
|-------------------|--------------|-----------------------|-----------|
| <b>Test Mode:</b> | Transmitting | <b>Test Engineer:</b> | Lucas Lin |
| <b>Test Date:</b> | 2025-04-24   | <b>Test Result:</b>   | Pass      |

**Environment Conditions:**

|                      |      |                              |    |                        |       |
|----------------------|------|------------------------------|----|------------------------|-------|
| Temperature:<br>(°C) | 22.8 | Relative<br>Humidity:<br>(%) | 59 | ATM Pressure:<br>(kPa) | 100.1 |
|----------------------|------|------------------------------|----|------------------------|-------|

Please refer to below table:

| Test Frequency<br>(MHz) | 99% Occupied<br>Bandwidth<br>(kHz) | 20 dB<br>Bandwidth<br>(kHz) | Limit<br>(kHz) |
|-------------------------|------------------------------------|-----------------------------|----------------|
| 462.6375                | 9.936                              | 10.577                      | ≤12.5          |
| 467.6375                | 9.936                              | 10.577                      | ≤12.5          |

**Note:**

Emission bandwidth was based on calculation method instead of measurement.

Emission Designator

Per CFR 47 §2.201& §2.202, BW = 2M + 2D

**For FM Mode (Channel Spacing: 12.5 kHz)**

Emission Designator 11K0F3E

In this case, the maximum modulating frequency is 3.0 kHz with a 2.5 kHz deviation.


$BW = 2(M+D) = 2*(3.0 \text{ kHz} + 2.5 \text{ kHz}) = 11 \text{ kHz} = 11K0$

F3E portion of the designator represents an FM voice transmission

Therefore, the entire designator for 12.5 kHz channel spacing FM mode is 11K0F3E.


462.6375MHz

99% Occupied Bandwidth



Project No.:2507S03015E-RF Tester:Lucas Lin  
Date: 24.APR.2025 19:07:20


Emission Mask



Project No.:2507S03015E-RF Tester:Lucas Lin  
Date: 24.APR.2025 19:04:18


**467.6375MHz**

## 99% Occupied Bandwidth



Project No.:2507S03015E-RF      Tester:Lucas Lin  
Date: 24.APR.2025 19:09:04

### Emission Mask



Project No.:2507S03015E-RF      Tester:Lucas Lin  
Date: 24.APR.2025 18:56:22

---

**FCC §2.1053 & §95.579 - RADIATED SPURIOUS EMISSION**

---

**Applicable Standard**

FCC §2.1053 and §95.579

Each FRS transmitter type must be designed to satisfy the applicable unwanted emissions limits in this paragraph.

(a) Attenuation requirements. The power of unwanted emissions must be attenuated below the carrier power output in Watts (P) by at least:

- (1) 25 dB (decibels) in the frequency band 6.25 kHz to 12.5 kHz removed from the channel center frequency.
- (2) 35 dB in the frequency band 12.5 kHz to 31.25 kHz removed from the channel center frequency.
- (3)  $43 + 10 \log (P)$  dB in any frequency band removed from the channel center frequency by more than 31.25 kHz.

(b) Measurement bandwidths. The power of unwanted emissions in the frequency bands specified in paragraphs (a) (1) and (2) of this section is measured with a reference bandwidth of 300 Hz. The power of unwanted emissions in the frequency range specified in paragraph (a) (3) is measured with a reference bandwidth of at least 30 kHz.

(c) Measurement conditions. The requirements in this section apply to each FRS transmitter type both with and without the connection of permitted attachments, such as an external speaker, microphone and/or power cord.

**Test Procedure:**

ANSI C63.26-2015 Section 5.5.3

- a) Place the EUT in the center of the turntable. The EUT shall be configured to transmit into the standard non-radiating load (for measuring radiated spurious emissions), connected with cables of minimal length unless specified otherwise. If the EUT uses an adjustable antenna, the antenna shall be positioned to the length that produces the worst case emission at the fundamental operating frequency.
- b) Each emission under consideration shall be evaluated:
  - 1) Raise and lower the measurement antenna in accordance 5.5.2, as necessary to enable detection of the maximum emission amplitude relative to measurement antenna height.
  - 2) Rotate the EUT through 360° to determine the maximum emission level relative to the axial position.
  - 3) Return the turntable to the azimuth where the highest emission amplitude level was observed.
  - 4) Vary the measurement antenna height again through 1 m to 4 m again to find the height associated with the maximum emission amplitude.
  - 5) Record the measured emission amplitude level and frequency using the appropriate RBW.
- c) Repeat step b) for each emission frequency with the measurement antenna oriented in both the horizontal and vertical polarizations to determine the orientation that gives the maximum emissions amplitude.
- d) Set-up the substitution measurement with the reference point of the substitution antenna located as near as possible to where the center of the EUT radiating element was located during the initial EUT measurement.

- e) Maintain the previous measurement instrument settings and test set-up, with the exception that the EUT is removed and replaced by the substitution antenna.
- f) Connect a signal generator to the substitution antenna; locate the signal generator so as to minimize any potential influences on the measurement results. Set the signal generator to the frequency where emissions are detected, and set an output power level such that the radiated signal can be detected by the measurement instrument, with sufficient dynamic range relative to the noise floor.
- g) For each emission that was detected and measured in the initial test [i.e., in step b) and step c)]:
  - 1) Vary the measurement antenna height between 1 m to 4 m to maximize the received (measured) signal amplitude.
  - 2) Adjust the signal generator output power level until the amplitude detected by the measurement instrument equals the amplitude level of the emission previously measured directly in step b) and step c).
  - 3) Record the output power level of the signal generator when equivalence is achieved in step 2).
- h) Repeat step e) through step g) with the measurement antenna oriented in the opposite polarization.
- i) Calculate the emission power in dBm referenced to a half-wave dipole using the following equation:

$$P_e = P_s(\text{dBm}) - \text{cable loss (dB)} + \text{antenna gain (dBd)}$$

where

- $P_e$  = equivalent emission power in dBm
- $P_s$  = source (signal generator) power in dBm

NOTE—dBd refers to the measured antenna gain in decibels relative to a half-wave dipole.

- j) Correct the antenna gain of the substitution antenna if necessary to reference the emission power to a half-wave dipole. When using measurement antennas with the gain specified in dBi, the equivalent dipole-referenced gain can be determined from:  $\text{gain (dBd)} = \text{gain (dBi)} - 2.15 \text{ dB}$ . If necessary, the antenna gain can be calculated from calibrated antenna factor information
- k) Provide the complete measurement results as a part of the test report.

## EUT Setup Block Diagram




Figure 6 —Test site-up for radiated ERP and/or EIRP measurements




Figure 7 —Substitution method set-up for radiated emission

**Test Data**

|                   |              |                       |            |
|-------------------|--------------|-----------------------|------------|
| <b>Test Mode:</b> | Transmitting | <b>Test Engineer:</b> | Apollo Luo |
| <b>Test Date:</b> | 2025-04-28   | <b>Test Result:</b>   | Pass       |

**Environment Conditions:**

|                      |      |                              |    |                        |       |
|----------------------|------|------------------------------|----|------------------------|-------|
| Temperature:<br>(°C) | 22.8 | Relative<br>Humidity:<br>(%) | 59 | ATM Pressure:<br>(kPa) | 100.1 |
|----------------------|------|------------------------------|----|------------------------|-------|

Please refer to below table:

**30MHz-5GHz:**

| Frequency<br>(MHz)         | Polar<br>(H/V) | Receiver<br>Reading<br>(dBμV) | Substituted Method            |                              |                       | Absolute<br>Level<br>(dBm) | Limit<br>(dBm) | Margin<br>(dB) |
|----------------------------|----------------|-------------------------------|-------------------------------|------------------------------|-----------------------|----------------------------|----------------|----------------|
|                            |                |                               | Substituted<br>Level<br>(dBm) | Antenna<br>Gain<br>(dBd/dBi) | Cable<br>Loss<br>(dB) |                            |                |                |
| FM, Frequency: 462.6375MHz |                |                               |                               |                              |                       |                            |                |                |
| 925.28                     | H              | 69.42                         | -19.65                        | 0.00                         | 0.42                  | -20.07                     | -13.00         | 7.07           |
| 925.28                     | V              | 67.68                         | -21.20                        | 0.00                         | 0.42                  | -21.62                     | -13.00         | 8.62           |
| 1387.91                    | H              | 79.78                         | -36.05                        | 7.65                         | 1.52                  | -29.92                     | -13.00         | 16.92          |
| 1387.91                    | V              | 76.41                         | -39.89                        | 7.65                         | 1.52                  | -33.76                     | -13.00         | 20.76          |
| 1850.55                    | H              | 72.95                         | -38.49                        | 6.69                         | 1.72                  | -33.52                     | -13.00         | 20.52          |
| 1850.55                    | V              | 79.17                         | -32.55                        | 6.69                         | 1.72                  | -27.58                     | -13.00         | 14.58          |
| 2313.19                    | H              | 69.09                         | -38.53                        | 3.75                         | 1.91                  | -36.69                     | -13.00         | 23.69          |
| 2313.19                    | V              | 68.56                         | -39.36                        | 3.75                         | 1.91                  | -37.52                     | -13.00         | 24.52          |
| 2775.83                    | H              | 69.38                         | -36.27                        | 3.85                         | 2.09                  | -34.51                     | -13.00         | 21.51          |
| 2775.83                    | V              | 64.66                         | -41.26                        | 3.85                         | 2.09                  | -39.50                     | -13.00         | 26.50          |
| 3238.46                    | H              | 70.32                         | -34.76                        | 4.09                         | 2.26                  | -32.93                     | -13.00         | 19.93          |
| 3238.46                    | V              | 68.39                         | -37.12                        | 4.09                         | 2.26                  | -35.29                     | -13.00         | 22.29          |
| 3701.10                    | H              | 65.71                         | -39.27                        | 6.00                         | 2.39                  | -35.66                     | -13.00         | 22.66          |
| 3701.10                    | V              | 64.77                         | -40.48                        | 6.00                         | 2.39                  | -36.87                     | -13.00         | 23.87          |
| 4163.74                    | H              | 64.61                         | -40.35                        | 7.88                         | 2.51                  | -34.98                     | -13.00         | 21.98          |
| 4163.74                    | V              | 65.61                         | -39.12                        | 7.88                         | 2.51                  | -33.75                     | -13.00         | 20.75          |
| 4626.38                    | H              | 65.31                         | -40.19                        | 10.61                        | 2.65                  | -32.23                     | -13.00         | 19.23          |
| 4626.38                    | V              | 65.86                         | -39.75                        | 10.61                        | 2.65                  | -31.79                     | -13.00         | 18.79          |

| Frequency<br>(MHz)         | Polar<br>(H/V) | Receiver<br>Reading<br>(dBμV) | Substituted Method            |                              |                       | Absolute<br>Level<br>(dBm) | Limit<br>(dBm) | Margin<br>(dB) |
|----------------------------|----------------|-------------------------------|-------------------------------|------------------------------|-----------------------|----------------------------|----------------|----------------|
|                            |                |                               | Substituted<br>Level<br>(dBm) | Antenna<br>Gain<br>(dBd/dBi) | Cable<br>Loss<br>(dB) |                            |                |                |
| FM, Frequency: 467.6375MHz |                |                               |                               |                              |                       |                            |                |                |
| 935.28                     | H              | 68.52                         | -20.97                        | 0.00                         | 0.42                  | -21.39                     | -13.00         | 8.39           |
| 935.28                     | V              | 68.68                         | -20.63                        | 0.00                         | 0.42                  | -21.05                     | -13.00         | 8.05           |
| 1402.91                    | H              | 70.11                         | -45.71                        | 7.71                         | 1.53                  | -39.53                     | -13.00         | 26.53          |
| 1402.91                    | V              | 73.60                         | -42.69                        | 7.71                         | 1.53                  | -36.51                     | -13.00         | 23.51          |
| 1870.55                    | H              | 73.14                         | -38.05                        | 6.17                         | 1.73                  | -33.61                     | -13.00         | 20.61          |
| 1870.55                    | V              | 78.83                         | -32.63                        | 6.17                         | 1.73                  | -28.19                     | -13.00         | 15.19          |
| 2338.19                    | H              | 70.65                         | -36.81                        | 3.65                         | 1.92                  | -35.08                     | -13.00         | 22.08          |
| 2338.19                    | V              | 69.32                         | -38.45                        | 3.65                         | 1.92                  | -36.72                     | -13.00         | 23.72          |
| 2805.83                    | H              | 74.55                         | -31.01                        | 3.90                         | 2.10                  | -29.21                     | -13.00         | 16.21          |
| 2805.83                    | V              | 66.30                         | -39.53                        | 3.90                         | 2.10                  | -37.73                     | -13.00         | 24.73          |
| 3273.46                    | H              | 71.99                         | -33.10                        | 4.58                         | 2.27                  | -30.79                     | -13.00         | 17.79          |
| 3273.46                    | V              | 67.32                         | -38.23                        | 4.58                         | 2.27                  | -35.92                     | -13.00         | 22.92          |
| 3741.10                    | H              | 64.86                         | -40.09                        | 5.92                         | 2.40                  | -36.57                     | -13.00         | 23.57          |
| 3741.10                    | V              | 69.37                         | -35.77                        | 5.92                         | 2.40                  | -32.25                     | -13.00         | 19.25          |
| 4208.74                    | H              | 66.90                         | -38.12                        | 8.12                         | 2.53                  | -32.53                     | -13.00         | 19.53          |
| 4208.74                    | V              | 67.74                         | -37.09                        | 8.12                         | 2.53                  | -31.50                     | -13.00         | 18.50          |
| 4676.38                    | H              | 69.18                         | -36.34                        | 11.01                        | 2.66                  | -27.99                     | -13.00         | 14.99          |
| 4676.38                    | V              | 66.68                         | -39.01                        | 11.01                        | 2.66                  | -30.66                     | -13.00         | 17.66          |

Note 1: The unit of antenna gain is dBd for frequency below 1GHz and is dBi for frequency above 1GHz.

Note 2: Absolute Level = Substituted Level - Cable loss + Antenna Gain

Margin = Limit- Absolute Level.


## FCC§2.1055 (d), §95.565 – FRS FREQUENCY ACCURACY

### Applicable Standard

According to FCC §95.565

Each FRS transmitter type must be designed such that the carrier frequencies remain within  $\pm 2.5$  parts per million of the channel center frequencies specified in § 95.563 during normal operating conditions.

### EUT Setup Block Diagram



### Test Procedure

C63.26-2015, Clause 5.6

Frequency stability is a measure of the frequency drift due to temperature and supply voltage variations, with reference to the frequency measured at +20°C and rated supply voltage. The operating carrier frequency shall be set up in accordance with the manufacturer's published operation and instruction manual prior to the commencement of these tests. No adjustment of any frequency determining circuit element shall be made subsequent to this initial set-up. Frequency stability is tested:

- a) At 10°C intervals of temperatures between -30°C and +50°C at the manufacturer's rated supply voltage, and
- b) At +20°C temperature and  $\pm 15\%$  supply voltage variations. If a product is specified to operate over a range of input voltage then the -15% variation is applied to the lowermost voltage and the +15% is applied to the uppermost voltage. During the test all necessary settings, adjustments and control of the EUT have to be performed without disturbing the test environment, i.e., without opening the environmental chamber. The frequency stabilities can be maintained to a lesser temperature range provided that the transmitter is automatically inhibited from operating outside the lesser temperature range. For handheld equipment that is only capable of operating from internal batteries and the supply voltage cannot be varied, the frequency stability tests shall be performed at the nominal battery voltage and the battery end point voltage specified by the manufacturer. An external supply voltage can be used and set at the internal battery nominal voltage, and again at the battery operating end point voltage which shall be specified by the equipment manufacturer.

If an unmodulated carrier is not available, the mean frequency of a modulated carrier can be obtained by using a frequency counter with gating time set to an appropriately large multiple of bit periods (gating time depending on the required accuracy). Full details on the choice of values shall be included in the test report.

**Test Data**

|                   |              |                       |           |
|-------------------|--------------|-----------------------|-----------|
| <b>Test Mode:</b> | Transmitting | <b>Test Engineer:</b> | Lucas Lin |
| <b>Test Date:</b> | 2025-04-23   | <b>Test Result:</b>   | Pass      |

**Enviroment Conditions:**

|                      |      |                              |    |                        |       |
|----------------------|------|------------------------------|----|------------------------|-------|
| Temperature:<br>(°C) | 23.1 | Relative<br>Humidity:<br>(%) | 58 | ATM Pressure:<br>(kPa) | 100.1 |
|----------------------|------|------------------------------|----|------------------------|-------|

Please refer to test table:

| Test Frequency<br>(MHz) | Temperature<br>(°C) | Voltage<br>(V) | Measured<br>Frequency<br>(MHz) | Frequency<br>Error<br>(ppm) | limit<br>(ppm) |
|-------------------------|---------------------|----------------|--------------------------------|-----------------------------|----------------|
| 462.6375                | -30                 | 3.7            | 462.6381153                    | 1.33                        | ≤2.5           |
|                         | -20                 | 3.7            | 462.6380459                    | 1.18                        | ≤2.5           |
|                         | -10                 | 3.7            | 462.6379858                    | 1.05                        | ≤2.5           |
|                         | 0                   | 3.7            | 462.6379256                    | 0.92                        | ≤2.5           |
|                         | 10                  | 3.7            | 462.6378794                    | 0.82                        | ≤2.5           |
|                         | 20                  | 3.7            | 462.6378571                    | 0.77                        | ≤2.5           |
|                         | 30                  | 3.7            | 462.6379395                    | 0.95                        | ≤2.5           |
|                         | 40                  | 3.7            | 462.6380043                    | 1.09                        | ≤2.5           |
|                         | 50                  | 3.7            | 462.6380922                    | 1.28                        | ≤2.5           |
|                         | 20                  | 3.2            | 462.6379441                    | 0.96                        | ≤2.5           |
|                         | 20                  | 4.2            | 462.6379118                    | 0.89                        | ≤2.5           |

| Test Frequency<br>(MHz) | Temperature<br>(°C) | Voltage<br>(V) | Measured<br>Frequency<br>(MHz) | Frequency<br>Error<br>(ppm) | limit<br>(ppm) |
|-------------------------|---------------------|----------------|--------------------------------|-----------------------------|----------------|
| 467.6375                | -30                 | 3.7            | 467.6381407                    | 1.37                        | ≤2.5           |
|                         | -20                 | 3.7            | 467.6380658                    | 1.21                        | ≤2.5           |
|                         | -10                 | 3.7            | 467.6379957                    | 1.06                        | ≤2.5           |
|                         | 0                   | 3.7            | 467.6379583                    | 0.98                        | ≤2.5           |
|                         | 10                  | 3.7            | 467.6379256                    | 0.91                        | ≤2.5           |
|                         | 20                  | 3.7            | 467.6379015                    | 0.86                        | ≤2.5           |
|                         | 30                  | 3.7            | 467.6379723                    | 1.01                        | ≤2.5           |
|                         | 40                  | 3.7            | 467.6380425                    | 1.16                        | ≤2.5           |
|                         | 50                  | 3.7            | 467.6381079                    | 1.30                        | ≤2.5           |
|                         | 20                  | 3.2            | 467.6379817                    | 1.03                        | ≤2.5           |
|                         | 20                  | 4.2            | 467.6379536                    | 0.97                        | ≤2.5           |

Note: the voltage range was declared by manufacturer.

---

## **§95.571 – FRS EMISSION TYPES**

---

### **Applicable Standard**

FCC §95.571

Each FRS transmitter type must be designed such that it can transmit only the following emission types: F3E, G3E, F2D, and G2D.

### **Judgement**

The emission type is F3E Only.

## **§95.587 – FRS ADDITIONAL REQUIREMENT**

### **Applicable Standard**

FCC §95.587

Each FRS transmitter type must be designed to meet the following additional requirements.

- (a) Transmit frequency capability. FRS transmitter types must not be capable of transmitting on any frequency or channel other than those listed in § 95.563.
- (b) Antenna. The antenna of each FRS transmitter type must meet the following requirements.
  - (1) The antenna must be a non-removable integral part of the FRS transmitter type.
  - (2) The gain of the antenna must not exceed that of a half-wave dipole antenna.
  - (3) The antenna must be designed such that the electric field of the emitted waves is vertically polarized when the unit is operated in the normal orientation.
- (c) Digital data transmissions. FRS transmitter types having the capability to transmit digital data must be designed to meet the following requirements.
  - (1) FRS units may transmit digital data containing location information, or requesting location information from one or more other FRS or GMRS units, or containing a brief text message to another specific FRS or GMRS unit or units.
  - (2) Digital data transmissions may be initiated by a manual action or command of the operator or on an automatic or periodic basis, and FRS units may be designed to automatically respond with location data upon receiving an interrogation request from another
  - (3) Digital data transmissions must not exceed one second in duration.
  - (4) Digital data transmissions must not be sent more frequently than one digital data transmission within a thirty-second period, except that an FRS unit may automatically respond to more than one interrogation request received within a thirty-second period.
- (d) Packet mode. FRS transmitter types must not be capable of transmitting data in the store-and-forward packet operation mode.
- (e) Effective September 30, 2019, no person shall manufacture or import hand-held portable radio equipment capable of operating under this subpart (FRS) and other licensed or licensed-by-rule services in this chapter (part 15 unlicensed equipment authorizations are permitted if consistent with part 15 rules).

### **Judgment**

Transmit frequency capability: Compliant, the frequency range is 462.5500-462.7250MHz, 467.5625-467.7125MHz, please refer to **Description of Test Configuration**.

Antenna: Compliant, the antenna is integrated, please refer to ★**Antenna Information**.

Digital Data transmissions: Not Applicable, no digital modulation function.

Packet mode: Not Applicable, no digital modulation function.

No capable of FRS combined other licensed: Compliance, Only FRS function.

## **EUT PHOTOGRAPHS**

---

Please refer to the attachment 2507S03015E-RF-EXP EUT EXTERNAL PHOTOGRAPHS and 2507S03015E-RF-INP EUT INTERNAL PHOTOGRAPHS.

## **TEST SETUP PHOTOGRAPHS**

---

Please refer to the attachment 2507S03015E-RF-TSP TEST SETUP PHOTOGRAPHS.

## Declarations

1. Bay Area Compliance Laboratories Corp. (Xiamen) is not responsible for authenticity of any information provided by the applicant. Information from the applicant that may affect test results are marked with an asterisk “★”.
2. Unless otherwise stated, the results shown in this test report refer only to the sample(s) tested.
3. Unless required by the rule provided by the applicant or product regulations, then decision rule in this report did not consider the uncertainty.
4. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor  $k=2$  with the 95% confidence interval.
5. This report cannot be reproduced except in full, without prior written approval of Bay Area Compliance Laboratories Corp. (Xiamen).
6. This report is valid only with a valid digital signature. The digital signature may be available only under the adobe software above version 7.0.

**\*\*\*\*\* END OF REPORT\*\*\*\*\***