



SAR Test Report

Report No.: STS2602061H01

Issued for

Fujian Morefun Electronic Technology Co., Ltd.

4th Floor, #15 Building, Standard plant, Fuwan, Jinshan
Industry CenterArea, #869 Panyu Rd, Gaishan Town,
Cangshan Area, Fuzhou, Fujian, China

Product Name: Smart POS Terminal

Brand Name:  MoreFun

Model Name: SR800

Series Model(s): N/A

FCC ID: 2AQRE-SR800

Test Standard: ANSI/IEEE Std. C95.1
FCC 47 CFR Part 2 (2.1093)
IEEE Std. 1528-2013

Max. Report
SAR (1g) Body: 1.261 W/kg

The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of the Shenzhen STS Test Services Co., Ltd.



TEST REPORT CERTIFICATION

Applicant's name : Fujian Morefun Electronic Technology Co., Ltd.
4th Floor, #15 Building, Standard plant, Fuwan, Jinshan Industry
Address : CenterArea, #869 Panyu Rd, Gaishan Town, Cangshan Area,
Fuzhou, Fujian, China
Manufacturer's Name : Fujian Morefun Electronic Technology Co., Ltd.
4th Floor, #15 Building, Standard plant, Fuwan, Jinshan Industry
Address : CenterArea, #869 Panyu Rd, Gaishan Town, Cangshan Area,
Fuzhou, Fujian, China

Product description

Product name : Smart POS Terminal
Brand name :  **MoreFun**
Model name : SR800
Series Model..... : N/A

Standards..... : ANSI/IEEE Std. C95.1
FCC 47 CFR Part 2 (2.1093)
IEEE Std. 1528-2013

The device was tested by Shenzhen STS Test Services Co., Ltd. in accordance with the measurement methods and procedures specified in KDB 865664 The test results in this report apply only to the tested sample of the stated device/equipment. Other similar device/equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Date of Test..... :

Date (s) of performance of tests..... : 23 Feb. 2026 ~ 27 Feb. 2026

Date of Issue..... : 23 Mar. 2026

Test Result..... : **Pass**

Testing Engineer :

Xin Liu

(Xin.Liu)

Technical Manager :

Shi fan-long

(Shifan. Long)

Authorized Signatory :

Bovey Yang

(Bovey Yang)





Table of Contents

1. General Information	5
1.1 EUT Description	5
1.2 Test Environment	7
1.3 Test Factory	7
2. Test Standards and Limits	8
3. SAR Measurement System	9
3.1 Definition of Specific Absorption Rate (SAR)	9
3.2 SAR System	9
3.3 DASY5 E-field Probe System	11
3.4 Phantoms	12
3.5 Device Holder	12
3.6 Scanning Procedure	13
3.7 Data Storage and Evaluation	14
4. Tissue Simulating Liquids	16
4.1 Simulating Liquids Parameter Check	16
5. SAR System Validation	21
5.1 Validation System	21
5.2 Validation Result	22
6. SAR Evaluation Procedures	23
7. EUT Antenna Location Sketch	24
7.1 SAR test exclusion consider table	25
8. EUT Test Position	32
9. Uncertainty	33
9.1 Measurement Uncertainty	33
10. Conducted Power Measurement	36
10.1 Test Result	36
11. EUT and Test Setup Photo	71
11.1 EUT Photo	71
11.2 Setup Photo	74
12. SAR Result Summary	78
12.1 Body-worn SAR	78
12.3 Repeated SAR	84
12.4 Repeated SAR measurement	85
12.5 Simultaneous Multi-band Transmission Evaluation	87
13. Equipment List	89
Appendix A. System Validation Plots	90
Appendix B. SAR Test Plots	100
Appendix C. Probe Calibration and Dipole Calibration Report	124



Rev.	Issue Date	Report No.	Effect Page	Contents
00	23 Mar. 2026	STS2602061H01	ALL	Initial Issue



1. General Information

Environmental evaluation measurements of specific absorption rate (SAR) distributions in emulated human head and body tissues exposed to radio frequency (RF) radiation from wireless portable devices for compliance with the rules and regulations of the U.S. Federal Communications Commission (FCC).

1.1 EUT Description

Product Name	Smart POS Terminal		
Brand Name	 MoreFun		
Model Name	SR800		
Series Model	N/A		
Model Difference	N/A		
Sample number	260206006-2		
Battery	Model: 572965 Brand: EPT Rated Voltage: 3.85V Charge Limit Voltage: 4.4V Capacity: 1600mAh		
Device Category	Portable		
Product stage	Production unit		
RF Exposure Environment	General Population / Uncontrolled		
Hardware Version	A20		
Software Version	N/a		
Frequency Range	GSM 850: 824 MHz ~ 849 MHz PCS1900: 1850 MHz ~ 1910 MHz WCDMA Band II: 1850 MHz ~ 1910 MHz WCDMA Band IV: 1710 MHz ~ 1755 MHz WCDMA Band V: 824 MHz ~ 849 MHz LTE Band 2: 1850 MHz ~ 1910 MHz LTE Band 4: 1710 MHz ~ 1755 MHz LTE Band 5: 824 MHz ~ 849 MHz LTE Band 7: 2500 MHz ~ 2570 MHz LTE Band 12: 699 MHz ~ 716 MHz LTE Band 17: 704 MHz ~ 716 MHz LTE Band 25: 1850 MHz ~ 1915 MHz LTE Band 26: 814 MHz ~ 824 MHz / 824 MHz ~ 849 MHz LTE Band 41: 2496 MHz ~ 2690 MHz LTE Band 66: 1710 MHz ~ 1780 MHz WLAN 802.11b/g/n20: 2412 MHz ~ 2462 MHz WLAN 802.11n40: 2422 MHz ~ 2452 MHz WLAN 802.11a/n20/n40/ac20/ac40/ac80: 5150 ~ 5250 MHz WLAN 802.11a/n20/n40/ac20/ac40/ac80: 5250 ~ 5350 MHz WLAN 802.11a/n20/n40/ac20/ac40/ac80: 5470 ~ 5725 MHz WLAN 802.11a/n20/n40/ac20/ac40/ac80: 5725 ~ 5850 MHz Bluetooth: 2402 MHz to 2480 MHz NFC: 13.56MHz		
Max. Reported SAR(1g): (Limit: 1.6W/kg) Test distance: Body: 0mm	Band	Mode	Body Worn (W/kg)
	PCE	GSM 850	0.306
	PCE	GSM 1900	0.517
	PCE	WCDMA Band II	1.183
	PCE	WCDMA Band V	0.825
	PCE	WCDMA Band IV	0.466



	PCE	LTE Band 2	0.654
	PCE	LTE Band 4	0.942
	PCE	LTE Band 5	1.125
	PCE	LTE Band 7	1.131
	PCE	LTE Band 12	1.057
	PCE	LTE Band 13	0.795
	PCE	LTE Band 17	0.853
	PCE	LTE Band 25	0.809
	PCE	LTE Band 26	0.895
	PCE	LTE Band 41	0.999
	PCE	LTE Band 66	0.780
	PCE	LTE Band 71	1.261
	DTS	2.4G WLAN	0.171
	DSS	BT	0.035
	DXX	NFC	0.000
	NII	5.2G WLAN	0.171
	NII	5.3G WLAN	0.187
	NII	5.6G WLAN	0.115
NII	5.8G WLAN	0.143	
1-g Sum SAR			1.448
FCC Equipment Class	Licensed Portable Transmitter Held to Ear (PCE) Part 15 Spread Spectrum Transmitter (DSS) Digital Transmission System (DTS) Unlicensed National Information Infrastructure TX(NII) Part 15 Low Power Communication Device Transmitter (DXX)		
Operating Mode:	GSM: GSM Voice; GPRS/EGPRS Class 12 WCDMA: RMC, HSDPA, HSUPA Release 6 LTE: QPSK, 16QAM 2.4G WLAN : 802.11b(DSSS):CCK,DQPSK,DBPSK 802.11g(OFDM):BPSK,QPSK,16-QAM,64-QAM 802.11n(OFDM):BPSK,QPSK,16-QAM,64-QAM 5G WLAN: 802.11a(OFDM):BPSK,QPSK,16-QAM,64-QAM 802.11n(OFDM):BPSK,QPSK,16-QAM,64-QAM 802.11ac(OFDM):BPSK,QPSK,16-QAM,64-QAM,256-QAM Bluetooth: GFSK + $\pi/4$ DQPSK+8DPSK BLE: GFSK NFC: ASK		
Antenna Specification:	GSM/WCDMA/LTE: PIFA Antenna Bluetooth: PIFA Antenna WLAN: PIFA Antenna NFC: Coil Antenna		
SIM Card	Support dual-SIM, dual standby, the multiple SIM card with two lines cannot transmitting at the same time		
Hotspot Mode	Not Support		
DTM Mode	Not Support		
Note: 1. The dual SIM card mobile has 2 SIM slots and supports dual SIM dual standby. The WWAN radio transmission will be enabled by either one SIM at a time (Single active) 2. After pre-scan two SIM cards power, we found test result of the SIM1 was the worse, so we chose SIM1 card to perform all tests. 3. The EUT battery must be fully charged and checked periodically during the test to ascertain uniform power			



1.2 Test Environment

Ambient conditions in the SAR laboratory:

Items	Required
Temperature (°C)	18-25
Humidity (%RH)	30-70

1.3 Test Factory

ShenZhen STS Test Services Co.,Ltd.

A 1/F, Building B, Zhuoke Science Park, No.190 Chongqing Road, HepingShequ, Fuyong Sub-District, Bao'an District, Shenzhen, Guang Dong, China

FCC test Firm Registration No.: 625569

IC Registration No.: 12108A

A2LA Certificate No.: 4338.01



2. Test Standards and Limits

No.	Identity	Document Title
1	47 CFR Part 2	Frequency Allocations and Radio Treaty Matters; General Rules and Regulations
2	IEEE Std C95.1, 2019	IEEE Standard for Safety Levels with Respect to Human Exposure to Electric, Magnetic, and Electromagnetic Fields, 0 Hz to 300 GHz. It specifies the maximum exposure limit of 1.6 W/kg as averaged over any 1 gram of tissue for portable devices being used within 20 cm of the user in the uncontrolled environment.
3	IEEE Std. 1528-2013	Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques
4	FCC KDB 447498 D04 v01	RF Exposure Procedures and Equipment Authorization Policies for Mobile and Portable Devices
5	FCC KDB 865664 D01 v01r04	SAR Measurement 100 MHz to 6 GHz
6	FCC KDB 865664 D02 v01r02	RF Exposure Reporting
7	FCC KDB 941225 D01 v03r01	SAR Measurement Procedures for 3G Devices
8	FCC KDB 941225 D05 v02r05	SAR for LTE Devices
9	FCC KDB 248227 D01 Wi-Fi SAR v02r02	SAR Considerations for 802.11 Devices

(A). Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

(B). Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

NOTE: Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 1 gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

Population/Uncontrolled Environments:

Are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

Occupational/Controlled Environments:

Are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

NOTE

GENERAL POPULATION/UNCONTROLLED EXPOSURE

PARTIAL BODY LIMIT

1.6 W/kg



3. SAR Measurement System

3.1 Definition of Specific Absorption Rate (SAR)

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg) SAR measurement can be related to the electrical field in the tissue by

$$SAR = \frac{\sigma E^2}{\rho}$$

Where: σ is the conductivity of the tissue,

ρ is the mass density of the tissue and E is the RMS electrical field strength.

3.2 SAR System

The DASY5 system for performing compliance tests consists of the following items:

A standard high precision 6-axis robot (Stäubli RX family) with controller and software. An arm extension for accommodating the data acquisition electronics (DAE).

A dosimetric probe, i.e. an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.

A data acquisition electronic (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.

A unit to operate the optical surface detector which is connected to the EOC.

The Electro-Optical Coupler (EOC) performs the conversion from the optical into a digital electric signal of the DAE. The EOC is connected to the DASY5 measurement server.

The DASY5 measurement server, which performs all real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operation. A computer operating Windows 2003.

DASY5 software and SEMCAD data evaluation software.

Remote control with teach panel and additional circuitry for robot safety such as warning lamps, etc.


The generic twin phantom enabling the testing of left-hand and right-hand usage.



The device holder for handheld Mobile Phones.

Tissue simulating liquid mixed according to the given recipes.

System validation dipoles allowing to validate the proper functioning of the system.



3.3 DASY5 E-field Probe System

The SAR measurements were conducted with the dosimetric probe ES3DV3 (manufactured by SPEAG), designed in the classical triangular configuration and optimized for dosimetric evaluation.

Probe Specification

Construction Symmetrical design with triangular core
Interleaved sensors
Built-in shielding against static charges
PEEK enclosure material (resistant to organic solvents, e.g., DGBE)

Calibration ISO/IEC 17025 calibration service available.

Frequency 10 MHz to 4 GHz;
Linearity: ± 0.2 dB (30 MHz to 4 GHz)

Directivity ± 0.2 dB in HSL (rotation around probe axis)
 ± 0.3 dB in tissue material (rotation normal to probe axis)

Dynamic Range 5 μ W/g to > 100 mW/g;
Linearity: ± 0.2 dB

Dimensions Overall length: 337 mm (Tip: 20 mm)
Tip diameter: 3.9 mm (Body: 12 mm)
Distance from probe tip to dipole centers: 2.0 mm

Application General dosimetry up to 4 GHz
Dosimetry in strong gradient fields
Compliance tests of Mobile Phones


Compatibility DASY3, DASY5, DASY52 SAR and higher,
EASY4/MRI



Isotropic E-Field Probe


The isotropic E-Field probe has been fully calibrated and assessed for isotropicity, and boundary effect within a controlled environment. Depending on the frequency for which the probe is calibrated the method utilized for calibration will change.

The E-Field probe utilizes a triangular sensor arrangement as detailed in the diagram below:



3.4 Phantoms

The phantom used for all tests i.e. for both system checks and device testing, was the twin-headed "SAM Phantom", manufactured by SPEAG. The SAM twin phantom is a fiberglass shell phantom with 2mm shell thickness (except the ear region, where shell thickness increases to 6mm). System checking was performed using the flat section, whilst Head SAR tests used the left and right head profile sections. Body SAR testing also used the flat section between the head profiles.



SAM Twin Phantom

3.5 Device Holder

The device was placed in the device holder (illustrated below) that is supplied by SPEAG as an integral part of the DASY system.

The DASY device holder is designed to cope with the different positions given in the standard. It has two scales for device rotation (with respect to the body axis) and device inclination (with respect to the line between the ear reference points). The rotation centers for both scales is the ear reference point (ERP). Thus the device needs no repositioning when changing the angles.



Device holder supplied by SPEAG



3.6 Scanning Procedure

The DASY5 installation includes predefined files with recommended procedures for measurements and validation. They are read-only document files and destined as fully defined but unmeasured masks. All test positions (head or body-worn) are tested with the same configuration of test steps differing only in the grid definition for the different test positions.

The “reference” and “drift” measurements are located at the beginning and end of the batch process. They measure the field drift at one single point in the liquid over the complete procedure. The indicated drift is mainly the variation of the DUT’s output power and should vary max. $\pm 5\%$.

The “surface check” measurement tests the optical surface detection system of the DASY5 system by repeatedly detecting the surface with the optical and mechanical surface detector and comparing the results. The output gives the detecting heights of both systems, the difference between the two systems and the standard deviation of the detection repeatability. Air bubbles or refraction in the liquid due to separation of the sugar-water mixture gives poor repeatability (above $\pm 0.1\text{mm}$). To prevent wrong results tests are only executed when the liquid is free of air bubbles. The difference between the optical surface detection and the actual surface depends on the probe and is specified with each probe (It does not depend on the surface reflectivity or the probe angle to the surface within $\pm 30^\circ$.)

Area Scan

The Area Scan is used as a fast scan in two dimensions to find the area of high field values before running a detailed measurement around the hot spot. Before starting the area scan a grid spacing of $15\text{ mm} \times 15\text{ mm}$ is set. During the scan the distance of the probe to the phantom remains unchanged. After finishing area scan, the field maxima within a range of 2 dB will be ascertained.

Zoom Scan

Zoom Scans are used to estimate the peak spatial SAR values within a cubic averaging volume containing 1 g and 10 g of simulated tissue. The default Zoom Scan is done by $7 \times 7 \times 7$ points within a cube whose base is centered around the maxima found in the preceding area scan.

Spatial Peak Detection

The procedure for spatial peak SAR evaluation has been implemented and can determine values of masses of 1g and 10g, as well as for user-specific masses. The DASY5 system allows evaluations that combine measured data and robot positions, such as: • maximum search • extrapolation • boundary correction • peak search for averaged SAR. During a maximum search, global and local maxima searches are automatically performed in 2-D after each Area Scan measurement with at least 6 measurement points. It is based on the evaluation of the local SAR gradient calculated by the Quadratic Shepard’s method. The algorithm will find the global maximum and all local maxima within -2 dB of the global maxima for all SAR distributions.

Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. Several measurements at different distances are necessary for the extrapolation. Extrapolation routines require at least 10 measurement points in 3-D space. They are used in the Zoom Scan to obtain SAR values between the lowest measurement points and the inner phantom surface. The routine uses the modified Quadratic Shepard’s method for extrapolation. For a grid using $7 \times 7 \times 7$ measurement points with 5mm resolution amounting to 343 measurement points, the uncertainty of the extrapolation routines is less than 1% for 1g and 10g cubes.

A Z-axis scan measures the total SAR value at the x-and y-position of the maximum SAR value found during the cube $7 \times 7 \times 7$ scan. The probe is moved away in z-direction from the bottom of the SAM phantom in 5mm steps.



3.7 Data Storage and Evaluation

Data Storage

The DASY5 software stores the acquired data from the data acquisition electronics as raw data (in microvolt readings from the probe sensors), together with all necessary software parameters for the data evaluation (probe calibration data, liquid parameters and device frequency and modulation data) in measurement files with the extension ".DA4". The software evaluates the desired unit and format for output each time the data is visualized or exported. This allows verification of the complete software setup even after the measurement and allows correction of incorrect parameter settings. For example, if a measurement has been performed with a wrong crest factor parameter in the device setup, the parameter can be corrected afterwards and the data can be re-evaluated.

The measured data can be visualized or exported in different units or formats, depending on the selected probe type ([V/m], [A/m], [°C], [mW/g], [mW/cm²], [dBrel], etc.). Some of these units are not available in certain situations or show meaningless results, e.g., a SAR output in a lossless media will always be zero. Raw data can also be exported to perform the evaluation with other software packages.

Data Evaluation

The SEMCAD software automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software:

Probe parameters:	- Sensitivity	Normi, ai0, ai1, ai2
	- Conversion factor	ConvFi
	- Diode compression point	Dcpi
Device parameters:	- Frequency	f
	- Crest factor	cf
Media parameters:	- Conductivity	σ
	- Density	ρ

These parameters must be set correctly in the software. They can be found in the component documents or they can be imported into the software from the configuration files issued for the DASY5 components. In the direct measuring mode of the multimeter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics. If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given as:

$$V_i = U_i + U_i^2 \cdot \frac{cf}{dcp_i}$$

With V_i = compensated signal of channel i ($i = x, y, z$)
 U_i = input signal of channel i ($i = x, y, z$)
 cf = crest factor of exciting field (DASY parameter)
 dcp_i = diode compression point (DASY parameter)

From the compensated input signals the primary field data for each channel can be evaluated:

$$E - \text{fieldprobes} : E_i = \sqrt{\frac{V_i}{Norm_i \cdot ConvF}}$$

$$H - \text{fieldprobes} : H_i = \sqrt{V_i} \cdot \frac{a_{i0} + a_{i1}f + a_{i2}f^2}{f}$$

With V_i = compensated signal of channel i ($i = x, y, z$)
 $Norm_i$ = sensor sensitivity of channel i ($i = x, y, z$)
[mV/(V/m)²] for E-field Probes



ConvF	= sensitivity enhancement in solution
aij	= sensor sensitivity factors for H-field probes
f	= carrier frequency [GHz]
Ei	= electric field strength of channel i in V/m
Hi	= magnetic field strength of channel i in A/m

The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{tot} = \sqrt{E_x^2 + E_y^2 + E_z^2}$$

The primary field data are used to calculate the derived field units.

$$SAR = E_{tot}^2 \cdot \frac{\sigma}{\rho \cdot 1'000}$$

with	SAR	= local specific absorption rate in mW/g
	Etot	= total field strength in V/m
	σ	= conductivity in [mho/m] or [Siemens/m]
	ρ	= equivalent tissue density in g/cm ³

Note that the density is normally set to 1 (or 1.06), to account for actual brain density rather than the density of the simulation liquid.



4. Tissue Simulating Liquids

4.1 Simulating Liquids Parameter Check

The simulating liquids should be checked at the beginning of a series of SAR measurements to determine if the dielectric parameters are within the tolerances of the specified target values

The uncertainty due to the liquid conductivity and permittivity arises from two different sources. The first source of error is the deviation of the liquid conductivity from its target value (max _ 5 %) and the second source of error arises from the measurement procedures used to assess conductivity. The uncertainty shall be assessed using a rectangular probability For 1 g averaging, the maximum weighting coefficient for SAR is 0,5.

IEEE SCC-34/SC-2 RECOMMENDED TISSUE DIELECTRIC PARAMETERS

The head and body tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 have been incorporated in the following table.

Frequency	ϵ_r	σ 10g S/m
300	45.3	0.87
450	43.5	0.87
750	41.9	0.89
835	41.5	0.90
900	41.5	0.97
1450	40.5	1.20
1800 to 2000	40.0	1.40
2100	39.8	1.49
2450	39.2	1.80
2600	39.0	1.96
3000	38.5	2.40
3500	37.9	2.91
4000	37.4	3.43
4500	36.8	3.94
5000	36.2	4.45
5200	36.0	4.66
5400	35.8	4.86
5600	35.5	5.07
5800	35.3	5.27



The following table gives the recipes for tissue simulating liquid and the theoretical Conductivity/Permittivity.

Head (Reference IEEE1528)								
Frequency (MHz)	Water (%)	Sugar (%)	Cellulose (%)	Salt (%)	Preventol (%)	DGBE (%)	Conductivity σ (S/m)	Permittivity ϵ
750	41.1	57.0	0.2	1.4	0.2	0	0.89	41.9
835	40.3	57.9	0.2	1.4	0.2	0	0.90	41.5
900	40.3	57.9	0.2	1.4	0.2	0	0.97	41.5
1800, 1900, 2000	55.2	0	0	0.3	0	44.5	1.4	40.0
2450	55.0	0	0	0.1	0	44.9	1.80	39.2
2600	54.9	0	0	0.1	0	45.0	1.96	39.0
Frequency (MHz)	Water (%)	Hexyl Carbitol (%)			Triton X-100 (%)		Conductivity σ (S/m)	Permittivity ϵ
5200	62.52	17.24			17.24		4.66	36.0
5800	62.52	17.24			17.24		5.27	35.3
Body (From instrument manufacturer)								
Frequency (MHz)	Water (%)	Sugar (%)	Cellulose (%)	Salt (%)	Preventol (%)	DGBE (%)	Conductivity σ (S/m)	Permittivity ϵ
750	51.7	47.2	0	0.9	0.1	0	0.96	55.5
835	50.8	48.2	0	0.9	0.1	0	0.97	55.2
900	50.8	48.2	0	0.9	0.1	0	1.05	55.0
1800, 1900, 2000	70.2	0	0	0.4	0	29.4	1.52	53.3
2450	68.6	0	0	0.1	0	31.3	1.95	52.7
2600	68.2	0	0	0.1	0	31.7	2.16	52.5
Frequency(MHz)	Water	DGBE (%)			Salt (%)		Conductivity σ (S/m)	Permittivity ϵ
5200	78.60	21.40			/		5.30	49.00
5800	78.50	21.40			0.1		6.00	48.20

**LIQUID MEASUREMENT RESULTS**

Date	Ambient		Simulating Liquid		Parameters	Target	Measured	Deviation %	Limited %
	Temp. [°C]	Humidity %	Frequency (MHz)	Temp. [°C]					
2026-02-23	22.4	53	673	22.1	Permittivity	42.31	42.76	1.06	±5
					Conductivity	0.88	0.88	-0.55	±5
2026-02-23	22.4	53	681	22.1	Permittivity	42.27	42.36	0.21	±5
					Conductivity	0.89	0.90	1.65	±5
2026-02-23	22.4	53	688	22.1	Permittivity	42.23	42.18	-0.12	±5
					Conductivity	0.89	0.87	-1.79	±5
2026-02-23	22.4	53	704	22.1	Permittivity	42.15	42.73	1.39	±5
					Conductivity	0.89	0.88	-0.78	±5
2026-02-23	22.4	53	708	22.1	Permittivity	42.13	42.75	1.48	±5
					Conductivity	0.89	0.89	0.32	±5
2026-02-23	22.4	53	709	22.1	Permittivity	42.12	42.24	0.29	±5
					Conductivity	0.89	0.91	2.44	±5
2026-02-23	22.4	53	710	22.1	Permittivity	42.11	42.56	1.06	±5
					Conductivity	0.89	0.91	2.43	±5
2026-02-23	22.4	53	711	22.1	Permittivity	42.11	43.26	2.74	±5
					Conductivity	0.89	0.91	2.43	±5
2026-02-23	22.4	53	750	22.1	Permittivity	41.90	42.41	1.22	±5
					Conductivity	0.89	0.91	2.13	±5
2026-02-23	22.4	53	782	22.1	Permittivity	41.73	42.07	0.82	±5
					Conductivity	0.89	0.91	1.88	±5
2026-02-24	22.9	56	821.5	22.5	Permittivity	41.56	42.16	1.44	±5
					Conductivity	0.90	0.89	-0.94	±5
2026-02-24	22.9	56	826.4	22.5	Permittivity	41.54	41.01	-1.28	±5
					Conductivity	0.90	0.91	1.22	±5
2026-02-24	22.9	56	829	22.5	Permittivity	41.53	42.01	1.16	±5
					Conductivity	0.90	0.91	1.19	±5
2026-02-24	22.9	56	831.5	22.5	Permittivity	41.52	42.37	2.06	±5
					Conductivity	0.90	0.89	-1.07	±5
2026-02-24	22.9	56	835	22.5	Permittivity	41.50	41.87	0.89	±5
					Conductivity	0.90	0.92	2.22	±5
2026-02-24	22.9	56	836.5	22.5	Permittivity	41.49	42.14	1.56	±5
					Conductivity	0.90	0.89	-1.13	±5
2026-02-24	22.9	56	841.5	22.5	Permittivity	41.47	42.12	1.57	±5
					Conductivity	0.90	0.89	-1.20	±5
2026-02-24	22.9	56	844	22.5	Permittivity	41.46	42.36	2.18	±5
					Conductivity	0.90	0.90	-0.12	±5
2026-02-24	22.9	56	848.8	22.5	Permittivity	41.44	41.39	-0.11	±5
					Conductivity	0.90	0.92	2.04	±5
2026-02-25	23.2	60	1712.6	22.9	Permittivity	40.12	40.70	1.43	±5
					Conductivity	1.35	1.36	0.74	±5
2026-02-25	23.2	60	1720	22.9	Permittivity	40.11	40.42	0.76	±5
					Conductivity	1.35	1.35	-0.32	±5
2026-02-25	23.2	60	1732.5	22.9	Permittivity	40.10	39.91	-0.46	±5
					Conductivity	1.36	1.36	-0.10	±5
2026-02-25	23.2	60	1740	22.9	Permittivity	40.09	40.18	0.24	±5
					Conductivity	1.37	1.35	-1.15	±5
2026-02-25	23.2	60	1745	22.9	Permittivity	40.08	40.51	1.08	±5
					Conductivity	1.37	1.36	-0.63	±5



2026-02-25	23.2	60	1752.4	22.9	Permittivity	40.07	40.15	0.20	±5
					Conductivity	1.37	1.36	-0.93	±5
2026-02-25	23.2	60	1770	22.9	Permittivity	40.04	41.25	3.01	±5
					Conductivity	1.38	1.36	-1.65	±5
2026-02-25	23.2	60	1800	22.9	Permittivity	40.00	40.27	0.68	±5
					Conductivity	1.40	1.38	-1.43	±5
2026-02-26	23.8	49	1850.2	23.5	Permittivity	40.00	39.79	-0.53	±5
					Conductivity	1.40	1.38	-1.43	±5
2026-02-26	23.8	49	1852.4	23.5	Permittivity	40.00	40.49	1.23	±5
					Conductivity	1.40	1.39	-0.71	±5
2026-02-26	23.8	49	1860	23.5	Permittivity	40.00	41.14	2.85	±5
					Conductivity	1.40	1.42	1.43	±5
2026-02-26	23.8	49	1880	23.5	Permittivity	40.00	40.02	0.05	±5
					Conductivity	1.40	1.38	-1.43	±5
2026-02-26	23.8	49	1882.5	23.5	Permittivity	40.00	40.45	1.13	±5
					Conductivity	1.40	1.39	-0.71	±5
2026-02-26	23.8	49	1900	23.5	Permittivity	40.00	40.08	0.20	±5
					Conductivity	1.40	1.39	-0.71	±5
2026-02-26	23.8	49	1905	23.5	Permittivity	40.00	39.87	-0.33	±5
					Conductivity	1.40	1.40	0.00	±5
2026-02-26	23.8	49	1907.6	23.5	Permittivity	40.00	40.32	0.80	±5
					Conductivity	1.40	1.41	0.71	±5
2026-02-27	22.8	60	2437	22.5	Permittivity	39.22	39.86	1.62	±5
					Conductivity	1.79	1.78	-0.47	±5
2026-02-27	22.8	60	2441	22.5	Permittivity	39.22	39.90	1.74	±5
					Conductivity	1.79	1.77	-1.23	±5
2026-02-27	22.8	60	2450	22.5	Permittivity	39.20	39.93	1.86	±5
					Conductivity	1.80	1.81	0.56	±5
2026-02-25	23.2	60	2506	22.9	Permittivity	39.13	39.81	1.75	±5
					Conductivity	1.86	1.84	-1.06	±5
2026-02-25	23.2	60	2510	22.9	Permittivity	39.12	39.07	-0.13	±5
					Conductivity	1.86	1.85	-0.75	±5
2026-02-25	23.2	60	2535	22.9	Permittivity	39.09	39.09	0.01	±5
					Conductivity	1.89	1.86	-1.62	±5
2026-02-25	23.2	60	2560	22.9	Permittivity	39.05	39.11	0.15	±5
					Conductivity	1.92	1.89	-1.43	±5
2026-02-25	23.2	60	2600	22.9	Permittivity	39.00	39.05	0.13	±5
					Conductivity	1.96	1.93	-1.53	±5
2026-02-27	22.8	60	5180	22.5	Permittivity	36.02	37.22	3.33	±5
					Conductivity	4.64	4.64	0.02	±5
2026-02-27	22.8	60	5200	22.5	Permittivity	36.00	36.71	1.97	±5
					Conductivity	4.66	4.67	0.21	±5
2026-02-27	22.8	60	5320	22.5	Permittivity	35.88	36.26	1.06	±5
					Conductivity	4.78	4.76	-0.42	±5
2026-02-27	22.8	60	5400	22.5	Permittivity	35.80	35.68	-0.34	±5
					Conductivity	4.86	4.85	-0.21	±5
2026-02-27	22.8	60	5500	22.5	Permittivity	35.68	35.91	0.66	±5
					Conductivity	4.96	4.97	0.15	±5
2026-02-27	22.8	60	5600	22.5	Permittivity	35.55	35.71	0.45	±5
					Conductivity	5.07	5.07	0.10	±5
2026-02-27	22.8	60	5785	22.5	Permittivity	35.32	35.00	-0.89	±5
					Conductivity	5.25	5.26	0.11	±5
2026-02-27	22.8	60	5800	22.5	Permittivity	35.30	35.55	0.71	±5
					Conductivity	5.27	5.26	-0.19	±5




5. SAR System Validation

5.1 Validation System

The purpose of the system check is to verify that the system operates within its specifications at the device test frequency. The system check is a simple check of repeatability to make sure that the system works correctly at the time of the compliance test;

System check results have to be equal or near the values determined during dipole calibration with the relevant liquids and test system ($\pm 10\%$).

System check is performed regularly on all frequency bands where tests are performed with the DASY5 system.



**5.2 Validation Result**

Date	Frequency (MHz)	Power	SAR _{1g} (W/Kg)	SAR _{10g} (W/Kg)	Drift (%)	1W Target		Difference percentage		Limited %
						SAR _{1g} (W/Kg)	SAR _{10g} (W/Kg)	1g	10g	
2026-02-23	750	100 mW	0.821	0.545	-0.15	8.49	5.53	-3.30%	-1.45%	10
		Normalize to 1 Watt	8.21	5.45						
2026-02-24	835	100 mW	0.972	0.633	-0.61	9.63	6.15	0.93%	2.93%	10
		Normalize to 1 Watt	9.72	6.33						
2026-02-25	1800	100 mW	3.810	1.990	-0.74	37.95	20.49	0.40%	-2.88%	10
		Normalize to 1 Watt	38.10	19.90						
2026-02-26	1900	100 mW	4.050	2.080	-0.30	39.84	20.20	1.66%	2.97%	10
		Normalize to 1 Watt	40.50	20.80						
2026-02-27	2450	100 mW	5.240	2.450	-0.61	54.70	24.11	-4.20%	1.62%	10
		Normalize to 1 Watt	52.40	24.50						
2026-02-25	2600	100 mW	5.600	2.550	-0.01	56.19	24.08	-0.34%	5.90%	10
		Normalize to 1 Watt	56.00	25.50						
2026-02-27	5200	10 mW	1.605	0.617	-3.74	163.88	57.29	-2.06%	7.70%	10
		Normalize to 1 Watt	160.50	61.70						
2026-02-27	5400	10 mW	1.714	0.597	2.57	172.23	59.16	-0.48%	0.91%	10
		Normalize to 1 Watt	171.40	59.70						
2026-02-27	5600	10 mW	1.723	0.641	-2.74	181.28	61.57	-4.95%	4.11%	10
		Normalize to 1 Watt	172.30	64.10						
2026-02-27	5800	10 mW	1.843	0.678	-2.69	188.95	63.45	-2.46%	6.86%	10
		Normalize to 1 Watt	184.30	67.80						

Note:

(1) We use a CW signal of 20dBm(750,835,1800,1900,2450,2600MHz) and 10dBm(5000-6000MHz) for system check, and then all SAR values are normalized to 1W forward power. The result must be within $\pm 10\%$ of target value.



6. SAR Evaluation Procedures

The procedure for assessing the average SAR value consists of the following steps:

The following steps are used for each test position

- Establish a call with the maximum output power with a base station simulator. The connection between the mobile and the base station simulator is established via air interface
- Measurement of the local E-field value at a fixed location. This value serves as a reference value for calculating a possible power drift.
- Measurement of the SAR distribution with a grid of 8 to 16mm * 8 to 16 mm and a constant distance to the inner surface of the phantom. Since the sensors cannot directly measure at the inner phantom surface, the values between the sensors and the inner phantom surface are extrapolated. With these values the area of the maximum SAR is calculated by an interpolation scheme.
- Around this point, a cube of 30 * 30 * 30 mm or 32 * 32 * 32 mm is assessed by measuring 5 or 8 * 5 or 8*4 or 5 mm. With these data, the peak spatial-average SAR value can be calculated.


➤ Area Scan& Zoom Scan

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g. Area scan and zoom scan resolution setting follows KDB 865664 D01 quoted below. When the 1-g SAR of the highest peak is within 2 dB of the SAR limit, additional zoom scans are required for other peaks within 2 dB of the highest peak that have not been included in any zoom scan to ensure there is no increase in SAR.

7. EUT Antenna Location Sketch

It is a Smart POS Terminal, support GSM/WCDMA/LTE/WLAN/BT mode.

Top side



- WWAN Antenna
- WLAN Antenna
- NFC Antenna

Antenna Separation Distance(cm)						
ANT	Back Side	Front Side	Left Side	Right Side	Top Side	Bottom Side
WLAN/BT	≤0.5	1.5	≤0.5	7	1	7
WWAN_Main	≤0.5	1.5	≤0.5	5.5	7.5	≤0.5
NFC	≤0.5	1.5	≤0.5	≤0.5	5	≤0.5

Note 1: The antenna information refer the manufacturer provide report, applicable only to the tested sample identified in the report.

**7.1 SAR test exclusion consider table**

The WWAN/WLAN/BT SAR evaluation of Maximum power (dBm) summing tolerance.

Exposure Position	Wireless Interface	GSM850	PCS1900	WCDMA II	WCDMA IV	WCDMA V
Exposure Position	Calculated Frequency(GHz)	0.8366	1.8502	1.88	1.74	0.8264
	Maximum Turn-up power (dBm)	33	30.5	24	24	24.5
	Maximum rated power(mW)	1995.26	1122.02	251.19	251.19	281.84
Back Side	Separation distance (cm)	≤0.5	≤0.5	≤0.5	≤0.5	≤0.5
	exclusion threshold(mW)	9.22	3.44	3.39	3.30	6.55
	Testing required?	YES	YES	YES	YES	YES
Front Side	Separation distance (cm)	1.5	1.5	1.5	1.5	1.5
	exclusion threshold(mW)	43.66	25.97	25.74	26.39	40.87
	Testing required?	YES	YES	YES	YES	YES
Left Side	Separation distance (cm)	≤0.5	≤0.5	≤0.5	≤0.5	≤0.5
	exclusion threshold(mW)	9.22	3.44	3.39	3.30	6.55
	Testing required?	YES	YES	YES	YES	YES
Right Side	Separation distance (cm)	5.5	5.5	5.5	5.5	5.5
	exclusion threshold(mW)	274.57	284.07	282.80	308.48	356.09
	Testing required?	YES	YES	NO	NO	NO
Top Side	Separation distance (cm)	7.5	7.5	7.5	7.5	7.5
	exclusion threshold(mW)	425.89	502.85	501.14	554.78	597.02
	Testing required?	YES	YES	NO	NO	NO
Bottom Side	Separation distance (cm)	≤0.5	≤0.5	≤0.5	≤0.5	≤0.5
	exclusion threshold(mW)	9.22	3.44	3.39	3.30	6.55
	Testing required?	YES	YES	YES	YES	YES



Exposure Position	Wireless Interface	LTE Band 2	LTE Band 4	LTE Band 5	LTE Band 7	LTE Band 12
	Calculated Frequency(GHz)	1.8575	1.7325	0.8255	2.535	0.7015
	Maximum Turn-up power (dBm)	23.5	23.5	24	23.5	24.5
	Maximum rated power(mW)	223.87	223.87	251.19	223.87	281.84
Back Side	Separation distance (cm)	≤0.5	≤0.5	≤0.5	≤0.5	≤0.5
	exclusion threshold(mW)	3.43	3.62	9.40	2.67	11.81
	Testing required?	YES	YES	YES	YES	YES
Front Side	Separation distance (cm)	1.5	1.5	1.5	1.5	1.5
	exclusion threshold(mW)	25.91	26.95	44.06	21.76	49.28
	Testing required?	YES	YES	YES	YES	YES
Left Side	Separation distance (cm)	≤0.5	≤0.5	≤0.5	≤0.5	≤0.5
	exclusion threshold(mW)	3.43	3.62	9.40	2.67	11.81
	Testing required?	YES	YES	YES	YES	YES
Right Side	Separation distance (cm)	5.5	5.5	5.5	5.5	5.5
	exclusion threshold(mW)	283.76	289.36	273.99	260.07	266.99
	Testing required?	NO	NO	NO	NO	YES
Top Side	Separation distance (cm)	7.5	7.5	7.5	7.5	7.5
	exclusion threshold(mW)	502.43	509.94	423.84	470.23	399.65
	Testing required?	NO	NO	NO	NO	NO
Bottom Side	Separation distance (cm)	≤0.5	≤0.5	≤0.5	≤0.5	≤0.5
	exclusion threshold(mW)	3.43	3.62	9.40	2.67	11.81
	Testing required?	YES	YES	YES	YES	YES



Exposure Position	Wireless Interface	LTE Band 13	LTE Band 17	LTE Band 25	LTE Band 26	LTE Band 41
	Calculated Frequency(GHz)	0.7845	0.71	1.8255	0.8155	2.5035
	Maximum Turn-up power (dBm)	24	24.5	23.5	24.5	23.5
	Maximum rated power(mW)	251.19	281.84	223.87	281.84	223.87
Back Side	Separation distance (cm)	≤0.5	≤0.5	≤0.5	≤0.5	≤0.5
	exclusion threshold(mW)	10.09	11.61	3.09	9.56	2.70
	Testing required?	YES	YES	YES	YES	YES
Front Side	Separation distance (cm)	1.5	1.5	1.5	1.5	1.5
	exclusion threshold(mW)	45.63	48.87	25.53	44.43	21.91
	Testing required?	YES	YES	YES	YES	YES
Left Side	Separation distance (cm)	≤0.5	≤0.5	≤0.5	≤0.5	≤0.5
	exclusion threshold(mW)	10.09	11.61	3.09	9.56	2.70
	Testing required?	YES	YES	YES	YES	YES
Right Side	Separation distance (cm)	5.5	5.5	5.5	5.5	5.5
	exclusion threshold(mW)	271.78	267.50	310.84	273.46	260.99
	Testing required?	NO	YES	NO	YES	NO
Top Side	Separation distance (cm)	7.5	7.5	7.5	7.5	7.5
	exclusion threshold(mW)	416.11	401.39	564.47	421.98	471.48
	Testing required?	NO	NO	NO	NO	NO
Bottom Side	Separation distance (cm)	≤0.5	≤0.5	≤0.5	≤0.5	≤0.5
	exclusion threshold(mW)	10.09	11.61	3.09	9.56	2.70
	Testing required?	YES	YES	YES	YES	YES



Exposure Position	Wireless Interface	LTE Band 66	LTE Band 71	BT	2.4G WLAN
	Calculated Frequency(GHz)	1.7775	0.6705	2.441	2.437
	Maximum Turn-up power (dBm)	24	24.5	4.5	18
	Maximum rated power(mW)	251.19	281.84	2.82	63.10
Back Side	Separation distance (cm)	≤0.5	≤0.5	≤0.5	≤0.5
	exclusion threshold(mW)	3.55	7.75	2.75	2.76
	Testing required?	YES	YES	YES	YES
Front Side	Separation distance (cm)	1.5	1.5	1.5	1.5
	exclusion threshold(mW)	26.56	45.97	22.22	22.24
	Testing required?	YES	YES	NO	YES
Left Side	Separation distance (cm)	≤0.5	≤0.5	≤0.5	≤0.5
	exclusion threshold(mW)	3.55	7.75	2.75	2.76
	Testing required?	YES	YES	YES	YES
Right Side	Separation distance (cm)	5.5	5.5	7	7
	exclusion threshold(mW)	287.28	377.58	415.75	415.91
	Testing required?	NO	NO	NO	NO
Top Side	Separation distance (cm)	7.5	7.5	1	1
	exclusion threshold(mW)	507.16	624.20	10.28	10.29
	Testing required?	NO	NO	NO	YES
Bottom Side	Separation distance (cm)	≤0.5	≤0.5	7	7
	exclusion threshold(mW)	3.55	7.75	415.75	415.91
	Testing required?	YES	YES	NO	NO



Exposure Position	Wireless Interface	5.2G WLAN	5.3G WLAN	5.6G WLAN	5.8G WLAN	NFC
	Calculated Frequency(GHz)	5.18	5.32	5.5	5.785	0.01356
	Maximum Turn-up power (dBm)	13.5	14	14	13.5	-41.5
	Maximum rated power(mW)	22.39	25.12	25.12	22.39	0.00
Back Side	Separation distance (cm)	≤0.5	≤0.5	≤0.5	≤0.5	≤0.5
	exclusion threshold(mW)	1.51	1.47	1.44	1.38	176.28
	Testing required?	YES	YES	YES	YES	NO
Front Side	Separation distance (cm)	1.5	1.5	1.5	1.5	1.5
	exclusion threshold(mW)	14.56	14.34	14.07	13.68	412.44
	Testing required?	YES	YES	YES	YES	NO
Left Side	Separation distance (cm)	≤0.5	≤0.5	≤0.5	≤0.5	≤0.5
	exclusion threshold(mW)	1.51	1.47	1.44	1.38	176.28
	Testing required?	YES	YES	YES	YES	NO
Right Side	Separation distance (cm)	7	7	7	7	≤0.5
	exclusion threshold(mW)	350.22	348.10	345.47	341.51	176.28
	Testing required?	NO	NO	NO	NO	NO
Top Side	Separation distance (cm)	1	1	1	1	5
	exclusion threshold(mW)	6.30	6.19	6.06	5.86	1046.91
	Testing required?	YES	YES	YES	YES	NO
Bottom Side	Separation distance (cm)	7	7	7	7	≤0.5
	exclusion threshold(mW)	350.22	348.10	345.47	341.51	176.28
	Testing required?	NO	NO	NO	NO	NO

Note:

1. maximum power is the source-based time-average power and represents the maximum RF output power among production units.
2. Per KDB 447498 D04, for larger devices, the test separation distance of adjacent edge configuration is determined by the closest separation between the antenna and the user.
3. Per KDB 447498 D04, if the maximum time-averaged power available does not exceed 1 mW. This stand-alone SAR exemption test.



4. Per KDB 447498 D04, the available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

d = the separation distance (cm);

5. Per KDB 447498 D04, An alternative to the SAR-based exemption is using below table and the minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in below table to apply, R must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

RF Source frequency (MHz)	Threshold ERP(watts)
0.3-1.34	$1,920 R^2$.
1.34-30	$3,450 R^2/f^2$.
30-300	$3.83 R^2$.
300-1,500	$0.0128 R^2 f$.
1,500-100,000	$19.2 R^2$.




6. Per KDB 248227 D01, choose the highest output power channel to test SAR and determine further SAR exclusion 8. for each frequency band, testing at higher data rates and higher order modulations is not required when the maximum average output power for each of each of these configurations is less than 1/4db higher than those measured at the lower data rate than 11b mode, thus the SAR can be excluded.
7. Per KDB 616217 D04, SAR evaluation for the front surface of tablet display screens are generally not necessary.
8. Per KDB 248227, as maximum rated power for U-NII-2A > U-NII-1, U-NII-2A was chosen for SAR evaluation. Based on the measurements obtained, SAR measurements on U-NII-1 are not required as highest reported SAR from U-NII-2A band is $\leq 1.2\text{W/Kg}$.

8. EUT Test Position

This EUT was tested in Front Face, Back Side, Left Side, Right Side, Top Side and Bottom Side.

8.1 Body-worn Position Conditions:

Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in KDB Publication 447498 D04 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. When the same wireless transmission configuration is used for testing body-worn accessory and hotspot mode SAR, respectively, in voice and data mode, SAR results for the most conservative *test separation distance* configuration may be used to support both SAR conditions. When the *reported* SAR for a body-worn accessory, measured without a headset connected to the handset, is $> 1.2 \text{ W/kg}$, the highest *reported* SAR configuration for that wireless mode and frequency band should be repeated for the body-worn accessory with a headset attached to the handset.





9. Uncertainty

9.1 Measurement Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in IEEE 1528: 2013. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Measurement uncertainty for DUT averaged over 1 gram / 10 gram.									
Uncertainty Component	Sec.	Tol (+ - %)	Prob. Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (+ %)	10g Ui (+ %)	vi
Measurement System									
Probe calibration	E.2.1	5.72	N	1.00	1.00	1.00	5.72	5.72	∞
Axial Isotropy	E.2.2	0.18	R	1.73	0.71	0.71	0.07	0.07	∞
Hemispherical Isotropy	E.2.2	1.04	R	1.73	0.71	0.71	0.42	0.42	∞
Boundary effect	E.2.3	0.80	R	1.73	1.00	1.00	0.46	0.46	∞
Linearity	E.2.4	1.25	R	1.73	1.00	1.00	0.72	0.72	∞
System detection limits	E.2.4	1.20	R	1.73	1.00	1.00	0.69	0.69	∞
Modulation response	E.2.5	3.42	R	1.73	1.00	1.00	1.97	1.97	∞
Readout Electronics	E.2.6	0.26	N	1.00	1.00	1.00	0.26	0.26	∞
Response Time	E.2.7	0.17	R	1.73	1.00	1.00	0.10	0.10	∞
Integration Time	E.2.8	1.43	R	1.73	1.00	1.00	0.83	0.83	∞
RF ambient conditions-Noise	E.6.1	3.51	R	1.73	1.00	1.00	2.03	2.03	∞
RF ambient conditions- reflections	E.6.1	3.15	R	1.73	1.00	1.00	1.82	1.82	∞
Probe positioner mechanical tolerance	E.6.2	1.20	R	1.73	1.00	1.00	0.69	0.69	∞
Probe positioning with respect to phantom shell	E.6.3	1.40	R	1.73	1.00	1.00	0.81	0.81	∞
Extrapolation, interpolation, and integrations algorithms for max. SAR evaluation	E.5	2.10	R	1.73	1.00	1.00	1.21	1.21	∞
Test sample Related									
Test sample positioning	E.4.2	3.10	N	1.00	1.00	1.00	3.10	3.10	∞
Device holder uncertainty	E.4.1	3.80	N	1.00	1.00	1.00	3.80	3.80	∞
Output power variation— SAR drift measurement	E.2.9	4.50	R	1.73	1.00	1.00	2.60	2.60	∞
SAR scaling	E.6.5	1.80	R	1.73	1.00	1.00	1.04	1.04	∞
Phantom and tissue parameters									
Phantom shell uncertainty— shape, thickness, and permittivity	E.3.1	3.70	R	1.73	1.00	1.00	2.14	2.14	∞
Uncertainty in SAR correction for deviations in permittivity and conductivity	E.3.2	1.90	N	1.00	1.00	0.84	1.90	1.60	∞
Liquid conductivity measurement	E.3.3	2.40	R	1.73	0.78	0.71	1.08	0.98	M
Liquid permittivity measurement	E.3.3	4.10	N	1.00	0.78	0.71	3.20	2.91	M
Liquid conductivity— temperature uncertainty	E.3.4	2.70	R	1.73	0.23	0.26	0.36	0.41	∞
Liquid permittivity— temperature uncertainty	E.3.4	4.80	N	1.00	0.23	0.26	1.10	1.25	∞
Combined Standard Uncertainty			RSS				10.08	9.59	
Expanded Uncertainty (95% Confidence interval)			K=2				19.58	19.18	



System Validation uncertainty for DUT averaged over 1 gram / 10 gram.									
Uncertainty Component	Sec.	Tol (+-%)	Prob. Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (+-%)	10g Ui (+-%)	vi
Measurement System									
Probe calibration	E.2.1	5.72	N	1.00	1.00	1.00	5.72	5.72	∞
Axial Isotropy	E.2.2	0.18	R	1.73	1.00	1.00	0.10	0.10	∞
Hemispherical Isotropy	E.2.2	1.04	R	1.73	0.00	0.00	0.00	0.00	∞
Boundary effect	E.2.3	0.80	R	1.73	1.00	1.00	0.46	0.46	∞
Linearity	E.2.4	1.25	R	1.73	1.00	1.00	0.72	0.72	∞
System detection limits	E.2.4	1.20	R	1.73	1.00	1.00	0.69	0.69	∞
Modulation response	E.2.5	3.42	R	1.73	0.00	0.00	0.00	0.00	∞
Readout Electronics	E.2.6	0.26	N	1.00	1.00	1.00	0.26	0.26	∞
Response Time	E.2.7	0.17	R	1.73	0.00	0.00	0.00	0.00	∞
Integration Time	E.2.8	1.43	R	1.73	0.00	0.00	0.00	0.00	∞
RF ambient conditions-Noise	E.6.1	3.51	R	1.73	1.00	1.00	2.03	2.03	∞
RF ambient conditions-reflections	E.6.1	3.15	R	1.73	1.00	1.00	1.82	1.82	∞
Probe positioner mechanical tolerance	E.6.2	1.20	R	1.73	1.00	1.00	0.69	0.69	∞
Probe positioning with respect to phantom shell	E.6.3	1.40	R	1.73	1.00	1.00	0.81	0.81	∞
Extrapolation, interpolation, and integrations algorithms for max. SAR evaluation	E.5	2.10	R	1.73	1.00	1.00	1.21	1.21	∞
System validation source									
Deviation of experimental dipole from numerical dipole	E.6.4	4.80	N	1.00	1.00	1.00	4.80	4.80	∞
Input power and SAR drift measurement	8,6.6.4	5.10	R	1.73	1.00	1.00	2.94	2.94	∞
Dipole axis to liquid distance	8,E.6.6	2.40	R	1.73	1.00	1.00	1.39	1.39	∞
Phantom and set-up									
Phantom shell uncertainty—shape, thickness, and permittivity	E.3.1	3.70	R	1.73	1.00	1.00	2.14	2.14	∞
Uncertainty in SAR correction for deviations in permittivity and conductivity	E.3.2	1.90	N	1.00	1.00	0.84	1.90	1.60	∞
Liquid conductivity (temperature uncertainty)	E.3.3	2.40	R	1.73	0.78	0.71	1.08	0.98	∞
Liquid conductivity (measured)	E.3.3	4.10	N	1.00	0.78	0.71	3.20	2.91	M
Liquid permittivity (temperature uncertainty)	E.3.4	2.70	R	1.73	0.23	0.26	0.36	0.41	∞
Liquid permittivity (measured)	E.3.4	4.80	N	1.00	0.23	0.26	1.10	1.25	M
Combined Standard Uncertainty			RSS				9.72	9.52	
Expanded Uncertainty (95% Confidence interval)			K=2				19.44	19.03	



。 System Check uncertainty for DUT averaged over 1 gram / 10 gram.									
Uncertainty Component	Sec.	Tol (+-%)	Prob. Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (+-%)	10g Ui (+-%)	vi
Measurement System									
Probe calibration drift	E.2.1.3	5.72	N	1.00	1.00	1.00	5.72	5.72	∞
Axial Isotropy	E.2.2	0.18	R	1.73	0.00	0.00	0.00	0.00	∞
Hemispherical Isotropy	E.2.2	1.04	R	1.73	0.00	0.00	0.00	0.00	∞
Boundary effect	E.2.3	0.8	R	1.73	0.00	0.00	0.00	0.00	∞
Linearity	E.2.4	1.25	R	1.73	0.00	0.00	0.00	0.00	∞
System detection limits	E.2.4	1.20	R	1.73	0.00	0.00	0.00	0.00	∞
Modulation response	E.2.5	3.42	R	1.73	0.00	0.00	0.00	0.00	∞
Readout Electronics	E.2.6	0.26	N	1.00	0.00	0.00	0.00	0.00	∞
Response Time	E.2.7	0.17	R	1.73	0.00	0.00	0.00	0.00	∞
Integration Time	E.2.8	1.43	R	1.73	0.00	0.00	0.00	0.00	∞
RF ambient conditions-Noise	E.6.1	3.51	R	1.73	0.00	0.00	0.00	0.00	∞
RF ambient conditions-reflections	E.6.1	3.15	R	1.73	0.00	0.00	0.00	0.00	∞
Probe positioner mechanical tolerance	E.6.2	1.2	R	1.73	1.00	1.00	0.69	0.69	∞
Probe positioning with respect to phantom shell	E.6.3	1.4	R	1.73	1.00	1.00	0.81	0.81	∞
Extrapolation, interpolation, and integrations algorithms for max. SAR evaluation	E.5	3.9	R	1.73	0.00	0.00	0.00	0.00	∞
System check source (dipole)									
Deviation of experimental dipoles	E.6.4	4.8	N	1.00	1.00	1.00	4.80	4.80	∞
Input power and SAR drift measurement	8,6.6.4	5.1	R	1.73	1.00	1.00	2.94	2.94	∞
Dipole axis to liquid distance	8,E.6.6	2.4	R	1.73	1.00	1.00	1.39	1.39	∞
Phantom and tissue parameters									
Phantom shell uncertainty—shape, thickness, and permittivity	E.3.1	3.7	R	1.73	1.00	1.00	2.14	2.14	∞
Uncertainty in SAR correction for deviations in permittivity and conductivity	E.3.2	1.9	N	1.00	1.00	0.84	1.90	1.60	∞
Liquid conductivity measurement	E.3.3	2.4	R	1.73	0.78	0.71	1.08	0.98	∞
Liquid permittivity measurement	E.3.3	4.1	N	1.00	0.78	0.71	3.20	2.91	M
Liquid conductivity—temperature uncertainty	E.3.4	2.7	R	1.73	0.23	0.26	0.36	0.41	∞
Liquid permittivity—temperature uncertainty	E.3.4	4.8	N	1.00	0.23	0.26	1.10	1.25	M
Combined Standard Uncertainty			RSS				5.56	5.20	
Expanded Uncertainty (95% Confidence interval)			K=2				11.12	10.41	



10. Conducted Power Measurement

10.1 Test Result

Burst Average Power (dBm)						
Band	GSM 850			PCS 1900		
Channel	128	190	251	512	661	810
Frequency (MHz)	824.2	836.6	848.8	1850.2	1880.0	1909.8
GSM(GMSK, 1-Slot)	32.48	32.71	32.58	29.99	29.89	29.65
GPRS (GMSK, 1-Slot)	32.74	32.9	32.75	30.04	29.97	29.71
GPRS (GMSK, 2-Slot)	31.93	21.94	31.96	29.12	29	28.77
GPRS (GMSK, 3-Slot)	29.87	30.03	29.93	27.05	26.97	26.72
GPRS (GMSK, 4-Slot)	28.6	28.8	28.65	25.74	25.67	25.51
EGPRS(8PSK, 1-Slot)	28.06	28.19	28.08	27.07	26.98	26.69
EGPRS(8PSK, 2-Slot)	27.19	26.98	27.03	25.72	26.15	25.54
EGPRS(8PSK, 3-Slot)	24.75	25.1	25.26	23.81	23.91	23.47
EGPRS(8PSK, 4-Slot)	23.73	24.18	23.85	22.58	23.02	22.43
Remark: GPRS, CS4 coding scheme. EGPRS, MCS5 coding scheme. Multi-Slot Class 8, Support Max 4 downlink, 1 uplink, 5 working link Multi-Slot Class 10, Support Max 4 downlink, 2 uplink, 5 working link Multi-Slot Class 12, Support Max 4 downlink, 4 uplink, 5 working link						

Frame- Average Power(dBm)						
Band	GSM 850			PCS 1900		
Channel	128	190	251	512	661	810
Frequency (MHz)	824.2	836.6	848.8	1850.2	1880.0	1909.8
GSM(GMSK, 1-Slot)	23.45	23.68	23.55	20.96	20.86	20.62
GPRS (GMSK, 1-Slot)	23.71	23.87	23.72	21.01	20.94	20.68
GPRS (GMSK, 2-Slot)	25.91	15.92	25.94	23.10	22.98	22.75
GPRS (GMSK, 3-Slot)	25.61	25.77	25.67	22.79	22.71	22.46
GPRS (GMSK, 4-Slot)	25.59	25.79	25.64	22.73	22.66	22.50
EGPRS(8PSK, 1-Slot)	19.03	19.16	19.05	18.04	17.95	17.66
EGPRS(8PSK, 2-Slot)	21.17	20.96	21.01	19.70	20.13	19.52
EGPRS(8PSK, 3-Slot)	20.49	20.84	21.00	19.55	19.65	19.21
EGPRS(8PSK, 4-Slot)	20.72	21.17	20.84	19.57	20.01	19.42
Remark : 1. SAR testing was performed on the maximum frame-averaged power mode. 2. The frame-averaged power is linearly proportion to the slot number configured and it is linearly scaled the maximum Burst - averaged power based on time slots. The calculated method is shown as below: Frame-averaged power = Burst averaged power (1 TX Slot) – 9.03 dB Frame-averaged power = Burst averaged power (2 TX Slots) – 6.02 dB Frame-averaged power = Burst averaged power (3 TX Slots) - 4.26 dB Frame-averaged power = Burst averaged power (4 TX Slots) – 3.01 dB						

**WCDMA**

Band	WCDMA Band 2			WCDMA Band 4			WCDMA Band 5		
Channel	9262	9400	9538	1312	1413	1513	4132	4183	4233
Frequency (MHz)	1852.4	1880	1907.6	1712.6	1740	1752.4	826.4	836.6	846.6
RMC 12.2Kbps	23.75	23.8	23.78	23.64	23.7	23.68	24.08	23.92	23.77
HSDPA Subtest-1	22.74	22.11	21.28	22.61	22.28	21.14	23.16	22.47	21.52
HSDPA Subtest-2	20.95	22.79	22.44	21.12	22.69	22.41	21.26	22.95	22.41
HSDPA Subtest-3	21.28	21.36	22.77	21.22	21.21	22.64	21.09	21.52	22.78
HSDPA Subtest-4	22.37	21.24	21.02	22.46	20.9	21.18	22.15	21.24	21.29
HSUPA Subtest-1	21.52	22.5	21.2	22.34	22.46	21.3	22.81	22.93	22.04
HSUPA Subtest-2	22.7	21.05	22.46	22.59	21.71	22.37	23.04	22.55	22.58
HSUPA Subtest-3	22.57	21.79	22.72	22.46	21.1	22.7	22.58	21.49	22.84
HSUPA Subtest-4	22.1	22.5	22.64	21.76	22.37	22.45	22.15	22.51	22.59
HSUPA Subtest-5	21.2	22.74	21.96	21.26	22.63	21.48	21.12	22.69	21.95

According to 3GPP 25.101 sub-clause 6.2.2, the maximum output power is allowed to be reduced by following the table.

Table 6.1A: UE maximum output power with HS-DPCCH and E-DCH

UE Transmit Channel Configuration	CM(db)	MPR(db)
For all combinations of ,DPDCH,DPCCH HS-DPDCH,E-DPDCH and E-DPCCH	$0 \leq CM \leq 3.5$	$MAX(CM-1,0)$
Note: CM=1 for $\beta_c/\beta_d=12/15$, $\beta_{hs}/\beta_c=24/15$. For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.		

The device supports MPR to solve linearity issues (ACLR or SEM) due to the higher peak-to average ratios (PAR) of the HSUPA signal. This prevents saturating the full range of the TX DAC inside of device and provides a reduced power output to the RF transceiver chip according to the Cubic Metric (a function of the combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH).

When E-DPDCH channels are present the beta gains on those channels are reduced firsts to try to get the power under the allowed limit. If the beta gains are lowered as far as possible, then a hard limiting is applied at the maximum allowed level.

The SW currently recalculates the cubic metric every time the beta gains on the E-DPDCH are reduced. The cubic metric will likely get lower each time this is done .However, there is no reported reduction of maximum output power in the HSUPA mode since the device also provides a compensation for the power back-off by increasing the gain of TX_AGC in the transceiver (PA) device.

The end effect is that the DUT output power is identical to the case where there is no MPR in the device.



2.4G WLAN

2.4GWIFI				
Mode	Channel Number	Frequency (MHz)	Conducted Power (dBm)	Output Power (mW)
802.11b	1	2412	16.31	42.76
	7	2437	16.87	48.64
	11	2462	16.72	46.99
802.11g	1	2412	17.14	51.76
	7	2437	17.91	61.80
	11	2462	17.62	57.81
802.11 n-HT20	1	2412	17.24	52.97
	7	2437	17.92	61.94
	11	2462	17.3	53.70
802.11 n-HT40	3	2422	17.72	59.16
	6	2437	17.88	61.38
	9	2452	17.79	60.12

Bluetooth

BT				
Mode	Channel Number	Frequency (MHz)	Conducted Power (dBm)	Output Power (mW)
GFSK(1Mbps)	0	2402	3.45	2.21
	39	2441	4.36	2.73
	78	2480	3.54	2.26
$\pi/4$ -QPSK(2Mbps)	0	2402	2.61	1.82
	39	2441	3.6	2.29
	78	2480	2.75	1.88
8DPSK(3Mbps)	0	2402	2.55	1.80
	39	2441	3.48	2.23
	78	2480	2.72	1.87

BLE

BLE				
Mode	Channel Number	Frequency (MHz)	Conducted Power (dBm)	Output Power (mW)
GFSK(1Mbps)	0	2402	1.07	1.28
	19	2440	2.13	1.63
	39	2480	1.16	1.31
GFSK(2Mbps)	0	2402	1.03	1.27
	19	2440	2.05	1.60
	39	2480	1.3	1.35

**WLAN (5.2Gband)**

5.2G WLAN				
Mode	Channel Number	Frequency (MHz)	Total Power (dBm)	Output Power (mW)
802.11a	36	5180	11.97	15.74
	40	5200	11.79	15.10
	48	5240	12.41	17.42
802.11 n-HT20	36	5180	13.02	20.04
	40	5200	12.27	16.87
	48	5240	12.7	18.62
802.11 n-HT40	38	5190	11.23	13.27
	46	5230	11.58	14.39
802.11ac-VHT20	36	5180	11.41	13.84
	40	5200	11.18	13.12
	48	5240	11.77	15.03
802.11ac-VHT40	38	5190	11.96	15.70
	46	5230	12.16	16.44
802.11ac-VHT80	42	5210	11.9	15.49

WLAN (5.3Gband)

5.3G WLAN				
Mode	Channel Number	Frequency (MHz)	Total Power (dBm)	Output Power (mW)
802.11a	52	5260	11.55	14.29
	60	5300	11.4	13.80
	64	5320	12.03	15.96
802.11 n-HT20	52	5260	13.08	20.32
	60	5300	13.25	21.13
	64	5320	13.51	22.44
802.11 n-HT40	54	5270	12.46	17.62
	62	5310	12.79	19.01
802.11ac-VHT20	52	5260	12.61	18.24
	60	5300	12.82	19.14
	64	5320	12.32	17.06
802.11ac-VHT40	54	5270	12.41	17.42
	62	5310	12.61	18.24
802.11ac-VHT80	58	5290	12.43	17.50

**WLAN (5.6Gband)**

5.6G WLAN				
Mode	Channel Number	Frequency (MHz)	Total Power (dBm)	Output Power (mW)
802.11a	100	5500	11.95	15.67
	116	5580	10.95	12.45
	140	5700	10.66	11.64
802.11 n-HT20	100	5500	13.93	24.72
	116	5580	12.75	18.84
	140	5700	12.47	17.66
802.11 n-HT40	102	5510	12.73	18.75
	110	5550	12.16	16.44
	134	5670	11.28	13.43
802.11ac-VHT20	100	5500	12.71	18.66
	116	5580	11.71	14.83
	140	5700	10.95	12.45
802.11ac-VHT40	102	5510	12.77	18.92
	110	5550	12.26	16.83
	134	5670	11.37	13.71
802.11ac-VHT80	106	5530	12.81	19.10
	122	5610	11.63	14.55

WLAN (5.8Gband)

5.8G WLAN				
Mode	Channel Number	Frequency (MHz)	Total Power (dBm)	Output Power (mW)
802.11a	149	5745	11.44	13.93
	157	5785	11.39	13.77
	165	5825	11.32	13.55
802.11 n-HT20	149	5745	13.23	21.04
	157	5785	13.24	21.09
	165	5825	13.15	20.65
802.11 n-HT40	151	5755	12.12	16.29
	159	5795	11.94	15.63
802.11ac-VHT20	149	5745	12.22	16.67
	157	5785	12.25	16.79
	165	5825	12.2	16.60
802.11ac-VHT40	151	5755	12.13	16.33
	159	5795	12.05	16.03
802.11ac-VHT80	155	5775	11.89	15.45

NFC:

NFC			
Mode	Frequency (MHz)	Average Power (dBm)	Output Power (mW)
MASK	13.65	-41.87	0.00

**LTE Conducted Power****General Note:**

1. Rohde & Schwarz CMW500 base station simulator was used to setup the connection with EUT; the frequency band, channel bandwidth, RB allocation configuration, modulation type are set in the base station simulator to configure EUT transmitting at maximum power and at different configurations which are requested to be reported to FCC, for conducted power measurement and SAR testing.
2. Per KDB 941225 D05, when a properly configured base station simulator is used for the SAR and power measurements, spectrum plots for each RB allocation and offset configuration is not required.
3. Per KDB 941225 D05, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
4. Per KDB 941225 D05, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
5. Per KDB 941225 D05, For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
6. Per KDB 941225 D05, 16QAM output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is ≤ 1.45 W/kg; Per KDB 941225 D05, 16QAM SAR testing is not required.
7. Per KDB 941225 D05, Smaller bandwidth output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is ≤ 1.45 W/kg; Per KDB 941225 D05, smaller bandwidth SAR testing is not required.



LTE Band 2 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	22.89	22.86	22.9
1.4	1	2		23.02	23.04	23
1.4	1	5		22.87	22.84	22.85
1.4	3	0		22.92	22.97	22.92
1.4	3	1		22.96	23.01	22.91
1.4	3	2		22.99	22.98	22.92
1.4	6	0		21.91	21.92	21.92
1.4	1	0	16-QAM	21.78	21.97	22.11
1.4	1	2		21.91	22.14	22.27
1.4	1	5		21.74	21.96	22.11
1.4	3	0		21.9	22.05	22.07
1.4	3	1		21.95	22.06	22.07
1.4	3	2		21.95	22.02	22.07
1.4	6	0		21.07	21.19	21
3	1	0	QPSK	22.82	22.95	22.87
3	1	7		23.22	23.24	23.13
3	1	14		22.82	23.04	22.88
3	8	0		21.9	21.94	21.88
3	8	4		21.9	21.98	21.92
3	8	7		21.85	21.94	21.86
3	15	0		21.84	21.94	21.88
3	1	0	16-QAM	21.86	22.28	22.07
3	1	7		22.13	22.54	22.27
3	1	14		21.86	22.24	22.08
3	8	0		20.96	20.95	20.99
3	8	4		21.01	20.97	21
3	8	7		20.96	20.96	20.97
3	15	0		20.78	21.05	20.83



LTE Band 2 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	22.77	22.86	22.88
5	1	12		23.1	23.26	23.29
5	1	24		22.75	22.81	22.9
5	12	0		21.88	21.94	21.83
5	12	6		21.92	22.04	21.92
5	12	11		21.79	21.96	21.85
5	25	0		21.89	21.99	21.87
5	1	0	16-QAM	22.08	22	21.91
5	1	12		22.46	22.39	22.35
5	1	24		22.07	22.01	21.95
5	12	0		20.85	21.08	20.97
5	12	6		20.96	21.13	21.09
5	12	11		20.8	21.01	20.96
5	25	0		20.92	21	20.9
10	1	0	QPSK	22.83	22.94	22.92
10	1	24		22.93	23.01	23
10	1	49		22.84	22.91	22.93
10	25	0		22.02	21.98	21.82
10	25	12		21.86	22	21.89
10	25	24		21.82	21.96	21.91
10	50	0		21.91	22.02	21.88
10	1	0	16-QAM	22.04	22.05	22.19
10	1	24		22.11	22.11	22.33
10	1	49		22.06	22	22.17
10	25	0		21.11	21.07	20.89
10	25	12		21.01	21.1	20.97
10	25	24		20.94	21.02	20.99
10	50	0		20.96	21.09	20.94



LTE Band 2 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	22.88	22.86	22.78
15	1	37		23.33	23.17	23.25
15	1	74		22.82	22.84	22.8
15	36	0		22.08	22.02	21.95
15	36	18		22	22.05	21.99
15	36	39		21.9	21.98	22
15	75	0		21.96	21.99	21.99
15	1	0	16-QAM	21.79	22.16	21.87
15	1	38		22.19	22.34	22.35
15	1	75		21.83	22.04	21.87
15	36	0		21.03	21.01	20.95
15	36	18		20.97	21.08	21.04
15	36	39		20.89	21	21.01
15	75	0		20.96	21	20.95
20	1	0	QPSK	22.67	22.75	22.61
20	1	49		23	23.14	22.99
20	1	99		22.72	22.73	22.7
20	50	0		22.1	21.88	22.02
20	50	24		21.95	22.03	21.99
20	50	49		21.95	21.85	22.06
20	100	0		22.04	21.83	22.04
20	1	0	16-QAM	21.68	21.83	21.79
20	1	49		22.01	22.16	22.21
20	1	99		21.79	21.77	21.88
20	50	0		21.13	21.01	21.05
20	50	24		21.02	21.15	21.08
20	50	49		21	20.91	21.13
20	100	0		21.1	20.89	21.1



LTE Band 4 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	22.81	22.8	22.85
1.4	1	2		22.96	23	22.96
1.4	1	5		22.83	22.81	22.82
1.4	3	0		22.88	22.93	22.89
1.4	3	1		22.86	22.96	22.88
1.4	3	2		22.94	22.96	22.87
1.4	6	0		21.81	21.9	21.85
1.4	1	0	16-QAM	21.71	21.91	22.13
1.4	1	2		21.85	22.09	22.25
1.4	1	5		21.69	21.94	22.1
1.4	3	0		21.85	22.01	22.03
1.4	3	1		21.9	22.06	22.06
1.4	3	2		21.9	22.02	22.04
1.4	6	0		20.98	21.15	20.96
3	1	0	QPSK	22.82	22.92	22.87
3	1	7		22.96	23.28	23.12
3	1	14		22.74	23	22.84
3	8	0		21.8	21.9	21.82
3	8	4		21.82	21.93	21.88
3	8	7		21.82	21.91	21.84
3	15	0		21.8	21.9	21.84
3	1	0	16-QAM	21.89	22.26	22.09
3	1	7		22.16	22.56	22.38
3	1	14		21.86	22.29	22.09
3	8	0		20.88	20.93	20.91
3	8	4		20.92	20.96	20.97
3	8	7		20.92	20.95	20.94
3	15	0		20.74	21.04	20.81



LTE Band 4 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	22.73	22.9	22.77
5	1	12		23.18	23.32	23.22
5	1	24		22.69	22.93	22.8
5	12	0		21.78	21.91	21.86
5	12	6		21.87	21.99	21.92
5	12	11		21.84	21.95	21.89
5	25	0		21.86	21.93	21.89
5	1	0	16-QAM	21.95	21.95	22.13
5	1	12		22.3	22.43	22.57
5	1	24		21.87	22	22.14
5	12	0		20.91	21.04	20.91
5	12	6		21.01	21.14	20.94
5	12	11		20.97	21.11	20.88
5	25	0		20.9	21	20.96
10	1	0	QPSK	22.83	22.84	22.8
10	1	24		22.96	23.03	22.92
10	1	49		22.81	22.9	22.82
10	25	0		21.77	21.95	21.92
10	25	12		21.78	21.95	21.87
10	25	24		21.84	22	21.89
10	50	0		21.8	21.95	21.92
10	1	0	16-QAM	22.08	22.1	21.94
10	1	24		22.23	22.3	22
10	1	49		22.1	22.14	21.88
10	25	0		20.84	21.06	20.98
10	25	12		20.86	21.09	20.96
10	25	24		20.89	21.06	20.95
10	50	0		20.87	21.06	20.97



LTE Band 4 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	22.68	22.85	22.78
15	1	37		22.99	23.33	23.1
15	1	74		22.79	22.87	22.75
15	36	0		21.77	21.94	21.86
15	36	18		21.88	21.98	21.93
15	36	39		21.85	21.94	21.87
15	75	0		21.87	21.98	21.89
15	1	0	16-QAM	21.83	21.8	22.02
15	1	38		22.1	22.33	22.37
15	1	75		21.82	21.88	21.98
15	36	0		20.81	20.96	20.89
15	36	18		20.93	20.98	20.94
15	36	39		20.88	20.96	20.87
15	75	0		20.88	21	20.91
20	1	0	QPSK	22.52	22.65	22.66
20	1	49		22.92	23.1	22.96
20	1	99		22.65	22.72	22.62
20	50	0		21.7	21.92	21.87
20	50	24		21.84	21.97	21.87
20	50	49		21.85	21.92	21.83
20	100	0		21.8	21.91	21.87
20	1	0	16-QAM	21.6	21.66	21.85
20	1	49		21.99	22.14	22.19
20	1	99		21.74	21.7	21.76
20	50	0		20.76	20.97	20.93
20	50	24		20.89	21.08	20.97
20	50	49		20.9	20.99	20.94
20	100	0		20.9	21.01	20.91



LTE Band 5 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	23.56	23.42	23.26
1.4	1	2		23.74	23.53	23.42
1.4	1	5		23.6	23.38	23.22
1.4	3	0		23.56	23.47	23.32
1.4	3	1		23.63	23.52	23.31
1.4	3	2		23.62	23.51	23.27
1.4	6	0		22.57	22.5	22.34
1.4	1	0	16-QAM	22.47	22.5	22.52
1.4	1	2		22.6	22.59	22.64
1.4	1	5		22.52	22.46	22.52
1.4	3	0		22.55	22.52	22.47
1.4	3	1		22.67	22.57	22.46
1.4	3	2		22.66	22.5	22.4
1.4	6	0		21.72	21.67	21.4
3	1	0	QPSK	23.52	23.51	23.34
3	1	7		23.93	23.86	23.46
3	1	14		23.57	23.51	23.23
3	8	0		22.59	22.47	22.29
3	8	4		22.61	22.51	22.34
3	8	7		22.57	22.44	22.33
3	15	0		22.56	22.43	22.3
3	1	0	16-QAM	22.6	22.81	22.55
3	1	7		22.97	23.07	22.83
3	1	14		22.65	22.73	22.4
3	8	0		21.64	21.43	21.37
3	8	4		21.68	21.46	21.41
3	8	7		21.67	21.43	21.4
3	15	0		21.45	21.54	21.24



LTE Band 5 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	23.45	23.53	23.24
5	1	12		23.91	23.75	23.61
5	1	24		23.47	23.42	23.16
5	12	0		22.6	22.36	22.41
5	12	6		22.66	22.52	22.39
5	12	11		22.53	22.5	22.4
5	25	0		22.57	22.52	22.43
5	1	0	16-QAM	22.67	22.56	22.6
5	1	12		23.07	22.79	23.13
5	1	24		22.63	22.45	22.54
5	12	0		21.72	21.51	21.41
5	12	6		21.75	21.6	21.38
5	12	11		21.61	21.58	21.4
5	25	0		21.59	21.51	21.47
10	1	0	QPSK	23.53	23.57	23.37
10	1	24		23.66	23.6	23.43
10	1	49		23.55	23.39	23.25
10	25	0		22.74	22.53	22.56
10	25	12		22.6	22.5	22.42
10	25	24		22.7	22.63	22.45
10	50	0		22.69	22.56	22.54
10	1	0	16-QAM	22.63	22.83	22.63
10	1	24		22.73	22.9	22.71
10	1	49		22.57	22.73	22.48
10	25	0		21.79	21.52	21.66
10	25	12		21.68	21.5	21.49
10	25	24		21.64	21.61	21.51
10	50	0		21.71	21.56	21.55



LTE Band 7 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	22.65	22.82	22.65
5	1	12		23.03	23.11	23.05
5	1	24		22.59	22.79	22.64
5	12	0		21.64	21.88	21.64
5	12	6		21.77	21.91	21.65
5	12	11		21.71	21.85	21.63
5	25	0		21.68	21.89	21.63
5	1	0	16-QAM	21.99	21.92	21.65
5	1	12		22.33	22.25	22.16
5	1	24		21.99	21.88	21.69
5	12	0		20.63	20.94	20.67
5	12	6		20.74	21.02	20.75
5	12	11		20.71	20.94	20.74
5	25	0		20.78	20.81	20.62
10	1	0	QPSK	22.7	22.91	22.67
10	1	24		22.74	23.09	22.77
10	1	49		22.63	22.93	22.69
10	25	0		21.65	21.91	21.76
10	25	12		21.66	21.89	21.67
10	25	24		21.74	21.96	21.68
10	50	0		21.68	21.93	21.69
10	1	0	16-QAM	21.7	22.1	21.81
10	1	24		21.77	22.27	21.91
10	1	49		21.61	22.14	21.84
10	25	0		20.67	20.91	20.8
10	25	12		20.75	20.89	20.79
10	25	24		20.81	20.99	20.78
10	50	0		20.77	20.97	20.7



LTE Band 7 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	22.58	22.8	22.64
15	1	37		22.86	23.13	22.98
15	1	74		22.51	22.75	22.67
15	36	0		21.65	21.99	21.76
15	36	18		21.7	22.03	21.75
15	36	39		21.75	22.02	21.79
15	75	0		21.67	22.02	21.77
15	1	0	16-QAM	21.77	21.77	21.58
15	1	37		22.08	22.12	21.85
15	1	74		21.62	21.81	21.57
15	36	0		20.61	20.93	20.67
15	36	18		20.67	20.97	20.73
15	36	39		20.69	20.96	20.71
15	75	0		20.65	20.95	20.72
20	1	0	QPSK	22.39	22.64	22.47
20	1	49		22.67	23.01	22.9
20	1	99		22.39	22.65	22.54
20	50	0		21.47	21.84	21.65
20	50	24		21.6	21.91	21.73
20	50	49		21.55	21.92	21.7
20	100	0		21.55	21.88	21.69
20	1	0	16-QAM	21.55	21.6	21.51
20	1	49		21.76	21.95	21.87
20	1	99		21.47	21.69	21.55
20	50	0		20.45	20.88	20.7
20	50	24		20.64	20.97	20.78
20	50	49		20.59	20.96	20.72
20	100	0		20.59	20.91	20.68



LTE Band 12 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	24.14	24	23.89
1.4	1	2		24.25	24.16	24.04
1.4	1	5		24.14	24.03	23.87
1.4	3	0		24.17	24.06	23.99
1.4	3	1		24.14	24.04	24
1.4	3	2		24.21	24.07	23.98
1.4	6	0		23.13	23.02	22.98
1.4	1	0	16-QAM	23.35	22.88	22.96
1.4	1	2		23.5	23.03	23.07
1.4	1	5		23.39	22.94	22.9
1.4	3	0		23.29	23.06	23
1.4	3	1		23.28	23.1	23.03
1.4	3	2		23.32	23.11	22.96
1.4	6	0		22.25	22.15	22.17
3	1	0	QPSK	24.08	23.97	23.91
3	1	7		24.3	24.25	24.27
3	1	14		24.04	23.96	23.99
3	8	0		23.07	23.01	22.98
3	8	4		23.1	23.04	22.98
3	8	7		23.09	23.02	22.93
3	15	0		23.09	22.99	22.91
3	1	0	16-QAM	23.31	23.02	23.26
3	1	7		23.64	23.29	23.55
3	1	14		23.33	23.04	23.19
3	8	0		22.17	22.17	21.94
3	8	4		22.25	22.14	21.96
3	8	7		22.26	22.09	21.9
3	15	0		22.1	21.92	22.04



LTE Band 12 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	23.98	23.9	23.9
5	1	12		24.35	24.17	24.4
5	1	24		23.9	23.92	23.92
5	12	0		22.97	23.08	22.87
5	12	6		23.11	23.09	23
5	12	11		23.09	23.02	22.82
5	25	0		23.05	23.06	22.93
5	1	0	16-QAM	23.31	23.06	22.99
5	1	12		23.62	23.44	23.39
5	1	24		23.27	23.09	23
5	12	0		22.05	22.2	22.05
5	12	6		22.17	22.16	22.1
5	12	11		22.15	22.12	21.92
5	25	0		22.15	22.06	21.91
10	1	0	QPSK	24.01	24.05	23.93
10	1	24		24.11	24.11	24.08
10	1	49		23.94	24.08	23.94
10	25	0		23	23.18	23.06
10	25	12		23.01	23.02	23.03
10	25	24		22.9	23.14	22.96
10	50	0		22.95	23.18	23.07
10	1	0	16-QAM	23.12	23.3	23.15
10	1	24		23.15	23.38	23.32
10	1	49		23.04	23.28	23.2
10	25	0		22.1	22.29	22.16
10	25	12		22.14	22.1	22.14
10	25	24		22.03	22.14	22.06
10	50	0		22.06	22.22	22.05



LTE Band 13 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	23.42	23.43	23.57
5	1	12		23.84	23.61	23.89
5	1	24		23.43	23.47	23.55
5	12	0		22.61	22.65	22.45
5	12	6		22.59	22.63	22.6
5	12	11		22.35	22.56	22.65
5	25	0		22.51	22.64	22.65
5	1	0	16-QAM	22.71	22.64	22.56
5	1	12		23.23	22.9	22.9
5	1	24		22.76	22.54	22.6
5	12	0		21.6	21.7	21.54
5	12	6		21.56	21.67	21.65
5	12	11		21.4	21.68	21.75
5	25	0		21.57	21.62	21.64
10	1	0	QPSK	/	23.54	/
10	1	24		/	23.59	/
10	1	49		/	23.56	/
10	25	0		/	22.81	/
10	25	12		/	22.55	/
10	25	24		/	22.84	/
10	50	0		/	22.78	/
10	1	0	16-QAM	/	22.73	/
10	1	24		/	22.79	/
10	1	49		/	22.72	/
10	25	0		/	21.91	/
10	25	12		/	21.63	/
10	25	24		/	21.86	/
10	50	0		/	21.86	/



LTE Band 17 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	23.97	23.91	24
5	1	12		24.34	24.35	24.34
5	1	24		23.99	23.91	23.96
5	12	0		23.18	23.04	22.93
5	12	6		23.14	23.13	23.04
5	12	11		23.03	23.12	22.88
5	25	0		23.06	23.14	22.91
5	1	0	16-QAM	23.33	23.16	23.04
5	1	12		23.72	23.53	23.44
5	1	24		23.32	23.09	23.07
5	12	0		22.21	22.19	22.02
5	12	6		22.1	22.22	22.15
5	12	11		21.98	22.19	21.96
5	25	0		22.14	22.09	21.94
10	1	0	QPSK	24.03	24.02	23.99
10	1	24		24.15	24.12	24.11
10	1	49		24.06	24	23.99
10	25	0		23.22	23.17	23.09
10	25	12		23.06	23.07	23.06
10	25	24		23.25	23.17	23.04
10	50	0		23.23	23.12	23.08
10	1	0	16-QAM	23.33	23.21	23.08
10	1	24		23.43	23.35	23.19
10	1	49		23.29	23.21	23.04
10	25	0		22.21	22.28	22.12
10	25	12		22.07	22.15	22.08
10	25	24		22.24	22.22	22.07
10	50	0		22.24	22.18	22.12



LTE Band 25 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	22.98	22.99	22.97
1.4	1	2		23.09	23.17	23.08
1.4	1	5		22.98	23.02	22.96
1.4	3	0		23.02	23.07	22.96
1.4	3	1		22.98	23.09	23.01
1.4	3	2		23.02	23.09	22.94
1.4	6	0		22.05	22.1	22.03
1.4	1	0	16-QAM	21.81	22.05	22.19
1.4	1	2		21.95	22.18	22.3
1.4	1	5		21.8	22.02	22.16
1.4	3	0		21.96	22.13	22.08
1.4	3	1		22.01	22.15	22.07
1.4	3	2		21.98	22.05	22.11
1.4	6	0		21.12	21.3	21.07
3	1	0	QPSK	22.99	23.11	23.04
3	1	7		23.26	23.36	23.34
3	1	14		23	23.15	22.98
3	8	0		22.03	22.09	22.05
3	8	4		22.04	22.12	22.05
3	8	7		22	22.08	21.98
3	15	0		21.97	22.06	22.01
3	1	0	16-QAM	21.94	22.34	22.15
3	1	7		22.16	22.6	22.42
3	1	14		21.94	22.31	22.15
3	8	0		21.08	21.09	21.13
3	8	4		21.08	21.1	21.1
3	8	7		21.02	21.09	21.12
3	15	0		20.88	21.17	20.95



LTE Band 25 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	22.88	23.01	23
5	1	12		23.2	23.43	23.47
5	1	24		22.88	22.98	22.97
5	12	0		21.98	22.07	22.15
5	12	6		22.04	22.15	22.09
5	12	11		21.89	22.09	21.92
5	25	0		21.95	22.12	22.04
5	1	0	16-QAM	22.18	22.13	22.04
5	1	12		22.6	22.56	22.46
5	1	24		22.18	22.1	22.07
5	12	0		20.94	21.21	21.22
5	12	6		21.06	21.24	21.2
5	12	11		20.92	21.2	21.08
5	25	0		20.99	21.12	21.07
10	1	0	QPSK	22.98	23.04	22.93
10	1	24		23.13	23.17	23.14
10	1	49		23.01	22.99	23.03
10	25	0		22.07	22.1	22.06
10	25	12		21.99	22.12	22.02
10	25	24		21.97	22.07	21.84
10	50	0		22	22.1	21.94
10	1	0	16-QAM	22.15	22.25	21.94
10	1	24		22.29	22.36	22.11
10	1	49		22.19	22.2	22.01
10	25	0		21.09	21.23	21.11
10	25	12		21.04	21.19	21.06
10	25	24		20.96	21.16	20.88
10	50	0		21.06	21.17	21.01



LTE Band 25 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	22.96	23	23
15	1	37		23.2	23.46	23.27
15	1	74		22.95	22.95	23.04
15	36	0		22.19	22.18	21.99
15	36	18		22.16	22.22	22.18
15	36	39		22.08	22.12	22.01
15	75	0		22.13	22.11	22.01
15	1	0	16-QAM	22.06	22.04	21.93
15	1	38		22.34	22.33	22.32
15	1	75		22.15	22	21.95
15	36	0		21.15	21.17	20.95
15	36	18		21.08	21.22	21.08
15	36	39		21.07	21.07	20.94
15	75	0		21.13	21.1	20.97
20	1	0	QPSK	22.75	22.88	22.78
20	1	49		23.14	23.13	23.23
20	1	99		22.84	22.8	22.89
20	50	0		22.19	22.03	21.9
20	50	24		22.08	22.16	22.08
20	50	49		22.09	21.92	21.8
20	100	0		22.14	21.93	21.84
20	1	0	16-QAM	21.82	21.89	21.82
20	1	49		22.24	22.22	22.21
20	1	99		22	21.81	21.89
20	50	0		21.2	21.12	21
20	50	24		21.12	21.19	21.15
20	50	49		21.14	20.96	20.85
20	100	0		21.19	21.01	20.91



LTE Band 26 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	23.66	23.45	23.38
1.4	1	2		23.81	23.63	23.5
1.4	1	5		23.66	23.44	23.35
1.4	3	0		23.69	23.58	23.43
1.4	3	1		23.72	23.55	23.41
1.4	3	2		23.7	23.56	23.38
1.4	6	0		22.67	22.56	22.4
1.4	1	0	16-QAM	22.62	22.6	22.6
1.4	1	2		22.7	22.72	22.76
1.4	1	5		22.57	22.54	22.66
1.4	3	0		22.72	22.65	22.57
1.4	3	1		22.75	22.65	22.53
1.4	3	2		22.76	22.61	22.53
1.4	6	0		21.8	21.76	21.49
3	1	0	QPSK	23.65	23.61	23.38
3	1	7		24.09	23.7	23.62
3	1	14		23.79	23.51	23.38
3	8	0		22.68	22.56	22.45
3	8	4		22.69	22.62	22.47
3	8	7		22.67	22.6	22.5
3	15	0		22.63	22.55	22.43
3	1	0	16-QAM	23.02	22.83	22.48
3	1	7		23.42	23.09	22.77
3	1	14		23.02	22.76	22.43
3	8	0		21.64	21.61	21.52
3	8	4		21.67	21.69	21.52
3	8	7		21.69	21.65	21.54
3	15	0		21.76	21.49	21.31



LTE Band 26 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	23.7	23.51	23.29
5	1	12		24.04	23.77	23.78
5	1	24		23.72	23.43	23.3
5	12	0		22.67	22.59	22.52
5	12	6		22.75	22.63	22.51
5	12	11		22.65	22.62	22.56
5	25	0		22.72	22.62	22.57
5	1	0	16-QAM	22.73	22.9	22.56
5	1	12		23.18	23.2	22.79
5	1	24		22.79	22.83	22.49
5	12	0		21.85	21.49	21.58
5	12	6		21.88	21.62	21.6
5	12	11		21.83	21.63	21.62
5	25	0		21.75	21.65	21.55
10	1	0	QPSK	23.68	23.68	23.4
10	1	24		23.85	23.68	23.54
10	1	49		23.62	23.48	23.38
10	25	0		22.84	22.67	22.68
10	25	12		22.74	22.63	22.49
10	25	24		22.77	22.72	22.51
10	50	0		22.82	22.65	22.62
10	1	0	16-QAM	22.99	22.9	22.55
10	1	24		23.15	22.92	22.59
10	1	49		22.88	22.76	22.46
10	25	0		21.87	21.71	21.73
10	25	12		21.74	21.67	21.55
10	25	24		21.77	21.81	21.55
10	50	0		21.87	21.69	21.69



LTE Band 26 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	23.62	23.68	23.52
15	1	37		23.9	23.8	23.74
15	1	74		23.45	23.44	23.35
15	36	0		22.8	22.62	22.47
15	36	18		22.75	22.64	22.54
15	36	39		22.8	22.58	22.45
15	75	0		22.85	22.67	22.47
15	1	0	16-QAM	22.67	22.72	22.76
15	1	38		22.99	22.82	22.87
15	1	75		22.55	22.46	22.53
15	36	0		21.82	21.6	21.43
15	36	18		21.75	21.55	21.52
15	36	39		21.74	21.52	21.42
15	75	0		21.71	21.63	21.48



LTE Band 26 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	23.65	23.68	23.59
1.4	1	2		23.78	23.81	23.76
1.4	1	5		23.63	23.65	23.53
1.4	3	0		23.67	23.71	23.66
1.4	3	1		23.7	23.72	23.68
1.4	3	2		23.64	23.71	23.69
1.4	6	0		22.65	22.69	22.66
1.4	1	0	16-QAM	22.97	22.56	22.73
1.4	1	2		23.05	22.68	22.78
1.4	1	5		22.92	22.56	22.68
1.4	3	0		22.83	22.7	22.75
1.4	3	1		22.82	22.74	22.75
1.4	3	2		22.82	22.74	22.74
1.4	6	0		21.79	21.81	21.88
3	1	0	QPSK	23.73	23.7	23.65
3	1	7		23.98	24.04	24.01
3	1	14		23.77	23.64	23.68
3	8	0		22.72	22.66	22.67
3	8	4		22.67	22.68	22.67
3	8	7		22.66	22.68	22.69
3	15	0		22.69	22.64	22.64
3	1	0	16-QAM	23.02	22.88	22.75
3	1	7		23.28	23.12	23.05
3	1	14		22.91	22.91	22.75
3	8	0		21.69	21.69	21.72
3	8	4		21.67	21.7	21.77
3	8	7		21.65	21.77	21.74
3	15	0		21.74	21.61	21.58



LTE Band 26 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	23.66	23.55	23.71
5	1	12		23.99	24	24.01
5	1	24		23.59	23.57	23.69
5	12	0		22.77	22.61	22.64
5	12	6		22.71	22.72	22.72
5	12	11		22.76	22.71	22.63
5	25	0		22.72	22.74	22.66
5	1	0	16-QAM	22.97	22.72	22.77
5	1	12		23.38	23.05	23.14
5	1	24		22.96	22.77	22.75
5	12	0		21.71	21.63	21.72
5	12	6		21.71	21.83	21.83
5	12	11		21.68	21.78	21.76
5	25	0		21.77	21.7	21.69
10	1	0	QPSK	/	23.65	/
10	1	24		/	23.79	/
10	1	49		/	23.61	/
10	25	0		/	22.65	/
10	25	12		/	22.73	/
10	25	24		/	22.83	/
10	50	0		/	22.77	/
10	1	0	16-QAM	/	22.87	/
10	1	24		/	22.99	/
10	1	49		/	22.88	/
10	25	0		/	21.77	/
10	25	12		/	21.77	/
10	25	24		/	21.9	/
10	50	0		/	21.77	/



LTE Band 41 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	22.91	22.74	22.65
5	1	12		23.21	23.03	22.93
5	1	24		22.97	22.7	22.6
5	12	0		21.88	21.77	21.69
5	12	6		21.99	21.84	21.67
5	12	11		21.93	21.77	21.64
5	25	0		21.92	21.78	21.68
5	1	0	16-QAM	22.16	21.71	21.62
5	1	12		22.44	21.99	21.98
5	1	24		22.2	21.67	21.69
5	12	0		20.86	20.86	20.72
5	12	6		20.95	20.92	20.75
5	12	11		20.91	20.86	20.7
5	25	0		20.92	20.71	20.7
10	1	0	QPSK	22.92	22.77	22.55
10	1	24		23.11	22.92	22.79
10	1	49		22.93	22.77	22.58
10	25	0		21.89	21.82	21.75
10	25	12		21.93	21.82	21.68
10	25	24		21.95	21.85	21.63
10	50	0		21.91	21.85	21.69
10	1	0	16-QAM	22.19	22.1	21.52
10	1	24		22.37	22.26	21.74
10	1	49		22.22	22.08	21.53
10	25	0		20.94	20.89	20.75
10	25	12		20.92	20.9	20.68
10	25	24		20.98	20.93	20.66
10	50	0		20.94	20.83	20.67



LTE Band 41 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	22.91	22.71	22.45
15	1	37		23.27	22.98	22.76
15	1	74		22.94	22.59	22.44
15	36	0		21.99	21.9	21.73
15	36	18		22.06	21.91	21.77
15	36	39		22.05	21.91	21.64
15	75	0		22.04	21.93	21.73
15	1	0	16-QAM	21.82	22.06	21.45
15	1	37		22.18	22.32	21.76
15	1	74		21.88	21.99	21.45
15	36	0		20.91	20.87	20.67
15	36	18		20.99	20.84	20.73
15	36	39		20.99	20.85	20.65
15	75	0		21	20.87	20.64
20	1	0	QPSK	22.71	22.58	22.52
20	1	49		23.15	22.98	22.92
20	1	99		22.75	22.51	22.54
20	50	0		21.79	21.67	21.59
20	50	24		21.93	21.83	21.64
20	50	49		21.92	21.79	21.56
20	100	0		21.88	21.77	21.6
20	1	0	16-QAM	21.65	21.57	21.39
20	1	49		22.07	22.02	21.83
20	1	99		21.7	21.61	21.44
20	50	0		20.85	20.68	20.62
20	50	24		20.98	20.86	20.67
20	50	49		20.97	20.8	20.57
20	100	0		20.86	20.75	20.52



LTE Band 66 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	22.91	22.85	22.97
1.4	1	2		23.08	23.02	23.09
1.4	1	5		22.91	22.85	22.98
1.4	3	0		23	22.98	23.03
1.4	3	1		22.98	22.99	23.07
1.4	3	2		22.98	23.01	23.05
1.4	6	0		21.9	21.93	22
1.4	1	0	16-QAM	21.84	21.96	22.22
1.4	1	2		21.95	22.15	22.37
1.4	1	5		21.81	21.95	22.23
1.4	3	0		21.97	22.04	22.16
1.4	3	1		22.01	22.11	22.16
1.4	3	2		21.98	22.03	22.17
1.4	6	0		21.11	21.19	21.13
3	1	0	QPSK	22.91	22.98	23.03
3	1	7		23.19	23.23	23.28
3	1	14		22.98	22.86	23.01
3	8	0		21.91	21.94	22.07
3	8	4		21.93	21.98	22.05
3	8	7		21.92	21.97	22.01
3	15	0		21.91	21.97	22.02
3	1	0	16-QAM	22.23	22.21	22.13
3	1	7		22.39	22.49	22.34
3	1	14		22.26	22.22	22.02
3	8	0		20.93	21.02	21.17
3	8	4		20.96	21.11	21.14
3	8	7		20.94	21.06	21.12
3	15	0		21.07	20.92	20.98



LTE Band 66 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	22.87	22.88	23.05
5	1	12		23.26	23.21	23.56
5	1	24		22.86	22.84	23.01
5	12	0		21.95	22.01	22.1
5	12	6		21.98	22.03	22.12
5	12	11		22.01	22.01	22.02
5	25	0		21.97	21.98	22.09
5	1	0	16-QAM	22.25	22.08	22.09
5	1	12		22.55	22.34	22.64
5	1	24		22.21	22.05	22.09
5	12	0		20.95	21.08	21.2
5	12	6		21.01	21.17	21.26
5	12	11		20.97	21.11	21.18
5	25	0		21.04	20.99	21.15
10	1	0	QPSK	22.86	22.93	23.04
10	1	24		23.02	23.06	23.23
10	1	49		22.83	22.92	23.03
10	25	0		21.92	21.99	22.09
10	25	12		21.95	21.98	22.09
10	25	24		22	22.06	22.11
10	50	0		21.95	22.06	22.13
10	1	0	16-QAM	22.1	22.03	22.31
10	1	24		22.28	22.16	22.47
10	1	49		22.12	21.99	22.27
10	25	0		21.04	21.08	21.19
10	25	12		21.1	21.11	21.14
10	25	24		21.1	21.11	21.13
10	50	0		21.04	21.1	21.18



LTE Band 66 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	22.88	22.85	22.88
15	1	37		23.29	23.21	23.16
15	1	74		22.9	22.84	22.92
15	36	0		21.84	21.98	22.12
15	36	18		21.95	22.03	22.17
15	36	39		21.99	22.04	22.13
15	75	0		21.96	22.02	22.16
15	1	0	16-QAM	21.92	22.18	21.97
15	1	38		22.19	22.4	22.42
15	1	75		21.94	22.07	21.99
15	36	0		20.86	21.03	21.11
15	36	18		20.96	21.08	21.16
15	36	39		20.99	21.03	21.14
15	75	0		21.03	21.05	21.14
20	1	0	QPSK	22.64	22.75	22.68
20	1	49		22.97	23.03	23.2
20	1	99		22.79	22.67	22.82
20	50	0		21.84	22	22.01
20	50	24		21.95	22	22.05
20	50	49		21.91	21.96	22.03
20	100	0		21.9	21.99	21.99
20	1	0	16-QAM	21.82	21.87	21.72
20	1	49		22.17	22.13	22.23
20	1	99		21.96	21.75	21.83
20	50	0		20.91	21.03	21.07
20	50	24		21.01	21.13	21.17
20	50	49		21	20.99	21.13
20	100	0		20.93	21.02	21.07



LTE Band 71 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	24.05	23.98	24.16
5	1	12		24.44	24.39	24.47
5	1	24		24.04	24.04	24.09
5	12	0		22.93	23.12	23.17
5	12	6		23.12	23.16	23.19
5	12	11		23.05	23.09	23.27
5	25	0		22.98	23.1	23.25
5	1	0	16-QAM	23.28	23.1	23.23
5	1	12		23.57	23.47	23.63
5	1	24		23.34	23.2	23.17
5	12	0		21.92	22.23	22.34
5	12	6		22.13	22.26	22.35
5	12	11		22.07	22.15	22.44
5	25	0		22.07	22.14	22.28
10	1	0	QPSK	24.19	24	24.19
10	1	24		24.21	24.19	24.33
10	1	49		24.11	24.17	24.21
10	25	0		23.07	23.17	23.25
10	25	12		23.1	23.12	23.24
10	25	24		23.19	23.11	23.26
10	50	0		23.07	23.12	23.23
10	1	0	16-QAM	23.2	23.05	23.46
10	1	24		23.39	23.21	23.56
10	1	49		23.28	23.2	23.4
10	25	0		22.2	22.23	22.34
10	25	12		22.24	22.23	22.27
10	25	24		22.29	22.16	22.28
10	50	0		22.15	22.19	22.32




LTE Band 71 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	24.2	23.96	24.05
15	1	37		24.48	24.4	24.39
15	1	74		24.11	24.22	24.1
15	36	0		23.24	23.15	23.34
15	36	18		23.23	23.24	23.37
15	36	39		23.31	23.18	23.32
15	75	0		23.3	23.17	23.37
15	1	0	16-QAM	22.86	23.19	23.1
15	1	37		23.37	23.52	23.48
15	1	74		23.05	23.37	23.1
15	36	0		22.22	22.11	22.27
15	36	18		22.17	22.24	22.38
15	36	39		22.27	22.2	22.38
15	75	0		22.33	22.2	22.36
20	1	0	QPSK	23.88	23.89	23.79
20	1	49		24.21	24.25	24.32
20	1	99		23.98	24.03	23.97
20	50	0		23.12	22.96	23.34
20	50	24		23.13	23.16	23.25
20	50	49		23.12	23.09	23.25
20	100	0		23.09	22.99	23.27
20	1	0	16-QAM	22.78	22.87	22.94
20	1	49		23.23	23.26	23.46
20	1	99		22.96	23.09	23.08
20	50	0		22.18	22.04	22.45
20	50	24		22.19	22.28	22.35
20	50	49		22.15	22.14	22.35
20	100	0		22.17	22.08	22.36


11. EUT and Test Setup Photo

11.1 EUT Photo


Front side




Back side




Top side




Bottom side



Left side



Right side



11.2 Setup Photo

Body Front side(separation distance is 0mm)




Body Back side(separation distance is 0mm)



Body Left side(separation distance is 0mm)




Body Right side(separation distance is 0mm)



Body Bottom side(separation distance is 0mm)




Body Top side(separation distance is 0mm)





Liquid depth (15 cm)





12. SAR Result Summary

12.1 Body-worn SAR

Band	BW (MHz)	Mod.	RB Size	RB offset	Test Position	Freq.	Result 1g (W/Kg)	Power Drift (%)	Max. Turn-up Power (dBm)	Meas. Output Power (dBm)	Scaling Factor	Scaled SAR (W/Kg)	Meas. No.
GSM850	N/A	GPRS (GMSK, 2-Slot)	N/A	N/A	Front Side	848.8	0.046	3.12	32.00	31.96	1.009	0.046	/
					Back Side	848.8	0.303	1.32	32.00	31.96	1.009	0.306	1
					Left Side	848.8	0.237	2.30	32.00	31.96	1.009	0.239	/
					Right Side	848.8	0.012	1.12	32.00	31.96	1.009	0.012	/
					Top Side	848.8	0.010	-0.89	32.00	31.96	1.009	0.010	/
					Bottom Side	848.8	0.218	-0.89	32.00	31.96	1.009	0.220	/
GSM1900	N/A	GPRS Data-4 Slot	N/A	N/A	Front Side	1850.2	0.0501	-1.38	29.50	29.12	1.091	0.055	/
					Back Side	1850.2	0.474	3.87	29.50	29.12	1.091	0.517	2
					Left Side	1850.2	0.309	-3.79	29.50	29.12	1.091	0.337	/
					Right Side	1850.2	0.028	0.40	29.50	29.12	1.091	0.031	/
					Top Side	1850.2	0.015	-3.90	29.50	29.12	1.091	0.016	/
					Bottom Side	1850.2	0.251	-3.75	29.50	29.12	1.091	0.274	/
WCDMA Band II	N/A	RMC	N/A	N/A	Front Side	1880	0.667	1.32	24.00	23.80	1.047	0.698	/
					Back Side	1852.4	0.933	1.19	24.00	23.75	1.059	0.988	/
					Back Side	1880	1.13	0.72	24.00	23.80	1.047	1.183	3
					Back Side	1907.6	1.02	1.39	24.00	23.78	1.052	1.073	/
					Left Side	1880	0.719	3.90	24.00	23.80	1.047	0.753	/
					Bottom Side	1880	0.725	0.51	24.00	23.80	1.047	0.759	/
WCDMA Band IV	N/A	RMC	N/A	N/A	Front Side	1740	0.519	2.77	24.00	23.70	1.072	0.556	/
					Back Side	1712.6	0.687	2.01	24.00	23.64	1.086	0.746	/
					Back Side	1740	0.77	3.63	24.00	23.70	1.072	0.825	4
					Back Side	1752.4	0.725	1.34	24.00	23.68	1.076	0.780	/
					Left Side	1740	0.556	-3.78	24.00	23.70	1.072	0.596	/
					Bottom Side	1740	0.522	-3.05	24.00	23.70	1.072	0.559	/
WCDMA Band V	N/A	RMC	N/A	N/A	Front Side	826.4	0.381	0.42	24.50	24.08	1.102	0.420	/
					Back Side	826.4	0.423	-2.59	24.50	24.08	1.102	0.466	5
					Left Side	826.4	0.404	0.95	24.50	24.08	1.102	0.445	/
					Bottom Side	826.4	0.417	-2.45	24.50	24.08	1.102	0.459	/
LTE Band 2	20M	QPSK	1	49	Front side	1880	0.427	-2.52	23.5	23.14	1.086	0.464	/
			50	0	Front side	1860	0.404	-2.84	22.5	22.1	1.096	0.443	/



			1	49	Back Side	1880	0.602	-1.51	23.5	23.14	1.086	0.654	6
			50	0	Back Side	1860	0.551	-1.95	22.5	22.1	1.096	0.604	/
			1	49	Left Side	1880	0.416	-2.57	23.5	23.14	1.086	0.452	/
			50	0	Left Side	1860	0.397	1.94	22.5	22.1	1.096	0.435	/
			1	49	Bottom Side	1880	0.378	3.72	23.5	23.14	1.086	0.411	/
			50	0	Bottom Side	1860	0.351	-1.42	22.5	22.1	1.096	0.385	/
LTE Band 4	20M	QPSK	1	49	Front side	1732.5	0.667	-3.06	23.5	23.1	1.096	0.731	/
			50	24	Front side	1732.5	0.602	1.60	22	21.97	1.007	0.606	/
			1	49	Back Side	1720	0.813	-2.31	23	22.92	1.019	0.828	/
			1	49	Back Side	1732.5	0.859	-3.44	23.5	23.1	1.096	0.942	7
			1	49	Back Side	1745	0.848	-1.32	23	22.96	1.009	0.856	/
			50	24	Back Side	1732.5	0.751	2.16	22	21.97	1.007	0.756	/
			1	49	Left Side	1732.5	0.727	2.87	23.5	23.1	1.096	0.797	/
			50	24	Left Side	1732.5	0.704	-3.79	22	21.97	1.007	0.709	/
			1	49	Bottom Side	1732.5	0.719	-1.52	23.5	23.1	1.096	0.788	/
			50	24	Bottom Side	1732.5	0.688	0.64	22	21.97	1.007	0.693	/
LTE Band 5	10M	QPSK	1	24	Front side	829	0.712	-3.16	24	23.66	1.081	0.770	/
			25	0	Front side	829	0.688	1.32	23	22.74	1.062	0.730	/
			1	24	Back Side	829	1.040	-3.16	24	23.66	1.081	1.125	8
			1	24	Back Side	836.5	0.917	-2.22	24	23.6	1.096	1.005	/
			1	24	Back Side	844	0.935	3.80	23.5	23.43	1.016	0.950	/
			25	0	Back Side	829	0.743	3.30	23	22.74	1.062	0.789	/
			1	24	Left Side	829	0.692	2.48	24	23.66	1.081	0.748	/
			25	0	Left Side	829	0.642	1.20	23	22.74	1.062	0.682	/
			1	24	Bottom Side	829	0.673	-1.85	24	23.66	1.081	0.728	/
			25	0	Bottom Side	829	0.651	1.63	23	22.74	1.062	0.691	/
LTE Band 7	10M	QPSK	1	49	Front side	2535	0.712	1.21	23.5	23.01	1.119	0.797	/
			50	49	Front side	2535	0.693	2.22	22	21.92	1.019	0.706	/
			1	49	Back Side	2510	0.952	0.89	23	22.67	1.079	1.027	/
			1	49	Back Side	2535	1.010	0.89	23.5	23.01	1.119	1.131	9
			1	49	Back Side	2560	0.961	0.89	23	22.9	1.023	0.983	/
			50	49	Back Side	2535	0.761	1.21	22	21.92	1.019	0.775	/
			1	49	Left Side	2535	0.686	0.10	23.5	23.01	1.119	0.768	/
			50	49	Left Side	2535	0.617	2.59	22	21.92	1.019	0.628	/



			1	49	Bottom Side	2535	0.650	2.77	23.5	23.01	1.119	0.728	/
			50	49	Bottom Side	2535	0.601	-2.19	22	21.92	1.019	0.612	/
LTE Band 12	10M	QPSK	1	24	Front side	707.5	0.737	0.37	24.5	24.11	1.094	0.806	/
			25	0	Front side	707.5	0.694	2.32	23.5	23.18	1.076	0.747	/
			1	24	Back Side	704	0.937	-0.43	24.5	24.11	1.094	1.025	/
			1	24	Back Side	707.5	0.966	1.44	24.5	24.11	1.094	1.057	10
			1	24	Back Side	711	0.919	-3.06	24.5	24.08	1.102	1.012	/
			25	0	Back Side	707.5	0.718	-3.71	23.5	23.18	1.076	0.773	/
			1	24	Left Side	707.5	0.665	-2.50	24.5	24.11	1.094	0.727	/
			25	0	Left Side	707.5	0.649	1.44	23.5	23.18	1.076	0.699	/
			1	24	Right Side	707.5	0.105	-0.46	24.5	24.11	1.094	0.115	/
			25	0	Right Side	707.5	0.074	-3.89	23.5	23.18	1.076	0.080	/
			1	24	Bottom Side	707.5	0.697	-0.91	24.5	24.11	1.094	0.762	/
			25	0	Bottom Side	707.5	0.623	0.63	23.5	23.18	1.076	0.671	/
LTE Band 13	10M	QPSK	1	24	Front side	782	0.701	-3.96	24	23.59	1.099	0.770	/
			25	24	Front side	782	0.653	-1.66	23	22.84	1.038	0.678	/
			1	24	Back Side	782	0.723	3.30	24	23.59	1.099	0.795	11
			25	24	Back Side	782	0.664	-3.58	23	22.84	1.038	0.689	/
			1	24	Left Side	782	0.637	-3.72	24	23.59	1.099	0.700	/
			25	24	Left Side	782	0.610	-3.24	23	22.84	1.038	0.633	/
			1	24	Bottom Side	782	0.645	-1.33	24	23.59	1.099	0.709	/
			25	24	Bottom Side	782	0.606	-0.04	23	22.84	1.038	0.629	/
LTE Band 17	10M	QPSK	1	24	Front side	709	0.587	-2.11	24.5	24.15	1.084	0.636	/
			25	24	Front side	709	0.526	3.23	23.5	23.25	1.059	0.557	/
			1	24	Back Side	709	0.787	3.19	24.5	24.15	1.084	0.853	12
			1	24	Back Side	710	0.735	0.14	24.5	24.12	1.091	0.802	/
			1	24	Back Side	711	0.759	2.17	24.5	24.11	1.094	0.830	/
			25	24	Back Side	709	0.705	-0.59	23.5	23.25	1.059	0.747	/
			1	24	Left Side	709	0.736	-2.42	24.5	24.15	1.084	0.798	/
			25	24	Left Side	709	0.681	-0.96	23.5	23.25	1.059	0.721	/
			1	24	Right Side	709	0.113	-3.67	24.5	24.15	1.084	0.122	/
			25	24	Right Side	709	0.049	-0.89	23.5	23.25	1.059	0.052	/
			1	24	Bottom Side	709	0.695	-0.73	24.5	24.15	1.084	0.753	/
			25	24	Bottom Side	709	0.660	3.39	23.5	23.25	1.059	0.699	/



LTE Band 25	20M	QPSK	1	49	Front side	1905	0.553	0.25	23.5	23.23	1.064	0.588	/
			50	0	Front side	1860	0.517	0.66	22.5	22.19	1.074	0.555	/
			1	49	Back Side	1860	0.742	0.84	23.5	23.14	1.086	0.806	/
			1	49	Back Side	1882.5	0.715	2.09	23.5	23.13	1.089	0.779	/
			1	49	Back Side	1905	0.760	-1.68	23.5	23.23	1.064	0.809	13
			50	0	Back Side	1860	0.715	2.04	22.5	22.19	1.074	0.768	/
			1	49	Left Side	1905	0.613	-3.45	23.5	23.23	1.064	0.652	/
			50	0	Left Side	1860	0.606	1.53	22.5	22.19	1.074	0.651	/
			1	49	Bottom Side	1905	0.587	-2.91	23.5	23.23	1.064	0.625	/
			50	0	Bottom Side	1860	0.561	0.96	22.5	22.19	1.074	0.603	/
LTE Band 26	15M	QPSK	1	37	Front side	821.5	0.691	-1.67	24	23.9	1.023	0.707	/
			36	0	Front side	821.5	0.647	0.11	23	22.8	1.047	0.677	/
			1	37	Back Side	821.5	0.875	-0.78	24	23.9	1.023	0.895	14
			1	37	Back Side	831.5	0.822	1.54	24	23.8	1.047	0.861	/
			1	37	Back Side	841.5	0.817	0.52	24	23.74	1.062	0.867	/
			36	0	Back Side	821.5	0.754	0.25	23	22.8	1.047	0.790	/
			1	37	Left Side	821.5	0.721	0.29	24	23.9	1.023	0.738	/
			36	0	Left Side	821.5	0.685	2.30	23	22.8	1.047	0.717	/
			1	37	Right Side	821.5	0.133	-0.19	24	23.9	1.023	0.136	/
			36	0	Right Side	821.5	0.092	1.11	23	22.8	1.047	0.096	/
			1	37	Bottom Side	821.5	0.694	-1.50	24	23.9	1.023	0.710	/
			36	0	Bottom Side	821.5	0.651	-3.28	23	22.8	1.047	0.682	/
LTE Band 41	20M	QPSK	1	49	Front side	2506	0.632	0.57	23.5	23.15	1.084	0.685	/
			50	24	Front side	2506	0.613	-3.53	22	21.93	1.016	0.623	/
			1	49	Back Side	2506	0.922	-0.15	23.5	23.15	1.084	0.999	15
			1	49	Back Side	2593	0.891	3.64	23	22.98	1.005	0.895	/
			1	49	Back Side	2680	0.868	-0.40	23	22.92	1.019	0.884	/
			50	24	Back Side	2506	0.773	-3.85	22	21.93	1.016	0.786	/
			1	49	Left Side	2506	0.710	-0.12	23.5	23.15	1.084	0.770	/
			50	24	Left Side	2506	0.641	0.12	22	21.93	1.016	0.651	/
			1	49	Bottom Side	2506	0.739	-1.55	23.5	23.15	1.084	0.801	/
			50	24	Bottom Side	2506	0.608	-0.68	22	21.93	1.016	0.618	/
LTE Band 66	20M	QPSK	1	49	Front side	1770	0.558	0.71	23.5	23.2	1.072	0.598	/
			50	24	Front side	1770	0.531	1.33	22.5	22.05	1.109	0.589	/



			1	49	Back Side	1770	0.728	3.45	23.5	23.2	1.072	0.780	16
			50	24	Back Side	1770	0.701	3.68	22.5	22.05	1.109	0.778	/
			1	49	Left Side	1770	0.679	2.92	23.5	23.2	1.072	0.728	/
			50	24	Left Side	1770	0.635	-0.48	22.5	22.05	1.109	0.704	/
			1	49	Bottom Side	1770	0.661	0.28	23.5	23.2	1.072	0.708	/
			50	24	Bottom Side	1770	0.607	1.90	22.5	22.05	1.109	0.673	/
LTE Band 71	20M	QPSK	1	49	Front side	688	0.761	1.70	24.5	24.32	1.042	0.793	/
			50	0	Front side	688	0.724	1.50	23.5	23.34	1.038	0.751	/
			1	49	Back Side	673	0.965	1.61	24.5	24.21	1.069	1.032	/
			1	49	Back Side	680.5	1.020	1.50	24.5	24.25	1.059	1.080	/
			1	49	Back Side	688	1.210	2.51	24.5	24.32	1.042	1.261	17
			50	0	Back Side	673	0.837	3.18	23.5	23.12	1.091	0.914	/
			50	0	Back Side	680.5	0.824	-3.71	23	22.96	1.009	0.832	/
			50	0	Back Side	688	0.815	0.15	23.5	23.34	1.038	0.846	/
			100	0	Back Side	688	0.729	0.58	23.5	23.27	1.054	0.769	/
			1	49	Left Side	688	0.748	1.87	24.5	24.32	1.042	0.780	/
			50	0	Left Side	688	0.710	-2.49	23.5	23.34	1.038	0.737	/
			1	49	Bottom Side	688	0.737	2.32	24.5	24.32	1.042	0.768	/
			50	0	Bottom Side	688	0.682	0.80	23.5	23.34	1.038	0.708	/
2.4GHz WLAN	N/A	802.11b	N/A	N/A	Front Side	2437	0.121	0.34	17.00	16.87	1.030	0.125	/
					Back Side	2437	0.166	-1.60	17.00	16.87	1.030	0.171	18
					Left Side	2437	0.088	-2.32	17.00	16.87	1.030	0.091	/
					Top Side	2437	0.092	2.78	17.00	16.87	1.030	0.095	/
BT	N/A	GFSK	N/A	N/A	Back Side	2441	0.034	2.70	4.50	4.36	1.033	0.035	19
					Left Side	2441	0.026	3.22	4.50	4.36	1.033	0.027	/
5.2GHz WLAN	N/A	802.11 n-HT20	N/A	N/A	Front Side	5180	0.067	0.14	13.50	13.02	1.117	0.075	/
					Back Side	5180	0.153	1.48	13.50	13.02	1.117	0.171	20
					Left Side	5180	0.105	-2.64	13.50	13.02	1.117	0.117	/
					Top Side	5180	0.113	1.25	13.50	13.02	1.117	0.126	/
5.3GHz WLAN	N/A	802.11 n-HT20	N/A	N/A	Front Side	5320	0.095	2.75	14.00	13.51	1.119	0.106	/
					Back Side	5320	0.167	-2.02	14.00	13.51	1.119	0.187	21
					Left Side	5320	0.116	1.32	14.00	13.51	1.119	0.130	/
					Top Side	5320	0.099	-1.39	14.00	13.51	1.119	0.111	/
5.6GHz WLAN	N/A	802.11 n-HT20	N/A	N/A	Front Side	5500	0.072	-1.42	14.00	13.93	1.016	0.073	/



					Back Side	5500	0.113	-3.43	14.00	13.93	1.016	0.115	22
					Left Side	5500	0.086	-3.70	14.00	13.93	1.016	0.087	/
					Top Side	5500	0.091	-2.02	14.00	13.93	1.016	0.092	/
5.8GHz WLAN	N/A	802.11 n-HT20	N/A	N/A	Front Side	5785	0.102	2.47	13.50	13.24	1.062	0.108	/
					Back Side	5785	0.135	0.89	13.50	13.24	1.062	0.143	23
					Left Side	5785	0.127	1.41	13.50	13.24	1.062	0.135	/
					Top Side	5785	0.119	1.31	13.50	13.24	1.062	0.126	/

Note:

1. The test separation of all above table is 0mm.
2. Per KDB 447498 D04, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
 - a. Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
 - b. Scaled SAR(W/kg)= Measured SAR(W/kg)*Tune-up Scaling Factor
3. Per KDB 248227- When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg. (The highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power was **0.217** W/Kg for Body)
4. When the user enables the personal Wireless router functions for the handsets, actual operations include simultaneous transmission of both the Wi-Fi transmitting frequency and thus cannot be evaluated for SAR under actual use conditions. The "Portable Hotspot" feature on the handset was NOT activated, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal.

**12.3 Repeated SAR**

Band	Mode	Test Position	Freq.	Result 1g (W/Kg)	Power Drift(%)	Max.Turn-up Power(dBm)	Meas.Output Power(dBm)	Scaled SAR(W/Kg)	Meas. No.
WCDMA Band II	RMC	Back Side	1852.4	0.902	-1.44	24	23.75	0.956	-
		Back Side	1880	1.081	-2.04	24	23.8	1.132	-
		Back Side	1907.6	1.018	-2.38	24	23.78	1.071	-
WCDMA Band IV	RMC	Back Side	1740	0.757	2.32	24	23.7	0.811	-

Band	BW (MHz)	Mod.	RB Size	RB offset	Test Position	Freq.	Result 1g (W/Kg)	Power Drift (%)	Max. Turn-up Power (dBm)	Meas. Output Power (dBm)	Scaled SAR (W/Kg)	Meas. No.
LTE Band 2	20M	QPSK	1	49	Back Side	1860	0.838	-2.05	23.5	23.00	0.941	-
			1	49	Back Side	1880	0.917	3.61	23.5	23.14	0.996	-
			1	49	Back Side	1900	0.822	1.85	23	22.99	0.824	-
LTE Band 4	20M	QPSK	1	49	Back Side	1720	0.782	2.86	23	22.92	0.797	-
			1	49	Back Side	1732.5	0.835	-2.76	23.5	23.10	0.915	-
			1	49	Back Side	1745	0.824	-3.45	23	22.96	0.832	-
LTE Band 5	10M	QPSK	1	24	Back Side	829	1.033	1.17	24	23.66	1.117	-
			1	24	Back Side	836.5	0.909	-0.44	24	23.60	0.996	-
			1	24	Back Side	844	0.912	1.37	23.5	23.43	0.927	-
LTE Band 7	20M	QPSK	1	49	Back Side	2510	0.925	-1.50	23	22.67	0.999	-
			1	49	Back Side	2535	0.974	-1.85	23.5	23.01	1.091	-
			1	49	Back Side	2560	0.938	-1.78	23	22.90	0.960	-
LTE Band 12	10M	QPSK	1	24	Back Side	707.5	0.937	1.01	24.5	24.11	1.025	-
			1	24	Back Side	707.5	0.969	3.72	24.5	24.11	1.060	-
			1	24	Back Side	707.5	0.919	1.48	24.5	24.08	1.012	-
LTE Band 17	10M	QPSK	1	24	Back Side	709	0.787	-2.66	24.5	24.15	0.853	-
			1	24	Back Side	710	0.735	1.58	24.5	24.12	0.802	-
			1	24	Back Side	711	0.759	3.56	24.5	24.11	0.830	-
LTE Band 25	20M	QPSK	1	49	Back Side	1860	0.742	-2.57	23.5	23.14	0.806	-
			1	49	Back Side	1905	0.760	0.63	23.5	23.23	0.809	-
	15M	QPSK	1	37	Back Side	821.5	0.875	1.08	24	23.90	0.895	-



LTE Band 26			1	37	Back Side	831.5	0.822	3.34	24	23.80	0.861	-
			1	37	Back Side	841.5	0.817	-3.87	24	23.74	0.867	-
LTE Band 41	20M	QPSK	1	49	Back Side	2506	0.922	0.55	23.5	23.15	0.999	-
			1	49	Back Side	2593	0.891	0.29	23	22.98	0.895	-
			1	49	Back Side	2680	0.868	1.75	23	22.92	0.884	-
LTE Band 71	20M	QPSK	1	49	Back Side	673	0.965	0.45	24.5	24.21	1.032	-
			1	49	Back Side	680.5	1.020	2.12	24.5	24.25	1.080	-
			1	49	Back Side	688	1.190	0.61	24.5	24.32	1.240	-
			50	0	Back Side	673	0.837	3.39	23.5	23.12	0.914	-
			50	0	Back Side	680.5	0.824	1.85	23	22.96	0.832	-
			50	0	Back Side	688	0.815	-0.51	23.5	23.34	0.846	-

12.4 Repeated SAR measurement

Band	Mode	Test Position	Freq.	Original Measured SAR 1g(W/kg)	1 st Repeated SAR 1g	Ratio	Original Measured SAR 1g(W/kg)	2nd Repeated SAR 1g	Ratio
WCDMA Band II	RMC	Back Side	1852.4	0.933	0.902	1.034	-	-	-
		Back Side	1880	1.13	1.081	1.045	-	-	-
		Back Side	1907.6	1.02	1.018	1.002	-	-	-
WCDMA Band IV	RMC	Back Side	1740	0.77	0.757	1.018	-	-	-

Band	BW (MHz)	Mod.	RB Size	RB offset	Test Position	Freq.	Original Measured SAR 1g(W/kg) 1g (W/Kg)	1 st Repeated SAR 1g	Ratio	Original Measured	2nd Repeated SAR 1g	Ratio
LTE Band 2	20M	QPSK	1	49	Back Side	1860	0.871	0.838	1.039	-	-	-
			1	49	Back Side	1880	0.934	0.917	1.018	-	-	-
			1	49	Back Side	1900	0.864	0.822	1.051	-	-	-
LTE Band 4	20M	QPSK	1	49	Back Side	1720	0.813	0.782	1.039	-	-	-
			1	49	Back Side	1732.5	0.859	0.835	1.029	-	-	-
			1	49	Back Side	1745	0.848	0.824	1.029	-	-	-
LTE Band 5	10M	QPSK	1	24	Back Side	829	1.04	1.033	1.007	-	-	-
			1	24	Back Side	836.5	0.917	0.909	1.009	-	-	-



			1	24	Back Side	844	0.935	0.912	1.025	-	-	-
LTE Band 7	20M	QPSK	1	49	Back Side	2510	0.952	0.925	1.029	-	-	-
			1	49	Back Side	2535	1.01	0.974	1.037	-	-	-
			1	49	Back Side	2560	0.961	0.938	1.025	-	-	-
LTE Band 12	10M	QPSK	1	24	Back Side	707.5	0.937	0.932	1.005	-	-	-
			1	24	Back Side	707.5	0.969	0.963	1.007	-	-	-
			1	24	Back Side	707.5	0.919	0.907	1.013	-	-	-
LTE Band 17	10M	QPSK	1	24	Back Side	709	0.787	0.748	1.052	-	-	-
			1	24	Back Side	710	0.735	0.729	1.009	-	-	-
			1	24	Back Side	711	0.759	0.735	1.032	-	-	-
LTE Band 25	20M	QPSK	1	49	Back Side	1860	0.742	0.732	1.014	-	-	-
			1	49	Back Side	1905	0.76	0.737	1.031	-	-	-
LTE Band 26	15M	QPSK	1	37	Back Side	821.5	0.875	0.843	1.039	-	-	-
			1	37	Back Side	831.5	0.822	0.795	1.033	-	-	-
			1	37	Back Side	841.5	0.817	0.786	1.040	-	-	-
LTE Band 41	20M	QPSK	1	49	Back Side	2506	0.922	0.891	1.035	-	-	-
			1	49	Back Side	2593	0.891	0.874	1.019	-	-	-
			1	49	Back Side	2680	0.868	0.843	1.030	-	-	-
LTE Band 71	20M	QPSK	1	49	Back Side	673	0.965	0.932	1.036	-	-	-
			1	49	Back Side	680.5	1.02	0.986	1.035	-	-	-
			1	49	Back Side	688	1.19	1.189	1.001	-	-	-
			50	0	Back Side	673	0.837	0.825	1.014	-	-	-
			50	0	Back Side	680.5	0.824	0.813	1.014	-	-	-
			50	0	Back Side	688	0.815	0.785	1.038	-	-	-

Note:

1. Per KDB 865664 D01, for each frequency band, repeated SAR measurement is required only when the measured SAR is $\geq 0.8\text{W/Kg}$.
2. Per KDB 865664 D01, if the ratio of largest to smallest SAR for the original and first repeated measurement is ≤ 1.2 and the measured SAR $< 1.45\text{W/Kg}$, only one repeated measurement is required.
3. Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is $\geq 1.45\text{W/Kg}$.
4. The ratio is the difference in percentage between original and repeated measured SAR.



12.5 Simultaneous Multi-band Transmission Evaluation

Application Simultaneous Transmission information:

Position	Simultaneous State
Body	1. GSM + 2.4GHz WLAN/5G WLAN
	2. GSM + Bluetooth
	3. WCDMA + 2.4GHz WLAN/5G WLAN
	4. WCDMA + Bluetooth
	5. LTE + 2.4GHz WLAN/5G WLAN
	6. LTE + Bluetooth

NOTE:

1. Bluetooth and WLAN can't simultaneous transmission at the same time.
2. For simultaneous transmission at head and body exposure position, 2 transmitters simultaneous transmission was the worst state.
3. If the test separation distance is <5mm, 5mm is used for excluded SAR calculation.
4. KDB 447498 / 4.3.2 (2) when standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion: a) (max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]·[√f (GHz) /x] W/kg for test separation distances≤ 50 mm; Where x = 7.5 for 1-g SAR, and x = 18.75 for 10-g SAR. b) 0.4W/Kg for 1-g SAR and 1.0W/Kg for 10-g SAR, when the separation distance is >50mm.

Estimated SAR		Maximum Average Power		Dis.	Frequency(GHz)	Stand alone SAR(1&10g) [W/kg]
		dBm	mW			
NFC	Body	-41.87	0.000	5	0.01356	0.000



Simultaneous Mode	Position	Mode	Max. 1-g SAR	1-g Sum SAR
			(W/kg)	(W/kg)
GSM + 2.4G WLAN	Body	GSM	0.517	0.688
		2.4G WLAN	0.171	
GSM + Bluetooth	Body	GSM	0.517	0.552
		Bluetooth	0.035	
GSM + NFC	Body	GSM	0.517	0.517
		NFC	0.000	
GSM + 5G WLAN	Body	GSM	0.517	0.704
		5G WLAN	0.187	
WCDMA + 2.4G WLAN	Body	WCDMA	1.183	1.354
		2.4G WLAN	0.171	
WCDMA + Bluetooth	Body	WCDMA	1.183	1.218
		Bluetooth	0.035	
WCDMA + NFC	Body	WCDMA	1.183	1.183
		NFC	0.000	
WCDMA + 5G WLAN	Body	WCDMA	1.183	1.370
		5G WLAN	0.187	
LTE + 2.4G WLAN	Body	LTE	1.261	1.432
		2.4G WLAN	0.171	
LTE + Bluetooth	Body	LTE	1.261	1.296
		Bluetooth	0.035	
LTE + NFC	Body	LTE	1.261	1.261
		NFC	0.000	
LTE + 5G WLAN	Body	LTE	1.261	1.448
		5G WLAN	0.187	

Simultaneous transmission SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneous transmitting antenna.

When the sum of SAR 1g of all simultaneously transmitting antennas in an operating mode and exposure condition combination is within the SAR limit (SAR-1g 1.6 W/kg), the simultaneous transmission SAR is not required. When the sum of SAR 1g is greater than the SAR limit (SAR-1g 1.6 W/kg), SAR test exclusion is determined by the SPLSR.



13. Equipment List

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last Calibration	Calibrated Until
750MHz Dipole	MVG	SID750	SN 30/14 DIP0G750-331	2023.07.04	2026.07.03
835MHz Dipole	MVG	SID835	SN 30/14 DIP0G835-332	2023.07.04	2026.07.03
1800MHz Dipole	MVG	SID1800	5023-DIP1G800-747	2023.12.20	2026.12.19
1900MHz Dipole	MVG	SID1900	SN 30/14 DIP1G900-333	2023.09.14	2026.09.13
2450MHz Dipole	MVG	SID2450	SN 30/14 DIP2G450-335	2023.07.04	2026.07.03
2600MHz Dipole	MVG	SID2600	SN 30/14 DIP2G600-336	2023.07.04	2026.07.03
Waveguide	MVG	SWG5500	SN 13/14 WGA32	2023.07.04	2026.07.03
Data Acquisition Electronics DAE _x	SPEAG	DAE3	428	2025.09.08	2026.09.07
E-field Probe	SPEAG	EX3DV4	3806	2025-09-11	2025-09-10
Dielectric Probe Kit	MVG	SCLMP	SN 32/14 OCPG67	2025.09.15	2026.09.14
Antenna	MVG	ANTA3	SN 07/13 ZNTA52	N/A	N/A
Attenuator	Agilent	HXT-10-8-SMA	240327017	2025-02-22	2026-02-21
Directional coupler	Xi'an Xingbo	XBOH-OA08-20dB	211123-4-3	2025-02-22	2026-02-21
Network Analyzer	Agilent	E5071C	MY46520378	2025-09-26	2026-09-24
Multi Meter	Keithley	Multi Meter 2000	4050073	2025-09-22	2026-09-21
Signal Generator	Agilent	N5182A	MY50140530	2025-09-26	2026-09-25
Wireless Communication Test Set	Agilent	8960-E5515C	MY48360751	2025-02-22	2026-02-21
Wireless Communication Test Set	R&S	CMW500	156324	2025-09-25	2026-09-24
Power Amplifier	DESAY	WCS-DLNA50M8G50G1	CSKJLNA231227A	2025-09-29	2026-09-28
Power Meter	R&S	NRP	100510	2025-09-25	2026-09-24
Power Sensor	R&S	NRP-Z11	101919	2025-09-25	2026-09-24
Power Sensor	Keysight	U2021XA	MY56280002	2025-09-25	2026-09-24
Temperature hygrometer	TOPRIE	TP502V4-P	6700000124198	2025.10.09	2026.10.08
Thermograph	Elitech	RC-4	S/N EF7176501537	2025.10.17	2026.10.16



Appendix A. System Validation Plots

Test Laboratory: STS Lab

Time: 2026-02-23

System Check_750MHz

DUT: Dipole 750 MHz

Communication System: UID 0, CW (0); Communication System Band: D750 (750.0 MHz); Frequency: 750 MHz; Communication System PAR: 0 dB; PMF: 1

Medium parameters used: $f = 750$ MHz; $\sigma = 0.91$ S/m; $\epsilon_r = 42.41$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: EX3DV4 - SN3806; ConvF(8.35, 8.89, 9.14) @ 750 MHz; Calibrated: 2025/9/11
- Sensor-Surface: 1.8mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE3 Sn428; Calibrated: 2025/9/8
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Type: QD 000 P40 CD; Serial: xxxx
- DASY52 52.10.3(1513); SEMCAD X 14.6.13(7474)

Area Scan (6x15x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.910 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 36.77 V/m; Power Drift = -0.15 dB


Peak SAR (extrapolated) = 1.19 W/kg

SAR(1 g) = 0.821 W/kg; SAR(10 g) = 0.545 W/kg

Smallest distance from peaks to all points 3 dB below = 18.7 mm

Ratio of SAR at M2 to SAR at M1 = 68.7%

Maximum value of SAR (measured) = 1.04 W/kg



**System Check_835MHz****DUT: Dipole 835 MHz**

Communication System: UID 0, CW (0); Communication System Band: D835 (835.0 MHz); Frequency: 835 MHz; Communication System PAR: 0 dB; PMF: 1

Medium parameters used (interpolated): $f = 835$ MHz; $\sigma = 0.92$ S/m; $\epsilon_r = 41.87$; $\rho = 1000$ kg/m³

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: EX3DV4 - SN3806; ConvF(8.2, 8.73, 8.98) @ 835 MHz; Calibrated: 2025/9/11
- Sensor-Surface: 1.8mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE3 Sn428; Calibrated: 2025/9/8
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Type: QD 000 P40 CD; Serial: xxxx
- DASYS 52.10.3(1513); SEMCAD X 14.6.13(7474)

Area Scan (7x15x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 1.21 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 41.00 V/m; Power Drift = -0.61 dB


Peak SAR (extrapolated) = 1.42 W/kg

SAR(1 g) = 0.972 W/kg; SAR(10 g) = 0.633 W/kg

Smallest distance from peaks to all points 3 dB below = 16 mm

Ratio of SAR at M2 to SAR at M1 = 67.9%

Maximum value of SAR (measured) = 1.25 W/kg





System Check_1800MHz

DUT: Dipole 1800 MHz

Communication System: UID 0, CW (0); Communication System Band: D1800 (1800.0 MHz); Frequency: 1800 MHz; Communication System PAR: 0 dB; PMF: 1

Medium parameters used: $f = 1800$ MHz; $\sigma = 1.38$ S/m; $\epsilon_r = 40.27$; $\rho = 1000$ kg/m³

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: EX3DV4 - SN3806; ConvF(7.06, 7.52, 7.74) @ 1800 MHz; Calibrated: 2025/9/11
- Sensor-Surface: 1.8mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE3 Sn428; Calibrated: 2025/9/8
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Type: QD 000 P40 CD; Serial: xxxx
- DASY52 52.10.3(1513); SEMCAD X 14.6.13(7474)

Area Scan (7x13x1): Measurement grid: $dx=8$ mm, $dy=8$ mm

Maximum value of SAR (measured) = 5.41 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 70.08 V/m; Power Drift = -0.74 dB


Peak SAR (extrapolated) = 6.80 W/kg

SAR(1 g) = 3.81 W/kg; SAR(10 g) = 1.99 W/kg

Smallest distance from peaks to all points 3 dB below = 10.1 mm

Ratio of SAR at M2 to SAR at M1 = 55.6%

Maximum value of SAR (measured) = 5.61 W/kg



**System Check_1900MHz****DUT: Dipole 1900 MHz**

Communication System: UID 0, CW (0); Communication System Band: D1900 (1900.0 MHz); Frequency: 1900 MHz; Communication System PAR: 0 dB; PMF: 1

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.39$ S/m; $\epsilon_r = 40.08$; $\rho = 1000$ kg/m³

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: EX3DV4 - SN3806; ConvF(6.85, 7.3, 7.51) @ 1900 MHz; Calibrated: 2025/9/11
- Sensor-Surface: 1.8mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE3 Sn428; Calibrated: 2025/9/8
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Type: QD 000 P40 CD; Serial: xxxx
- DASYS 52.10.3(1513); SEMCAD X 14.6.13(7474)

Area Scan (5x9x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 5.40 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 65.66 V/m; Power Drift = -0.30 dB


Peak SAR (extrapolated) = 7.26 W/kg

SAR(1 g) = 4.05 W/kg; SAR(10 g) = 2.08 W/kg

Smallest distance from peaks to all points 3 dB below = 9.6 mm

Ratio of SAR at M2 to SAR at M1 = 55.4%

Maximum value of SAR (measured) = 5.95 W/kg





System Check_2450MHz

DUT: Dipole 2450 MHz

Communication System: UID 0, CW (0); Communication System Band: D2450 (2450.0 MHz); Frequency: 2450 MHz; Communication System PAR: 0 dB; PMF: 1

Medium parameters used: $f = 2450$ MHz; $\sigma = 1.81$ S/m; $\epsilon_r = 39.93$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: EX3DV4 - SN3806; ConvF(6.3, 6.71, 6.9) @ 2450 MHz; Calibrated: 2025/9/11
- Sensor-Surface: 1.8mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE3 Sn428; Calibrated: 2025/9/8
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Type: QD 000 P40 CD; Serial: xxxx
- DASY52 52.10.3(1513); SEMCAD X 14.6.13(7474)

Area Scan (6x11x1): Measurement grid: $dx=8$ mm, $dy=8$ mm

Maximum value of SAR (measured) = 8.09 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 72.77 V/m; Power Drift = -0.61 dB


Peak SAR (extrapolated) = 10.2 W/kg

SAR(1 g) = 5.24 W/kg; SAR(10 g) = 2.45 W/kg

Smallest distance from peaks to all points 3 dB below = 9.6 mm

Ratio of SAR at M2 to SAR at M1 = 50.7%

Maximum value of SAR (measured) = 8.10 W/kg



**System Check_2600MHz****DUT: Dipole 2600 MHz**

Communication System: UID 0, CW (0); Communication System Band: D2600 (2600.0 MHz); Frequency: 2600 MHz; Communication System PAR: 0 dB; PMF: 1

Medium parameters used: $f = 2600$ MHz; $\sigma = 1.93$ S/m; $\epsilon_r = 39.05$; $\rho = 1000$ kg/m³

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: EX3DV4 - SN3806; ConvF(6.14, 6.54, 6.73) @ 2600 MHz; Calibrated: 2025/9/11
- Sensor-Surface: 1.8mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE3 Sn428; Calibrated: 2025/9/8
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Type: QD 000 P40 CD; Serial: xxxx
- DASYS 52.10.3(1513); SEMCAD X 14.6.13(7474)

Area Scan (8x13x1): Measurement grid: $dx=8$ mm, $dy=8$ mm

Maximum value of SAR (measured) = 7.90 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 70.23 V/m; Power Drift = -0.01 dB


Peak SAR (extrapolated) = 11.3 W/kg

SAR(1 g) = 5.6 W/kg; SAR(10 g) = 2.55 W/kg

Smallest distance from peaks to all points 3 dB below = 9.6 mm

Ratio of SAR at M2 to SAR at M1 = 49.6%

Maximum value of SAR (measured) = 8.81 W/kg





System Check_5200MHz

DUT: Dipole 5000 MHz

Communication System: UID 0, CW (0); Communication System Band: ITD5500 (5000.0 - 5900.0 MHz);

Frequency: 5200 MHz; Communication System PAR: 0 dB; PMF: 1

Medium parameters used: $f = 5200$ MHz; $\sigma = 4.67$ S/m; $\epsilon_r = 36.71$; $\rho = 1000$ kg/m³

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: EX3DV4 - SN3806; ConvF(4.96, 5.28, 5.44) @ 5200 MHz; Calibrated: 2025/9/11
- Sensor-Surface: 1.8mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE3 Sn428; Calibrated: 2025/9/8
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Type: QD 000 P40 CD; Serial: xxxx
- DASY52 52.10.3(1513); SEMCAD X 14.6.13(7474)

Area Scan (12x28x1): Measurement grid: $dx=8$ mm, $dy=8$ mm

Maximum value of SAR (measured) = 3.57 W/kg

Zoom Scan (7x7x12)/Cube 0: Measurement grid: $dx=4$ mm, $dy=4$ mm, $dz=2$ mm

Reference Value = 20.16 V/m; Power Drift = -3.74 dB


Peak SAR (extrapolated) = 7.67 W/kg

SAR(1 g) = 1.605 W/kg; SAR(10 g) = 0.617 W/kg

Smallest distance from peaks to all points 3 dB below = 8 mm

Ratio of SAR at M2 to SAR at M1 = 55.2%

Maximum value of SAR (measured) = 3.67 W/kg



**System Check_5400MHz****DUT: Dipole 5000 MHz**

Communication System: UID 0, CW (0); Communication System Band: D5GHz (5000.0 - 6000.0 MHz);

Frequency: 5400 MHz; Communication System PAR: 0 dB; PMF: 1

Medium parameters used: $f = 5400$ MHz; $\sigma = 4.85$ S/m; $\epsilon_r = 35.68$; $\rho = 1000$ kg/m³

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: EX3DV4 - SN3806; ConvF(4.96, 5.28, 5.44) @ 5400 MHz; Calibrated: 2025/9/11
- Sensor-Surface: 1.8mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE3 Sn428; Calibrated: 2025/9/8
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Type: QD 000 P40 CD; Serial: xxxx
- DASY52 52.10.3(1513); SEMCAD X 14.6.13(7474)

Area Scan (9x9x1): Measurement grid: dx=8mm, dy=8mm

Maximum value of SAR (measured) = 3.07 W/kg

Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 27.30 V/m; Power Drift = 2.57 dB


Peak SAR (extrapolated) = 6.35 W/kg

SAR(1 g) = 1.714 W/kg; SAR(10 g) = 0.597 W/kg

Smallest distance from peaks to all points 3 dB below = 8.2 mm

Ratio of SAR at M2 to SAR at M1 = 63.9%

Maximum value of SAR (measured) = 3.04 W/kg





System Check_5600MHz

DUT: Dipole 5500 MHz

Communication System: UID 0, CW (0); Communication System Band: D5GHz (5000.0 - 6000.0 MHz);

Frequency: 5600 MHz; Communication System PAR: 0 dB; PMF: 1

Medium parameters used: $f = 5600$ MHz; $\sigma = 5.07$ S/m; $\epsilon_r = 35.71$; $\rho = 1000$ kg/m³

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: EX3DV4 - SN3806; ConvF(4.57, 4.87, 5.01) @ 5600 MHz; Calibrated: 2025/9/11
- Sensor-Surface: 1.8mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE3 Sn428; Calibrated: 2025/9/8
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Type: QD 000 P40 CD; Serial: xxxx
- DASY52 52.10.3(1513); SEMCAD X 14.6.13(7474)

Area Scan (8x8x1): Measurement grid: $dx=8$ mm, $dy=8$ mm

Maximum value of SAR (measured) = 3.33 W/kg

Zoom Scan (7x7x12)/Cube 0: Measurement grid: $dx=4$ mm, $dy=4$ mm, $dz=2$ mm

Reference Value = 25.16 V/m; Power Drift = -2.74 dB


Peak SAR (extrapolated) = 7.45 W/kg

SAR(1 g) = 1.723 W/kg; SAR(10 g) = 0.641 W/kg

Smallest distance from peaks to all points 3 dB below = 9.3 mm

Ratio of SAR at M2 to SAR at M1 = 51.7%

Maximum value of SAR (measured) = 3.17 W/kg



**System Check_5800MHz****DUT: Dipole 5500 MHz**

Communication System: UID 0, CW (0); Communication System Band: D5GHz (5000.0 - 6000.0 MHz);

Frequency: 5800 MHz; Communication System PAR: 0 dB; PMF: 1

Medium parameters used: $f = 5800$ MHz; $\sigma = 5.26$ S/m; $\epsilon_r = 35.55$; $\rho = 1000$ kg/m³

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: EX3DV4 - SN3806; ConvF(4.59, 4.89, 5.03) @ 5800 MHz; Calibrated: 2025/9/11
- Sensor-Surface: 1.8mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE3 Sn428; Calibrated: 2025/9/8
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Type: QD 000 P40 CD; Serial: xxxx
- DASYS 52.10.3(1513); SEMCAD X 14.6.13(7474)

Area Scan (9x9x1): Measurement grid: dx=8mm, dy=8mm

Maximum value of SAR (measured) = 3.67 W/kg

Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 28.25 V/m; Power Drift = -2.69 dB


Peak SAR (extrapolated) = 8.48 W/kg

SAR(1 g) = 1.843 W/kg; SAR(10 g) = 0.678 W/kg

Smallest distance from peaks to all points 3 dB below = 8.6 mm

Ratio of SAR at M2 to SAR at M1 = 49.6%

Maximum value of SAR (measured) = 3.56 W/kg





Appendix B. SAR Test Plots

Test Laboratory: STS Lab

Time: 2026-02-24

GSM 850_Back Side_0mm**DUT: Smart POS Terminal**

Communication System: UID 0, Generic GSM (0); Communication System Band: GSM 850 (824.0 - 849.0 MHz); Frequency: 848.8 MHz; Communication System PAR: 9.191 dB; PMF: 2.88104

Medium parameters used (interpolated): $f = 848.8$ MHz; $\sigma = 0.92$ S/m; $\epsilon_r = 41.39$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: EX3DV4 - SN3806; ConvF(8.2, 8.73, 8.98) @ 848.8 MHz; Calibrated: 2025/9/11
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE3 Sn428; Calibrated: 2025/9/8
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Type: QD 000 P40 CD; Serial: xxxx
- DASY52 52.10.3(1513); SEMCAD X 14.6.13(7474)

Area Scan (9x10x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.315 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 19.17 V/m; Power Drift = 1.32 dB


Peak SAR (extrapolated) = 0.392 W/kg

SAR(1 g) = 0.303 W/kg; SAR(10 g) = 0.223 W/kg

Smallest distance from peaks to all points 3 dB below = 9.7 mm

Ratio of SAR at M2 to SAR at M1 = 76%

Maximum value of SAR (measured) = 0.320 W/kg





**GSM 1900_Back Side_0mm****DUT: Smart POS Terminal**

Communication System: UID 0, Generic GSM (0); Communication System Band: PCS 1900 (1850.0 - 1910.0 MHz); Frequency: 1850.2 MHz; Communication System PAR: 9.191 dB; PMF: 2.88104

Medium parameters used (interpolated): $f = 1850.2$ MHz; $\sigma = 1.38$ S/m; $\epsilon_r = 39.79$; $\rho = 1000$ kg/m³

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: EX3DV4 - SN3806; ConvF(6.85, 7.3, 7.51) @ 1850.2 MHz; Calibrated: 2025/9/11
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0$, 31.0
- Electronics: DAE3 Sn428; Calibrated: 2025/9/8
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Type: QD 000 P40 CD; Serial: xxxx
- DASY52 52.10.3(1513); SEMCAD X 14.6.13(7474)

Area Scan (9x10x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.461 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 1.296 V/m; Power Drift = -3.32 dB


Peak SAR (extrapolated) = 1.27 W/kg

SAR(1 g) = 0.474 W/kg; SAR(10 g) = 0.191 W/kg

Smallest distance from peaks to all points 3 dB below = 8.6 mm

Ratio of SAR at M2 to SAR at M1 = 44.7%

Maximum value of SAR (measured) = 0.488 W/kg



**WCDMA B2_Back Side_0mm****DUT: Smart POS Terminal**

Communication System: UID 0, Generic WCDMA (0); Communication System Band: WCDMA B2; Frequency: 1880 MHz; Communication System PAR: 0 dB; PMF: 1.12202e-005

Medium parameters used (interpolated): $f = 1880$ MHz; $\sigma = 1.38$ S/m; $\epsilon_r = 40.02$; $\rho = 1000$ kg/m³

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: EX3DV4 - SN3806; ConvF(6.85, 7.3, 7.51) @ 1880 MHz; Calibrated: 2025/9/11
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE3 Sn428; Calibrated: 2025/9/8
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Type: QD 000 P40 CD; Serial: xxxx
- DASYS 52.10.3(1513); SEMCAD X 14.6.13(7474)

Area Scan (9x10x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.883 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 4.926 V/m; Power Drift = 0.72 dB


Peak SAR (extrapolated) = 2.91 W/kg

SAR(1 g) = 1.13 W/kg; SAR(10 g) = 0.468 W/kg

Smallest distance from peaks to all points 3 dB below = 9.8 mm

Ratio of SAR at M2 to SAR at M1 = 44.3%

Maximum value of SAR (measured) = 1.19 W/kg



**WCDMA B4_Back Side_0mm****DUT: Smart POS Terminal**

Communication System: UID 0, Generic WCDMA (0); Communication System Band: WCDMA B4; Frequency: 1740 MHz; Communication System PAR: 0 dB; PMF: 1.12202e-005

Medium parameters used (interpolated): $f = 1740$ MHz; $\sigma = 1.35$ S/m; $\epsilon_r = 40.18$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: EX3DV4 - SN3806; ConvF(7.06, 7.52, 7.74) @ 1740 MHz; Calibrated: 2025/9/11
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0$, 31.0
- Electronics: DAE3 Sn428; Calibrated: 2025/9/8
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Type: QD 000 P40 CD; Serial: xxxx
- DASY52 52.10.3(1513); SEMCAD X 14.6.13(7474)

Area Scan (9x10x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.560 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 6.481 V/m; Power Drift = 3.63 dB


Peak SAR (extrapolated) = 1.98 W/kg

SAR(1 g) = 0.770 W/kg; SAR(10 g) = 0.341 W/kg

Smallest distance from peaks to all points 3 dB below = 10.1 mm

Ratio of SAR at M2 to SAR at M1 = 44.4%

Maximum value of SAR (measured) = 0.894 W/kg



**WCDMA B5_Back Side_0mm****DUT: Smart POS Terminal**

Communication System: UID 0, Generic WCDMA (0); Communication System Band: WCDMA B5; Frequency: 826.4 MHz; Communication System PAR: 0 dB; PMF: 1.12202e-005

Medium parameters used (interpolated): $f = 826.4$ MHz; $\sigma = 0.91$ S/m; $\epsilon_r = 41.01$; $\rho = 1000$ kg/m³

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: EX3DV4 - SN3806; ConvF(8.2, 8.73, 8.98) @ 826.4 MHz; Calibrated: 2025/9/11
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0$, 31.0
- Electronics: DAE3 Sn428; Calibrated: 2025/9/8
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Type: QD 000 P40 CD; Serial: xxxx
- DASY52 52.10.3(1513); SEMCAD X 14.6.13(7474)

Area Scan (9x10x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.466 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 11.95 V/m; Power Drift = -2.59 dB


Peak SAR (extrapolated) = 0.836 W/kg

SAR(1 g) = 0.423 W/kg; SAR(10 g) = 0.197 W/kg

Smallest distance from peaks to all points 3 dB below = 14.5 mm

Ratio of SAR at M2 to SAR at M1 = 38.7%

Maximum value of SAR (measured) = 0.831 W/kg



**LTE B2_Back Side_0mm****DUT: Smart POS Terminal**

Communication System: UID 0, Generic LTE (0); Communication System Band: Band 2, E-UTRA/FDD (1850.0 - 1910.0 MHz); Frequency: 1880 MHz; Communication System PAR: 0 dB; PMF: 1

Medium parameters used (interpolated): $f = 1880$ MHz; $\sigma = 1.38$ S/m; $\epsilon_r = 40.02$; $\rho = 1000$ kg/m³

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: EX3DV4 - SN3806; ConvF(6.85, 7.3, 7.51) @ 1880 MHz; Calibrated: 2025/9/11
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0$, 31.0
- Electronics: DAE3 Sn428; Calibrated: 2025/9/8
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Type: QD 000 P40 CD; Serial: xxxx
- DASY52 52.10.3(1513); SEMCAD X 14.6.13(7474)

Area Scan (9x10x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.453 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 3.446 V/m; Power Drift = -1.51 dB


Peak SAR (extrapolated) = 1.55 W/kg

SAR(1 g) = 0.602 W/kg; SAR(10 g) = 0.248 W/kg

Smallest distance from peaks to all points 3 dB below = 9.4 mm

Ratio of SAR at M2 to SAR at M1 = 47.1%

Maximum value of SAR (measured) = 0.616 W/kg



**LTE B4_Back Side_0mm****DUT: Smart POS Terminal**

Communication System: UID 0, Generic LTE (0); Communication System Band: Band 4, E-UTRA/FDD (1710.0 - 1755.0 MHz); Frequency: 1732.5 MHz; Communication System PAR: 0 dB; PMF: 1

Medium parameters used (interpolated): $f = 1732.5$ MHz; $\sigma = 1.36$ S/m; $\epsilon_r = 39.91$; $\rho = 1000$ kg/m³

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: EX3DV4 - SN3806; ConvF(7.06, 7.52, 7.74) @ 1732.5 MHz; Calibrated: 2025/9/11
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE3 Sn428; Calibrated: 2025/9/8
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Type: QD 000 P40 CD; Serial: xxxx
- DASY52 52.10.3(1513); SEMCAD X 14.6.13(7474)

Area Scan (9x10x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.635 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 7.696 V/m; Power Drift = -3.44 dB


Peak SAR (extrapolated) = 2.19 W/kg

SAR(1 g) = 0.859 W/kg; SAR(10 g) = 0.384 W/kg

Smallest distance from peaks to all points 3 dB below = 10.2 mm

Ratio of SAR at M2 to SAR at M1 = 43.3%

Maximum value of SAR (measured) = 0.994 W/kg





LTE B5_Back Side_0mm

DUT: Smart POS Terminal

Communication System: UID 0, Generic LTE (0); Communication System Band: Band 5, E-UTRA/FDD (824.0 - 849.0 MHz); Frequency: 829 MHz; Communication System PAR: 0 dB; PMF: 1

Medium parameters used (interpolated): $f = 829$ MHz; $\sigma = 0.91$ S/m; $\epsilon_r = 42.01$; $\rho = 1000$ kg/m³

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: EX3DV4 - SN3806; ConvF(8.2, 8.73, 8.98) @ 829 MHz; Calibrated: 2025/9/11
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE3 Sn428; Calibrated: 2025/9/8
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Type: QD 000 P40 CD; Serial: xxxx
- DASY52 52.10.3(1513); SEMCAD X 14.6.13(7474)

Area Scan (9x10x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 1.09 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 21.92 V/m; Power Drift = -3.16 dB


Peak SAR (extrapolated) = 2.28 W/kg

SAR(1 g) = 1.04 W/kg; SAR(10 g) = 0.557 W/kg

Smallest distance from peaks to all points 3 dB below = 9.6 mm

Ratio of SAR at M2 to SAR at M1 = 49.9%

Maximum value of SAR (measured) = 1.20 W/kg



**LTE B7_Back Side_0mm****DUT: Smart POS Terminal**

Communication System: UID 0, Generic LTE (0); Communication System Band: Band 7, E-UTRA/FDD (2500.0 - 2570.0 MHz); Frequency: 2535 MHz; Communication System PAR: 0 dB; PMF: 1

Medium parameters used (interpolated): $f = 2535$ MHz; $\sigma = 1.86$ S/m; $\epsilon_r = 39.09$; $\rho = 1000$ kg/m³

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: EX3DV4 - SN3806; ConvF(6.14, 6.54, 6.73) @ 2535 MHz; Calibrated: 2025/9/11
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE3 Sn428; Calibrated: 2025/9/8
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Type: QD 000 P40 CD; Serial: xxxx
- DASY52 52.10.3(1513); SEMCAD X 14.6.13(7474)

Area Scan (9x10x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 1.12 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 2.540 V/m; Power Drift = 0.89 dB


Peak SAR (extrapolated) = 1.96 W/kg

SAR(1 g) = 1.01 W/kg; SAR(10 g) = 0.477 W/kg

Smallest distance from peaks to all points 3 dB below = 10.2 mm

Ratio of SAR at M2 to SAR at M1 = 53.8%

Maximum value of SAR (measured) = 1.15 W/kg





LTE B12_Back Side_0mm

DUT: Smart POS Terminal

Communication System: UID 0, Generic LTE (0); Communication System Band: Band 12, E-UTRA/FDD (698.0 - 716.0 MHz); Frequency: 707.5 MHz; Communication System PAR: 0 dB; PMF: 1

Medium parameters used (interpolated): $f = 707.5$ MHz; $\sigma = 0.89$ S/m; $\epsilon_r = 42.75$; $\rho = 1000$ kg/m³

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: EX3DV4 - SN3806; ConvF(8.35, 8.89, 9.14) @ 707.5 MHz; Calibrated: 2025/9/11
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0$, 31.0
- Electronics: DAE3 Sn428; Calibrated: 2025/9/8
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Type: QD 000 P40 CD; Serial: xxxx
- DASY52 52.10.3(1513); SEMCAD X 14.6.13(7474)

Area Scan (9x10x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 1.01 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 21.65 V/m; Power Drift = 1.44 dB


Peak SAR (extrapolated) = 2.12 W/kg

SAR(1 g) = 0.966 W/kg; SAR(10 g) = 0.517 W/kg

Smallest distance from peaks to all points 3 dB below = 9.6 mm

Ratio of SAR at M2 to SAR at M1 = 49.9%

Maximum value of SAR (measured) = 1.11 W/kg





LTE B13_Back Side_0mm

DUT: Smart POS Terminal

Communication System: UID 0, Generic LTE (0); Communication System Band: Band 13, E-UTRA/FDD (777.0 - 787.0 MHz); Frequency: 782 MHz; Communication System PAR: 0 dB; PMF: 1

Medium parameters used (interpolated): $f = 782$ MHz; $\sigma = 0.91$ S/m; $\epsilon_r = 42.07$; $\rho = 1000$ kg/m³

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: EX3DV4 - SN3806; ConvF(8.35, 8.89, 9.14) @ 782 MHz; Calibrated: 2025/9/11
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE3 Sn428; Calibrated: 2025/9/8
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Type: QD 000 P40 CD; Serial: xxxx
- DASY52 52.10.3(1513); SEMCAD X 14.6.13(7474)

Area Scan (9x10x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.617 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 21.24 V/m; Power Drift = 3.30 dB


Peak SAR (extrapolated) = 1.64 W/kg

SAR(1 g) = 0.723 W/kg; SAR(10 g) = 0.411 W/kg

Smallest distance from peaks to all points 3 dB below = 9.3 mm

Ratio of SAR at M2 to SAR at M1 = 50.3%

Maximum value of SAR (measured) = 0.811 W/kg





LTE B17_Back Side_0mm

DUT: Smart POS Terminal

Communication System: UID 0, Generic LTE (0); Communication System Band: Band 17, E-UTRA/FDD (704.0 - 716.0 MHz); Frequency: 709 MHz; Communication System PAR: 0 dB; PMF: 1

Medium parameters used (interpolated): $f = 709$ MHz; $\sigma = 0.91$ S/m; $\epsilon_r = 42.24$; $\rho = 1000$ kg/m³

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: EX3DV4 - SN3806; ConvF(8.35, 8.89, 9.14) @ 709 MHz; Calibrated: 2025/9/11
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE3 Sn428; Calibrated: 2025/9/8
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Type: QD 000 P40 CD; Serial: xxxx
- DASYS 52.10.3(1513); SEMCAD X 14.6.13(7474)

Area Scan (9x10x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.695 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 22.19 V/m; Power Drift = 3.19 dB


Peak SAR (extrapolated) = 1.79 W/kg

SAR(1 g) = 0.787 W/kg; SAR(10 g) = 0.460 W/kg

Smallest distance from peaks to all points 3 dB below = 8 mm

Ratio of SAR at M2 to SAR at M1 = 44.6%

Maximum value of SAR (measured) = 0.857 W/kg





LTE B25_Back Side_0mm

DUT: Smart POS Terminal

Communication System: UID 0, Generic LTE (0); Communication System Band: Band 25, E-UTRA/FDD (1850.0 - 1915.0 MHz); Frequency: 1905 MHz; Communication System PAR: 0 dB; PMF: 1

Medium parameters used (interpolated): $f = 1905$ MHz; $\sigma = 1.40$ S/m; $\epsilon_r = 39.87$; $\rho = 1000$ kg/m³

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: EX3DV4 - SN3806; ConvF(6.85, 7.3, 7.51) @ 1905 MHz; Calibrated: 2025/9/11
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0$, 31.0
- Electronics: DAE3 Sn428; Calibrated: 2025/9/8
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Type: QD 000 P40 CD; Serial: xxxx
- DASY52 52.10.3(1513); SEMCAD X 14.6.13(7474)

Area Scan (9x10x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.653 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 3.057 V/m; Power Drift = -1.68 dB


Peak SAR (extrapolated) = 1.98 W/kg

SAR(1 g) = 0.760 W/kg; SAR(10 g) = 0.308 W/kg

Smallest distance from peaks to all points 3 dB below = 8.8 mm

Ratio of SAR at M2 to SAR at M1 = 44.4%

Maximum value of SAR (measured) = 0.798 W/kg





LTE B26_Back Side_0mm

DUT: Smart POS Terminal

Communication System: UID 0, Generic LTE (0); Communication System Band: Band 26, E-UTRA/FDD (814.0 - 849.0 MHz); Frequency: 821.5 MHz; Communication System PAR: 0 dB; PMF: 1

Medium parameters used (interpolated): $f = 821.5$ MHz; $\sigma = 0.89$ S/m; $\epsilon_r = 42.16$; $\rho = 1000$ kg/m³

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: EX3DV4 - SN3806; ConvF(8.2, 8.73, 8.98) @ 821.5 MHz; Calibrated: 2025/9/11
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE3 Sn428; Calibrated: 2025/9/8
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Type: QD 000 P40 CD; Serial: xxxx
- DASYS 52.10.3(1513); SEMCAD X 14.6.13(7474)

Area Scan (9x10x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.724 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 22.04 V/m; Power Drift = -0.78 dB


Peak SAR (extrapolated) = 2.00 W/kg

SAR(1 g) = 0.875 W/kg; SAR(10 g) = 0.473 W/kg

Smallest distance from peaks to all points 3 dB below = 10.1 mm

Ratio of SAR at M2 to SAR at M1 = 48.1%

Maximum value of SAR (measured) = 1.02 W/kg





LTE B41_Back Side_0mm

DUT: Smart POS Terminal

Communication System: UID 0, Generic LTE (0); Communication System Band: Band 41, E-UTRA/TDD

(2496.0 - 2690.0 MHz); Frequency: 2506 MHz; Communication System PAR: 0 dB; PMF: 1

Medium parameters used (interpolated): $f = 2506$ MHz; $\sigma = 1.84$ S/m; $\epsilon_r = 39.81$; $\rho = 1000$ kg/m³

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: EX3DV4 - SN3806; ConvF(6.14, 6.54, 6.73) @ 2506 MHz; Calibrated: 2025/9/11
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE3 Sn428; Calibrated: 2025/9/8
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Type: QD 000 P40 CD; Serial: xxxx
- DASY52 52.10.3(1513); SEMCAD X 14.6.13(7474)

Area Scan (9x10x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.692 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 1.15 V/m; Power Drift = -0.15 dB


Peak SAR (extrapolated) = 2.42 W/kg

SAR(1 g) = 0.922 W/kg; SAR(10 g) = 0.345 W/kg

Smallest distance from peaks to all points 3 dB below = 9.6 mm

Ratio of SAR at M2 to SAR at M1 = 43.3%

Maximum value of SAR (measured) = 1.12 W/kg





LTE B66_Back Side_0mm

DUT: Smart POS Terminal

Communication System: UID 0, Generic LTE (0); Communication System Band: Band 66, E-UTRA/FDD

(1920.0 - 1980.0 MHz); Frequency: 1770 MHz; Communication System PAR: 0 dB; PMF: 1

Medium parameters used (interpolated): $f = 1770$ MHz; $\sigma = 1.36$ S/m; $\epsilon_r = 41.25$; $\rho = 1000$ kg/m³

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: EX3DV4 - SN3806; ConvF(7.06, 7.52, 7.74) @ 1770 MHz; Calibrated: 2025/9/11
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0$, 31.0
- Electronics: DAE3 Sn428; Calibrated: 2025/9/8
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Type: QD 000 P40 CD; Serial: xxxx
- DASY52 52.10.3(1513); SEMCAD X 14.6.13(7474)

Area Scan (9x10x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.506 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 6.135 V/m; Power Drift = 3.45 dB


Peak SAR (extrapolated) = 1.88 W/kg

SAR(1 g) = 0.728 W/kg; SAR(10 g) = 0.323 W/kg

Smallest distance from peaks to all points 3 dB below = 9.3 mm

Ratio of SAR at M2 to SAR at M1 = 43.1%

Maximum value of SAR (measured) = 0.842 W/kg



**LTE B71_Back Side_0mm****DUT: Smart POS Terminal**

Communication System: UID 0, Generic LTE (0); Communication System Band: Band 71, E-UTRA/FDD (663.0 - 698.0 MHz); Frequency: 680.5 MHz; Communication System PAR: 0 dB; PMF: 1

Medium parameters used (interpolated): $f = 680.5$ MHz; $\sigma = 0.90$ S/m; $\epsilon_r = 42.36$; $\rho = 1000$ kg/m³

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: EX3DV4 - SN3806; ConvF(8.35, 8.89, 9.14) @ 680.5 MHz; Calibrated: 2025/9/11
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE3 Sn428; Calibrated: 2025/9/8
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Type: QD 000 P40 CD; Serial: xxxx
- DASYS 52.10.3(1513); SEMCAD X 14.6.13(7474)

Area Scan (9x10x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 1.04 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 26.15 V/m; Power Drift = 2.51 dB


Peak SAR (extrapolated) = 2.85 W/kg

SAR(1 g) = 1.21 W/kg; SAR(10 g) = 0.697 W/kg

Smallest distance from peaks to all points 3 dB below = 9.6 mm

Ratio of SAR at M2 to SAR at M1 = 48.3%

Maximum value of SAR (measured) = 1.37 W/kg





2.4G WLAN_Rear Face_0mm

DUT: Smart POS Terminal

Communication System: UID 0, WLAN 2.4G (0); Communication System Band: 2.4G BW20; Frequency: 2437 MHz; Communication System PAR: 0 dB; PMF: 1.12202e-005

Medium parameters used (interpolated): $f = 2437$ MHz; $\sigma = 1.78$ S/m; $\epsilon_r = 39.86$; $\rho = 1000$ kg/m³

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: EX3DV4 - SN3806; ConvF(6.3, 6.71, 6.9) @ 2437 MHz; Calibrated: 2025/9/11
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE3 Sn428; Calibrated: 2025/9/8
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Type: QD 000 P40 CD; Serial: xxxx
- DASY52 52.10.3(1513); SEMCAD X 14.6.13(7474)

Area Scan (9x10x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.183 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 3.930 V/m; Power Drift = -1.60 dB


Peak SAR (extrapolated) = 0.321 W/kg

SAR(1 g) = 0.166 W/kg; SAR(10 g) = 0.085 W/kg

Smallest distance from peaks to all points 3 dB below = 10.8 mm

Ratio of SAR at M2 to SAR at M1 = 50.6%

Maximum value of SAR (measured) = 0.187 W/kg





BT_Rear Face_0mm

DUT: Smart POS Terminal

Communication System: UID 0, BT (0); Communication System Band: BT; Frequency: 2441

MHz; Communication System PAR: 0 dB; PMF: 1.12202e-005

Medium parameters used (interpolated): $f = 2441$ MHz; $\sigma = 1.77$ S/m; $\epsilon_r = 39.90$; $\rho = 1000$ kg/m³

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: EX3DV4 - SN3806; ConvF(6.3, 6.71, 6.9) @ 2441 MHz; Calibrated: 2025/9/11
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE3 Sn428; Calibrated: 2025/9/8
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Type: QD 000 P40 CD; Serial: xxxx
- DASY52 52.10.3(1513); SEMCAD X 14.6.13(7474)

Area Scan (9x10x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.0363 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 1.019 V/m; Power Drift = 2.70 dB


Peak SAR (extrapolated) = 0.0860 W/kg

SAR(1 g) = 0.034 W/kg; SAR(10 g) = 0.018 W/kg

Smallest distance from peaks to all points 3 dB below = 10.1 mm

Ratio of SAR at M2 to SAR at M1 = 52.2%

Maximum value of SAR (measured) = 0.0451 W/kg





5.2G WLAN_Rear Face_0mm

DUT: Smart POS Terminal

Communication System: UID 0, WLAN 5G (0); Communication System Band: 5G 20M; Frequency: 5180 MHz; Communication System PAR: 0 dB; PMF: 1.12202e-005

Medium parameters used (interpolated): $f = 5180$ MHz; $\sigma = 4.64$ S/m; $\epsilon_r = 37.22$; $\rho = 1000$ kg/m³

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: EX3DV4 - SN3806; ConvF(4.96, 5.28, 5.44) @ 5180 MHz; Calibrated: 2025/9/11
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE3 Sn428; Calibrated: 2025/9/8
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Type: QD 000 P40 CD; Serial: xxxx
- DASY52 52.10.3(1513); SEMCAD X 14.6.13(7474)

Area Scan (17x19x1): Measurement grid: $dx=8$ mm, $dy=8$ mm

Maximum value of SAR (measured) = 0.139 W/kg

Zoom Scan (7x7x12)/Cube 0: Measurement grid: $dx=4$ mm, $dy=4$ mm, $dz=2$ mm

Reference Value = 3.6 V/m; Power Drift = 1.48 dB


Peak SAR (extrapolated) = 0.404 W/kg

SAR(1 g) = 0.153 W/kg; SAR(10 g) = 0.048 W/kg

Smallest distance from peaks to all points 3 dB below = 8 mm

Ratio of SAR at M2 to SAR at M1 = 34.1%

Maximum value of SAR (measured) = 0.194 W/kg



**5.3G WLAN_Rear Face_0mm****DUT: Smart POS Terminal**

Communication System: UID 0, WLAN 5G (0); Communication System Band: 5G 20M; Frequency: 5320 MHz; Communication System PAR: 0 dB; PMF: 1.12202e-005

Medium parameters used (interpolated): $f = 5320$ MHz; $\sigma = 4.76$ S/m; $\epsilon_r = 36.26$; $\rho = 1000$ kg/m³

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: EX3DV4 - SN3806; ConvF(4.96, 5.28, 5.44) @ 5320 MHz; Calibrated: 2025/9/11
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE3 Sn428; Calibrated: 2025/9/8
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Type: QD 000 P40 CD; Serial: xxxx
- DASY52 52.10.3(1513); SEMCAD X 14.6.13(7474)

Area Scan (17x19x1): Measurement grid: $dx=8$ mm, $dy=8$ mm

Maximum value of SAR (measured) = 0.161 W/kg

Zoom Scan (7x7x12)/Cube 0: Measurement grid: $dx=4$ mm, $dy=4$ mm, $dz=2$ mm

Reference Value = 2.65 V/m; Power Drift = 2.75 dB


Peak SAR (extrapolated) = 0.498 W/kg

SAR(1 g) = 0.167 W/kg; SAR(10 g) = 0.050 W/kg

Smallest distance from peaks to all points 3 dB below = 8 mm

Ratio of SAR at M2 to SAR at M1 = 48.3%

Maximum value of SAR (measured) = 0.205 W/kg



**5.6G WLAN_Rear Face_0mm****DUT: Smart POS Terminal**

Communication System: UID 0, WLAN 5G (0); Communication System Band: 5G 20M; Frequency: 5500MHz; Communication System PAR: 0 dB; PMF: 1.12202e-005

Medium parameters used: $f = 5500$ MHz; $\sigma = 4.97$ S/m; $\epsilon_r = 35.91$; $\rho = 1000$ kg/m³

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: EX3DV4 - SN3806; ConvF(4.57, 4.87, 5.01) @ 5500MHz; Calibrated: 2025/9/11
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0$, 31.0
- Electronics: DAE3 Sn428; Calibrated: 2025/9/8
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Type: QD 000 P40 CD; Serial: xxxx
- DASY52 52.10.3(1513); SEMCAD X 14.6.13(7474)

Area Scan (17x19x1): Measurement grid: $dx=8$ mm, $dy=8$ mm

Maximum value of SAR (measured) = 0.0824 W/kg

Zoom Scan (7x7x12)/Cube 0: Measurement grid: $dx=4$ mm, $dy=4$ mm, $dz=2$ mm

Reference Value = 2.61 V/m; Power Drift = -3.43 dB


Peak SAR (extrapolated) = 0.342 W/kg

SAR(1 g) = 0.113 W/kg; SAR(10 g) = 0.037 W/kg

Smallest distance from peaks to all points 3 dB below = 8.6 mm

Ratio of SAR at M2 to SAR at M1 = 37.5%

Maximum value of SAR (measured) = 0.142 W/kg



**5.8G WLAN_Rear Face_0mm****DUT: Smart POS Terminal**

Communication System: UID 0, WLAN 5G (0); Communication System Band: 5G 20M; Frequency: 5785

MHz; Communication System PAR: 0 dB; PMF: 1.12202e-005

Medium parameters used (interpolated): $f = 5785$ MHz; $\sigma = 5.26$ S/m; $\epsilon_r = 35.00$; $\rho = 1000$ kg/m³

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: EX3DV4 - SN3806; ConvF(4.59, 4.89, 5.03) @ 5785 MHz; Calibrated: 2025/9/11
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0$, 31.0
- Electronics: DAE3 Sn428; Calibrated: 2025/9/8
- Phantom: Twin-SAM V5.0 (30deg probe tilt); Type: QD 000 P40 CD; Serial: xxxx
- DASY52 52.10.3(1513); SEMCAD X 14.6.13(7474)

Area Scan (17x19x1): Measurement grid: $dx=8$ mm, $dy=8$ mm

Maximum value of SAR (measured) = 0.0846 W/kg

Zoom Scan (7x7x12)/Cube 0: Measurement grid: $dx=4$ mm, $dy=4$ mm, $dz=2$ mm

Reference Value = 1.99 V/m; Power Drift = 0.89 dB


Peak SAR (extrapolated) = 0.392 W/kg

SAR(1 g) = 0.135 W/kg; SAR(10 g) = 0.043 W/kg

Smallest distance from peaks to all points 3 dB below = 8.6 mm

Ratio of SAR at M2 to SAR at M1 = 57.9%

Maximum value of SAR (measured) = 0.175 W/kg





Appendix C. Probe Calibration and Dipole Calibration Report

Refer the appendix Calibration Report.

※※※※END OF THE REPORT※※※※