

[illegible]

WAG-F-LBG0-00-032 Specification

1. Explanation of part number :

WAG F LBG0 00 032
(1) (2) (3) (4) (5)

(1) Product Type: Wireless Antenna

(2) Material: FPCB

(3) Frequency : 1575.42MHz ,2400-2500MHz, 5150-5850MHz

(4) Coaxial Cable Type : no cable

(5) Suffix :032

2. Storage Condition:

Temperature -40 to +85°C
Humidity 20 to 65 %RH

Recommended storage condition:

Store in room condition as listed below: Temperature -20°C~+45°C, Humidity 80% Max.

3. Operating Condition:

Temperature -40 to +85°C
Humidity 10 to 85 %RH

4. Electrical Specification :

Those specifications were specially defined for GH6573 model, and all characteristics were measured in the customer's machine. .

4-1. Frequency Band:

Frequency Band	MHz
GPS/WIFI	1575.42,2400-2500,5150-5850

4-2. Impedance

50 ohm nominal

UNLESS OTHER SPECIFIED TOLERANCES ON:

X=± X.X=± X.XX=±

ANGLES=± HOLEDIA=±

SCALE: UNIT: mm

DRAWN BY: 王婷 CHECKED BY: 张涛

DESIGNED BY: 吴振江 APPROVED BY: 范东亚

TITLE: WAG-F-LBG0-00-032 Specification



INPAQ TECHNOLOGY CO., LTD.

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION


DOCUMENT
NO.

PAGE REV.
A0

4-3. Matching

四合一天线版本：V1
四合一天线匹配：
GPS/WIFI2.4G:并10nh串0欧姆并0.3pf
WIFI5G:串1.0nh

4-4. VSWR

Frequency Band	1575	2400	2500	5150	5850		
4-4-1. Typical Value:	≤ 2.0	≤ 3.0	≤ 3.5	≤ 3.0	≤ 3.0		
4-4-2. Measuring Method	1. A 50Ωcoaxial cable is connected to the pcb antenna. Then this cable is connected to a network analyzer to measure the VSWR. 2. Keeping this jig away from metal at least 20 cm.						
4-4-3. Picture							

UNLESS OTHER SPECIFIED TOLERANCES ON:

X=± X.X=± X.XX=±

ANGLES=± HOLEDIA=±

SCALE: UNIT: mm

DRAWN BY: 王婷 CHECKED BY: 张涛

DESIGNED BY: 吴振江 APPROVED BY: 范东亚

TITLE: WAG-F-LBG0-00-032 Specification




INPAQ TECHNOLOGY CO., LTD.

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

DOCUMENT NO.

PAGE REV.
A0



UNLESS OTHER SPECIFIED TOLERANCES ON:

X=± X.X=± X.XX=±
ANGLES=± HOLEDIA=±

SCALE: UNIT: mm

DRAWN BY: 王婷 CHECKED BY: 张涛

DESIGNED BY: 吴振江 APPROVED BY: 范东亚

TITLE: WAG-F-LBG0-00-032 Specification



INPAQ TECHNOLOGY CO., LTD.

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

DOCUMENT
NO.

PAGE REV.
A0

4-5. Efficiency and Gain

4-5.1 Measuring equipment

Measuring instrument:


Microwave chamber, Network analyzer, and standard antenna.

Instructions for microwave chamber:

This is a microwave chamber set up by our company in Suzhou, This microwave chamber belongs to a set of near-field measurement system. The size of the chamber is 2.95M * 3M * 3M.



RayZone2800 Test Setup



The microwave chamber, shown above, using a unique multi-probe technique, The aim is to reduce the measurement time of the whole measurement system. The measuring system use multi-probe array instead of single probe to scan the measured surface of the antenna under test, a single probe has the capability of measuring orthogonal polarization amplitude and phase, it also has a wide frequency range, the corresponding multi-probe array is switched quickly by electronic switch, greatly improved the measurement efficiency.

The probe model: MA186960A(400MHz~7.5GHz) . Because of its capability of broadband frequency and the orthogonal polarization function, the number of probes needed to be equipped with the system is reduced; The small size of the probe reduces the coupling between the probes, make it is possible to insert probes of other frequency bands between probes, then a single system can support a wider frequency range.

UNLESS OTHER SPECIFIED TOLERANCES ON: X=± X.X=± X.XX=± ANGLES=± HOLEDIA=±			INPAQ TECHNOLOGY CO., LTD.
SCALE:	UNIT: mm		
DRAWN BY: 王婷	CHECKED BY: 张涛	THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION	
DESIGNED BY: 吴振江	APPROVED BY: 范东亚		
TITLE: WAG-F-LBG0-00-032 Specification		DOCUMENT NO.	PAGE REV. A0

4-5.2 Efficiency and Gain

GPS/WIFI2.4G			
FS			
Frequency (MHz)	Efficiency (dB)	Efficiency (%)	Gain (dBi)
1570	-4.6	34.7	-1.6
1571	-4.6	34.7	-1.6
1572	-4.6	34.7	-1.6
1573	-4.6	34.6	-1.6
1574	-4.6	34.6	-1.6
1575	-4.6	34.5	-1.6
1575.42	-4.6	34.5	-1.6
1576	-4.6	34.6	-1.6
1577	-4.6	34.7	-1.6
1578	-4.6	34.7	-1.6
1579	-4.6	34.8	-1.6
1580	-4.6	34.9	-1.6
2400	-4.1	39.2	0.1
2410	-3.9	40.4	0.1
2420	-4.3	36.8	-0.4
2430	-4.5	35.3	-0.7
2440	-4.4	36.2	-0.7
2450	-4.6	34.8	-1.0
2460	-4.6	34.7	-1.0
2470	-4.6	34.3	-1.0
2480	-4.8	32.8	-1.3
2490	-4.9	32.4	-1.3
2500	-5.0	31.9	-1.5
WIFI5G			
FS			
Frequency (MHz)	Efficiency (dB)	Efficiency (%)	Gain (dBi)
5150	-5.5	28.5	-1.0
5200	-5.0	31.6	-0.2
5250	-4.8	33.2	0.3
5300	-4.7	33.7	0.4
5350	-4.7	33.8	0.3
5400	-4.9	32.0	-0.8
5450	-5.1	30.6	-0.7
5500	-5.6	27.6	-1.3
5550	-5.2	30.5	-1.0
5600	-5.3	29.4	-0.5
5650	-5.5	28.0	0.0
5700	-5.4	29.0	0.2
5750	-5.2	30.1	0.5
5800	-4.9	32.6	0.7
5850	-5.0	31.9	0.4

UNLESS OTHER SPECIFIED TOLERANCES ON:

X=± X.X=± X.XX=±

ANGLES=± HOLEDIA=±

SCALE: UNIT: mm

DRAWN BY: 王婷 CHECKED BY: 张涛

DESIGNED BY: 吴振江 APPROVED BY: 范东亚

TITLE: WAG-F-LBG0-00-032 Specification



INPAQ TECHNOLOGY CO., LTD.


THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

DOCUMENT
NO.


PAGE REV.
A0

5. Antenna 3D Radiation Pattern:


-GPS



-WIFI 2.4G



-WIFI 5G



UNLESS OTHER SPECIFIED TOLERANCES ON:

X=± X.X=± X.XX=±
ANGLES=± HOLEDIA=±

SCALE: UNIT: mm

DRAWN BY: 王婷 CHECKED BY: 张涛

DESIGNED BY: 吴振江 APPROVED BY: 范东亚

TITLE: WAG-F-LBG0-00-032 Specification




INPAQ TECHNOLOGY CO., LTD.

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

DOCUMENT
NO.

PAGE REV.
A0

6. Mechanical Specification:



UNLESS OTHER SPECIFIED TOLERANCES ON: X=± X.X=± X.XX=± ANGLES=± HOLEDIA=±		 INPAQ TECHNOLOGY CO., LTD.
SCALE:	UNIT: mm	
DRAWN BY: 王婷	CHECKED BY: 张涛	THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION
DESIGNED BY: 吴振江	APPROVED BY: 范东亚	
TITLE: WAG-F-LBG0-00-032 Specification		DOCUMENT NO.
		PAGE REV. A0