




SAR Test Report

For

Applicant Name: FOXX Development Inc.
Address: 3480 Preston Ridge Road, Suite500, Alpharetta, GA 30005, USA
EUT Name: Smart Phone
Brand Name: MIRO, FOXX, FOXXD, AIRVOICE, FOXXD HTH
Model Number: C69M

Issued By

Company Name: BTF Testing Lab (Shenzhen) Co., Ltd.
Address: 101/201/301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Subdistrict, Bao'an District, Shenzhen, China
Report Number: BTF250821R00401
Test Standards: FCC 47 CFR§2.1093 IEEE Std. 1528-2013
IEEE C95.1-2019
FCC ID: 2AQRM-C69M
Test Conclusion: Pass
Test Date: 2025-08-23 to 2025-09-07
Date of Issue: 2025-09-08
Tested By: 
Kris Li / Tester
Date: 2025-09-08
Prepared By: 
Amenda Zhong / Project Engineer
Date: 2025-09-08
Approved By: 
Ryan.CJ / EMC Manager
Date: 2025-09-08



Note: All the test results in this report only related to the testing samples. Which can be duplicated completely for the legal use with approval of applicant; it shall not be reproduced except in full without the written approval of BTF Testing Lab (Shenzhen) Co., Ltd., All the objections should be raised within thirty days from the date of issue. To validate the report, you can contact us.

Revision History		
Version	Issue Date	Revisions Content
R_V0	2025-09-08	Original
Note:		Once the revision has been made, then previous versions reports are invalid.

Table of Contents

1. Introduction	4
1.1 Identification of Testing Laboratory	4
1.2 Identification of the Responsible Testing Location	4
1.3 Laboratory Condition	4
1.4 Announcement	4
2. Product Information	5
2.1 Application Information	5
2.2 Manufacturer Information	5
2.3 Factory Information	5
2.4 General Description of Equipment under Test (EUT)	5
2.5 Equipment under Test Ancillary Equipment	5
2.6 Technical Information	5
3. Summary of Test Results	7
3.1 Test Standards	7
3.2 Device Category and SAR Limit	7
3.3 Test Result Summary	8
3.4 Test Uncertainty	9
4. Measurement System	11
4.1 Specific Absorption Rate (SAR) Definition	11
4.2 MVG SAR System	11
5. System Verification	16
5.1 Purpose of System Check	16
5.2 System Check Setup	16
6. TEST POSITION CONFIGURATIONS	17
6.1 Head Exposure Conditions	17
6.2 Body-worn Position Conditions	19
6.3 Hotspot Mode Exposure Position Conditions	20
6.4 Product Specific 10g Exposure Consideration	20
7. Measurement Procedure	21
7.1 Measurement Process Diagram	21
7.2 SAR Scan General Requirement	22
7.3 Measurement Procedure	23
7.4 Area & Zoom Scan Procedure	23
8. Conducted RF Output Power	24
8.1 GSM	24
8.2 WCDMA	25
8.3 LTE	26
8.4 Wi-Fi	40
8.5 Bluetooth	41
9. Test Exclusion Consideration	42
9.1 SAR Test Exclusion Consideration Table	42
10. Test Result	43
11. SAR Measurement Variability	50
12. Simultaneous Transmission	51
12.1 Simultaneous Transmission Mode Considerations	51
12.2 Sum SAR of Simultaneous Transmission	51
13. Test Equipment List	52
ANNEX A Simulating Liquid Verification Result	53
ANNEX B System Check Result	53
ANNEX C Test Data	74
ANNEX D SAR Test Setup Photos	154
ANNEX E EUT External and Internal Photos	156
ANNEX F Calibration Information	156

1. Introduction

1.1 Identification of Testing Laboratory

Company Name:	BTF Testing Lab (Shenzhen) Co., Ltd.
Address:	101/201/301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Subdistrict, Bao'an District, Shenzhen, China
Phone Number:	+86-0755-23146130
Fax Number:	+86-0755-23146130

1.2 Identification of the Responsible Testing Location

Test Location:	BTF Testing Lab (Shenzhen) Co., Ltd.
Address:	101/201/301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Subdistrict, Bao'an District, Shenzhen, China
Description:	All measurement facilities used to collect the measurement data are located at 101/201/301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Subdistrict, Bao'an District, Shenzhen, China
FCC Registration Number	518915
Designation Number	CN1409

1.3 Laboratory Condition

Ambient Temperature:	21°C to 25°C
Ambient Relative Humidity:	48% to 59%
Ambient Pressure:	100 kPa to 102 kPa

1.4 Announcement

- (1) The test report reference to the report template version v0.
- (2) The test report is invalid if not marked with the signatures of the persons responsible for preparing, reviewing and approving the test report.
- (3) The test report is invalid if there is any evidence and/or falsification.
- (4) This document may not be altered or revised in any way unless done so by BTF and all revisions are duly noted in the revisions section.
- (5) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.
- (6) The laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant.

2. Product Information

2.1 Application Information

Company Name:	FOXX Development Inc.
Address:	3480 Preston Ridge Road, Suite500, Alpharetta, GA 30005, USA

2.2 Manufacturer Information

Company Name:	FOXX Development Inc.
Address:	3480 Preston Ridge Road, Suite500, Alpharetta, GA 30005, USA

2.3 Factory Information

Company Name:	FOXX Development Inc.
Address:	3480 Preston Ridge Road, Suite500, Alpharetta, GA 30005, USA

2.4 General Description of Equipment under Test (EUT)

EUT Name	Smart Phone
Under Test Model Name	C69M
Sample No.	BTFSN250821002

2.5 Equipment under Test Ancillary Equipment

Ancillary Equipment 1	Rechargeable Battery	
	Capacity	5000mAh
	Nominal Voltage	3.87V

2.6 Technical Information

Network and Wireless connectivity	2G Network GSM/GPRS/EGPRS 850/1900 3G Network WCDMA/HSDPA/HSUPA Band 2/4/5 4G Network FDD LTE Band 2/4/5/12/13/25/66/71 TDD LTE Band 41 2.4G WIFI 802.11b, 802.11g, 802.11n(HT20/40) 5G WIFI 802.11a, 802.11n(HT20/40), 802.11ac(VHT20/40/80) BT (EDR+BLE)
-----------------------------------	---

The requirement for the following technical information of the EUT was tested in this report:

Operating Mode	GSM, WCDMA, LTE, WLAN, Bluetooth		
Frequency Range	GSM 850	TX: 824 ~ 849 MHz	RX: 869 ~ 894 MHz
	GSM 1900	TX: 1850 ~ 1910 MHz	RX: 1930 ~ 1990 MHz
	WCDMA Band 2	TX: 1850 ~ 1910 MHz	RX: 1930 ~ 1990 MHz
	WCDMA Band 4	TX: 1710 ~ 1755 MHz	RX: 2110 ~ 2155 MHz
	WCDMA Band 5	TX: 824 ~ 849 MHz	RX: 869 ~ 894 MHz
	LTE Band 2	TX: 1850 ~ 1910 MHz	RX: 1930 ~ 1990 MHz
	LTE Band 4	TX: 1710 ~ 1755 MHz	RX: 2110 ~ 2155 MHz
	LTE Band 5	TX: 824 ~ 849 MHz	RX: 869 ~ 894 MHz
	LTE Band 12	TX: 698 ~ 716 MHz	RX: 728 ~ 746 MHz
	LTE Band 13	TX: 777 ~ 787 MHz	RX: 746 ~ 756 MHz
	LTE Band 25	TX: 1850 ~ 1915 MHz	RX: 1930 ~ 1995 MHz
	LTE Band 41	2496 ~ 2690 MHz	
	LTE Band 66	TX: 1710 ~ 1780 MHz	RX: 2110 ~ 2200 MHz
	LTE Band 71	TX: 663 ~ 698 MHz	RX: 617 ~ 652 MHz
	802.11b/g/n(HT20)	2412 ~ 2462 MHz	
	802.11n(HT40)	2422 ~ 2452 MHz	
	802.11a /802.11n(HT20/40) /802.11ac(HT20/40/80)	U-NII-1: 5180 MHz ~ 5240 MHz, U-NII-2A: 5260 MHz ~ 5320 MHz, U-NII-2C: 5500 MHz ~ 5700 MHz, U-NII-3: 5745 MHz ~ 5825 MHz	
	Bluetooth	2402 ~ 2480 MHz	
Antenna Type	WWAN: PIFA Antenna WLAN: PIFA Antenna BT: PIFA Antenna		
Hotspot Function	Support		
Power Reduction	Not Support		
Exposure Category	General Population/Uncontrolled exposure		
EUT Stage	Portable Device		
Product	Type		
	☐ Production unit	☒ Identical prototype	

3. Summary of Test Results

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 2.1093	Radiofrequency radiation exposure evaluation: portable devices
2	IEEE Std. 1528-2013	Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques
3	IEEE C95.1-2019	IEEE Standard for Safety Levels with Respect to Human Exposure to Electric, Magnetic, and Electromagnetic Fields, 0 Hz to 300 GHz
4	KDB447498 D04	Interim General RF Exposure Guidance v01
5	KDB865664 D01	SAR measurement 100MHz to 6GHz v01r04
6	KDB865664 D02	RF Exposure Reporting v01r02
7	KDB941225 D01	3G SAR Procedures v03r01
8	KDB941225 D05	SAR for LTE Devices v02r05
9	KDB248227 D01	802.11 Wi-Fi SAR v02r02
10	KDB941225 D06	Hotspot Mode v02r01
11	KDB648474 D04	Handset SAR v01r03
12	KDB690783 D01	SAR Listings on Grant v01r03

3.2 Device Category and SAR Limit

This device belongs to portable device category because its radiating structure is allowed to be used within 20 centimeters of the body of the user. Limit for General Population/Uncontrolled exposure should be applied for this device, it is 1.6 W/kg as averaged over any 1 gram of tissue.

Body Position	SAR Value (W/Kg)	
	General Population/ Uncontrolled Exposure	Occupational/ Controlled Exposure
Whole-Body SAR (averaged over the entire body)	0.08	0.4
Partial-Body SAR (averaged over any 1 gram of tissue)	1.60	8.0
SAR for hands, wrists, feet and ankles (averaged over any 10 grams of tissue)	4.0	20.0

NOTE:

General Population/Uncontrolled Exposure: Locations where there is the exposure of individuals who have no knowledge or control of their exposure. General population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

Occupational/Controlled Exposure: Locations where there is exposure that may be incurred by persons who are aware of the potential for exposure. In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

3.3 Test Result Summary

The maximum results of Specific Absorption Rate (SAR) found during test as follows:

<Highest Reported standalone SAR Summary>

Exposure Position	Frequency Band	Reported SAR (W/kg)	Equipment Class	Highest Reported SAR (W/kg)
Head 1-g SAR (0 mm Gap)	GSM 850	0.090	PCE	0.878
	GSM 1900	0.093		
	WCDMA Band II	0.666		
	WCDMA Band IV	0.552		
	WCDMA Band V	0.092		
	LTE Band 2	0.855		
	LTE Band 4	0.865		
	LTE Band 5	0.084		
	LTE Band 12	0.042		
	LTE Band 13	0.082		
	LTE Band 25	0.878		
	LTE Band 41	0.330		
	LTE Band 66	0.849		
	LTE Band 71	0.037		
	WLAN 2.4 GHz	0.321	DTS	
	WLAN 5.2 GHz	0.299	NII	
	WLAN 5.4 GHz	0.618		
	WLAN 5.6 GHz	0.087		
WLAN 5.8 GHz	0.108			
Bluetooth	0.005	DSS		
Exposure Position	Frequency Band	Reported SAR (W/kg)	Equipment Class	Highest Reported SAR (W/kg)
Hotspot(Body) 1-g SAR (10 mm Gap)	GSM 850	0.181	PCE	0.767
	GSM 1900	0.256		
	WCDMA Band II	0.470		
	WCDMA Band IV	0.513		
	WCDMA Band V	0.156		
	LTE Band 2	0.428		
	LTE Band 4	0.337		
	LTE Band 5	0.110		
	LTE Band 12	0.126		
	LTE Band 13	0.132		
	LTE Band 25	0.461		
	LTE Band 41	0.151		
	LTE Band 66	0.386		
	LTE Band 71	0.156		
	WLAN 2.4 GHz	0.678	DTS	
	WLAN 5.2 GHz	0.224	NII	
	WLAN 5.4 GHz	0.767		
	WLAN 5.6 GHz	0.476		
	WLAN 5.8 GHz	0.427		
	Bluetooth	0.003	DSS	

This device is in compliance with Specific Absorption Rate(SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC47 CFR part 2(2.1093) and ANSI/IEEE C95.1-2019, and had been tested in accordance with the measurement methods and procedures specified in IEEE Std. 1528-2013.

<Highest Reported Simultaneous SAR>

Exposure Position	Simultaneous Configuration	Highest Reported Simultaneous Transmission SAR (W/kg)	Limit (W/kg)	Verdict
Head 1-g SAR (0 mm Gap)	LTE Band 25 + 5.4G WIFI	1.496	1.6	Pass
Hotspot(Body) 1-g SAR (10 mm Gap)	WCDMA Band IV + 5.4G WIFI	1.280	1.6	Pass

3.4 Test Uncertainty

3.4.1 Measurement uncertainty evaluation for SAR test

Measurement uncertainty evaluation for SAR test (450MHz to 6GHz)

Uncertainty Component	Tol (+-%)	Prob. Dist.	Div.	Unc. $u(x_i)=a(x_i)/q_i$	Ci (1g)	Ci (10g)	1g U_i (+-%)	10 g U_i (+-%)	V_i v_{eff}
Measurement System									
Probe calibration	14	N (k = 2)	2	7.00	1	1	7.00	7.00	∞
Probe calibration drift	4	R	$\sqrt{3}$	2.31	1	1	2.31	2.31	∞
Probe linearity	4.7	R	$\sqrt{3}$	2.71	1	1	2.71	2.71	∞
detection limit	1	R	$\sqrt{3}$	0.58	1	1	0.58	0.58	∞
Probe isotropy	3.5	R	$\sqrt{3}$	2.02	0.71	0.71	1.43	1.43	∞
Hemispherical Isotropy	5.9	N	1	5.90	0.71	0.71	4.19	4.19	∞
Boundary effect	1	R	1.73	0.58	1	1	0.58	0.58	∞
Integration time	1.4	R	1.73	0.81	1	1	0.81	0.81	∞
Response time	0	R	1.73	0.00	1	1	0.00	0.00	∞
Readout electronics	0.5	N	1	0.50	1	1	0.50	0.50	∞
RF ambient and noise	3	R	$\sqrt{3}$	1.73	1	1	1.73	1.73	∞
Probe positioning errors	3.28	N	1	3.28	0.33	0.33	1.08	1.08	∞
Data processing errors	2.3	R	1	1.33	1	1	1.33	1.33	∞
Conductivity measurement	4.07	N	1	2.35	0.79	0.77	1.86	1.81	∞
Permittivity measurement	5.06	N	1	2.92	0.23	0.26	0.67	0.76	∞
Liquid Conductivity - Temperature Uncertainty	2.5	R	1	1.44	0.79	0.77	1.14	1.11	∞
Liquid Permittivity - Temperature Uncertainty	2.5	R	$\sqrt{3}$	1.44	0.23	0.26	0.33	0.38	∞
Shell permittivity	2.9	R	$\sqrt{3}$	1.67	0.25	0.25	0.42	0.42	∞
Repeatability of positioning the DUT or source against the phantom	2.7	N	1	2.70	2	2	5.40	5.40	∞
Uncertainty in accepted power	3	R	1	3.00	1	1	3.00	3.00	∞
Effect of operating mode on probe sensitivity	2.3	R	$\sqrt{3}$	1.33	1	1	1.33	1.33	∞
Variation in SAR due to drift in output of DUT	2.2	N	1	2.20	1	1	2.20	2.20	∞
Phantom deviation from target (ϵ' , σ)	1.9	N	1	1.90	1	1	1.90	1.90	∞
SAR scaling	0	R	$\sqrt{3}$	0.00	1	1	0.00	0.00	∞
Probe calibration	14	N (k = 2)	2	7.00	1	1	7.00	7.00	∞
Combined uncertainty	/						11.94	11.94	
Expanded Uncertainty (95% Confidence interval)	/						23.89	23.88	

* This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3.4.2 Measurement uncertainty evaluation for system check

Uncertainty Component	Tol (+-%)	Prob. Dist.	Div.	Unc. $u(x_i)=a(x_i)/q_i$	Ci (1g)	Ci (10 g)	1g Ui (+-%)	10 g Ui (+-%)	Vi veff
Measurement System									
Probe calibration	14	N (k = 2)	2	7.00	1	1	7.00	7.00	∞
Probe calibration drift	4	R	1.73	2.31	1	1	2.31	2.31	∞
Probe linearity	4.7	R	1.73	2.72	1	1	2.72	2.72	∞
Detection limit	1	R	1.73	0.58	1	1	0.58	0.58	∞
Axial Isotropy	3.5	R	1.73	2.02	1	1	2.02	2.02	∞
Hemispherical Isotropy	5.9	R	1.73	3.41	0.71	0.71	2.42	2.42	∞
Boundary effect	1	R	1.73	0.58	0.71	0.71	0.41	0.41	∞
Integration time	1.4	R	1.73	0.81	1	1	0.81	0.81	∞
Response time	0	R	1.73	0.00	1	1	0.00	0.00	∞
Readout electronics	0.5	N	1	0.50	1	1	0.50	0.50	∞
Noise	3	R	1.73	1.73	1	1	1.73	1.73	∞
Reflections	3	R	1.73	1.73	1	1	1.73	1.73	∞
Positioner Mechanical Tolerance	3.28	R	1.73	1.90	0.33	0.33	0.63	0.63	∞
Positioning with respect to Phantom Shell	3.28	R	1.73	1.90	0.33	0.33	0.63	0.63	∞
Data processing errors	2.3	R	1.73	1.33	1	1	1.33	1.33	∞
Conductivity measurement	4.07	N	1	4.07	0.79	0.77	3.22	3.13	∞
Permittivity measurement	5.06	N	1	5.06	0.23	0.26	1.16	1.32	∞
Liquid Conductivity - Temperature Uncertainty	2.5	R	1.73	1.45	0.79	0.77	1.14	1.11	∞
Liquid Permittivity - Temperature Uncertainty	2.5	R	1.73	1.45	0.23	0.26	0.33	0.38	∞
Shell permittivity	2.9	R	1.73	1.68	0.25	0.25	0.42	0.42	∞
Distance between the radiating element of the DUT and the phantom medium	2.7	N	1	2.70	2	2	5.40	5.40	∞
Deviation of experimental antennas	4.5	N	1.73	2.60	1	1	2.60	2.60	∞
Other uncertainty contributions	2	R	1	2.00	1	1	2.00	2.00	∞
Uncertainty in accepted power	3	R	1.73	1.73	1	1	1.73	1.73	∞
Phantom deviation from target (ϵ', σ)	1.9	N	1	1.90	1	0.87	1.90	1.65	∞
$u(\Delta SAR)$	/						11.89	11.85	
Expanded uncertainty (95% confidence interval)	/						23.79	23.70	

4. Measurement System

4.1 Specific Absorption Rate (SAR) Definition

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$


SAR is expressed in units of Watts per kilogram (W/kg) SAR measurement can be related to the electrical field in the tissue by

$$SAR = \frac{\sigma E^2}{\rho}$$

Where: σ is the conductivity of the tissue,
 ρ is the mass density of the tissue and E is the RMS electrical field strength.

4.2 MVG SAR System

4.2.1 SAR system diagram



4.2.2 Robot



A standard high precision 6-axis robot (Denso) with teaches pendant with Scanning System

- It must be able to scan all the volume of the phantom to evaluate the tridimensional distribution of SAR.
- Must be able to set the probe orthogonal of the surface of the phantom ($\pm 30^\circ$).
- Detects stresses on the probe and stop itself if necessary to keep the integrity of the probe.

4.2.3 E-Field Probe

For the measurements, the Specific Dosimetric SSE2 E-Field Probe with following specifications is used:

- Dynamic range: 0.01-100 W/kg
- Tip diameter: 2mm for SSE2
- Distance between probe tip and sensor centre: 1mm for SSE2
- Distance between sensor centre and the inner phantom surface: 2mm for $f \geq 4\text{GHz}$.
- Probe linearity: $<0.25\text{dB}$.
- Axial Isotropy: $<0.25\text{dB}$.
- Spherical Isotropy: $<0.50\text{dB}$.
- Calibration range: 150 to 6000 MHz for head & body simulating liquid
- Angle between probe axis (evaluation axis) and surface normal line: less than 20° .



4.2.4 Phantoms

SAM Phantom

For the measurements the Specific Anthropomorphic Mannequin (SAM) defined by the IEEE SCC-34/SC2 group is used. The probe scanning of the E-Field is done in the 2 halves of the normalized head. The normalized shape of the phantom corresponds to the dimensions of 90% of an adult head size. It enables the dosimetric evaluation of left and right-hand phone usage and includes an additional flat phantom part for the simplified body performance check. The phantom set-up includes a cover, which prevents the evaporation of the liquid.



SAM Phantom

The thickness of the phantom amounts to $2\text{ mm} \pm 0.2\text{ mm}$. The materials for the phantom do not affect the radiation of the device under test (DUT) : $\epsilon_r' < 5$
The head is filled with tissue simulating liquid. The hand do not have to be modeled.

TWIN SAM phantom			
	Mechanical	Electrical	
Overall thickness	$2 \pm 0.2\text{ mm}$ (except ear area)	Relative permittivity	3.4
Dimensions	1000 mm(L) x 500 mm(W) x 200 mm(H)	Loss tangent	0.02
Maximum volume	27 L		
Material	Fiberglass based		

ELLIPTICAL Phantom

The phantom is for Body performance check filled with tissue-equivalent liquid to a depth of at least 150 mm, whose shell material is resistant to damage or reaction with tissue-equivalent liquid chemicals.




ELLI Phantom

The shape of the phantom is an ellipse with length $600\text{ mm} \pm 5\text{ mm}$ and width $400\text{ mm} \pm 5\text{ mm}$.
The phantom shell is made of low-loss and low-permittivity material, having loss tangent $\tan \delta \leq 0.05$ and relative permittivity:
 $\epsilon_r' \leq 5$ for $f \leq 3\text{ GHz}$
 $3 \leq \epsilon_r' \leq 5$ for $f > 3\text{ GHz}$
The thickness of the bottom-wall of the flat phantom is 2.0 mm with a tolerance of $\pm 0.2\text{ mm}$.

Technical & mechanical characteristics	
Shell thickness	$2\text{ mm} \pm 0.2\text{ mm}$
Filling volume	25 L
Dimensions	600 mm x 400 mm x 200 mm
Permittivity	4.4
Loss tangent	0.017

4.2.5 Device Holder



System Material	Permittivity	Loss tangent
Delrin	3.7	0.005

(The positioning system allows obtaining cheek and tilting position with a very good accuracy. In compliance with CENELEC, the tilt angle uncertainty is lower than 1°.)

System Material	Permittivity	Loss tangent
PMMA	2.9	0.028


4.2.6 Simulating Liquid

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15 cm. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm. The nominal dielectric values of the tissue simulating liquids in the phantom and the tolerance of 5%.

Head Liquid Depth



Body Liquid Depth



The following table gives the recipes for tissue simulating liquid and the theoretical Conductivity/Permittivity.


Head (Reference IEEE1528)								
Frequency (MHz)	Water (%)	Sugar (%)	Cellulose (%)	Salt (%)	Preventol (%)	DGBE (%)	Conductivity σ (S/m)	Permittivity ε
750	41.1	57.0	0.2	1.4	0.2	0	0.89	41.9
835	40.3	57.9	0.2	1.4	0.2	0	0.90	41.5
900	40.3	57.9	0.2	1.4	0.2	0	0.97	41.5
1800, 1900, 2000	55.2	0	0	0.3	0	44.5	1.4	40.0
2450	55.0	0	0	0.1	0	44.9	1.80	39.2
2600	54.9	0	0	0.1	0	45.0	1.96	39.0
Frequency (MHz)	Water (%)	Hexyl Carbitol (%)			Triton X-100 (%)		Conductivity σ (S/m)	Permittivity ε
5200	62.52	17.24			17.24		4.66	36.0
5800	62.52	17.24			17.24		5.27	35.3
Body (From instrument manufacturer)								
Frequency (MHz)	Water (%)	Sugar (%)	Cellulose (%)	Salt (%)	Preventol (%)	DGBE (%)	Conductivity σ (S/m)	Permittivity ε
750	51.7	47.2	0	0.9	0.1	0	0.96	55.5
835	50.8	48.2	0	0.9	0.1	0	0.97	55.2
900	50.8	48.2	0	0.9	0.1	0	1.05	55.0
1800, 1900, 2000	70.2	0	0	0.4	0	29.4	1.52	53.3
2450	68.6	0	0	0.1	0	31.3	1.95	52.7
2600	68.2	0	0	0.1	0	31.7	2.16	52.5
Frequency(MHz)	Water	DGBE (%)			Salt (%)		Conductivity σ (S/m)	Permittivity ε
5200	78.60	21.40			/		5.30	49.00
5800	78.50	21.40			0.1		6.00	48.20

5. System Verification

5.1 Purpose of System Check

The system performance check verifies that the system operates within its specifications. System and operator errors can be detected and corrected. It is recommended that the system performance check be performed prior to any usage of the system in order to guarantee reproducible results. The system performance check uses normal SAR measurements in a simplified setup with a well characterized source. The setup was selected to give a high sensitivity to all parameters that might fail or vary over time. The system check does not intend to replace the calibration of the components, but indicates situations where the system uncertainty is exceeded due to drift or failure.

5.2 System Check Setup



6. TEST POSITION CONFIGURATIONS


According to KDB 648474 D04 Handset, handsets are tested for SAR compliance in head, body-worn accessory and other use configurations described in the following subsections.

6.1 Head Exposure Conditions

Head exposure is limited to next to the ear voice mode operations. Head SAR compliance is tested according to the test positions defined in IEEE Std 1528-2013 using the SAM phantom illustrated as below.


6.1.1 Two Imaginary Lines on the Handset

- The vertical center line passes through two points on the front side of the handset - the midpoint of the width w_t of the handset at the level of the acoustic output, and the midpoint of the width w_b of the bottom of the handset.
- The horizontal line is perpendicular to the vertical center line and passes through the center of the acoustic output. The horizontal line is also tangential to the face of the handset at point A.
- The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical center line is not necessarily parallel to the front face of the handset, especially for clamshell handsets, handsets with flip covers, and other irregularly shaped handsets.




6.1.2 Two Imaginary Lines on the Handset

- To position the device with the vertical center line of the body of the device and the horizontal line crossing the center piece in a plane parallel to the sagittal plane of the phantom. While maintaining the device in this plane, align the vertical center line with the reference plane containing the three ear and mouth reference point (M: Mouth, RE: Right Ear, and LE: Left Ear) and align the center of the ear piece with the line RE-LE.
- To move the device towards the phantom with the ear piece aligned with the line LE-RE until the phone touched the ear. While maintaining the device in the reference plane and maintaining the phone contact with the ear, move the bottom of the phone until any point on the front side is in contact with the cheek of the phantom or until contact with the ear is lost.



6.1.3 Titled Position

- To position the device in the “cheek” position described above.
- While maintaining the device the reference plane described above and pivoting against the ear, moves it outward away from the mouth by an angle of 15 degrees or until contact with the ear is lost.




6.2 Body-worn Position Conditions

Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in KDB 447498 are used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode. When the reported SAR for a body-worn accessory.


Body-worn accessories that do not contain metallic or conductive components may be tested according to worst-case exposure configurations, typically according to the smallest test separation distance required for the group of body-worn accessories with similar operating and exposure characteristics. All body-worn accessories containing metallic components are tested in conjunction with the host device.

Body-worn accessory SAR compliance is based on a single minimum test separation distance for all wireless and operating modes applicable to each body-worn accessory used by the host, and according to the relevant voice and/or data mode transmissions and operations. If a body-worn accessory supports voice only operations in its normal and expected use conditions, testing of data mode for body-worn compliance is not required. A conservative minimum test separation distance for supporting off-the-shelf body-worn accessories that may be acquired by users of consumer handsets is used to test for body-worn accessory SAR compliance. This distance is determined by the handset manufacturer, according to the requirements of Supplement C 01-01. Devices that are designed to operate on the body of users using lanyards and straps, or without requiring additional body-worn accessories, will be tested using a conservative minimum test separation distance ≤ 5 mm to support compliance.



6.3 Hotspot Mode Exposure Position Conditions

For handsets that support hotspot mode operations, with wireless router capabilities and various web browsing functions, the relevant hand and body exposure conditions are tested according to the hotspot SAR procedures in KDB 941225. A test separation distance of 10 mm is required between the phantom and all surfaces and edges with a transmitting antenna located within 25 mm from that surface or edge. When the form factor of a handset is smaller than 9 cm x 5 cm, a test separation distance of 5 mm (instead of 10 mm) is required for testing hotspot mode. When the separation distance required for body-worn accessory testing is larger than or equal to that tested for hotspot mode, in the same wireless mode and for the same surface of the phone, the hotspot mode SAR data may be used to support body-worn accessory SAR compliance for that particular configuration (surface).



6.4 Product Specific 10g Exposure Consideration


According with FCC KDB 648474 D04, for smart phones with a display diagonal dimension > 15.0 cm or an overall diagonal dimension > 16.0 cm that provide similar mobile web access and multimedia support found in mini-tablets or UMPC mini-tablets that support voice calls next to the ear, unless it is confirmed otherwise through KDB inquiries, the following phablet procedures should be applied to evaluate SAR compliance for each applicable wireless modes and frequency band. Devices marketed as phablets, regardless of form factors and operating characteristics must be tested as a phablet to determine SAR compliance;

The UMPC mini-tablet procedures must also be applied to test the SAR of all surfaces and edges with an antenna located at ≤ 25 mm from that surface or edge, in direct contact with a flat phantom, for 10-g extremity SAR according to the body-equivalent tissue dielectric parameters in KDB 865664 to address interactive hand use exposure conditions. The UMPC mini-tablet 1-g SAR at 5 mm is not required. When hotspot mode applies, 10-g extremity SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg.

7. Measurement Procedure

7.1 Measurement Process Diagram

Body SAR



IEC

7.2 SAR Scan General Requirement

Probe boundary effect error compensation is required for measurements with the probe tip closer than half a probe tip diameter to the phantom surface. Both the probe tip diameter and sensor offset distance must satisfy measurement protocols; to ensure probe boundary effect errors are minimized and the higher fields closest to the phantom surface can be correctly measured and extrapolated to the phantom surface for computing 1 g SAR. Tolerances of the post-processing algorithms must be verified by the test laboratory for the scan resolutions used in the SAR measurements, according to the reference distribution functions specified in IEEE Std 1528-2013.

			≤3GHz	>3GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface			5±1 mm	½ δ·ln(2)±0.5 mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location			30°±1°	20°±1°
Maximum area scan spatial resolution: Δx Area , Δy Area			≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3–4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
			When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be ≤ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	
Maximum zoom scan spatial resolution: Δx Zoom , Δy Zoom			≤ 2 GHz: ≤ 8 mm 2–3 GHz: ≤ 5 mm*	3–4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: Δz Zoom (n)		≤ 5 mm	3–4 GHz: ≤ 4 mm
				4–5 GHz: ≤ 3 mm
				5–6 GHz: ≤ 2 mm
	graded grid	Δz Zoom (1): between 1st two points closest to phantom surface	≤ 4 mm	3–4 GHz: ≤ 3 mm
				4–5 GHz: ≤ 2.5 mm
				5–6 GHz: ≤ 2 mm
		≤ 1.5·Δz Zoom (n-1)		
Minimum zoom scan volume	x, y, z		≥30 mm	3–4 GHz: ≥ 28 mm
				4–5 GHz: ≥ 25 mm
				5–6 GHz: ≥ 22 mm
Note:				
1. δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528- 2011 for details.				
2. * When zoom scan is required and the reported SAR from the area scan based 1 g SAR estimation procedures of KDB				
447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

7.3 Measurement Procedure

The following steps are used for each test position

- a. Establish a call with the maximum output power with a base station simulator. The connection between the mobile and the base station simulator is established via air interface
- b. Measurement of the local E-field value at a fixed location. This value serves as a reference value for calculating a possible power drift.
- c. Measurement of the SAR distribution with a grid of 8 to 16mm * 8 to 16 mm and a constant distance to the inner surface of the phantom. Since the sensors cannot directly measure at the inner phantom surface, the values between the sensors and the inner phantom surface are extrapolated. With these values the area of the maximum SAR is calculated by an interpolation scheme.
- d. Around this point, a cube of 30 * 30 * 30 mm or 32 * 32 * 32 mm is assessed by measuring 5 or 8 * 5 or 8*4 or 5 mm. With these data, the peak spatial-average SAR value can be calculated.

7.4 Area & Zoom Scan Procedure

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g.

When the 1 g SAR of the highest peak is within 2 dB of the SAR limit, additional zoom scans are required for other peaks within 2 dB of the highest peak that have not been included in any zoom scan to ensure there is no increase in SAR.

8. Conducted RF Output Power

8.1 GSM

Mode: GSM850		Maximum Tune-up(dBm)	Burst Average Power (dBm)			Division Factors	Frame-Average Power (dBm)		
			CH128	CH190	CH251		CH128	CH190	CH251
			824.2MHz	836.6MHz	848.8MHz		824.2MHz	836.6MHz	848.8MHz
GSM		32.50	32.30	32.31	32.28	-9.03	23.27	23.28	23.25
GPRS (GMSK)	1Tx slot	32.50	32.31	32.27	32.23	-9.03	23.28	23.24	23.20
	2Tx slots	32.00	31.68	31.66	31.62	-6.02	25.66	25.64	25.60
	3Tx slots	30.50	30.22	30.15	30.08	-4.26	25.96	25.89	25.82
	4Tx slots	29.50	29.22	29.16	29.10	-3.01	26.21	26.15	26.09
EGPRS (8PSK)	1Tx slot	28.50	26.07	28.06	28.06	-9.03	17.04	19.03	19.03
	2Tx slots	25.00	24.83	24.80	24.91	-6.02	18.81	18.78	18.89
	3Tx slots	23.00	22.76	22.67	22.94	-4.26	18.50	18.41	18.68
	4Tx slots	22.00	21.36	21.44	21.68	-3.01	18.35	18.43	18.67
Mode: GSM1900		Maximum Tune-up(dBm)	Burst Average Power (dBm)			Division Factors	Frame-Average Power (dBm)		
			CH512	CH661	CH810		CH512	CH661	CH810
			1850.2MHz	1880.0MHz	1909.8MHz		1850.2MHz	1880.0MHz	1909.8MHz
GSM		29.50	29.08	29.02	28.99	-9.03	20.05	19.99	19.96
GPRS (GMSK)	1Tx slot	29.50	29.08	29.00	28.97	-9.03	20.05	19.97	19.94
	2Tx slots	28.50	28.37	28.31	28.25	-6.02	22.35	22.29	22.23
	3Tx slots	27.00	26.61	26.56	26.40	-4.26	22.35	22.30	22.14
	4Tx slots	25.50	25.48	25.44	25.24	-3.01	22.47	22.43	22.23
EGPRS (8PSK)	1Tx slot	27.00	26.89	26.71	26.55	-9.03	17.86	17.68	17.52
	2Tx slots	26.00	25.71	25.69	25.36	-6.02	19.69	19.67	19.34
	3Tx slots	24.50	23.39	23.53	24.01	-4.26	19.13	19.27	19.75
	4Tx slots	22.00	21.90	21.79	21.66	-3.01	18.89	18.78	18.65
Note: 1) Division Factors To average the power, the division factor is as follows: 1Tx-slot = 1 transmit time slot out of 8 time slots=> conducted power divided by (8/1) => -9.03dB 2Tx-slots = 2 transmit time slots out of 8 time slots=> conducted power divided by (8/2) => -6.02dB 3Tx-slots = 3 transmit time slots out of 8 time slots=> conducted power divided by (8/3) => -4.26dB 4Tx-slots = 4 transmit time slots out of 8 time slots=> conducted power divided by (8/4) => -3.01dB									

8.2 WCDMA

Mode		Maximum Tune-up(dBm)	WCDMA Band II		
			Conducted Power (dBm)		
			CH9262	CH9400	CH9538
RMC 12.2K		22.00	1852.4	1880.0	1907.6
HSDPA	Subtest-1	20.00	21.83	21.84	21.79
	Subtest-2	20.00	19.54	19.61	19.53
	Subtest-3	20.00	19.59	19.61	19.50
	Subtest-4	20.00	19.56	19.59	19.51
HSUPA	Subtest-1	17.50	19.57	19.58	19.51
	Subtest-2	18.00	17.04	16.95	17.26
	Subtest-3	17.50	17.54	17.28	16.79
	Subtest-4	17.50	17.01	17.49	16.98
	Subtest-5	18.50	17.37	17.48	17.30
			17.91	18.16	17.19
Mode		Maximum Tune-up(dBm)	WCDMA Band IV		
			Conducted Power (dBm)		
			CH1312	CH1413	CH1513
RMC 12.2K		22.50	1712.4	1732.6	1752.6
HSDPA	Subtest-1	20.50	22.33	22.34	22.34
	Subtest-2	20.00	19.95	19.97	20.03
	Subtest-3	20.50	19.92	19.98	19.98
	Subtest-4	20.50	19.94	19.96	20.00
HSUPA	Subtest-1	18.00	19.94	19.95	20.03
	Subtest-2	18.50	17.56	17.49	17.55
	Subtest-3	18.00	17.55	17.31	18.04
	Subtest-4	18.00	17.81	17.52	17.77
	Subtest-5	19.00	17.49	17.51	17.79
			18.05	18.02	18.73
Mode		Maximum Tune-up(dBm)	WCDMA Band V		
			Conducted Power (dBm)		
			CH4132	CH4183	CH4233
RMC 12.2K		23.00	826.4	836.6	846.6
HSDPA	Subtest-1	21.00	22.78	22.72	22.81
	Subtest-2	21.00	20.59	20.48	20.52
	Subtest-3	21.00	20.56	20.51	20.51
	Subtest-4	21.00	20.57	20.50	20.56
HSUPA	Subtest-1	18.50	20.60	20.50	20.52
	Subtest-2	18.50	17.84	18.28	17.85
	Subtest-3	18.50	17.98	18.30	18.02
	Subtest-4	18.50	18.30	17.99	18.03
	Subtest-5	18.50	18.02	18.00	18.03
			18.20	18.20	18.24
Per KDB 941225 D01, when the maximum output power and tune-up tolerance specified for production units in a secondary mode is ≤1/2dB higher than the primary mode (RMC12.2kbps) or when the highest reported SAR of the primary mode is scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for the secondary mode.					

8.3 LTE

Band 2

LTE-FDD Band 2				Maximum Tune-up(dBm)	Conducted Power(dBm)		
Bandwidth	Modulation	RB allocation	RB offset		18607	18900	19193
					1850.7MHz	1880.0MHz	1909.3MHz
1.4MHz	QPSK	1	0	28.50	28.07	28.22	28.33
			2	28.50	28.17	28.35	28.49
			5	28.50	28.11	28.22	28.34
		3	0	28.50	28.12	28.32	28.30
			2	28.50	28.23	28.32	28.34
			3	28.50	28.14	28.27	28.35
		6	0	27.50	27.25	27.34	27.41
	16QAM	1	0	27.50	27.20	27.21	27.27
			2	27.50	27.32	27.31	27.42
			5	27.50	27.26	27.21	27.31
		3	0	27.50	27.06	27.38	27.27
			2	27.50	27.14	27.38	27.31
			3	27.50	27.08	27.39	27.27
		6	0	26.50	26.21	26.30	26.30
Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	18615	18900	19185
					1851.5MHz	1880.0MHz	1908.5MHz
3MHz	QPSK	1	0	28.50	28.26	28.31	28.37
			7	29.00	28.41	28.50	28.53
			14	28.50	28.28	28.35	28.38
		8	0	27.50	27.26	27.37	27.40
			4	27.50	27.30	27.41	27.42
			7	27.50	27.25	27.35	27.36
		15	0	27.50	27.20	27.31	27.34
	16QAM	1	0	28.00	27.23	27.45	27.75
			7	28.00	27.39	27.60	27.89
			14	28.00	27.19	27.48	27.75
		8	0	26.50	26.23	26.30	26.47
			4	27.00	26.24	26.34	26.51
			7	26.50	26.24	26.31	26.46
		15	0	26.50	26.17	26.25	26.32
Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	18625	18900	19175
					1852.5MHz	1880.0MHz	1907.5MHz
5MHz	QPSK	1	0	28.50	28.10	28.19	28.28
			13	28.50	28.32	28.38	28.46
			24	28.50	28.19	28.24	28.27
		12	0	27.50	27.18	27.28	27.34
			6	27.50	27.28	27.37	27.41
			13	27.50	27.23	27.29	27.29
		25	0	27.50	27.19	27.29	27.30
	16QAM	1	0	27.50	27.16	27.42	27.11
			13	28.00	27.31	27.60	27.28
			24	27.50	27.22	27.42	27.12
		12	0	26.50	26.09	26.25	26.29
			6	26.50	26.18	26.30	26.35
			13	26.50	26.15	26.25	26.21
		25	0	26.50	26.16	26.23	26.29

LTE-FDD Band 2				Maximum Tune-up(dBm)	Conducted Power(dBm)				
Bandwidth	Modulation	RB allocation	RB offset		18650	18900	19150		
					1855.0MHz	1880.0MHz	1905.0MHz		
10MHz	QPSK	1	0	28.50	28.20	28.28	28.38		
			25	29.00	28.40	28.47	28.56		
			49	28.50	28.25	28.33	28.38		
		25	0	27.50	27.14	27.30	27.33		
			13	27.50	27.22	27.31	27.35		
			25	27.50	27.19	27.31	27.26		
		50	0	27.50	27.15	27.26	27.27		
			16QAM	1	0	28.00	27.15	27.40	27.79
					25	28.00	27.34	27.57	27.94
	49	28.00			27.14	27.44	27.74		
	25	0		26.50	26.16	26.26	26.33		
		13		26.50	26.23	26.28	26.35		
		25		26.50	26.21	26.25	26.25		
	50	0	26.50	26.10	26.21	26.25			
	Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	18675	18900	19125	
1857.5MHz						1880.0MHz	1902.5MHz		
15MHz	QPSK	1	0	28.50	28.16	28.18	28.31		
			38	28.50	28.22	28.33	28.42		
			74	28.50	28.08	28.25	28.33		
		36	0	27.50	27.26	27.37	27.41		
			18	27.50	27.32	27.43	27.49		
			39	27.50	27.27	27.40	27.37		
		75	0	27.50	27.26	27.36	27.40		
			16QAM	1	0	28.00	27.34	27.32	27.76
					38	28.00	27.48	27.45	27.86
	74	28.00			27.30	27.41	27.65		
	36	0		26.50	26.14	26.29	26.36		
		18		26.50	26.21	26.34	26.40		
		39		26.50	26.17	26.30	26.32		
	75	0	26.50	26.18	26.33	26.33			
	Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	18700	18900	19100	
1860.0MHz						1880.0MHz	1900.0MHz		
20MHz	QPSK	1	0	28.50	27.96	28.05	28.12		
			50	29.00	28.34	28.50	28.58		
			99	28.50	28.05	28.17	28.17		
		50	0	27.50	27.19	27.30	27.33		
			25	27.50	27.23	27.33	27.39		
			50	27.50	27.20	27.27	27.28		
		100	0	27.50	27.19	27.32	27.33		
			16QAM	1	0	27.50	27.41	27.19	27.30
					50	28.00	27.82	27.62	27.74
	99	27.50			27.49	27.27	27.34		
	50	0		26.50	26.11	26.24	26.29		
		25		26.50	26.16	26.26	26.36		
		50		26.50	26.15	26.22	26.21		
	100	0	26.50	26.15	26.25	26.28			

Band 4

LTE-FDD Band 4				Maximum Tune-up(dBm)	Conducted Power(dBm)		
Bandwidth	Modulation	RB allocation	RB offset		19957	20175	20393
					1710.7MHz	1732.5MHz	1754.3MHz
1.4MHz	QPSK	1	0	28.50	27.95	28.00	27.97
			2	28.50	28.08	28.13	28.03
			5	28.50	28.00	28.02	27.98
		3	0	28.50	28.05	28.04	28.03
			2	28.50	28.12	28.06	28.07
			3	28.50	28.06	28.04	28.00
		6	0	27.50	27.06	27.05	27.06
	16QAM	1	0	27.50	26.97	26.96	27.11
			2	27.50	27.10	27.05	27.18
			5	27.50	27.00	27.03	27.13
		3	0	27.50	27.21	27.03	26.97
			2	27.50	27.24	27.06	27.02
			3	27.50	27.22	27.00	26.96
		6	0	26.50	26.07	25.92	26.04
Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	19965	20175	20385
					1711.5MHz	1732.5MHz	1753.5MHz
3MHz	QPSK	1	0	28.50	28.17	28.09	28.07
			7	28.50	28.28	28.21	28.19
			14	28.50	28.15	28.09	28.05
		8	0	27.50	27.14	27.11	27.07
			4	27.50	27.17	27.12	27.10
			7	27.50	27.17	27.10	27.09
		15	0	27.50	27.14	27.07	27.05
	16QAM	1	0	28.00	27.19	27.23	27.62
			7	28.00	27.30	27.34	27.73
			14	28.00	27.18	27.27	27.58
		8	0	26.50	26.17	26.03	26.19
			4	26.50	26.22	26.07	26.25
			7	26.50	26.20	26.03	26.21
		15	0	26.50	26.14	25.99	26.09
Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	19976	20175	20375
					1712.5MHz	1732.5MHz	1752.5MHz
5MHz	QPSK	1	0	28.50	28.12	28.09	28.06
			13	28.50	28.16	28.17	28.20
			24	28.50	28.13	28.07	28.09
		12	0	27.50	27.08	27.13	27.08
			6	27.50	27.20	27.20	27.14
			13	27.50	27.14	27.07	27.05
		25	0	27.50	27.12	27.12	27.07
	16QAM	1	0	27.50	27.22	27.29	26.93
			13	27.50	27.27	27.38	26.97
			24	27.50	27.20	27.27	26.92
		12	0	26.50	26.07	26.11	26.00
			6	26.50	26.14	26.15	26.07
			13	26.50	26.06	26.04	26.01
		25	0	26.50	26.14	26.08	26.07

LTE-FDD Band 4				Maximum Tune-up(dBm)	Conducted Power(dBm)		
Bandwidth	Modulation	RB allocation	RB offset		20000	20175	20350
					1715.0MHz	1732.5MHz	1750.0MHz
10MHz	QPSK	1	0	28.50	28.21	28.16	28.08
			25	28.50	28.32	28.27	28.13
			49	28.50	28.22	28.14	28.08
		25	0	27.50	27.11	27.23	27.04
			13	27.50	27.18	27.15	27.05
			25	27.50	27.18	27.02	27.06
		50	0	27.50	27.13	27.08	27.03
	16QAM	1	0	28.00	27.20	27.23	27.63
			25	28.00	27.29	27.39	27.68
			49	28.00	27.17	27.24	27.58
		25	0	26.50	26.18	26.19	26.07
			13	26.50	26.20	26.10	26.09
			25	26.50	26.24	26.03	26.11
		50	0	26.50	26.12	26.08	26.01
Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	20025	20175	20325
					1717.5MHz	1732.5MHz	1747.5MHz
15MHz	QPSK	1	0	28.50	28.04	28.08	28.02
			38	28.50	28.16	28.14	28.06
			74	28.50	28.09	28.05	27.98
		36	0	27.50	27.13	27.30	27.16
			18	27.50	27.22	27.26	27.12
			39	27.50	27.21	27.17	27.11
		75	0	27.50	27.18	27.25	27.11
	16QAM	1	0	28.00	27.45	27.23	27.55
			38	28.00	27.49	27.32	27.55
			74	28.00	27.36	27.23	27.52
		36	0	26.50	26.09	26.22	26.12
			18	26.50	26.15	26.16	26.06
			39	26.50	26.13	26.10	26.07
		75	0	26.50	26.14	26.19	26.11
Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	20050	20175	20300
					1720.0MHz	1732.5MHz	1745.0MHz
20MHz	QPSK	1	0	28.00	27.91	27.93	27.87
			50	28.50	28.21	28.30	28.25
			99	28.00	27.87	27.93	27.91
		50	0	27.50	27.02	27.19	27.13
			25	27.50	27.16	27.16	27.14
			50	27.50	27.11	27.01	27.08
		100	0	27.50	27.12	27.14	27.16
	16QAM	1	0	27.50	27.44	27.06	27.10
			50	28.00	27.77	27.43	27.48
			99	27.50	27.38	27.08	27.15
		50	0	26.50	26.01	26.15	26.12
			25	26.50	26.10	26.11	26.08
			50	26.50	26.07	25.98	26.04
		100	0	26.50	26.07	26.09	26.13

Band 5

LTE-FDD Band 5				Maximum Tune-up(dBm)	Conducted Power(dBm)		
Bandwidth	Modulation	RB allocation	RB offset		20407	20525	20643
					824.7MHz	836.5MHz	848.3MHz
1.4MHz	QPSK	1	0	29.50	29.08	28.99	28.89
			2	29.50	29.13	29.08	29.03
			5	29.50	29.08	29.01	28.95
		3	0	29.50	29.12	29.12	29.01
			2	29.50	29.17	29.13	28.95
			3	29.50	29.07	29.10	29.04
		6	0	28.50	28.07	28.07	27.96
	16QAM	1	0	28.50	28.14	28.00	27.94
			2	28.50	28.24	28.09	28.06
			5	28.50	28.13	28.02	28.06
		3	0	28.50	28.05	28.29	28.11
			2	28.50	28.05	28.30	28.16
			3	28.50	28.02	28.29	28.10
		6	0	27.50	27.02	27.08	26.92
Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	20415	20525	20635
					825.5MHz	836.5MHz	847.5MHz
3MHz	QPSK	1	0	29.00	28.90	28.93	28.87
			7	29.50	29.07	29.08	29.00
			14	29.00	28.95	28.89	28.84
		8	0	28.00	27.91	27.95	27.85
			4	28.00	27.99	27.98	27.79
			7	28.00	27.94	27.94	27.71
		15	0	28.00	27.92	27.95	27.64
	16QAM	1	0	28.50	27.99	28.13	28.09
			7	28.50	28.14	28.25	28.12
			14	28.50	28.00	28.10	27.98
		8	0	27.50	27.01	26.97	26.57
			4	27.50	27.05	27.03	26.69
			7	27.50	27.00	26.92	26.56
		15	0	27.00	26.97	26.94	26.48

LTE-FDD Band 5				Maximum Tune-up(dBm)	Conducted Power(dBm)		
Bandwidth	Modulation	RB allocation	RB offset		20425	20525	20625
					826.5MHz	836.5MHz	846.5MHz
5MHz	QPSK	1	0	29.00	28.64	28.93	28.84
			13	29.50	28.89	29.01	28.75
			24	29.00	28.76	28.89	28.36
		12	0	28.00	27.81	27.99	27.44
			6	28.50	27.83	28.04	27.48
			13	28.00	27.83	27.98	27.43
		25	0	28.50	27.89	28.04	27.42
	16QAM	1	0	28.50	27.89	28.22	27.21
			13	28.50	28.09	28.29	27.27
			24	28.50	27.98	28.13	27.18
		12	0	27.50	26.89	27.02	26.41
			6	27.50	27.03	27.04	26.40
			13	27.00	26.95	26.99	26.33
		25	0	27.50	26.93	27.01	26.38

Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	20450	20525	20600
					829.0MHz	836.5MHz	844.0MHz
10MHz	QPSK	1	0	29.00	28.72	28.84	28.77
			25	29.00	28.94	28.87	28.39
			49	29.00	28.83	28.47	28.24
		25	0	28.00	27.80	27.65	27.43
			13	28.00	27.85	27.75	27.37
			25	28.00	27.83	27.50	27.30
		50	0	28.00	27.85	27.58	27.36
			0	28.00	27.77	27.56	27.89
			25	28.50	27.98	27.88	28.01
	16QAM	1	49	28.00	27.86	27.49	27.78
			0	27.00	26.90	26.65	26.53
			13	27.00	26.90	26.73	26.45
		25	25	27.00	26.89	26.70	26.35
			0	27.00	26.83	26.68	26.39
			0	27.00			
			0	27.00			

Band 12

LTE-FDD Band 12				Maximum Tune-up(dBm)	Conducted Power(dBm)		
Bandwidth	Modulation	RB allocation	RB offset		23017	23095	23173
					699.7MHz	707.5MHz	715.3MHz
1.4MHz	QPSK	1	0	29.00	28.94	28.98	28.99
			2	29.50	29.04	29.07	29.12
			5	29.50	28.93	29.00	29.00
		3	0	29.50	28.98	29.06	29.04
			2	29.50	29.04	29.09	29.09
			3	29.50	28.98	29.08	29.08
		6	0	28.50	28.07	28.08	28.06
	16QAM	1	0	28.50	28.12	27.99	27.99
			2	28.50	28.20	28.08	28.09
			5	28.50	28.09	27.99	28.05
		3	0	28.50	27.94	28.27	28.05
			2	28.50	28.00	28.29	28.06
			3	28.50	27.94	28.25	28.05
		6	0	27.50	27.04	27.10	27.00
Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	23025	23095	23165
					700.5MHz	707.5MHz	714.5MHz
3MHz	QPSK	1	0	29.50	29.06	29.07	29.06
			7	29.50	29.27	29.22	29.17
			14	29.50	29.09	29.06	28.67
		8	0	28.50	28.07	28.09	27.63
			4	28.50	28.11	28.11	28.06
			7	28.50	28.10	28.06	27.84
		15	0	28.50	28.07	28.06	27.93
	16QAM	1	0	28.50	28.04	28.24	28.45
			7	29.00	28.29	28.39	28.56
			14	28.50	28.07	28.20	28.27
		8	0	27.50	27.08	27.09	26.89
			4	27.50	27.18	27.13	27.22
			7	27.50	27.12	27.08	27.23
		15	0	27.50	27.05	27.05	27.10

Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	23035	23095	23155
					701.5MHz	707.5MHz	713.5MHz
5MHz	QPSK	1	0	29.00	28.93	28.92	28.71
			13	29.50	29.08	29.11	28.61
			24	29.00	28.99	28.95	28.47
		12	0	28.00	27.97	27.92	27.56
			6	28.50	28.10	27.79	27.64
			13	28.50	28.06	27.66	27.46
	16QAM	25	0	28.00	27.98	27.64	27.49
			0	28.50	28.03	27.70	27.39
			13	28.50	28.20	27.90	27.47
		12	24	28.50	28.11	27.81	27.34
			0	27.00	26.89	26.65	26.47
			6	27.50	27.04	26.65	26.58
		25	13	27.50	27.02	26.63	26.42
			0	27.00	26.98	26.65	26.60
Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	23060	23095	23130
					704.0MHz	707.5MHz	711.0MHz
10MHz	QPSK	1	0	29.00	28.99	28.99	28.51
			25	29.50	29.22	28.93	28.65
			49	29.50	29.11	28.59	28.57
		25	0	28.00	27.99	27.81	27.62
			13	28.50	28.09	27.62	27.66
			25	28.00	27.98	27.73	27.63
	16QAM	50	0	28.00	27.99	27.73	27.62
			0	28.50	27.92	27.68	28.11
			25	28.50	28.18	27.94	28.32
		1	49	28.50	27.78	27.76	28.10
			0	27.00	26.72	26.78	26.68
			13	27.50	27.05	26.64	26.70
		25	25	27.00	26.84	26.72	26.68
			0	27.00	26.91	26.76	26.63

Band 13

LTE-FDD Band 13				Maximum Tune-up(dBm)	Conducted Power(dBm)		
Bandwidth	Modulation	RB allocation	RB offset		23205	23230	23255
5MHz	QPSK	1	0	29.00	28.84	28.33	28.32
			13	29.50	29.06	28.47	28.40
			24	29.00	28.84	28.33	28.32
		12	0	28.00	27.58	27.35	27.35
			6	28.00	27.50	27.44	27.43
			13	28.00	27.52	27.45	27.30
	16QAM	25	0	28.00	27.51	27.39	27.29
			0	28.00	27.20	27.46	27.56
			13	28.00	27.38	27.56	27.63
		1	24	28.00	27.21	27.43	27.57
			0	26.50	26.43	26.35	26.44
			6	27.00	26.50	26.45	26.58
		12	13	27.00	26.54	26.47	26.32
			0	27.00	26.55	26.47	26.35

Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	23230
					782.0MHz
10MHz	QPSK	1	0	29.00	28.81
			25	29.50	29.00
			49	29.00	28.89
		25	0	28.00	27.79
			13	28.00	27.89
			25	28.00	27.87
		50	0	28.00	27.85
			0	28.00	27.94
			25	28.50	28.04
	16QAM	1	49	28.00	27.90
			0	27.00	26.92
			13	27.50	27.01
		25	25	27.50	27.01
			0	27.00	26.95
		50	0	27.00	26.95
			0	27.00	26.95

Band 25

LTE-FDD Band 25				Maximum Tune-up(dBm)	Conducted Power(dBm)		
Bandwidth	Modulation	RB allocation	RB offset		26047	26365	26683
					1850.7MHz	1882.5MHz	1914.3MHz
1.4MHz	QPSK	1	0	28.50	27.85	28.05	28.14
			2	28.50	27.98	28.14	28.28
			5	28.50	27.91	28.05	28.10
		3	0	28.50	27.92	28.12	27.95
			2	28.50	27.99	28.09	27.92
			3	28.50	27.96	28.06	27.89
		6	0	27.50	27.06	27.15	27.22
	16QAM	1	0	27.50	27.03	27.02	27.05
			2	27.50	27.14	27.13	27.09
			5	27.50	27.04	27.05	26.91
		3	0	27.50	26.85	27.21	27.14
			2	27.50	26.91	27.26	27.13
			3	27.50	26.88	27.20	26.92
		6	0	26.50	26.02	26.15	26.14
		Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	26055
1851.5MHz	1882.5MHz						1913.5MHz
3MHz	QPSK	1	0	28.50	27.95	28.14	28.16
			7	28.50	28.11	28.27	28.30
			14	28.50	27.97	28.11	28.21
		8	0	27.50	27.00	27.13	27.18
			4	27.50	27.05	27.17	27.19
			7	27.50	27.01	27.13	27.16
		15	0	27.50	26.95	27.10	27.11
	16QAM	1	0	28.00	27.10	27.57	27.11
			7	28.00	27.26	27.70	27.26
			14	28.00	27.09	27.57	27.15
		8	0	26.50	25.93	26.22	26.14
			4	26.50	25.97	26.26	26.20
			7	26.50	25.94	26.21	26.15
		15	0	26.50	25.87	26.08	26.09

Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	26065	26365	26665
					1852.5MHz	1882.5MHz	1912.5MHz
5MHz	QPSK	1	0	28.50	27.90	28.04	28.03
			13	28.50	28.01	28.15	28.16
			24	28.50	27.95	28.07	28.09
		12	0	27.50	26.94	27.08	27.14
			6	27.50	27.04	27.16	27.17
			13	27.50	26.99	27.08	27.10
		25	0	27.50	26.98	27.07	27.10
	16QAM	1	0	27.50	26.96	27.24	26.87
			13	27.50	27.09	27.36	26.97
			24	27.50	27.01	27.24	26.93
		12	0	26.50	25.84	26.04	26.06
			6	26.50	25.94	26.10	26.08
			13	26.50	25.87	26.04	26.03
		25	0	26.50	25.94	25.99	26.08

LTE-FDD Band 25				Maximum Tune-up(dBm)	Conducted Power(dBm)		
Bandwidth	Modulation	RB allocation	RB offset		26090	26365	26640
10MHz	QPSK	1	0	28.50	28.03	28.14	28.11
			25	28.50	28.21	28.31	28.31
			49	28.50	28.06	28.15	28.18
		25	0	27.50	26.98	27.18	27.19
			13	27.50	27.04	27.18	27.10
			25	27.50	27.04	27.14	27.07
		50	0	27.50	26.97	27.12	27.09
	16QAM	1	0	28.00	26.98	27.30	27.52
			25	28.00	27.16	27.41	27.65
			49	28.00	27.04	27.27	27.60
		25	0	26.50	25.98	26.14	26.17
			13	26.50	26.05	26.14	26.07
			25	26.50	26.06	26.10	26.05
		50	0	26.50	25.94	26.06	26.01
15MHz	QPSK	1	0	28.50	27.87	28.07	28.06
			38	28.50	28.03	28.14	28.16
			74	28.50	28.01	28.06	28.13
		36	0	27.50	27.06	27.23	27.21
			18	27.50	27.10	27.22	27.23
			39	27.50	27.11	27.19	27.13
		75	0	27.50	27.06	27.19	27.15
	16QAM	1	0	28.00	27.18	27.17	27.50
			38	28.00	27.30	27.26	27.54
			74	28.00	27.19	27.21	27.50
		36	0	26.50	25.97	26.16	26.13
			18	26.50	26.01	26.15	26.15
			39	26.50	25.99	26.14	26.05
		75	0	26.50	25.96	26.13	26.07

Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	26140	26365	26590
					1860.0MHz	1882.5MHz	1905.0MHz
20MHz	QPSK	1	0	28.00	27.70	27.86	27.89
			50	28.50	28.17	28.25	28.26
			99	28.00	27.81	27.96	27.93
		50	0	27.50	26.92	27.17	27.08
			25	27.50	27.03	27.12	27.09
			50	27.50	27.03	27.09	26.88
		100	0	27.50	26.99	27.12	27.03
			0	27.50	27.19	26.99	27.11
			50	28.00	27.63	27.37	27.46
	16QAM	1	99	27.50	27.29	27.08	27.14
		50	0	26.50	25.84	26.11	26.05
			25	26.50	25.96	26.07	26.03
			50	26.50	25.96	26.03	25.80
		100	0	26.50	25.93	26.06	25.97

Band 41

LTE-TDD Band 41				Maximum Tune-up(dBm)	Conducted Power(dBm)		
Bandwidth	Modulation	RB allocation	RB offset		39675	40620	41565
5MHz	QPSK	1	0	29.50	28.64	29.18	28.80
			13	29.50	28.76	29.17	29.02
			24	29.50	28.70	29.04	28.95
		12	0	28.50	27.69	28.10	27.90
			6	28.50	27.81	28.24	27.82
			13	28.50	27.81	28.07	27.78
		25	0	28.50	27.86	28.18	27.76
			0	28.50	27.74	28.14	27.70
			13	28.50	27.82	28.29	28.15
	16QAM	1	24	28.50	27.73	28.19	27.75
		12	0	27.50	26.75	27.17	26.47
			6	27.50	26.74	27.04	26.52
			13	27.50	26.65	27.17	26.60
		25	0	27.50	26.75	27.13	26.71

Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	39700	40620	41540
10MHz	QPSK	1	0	29.50	28.66	29.08	28.83
			25	29.50	28.96	29.41	29.00
			49	29.50	28.73	29.18	28.84
		25	0	28.50	27.64	28.07	27.72
			13	28.50	27.78	28.20	27.75
			25	28.50	27.79	28.07	27.74
		50	0	28.50	27.73	28.08	27.70
			0	28.00	27.85	27.94	27.65
			25	28.50	27.73	28.17	27.98
	16QAM	1	49	28.00	27.91	27.99	27.80
		25	0	27.50	26.63	27.08	26.70
			13	27.50	26.67	27.14	26.83
			25	27.50	26.77	27.13	26.79
		50	0	27.50	26.70	27.14	26.63

LTE-TDD Band 41				Maximum Tune-up(dBm)	Conducted Power(dBm)				
Bandwidth	Modulation	RB allocation	RB offset		39725	40620	41515		
					2503.5MHz	2593.0MHz	2682.5MHz		
15MHz	QPSK	1	0	29.50	28.69	29.20	28.72		
			38	29.50	28.85	29.26	28.82		
			74	29.50	28.57	29.07	28.71		
		36	0	28.50	27.77	28.31	27.97		
			18	28.50	27.93	28.22	27.84		
			39	28.50	27.90	28.18	28.06		
		75	0	28.50	27.80	28.20	27.93		
	16QAM	1	0	28.00	27.52	27.89	27.76		
			38	28.50	28.06	28.02	27.84		
			74	28.00	27.47	27.91	27.54		
		36	0	27.50	26.79	27.08	26.85		
			18	27.50	26.75	27.18	26.76		
			39	27.50	26.86	27.18	26.72		
		75	0	27.50	26.72	27.24	26.70		
		Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	39750	40620	41490
							2506.0MHz	2593.0MHz	2680.0MHz
20MHz	QPSK	1	0	29.00	28.51	28.92	28.67		
			50	29.50	28.95	29.34	28.88		
			99	29.00	28.60	28.89	28.54		
		50	0	28.50	27.69	28.24	27.89		
			25	28.50	27.85	28.25	27.71		
			50	28.50	27.84	28.10	27.65		
		100	0	28.50	27.80	28.19	27.71		
	16QAM	1	0	28.00	27.06	27.72	27.52		
			50	28.50	27.44	28.44	28.27		
			99	28.00	27.14	27.69	27.86		
		50	0	27.50	26.70	27.18	26.82		
			25	27.50	26.77	27.17	26.78		
			50	27.50	26.77	27.01	26.74		
		100	0	27.50	26.71	27.08	26.65		

Band 66

LTE-FDD Band 66				Maximum Tune-up(dBm)	Conducted Power(dBm)		
Bandwidth	Modulation	RB allocation	RB offset		131979	132322	132665
					1710.7MHz	1745.0MHz	1779.3MHz
1.4MHz	QPSK	1	0	25.00	24.67	20.98	18.15
			2	25.00	24.80	21.09	18.33
			5	25.00	24.63	20.86	18.20
		3	0	25.00	24.70	20.93	18.21
			2	25.00	24.69	20.90	18.23
			3	25.00	24.64	20.84	18.19
		6	0	24.00	23.66	19.90	17.20
	16QAM	1	0	24.00	23.54	19.84	17.04
			2	24.00	23.64	19.95	17.17
			5	24.00	23.50	19.72	17.08
		3	0	24.00	23.65	20.04	17.15
			2	24.00	23.63	20.05	17.19
			3	24.00	23.59	20.00	17.17
		6	0	23.00	22.64	18.90	16.16

Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	131987	132322	132657
					1711.5MHz	1745.0MHz	1778.5MHz
3MHz	QPSK	1	0	25.00	24.75	21.10	18.18
			7	25.00	24.93	21.18	18.48
			14	25.00	24.61	20.77	18.28
		8	0	24.00	23.67	20.04	17.18
			4	24.00	23.67	19.93	17.24
			7	24.00	23.61	19.86	17.25
		15	0	24.00	23.62	19.90	17.15
			0	24.00	23.62	20.24	17.36
			7	24.00	23.79	20.27	17.60
	16QAM	1	14	23.50	23.44	19.84	17.45
			0	23.00	22.66	18.99	16.16
			4	23.00	22.69	18.91	16.23
		8	7	23.00	22.61	18.80	16.21
			0	23.00	22.60	18.80	16.11
			0	23.00	22.60	18.80	16.11
Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	131997	132322	132647
					1712.5MHz	1745.0MHz	1777.5MHz
5MHz	QPSK	1	0	25.00	24.56	21.16	18.06
			13	24.50	24.47	20.90	18.19
			24	24.50	24.25	20.53	18.18
		12	0	24.00	23.58	20.11	17.17
			6	24.00	23.61	19.99	17.20
			13	23.50	23.43	19.69	17.15
		25	0	24.00	23.56	19.89	17.15
			0	24.00	23.82	20.27	17.25
			13	24.00	23.76	19.98	17.38
	16QAM	1	24	24.00	23.52	19.66	17.40
			0	23.00	22.59	18.97	16.05
			6	23.00	22.57	18.87	16.16
		12	13	22.50	22.41	18.58	16.07
			0	23.00	22.54	18.83	16.14
			0	23.00	22.54	18.83	16.14

Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	132022	132322	132622
					1715.0MHz	1745.0MHz	1775.0MHz
10MHz	QPSK	1	0	25.00	24.74	21.54	18.15
			25	25.00	24.56	21.07	18.30
			49	24.50	24.04	20.29	18.32
		25	0	24.00	23.56	20.33	17.22
			13	23.50	23.39	20.00	17.21
			25	23.50	23.22	19.60	17.16
		50	0	23.50	23.35	19.97	17.14
			0	24.00	23.59	20.65	17.30
			25	23.50	23.40	20.15	17.44
	16QAM	1	49	23.00	22.88	19.38	17.46
			0	23.00	22.51	19.30	16.20
			13	22.50	22.37	18.97	16.19
		25	25	22.50	22.20	18.57	16.18
			0	22.50	22.32	18.91	16.07
			0	22.50	22.32	18.91	16.07

LTE-FDD Band 66				Maximum Tune-up(dBm)	Conducted Power(dBm)		
Bandwidth	Modulation	RB allocation	RB offset		132047	132322	132597
					1717.5MHz	1745.0MHz	1772.5MHz
15MHz	QPSK	1	0	25.00	24.64	21.77	18.24
			38	24.50	24.19	20.94	18.18
			74	23.50	23.45	19.86	18.08
		36	0	24.00	23.50	20.57	17.33
			18	23.50	23.27	20.10	17.24
			39	23.00	22.92	19.46	17.15
		75	0	23.50	23.18	20.07	17.23
	16QAM	1	0	24.00	23.70	20.87	17.34
			38	23.50	23.28	20.04	17.33
			74	22.50	22.45	18.96	17.25
		36	0	22.50	22.46	19.50	16.08
			18	22.50	22.19	19.05	16.13
			39	22.00	21.86	18.42	16.06
		75	0	22.50	22.13	19.03	16.18
Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	132072	132322	132572
					1720.0MHz	1745.0MHz	1770.0MHz
20MHz	QPSK	1	0	24.50	24.44	21.95	18.41
			50	24.50	24.09	21.09	18.26
			99	23.00	22.70	19.40	17.67
		50	0	23.50	23.27	20.68	17.25
			25	23.00	22.93	19.99	16.98
			50	22.50	22.46	19.26	16.78
		100	0	23.00	22.86	20.08	17.05
	16QAM	1	0	23.50	23.26	20.76	17.23
			50	23.00	22.87	20.01	17.01
			99	21.50	21.44	18.17	16.57
		50	0	22.50	22.24	19.61	16.10
			25	22.00	21.95	18.94	16.01
			50	21.50	21.44	18.20	15.78
		100	0	22.00	21.84	19.07	16.04

Band 71

LTE-FDD Band 71				Maximum Tune-up(dBm)	Conducted Power(dBm)		
Bandwidth	Modulation	RB allocation	RB offset		133147	133297	133447
					665.5MHz	680.5MHz	695.5MHz
5MHz	QPSK	1	0	29.00	28.95	28.91	28.95
			13	29.50	29.11	29.08	28.65
			24	29.00	28.97	28.94	28.44
		12	0	28.50	27.95	28.08	27.50
			6	28.50	28.13	28.08	27.62
			13	28.50	28.13	28.00	27.54
		25	0	28.50	28.09	28.02	27.56
	16QAM	1	0	28.50	28.24	27.81	27.54
			13	28.50	28.39	27.93	27.71
			24	28.50	28.28	27.77	27.60
		12	0	27.00	26.96	26.93	26.47
			6	27.50	27.14	27.05	26.53
			13	27.50	27.06	26.96	26.47
		25	0	27.50	27.03	26.90	26.55

Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	133172	133297	133422
					668.0MHz	680.5MHz	693.0MHz
10MHz	QPSK	1	0	29.50	29.05	28.50	28.49
			25	29.50	29.26	28.75	28.60
			49	29.50	29.16	28.54	28.54
		25	0	28.00	27.87	27.71	27.55
			13	28.00	27.83	27.61	27.61
			25	28.00	27.71	27.59	27.55
	16QAM	50	0	28.00	27.63	27.64	27.55
			0	28.50	27.58	27.66	28.11
			25	28.50	27.79	27.87	28.37
		1	49	28.50	27.62	27.78	28.09
			0	27.00	26.58	26.71	26.56
			13	27.00	26.71	26.62	26.66
		25	25	27.00	26.70	26.57	26.59
			0	27.00	26.56	26.65	26.52
Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	133197	133297	133397
					670.5MHz	680.5MHz	690.5MHz
15MHz	QPSK	1	0	29.00	28.94	28.41	28.35
			38	29.00	28.57	28.57	28.48
			74	29.00	28.44	28.51	28.45
		36	0	28.00	27.54	27.68	27.56
			18	28.00	27.64	27.61	27.60
			39	28.00	27.61	27.63	27.65
	16QAM	75	0	28.00	27.55	27.71	27.61
			0	28.00	27.83	27.59	27.97
			38	28.50	27.95	27.71	28.13
		1	74	28.50	27.86	27.74	28.04
			0	27.00	26.44	26.70	26.54
			18	27.00	26.56	26.59	26.59
		36	39	27.00	26.56	26.62	26.60
			0	27.00	26.51	26.66	26.57
Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	133222	133322	133372
					673.0MHz	683.0MHz	688.0MHz
20MHz	QPSK	1	0	29.00	28.79	28.21	28.20
			50	29.00	28.72	28.65	28.69
			99	28.50	28.33	28.32	28.32
		50	0	28.00	27.41	27.78	27.57
			25	28.00	27.52	27.63	27.59
			50	28.00	27.32	27.68	27.59
	16QAM	100	0	28.00	27.34	27.74	27.57
			0	28.00	27.53	27.78	27.43
			50	28.50	28.01	28.23	27.90
		1	99	28.00	27.64	27.90	27.54
			0	27.00	26.34	26.74	26.53
			25	27.00	26.49	26.62	26.57
		50	50	27.00	26.30	26.68	26.54
			0	27.00	26.35	26.71	26.56

8.4 Wi-Fi

2.4G

Band (GHz)	Mode	Channel	Freq. (MHz)	Average Power (dBm)	Maximum Tune-up(dBm)	SAR Test Require.
2.4g Wifi (2.4~2.4835)	802.11b	1	2412	14.76	15.00	No
		6	2437	15.74	16.00	Yes
		11	2462	15.69	16.00	No
	802.11g	1	2412	14.64	15.00	No
		6	2437	15.61	16.00	No
		11	2462	15.63	16.00	No
	802.11n(HT20)	1	2412	14.53	15.00	No
		6	2437	15.61	16.00	No
		11	2462	15.54	16.00	No
	802.11n(HT40)	3	2422	15.40	15.50	No
		6	2437	15.69	16.00	No
		9	2452	15.88	16.00	No

Note: SAR is not required for the following 2.4 GHz OFDM conditions as the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is $\leq 1.2\text{W/kg}$.

5G

Band (GHz)	Mode	Channel	Freq. (MHz)	Average Power (dBm)	Maximum Tune-up(dBm)	SAR Test Require.
U-NII-1 (5.150~5.250)	802.11a	36	5180	13.53	14.00	No
		40	5200	13.73	14.00	No
		48	5240	13.72	14.00	No
	802.11n(HT20)	36	5180	13.34	13.50	No
		40	5200	13.46	13.50	No
		48	5240	13.56	14.00	No
	802.11ac(VHT20)	36	5180	13.24	13.50	No
		40	5200	13.38	13.50	No
		48	5240	13.41	13.50	No
	802.11n(HT40)	38	5190	13.56	14.00	No
		46	5230	13.67	14.00	No
	802.11ac(VHT40)	38	5190	13.61	14.00	No
		46	5230	13.76	14.00	No
	802.11ac(VHT80)	42	5210	14.15	14.50	Yes
Band (GHz)	Mode	Channel	Freq. (MHz)	Average Power (dBm)	Maximum Tune-up(dBm)	SAR Test Require.
U-NII-2a (5.250~5.350)	802.11a	52	5260	13.74	14.00	No
		60	5300	13.48	13.50	No
		64	5320	13.30	13.50	No
	802.11n(HT20)	52	5260	13.40	13.50	No
		60	5300	13.31	13.50	No
		64	5320	13.07	13.50	No
	802.11ac(VHT20)	52	5260	13.35	13.50	No
		60	5300	13.24	13.50	No
		64	5320	12.94	13.00	No
	802.11n(HT40)	54	5270	13.69	14.00	No
		62	5310	13.28	13.50	No
	802.11ac(VHT40)	54	5270	13.48	13.50	No
		62	5310	13.37	13.50	No
	802.11ac(VHT80)	58	5290	13.95	14.00	Yes
Band (GHz)	Mode	Channel	Freq. (MHz)	Average Power (dBm)	Maximum Tune-up(dBm)	SAR Test Require.
U-NII-2c (5.470~5.725)	802.11a	100	5500	12.70	13.00	No
		116	5580	13.96	14.00	No
		140	5700	12.38	12.50	No

	802.11n(HT20)	100	5500	12.36	12.50	No
		116	5580	13.70	14.00	No
		140	5700	12.07	12.50	No
	802.11ac(VHT20)	100	5500	12.41	12.50	No
		116	5580	13.75	14.00	No
		140	5700	12.03	12.50	No
	802.11n(HT40)	102	5510	12.55	13.00	No
		110	5550	13.40	13.50	No
		134	5670	13.11	13.50	No
	802.11ac(VHT40)	102	5510	12.55	13.00	No
		110	5550	13.35	13.50	No
		134	5670	13.11	13.50	No
	802.11ac(VHT80)	106	5530	13.27	13.50	No
		122	5610	14.13	14.50	Yes
Band (GHz)	Mode	Channel	Freq. (MHz)	Average Power (dBm)	Maximum Tune-up(dBm)	SAR Test Require.
U-NII-3 (5.725~5.850)	802.11a	149	5745	11.35	11.50	No
		157	5785	10.89	11.00	No
		165	5825	10.82	11.00	No
	802.11n(HT20)	149	5745	11.08	11.50	No
		157	5785	10.73	11.00	No
		165	5825	10.63	11.00	No
	802.11ac(VHT20)	149	5745	11.00	11.50	No
		157	5785	10.73	11.00	No
		165	5825	10.53	11.00	No
	802.11n(HT40)	151	5755	11.09	11.50	No
		159	5795	10.78	11.00	No
	802.11ac(VHT40)	151	5755	11.10	11.50	No
		159	5795	10.91	11.00	No
	802.11ac(VHT80)	155	5775	11.81	12.00	Yes

8.5 Bluetooth

EDR	Mode	Maximum Tune-up(dBm)	Average Conducted Output Power (dBm)		
			0	39	78
			2402MHz	2441MHz	2480MHz
	GFSK	5.50	4.92	5.30	5.49
	$\pi/4$ QPSK	5.00	4.39	4.80	4.92
	8DPSK	5.00	4.42	4.79	4.90
BLE	Mode	Maximum Tune-up(dBm)	Average Conducted Output Power (dBm)		
			0	20	39
			2402MHz	2440MHz	2480MHz
	1Mbps	5.50	5.15	5.40	5.34
	2Mbps	5.50	5.17	5.43	5.40

Note

- Per KDB 447498 D04 Interim General RF Exposure Guidance v01, the 1-g SAR test exclusion thresholds for 300 MHz to 6 GHz at *test separation distances* ≤ 40 cm are determined by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases} \quad (\text{B. 2})$$

where

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B. 1})$$


$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and $ERP_{20 \text{ cm}}$ is per Formula (B. 1).

- *When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine estimated SAR.
- Per KDB 248227 D01 v02r02, choose the highest output power channel to test SAR and determine further SAR exclusion.
 - The output power of all data rate were prescan, just the worst case (the lowest data rate) of all mode were shown in report.

9. Test Exclusion Consideration

Antenna information:



WWAN Antenna	GSM/WCDMA/LTE TX/RX
WLAN/BT Antenna	WLAN/BT TX/RX
Note: 1. KDB 447498 D04v01, particular DUT edges were not required to be evaluated for SAR if the antenna-to-edge distance is greater than 2.5cm. 2. Per KDB648474 D04, 10-g extremity SAR is not required when Body-Worn mode 1-g reported SAR<1.2W/Kg.	

Distance of The Antenna to the EUT surface and edge (mm)						
Antenna	Front Side (mm)	Back Side (mm)	Left Edge (mm)	Right Edge (mm)	Top Edge (mm)	Bottom Edge (mm)
WWAN	<25	<25	<25	29	63	<25
BT/Wifi	<25	<25	65	<25	<25	64
Positions for SAR tests: Hotspot mode						
Antenna	Front Side (mm)	Back Side (mm)	Left Edge (mm)	Right Edge (mm)	Top Edge (mm)	Bottom Edge (mm)
WWAN	Yes	Yes	Yes	No	No	Yes
BT/Wifi	Yes	Yes	No	Yes	Yes	No

9.1 SAR Test Exclusion Consideration Table

Per KDB 447498 requires when the standalone SAR test exclusion of section 4.3.1 is applied to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to the following format to determine simultaneous transmission SAR test exclusion:

$$(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm}) \cdot [\sqrt{f(\text{GHz})} / x]$$

W/kg for test separation distances ≤ 50 mm;

where $x = 7.5$ for 1-g SAR, and $x = 18.75$ for 10-g SAR.

0.4 W/Kg for 1-g SAR and 1.0 W/kg for 10-g SAR, when the test separation distances is > 50 mm

10. Test Result

Head(0mm gap)												
Mode	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
GSM 850 (voice)	Left Cheek	190	836.6	-3.430	0.078	100.00	1.000	32.31	32.50	1.045	0.082	/
	Left Tilt	190	836.6	3.170	0.037	100.00	1.000	32.31	32.50	1.045	0.039	/
	Right Cheek	190	836.6	-4.330	0.086	100.00	1.000	32.31	32.50	1.045	0.090	1#
	Right Tilt	190	836.6	3.610	0.042	100.00	1.000	32.31	32.50	1.045	0.044	/
Body(10mm Gap)												
Mode	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
GSM 850 (voice)	Front	190	836.6	-0.780	0.122	100.00	1.000	32.31	32.50	1.045	0.127	/
	Back	190	836.6	1.390	0.161	100.00	1.000	32.31	32.50	1.045	0.168	/
	Left	190	836.6	-1.370	0.148	100.00	1.000	32.31	32.50	1.045	0.155	/
	Bottom	190	836.6	-0.950	0.116	100.00	1.000	32.31	32.50	1.045	0.121	/
Body(hotspot open, 10mm Gap)												
Mode	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
GPRS 850+4slots	Front	128	824.2	1.360	0.132	100.00	1.000	29.22	29.50	1.067	0.141	/
	Back	128	824.2	-4.280	0.170	100.00	1.000	29.22	29.50	1.067	0.181	2#
	Left	128	824.2	-4.960	0.151	100.00	1.000	29.22	29.50	1.067	0.161	/
	Bottom	128	824.2	0.890	0.105	100.00	1.000	29.22	29.50	1.067	0.112	/
Head(0mm gap)												
Mode	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
GSM 1900 (voice)	Left Cheek	512	1850.2	-2.210	0.077	100.00	1.000	29.08	29.50	1.102	0.085	/
	Left Tilt	512	1850.2	-1.590	0.038	100.00	1.000	29.08	29.50	1.102	0.042	/
	Right Cheek	512	1850.2	1.970	0.084	100.00	1.000	29.08	29.50	1.102	0.093	3#
	Right Tilt	512	1850.2	-3.100	0.041	100.00	1.000	29.08	29.50	1.102	0.045	/
Body(hotspot open, 10mm Gap)												
Mode	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
GSM 1900 (voice)	Front	512	1850.2	-4.660	0.246	100.00	1.000	29.08	29.50	1.102	0.271	/
	Back	512	1850.2	1.410	0.186	100.00	1.000	29.08	29.50	1.102	0.205	/
	Left	512	1850.2	-2.700	0.205	100.00	1.000	29.08	29.50	1.102	0.226	/
	Bottom	512	1850.2	4.050	0.171	100.00	1.000	29.08	29.50	1.102	0.188	/
Body(hotspot open, 10mm Gap)												
Mode	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
GPRS 1900+4slots	Front	512	1850.2	-4.360	0.255	100.00	1.000	25.48	25.50	1.005	0.256	4#
	Back	512	1850.2	3.210	0.199	100.00	1.000	25.48	25.50	1.005	0.200	/
	Left	512	1850.2	3.200	0.205	100.00	1.000	25.48	25.50	1.005	0.206	/
	Bottom	512	1850.2	-0.410	0.141	100.00	1.000	25.48	25.50	1.005	0.142	/
Head(0mm gap)												
Mode	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
WCDMA Band 2 (RMC*)	Left Cheek	9400	1880.0	-1.660	0.598	100.00	1.000	21.84	22.00	1.038	0.621	/
	Left Tilt	9400	1880.0	3.150	0.298	100.00	1.000	21.84	22.00	1.038	0.309	/
	Right Cheek	9400	1880.0	4.080	0.642	100.00	1.000	21.84	22.00	1.038	0.666	5#
	Right Tilt	9400	1880.0	-2.030	0.321	100.00	1.000	21.84	22.00	1.038	0.333	/
Body(hotspot open, 10mm Gap)												
Mode	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
WCDMA Band 2 (RMC*)	Front	9400	1880.0	-1.940	0.453	100.00	1.000	21.84	22.00	1.038	0.470	6#
	Back	9400	1880.0	-0.750	0.180	100.00	1.000	21.84	22.00	1.038	0.187	/
	Left	9400	1880.0	-0.930	0.224	100.00	1.000	21.84	22.00	1.038	0.233	/
	Bottom	9400	1880.0	-0.670	0.028	100.00	1.000	21.84	22.00	1.038	0.029	/

Head(0mm gap)												
Mode	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
WCDMA Band 4 (RMC*)	Left Cheek	1413	1732.6	-4.100	0.512	100.00	1.000	22.34	22.50	1.038	0.531	/
	Left Tilt	1413	1732.6	-3.060	0.257	100.00	1.000	22.34	22.50	1.038	0.267	/
	Right Cheek	1413	1732.6	-1.110	0.532	100.00	1.000	22.34	22.50	1.038	0.552	7#
	Right Tilt	1413	1732.6	3.410	0.265	100.00	1.000	22.34	22.50	1.038	0.275	/
Body(hotspot open, 10mm Gap)												
Mode	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
WCDMA Band 4 (RMC*)	Front	1413	1732.6	-1.760	0.368	100.00	1.000	22.34	22.50	1.038	0.382	/
	Back	1413	1732.6	-1.930	0.494	100.00	1.000	22.34	22.50	1.038	0.513	8#
	Left	1413	1732.6	-1.990	0.299	100.00	1.000	22.34	22.50	1.038	0.310	/
	Bottom	1413	1732.6	4.930	0.205	100.00	1.000	22.34	22.50	1.038	0.213	/

Head(0mm gap)												
Mode	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
WCDMA Band 5 (RMC*)	Left Cheek	4233	846.6	2.700	0.076	100.00	1.000	22.81	23.00	1.045	0.079	/
	Left Tilt	4233	846.6	-1.470	0.038	100.00	1.000	22.81	23.00	1.045	0.040	/
	Right Cheek	4233	846.6	-4.740	0.088	100.00	1.000	22.81	23.00	1.045	0.092	9#
	Right Tilt	4233	846.6	-3.220	0.043	100.00	1.000	22.81	23.00	1.045	0.045	/
Body(hotspot open, 10mm Gap)												
Mode	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
WCDMA Band 5 (RMC*)	Front	4233	846.6	4.800	0.086	100.00	1.000	22.81	23.00	1.045	0.090	/
	Back	4233	846.6	-3.870	0.149	100.00	1.000	22.81	23.00	1.045	0.156	10#
	Left	4233	846.6	-0.190	0.105	100.00	1.000	22.81	23.00	1.045	0.110	/
	Bottom	4233	846.6	4.870	0.055	100.00	1.000	22.81	23.00	1.045	0.057	/

Head(0mm gap)													
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
Band 2 (BW: 20MHz)	1RB	Left Cheek	19100	1900.0	0.040	0.679	100.00	1.000	28.58	29.00	1.102	0.748	/
		Left Tilt	19100	1900.0	-4.810	0.338	100.00	1.000	28.58	29.00	1.102	0.372	/
		Right Cheek	18700	1860.0	-0.84	0.723	100.00	1.000	28.34	28.50	1.038	0.750	/
		Right Cheek	18900	1880.0	2.360	0.754	100.00	1.000	28.50	29.00	1.122	0.846	/
		Right Cheek	19100	1900.0	-0.080	0.776	100.00	1.000	28.58	29.00	1.102	0.855	11#
		Right Cheek-Repeat	19100	1900.0	1.470	0.772	100.00	1.000	28.58	29.00	1.102	0.851	/
	Right Tilt	19100	1900.0	4.810	0.389	100.00	1.000	28.58	29.00	1.102	0.429	/	
	50%RB	Left Cheek	19100	1900.0	-0.420	0.658	100.00	1.000	27.39	27.50	1.026	0.675	/
		Left Tilt	19100	1900.0	1.290	0.328	100.00	1.000	27.39	27.50	1.026	0.337	/
		Right Cheek	19100	1900.0	4.160	0.718	100.00	1.000	27.39	27.50	1.026	0.737	/
Right Tilt		19100	1900.0	-4.860	0.359	100.00	1.000	27.39	27.50	1.026	0.368	/	
Body(hotspot open, 10mm Gap)													
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
Band 2 (BW: 20MHz)	1RB	Front	19100	1900.0	-2.490	0.388	100.00	1.000	28.58	29.00	1.102	0.428	12#
		Back	19100	1900.0	-1.280	0.371	100.00	1.000	28.58	29.00	1.102	0.409	/
		Left	19100	1900.0	-2.570	0.376	100.00	1.000	28.58	29.00	1.102	0.414	/
		Bottom	19100	1900.0	1.270	0.201	100.00	1.000	28.58	29.00	1.102	0.222	/
	50%RB	Front	19100	1900.0	-1.100	0.306	100.00	1.000	27.39	27.50	1.026	0.314	/
		Back	19100	1900.0	4.800	0.264	100.00	1.000	27.39	27.50	1.026	0.271	/
		Left	19100	1900.0	-3.400	0.335	100.00	1.000	27.39	27.50	1.026	0.344	/
		Bottom	19100	1900.0	2.970	0.168	100.00	1.000	27.39	27.50	1.026	0.172	/

Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
Band 4 (BW: 20MHz)	1RB	Left Cheek	20175	1732.5	-4.370	0.818	100.00	1.000	28.30	28.50	1.047	0.856	/
		Left Tilt	20175	1732.5	4.370	0.408	100.00	1.000	28.30	28.50	1.047	0.427	/
		Right Cheek	20050	1720.0	3.251	0.805	100.00	1.000	28.21	28.50	1.069	0.861	/
		Right Cheek	20175	1732.5	-1.130	0.826	100.00	1.000	28.30	28.50	1.047	0.865	13#
		Right Cheek-Repeat	20175	1732.5	3.011	0.821	100.00	1.000	28.30	28.50	1.047	0.860	/
		Right Cheek	20300	1745.0	-0.210	0.811	100.00	1.000	28.25	28.50	1.059	0.859	/
		Right Tilt	20175	1732.5	-3.360	0.414	100.00	1.000	28.30	28.50	1.047	0.433	/
	50%RB	Left Cheek	20175	1732.5	2.680	0.751	100.00	1.000	27.19	27.50	1.074	0.807	/
		Left Tilt	20175	1732.5	-4.450	0.343	100.00	1.000	27.19	27.50	1.074	0.368	/
		Right Cheek	20175	1732.5	-2.370	0.776	100.00	1.000	27.19	27.50	1.074	0.833	/
		Right Tilt	20175	1732.5	0.700	0.351	100.00	1.000	27.19	27.50	1.074	0.377	/

Body(hotspot open, 10mm Gap)

Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
Band 4 (BW: 20MHz)	1RB	Front	20175	1732.5	0.650	0.322	100.00	1.000	28.30	28.50	1.047	0.337	14#
		Back	20175	1732.5	-1.400	0.295	100.00	1.000	28.30	28.50	1.047	0.309	/
		Left	20175	1732.5	1.430	0.297	100.00	1.000	28.30	28.50	1.047	0.311	/
		Bottom	20175	1732.5	-4.660	0.269	100.00	1.000	28.30	28.50	1.047	0.282	/
	50%RB	Front	20175	1732.5	1.070	0.281	100.00	1.000	27.19	27.50	1.074	0.302	/
		Back	20175	1732.5	-4.650	0.250	100.00	1.000	27.19	27.50	1.074	0.269	/
		Left	20175	1732.5	-2.490	0.216	100.00	1.000	27.19	27.50	1.074	0.232	/
		Bottom	20175	1732.5	1.320	0.223	100.00	1.000	27.19	27.50	1.074	0.240	/

Head(0mm gap)

Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
Band 5 (BW: 10MHz)	1RB	Left Cheek	20450	829.0	-3.150	0.077	100.00	1.000	28.94	29.00	1.014	0.078	/
		Left Tilt	20450	829.0	0.430	0.039	100.00	1.000	28.94	29.00	1.014	0.040	/
		Right Cheek	20450	829.0	-0.500	0.083	100.00	1.000	28.94	29.00	1.014	0.084	15#
		Right Tilt	20450	829.0	-3.520	0.041	100.00	1.000	28.94	29.00	1.014	0.042	/
	50%RB	Left Cheek	20450	829.0	4.160	0.063	100.00	1.000	27.85	28.00	1.035	0.065	/
		Left Tilt	20450	829.0	4.940	0.032	100.00	1.000	27.85	28.00	1.035	0.033	/
		Right Cheek	20450	829.0	-4.970	0.071	100.00	1.000	27.85	28.00	1.035	0.073	/
		Right Tilt	20450	829.0	-2.090	0.037	100.00	1.000	27.85	28.00	1.035	0.038	/

Body(hotspot open, 10mm Gap)

Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
Band 5 (BW: 10MHz)	1RB	Front	20450	829.0	-0.740	0.100	100.00	1.000	28.94	29.00	1.014	0.101	/
		Back	20450	829.0	0.040	0.108	100.00	1.000	28.94	29.00	1.014	0.110	16#
		Left	20450	829.0	-2.770	0.105	100.00	1.000	28.94	29.00	1.014	0.106	/
		Bottom	20450	829.0	-1.680	0.091	100.00	1.000	28.94	29.00	1.014	0.092	/
	50%RB	Front	20450	829.0	0.310	0.082	100.00	1.000	27.85	28.00	1.035	0.085	/
		Back	20450	829.0	1.260	0.097	100.00	1.000	27.85	28.00	1.035	0.100	/
		Left	20450	829.0	4.800	0.091	100.00	1.000	27.85	28.00	1.035	0.094	/
		Bottom	20450	829.0	-3.130	0.073	100.00	1.000	27.85	28.00	1.035	0.076	/

Head(0mm gap)

Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
Band 12 (BW: 10MHz)	1RB	Left Cheek	23060	704.0	3.750	0.036	100.00	1.000	29.22	29.50	1.067	0.038	/
		Left Tilt	23060	704.0	-4.770	0.017	100.00	1.000	29.22	29.50	1.067	0.018	/
		Right Cheek	23060	704.0	-4.100	0.039	100.00	1.000	29.22	29.50	1.067	0.042	17#
		Right Tilt	23060	704.0	-0.090	0.019	100.00	1.000	29.22	29.50	1.067	0.020	/
	50%RB	Left Cheek	23060	704.0	0.510	0.033	100.00	1.000	28.09	28.50	1.099	0.036	/
		Left Tilt	23060	704.0	4.700	0.016	100.00	1.000	28.09	28.50	1.099	0.018	/
		Right Cheek	23060	704.0	-0.850	0.036	100.00	1.000	28.09	28.50	1.099	0.040	/
		Right Tilt	23060	704.0	-3.830	0.018	100.00	1.000	28.09	28.50	1.099	0.020	/

Body(hotspot open, 10mm Gap)													
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
Band 12 (BW: 10MHz)	1RB	Front	23060	704.0	1.620	0.111	100.00	1.000	29.22	29.50	1.067	0.118	/
		Back	23060	704.0	-3.010	0.118	100.00	1.000	29.22	29.50	1.067	0.126	18#
		Left	23060	704.0	4.050	0.113	100.00	1.000	29.22	29.50	1.067	0.121	/
		Bottom	23060	704.0	1.860	0.109	100.00	1.000	29.22	29.50	1.067	0.116	/
	50%RB	Front	23060	704.0	-2.840	0.094	100.00	1.000	28.09	28.50	1.099	0.103	/
		Back	23060	704.0	1.650	0.103	100.00	1.000	28.09	28.50	1.099	0.113	/
		Left	23060	704.0	2.150	0.085	100.00	1.000	28.09	28.50	1.099	0.093	/
		Bottom	23060	704.0	-4.120	0.074	100.00	1.000	28.09	28.50	1.099	0.081	/

Head(0mm gap)													
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
Band 13 (BW: 10MHz)	1RB	Left Cheek	23230	782.0	1.680	0.071	100.00	1.000	29.00	29.50	1.122	0.080	/
		Left Tilt	23230	782.0	-0.260	0.035	100.00	1.000	29.00	29.50	1.122	0.039	/
		Right Cheek	23230	782.0	0.210	0.073	100.00	1.000	29.00	29.50	1.122	0.082	19#
		Right Tilt	23230	782.0	-4.110	0.036	100.00	1.000	29.00	29.50	1.122	0.040	/
	50%RB	Left Cheek	23230	782.0	2.330	0.062	100.00	1.000	27.89	28.00	1.026	0.064	/
		Left Tilt	23230	782.0	-1.170	0.027	100.00	1.000	27.89	28.00	1.026	0.028	/
		Right Cheek	23230	782.0	-0.180	0.066	100.00	1.000	27.89	28.00	1.026	0.068	/
		Right Tilt	23230	782.0	3.700	0.030	100.00	1.000	27.89	28.00	1.026	0.031	/

Body(hotspot open, 10mm Gap)													
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
Band 13 (BW: 10MHz)	1RB	Front	23230	782.0	2.960	0.112	100.00	1.000	29.00	29.50	1.122	0.126	/
		Back	23230	782.0	1.980	0.118	100.00	1.000	29.00	29.50	1.122	0.132	20#
		Left	23230	782.0	2.970	0.114	100.00	1.000	29.00	29.50	1.122	0.128	/
		Bottom	23230	782.0	2.410	0.101	100.00	1.000	29.00	29.50	1.122	0.113	/
	50%RB	Front	23230	782.0	-0.800	0.093	100.00	1.000	27.89	28.00	1.026	0.095	/
		Back	23230	782.0	0.670	0.110	100.00	1.000	27.89	28.00	1.026	0.113	/
		Left	23230	782.0	-0.770	0.100	100.00	1.000	27.89	28.00	1.026	0.103	/
		Bottom	23230	782.0	4.760	0.082	100.00	1.000	27.89	28.00	1.026	0.084	/

Head(0mm gap)														
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.	
Band 25 (BW:20MHz)	1RB	Left Cheek	26590	1905.0	4.480	0.827	100.00	1.000	28.26	28.50	1.057	0.874	/	
		Left Tilt	26590	1905.0	-2.360	0.413	100.00	1.000	28.26	28.50	1.057	0.437	/	
		Right Cheek	26140	1860.0	2.031	0.810	100.00	1.000	28.17	28.50	1.079	0.874	/	
		Right Cheek	26365	1882.5	1.654	0.828	100.00	1.000	28.25	28.50	1.059	0.877	/	
		Right Cheek	26590	1905.0	-0.190	0.831	100.00	1.000	28.26	28.50	1.057	0.878	21#	
		Right Cheek-Repeat	26590	1905.0	-1.112	0.827	100.00	1.000	28.26	28.50	1.057	0.874	/	
		Right Tilt	26590	1905.0	-2.440	0.415	100.00	1.000	28.26	28.50	1.057	0.439	/	
		Left Cheek	26590	1905.0	-0.100	0.762	100.00	1.000	27.09	27.50	1.099	0.837	/	

	50%RB	Left Tilt	26590	1905.0	1.400	0.340	100.00	1.000	27.09	27.50	1.099	0.374	/
		Right Cheek	26590	1905.0	-2.140	0.767	100.00	1.000	27.09	27.50	1.099	0.843	/
		Right Tilt	26590	1905.0	3.620	0.350	100.00	1.000	27.09	27.50	1.099	0.385	/
		Body(hotspot open, 10mm Gap)											
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
Band 25 (BW: 20MHz)	1RB	Front	26590	1905.0	-2.540	0.436	100.00	1.000	28.26	28.50	1.057	0.461	22#
		Back	26590	1905.0	-3.180	0.418	100.00	1.000	28.26	28.50	1.057	0.442	/
		Left	26590	1905.0	-2.850	0.425	100.00	1.000	28.26	28.50	1.057	0.449	/
		Bottom	26590	1905.0	3.370	0.387	100.00	1.000	28.26	28.50	1.057	0.409	/
	50%RB	Front	26590	1905.0	2.870	0.402	100.00	1.000	27.09	27.50	1.099	0.442	/
		Back	26590	1905.0	3.620	0.339	100.00	1.000	27.09	27.50	1.099	0.373	/
		Left	26590	1905.0	-3.350	0.351	100.00	1.000	27.09	27.50	1.099	0.386	/
		Bottom	26590	1905.0	-1.010	0.299	100.00	1.000	27.09	27.50	1.099	0.329	/

Head(0mm gap)													
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
Band 41 (BW:20MHz)	1RB	Left Cheek	40620	2593.0	4.950	0.311	100.00	1.000	29.34	29.50	1.038	0.323	/
		Left Tilt	40620	2593.0	0.970	0.156	100.00	1.000	29.34	29.50	1.038	0.162	/
		Right Cheek	40620	2593.0	-0.060	0.318	100.00	1.000	29.34	29.50	1.038	0.330	23#
		Right Tilt	40620	2593.0	-0.310	0.159	100.00	1.000	29.34	29.50	1.038	0.165	/
	50%RB	Left Cheek	40620	2593.0	-2.860	0.284	100.00	1.000	28.25	28.50	1.059	0.301	/
		Left Tilt	40620	2593.0	3.270	0.143	100.00	1.000	28.25	28.50	1.059	0.151	/
		Right Cheek	40620	2593.0	-0.090	0.289	100.00	1.000	28.25	28.50	1.059	0.306	/
		Right Tilt	40620	2593.0	3.200	0.144	100.00	1.000	28.25	28.50	1.059	0.152	/

Body(hotspot open, 10mm Gap)													
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
Band 41 (BW: 20MHz)	1RB	Front	40620	2593.0	-0.810	0.145	100.00	1.000	29.34	29.50	1.038	0.151	24#
		Back	40620	2593.0	3.740	0.126	100.00	1.000	29.34	29.50	1.038	0.131	/
		Left	40620	2593.0	1.750	0.136	100.00	1.000	29.34	29.50	1.038	0.141	/
		Bottom	40620	2593.0	3.610	0.101	100.00	1.000	29.34	29.50	1.038	0.105	/
	50%RB	Front	40620	2593.0	0.020	0.122	100.00	1.000	28.25	28.50	1.059	0.129	/
		Back	40620	2593.0	2.860	0.102	100.00	1.000	28.25	28.50	1.059	0.108	/
		Left	40620	2593.0	-3.250	0.116	100.00	1.000	28.25	28.50	1.059	0.123	/
		Bottom	40620	2593.0	-0.150	0.086	100.00	1.000	28.25	28.50	1.059	0.091	/

Head(0mm gap)													
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
Band 66 (BW: 20MHz)	1RB	Left Cheek	132072	1720.0	1.390	0.821	100.00	1.000	24.44	24.50	1.014	0.832	/
		Left Tilt	132072	1720.0	-2.150	0.442	100.00	1.000	24.44	24.50	1.014	0.448	/
		Right Cheek	132072	1720.0	-0.310	0.837	100.00	1.000	24.44	24.50	1.014	0.849	25#
		Right Cheek-Repeat	132072	1720.0	0.201	0.832	100.00	1.000	24.44	24.50	1.014	0.844	/
		Right Cheek	132322	1745.0	0.039	0.698	100.00	1.000	21.95	22.00	1.012	0.706	/
		Right Cheek	132572	1770.0	-1.224	0.487	100.00	1.000	18.41	18.50	1.021	0.497	/
		Right Tilt	132072	1720.0	3.750	0.452	100.00	1.000	24.44	24.50	1.014	0.458	/
	50%RB	Left Cheek	132072	1720.0	0.200	0.767	100.00	1.000	23.27	23.50	1.054	0.808	/
		Left Tilt	132072	1720.0	-4.630	0.405	100.00	1.000	23.27	23.50	1.054	0.427	/
		Right Cheek	132072	1720.0	3.600	0.775	100.00	1.000	23.27	23.50	1.054	0.817	/
		Right Tilt	132072	1720.0	-3.760	0.421	100.00	1.000	23.27	23.50	1.054	0.444	/

Body(hotspot open, 10mm Gap)													
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
Band 66 (BW: 20MHz)	1RB	Front	132072	1720.0	1.410	0.381	100.00	1.000	24.44	24.50	1.014	0.386	26#
		Back	132072	1720.0	1.800	0.342	100.00	1.000	24.44	24.50	1.014	0.347	/
		Left	132072	1720.0	2.980	0.267	100.00	1.000	24.44	24.50	1.014	0.271	/
		Bottom	132072	1720.0	-2.900	0.307	100.00	1.000	24.44	24.50	1.014	0.311	/
	50%RB	Front	132072	1720.0	-3.830	0.354	100.00	1.000	23.27	23.50	1.054	0.373	/
		Back	132072	1720.0	0.470	0.321	100.00	1.000	23.27	23.50	1.054	0.338	/
		Left	132072	1720.0	-0.180	0.240	100.00	1.000	23.27	23.50	1.054	0.253	/
		Bottom	132072	1720.0	4.310	0.294	100.00	1.000	23.27	23.50	1.054	0.310	/

Head(0mm gap)													
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
Band 71 (BW: 20MHz)	1RB	Left Cheek	133222	673.0	-0.640	0.030	100.00	1.000	28.79	29.00	1.050	0.032	/
		Left Tilt	133222	673.0	1.330	0.011	100.00	1.000	28.79	29.00	1.050	0.012	/
		Right Cheek	133222	673.0	-4.030	0.035	100.00	1.000	28.79	29.00	1.050	0.037	27#
		Right Tilt	133222	673.0	1.790	0.017	100.00	1.000	28.79	29.00	1.050	0.018	/
	50%RB	Left Cheek	133222	673.0	-0.680	0.018	100.00	1.000	27.52	28.00	1.117	0.020	/
		Left Tilt	133222	673.0	4.500	0.009	100.00	1.000	27.52	28.00	1.117	0.010	/
		Right Cheek	133222	673.0	3.520	0.019	100.00	1.000	27.52	28.00	1.117	0.021	/
		Right Tilt	133222	673.0	2.050	0.007	100.00	1.000	27.52	28.00	1.117	0.008	/

Body(hotspot open, 10mm Gap)													
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
Band 71 (BW: 20MHz)	1RB	Front	133222	673.0	2.460	0.140	100.00	1.000	28.79	29.00	1.050	0.147	/
		Back	133222	673.0	-0.110	0.149	100.00	1.000	28.79	29.00	1.050	0.156	28#
		Left	133222	673.0	0.370	0.103	100.00	1.000	28.79	29.00	1.050	0.108	/
		Bottom	133222	673.0	2.590	0.127	100.00	1.000	28.79	29.00	1.050	0.133	/
	50%RB	Front	133222	673.0	-2.690	0.117	100.00	1.000	27.52	28.00	1.117	0.131	/
		Back	133222	673.0	2.970	0.129	100.00	1.000	27.52	28.00	1.117	0.144	/
		Left	133222	673.0	-1.070	0.073	100.00	1.000	27.52	28.00	1.117	0.082	/
		Bottom	133222	673.0	-0.430	0.089	100.00	1.000	27.52	28.00	1.117	0.099	/

Head(0mm gap)												
Mode	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
2.4g (2.4~2.4835) 802.11b	Left Cheek	6	2437	4.640	0.300	100.00	1.000	15.74	16.00	1.062	0.319	/
	Left Tilt	6	2437	-4.830	0.152	100.00	1.000	15.74	16.00	1.062	0.161	/
	Right Cheek	6	2437	-4.800	0.302	100.00	1.000	15.74	16.00	1.062	0.321	29#
	Right Tilt	6	2437	-0.630	0.150	100.00	1.000	15.74	16.00	1.062	0.159	/
Body(hotspot open, 10mm Gap)												
Mode	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
2.4g (2.4~2.4835) 802.11b	Front	6	2437	-0.720	0.619	100.00	1.000	15.74	16.00	1.062	0.657	/
	Back	6	2437	-1.930	0.638	100.00	1.000	15.74	16.00	1.062	0.678	30#
	Right	6	2437	-0.040	0.571	100.00	1.000	15.74	16.00	1.062	0.606	/
	Top	6	2437	4.350	0.597	100.00	1.000	15.74	16.00	1.062	0.634	/

Head(0mm gap)												
Mode	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
U-NII-1 (5.150~5.250) 802.11ac(VHT80)	Left Cheek	42	5210	0.960	0.267	100.00	1.000	14.15	14.50	1.084	0.289	/
	Left Tilt	42	5210	0.210	0.130	100.00	1.000	14.15	14.50	1.084	0.141	/
	Right Cheek	42	5210	2.840	0.276	100.00	1.000	14.15	14.50	1.084	0.299	31#
	Right Tilt	42	5210	0.190	0.137	100.00	1.000	14.15	14.50	1.084	0.149	/
Body(hotspot open, 10mm Gap)												
Mode	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
U-NII-1 (5.150~5.250) 802.11ac(VHT80)	Front	42	5210	0.820	0.189	100.00	1.000	14.15	14.50	1.084	0.205	/
	Back	42	5210	-4.180	0.207	100.00	1.000	14.15	14.50	1.084	0.224	32#
	Right	42	5210	4.310	0.141	100.00	1.000	14.15	14.50	1.084	0.153	/
	Top	42	5210	3.300	0.166	100.00	1.000	14.15	14.50	1.084	0.180	/
Head(0mm gap)												
Mode	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
U-NII-2a (5.250~5.350) 802.11ac(VHT80)	Left Cheek	58	5290	-4.040	0.602	100.00	1.000	13.95	14.00	1.012	0.609	/
	Left Tilt	58	5290	3.160	0.300	100.00	1.000	13.95	14.00	1.012	0.304	/
	Right Cheek	58	5290	1.630	0.611	100.00	1.000	13.95	14.00	1.012	0.618	33#
	Right Tilt	58	5290	2.040	0.304	100.00	1.000	13.95	14.00	1.012	0.308	/
Body(hotspot open, 10mm Gap)												
Mode	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
U-NII-2a (5.250~5.350) 802.11ac(VHT80)	Front	58	5290	3.720	0.723	100.00	1.000	13.95	14.00	1.012	0.732	/
	Back	58	5290	-1.760	0.758	100.00	1.000	13.95	14.00	1.012	0.767	34#
	Right	58	5290	3.030	0.683	100.00	1.000	13.95	14.00	1.012	0.691	/
	Top	58	5290	1.750	0.705	100.00	1.000	13.95	14.00	1.012	0.713	/
Head(0mm gap)												
Mode	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
U-NII-2c (5.470~5.725) 802.11ac(VHT80)	Left Cheek	122	5610	2.190	0.077	100.00	1.000	14.13	14.50	1.089	0.084	/
	Left Tilt	122	5610	-0.770	0.038	100.00	1.000	14.13	14.50	1.089	0.041	/
	Right Cheek	122	5610	-0.300	0.080	100.00	1.000	14.13	14.50	1.089	0.087	35#
	Right Tilt	122	5610	0.940	0.041	100.00	1.000	14.13	14.50	1.089	0.045	/

Body(hotspot open, 10mm Gap)												
Mode	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
U-NII-2c (5.470~5.725) 802.11ac(VHT80)	Front	122	5610	3.140	0.419	100.00	1.000	14.13	14.50	1.089	0.456	/
	Back	122	5610	-3.470	0.437	100.00	1.000	14.13	14.50	1.089	0.476	36#
	Right	122	5610	-1.150	0.365	100.00	1.000	14.13	14.50	1.089	0.397	/
	Top	122	5610	2.580	0.394	100.00	1.000	14.13	14.50	1.089	0.429	/
Head(0mm gap)												
Mode	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
U-NII-3 (5.725~5.850) 802.11ac(VHT80)	Left Cheek	155	5775	0.430	0.098	100.00	1.000	11.81	12.00	1.045	0.102	/
	Left Tilt	155	5775	2.130	0.047	100.00	1.000	11.81	12.00	1.045	0.049	/
	Right Cheek	155	5775	-2.080	0.103	100.00	1.000	11.81	12.00	1.045	0.108	37#
	Right Tilt	155	5775	-1.080	0.051	100.00	1.000	11.81	12.00	1.045	0.053	/
Body(hotspot open, 10mm Gap)												
Mode	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
U-NII-3 (5.725~5.850) 802.11ac(VHT80)	Front	155	5775	3.090	0.400	100.00	1.000	11.81	12.00	1.045	0.418	/
	Back	155	5775	-3.360	0.409	100.00	1.000	11.81	12.00	1.045	0.427	38#
	Right	155	5775	1.150	0.358	100.00	1.000	11.81	12.00	1.045	0.374	/
	Top	155	5775	1.920	0.381	100.00	1.000	11.81	12.00	1.045	0.398	/
Head(0mm gap)												
Mode	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
Bluetooth	Left Cheek	78	2480	1.900	0.004	100.00	1.000	5.49	5.50	1.002	0.004	/
	Left Tilt	78	2480	3.330	0.001	100.00	1.000	5.49	5.50	1.002	0.001	/
	Right Cheek	78	2480	-1.170	0.005	100.00	1.000	5.49	5.50	1.002	0.005	39#
	Right Tilt	78	2480	-0.560	0.003	100.00	1.000	5.49	5.50	1.002	0.003	/
Body(hotspot open, 10mm Gap)												
Mode	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
Bluetooth	Front	78	2480	2.030	0.003	100.00	1.000	5.49	5.50	1.002	0.003	/
	Back	78	2480	0.270	0.003	100.00	1.000	5.49	5.50	1.002	0.003	40#
	Right	78	2480	-1.030	0.001	100.00	1.000	5.49	5.50	1.002	0.001	/
	Top	78	2480	-3.610	0.002	100.00	1.000	5.49	5.50	1.002	0.002	/

Note:

- The maximum SAR Value of each test band is marked bold.
- SAR plot is provided only for the highest measured SAR in each exposure configuration, wireless mode and frequency band combination.
- Per KDB 447498 D04 v01, for each exposure position, if the highest output power channel Reported SAR $\leq 0.8W/kg$, other channels SAR testing is not necessary.
- Per KDB 447498 D04 v01, head/body-worn use is evaluated with the device positioned at 0mm/10 mm from a head/flat phantom respectively filled with head tissue-equivalent medium.
- Per KDB Publication 941225 D06 where SAR test considerations for handsets ($L \times W \geq 9 \text{ cm} \times 5 \text{ cm}$) are based on a composite test separation distance of 10 mm from the front, back and edges of the device with antennas 2.5 cm or closer to the edge of the device, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.
- Per KDB 447498 D04 v01, the report SAR is measured SAR value adjusted for maximum tune-up tolerance. Scaling Factor= $10^{[(\text{tune-up limit power(dBm)} - \text{Ave.power power (dBm)})/10]}$, where tune-up limit is the maximum rated power among all production units.
Reported SAR(W/kg)=Measured SAR (W/kg)*Scaling Factor.

11. SAR Measurement Variability

According to KDB 865664 D01, SAR measurement variability was assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media are required for SAR measurements in a frequency band, the variability measurement procedures should be applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. Alternatively, if the highest measured SAR for both head and body tissue-equivalent media are ≤ 1.45 W/kg and the ratio of these highest SAR values, i.e., largest divided by smallest value, is ≤ 1.10 , the highest SAR configuration for either head or body tissue-equivalent medium may be used to perform the repeated measurement. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR repeated measurement procedure:

1. When the highest measured SAR is < 0.80 W/kg, repeated measurement is not required.
2. When the highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
3. If the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 , or when the original or repeated measurement is ≥ 1.45 W/kg, perform a second repeated measurement.
4. If the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 , and the original, first or second repeated measurement is ≥ 1.5 W/kg, perform a third repeated measurement.

Note: For 1g SAR, the highest measured 1g SAR is $0.837 > 0.80$ W/kg, repeated measurement is as below.

Mode	Position	Ch.	Freq. (MHz)	1g Meas SAR (W/kg)	the ratio of largest to smallest SAR for the original and first repeated measurements
LTE Band 2	Right Cheek	19100	1900.0	0.776	1.005
	Right Cheek-repeat	19100	1900.0	0.772	
LTE Band 4	Right Cheek	20175	1732.5	0.826	1.006
	Right Cheek-repeat	20175	1732.5	0.821	
LTE Band 25	Right Cheek	26590	1905.0	0.831	1.005
	Right Cheek-repeat	26590	1905.0	0.827	
LTE Band 66	Right Cheek	132072	1720.0	0.837	1.006
	Right Cheek-repeat	132072	1720.0	0.832	

12. Simultaneous Transmission

Simultaneous transmission SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneous transmitting antenna. When the sum of SAR 1g of all simultaneously transmitting antennas in an operating mode and exposure condition combination is within the SAR limit (SAR 1g 1.6 W/kg), the simultaneous transmission SAR is not required. When the sum of SAR 1g is greater than the SAR limit (SAR 1g 1.6 W/kg), SAR test exclusion is determined by the SAR to Peak Location Ratio (SPLSR).

12.1 Simultaneous Transmission Mode Considerations

Simultaneous transmission SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneous transmitting antenna. The device has 2 Tx antennas, WWAN main antenna, Wifi/BT antenna supports 2.4G&5G WIFI and BT. The 2 antennas can always transmit simultaneously. The work mode combination is showed as below table.

Application Simultaneous Transmission information:

NO.	Configuration	Head	Body-worn
1	WWAN+WIFI(2.4g)	Yes	Yes
2	WWAN+WIFI(5g)	Yes	Yes
3	WWAN+BT	Yes	Yes

12.2 Sum SAR of Simultaneous Transmission

Head

Band	Channel Type	Test Position	Scaled				Σ SAR (W/kg) WWAN + WIFI 2.4G	Σ SAR (W/kg) WWAN + WIFI 5G	Σ SAR (W/kg) WWAN + BT	SPLSR	Remark
			WWAN	WIFI 2.4G	WIFI 5G	Bluetooth					
LTE Band 25	1RB	Left Cheek	0.874	0.319	0.609	0.004	1.193	1.483	0.878	N/A	N/A
		Left Tilt	0.437	0.161	0.304	0.001	0.598	0.741	0.438	N/A	N/A
		Right Cheek	0.878	0.321	0.618	0.005	1.199	1.496	0.883	N/A	N/A
		Right Tilt	0.439	0.159	0.308	0.003	0.598	0.747	0.442	N/A	N/A
	50%RB	Left Cheek	0.837	0.319	0.609	0.004	1.156	1.446	0.841	N/A	N/A
		Left Tilt	0.374	0.161	0.304	0.001	0.535	0.678	0.375	N/A	N/A
		Right Cheek	0.843	0.321	0.618	0.005	1.164	1.461	0.848	N/A	N/A
		Right Tilt	0.385	0.159	0.308	0.003	0.544	0.693	0.388	N/A	N/A

Hotspot(body-worn)

Band	Test Position	Scaled				Σ SAR (W/kg) WWAN + WIFI 2.4G	Σ SAR (W/kg) WWAN + WIFI 5G	Σ SAR (W/kg) WWAN + BT	SPLSR	Remark
		WWAN	WIFI 2.4G	WIFI 5G	Bluetooth					
WCDMA Band IV	Front	0.382	0.657	0.732	0.003	1.039	1.114	0.385	N/A	N/A
	Back	0.513	0.678	0.767	0.003	1.191	1.280	0.516	N/A	N/A
	Left	0.310	/	/	/	0.310	0.310	0.310	N/A	N/A
	Right	/	0.606	0.691	0.001	0.606	0.691	0.001	N/A	N/A
	Top	/	0.634	0.713	0.002	0.634	0.713	0.002	N/A	N/A
	Bottom	0.213	/	/	/	0.213	0.213	0.213	N/A	N/A

13. Test Equipment List

Description	Manufacturer	Model	Serial No./Version	Cal. Date	Cal. Due
E-Field Probe	MVG	SSE2	0125-EPGO-445	2025/02/01	2026/01/31
6 1/2 Digital Multimeter	Keithley	DMM6500	4527164	2024/10/25	2025/10/24
Wideband Radio Communication Tester	ROHDE & SCHWARZ	CMW500	161997	2024/10/25	2025/10/24
MXG Vector Signal Generator	Agilent	N5182A	MY46240163	2024/10/25	2025/10/24
E-Series Avg. Power Sensor	KEYSIGHT	E9300A	MY55050017	2025/04/02	2026/04/01
EPM Series Power Meter	KEYSIGHT	E4418B	MY41293435	2025/04/02	2026/04/01
MXA Signal Analyzer	KEYSIGHT	N9020A	MY54410409	2024/10/25	2025/10/24
Broadband Preamplifier	Schwarzbeck	BBV9718D	00008	2024/09/24	2025/09/23
Coupler	MERRIMAC	CWM-10R-10.8G	LOT-83391	N/A	N/A
750MHz Validation Dipole	MVG	SID750	07/22 DIP 0G750-655	2025/05/26	2028/05/25
835MHz Validation Dipole	MVG	SID835	07/22 DIP 0G835-656	2025/05/26	2028/05/25
1800MHz Validation Dipole	MVG	SID1800	07/22 DIP 1G800-657	2025/05/26	2028/05/25
1900MHz Validation Dipole	MVG	SID1900	07/22 DIP 1G900-658	2025/05/26	2028/05/25
2450MHz Validation Dipole	MVG	SID2450	07/22 DIP 2G450-662	2025/05/26	2028/05/25
2600MHz Validation Dipole	MVG	SID2600	07/22 DIP 2G600-663	2025/05/26	2028/05/25
5200MHz-5800MHz Validation Dipole	MVG	SID5000	07/22 DIP5G000-670	2025/05/26	2028/05/25
LIMESAR Dielectric Probe	MVG	SCLMP	06/22 OCPG88	2025/02/05	2026/02/04
ENA Series Network Analyzer	Agilent	E5071B	MY42301221	2024/10/25	2025/10/24
Thermometer	Riters	DT-232	21A11	2025/04/02	2026/04/01
Antenna network emulator	MVG	ANTA 74	07/22 ANTA 74	N/A	N/A
SAM Phantom	MVG	SAM	07/22 SAM149	N/A	N/A
Mobile Phone Positioning System	MVG	MSH 118	07/22 MSH 118	N/A	N/A
Mechanical Calibration Kit	PNA	N/A	N/A	2024/10/25	2025/10/24
Open SAR test software	MVG	N/A	V5.3.5	N/A	N/A
Note: For dipole antennas, BTF has adopted 3 years as calibration intervals, and on annual basis, every measurement dipole has been evaluated and is in compliance with the following criteria: 1. There is no physical damage on the dipole; 2. System validation with specific dipole is within 10% of calibrated value; 3. Return-loss in within 20% of calibrated measurement. 4. Impedance (real or imaginary parts) in within 5 Ohms of calibrated measurement.					

ANNEX A Simulating Liquid Verification Result

The dielectric parameters of the liquids were verified prior to the SAR evaluation using an SCLMP Dielectric Probe Kit.

Dielectric performance of tissue simulating liquid									
Frequency (MHz)	ϵ_r		σ (s/m)		Delta (ϵ_r)	Delta (σ)	Limit	Temp (°C)	Date
	Target	Measured	Target	Measured					
750	41.90	42.08	0.89	0.86	0.43%	-3.37%	±5%	21.3	23/8/2025
835	41.50	41.86	0.90	0.88	0.87%	-2.22%	±5%	20.3	25/8/2025
1800	40.00	40.21	1.40	1.35	0.53%	-3.57%	±5%	21.2	27/8/2025
1900	40.00	40.15	1.40	1.41	0.37%	0.71%	±5%	20.8	29/8/2025
2450	39.20	38.86	1.80	1.78	-0.87%	-1.11%	±5%	21.4	31/8/2025
2600	39.00	38.66	1.96	1.91	-0.87%	-2.55%	±5%	21.4	31/8/2025
5200	36.00	36.12	4.66	4.49	0.33%	-3.65%	±5%	21.1	1/9/2025
5400	35.80	35.91	4.86	4.89	0.31%	0.62%	±5%	20.9	3/9/2025
5600	35.50	35.53	5.07	5.01	0.08%	-1.18%	±5%	21.3	5/9/2025
5800	35.30	35.23	5.27	5.25	-0.20%	-0.38%	±5%	21.5	7/9/2025

NOTE: The dielectric parameters of the tissue-equivalent liquid should be measured under similar ambient conditions and within 2 °C of the conditions expected during the SAR evaluation to satisfy protocol requirements.

ANNEX B System Check Result

Comparing to the original SAR value provided by MVG, the validation data should be within its specification of 10 %(for 10 g).

Frequency (MHz)	Input Power (mW)	10g SAR (W/Kg)	1g SAR (W/Kg)	10g SAR 1W input power normalized (W/Kg)	1g SAR 1W input power normalized (W/Kg)	10g SAR Standard target (1W) (W/Kg)	1g SAR Standard target (1W) (W/Kg)	10g SAR Deviation	1g SAR Deviation
750	100	0.543	0.812	5.43	8.12	5.55	8.41	-2.16%	-3.45%
835	100	0.661	1.001	6.61	10.01	6.12	9.46	8.01%	5.81%
1800	100	1.970	3.729	19.70	37.29	19.83	37.93	-0.66%	-1.69%
1900	100	2.200	4.183	22.00	41.83	20.82	40.29	5.67%	3.82%
2450	100	2.667	5.719	26.67	57.19	24.55	52.72	8.64%	8.48%
2600	100	2.608	5.589	26.08	55.89	24.43	53.76	6.75%	3.96%
5200	100	2.253	7.547	22.53	75.47	22.78	78.16	-1.10%	-3.44%
5400	100	2.422	8.037	24.22	80.37	22.55	78.64	7.41%	2.20%
5600	100	2.355	7.955	23.55	79.55	23.95	82.72	-1.67%	-3.83%
5800	100	2.225	7.549	22.25	75.49	22.71	78.32	-2.03%	-3.61%

System Performance Check Data (750 MHz)

System check at 750 MHz

Date of measurement: 23/8/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.24
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW750
Channels/Frequency	Middle
Signal	CW

B. Permittivity

Middle TX Frequency (MHz)	750.000
Relative permittivity (real part)	42.082
Relative permittivity (imaginary part)	21.634
Conductivity (S/m)	0.861

C. SAR Surface and Volume




Maximum location: X=0.00, Y=0.00 ; SAR Peak: 1.13 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.543
SAR 1g (W/Kg)	0.812
Variation (%)	-3.950
Horizontal validation criteria: minimum distance (mm)	22.627417
Vertical validation criteria: SAR ratio M2/M1 (%)	69.887625

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	1.135	0.847	0.592	0.421	0.305	0.220	0.162



F. 3D Image



System Performance Check Data (835 MHz)

System check at 835 MHz

Date of measurement: 25/8/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.15
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW835
Channels/Frequency	Middle
Signal	CW

B. Permittivity

Middle TX Frequency (MHz)	835.000
Relative permittivity (real part)	41.858
Relative permittivity (imaginary part)	19.842
Conductivity (S/m)	0.882

C. SAR Surface and Volume




Maximum location: X=0.00, Y=0.00 ; SAR Peak: 1.39 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.661
SAR 1g (W/Kg)	1.001
Variation (%)	-1.280
Horizontal validation criteria: minimum distance (mm)	22.627417
Vertical validation criteria: SAR ratio M2/M1 (%)	69.929109

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	1.368	1.026	0.718	0.506	0.367	0.260	0.195



F. 3D Image



System Performance Check Data (1800 MHz)

System check at 1800 MHz

Date of measurement: 27/8/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.20
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW1800
Channels/Frequency	Middle
Signal	CW

B. Permittivity

Middle TX Frequency (MHz)	1800.000
Relative permittivity (real part)	40.214
Relative permittivity (imaginary part)	14.083
Conductivity (S/m)	1.351

C. SAR Surface and Volume




Maximum location: X=0.00, Y=0.00 ; SAR Peak: 6.16 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	1.970
SAR 1g (W/Kg)	3.729
Variation (%)	1.220
Horizontal validation criteria: minimum distance (mm)	16.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	57.156967

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	6.212	4.010	2.292	1.359	0.830	0.509	0.316



F. 3D Image



System Performance Check Data (1900 MHz)

System check at 1900 MHz

Date of measurement: 29/8/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.31
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW1900
Channels/Frequency	Middle
Signal	CW

B. Permittivity

Middle TX Frequency (MHz)	1900.000
Relative permittivity (real part)	40.149
Relative permittivity (imaginary part)	13.275
Conductivity (S/m)	1.413

C. SAR Surface and Volume




Maximum location: X=0.00, Y=0.00 ; SAR Peak: 6.74 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	2.200
SAR 1g (W/Kg)	4.183
Variation (%)	0.390
Horizontal validation criteria: minimum distance (mm)	16.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	57.870529

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	6.792	4.429	2.563	1.537	0.933	0.570	0.350



F. 3D Image



System Performance Check Data (2450 MHz)

System check at 2450 MHz

Date of measurement: 31/8/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.40
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW2450
Channels/Frequency	Higher
Signal	CW

B. Permittivity

Middle TX Frequency (MHz)	2450.000
Relative permittivity (real part)	38.863
Relative permittivity (imaginary part)	13.331
Conductivity (S/m)	1.782

C. SAR Surface and Volume




Maximum location: X=-1.00, Y=0.00 ; SAR Peak: 10.31 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	2.667
SAR 1g (W/Kg)	5.719
Variation (%)	4.260
Horizontal validation criteria: minimum distance (mm)	16.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	50.902696

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	10.399	6.262	3.187	1.729	0.917	0.509	0.269



F. 3D Image



System Performance Check Data (2600 MHz)

System check at 2600 MHz

Date of measurement: 31/8/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.27
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW2600
Channels/Frequency	Higher
Signal	CW

B. Permittivity

Middle TX Frequency (MHz)	2600.000
Relative permittivity (real part)	38.663
Relative permittivity (imaginary part)	12.634
Conductivity (S/m)	1.914

C. SAR Surface and Volume




Maximum location: X=-2.00, Y=1.00 ; SAR Peak: 9.86 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	2.608
SAR 1g (W/Kg)	5.589
Variation (%)	-0.620
Horizontal validation criteria: minimum distance (mm)	16.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	51.630450

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	9.955	6.073	3.136	1.645	0.871	0.466	0.252



F. 3D Image



System Performance Check Data (5200 MHz)

System check at 5200 MHz

Date of measurement: 1/9/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.18
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	7x7x12,dx=4mm dy=4mm dz=2.0mm, Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW5200
Channels/Frequency	Middle
Signal	CW

B. Permittivity

Middle TX Frequency (MHz)	5200.000
Relative permittivity (real part)	36.124
Relative permittivity (imaginary part)	16.254
Conductivity (S/m)	4.489

C. SAR Surface and Volume




Maximum location: X=0.00, Y=0.00 ; SAR Peak: 23.99 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	2.253
SAR 1g (W/Kg)	7.547
Variation (%)	-2.790
Horizontal validation criteria: minimum distance (mm)	8.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	53.150698

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00	18.00	20.00	22.00
SAR (W/Kg)	22.771	13.822	7.347	4.003	2.167	1.191	0.653	0.342	0.190	0.093	0.056	0.033



F. 3D Image



System Performance Check Data (5400 MHz)

System check at 5400 MHz

Date of measurement: 3/9/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.14
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	7x7x12,dx=4mm dy=4mm dz=2.0mm, Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW5400
Channels/Frequency	Middle
Signal	CW

B. Permittivity

Middle TX Frequency (MHz)	5400.000
Relative permittivity (real part)	35.913
Relative permittivity (imaginary part)	16.318
Conductivity (S/m)	4.894

C. SAR Surface and Volume




Maximum location: X=0.00, Y=0.00 ; SAR Peak: 25.35 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	2.422
SAR 1g (W/Kg)	8.037
Variation (%)	1.990
Horizontal validation criteria: minimum distance (mm)	8.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	53.016311

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00	18.00	20.00	22.00
SAR (W/Kg)	23.959	14.547	7.712	4.231	2.277	1.263	0.675	0.368	0.197	0.116	0.063	0.032



F. 3D Image



System Performance Check Data (5600 MHz)

System check at 5600 MHz

Date of measurement: 5/9/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.12
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	7x7x12, dx=4mm dy=4mm dz=2.0mm, Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW5600
Channels/Frequency	Middle
Signal	CW

B. Permittivity

Middle TX Frequency (MHz)	5600.000
Relative permittivity (real part)	35.534
Relative permittivity (imaginary part)	16.419
Conductivity (S/m)	5.014

C. SAR Surface and Volume




Maximum location: X=0.00, Y=0.00 ; SAR Peak: 26.02 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	2.355
SAR 1g (W/Kg)	7.955
Variation (%)	1.940
Horizontal validation criteria: minimum distance (mm)	8.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	52.072188

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00	18.00	20.00	22.00
SAR (W/Kg)	24.636	14.764	7.688	4.022	2.120	1.097	0.566	0.296	0.144	0.149	0.039	0.017



F. 3D Image



System Performance Check Data (5800 MHz)

System check at 5800 MHz

Date of measurement: 7/9/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.11
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	7x7x12,dx=4mm dy=4mm dz=2.0mm, Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW5800
Channels/Frequency	Middle
Signal	CW

B. Permittivity

Middle TX Frequency (MHz)	5800.000
Relative permittivity (real part)	35.231
Relative permittivity (imaginary part)	16.482
Conductivity (S/m)	5.248

C. SAR Surface and Volume




Maximum location: X=0.00, Y=0.00 ; SAR Peak: 25.00 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	2.225
SAR 1g (W/Kg)	7.549
Variation (%)	-2.600
Horizontal validation criteria: minimum distance (mm)	8.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	50.844943

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00	18.00	20.00	22.00
SAR (W/Kg)	23.801	14.069	7.153	3.602	1.813	0.919	0.477	0.230	0.108	0.053	0.045	0.012



F. 3D Image



ANNEX C Test Data

1-Head with front position in dist. 0mm on Channel 190 in GSM850 voice

SAR Measurement at GSM850 (Cheek, Right)

Date of measurement: 25/8/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.15
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Right head
Device Position	Cheek
Band	GSM850
Channels/Frequency	Middle (190)/ frequency 836.600 Mhz
Signal	TDMA (GSM)
Modulation	GMSK

B. Permittivity

Middle TX Frequency (MHz)	836.600
Relative permittivity (real part)	41.855
Relative permittivity (imaginary part)	19.832
Conductivity (S/m)	0.883

C. SAR Surface and Volume




Maximum location: X=-55.00, Y=-54.00 ; SAR Peak: 0.11 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.066
SAR 1g (W/Kg)	0.086
Variation (%)	-4.330
Horizontal validation criteria: minimum distance (mm)	16.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	81.757393

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.128	0.089	0.065	0.061	0.045	0.041	0.025



F. 3D Image



2-Body with back position in dist. 10mm on Channel 128 in GPRS850+4slots

SAR Measurement at GPRS850 (Body, Validation Plane)

Date of measurement: 25/8/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.15
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	GPRS850
Channels/Frequency	Lower (128)/ frequency 824.200 Mhz
Signal	TDMA (GPRS)
Modulation	GMSK (CS-1)
TX-slots	4

B. Permittivity

Middle TX Frequency (MHz)	824.200
Relative permittivity (real part)	41.886
Relative permittivity (imaginary part)	20.070
Conductivity (S/m)	0.879

C. SAR Surface and Volume




Maximum location: X=8.00, Y=-16.00 ; SAR Peak: 0.23 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.127
SAR 1g (W/Kg)	0.170
Variation (%)	-4.280
Horizontal validation criteria: minimum distance (mm)	16.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	79.368769

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.207	0.170	0.135	0.107	0.086	0.070	0.054



F. 3D Image



3-Head with front position in dist. 0mm on Channel 512 in GSM1900 voice

SAR Measurement at GSM1900 (Cheek, Right)

Date of measurement: 29/8/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.31
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Right head
Device Position	Cheek
Band	GSM1900
Channels/Frequency	Lower (512)/ frequency 1850.200 Mhz
Signal	TDMA (GSM)
Modulation	GMSK

B. Permittivity

Middle TX Frequency (MHz)	1850.200
Relative permittivity (real part)	40.181
Relative permittivity (imaginary part)	13.677
Conductivity (S/m)	1.382

C. SAR Surface and Volume




Maximum location: X=-33.00, Y=0.00 ; SAR Peak: 0.13 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.047
SAR 1g (W/Kg)	0.084
Variation (%)	1.970
Horizontal validation criteria: minimum distance (mm)	16.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	65.362427

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.123	0.090	0.059	0.036	0.024	0.010	0.008



F. 3D Image



4-Body with front position in dist. 10mm on Channel 512 in GPRS1900+4slots

SAR Measurement at GPRS1900 (Body, Validation Plane)

Date of measurement: 29/8/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.31
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	GPRS1900
Channels/Frequency	Lower (512)/ frequency 1850.200 Mhz
Signal	TDMA (GPRS)
Modulation	GMSK (CS-1)
TX-slots	4

B. Permittivity

Middle TX Frequency (MHz)	1850.200
Relative permittivity (real part)	40.181
Relative permittivity (imaginary part)	13.677
Conductivity (S/m)	1.382

C. SAR Surface and Volume




D. SAR 1g & 10g


SAR 10g (W/Kg)	0.149
SAR 1g (W/Kg)	0.255
Variation (%)	-4.360
Horizontal validation criteria: minimum distance (mm)	22.627417
Vertical validation criteria: SAR ratio M2/M1 (%)	63.912733

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.373	0.269	0.172	0.107	0.065	0.039	0.026



F. 3D Image



5-Head with front position in dist. 0mm on Channel 9400 in WCDMA Band 2

SAR Measurement at Band 2 (1900) (Cheek, Right)

Date of measurement: 29/8/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.31
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Right head
Device Position	Cheek
Band	Band 2 (1900)
Channels/Frequency	Middle (9400)/ frequency 1880.000 Mhz
Signal	WCDMA
Mode	Release 99
Connection Type	RMC, 12.2 kbps

B. Permittivity

Middle TX Frequency (MHz)	1880.000
Relative permittivity (real part)	40.162
Relative permittivity (imaginary part)	13.437
Conductivity (S/m)	1.401

C. SAR Surface and Volume




Maximum location: X=-35.00, Y=-1.00 ; SAR Peak: 1.00 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.354
SAR 1g (W/Kg)	0.642
Variation (%)	4.080
Horizontal validation criteria: minimum distance (mm)	16.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	63.471181

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.972	0.698	0.443	0.272	0.162	0.093	0.058



F. 3D Image



6-Body with front position in dist. 10mm on Channel 9400 in WCDMA Band 2

SAR Measurement at Band 2 (1900) (Body, Validation Plane)

Date of measurement: 29/8/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.31
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	Band 2 (1900)
Channels/Frequency	Middle (9400)/ frequency 1880.000 Mhz
Signal	WCDMA
Mode	Release 99
Connection Type	RMC, 12.2 kbps

B. Permittivity

Middle TX Frequency (MHz)	1880.000
Relative permittivity (real part)	40.162
Relative permittivity (imaginary part)	13.437
Conductivity (S/m)	1.401

C. SAR Surface and Volume




Maximum location: X=-23.00, Y=18.00 ; SAR Peak: 0.69 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.263
SAR 1g (W/Kg)	0.453
Variation (%)	-1.940
Horizontal validation criteria: minimum distance (mm)	17.888544
Vertical validation criteria: SAR ratio M2/M1 (%)	62.733527

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.689	0.478	0.300	0.188	0.117	0.074	0.043



F. 3D Image



7-Head with front position in dist. 0mm on Channel 1413 in WCDMA Band 4

SAR Measurement at Band 4 (1700) (Cheek, Right)

Date of measurement: 27/8/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.20
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Right head
Device Position	Cheek
Band	Band 4 (1700)
Channels/Frequency	Middle (1413)/ frequency 1732.600 Mhz
Signal	WCDMA
Mode	Release 99
Connection Type	RMC, 12.2 kbps

B. Permittivity

Middle TX Frequency (MHz)	1732.600
Relative permittivity (real part)	40.329
Relative permittivity (imaginary part)	14.485
Conductivity (S/m)	1.318

C. SAR Surface and Volume




Maximum location: X=-34.00, Y=0.00 ; SAR Peak: 0.81 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.300
SAR 1g (W/Kg)	0.532
Variation (%)	-1.110
Horizontal validation criteria: minimum distance (mm)	16.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	64.424022

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.794	0.575	0.371	0.233	0.136	0.082	0.046



F. 3D Image



8-Body with back position in dist. 10mm on Channel 1413 in WCDMA Band 4

SAR Measurement at Band 4 (1700) (Body, Validation Plane)

Date of measurement: 27/8/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.20
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	Band 4 (1700)
Channels/Frequency	Middle (1413)/ frequency 1732.600 Mhz
Signal	WCDMA
Mode	Release 99
Connection Type	RMC, 12.2 kbps

B. Permittivity

Middle TX Frequency (MHz)	1732.600
Relative permittivity (real part)	40.329
Relative permittivity (imaginary part)	14.485
Conductivity (S/m)	1.318

C. SAR Surface and Volume




D. SAR 1g & 10g


SAR 10g (W/Kg)	0.282
SAR 1g (W/Kg)	0.494
Variation (%)	-1.930
Horizontal validation criteria: minimum distance (mm)	16.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	60.564932

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.772	0.520	0.315	0.195	0.122	0.076	0.046



F. 3D Image



9-Head with front position in dist. 0mm on Channel 4233 in WCDMA Band 5

SAR Measurement at Band 5 (850) (Cheek, Right)

Date of measurement: 25/8/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.15
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Right head
Device Position	Cheek
Band	Band 5 (850)
Channels/Frequency	Higher (4233)/ frequency 846.600 Mhz
Signal	WCDMA
Mode	Release 99
Connection Type	RMC, 12.2 kbps

B. Permittivity

Middle TX Frequency (MHz)	846.600
Relative permittivity (real part)	41.838
Relative permittivity (imaginary part)	19.773
Conductivity (S/m)	0.888

C. SAR Surface and Volume




Maximum location: X=-54.00, Y=-51.00 ; SAR Peak: 0.13 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.062
SAR 1g (W/Kg)	0.088
Variation (%)	-4.740
Horizontal validation criteria: minimum distance (mm)	37.271034
Vertical validation criteria: SAR ratio M2/M1 (%)	71.724090

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.148	0.094	0.062	0.047	0.054	0.041	0.041



F. 3D Image



10-Body with back position in dist. 10mm on Channel 4233 in WCDMA Band 5

SAR Measurement at Band 5 (850) (Body, Validation Plane)

Date of measurement: 25/8/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.15
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	Band 5 (850)
Channels/Frequency	Higher (4233)/ frequency 846.600 Mhz
Signal	WCDMA
Mode	Release 99
Connection Type	RMC, 12.2 kbps

B. Permittivity

Middle TX Frequency (MHz)	846.600
Relative permittivity (real part)	41.838
Relative permittivity (imaginary part)	19.773
Conductivity (S/m)	0.888

C. SAR Surface and Volume




Maximum location: X=1.00, Y=-16.00 ; SAR Peak: 0.23 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.086
SAR 1g (W/Kg)	0.149
Variation (%)	-3.870
Horizontal validation criteria: minimum distance (mm)	17.888544
Vertical validation criteria: SAR ratio M2/M1 (%)	61.959215

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.228	0.159	0.098	0.064	0.042	0.024	0.017



F. 3D Image



11-Head with front position in dist. 0mm on Channel 19100 in LTE band 2

SAR Measurement at LTE band 2 (Cheek, Right)

Date of measurement: 29/8/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.31
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Right head
Device Position	Cheek
Band	LTE band 2
Channels/Frequency	Higher (19100)/ frequency 1900.000 Mhz
Signal	LTE FDD
Cell Bandwidth	20 Mhz
Modulation	SC-OFDM - QPSK
RB offset	50
RB size	1

B. Permittivity

Middle TX Frequency (MHz)	1900.090
Relative permittivity (real part)	40.149
Relative permittivity (imaginary part)	13.275
Conductivity (S/m)	1.413

C. SAR Surface and Volume




Maximum location: X=-32.00, Y=-8.00 ; SAR Peak: 1.24 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.410
SAR 1g (W/Kg)	0.776
Variation (%)	-0.080
Horizontal validation criteria: minimum distance (mm)	16.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	61.269532

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	1.221	0.846	0.518	0.309	0.179	0.103	0.058



F. 3D Image



12-Body with front position in dist. 10mm on Channel 19100 in LTE band 2

SAR Measurement at LTE band 2 (Body, Validation Plane)

Date of measurement: 29/8/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.31
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 2
Channels/Frequency	Higher (19100)/ frequency 1900.000 Mhz
Signal	LTE FDD
Cell Bandwidth	20 Mhz
Modulation	SC-OFDM - QPSK
RB offset	50
RB size	1

B. Permittivity

Middle TX Frequency (MHz)	1900.090
Relative permittivity (real part)	40.149
Relative permittivity (imaginary part)	13.275
Conductivity (S/m)	1.413

C. SAR Surface and Volume




D. SAR 1g & 10g


SAR 10g (W/Kg)	0.224
SAR 1g (W/Kg)	0.388
Variation (%)	-2.490
Horizontal validation criteria: minimum distance (mm)	22.627417
Vertical validation criteria: SAR ratio M2/M1 (%)	63.228306

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.582	0.413	0.261	0.166	0.099	0.064	0.039



F. 3D Image



13-Head with front position in dist. 0mm on Channel 20175 in LTE band 4

SAR Measurement at LTE band 4 (Cheek, Right)

Date of measurement: 27/8/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.20
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Right head
Device Position	Cheek
Band	LTE band 4
Channels/Frequency	Middle (20175)/ frequency 1732.500 Mhz
Signal	LTE FDD
Cell Bandwidth	20 Mhz
Modulation	SC-OFDM - QPSK
RB offset	50
RB size	1

B. Permittivity

Middle TX Frequency (MHz)	1732.590
Relative permittivity (real part)	40.329
Relative permittivity (imaginary part)	14.485
Conductivity (S/m)	1.318

C. SAR Surface and Volume




Maximum location: X=-39.00, Y=-10.00 ; SAR Peak: 1.33 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.432
SAR 1g (W/Kg)	0.826
Variation (%)	-1.130
Horizontal validation criteria: minimum distance (mm)	16.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	61.029205

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	1.310	0.909	0.555	0.325	0.186	0.101	0.058



F. 3D Image



14-Body with front position in dist. 10mm on Channel 20175 in LTE band 4

SAR Measurement at LTE band 4 (Body, Validation Plane)

Date of measurement: 27/8/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.20
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 4
Channels/Frequency	Middle (20175)/ frequency 1732.500 Mhz
Signal	LTE FDD
Cell Bandwidth	20 Mhz
Modulation	SC-OFDM - QPSK
RB offset	50
RB size	1

B. Permittivity

Middle TX Frequency (MHz)	1732.590
Relative permittivity (real part)	40.329
Relative permittivity (imaginary part)	14.485
Conductivity (S/m)	1.318

C. SAR Surface and Volume




D. SAR 1g & 10g


SAR 10g (W/Kg)	0.194
SAR 1g (W/Kg)	0.322
Variation (%)	0.650
Horizontal validation criteria: minimum distance (mm)	22.627417
Vertical validation criteria: SAR ratio M2/M1 (%)	64.350672

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.469	0.339	0.218	0.141	0.088	0.050	0.036



F. 3D Image



15-Head with front position in dist. 0mm on Channel 20450 in LTE band 5

SAR Measurement at LTE band 5 (Cheek, Right)

Date of measurement: 25/8/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.15
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Right head
Device Position	Cheek
Band	LTE band 5
Channels/Frequency	Lower (20450)/ frequency 829.000 Mhz
Signal	LTE FDD
Cell Bandwidth	10 Mhz
Modulation	SC-OFDM - QPSK
RB offset	25
RB size	1

B. Permittivity

Middle TX Frequency (MHz)	829.090
Relative permittivity (real part)	41.874
Relative permittivity (imaginary part)	19.967
Conductivity (S/m)	0.881

C. SAR Surface and Volume




Maximum location: X=-51.00, Y=-54.00 ; SAR Peak: 0.10 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.065
SAR 1g (W/Kg)	0.083
Variation (%)	-0.500
Horizontal validation criteria: minimum distance (mm)	16.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	85.444085

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.092	0.086	0.073	0.062	0.050	0.043	0.035



F. 3D Image



16-Body with back position in dist. 10mm on Channel 20450 in LTE band 5

SAR Measurement at LTE band 5 (Body, Validation Plane)

Date of measurement: 25/8/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.15
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 5
Channels/Frequency	Lower (20450)/ frequency 829.000 Mhz
Signal	LTE FDD
Cell Bandwidth	10 Mhz
Modulation	SC-OFDM - QPSK
RB offset	25
RB size	1

B. Permittivity

Middle TX Frequency (MHz)	829.090
Relative permittivity (real part)	41.874
Relative permittivity (imaginary part)	19.967
Conductivity (S/m)	0.881

C. SAR Surface and Volume




D. SAR 1g & 10g


SAR 10g (W/Kg)	0.083
SAR 1g (W/Kg)	0.108
Variation (%)	0.040
Horizontal validation criteria: minimum distance (mm)	16.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	81.033743

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.133	0.112	0.088	0.071	0.051	0.044	0.031



F. 3D Image



17-Head with front position in dist. 0mm on Channel 23060 in LTE band 12

SAR Measurement at LTE band 12 (Cheek, Right)

Date of measurement: 23/8/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.24
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Right head
Device Position	Cheek
Band	LTE band 12
Channels/Frequency	Lower (23060)/ frequency 704.000 Mhz
Signal	LTE FDD
Cell Bandwidth	10 Mhz
Modulation	SC-OFDM - QPSK
RB offset	25
RB size	1

B. Permittivity

Middle TX Frequency (MHz)	704.090
Relative permittivity (real part)	42.203
Relative permittivity (imaginary part)	22.602
Conductivity (S/m)	0.850

C. SAR Surface and Volume




Maximum location: X=-63.00, Y=-40.00 ; SAR Peak: 0.05 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.029
SAR 1g (W/Kg)	0.039
Variation (%)	-4.100
Horizontal validation criteria: minimum distance (mm)	16.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	76.249492

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.058	0.040	0.028	0.024	0.019	0.015	0.012



F. 3D Image



18-Body with back position in dist. 10mm on Channel 23060 in LTE band 12

SAR Measurement at LTE band 12 (Body, Validation Plane)

Date of measurement: 23/8/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.24
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 12
Channels/Frequency	Lower (23060)/ frequency 704.000 Mhz
Signal	LTE FDD
Cell Bandwidth	10 Mhz
Modulation	SC-OFDM - QPSK
RB offset	25
RB size	1

B. Permittivity

Middle TX Frequency (MHz)	704.090
Relative permittivity (real part)	42.203
Relative permittivity (imaginary part)	22.602
Conductivity (S/m)	0.850

C. SAR Surface and Volume




Maximum location: X=-6.00, Y=-49.00 ; SAR Peak: 0.15 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.091
SAR 1g (W/Kg)	0.118
Variation (%)	-3.010
Horizontal validation criteria: minimum distance (mm)	16.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	81.955203

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.139	0.121	0.099	0.080	0.063	0.050	0.039



F. 3D Image



19-Head with front position in dist. 0mm on Channel 23230 in LTE band 13

SAR Measurement at LTE band 13 (Cheek, Right)

Date of measurement: 23/8/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.24
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Right head
Device Position	Cheek
Band	LTE band 13
Channels/Frequency	Middle (23230)/ frequency 782.000 Mhz
Signal	LTE FDD
Cell Bandwidth	10 Mhz
Modulation	SC-OFDM - QPSK
RB offset	25
RB size	1

B. Permittivity

Middle TX Frequency (MHz)	782.090
Relative permittivity (real part)	41.997
Relative permittivity (imaginary part)	20.957
Conductivity (S/m)	0.869

C. SAR Surface and Volume




Maximum location: X=-54.00, Y=-42.00 ; SAR Peak: 0.09 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.054
SAR 1g (W/Kg)	0.073
Variation (%)	0.210
Horizontal validation criteria: minimum distance (mm)	16.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	77.470419

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.088	0.074	0.058	0.047	0.040	0.030	0.029



F. 3D Image



20-Body with back position in dist. 10mm on Channel 23230 in LTE band 13

SAR Measurement at LTE band 13 (Body, Validation Plane)

Date of measurement: 23/8/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.24
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 13
Channels/Frequency	Middle (23230)/ frequency 782.000 Mhz
Signal	LTE FDD
Cell Bandwidth	10 Mhz
Modulation	SC-OFDM - QPSK
RB offset	25
RB size	1

B. Permittivity

Middle TX Frequency (MHz)	782.090
Relative permittivity (real part)	41.997
Relative permittivity (imaginary part)	20.957
Conductivity (S/m)	0.869

C. SAR Surface and Volume




D. SAR 1g & 10g


SAR 10g (W/Kg)	0.083
SAR 1g (W/Kg)	0.118
Variation (%)	1.980
Horizontal validation criteria: minimum distance (mm)	16.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	80.453060

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.140	0.121	0.097	0.079	0.063	0.049	0.042



F. 3D Image



21-Head with front position in dist. 0mm on Channel 26590 in LTE band 25

SAR Measurement at LTE band 25 (Cheek, Right)

Date of measurement: 29/8/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.31
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Right head
Device Position	Cheek
Band	LTE band 25
Channels/Frequency	Higher (26590)/ frequency 1905.000 Mhz
Signal	LTE FDD
Cell Bandwidth	20 Mhz
Modulation	SC-OFDM - QPSK
RB offset	50
RB size	1

B. Permittivity

Middle TX Frequency (MHz)	1905.090
Relative permittivity (real part)	40.137
Relative permittivity (imaginary part)	13.276
Conductivity (S/m)	1.416

C. SAR Surface and Volume




Maximum location: X=-30.00, Y=-2.00 ; SAR Peak: 1.27 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.471
SAR 1g (W/Kg)	0.831
Variation (%)	-0.190
Horizontal validation criteria: minimum distance (mm)	16.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	63.753651

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	1.252	0.890	0.567	0.356	0.218	0.131	0.078



F. 3D Image



22-Body with front position in dist. 10mm on Channel 26590 in LTE band 25

SAR Measurement at LTE band 25 (Body, Validation Plane)

Date of measurement: 29/8/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.31
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 25
Channels/Frequency	Higher (26590)/ frequency 1905.000 Mhz
Signal	LTE FDD
Cell Bandwidth	20 Mhz
Modulation	SC-OFDM - QPSK
RB offset	50
RB size	1

B. Permittivity

Middle TX Frequency (MHz)	1905.090
Relative permittivity (real part)	40.137
Relative permittivity (imaginary part)	13.276
Conductivity (S/m)	1.416

C. SAR Surface and Volume




D. SAR 1g & 10g


SAR 10g (W/Kg)	0.249
SAR 1g (W/Kg)	0.436
Variation (%)	-2.540
Horizontal validation criteria: minimum distance (mm)	17.888544
Vertical validation criteria: SAR ratio M2/M1 (%)	62.155234

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.670	0.464	0.289	0.182	0.111	0.065	0.039



F. 3D Image



23-Head with front position in dist. 0mm on Channel 40620 in LTE band 41

SAR Measurement at LTE band 41 (Cheek, Right)

Date of measurement: 31/8/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.27
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Right head
Device Position	Cheek
Band	LTE band 41
Channels/Frequency	Middle (40620)/ frequency 2593.000 Mhz
Signal	LTE TDD
Cell Bandwidth	20 Mhz
Modulation	SC-OFDM - QPSK
RB offset	50
RB size	1
Subframe configuration	0
Special subframe configuration	0
Cyclic prefix	Normal
Duty Cycle (%)	0.61

B. Permittivity

Middle TX Frequency (MHz)	2593.090
Relative permittivity (real part)	38.672
Relative permittivity (imaginary part)	12.666
Conductivity (S/m)	1.908

C. SAR Surface and Volume




Maximum location: X=-8.00, Y=8.00 ; SAR Peak: 0.58 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.142
SAR 1g (W/Kg)	0.318
Variation (%)	-0.060
Horizontal validation criteria: minimum distance (mm)	16.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	49.670649

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.571	0.341	0.170	0.085	0.043	0.018	0.008



F. 3D Image



24-Body with front position in dist. 10mm on Channel 40620 in LTE band 41

SAR Measurement at LTE band 41 (Body, Validation Plane)

Date of measurement: 31/8/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.27
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 41
Channels/Frequency	Middle (40620)/ frequency 2593.000 Mhz
Signal	LTE TDD
Cell Bandwidth	20 Mhz
Modulation	SC-OFDM - QPSK
RB offset	50
RB size	1
Subframe configuration	0
Special subframe configuration	0
Cyclic prefix	Normal
Duty Cycle (%)	0.61

B. Permittivity

Middle TX Frequency (MHz)	2593.090
Relative permittivity (real part)	38.672
Relative permittivity (imaginary part)	12.666
Conductivity (S/m)	1.908

C. SAR Surface and Volume




Maximum location: X=-21.00, Y=59.00 ; SAR Peak: 0.26 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.068
SAR 1g (W/Kg)	0.145
Variation (%)	-0.810
Horizontal validation criteria: minimum distance (mm)	16.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	50.442656

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.259	0.158	0.080	0.038	0.020	0.007	0.006



F. 3D Image



25-Head with front position in dist. 0mm on Channel 132072 in LTE band 66

SAR Measurement at LTE band 66 (Cheek, Right)

Date of measurement: 27/8/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.20
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Right head
Device Position	Cheek
Band	LTE band 66
Channels/Frequency	Lower (132072)/ frequency 1720.000 Mhz
Signal	LTE FDD
Cell Bandwidth	20 Mhz
Modulation	SC-OFDM - QPSK
RB offset	0
RB size	1

B. Permittivity

Middle TX Frequency (MHz)	1711.090
Relative permittivity (real part)	40.365
Relative permittivity (imaginary part)	14.614
Conductivity (S/m)	1.308

C. SAR Surface and Volume




Maximum location: X=-30.00, Y=-2.00 ; SAR Peak: 1.26 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.487
SAR 1g (W/Kg)	0.837
Variation (%)	-0.310
Horizontal validation criteria: minimum distance (mm)	16.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	65.076832

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	1.242	0.891	0.580	0.373	0.239	0.147	0.093



F. 3D Image



26-Body with front position in dist. 10mm on Channel 132072 in LTE band 66

SAR Measurement at LTE band 66 (Body, Validation Plane)

Date of measurement: 27/8/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.20
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 66
Channels/Frequency	Lower (132072)/ frequency 1720.000 Mhz
Signal	LTE FDD
Cell Bandwidth	20 Mhz
Modulation	SC-OFDM - QPSK
RB offset	0
RB size	1

B. Permittivity

Middle TX Frequency (MHz)	1711.090
Relative permittivity (real part)	40.365
Relative permittivity (imaginary part)	14.614
Conductivity (S/m)	1.308

C. SAR Surface and Volume




Maximum location: X=-31.00, Y=25.00 ; SAR Peak: 0.57 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.227
SAR 1g (W/Kg)	0.381
Variation (%)	1.410
Horizontal validation criteria: minimum distance (mm)	17.888544
Vertical validation criteria: SAR ratio M2/M1 (%)	64.322782

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.568	0.405	0.260	0.163	0.105	0.065	0.042



F. 3D Image



27-Head with front position in dist. 0mm on Channel 133222 in LTE band 71

SAR Measurement at LTE band 71 (Cheek, Right)

Date of measurement: 23/8/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.24
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Right head
Device Position	Cheek
Band	LTE band 71
Channels/Frequency	Lower (133222)/ frequency 673.000 Mhz
Signal	LTE FDD
Cell Bandwidth	20 Mhz
Modulation	SC-OFDM - QPSK
RB offset	0
RB size	1

B. Permittivity

Middle TX Frequency (MHz)	664.090
Relative permittivity (real part)	42.308
Relative permittivity (imaginary part)	23.445
Conductivity (S/m)	0.840

C. SAR Surface and Volume




Maximum location: X=-63.00, Y=-62.00 ; SAR Peak: 0.05 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.022
SAR 1g (W/Kg)	0.035
Variation (%)	-4.030
Horizontal validation criteria: minimum distance (mm)	16.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	81.603049

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.060	0.036	0.021	0.026	0.014	0.017	0.009



F. 3D Image



28-Body with back position in dist. 10mm on Channel 133222 in LTE band 71

SAR Measurement at LTE band 71 (Body, Validation Plane)

Date of measurement: 23/8/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.24
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 71
Channels/Frequency	Lower (133222)/ frequency 673.000 Mhz
Signal	LTE FDD
Cell Bandwidth	20 Mhz
Modulation	SC-OFDM - QPSK
RB offset	0
RB size	1

B. Permittivity

Middle TX Frequency (MHz)	664.090
Relative permittivity (real part)	42.308
Relative permittivity (imaginary part)	23.445
Conductivity (S/m)	0.840

C. SAR Surface and Volume




D. SAR 1g & 10g


SAR 10g (W/Kg)	0.115
SAR 1g (W/Kg)	0.149
Variation (%)	-0.110
Horizontal validation criteria: minimum distance (mm)	16.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	82.200461

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.173	0.154	0.127	0.102	0.080	0.064	0.052



F. 3D Image



29-Head with front position in dist. 0mm on Channel 6 in IEEE 802.11b ISM

SAR Measurement at ISM (Cheek, Right)

Date of measurement: 31/8/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.40
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Right head
Device Position	Cheek
Band	ISM
Channels/Frequency	Middle (6)/ frequency 2437.000 Mhz
Signal	IEEE 802.11 b

B. Permittivity

Middle TX Frequency (MHz)	2437.000
Relative permittivity (real part)	38.893
Relative permittivity (imaginary part)	13.330
Conductivity (S/m)	1.773

C. SAR Surface and Volume




Maximum location: X=-33.00, Y=-47.00 ; SAR Peak: 0.45 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.166
SAR 1g (W/Kg)	0.302
Variation (%)	-4.800
Horizontal validation criteria: minimum distance (mm)	16.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	64.661704

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.438	0.322	0.208	0.122	0.073	0.042	0.026



F. 3D Image



30-Body with back position in dist. 10mm on Channel 6 in IEEE 802.11b ISM

SAR Measurement at ISM (Body, Validation Plane)

Date of measurement: 31/8/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.40
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	ISM
Channels/Frequency	Middle (6)/ frequency 2437.000 Mhz
Signal	IEEE 802.11 b

B. Permittivity

Middle TX Frequency (MHz)	2437.000
Relative permittivity (real part)	38.893
Relative permittivity (imaginary part)	13.330
Conductivity (S/m)	1.773

C. SAR Surface and Volume




Maximum location: X=-18.00, Y=32.00 ; SAR Peak: 1.14 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.294
SAR 1g (W/Kg)	0.638
Variation (%)	-1.930
Horizontal validation criteria: minimum distance (mm)	16.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	52.256347

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	1.113	0.687	0.359	0.189	0.095	0.050	0.025



F. 3D Image



31-Head with front position in dist. 0mm on Channel 42 in IEEE 802.11ac U-NII

SAR Measurement at U-NII-1 (Cheek, Right)

Date of measurement: 1/9/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.18
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	7x7x12, dx=4mm dy=4mm dz=2.0mm, Complete
Phantom	Right head
Device Position	Cheek
Band	U-NII-1
Channels/Frequency	Higher (42)/ frequency 5210.000 Mhz
Signal	IEEE 802.11 ac

B. Permittivity

Middle TX Frequency (MHz)	5210.000
Relative permittivity (real part)	36.113
Relative permittivity (imaginary part)	16.257
Conductivity (S/m)	4.509

C. SAR Surface and Volume




Maximum location: X=-14.00, Y=-17.00 ; SAR Peak: 0.79 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.076
SAR 1g (W/Kg)	0.276
Variation (%)	2.840
Horizontal validation criteria: minimum distance (mm)	8.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	55.073054

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00	18.00	20.00	22.00
SAR (W/Kg)	0.505	0.300	0.165	0.079	0.038	0.025	0.016	0.006	0.004	0.004	0.004	0.004



F. 3D Image



32-Body with back position in dist. 10mm on Channel 42 in IEEE 802.11ac U-NII

SAR Measurement at U-NII-1 (Body, Validation Plane)

Date of measurement: 1/9/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.18
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	7x7x12,dx=4mm dy=4mm dz=2.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	U-NII-1
Channels/Frequency	Higher (42)/ frequency 5210.000 Mhz
Signal	IEEE 802.11 ac

B. Permittivity

Middle TX Frequency (MHz)	5210.000
Relative permittivity (real part)	36.113
Relative permittivity (imaginary part)	16.257
Conductivity (S/m)	4.509

C. SAR Surface and Volume




D. SAR 1g & 10g


SAR 10g (W/Kg)	0.068
SAR 1g (W/Kg)	0.207
Variation (%)	-4.180
Horizontal validation criteria: minimum distance (mm)	8.944272
Vertical validation criteria: SAR ratio M2/M1 (%)	47.678288

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00	18.00	20.00	22.00
SAR (W/Kg)	0.673	0.380	0.096	0.104	0.020	0.031	0.006	0.010	0.004	0.004	0.004	0.004



F. 3D Image



33-Head with front position in dist. 0mm on Channel 58 in IEEE 802.11ac U-NII

SAR Measurement at U-NII-2a (Cheek, Right)

Date of measurement: 3/9/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.14
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	7x7x12, dx=4mm dy=4mm dz=2.0mm, Complete
Phantom	Right head
Device Position	Cheek
Band	U-NII-2a
Channels/Frequency	Higher (58)/ frequency 5290.000 Mhz
Signal	IEEE 802.11 ac

B. Permittivity

Middle TX Frequency (MHz)	5290.000
Relative permittivity (real part)	36.029
Relative permittivity (imaginary part)	16.283
Conductivity (S/m)	4.671

C. SAR Surface and Volume




Maximum location: X=-17.00, Y=1.00 ; SAR Peak: 1.78 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.165
SAR 1g (W/Kg)	0.611
Variation (%)	1.630
Horizontal validation criteria: minimum distance (mm)	8.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	56.621918

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00	18.00	20.00	22.00
SAR (W/Kg)	1.143	0.703	0.398	0.210	0.112	0.052	0.032	0.012	0.007	0.008	0.005	0.005



F. 3D Image



34-Body with back position in dist. 10mm on Channel 58 in IEEE 802.11ac U-NII

SAR Measurement at U-NII-2a (Body, Validation Plane)

Date of measurement: 3/9/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.14
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	7x7x12, dx=4mm dy=4mm dz=2.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	U-NII-2a
Channels/Frequency	Higher (58)/ frequency 5290.000 Mhz
Signal	IEEE 802.11 ac

B. Permittivity

Middle TX Frequency (MHz)	5290.000
Relative permittivity (real part)	36.029
Relative permittivity (imaginary part)	16.283
Conductivity (S/m)	4.671

C. SAR Surface and Volume




Maximum location: X=-31.00, Y=23.00 ; SAR Peak: 2.15 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.282
SAR 1g (W/Kg)	0.758
Variation (%)	-1.760
Horizontal validation criteria: minimum distance (mm)	11.313708
Vertical validation criteria: SAR ratio M2/M1 (%)	54.689650

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00	18.00	20.00	22.00
SAR (W/Kg)	1.998	1.242	0.679	0.387	0.224	0.113	0.061	0.031	0.015	0.007	0.006	0.004



F. 3D Image



35-Head with front position in dist. 0mm on Channel 122 in IEEE 802.11ac U-NII

SAR Measurement at U-NII-2c (Cheek, Right)

Date of measurement: 5/9/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.12
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	7x7x12, dx=4mm dy=4mm dz=2.0mm, Complete
Phantom	Right head
Device Position	Cheek
Band	U-NII-2c
Channels/Frequency	Middle (122)/ frequency 5610.000 Mhz
Signal	IEEE 802.11 ac

B. Permittivity

Middle TX Frequency (MHz)	5610.000
Relative permittivity (real part)	35.519
Relative permittivity (imaginary part)	16.422
Conductivity (S/m)	5.026

C. SAR Surface and Volume




Maximum location: X=-39.00, Y=-48.00 ; SAR Peak: 0.67 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.028
SAR 1g (W/Kg)	0.080
Variation (%)	-0.300
Horizontal validation criteria: minimum distance (mm)	8.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	39.740995

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00	18.00	20.00	22.00
SAR (W/Kg)	0.298	0.163	0.065	0.032	0.013	0.008	0.004	0.011	0.005	0.005	0.005	0.005



F. 3D Image



36-Body with back position in dist. 10mm on Channel 122 in IEEE 802.11ac U-NII

SAR Measurement at U-NII-2c (Body, Validation Plane)

Date of measurement: 5/9/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.12
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	7x7x12, dx=4mm dy=4mm dz=2.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	U-NII-2c
Channels/Frequency	Middle (122)/ frequency 5610.000 Mhz
Signal	IEEE 802.11 ac

B. Permittivity

Middle TX Frequency (MHz)	5610.000
Relative permittivity (real part)	35.519
Relative permittivity (imaginary part)	16.422
Conductivity (S/m)	5.026

C. SAR Surface and Volume




D. SAR 1g & 10g


SAR 10g (W/Kg)	0.152
SAR 1g (W/Kg)	0.437
Variation (%)	-3.470
Horizontal validation criteria: minimum distance (mm)	11.313708
Vertical validation criteria: SAR ratio M2/M1 (%)	52.824054

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00	18.00	20.00	22.00
SAR (W/Kg)	1.255	0.726	0.281	0.192	0.065	0.050	0.024	0.007	0.007	0.004	0.005	0.005



F. 3D Image



37-Head with front position in dist. 0mm on Channel 155 in IEEE 802.11ac U-NII

SAR Measurement at U-NII-2 (Cheek, Right)

Date of measurement: 7/9/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.11
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	7x7x12, dx=4mm dy=4mm dz=2.0mm, Complete
Phantom	Right head
Device Position	Cheek
Band	U-NII-2
Channels/Frequency	Middle (155)/ frequency 5775.000 Mhz
Signal	IEEE 802.11 ac

B. Permittivity

Middle TX Frequency (MHz)	5775.000
Relative permittivity (real part)	35.269
Relative permittivity (imaginary part)	16.474
Conductivity (S/m)	5.219

C. SAR Surface and Volume




Maximum location: X=-39.00, Y=-57.00 ; SAR Peak: 0.46 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.035
SAR 1g (W/Kg)	0.103
Variation (%)	-2.080
Horizontal validation criteria: minimum distance (mm)	8.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	50.001947

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00	18.00	20.00	22.00
SAR (W/Kg)	0.243	0.138	0.069	0.025	0.020	0.004	0.005	0.007	0.005	0.016	0.005	0.005



F. 3D Image



38-Body with back position in dist. 10mm on Channel 155 in IEEE 802.11ac U-NII

SAR Measurement at U-NII-2 (Body, Validation Plane)

Date of measurement: 7/9/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.11
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	7x7x12, dx=4mm dy=4mm dz=2.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	U-NII-2
Channels/Frequency	Middle (155)/ frequency 5775.000 Mhz
Signal	IEEE 802.11 ac

B. Permittivity

Middle TX Frequency (MHz)	5775.000
Relative permittivity (real part)	35.269
Relative permittivity (imaginary part)	16.474
Conductivity (S/m)	5.219

C. SAR Surface and Volume




Maximum location: X=-24.00, Y=30.00 ; SAR Peak: 1.26 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.153
SAR 1g (W/Kg)	0.409
Variation (%)	-3.360
Horizontal validation criteria: minimum distance (mm)	11.313708
Vertical validation criteria: SAR ratio M2/M1 (%)	51.402003

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00	18.00	20.00	22.00
SAR (W/Kg)	1.165	0.702	0.361	0.196	0.102	0.036	0.021	0.011	0.008	0.010	0.005	0.004



F. 3D Image



39-Head with front position in dist. 0mm on Channel 78 in Bluetooth

SAR Measurement at Bluetooth (Cheek, Right)

Date of measurement: 31/8/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.40
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Right head
Device Position	Cheek
Band	Bluetooth
Channels/Frequency	Higher (78)/ frequency 2480.000 Mhz
Signal	Bluetooth

B. Permittivity

Middle TX Frequency (MHz)	2480.000
Relative permittivity (real part)	38.823
Relative permittivity (imaginary part)	13.192
Conductivity (S/m)	1.808

C. SAR Surface and Volume




Maximum location: X=0.00, Y=-8.00 ; SAR Peak: 0.03 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.002
SAR 1g (W/Kg)	0.005
Variation (%)	-1.170
Horizontal validation criteria: minimum distance (mm)	16.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	10.999118

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.037	0.013	0.002	0.002	0.002	0.002	0.002



F. 3D Image



40-Body with back position in dist. 10mm on Channel 78 in Bluetooth

SAR Measurement at Bluetooth (Body, Validation Plane)

Date of measurement: 31/8/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.40
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	Bluetooth
Channels/Frequency	Higher (78)/ frequency 2480.000 Mhz
Signal	Bluetooth

B. Permittivity

Middle TX Frequency (MHz)	2480.000
Relative permittivity (real part)	38.823
Relative permittivity (imaginary part)	13.192
Conductivity (S/m)	1.808

C. SAR Surface and Volume




Maximum location: X=16.00, Y=8.00 ; SAR Peak: 0.01 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.002
SAR 1g (W/Kg)	0.003
Variation (%)	0.270
Horizontal validation criteria: minimum distance (mm)	16.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	60.454077

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.004	0.003	0.002	0.002	0.002	0.002	0.002




F. 3D Image




ANNEX D SAR Test Setup Photos


Reference Photo: simulation liquid depth 15cm




Reference Photos




Left Head - Cheek




Left Head - Tilt




Right Head - Cheek




Right Head - Tilt




Front (dist. 10mm)




Back (dist. 10mm)



Left (dist. 10mm)



Right (dist. 10mm)



Top (dist. 10mm)



Bottom (dist. 10mm)

ANNEX E EUT External and Internal Photos

Please refer to RF Report.

ANNEX F Calibration Information

Please refer to the document "Calibration.pdf".



BTF Testing Lab (Shenzhen) Co., Ltd.

101/201/301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Subdistrict,
Bao'an District, Shenzhen, China

www.btf-lab.com

--END OF REPORT--