



品名：66BD-WGB-V1.0

History List

[illegible]

66BD-WGB-V1.0 Specification

1. Explanation of part number :

66BD – **WGB** – **V1.0**
(1) **(2)** **(3)**

(1) Model Name : 66BD

(2) Frequency : 1575MHz, 2400-2500MHz

(3) Suffix :V1.0

2. Electrical Specification :

2-1. Frequency Band:

Frequency Band	MHz
GPS,BT, 2.4G WIFI	1575MHz, 2400-2500MHz

2-2. Impedance

50 ohm nominal

UNLESS OTHER SPECIFIED TOLERANCES ON:

X=±2 X.X=±0.1 X.XX=±0.05

ANGLES = $\pm$

HOLEDIA=±

Deman

上海德门电子科技有限公司

Shanghai Deman Electronics Technology co., LTD

SCALE:

UNIT: mm

DRAWN BY:

CHECKED BY:

DESIGNED BY: 李进柱

APPROVED BY:

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF SHANGHAI DEMAN ELECTRONICS TECHNOLOGY CO., LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

TITLE: 66BD-WGB -V1.0Specification


DOCUMENT NO.

PAGE	REV.
------	------

A0

2-3. S11 ,Efficiency ,Matching and Active Data :

2-3.1 S11:

Frequency Band	1575	2400		
2-3-1. Typical Value:	≤ -15.5	≤ -9.5		
2-3-2Measuring Method	1. A 50 Ω coaxial cable is connected to the fpcb antenna. Then this cable is connected to a network analyzer to measure the S11 2. Keeping this jig away from metal at least 20 cm.			
2-3-3Picture				

UNLESS OTHER SPECIFIED TOLERANCES ON:

X=±2 X.X=±0.1 X.XX=±0.05

ANGLES=± HOLEDIA=±

SCALE: UNIT: mm

DRAWN BY: CHECKED BY:

DESIGNED BY: 李进柱 APPROVED BY:

TITLE: **66BD-WGB -V1.0Specification**

Deman


上海德门电子科技有限公司

Shanghai Deman Electronics Technology co., LTD

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF SHANGHAI DEMAN ELECTRONICS TECHNOLOGY CO., LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

DOCUMENT
NO.

PAGE REV.
A0



2-4. Measure and Chamber

2-4-1 Measure method

1. Using a low loss coaxial cable to link a standard handset jig
2. Fixed this handset jig on chamber's rotator plane
3. Linking jig into network analyzer port and using a probing horn antenna to collect data.
4. Using another standard gain horn antenna to calibrated those data

UNLESS OTHER SPECIFIED TOLERANCES ON:

X=±2 X.X=±0.1 X.XX=±0.05

ANGLES=±

HOLEDIA=±

Deman

上海德门电子科技有限公司

Shanghai Deman Electronics Technology co., LTD

SCALE:

UNIT: mm

DRAWN BY:

CHECKED BY:

DESIGNED BY: 李进柱

APPROVED BY:

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF SHANGHAI DEMAN ELECTRONICS TECHNOLOGY CO., LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION


TITLE: **66BD-WGB -V1.0**Specification

DOCUMENT
NO.

PAGE REV.

A0

2-4-2 Chamber definition



1. An anechoic chamber (8mx4mx3.5m) which satisfied far-field condition was applied to avoid multi-path effect
2. The quiet room region is 40cmx40cmx40cm at the center of rotator
3. The distance between DUT and standard antenna is 4.38 m
4. Probing antenna (9120D horn antenna) and standard gain horn antenna (BBHA9120 LPF 600MHz ~6GHz)

2-4-3 Antenna Efficiency

GPS				BT&WIFI			
Frequency (MHz)	Gain (dBi)	Efficiency (dB)	Efficiency (%)	Frequency (MHz)	Gain (dBi)	Efficiency (dB)	Efficiency (%)
1550	-2.78	-5.92	25.59	2400	-5.20	-9.16	12.13
1555	-2.60	-5.75	26.61	2410	-5.20	-9.5	11.22
1560	-2.42	-5.55	27.86	2420	-5.82	-9.87	10.30
1565	-2.20	-5.32	29.38	2430	-6.29	-10.31	9.31
1570	-2.00	-5.13	30.69	2440	-6.73	-10.77	8.38
1575	-1.88	-5.04	31.33	2450	-7.30	-11.33	7.36
1580	-1.76	-4.95	31.99	2460	-7.93	-11.9	6.46

UNLESS OTHER SPECIFIED TOLERANCES ON:

X=±2 X.X=±0.1 X.XX=±0.05

ANGLES=± HOLEDIA=±

SCALE: UNIT: mm

DRAWN BY: CHECKED BY:

DESIGNED BY: 李进柱 APPROVED BY:

TITLE: **66BD-WGB -V1.0** Specification

Deman

上海德门电子科技有限公司

Shanghai Deman Electronics Technology co., LTD

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF SHANGHAI DEMAN ELECTRONICS TECHNOLOGY CO., LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

DOCUMENT NO.


PAGE REV.
A0

1585	-1.63	-4.82	32.96	2470	-8.48	-12.43	5.71
1590	-1.50	-4.69	33.96	2480	-9.05	-12.94	5.08
1595	-1.45	-4.69	33.96	2490	-9.93	-13.8	4.17
1600	-1.49	-4.81	33.04	2500	-10.70	-14.53	3.52


UNLESS OTHER SPECIFIED TOLERANCES ON: X=±2 X.X=±0.1 X.XX=±0.05 ANGLES=± HOLEDIA=±		 上海德门电子科技有限公司 Shanghai Deman Electronics Technology co., LTD	
SCALE:	UNIT: mm	THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF SHANGHAI DEMAN ELECTRONICS TECHNOLOGY CO., LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION	
DRAWN BY:	CHECKED BY:		
DESIGNED BY: 李进柱	APPROVED BY:		
TITLE: 66BD-WGB -V1.0 Specification		DOCUMENT NO.	PAGE REV. A0

3. 3D Radiation Pattern

GPS [1575MHz]



BT&2.4G WIFI [2450MHz]



UNLESS OTHER SPECIFIED TOLERANCES ON:

X=±2 X.X=±0.1 X.XX=±0.05

ANGLES=± HOLEDIA=±

SCALE:

UNIT: mm

DRAWN BY:

CHECKED BY:

DESIGNED BY: 李进柱

APPROVED BY:

TITLE: **66BD-WGB -V1.0**Specification

Deman

上海德门电子科技有限公司

Shanghai Deman Electronics Technology co., LTD

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF SHANGHAI DEMAN ELECTRONICS TECHNOLOGY CO., LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

DOCUMENT
NO.

PAGE REV.

A0

4. Antenna Dimensions:

[illegible]

UNLESS OTHER SPECIFIED TOLERANCES ON:

X=±2 X.X=±0.1 X.XX=±0.05

ANGLES = $\pm$

HOLEDIA=±

SCALE:

UNIT: mm

DRAWN BY:

CHECKED BY:

DESIGNED BY: 李进柱	APPROVED BY:
TITLE: 66BD-WGB -V1.0Specification	

Demam

上海德门电子科技有限公司

Shanghai Deman Electronics Technology co., LTD

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF SHANGHAI DEMAN ELECTRONICS TECHNOLOGY CO., LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

DOCUMENT NO.

PAGE	REV.
A0	