

FCC TEST REPORT

(PART 90)

Applicant:	FOXX Development Inc
Address:	3480 Preston Ridge Road Suite 500, Alpharetta, GA 30005

Manufacturer or Supplier	FOXX Development Inc
Address	3480 Preston Ridge Road Suite 500, Alpharetta, GA 30005
Product	Redcap Moduel
Brand Name	FOXX
Model Name	IQ50
FCC ID	2AQRM-IQ50
Date of tests	Dec. 05, 2025 ~Dec. 31, 2025

The tests have been carried out according to the requirements of the following standard:

☒ **FCC Part 90, Subpart R, S**
☒ **ANSI/TIA/EIA-603- D**
☒ **FCC Part 2**

☒ **ANSI/TIA/EIA-603-E**
☒ **ANSI C63.26-2015**

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Prepared by Hanwen Xu Engineer / Mobile Department	Approved by Luke Lu Manager / Mobile Department
	
Date: Jan. 12, 2026	Date: Jan. 12, 2026

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



Table of Contents

1	SUMMARY OF TEST RESULTS	4
1.1	MEASUREMENT UNCERTAINTY	6
1.2	TEST SITE AND INSTRUMENTS	7
2	GENERAL INFORMATION	9
2.1	GENERAL DESCRIPTION OF EUT	9
2.2	CONFIGURATION OF SYSTEM UNDER TEST	12
2.3	DESCRIPTION OF SUPPORT UNITS	13
2.4	DESCRIPTION OF TEST MODES	14
2.5	GENERAL DESCRIPTION OF APPLIED STANDARDS	19
3	TEST TYPES AND RESULTS	20
3.1	OUTPUT POWER MEASUREMENT	20
3.1.1	LIMITS OF OUTPUT POWER MEASUREMENT	20
3.1.2	TEST PROCEDURES	20
3.1.3	TEST SETUP	21
3.1.4	TEST RESULTS	22
3.2	FREQUENCY STABILITY MEASUREMENT	32
3.2.1	LIMITS OF FREQUENCY STABILITY MEASUREMENT	32
3.2.2	TEST PROCEDURE	32
3.2.3	TEST SETUP	32
3.2.4	TEST RESULTS	33
3.3	OCCUPIED BANDWIDTH MEASUREMENT	34
3.3.1	LIMITS OF OCCUPIED BANDWIDTH MEASUREMENT	34
3.3.2	TEST SETUP	34
3.3.3	TEST PROCEDURES	34
3.3.4	TEST RESULTS	34
3.4	EMISSION MASK MEASUREMENT	35
3.4.1	LIMITS OF EMISSION MASK MEASUREMENT	35
3.4.2	TEST SETUP	36
3.4.3	TEST PROCEDURES	37
3.4.4	TEST RESULTS	37
3.5	CONDUCTED SPURIOUS EMISSIONS	38
3.5.1	LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT	38
3.5.2	TEST PROCEDURE	38
3.5.3	TEST SETUP	38
3.5.4	TEST RESULTS	39
3.6	RADIATED EMISSION MEASUREMENT	40
3.6.1	LIMITS OF RADIATED EMISSION MEASUREMENT	40
3.6.2	TEST PROCEDURES	40
3.6.3	DEVIATION FROM TEST STANDARD	40
3.6.4	TEST SETUP	41
3.6.5	TEST RESULTS	43
3.7	PEAK TO AVERAGE RATIO	77
3.7.1	LIMITS OF PEAK TO AVERAGE RATIO MEASUREMENT	77
3.7.2	TEST SETUP	77
3.7.3	TEST PROCEDURES	77
3.7.4	TEST RESULTS	77
4	INFORMATION ON THE TESTING LABORATORIES	78
5	MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	79
6	APPENDIX	80



RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
PSU-QBJ2512030110RF05	Original release	Jan. 12, 2026



1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

LTE Band 14

Ref Std.Clause	Test Items	Result (Pass/Fail)	Remark
§2.1046	Conducted Output Power	Reporting only	-
-	Peak-to-Average Ratio	Reporting only	-
§2.1049	Occupied Bandwidth	Reporting only	-
§2.1053 §90.543(e)(2)	Conducted Band Edge Measurement	PASS	-
§2.1051 §90.210(n)	Emission Masks	PASS	-
§2.1053 §90.543(e)(3)	Conducted Spurious Emissions	PASS	-
§2.1055 §90.539(e)	Frequency Stability Temperature & Voltage	PASS	-
§2.1053 §90.543(e)(3) §90.543(f)	Radiated Spurious Emissions	PASS	Under limit 21.29dB at 1584.000MHz

LTE Band 26

The EUT has been tested according to the following specifications:

Ref Std.Clause	Test Items	Result (Pass/Fail)	Remark
§2.1046	Conducted Output Power	Reporting only	-
-	Peak-to-Average Ratio	Reporting only	-
§2.1049	Occupied Bandwidth	Reporting only	-
§2.1053 § 90.691(a)	Conducted Band Edge Measurement	PASS	-

**Test Report No.: PSU-QBJ2512030110RF05**

§2.1051 § 90.691(a)	Emission Masks	PASS	-
§2.1053 § 90.691(a)	Conducted Spurious Emissions	PASS	-
§2.1055 § 90.213	Frequency Stability Temperature & Voltage	PASS	-
§2.1053 §90.691	Radiated Spurious Emissions	PASS	Under limit 21.29dB at 1584.000MHz

Test Lab Information Reference*Lab A:**

Huarui 7Layers High Technology (Suzhou) Co., Ltd.

Lab Address:

Tower N, Innovation Center, 88 Zuyi Road, High-tech District, Suzhou City, Anhui Province, China

Accredited Test Lab Cert 6613.01

The FCC Site Registration No. is 434559; The Designation No. is CN1325.




1.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz~30MHz	2.66dB
Radiated emissions	9KHz ~ 30MHz	2.68dB
	30MHz ~ 1GHz	3.26dB
	1GHz ~ 18GHz	4.48dB
	18GHz ~ 40GHz	4.12dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



The verdicts in this test report are given according the above diagram:

Case	Measured Value	Uncertainty Range	Verdict
1	below pass mark	below pass mark	Passed
2	below pass mark	within pass mark	Passed
3	above pass mark	within pass mark	Failed
4	above pass mark	above pass mark	Failed

That means, the laboratory applies, as decision rule (see ISO/IEC 17025:2017), the so-called shared risk principle.



1.2 TEST SITE AND INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Pre-Amplifier	R&S	SCU18F1	100815	Aug.29,25	Aug.28,27
Pre-Amplifier	R&S	SCU08F1	101028	Jan.22,24	Jan.21,26
Vector Signal Generator	R&S	SMBV100B	102176	Mar.29,24	Mar.28,26
Signal Generator	R&S	SMB100A	182185	Mar.29,24	Mar.28,26
3m Fully-anechoic Chamber	TDK	9m*6m*6m	HRSW-SZ-EMC-01Chamber	Nov.24,25	Nov.23,28
3m Semi-anechoic Chamber	TDK	9m*6m*6m	HRSW-SZ-EMC-02Chamber	Aug.20,25	Aug.19,28
EMI TEST Receiver	R&S	ESR26	101734	Mar.28,24	Mar.27,26
EMI TEST Receiver	R&S	ESW44	101973	Mar.28,24	Mar.27,26
Bilog Antenna	SCHWARZBECK	VULB 9163	1264	Jul.04,25	Jul.03,27
Horn Antenna	ETS-LINDGREN	3117	227836	Aug.20,25	Aug.19,27
Horn Antenna (18GHz-40GHz)	Steatite Q-par Antennas	QMS 00880	23486	Jul.15,24	Jul.14,26
Horn Antenna	Steatite Q-par Antennas	QMS 00208	23485	Mar.22,25	Mar.21,27
Loop Antenna	SCHWARZ	HFH2-Z2/Z2E	100976	Feb.22,25	Feb.21,27
WIDEBANDRADIO COMMUNICATION TESTER	R&S	CMW500	169399	Jun.19,24	Jun.18,26
Radio Communication Tester	Rohde&Schwarz	CMX500	101446	Mar.21,25	Mar.20,27
Test Software	EMC32	EMC32	N/A	N/A	N/A
6DB attenuator	Tonscend Technology Co., Ltd	N/A	23062787	N/A	N/A
Test Software	ELEKTRA	ELEKTRA4.32	N/A	N/A	N/A
Open Switch and Control Unit	R&S	OSP220	101964	N/A	N/A
DC Source	HYELEC	HY3010B	551016	Aug.30,25	Aug.29,27
Hygrothermograph	DELI	20210528	SZ014	Mar.18,25	Mar.17,27
PC	LENOVO	E14	HRSW0024	N/A	N/A
TMC-AMI18843A(CABLE)	R&S	HF290-NMNM-7.00M	N/A	N/A	N/A
TMC-AMI18843A(CABLE)	R&S	HF290-NMNM-4.00M	N/A	N/A	N/A
CABLE	R&S	W13.02	N/A	Apr.26,25	Apr.25,26
CABLE	R&S	W12.14	N/A	Apr.26,25	Apr.25,26
CABLE	R&S	J12J103539-00-1	SEP-03-20-069	Apr.26,25	Apr.25,26
CABLE	R&S	J12J103539-00-1	SEP-03-20-070	Apr.26,25	Apr.25,26
Temperature Chamber	votsch	VT4002	58566078100050	May.30,24	May.29,26



NOTE:

1. The calibration interval of the above test instruments is 12/ 24/ 36 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
2. The test was performed in 3m Semi-anechoic Chamber and RF Oven Room.
3. The horn antenna is used only for the measurement of emission frequency above 1GHz if tested.
4. The FCC Site Registration No. is 434559; The Designation No. is CN1325.



2 GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

PRODUCT*	Redcap Moduel	
BRAND NAME*	FOXX	
MODEL NAME*	IQ50	
NOMINAL VOLTAGE*	3.8Vdc	
MODULATION TECHNOLOGY*	LTE	QPSK, 16QAM, 64QAM
	5G NR	DFT-s-OFDM(Pi/2BPSK,QPSK,16QAM,64QAM,256QAM); CP-OFDM(QPSK,16QAM,64QAM,256QAM);
FREQUENCY RANGE	LTE Band 14 (Channel Bandwidth: 5MHz)	790.5MHz ~ 795.5MHz
	LTE Band 14 (Channel Bandwidth: 10MHz)	793MHz
	LTE Band 26 (Channel Bandwidth: 1.4MHz)	814.7MHz ~ 823.3MHz
	LTE Band 26 (Channel Bandwidth: 3MHz)	815.5MHz ~ 822.5MHz
	LTE Band 26 (Channel Bandwidth: 5MHz)	816.5MHz ~ 821.5MHz
	LTE Band 26 (Channel Bandwidth: 10MHz)	819MHz
	NR Band N14 (Channel Bandwidth: 5MHz)	790.5MHz ~ 795.5MHz
	NR Band N14 (Channel Bandwidth: 10MHz)	793MHz
	NR Band N26 (Channel Bandwidth: 5MHz)	816.5MHz ~ 821.5MHz
	NR Band N26 (Channel Bandwidth: 10MHz)	819MHz
EMISSION DESIGNATOR	LTE Band 14 (Channel Bandwidth: 5MHz)	QPSK: 4M52G7D
		16QAM: 4M53W7D
		64QAM: 4M52W7D



	LTE Band 14 (Channel Bandwidth: 10MHz)	QPSK: 8M99G7D
		16QAM: 8M99W7D
		64QAM: 8M97W7D
	LTE Band 26 (Channel Bandwidth: 1.4MHz)	QPSK: 1M11G7D
		16QAM: 1M10W7D
		64QAM: 1M10W7D
	LTE Band 26 (Channel Bandwidth: 3MHz)	QPSK: 2M71G7D
		16QAM: 2M70W7D
		64QAM: 2M71W7D
	LTE Band 26 (Channel Bandwidth: 5MHz)	QPSK: 4M52G7D
		16QAM: 4M53W7D
		64QAM: 4M53W7D
	LTE Band 26 (Channel Bandwidth: 10MHz)	QPSK: 8M98G7D
		16QAM: 8M99W7D
		64QAM: 8M96W7D
MAX. EIRP POWER	NR Band N14 (Channel Bandwidth: 5MHz)	Pi/2BPSK: 4M53G7D
		QPSK: 4M53G7D
		16QAM: 4M53W7D
		64QAM: 4M52W7D
		256QAM: 4M51G7D
	NR Band N14 (Channel Bandwidth: 10MHz)	Pi/2BPSK: 8M98G7D
		QPSK: 8M98G7D
		16QAM: 8M98W7D
		64QAM: 8M97W7D
	NR Band N26 (Channel Bandwidth: 5MHz)	256QAM: 8M97G7D
		Pi/2BPSK: 4M56G7D
		QPSK: 4M56G7D
		16QAM: 4M52W7D
	NR Band N26 (Channel Bandwidth: 10MHz)	64QAM: 4M53W7D
		256QAM: 4M52G7D
		Pi/2BPSK: 8M95G7D
		QPSK: 8M95G7D
	LTE Band 14 (Channel Bandwidth: 5MHz)	16QAM: 8M95W7D
		64QAM: 8M95W7D
		256QAM: 8M94G7D
MAX. EIRP POWER	LTE Band 14 (Channel Bandwidth: 10MHz)	152.76mW
	LTE Band 14 (Channel Bandwidth: 10MHz)	153.82mW
	LTE Band 26 (Channel Bandwidth: 1.4MHz)	198.61mW



	LTE Band 26 (Channel Bandwidth: 3MHz)	199.99mW
	LTE Band 26 (Channel Bandwidth: 5MHz)	200.91mW
	LTE Band 26 (Channel Bandwidth: 10MHz)	202.77mW
MAX. ERP POWER Redcap mode	NR Band N14 (Channel Bandwidth: 5MHz)	164.06mW
	NR Band N14 (Channel Bandwidth: 10MHz)	166.34mW
	NR Band N26 (Channel Bandwidth: 5MHz)	202.30mW
	NR Band N26 (Channel Bandwidth: 10MHz)	202.77mW
ANTENNA GAIN*	☒ Provided by client	
	LTE B14	1.21 dBi
	LTE B26	2.06 dBi
	NR N14	1.46 dBi
	NR N26	2.06dBi
ANTENNA TYPE*	External Antenna	
HW VERSION*	AT+SFHW	
SW VERSION*	AT+SGSW	
I/O PORTS*	Refer to user's manual	
DATA CABLE*	N/A	
EXTREME TEMPERATURE*	-40°C~85°C	
EXTREME VOLTAGE*	3.3V~4.35V	

NOTE:

- *Since the above data and/or information is provided by the client relevant results or conclusions of this report are only made for these data and/or information, Test Lab is not responsible for the authenticity, integrity and results of the data and information and/or the validity of the conclusion.
- For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
- The EUT incorporates a SISO function. Physically, the EUT provides one completed transmitter and two receivers.


MODULATION MODE	TX FUNCTION
LTE	1TX/2RX
NR	1TX/2RX

- For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.



2.2 CONFIGURATION OF SYSTEM UNDER TEST

FOR RADIATION EMISSION TEST





2.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	DC source	LONG WEI	PS-6403D	010934269	N/A
2	Adapter	N/A	N/A	N/A	N/A
3	USB Cable	N/A	N/A	N/A	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	DC Line: Unshielded, Detachable 1.8m
2	USB Cable: Unshielded, Detachable 1m

2.4 DESCRIPTION OF TEST MODES

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports. The worst case in ERP/EIRP and radiated emission was found when positioned on X-plane for LTE. Following channel(s) was (were) selected for the final test as listed below:

EUT CONFIGURE MODE	DESCRIPTION
A	EUT + Adapter + USB Cable with LTE link
B	EUT + DC Supply with LTE link

LTE BAND 14 MODE

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	CHANNEL BANDWIDTH	MODULATION	MODE
A	ERP	23305 to 23355	23305, 23330, 23355	5MHz	QPSK, 16QAM, 64QAM	1 RB / 0 RB Offset
		23330	23330	10MHz	QPSK, 16QAM, 64QAM	1 RB / 0 RB Offset
B	FREQUENCY STABILITY	23305 to 23355	23305, 23355	5MHz	QPSK	50 RB / 0 RB Offset
A	OCCUPIED BANDWIDTH	23305 to 23355	23305, 23330, 23355	5MHz	QPSK, 16QAM, 64QAM	25 RB / 0 RB Offset
		23330	23330	10MHz	QPSK, 16QAM, 64QAM	50 RB / 0 RB Offset
A	PEAK TO AVERAGE RATIO	23305 to 23355	23305, 23330, 23355	5MHz	QPSK, 16QAM, 64QAM	1 RB / 0 RB Offset 25 RB / 0 RB Offset
		23330	23330	10MHz	QPSK, 16QAM, 64QAM	1 RB / 0 RB Offset 50 RB / 0 RB Offset
A	BAND EDGE	23305 to 23355	23305	5MHz	QPSK, 16QAM, 64QAM	1 RB / 0 RB Offset
						25 RB / 0 RB Offset
			23355	5MHz	QPSK, 16QAM, 64QAM	1 RB / 24 RB Offset
						25 RB / 0 RB Offset
		23300	23330	10MHz	QPSK, 16QAM, 64QAM	1 RB / 0 RB Offset
						50 RB / 0 RB Offset
						1 RB / 49 RB Offset
						/
A	CONDUCTED EMISSION	23305 to 23355	23305, 23330, 23355	5MHz	QPSK	1 RB / 0 RB Offset
		23330	23330	10MHz	QPSK	1 RB / 0 RB Offset



A	RADIATED EMISSION	23305 to 23355	23305, 23330, 23355	5MHz	QPSK	1 RB / 0 RB Offset
		23330	23330	10MHz	QPSK	1 RB / 0 RB Offset

Note: This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation.

LTE BAND 26 MODE

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	CHANNEL BANDWIDTH	MODULATION	MODE
A	ERP	26697 to 26783	26697, 26740, 26783	1.4MHz	QPSK, 16QAM, 64QAM	1 RB / 0 RB Offset
		26705 to 26775	26705, 26740, 26775	3MHz	QPSK, 16QAM, 64QAM	1 RB / 0 RB Offset
		26715 to 26765	26715, 26740, 26765	5MHz	QPSK, 16QAM, 64QAM	1 RB / 0 RB Offset
		26740	26740	10MHz	QPSK, 16QAM, 64QAM	1 RB / 0 RB Offset
B	FREQUENCY STABILITY	26715 to 26765	26715, 26765	5MHz	QPSK	50 RB / 0 RB Offset
A	OCCUPIED BANDWIDTH	26697 to 26783	26697, 26740, 26783	1.4MHz	QPSK, 16QAM, 64QAM	6 RB / 0 RB Offset
		26705 to 26775	26705, 26740, 26775	3MHz	QPSK, 16QAM, 64QAM	15 RB / 0 RB Offset
		26715 to 26765	26715, 26740, 26765	5MHz	QPSK, 16QAM, 64QAM	25 RB / 0 RB Offset
		26740	26740	10MHz	QPSK, 16QAM, 64QAM	50 RB / 0 RB Offset
A	PEAK TO AVERAGE RATIO	26697 to 26783	26697, 26740, 26783	1.4MHz	QPSK, 16QAM, 64QAM	1 RB / 0 RB Offset 6 RB / 0 RB Offset
		26705 to 26775	26705, 26740, 26775	3MHz	QPSK, 16QAM, 64QAM	1 RB / 0 RB Offset 15 RB / 0 RB Offset
		26715 to 26765	26715, 26740, 26765	5MHz	QPSK, 16QAM, 64QAM	1 RB / 0 RB Offset 25 RB / 0 RB Offset
		26740	26740	10MHz	QPSK, 16QAM, 64QAM	1 RB / 0 RB Offset 50 RB / 0 RB Offset
A	BAND EDGE	26697 to 26783	26697	1.4MHz	QPSK, 16QAM, 64QAM	1 RB / 0 RB Offset 6 RB / 0 RB Offset
			26783	1.4MHz	QPSK, 16QAM, 64QAM	1 RB / 5 RB Offset 6 RB / 0 RB Offset
		26705 to 26775	26705	3MHz	QPSK, 16QAM, 64QAM	1 RB / 0 RB Offset 15 RB / 0 RB Offset
			26775	3MHz	QPSK, 16QAM, 64QAM	1 RB / 14 RB Offset 15 RB / 0 RB Offset
		26715 to 26765	26715	5MHz	QPSK, 16QAM, 64QAM	1 RB / 0 RB Offset 25 RB / 0 RB Offset
			26765	5MHz	QPSK, 16QAM, 64QAM	1 RB / 24 RB Offset 25 RB / 0 RB Offset
		26740	26740	10MHz	QPSK, 16QAM, 64QAM	1 RB / 0 RB Offset 50 RB / 0 RB Offset
			26740	10MHz	QPSK, 16QAM, 64QAM	1 RB / 49 RB Offset 50 RB / 0 RB Offset
		26697 to 26783	26697, 26740, 26783	1.4MHz	QPSK	1 RB / 0 RB Offset
			26705, 26740, 26775	3MHz	QPSK	1 RB / 0 RB Offset
		26715 to 26765	26715, 26740, 26765	5MHz	QPSK	1 RB / 0 RB Offset
			26740	10MHz	QPSK	1 RB / 0 RB Offset
A	CONDUCTED EMISSION	26697 to 26783	26740	1.4MHz	QPSK	1 RB / 0 RB Offset
		26705 to 26775	26705, 26740, 26775	3MHz	QPSK	1 RB / 0 RB Offset
		26715 to 26765	26715, 26740, 26765	5MHz	QPSK	1 RB / 0 RB Offset
A	RADIATED EMISSION	26697 to 26783	26740	1.4MHz	QPSK	1 RB / 0 RB Offset
		26705 to 26775	26705, 26740, 26775	3MHz	QPSK	1 RB / 0 RB Offset
		26715 to 26765	26740	5MHz	QPSK	1 RB / 0 RB Offset


BUREAU VERITAS Test Report No.: PSU-QBJ2512030110RF05

		26740	26740	10MHz	QPSK	1 RB / 0 RB Offset
--	--	-------	-------	-------	------	--------------------

Note: This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation.

REDCAP MODE
NR BAND N14

EUT CONFIGUR E MODE	TEST ITEM	AVAILABL E CP- OFDM CHANNEL	AVAILABLE DFT-S- OFDM CHANNEL	TESTED CHANNE L	CHANNEL BANDWIDT H	MODULATION	MODE(DF T-S-OFDM) (INCLUDE CP-OFDM)
A	ERP	158100 to 159100	158100,158600,159100	Low, Middle, High	5MHz	QPSK	1RB/ 0RB Offset
		158600	158600	Middle	10MHz	QPSK	1RB/ 0RB Offset
A	FREQUENC Y STABILITY	158100 to 159100	158100,159100	Low, High	5MHz	QPSK	Outer_ Full
A	PEAK TO AVERAGE RATIO	158100 to 159100	158100,158600,159100	Low, Middle, High	5MHz	QPSK	1RB/ 0RB Offset
							Outer_ Full
		158600	158600	Middle	10MHz	QPSK	1RB/ 0RB Offset
							Outer_ Full
A	OCCUPIED BANDWIDTH	158100 to 159100	158100,158600,159100	Middle	5MHz	Pi/2BPSK,QPSK,16QAM, 64QAM, 256QAM	Outer_ Full
		158600	158600	Middle	10MHz	Pi/2BPSK,QPSK,16QAM, 64QAM, 256QAM	Outer_ Full
A	BAND EDGE	158100 to 159100	158100,158600,159100	Low	5MHz	QPSK	1RB/ 0RB Offset
							Outer_ Full
				High	5MHz	QPSK	1RB/ 0RB Offset
							Outer_ Full
		158600	158600	Middle	10MHz	QPSK	1RB/ 0RB Offset
							Outer_ Full
A	CONDUCTE D EMISSION	158100 to 159100	158100,158600,159100	Low, Middle, High	5MHz	QPSK	1RB/ 0RB Offset
		158600	158600	Middle	10MHz	QPSK	1RB/ 0RB Offset
A	RADIATED EMISSION	158100 to 159100	158100,158600,159100	Middle	5MHz	QPSK	1RB/ 0RB Offset
		158600	158600	Middle	10MHz	QPSK	1RB/ 0RB Offset



BUREAU VERITAS Test Report No.: PSU-QBJ2512030110RF05

Note: 1.This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation.

2. The test data presented in the report from worst SA_n14

NR BAND N26

EUT CONFIGUR E MODE	TEST ITEM	AVAILABL E CP- OFDM CHANNEL	AVAILABLE DFT-S- OFDM CHANNEL	TESTED CHANNE L	CHANNEL BANDWIDT H	MODULATION	MODE(DF T-S-OFDM) (INCLUDE CP-OFDM)
A	ERP	163300 to 164300	163300,163800,164300	Low, Middle, High	5MHz	QPSK	1RB/ 0RB Offset
		163800	163800	Low, Middle, High	10MHz	QPSK	1RB/ 0RB Offset
A	FREQUENC Y STABILITY	163300 to 164300	163300,164300	Low, High	5MHz	QPSK	Outer_ Full
A	PEAK TO AVERAGE RATIO	163300 to 164300	163300,163800,164300	Low, Middle, High	5MHz	QPSK	1RB/ 0RB Offset
							Outer_ Full
		163800	163800	Middle	10MHz	QPSK	1RB/ 0RB Offset
							Outer_ Full
A	OCCUPIED BANDWIDTH	163300 to 164300	163800	Middle	5MHz	Pi/2BPSK,QPSK,16QAM, 64QAM, 256QAM	Outer_ Full
		163800	163800	Middle	10MHz	Pi/2BPSK,QPSK,16QAM, 64QAM, 256QAM	Outer_ Full
A	BAND EDGE	163300 to 164300	163300,164300	Low	5MHz	QPSK	1RB/ 0RB Offset
							Outer_ Full
				High	5MHz	QPSK	1RB/ 0RB Offset
							Outer_ Full
		163800	163800	Middle	10MHz	QPSK	1RB/ 0RB Offset
							Outer_ Full
A	CONDUCTE D EMISSION	163300 to 164300	163300,163800,164300	Low, Middle, High	5MHz	QPSK	1RB/ 0RB Offset
		163800	163800	Middle	10MHz	QPSK	1RB/ 0RB Offset
A	RADIATED EMISSION	163300 to 164300	163800	Middle	5MHz	QPSK	1RB/ 0RB Offset
		163800	163800	Middle	10MHz	QPSK	1RB/ 0RB Offset

Note: 1.This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation.

2. The test data presented in the report from worst SA_n26



TEST CONDITION			
TEST ITEM	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
EIRP(ERP)	24deg. C, 60%RH	DC 3.8V By Battery	Hanwen Xu
FREQUENCY STABILITY	24deg. C, 61%RH	DC 3.8V By DC Source	Hanwen Xu
OCCUPIED BANDWIDTH	24deg. C, 61%RH	DC 3.8V By Battery	Hanwen Xu
BAND EDGE	24deg. C, 61%RH	DC 3.8V By Battery	Hanwen Xu
CONDUCTED EMISSION	24deg. C, 61%RH	DC3.8V By Battery	Hanwen Xu
RADIATED EMISSION	23deg. C, 70%RH	AC 120V/60Hz	Hanwen Xu



2.5 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC 47 CFR Part 2

FCC 47 CFR Part 90

ANSI/TIA/EIA-603-D

ANSI/TIA/EIA-603-E

ANSI C63.26-2015

NOTE: All test items have been performed and recorded as per the above standards.



3 TEST TYPES AND RESULTS

3.1 OUTPUT POWER MEASUREMENT

3.1.1 LIMITS OF OUTPUT POWER MEASUREMENT

LTE B14

47 CFR 90.542(a)(6)

Control stations and mobile stations transmitting in the 758–768 MHz band and the 788–798 MHz band are limited to 30 watts ERP.

47 CFR 90.542(a)(7)

Portable stations (hand-held devices) transmitting in the 758–768 MHz band and the 788–798 MHz band are limited to 3 watts ERP.

LTE B26前段:

Per FCC Part 90.635(a)(b)

The maximum output power of the transmitter for mobile stations is 100 watts (20 dBw).

3.1.2 TEST PROCEDURES

EIRP / ERP MEASUREMENT:

Per KDB 971168 D01 Power Meas License Digital Systems v03r01 or subclause 5.2.5.5 of ANSI C63.26-2015, the relevant equation for determining the ERP or EIRP from the conducted RF output power measured using the guidance provided above is:

$$\text{ERP or EIRP} = P_{\text{Meas}} + G_{\text{T}} - L_{\text{C}}$$

Where:

ERP or EIRP = effective radiated power or equivalent isotropically radiated power, respectively

(expressed in the same units as P_{Meas} , typically dBW or dBm);

P_{Meas} = measured transmitter output power or PSD, in dBm or dBW;

G_{T} = gain of the transmitting antenna, in dBd (ERP) or dBi (EIRP);

L_{C} = signal attenuation in the connecting cable between the transmitter and antenna, in dB


CONDUCTED POWER MEASUREMENT:

- The EUT was set up for the maximum power with LTE link data modulation and link up with simulator.
- Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.



3.1.3 TEST SETUP

CONDUCTED POWER MEASUREMENT:



For the actual test configuration, please refer to the attached file (Test Setup Photo).



3.1.4 TEST RESULTS

AVERAGE CONDUCTED OUTPUT POWER (dBm)

LTE Band 14						
Band/BW	Modulation	RB Size	RB Offset	Low CH 23305	Mid CH 23330	High CH 23355
				Frequency 790.5 MHz	Frequency 793 MHz	Frequency 795.5 MHz
14/ 5	QPSK	1	0	22.69	22.78	22.62
		1	12	22.74	22.73	22.72
		1	24	22.73	22.63	22.77
		12	0	21.52	21.56	21.57
		12	6	21.54	21.66	21.52
		12	13	21.55	21.56	21.58
		25	0	21.63	21.75	21.56
	16QAM	1	0	21.89	21.73	21.89
		1	12	21.69	21.69	21.84
		1	24	21.79	21.78	21.79
		12	0	20.57	20.54	20.57
		12	6	20.57	20.52	20.58
		12	13	20.59	20.54	20.57
		25	0	20.68	20.75	20.64
	64QAM	1	0	20.84	20.70	20.79
		1	12	20.64	20.72	20.83
		1	24	20.76	20.73	20.76
		12	0	19.74	19.70	19.68
		12	6	19.51	19.60	19.63
		12	13	19.69	19.82	19.73
		25	0	19.55	19.56	19.72
Band/BW	Modulation	RB Size	RB Offset	/	Mid CH 23330	/
				/	Frequency 793 MHz	/
14/ 10	QPSK	1	0	/	22.78	/
		1	24	/	22.81	/
		1	49	/	22.80	/
		25	0	/	21.65	/
		25	12	/	21.67	/
		25	25	/	21.73	/
		50	0	/	21.76	/
	16QAM	1	0	/	21.89	/
		1	24	/	21.87	/
		1	49	/	21.90	/
		25	0	/	20.65	/
		25	12	/	20.58	/
		25	25	/	20.63	/
		50	0	/	20.74	/
	64QAM	1	0	/	20.88	/
		1	24	/	20.84	/
		1	49	/	20.91	/
		25	0	/	19.76	/
		25	12	/	19.71	/
		25	25	/	19.82	/
		50	0	/	19.73	/



LTE Band 26						
Band/BW	Modulation	RB Size	RB offset	Low CH 26697	Mid CH 23330	High CH 26783
				Frequency 814.7 MHz	Frequency 819 MHz	Frequency 823.3 MHz
26/ 1.4	QPSK	1	0	23.03	22.79	22.94
		1	2	23.07	23.06	23.02
		1	5	22.95	22.80	22.90
		3	0	22.84	22.90	22.82
		3	1	22.94	22.93	22.97
		3	3	23.01	23.02	22.93
		6	0	22.06	22.01	22.06
	16QAM	1	0	22.12	21.89	22.05
		1	2	22.21	22.24	22.31
		1	5	21.93	21.73	22.06
		3	0	21.96	22.16	22.05
		3	1	21.98	22.14	22.00
		3	3	22.06	22.05	22.02
		6	0	20.99	21.05	21.23
	64QAM	1	0	21.16	20.96	21.28
		1	2	21.17	21.01	21.17
		1	5	20.91	20.86	20.97
		3	0	21.10	20.94	21.02
		3	1	20.91	21.06	21.20
		3	3	20.97	20.94	21.03
		6	0	20.01	19.90	20.10
Band/BW	Modulation	RB Size	RB offset	Low CH 26705	Mid CH 23330	High CH 26775
				Frequency 815.5 MHz	Frequency 819 MHz	Frequency 822.5 MHz
26/ 3	QPSK	1	0	23.10	22.80	23.05
		1	12	23.09	23.06	23.05
		1	24	22.84	22.71	23.04
		12	0	21.80	21.92	21.86
		12	6	22.05	22.05	22.11
		12	13	21.86	22.06	21.90
		25	0	22.04	22.02	22.01
	16QAM	1	0	22.11	21.92	22.23
		1	12	22.18	22.09	22.19
		1	24	21.88	21.74	22.02
		12	0	21.10	21.16	20.85
		12	6	21.05	20.95	21.15
		12	13	21.04	20.89	21.14
		25	0	21.02	21.02	21.11
	64QAM	1	0	21.14	20.95	21.17
		1	12	21.11	21.07	21.21
		1	24	20.88	20.97	21.09
		12	0	20.12	19.96	20.02
		12	6	19.91	20.20	20.16
		12	13	20.15	20.05	20.02
		25	0	19.94	19.95	20.14



LTE Band 26						
Band/BW	Modulation	RB Size	RB offset	Low CH 26715	Mid CH 23330	High CH 26765
				Frequency 816.5 MHz	Frequency 819 MHz	Frequency 821.5 MHz
26/ 5	QPSK	1	0	22.95	22.93	22.96
		1	12	23.04	23.12	23.09
		1	24	22.86	22.86	23.10
		12	0	21.86	21.86	21.80
		12	6	21.92	21.89	22.10
		12	13	21.87	22.06	22.02
		25	0	21.86	22.10	22.11
	16QAM	1	0	22.05	21.80	22.05
		1	12	22.30	22.18	22.18
		1	24	21.95	21.74	22.11
		12	0	20.99	21.00	20.90
		12	6	20.89	21.05	21.03
		12	13	20.92	20.85	21.01
		25	0	21.03	21.13	21.10
	64QAM	1	0	21.12	20.92	21.26
		1	12	21.13	20.97	21.15
		1	24	20.83	20.83	20.95
		12	0	20.15	20.04	19.96
		12	6	19.89	20.12	20.24
		12	13	20.07	19.92	19.94
		25	0	20.15	19.88	19.99
Band/BW	Modulation	RB Size	RB offset	/	Mid CH 23330	/
				/	Frequency 819 MHz	/
26/ 10	QPSK	1	0	/	22.95	/
		1	24	/	23.16	/
		1	49	/	22.84	/
		25	0	/	21.94	/
		25	12	/	22.10	/
		25	25	/	22.09	/
		50	0	/	22.18	/
	16QAM	1	0	/	21.93	/
		1	24	/	22.28	/
		1	49	/	21.82	/
		25	0	/	21.04	/
		25	12	/	21.09	/
		25	25	/	21.08	/
		50	0	/	21.09	/
	64QAM	1	0	/	21.03	/
		1	24	/	21.26	/
		1	49	/	21.00	/
		25	0	/	20.17	/
		25	12	/	20.18	/
		25	25	/	20.01	/
		50	0	/	20.07	/



BUREAU VERITAS Test Report No.: PSU-QBJ2512030110RF05
REDCAP MODE
NR BAND N14

n14 (SCS 15kHz)								
BW [MHz]	DFT-s-OFDM	RB Size	RB Offset	Low	Mid	High	MPR (dB)	Max. Tune-up (dBm)
		Channel			158600			
		Frequency (MHz)			793			
10	Pi/2 BPSK	1	1		22.89		0	25.7
		1	26		22.74		0	25.7
		1	50		22.69		0	25.7
		25	0		22.33		0.5	25.2
		25	14		22.74		0	25.7
		25	27		22.43		0.5	25.2
		50	0		22.41		0.5	25.2
	QPSK	1	1		22.90		0	25.7
		1	26		22.88		0	25.7
		1	50		22.87		0	25.7
		25	0		21.83		1	24.7
		25	14		22.88		0	25.7
		25	27		21.96		1	24.7
		50	0		22.08		1	24.7
	16QAM	1	1		21.59		1	24.7
	64QAM	1	1		20.34		2.5	23.2
	256QAM	1	1		18.75		4.5	21.2
BW [MHz]	DFT-s-OFDM	Channel		158100	158600	159100	MPR (dB)	Max. Tune-up
		Frequency (MHz)		790.5	793	795.5		
5	QPSK	1	1	22.83	22.83	22.84	0	25.7



n26 (SCS 15kHz)								
BW [MHz]	DFT-s-OFDM	RB Size	RB Offset	Low	Mid	High	MPR (dB)	Max. Tune-up (dBm)
		Channel			163800			
		Frequency (MHz)			819			
10	Pi/2 BPSK	1	1		22.98		0	24.0
		1	26		23.01		0	24.0
		1	50		22.62		0	24.0
		25	0		22.21		0.5	23.5
		25	14		22.68		0	24.0
		25	27		22.33		0.5	23.5
		50	0		22.43		0.5	23.5
	QPSK	1	1		23.16		0	24.0
		1	26		23.02		0	24.0
		1	50		22.94		0	24.0
		25	0		21.75		1	23.0
		25	14		22.97		0	24.0
		25	27		21.92		1	23.0
		50	0		22.08		1	23.0
	16QAM	1	1		21.71		1	23.0
	64QAM	1	1		20.07		2.5	21.5
	256QAM	1	1		18.86		4.5	19.5
BW [MHz]	DFT-s-OFDM	Channel		163300	163800	164300	MPR (dB)	Max. Tune-up
		Frequency (MHz)		816.5	819	821.5		
5	QPSK	1	1	23.15	22.96	22.78	0	24.0



ERP

LTE BAND 14

5MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	ERP (dBm)	ERP (mW)	Limit (W)
23305	790.5	22.74	1.21	21.80	151.36	3
23330	793	22.78	1.21	21.84	152.76	3
23355	795.5	22.77	1.21	21.83	152.41	3

5MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	ERP (dBm)	ERP (mW)	Limit (W)
23305	790.5	21.89	1.21	20.95	124.45	3
23330	793	21.78	1.21	20.84	121.34	3
23355	795.5	21.89	1.21	20.95	124.45	3

5MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	ERP (dBm)	ERP (mW)	Limit (W)
23305	790.5	20.84	1.21	19.90	97.72	3
23330	793	20.73	1.21	19.79	95.28	3
23355	795.5	20.83	1.21	19.89	97.50	3

10MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	ERP (dBm)	ERP (mW)	Limit (W)
23330	793	22.81	1.21	21.87	153.82	3

10MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	ERP (dBm)	ERP (mW)	Limit (W)
23330	793	21.91	1.21	20.96	124.74	3

10MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	ERP (dBm)	ERP (mW)	Limit (W)
23330	793	20.91	1.21	19.97	99.31	3



LTE BAND 26						
1.4MHz QPSK						
Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	ERP (dBm)	ERP (mW)	Limit (W)
26697	814.7	23.07	2.06	22.98	198.61	100
23330	819	23.06	2.06	22.97	198.15	100
26783	823.3	23.02	2.06	22.93	196.34	100

1.4MHz 16QAM						
Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	ERP (dBm)	ERP (mW)	Limit (W)
26697	814.7	22.21	2.06	22.12	162.93	100
23330	819	22.24	2.06	22.15	164.06	100
26783	823.3	22.31	2.06	22.22	166.72	100

1.4MHz 64QAM						
Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	ERP (dBm)	ERP (mW)	Limit (W)
26697	814.7	21.17	2.06	21.08	128.23	100
23330	819	21.06	2.06	20.97	125.03	100
26783	823.3	21.28	2.06	21.19	131.52	100

3MHz QPSK						
Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	ERP (dBm)	ERP (mW)	Limit (W)
26705	815.5	23.10	2.06	23.01	199.99	100
23330	819	23.06	2.06	22.97	198.15	100
26775	822.5	23.05	2.06	22.96	197.70	100

3MHz 16QAM						
Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	ERP (dBm)	ERP (mW)	Limit (W)
26705	815.5	22.18	2.06	22.09	161.81	100
23330	819	22.09	2.06	22.00	158.49	100
26775	822.5	22.23	2.06	22.14	163.68	100



3MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	ERP (dBm)	ERP (mW)	Limit (W)
26705	815.5	21.14	2.06	21.05	127.35	100
23330	819	21.07	2.06	20.98	125.31	100
26775	822.5	21.21	2.06	21.12	129.42	100

5MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	ERP (dBm)	ERP (mW)	Limit (W)
26715	816.5	23.04	2.06	22.95	197.24	100
23330	819	23.12	2.06	23.03	200.91	100
26765	821.5	23.10	2.06	23.01	199.99	100

5MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	ERP (dBm)	ERP (mW)	Limit (W)
26715	816.5	22.30	2.06	22.21	166.34	100
23330	819	22.18	2.06	22.09	161.81	100
26765	821.5	22.18	2.06	22.09	161.81	100

5MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	ERP (dBm)	ERP (mW)	Limit (W)
26715	816.5	21.13	2.06	21.04	127.06	100
23330	819	20.97	2.06	20.88	122.46	100
26765	821.5	21.26	2.06	21.17	130.92	100

10MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	ERP (dBm)	ERP (mW)	Limit (W)
23330	819	23.61	2.06	23.07	202.77	100

10MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	ERP (dBm)	ERP (mW)	Limit (W)
23330	819	22.28	2.06	22.19	165.58	100



10MHz 64QAM						
Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
23330	819	21.26	2.06	21.17	130.92	100

REMARKS: ERP Output Power (dBm) = EIRP (dBm) -2.15(dB).

REDCAP MODE

NR BAND N14

n14 (SCS 15kHz)							
BW [MHz] Modulation	Channel	Frequency (MHz)	Conducted Power (dBm)	Gain (dB)	ERP (dBm)	ERP (mW)	Limit (W)
10M-Pi/2 BPSK	158600	793	22.89	1.46	22.20	165.96	3
10M-QPSK	158600	793	22.90	1.46	22.21	166.34	3
10M-16QAM	158600	793	21.59	1.46	20.90	123.03	3
10M-64QAM	158600	793	20.34	1.46	19.65	92.26	3
10M-256QAM	158600	793	18.75	1.46	18.06	63.97	3
BW [MHz] Modulation	Channel	Frequency (MHz)	Conducted Power (dBm)	Gain (dB)	ERP (dBm)	ERP (mW)	Limit (W)
5M-QPSK	158100	790.5	22.83	1.46	22.14	163.68	3
	158600	793	22.83	1.46	22.14	163.68	3
	159100	795.5	22.84	1.46	22.15	164.06	3



BUREAU VERITAS Test Report No.: PSU-QBJ2512030110RF05
NR BAND N26

n26 (SCS 15kHz)							
BW [MHz] Modulation	Channel	Frequency (MHz)	Conducted Power (dBm)	Gain (dB)	ERP (dBm)	ERP (mW)	Limit (W)
10M-Pi/2 BPSK	163800	819	23.01	2.06	22.92	195.88	100
10M-QPSK	163800	819	23.16	2.06	23.07	202.77	100
10M- 16QAM	163800	819	21.71	2.06	21.62	145.21	100
10M- 64QAM	163800	819	20.07	2.06	19.98	99.54	100
10M- 256QAM	163800	819	18.86	2.06	18.77	75.34	100
BW [MHz] Modulation	Channel	Frequency (MHz)	Conducted Power (dBm)	Gain (dB)	ERP (dBm)	ERP (mW)	Limit (W)
5M-QPSK	163300	816.5	23.15	2.06	23.06	202.30	100
	163800	819	22.96	2.06	22.87	193.64	100
	164300	821.5	22.78	2.06	22.69	185.78	100



3.2 FREQUENCY STABILITY MEASUREMENT

3.2.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT


The frequency stability of mobile, portable and control transmitters operating in the wideband segment must be 1.25 parts per million or better when AFC is locked to a base station, and 5 parts per million or better when AFC is not locked

3.2.2 TEST PROCEDURE

- Device is placed at the oven room. The oven room could control the temperatures and humidity. Power warm up is at least 15 min and power applied should perform before recording frequency error.
- EUT is connected the external power supply to control the DC input power. The test voltage range is from minimum to maximum working voltage. Each step shall be record the frequency error rate.
- The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the $\pm 0.5^{\circ}\text{C}$ during the measurement testing. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.

NOTE: The frequency error was recorded frequency error from the communication simulator.

3.2.3 TEST SETUP





3.2.4 TEST RESULTS

Please Refer to Appendix of this test report.

Note: VL = Low voltage(3.3V); VN/NV = Normal voltage(3.8V); VH = High voltage(4.35V);
NT = Normal temperature (25°C)




3.3 OCCUPIED BANDWIDTH MEASUREMENT

3.3.1 LIMITS OF OCCUPIED BANDWIDTH MEASUREMENT

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 %of the total mean power of a given emission.

3.3.2 TEST SETUP



3.3.3 TEST PROCEDURES

- The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.
- Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth.

3.3.4 TEST RESULTS

Please Refer to Appendix of this test report.



3.4 EMISSION MASK MEASUREMENT

3.4.1 LIMITS OF EMISSION MASK MEASUREMENT

LTE Band14:

According to FCC part 90.543(e) shall be tested the emission mask.

(e) For operations in the 758–768 MHz and the 788–798 MHz bands, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following:

(1) On all frequencies between 769–775 MHz and 799–805 MHz, by a factor not less than $76 + 10 \log (P)$ dB in a 6.25 kHz band segment, for base and fixed stations.

(2) On all frequencies between 769–775 MHz and 799–805 MHz, by a factor not less than $65 + 10 \log (P)$ dB in a 6.25 kHz band segment, for mobile and portable stations.

(3) On any frequency between 775–788 MHz, above 805 MHz, and below 758 MHz, by at least $43 + 10 \log (P)$ dB.

(4) Compliance with the provisions of paragraphs (e)(1) and (2) of this section is based on the use of measurement instrumentation such that the reading taken with any resolution bandwidth setting should be adjusted to indicate spectral energy in a 6.25 kHz segment.

(5) Compliance with the provisions of paragraph (e)(3) of this section is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater. However, in the 100 kHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of 30 kHz may be employed.




LTE Band26:

According to FCC part 90.691 shall be tested the emission mask. For any frequency removed from the EA licensee's frequency block by up to and including 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $116 \log_{10}(f/6.1)$ decibels or $50 + 10 \log_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 12.5 kHz.

For any frequency removed from the EA licensee's frequency block greater than 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 37.5 kHz.

3.4.2 TEST SETUP





3.4.3 TEST PROCEDURES

- a) Connect the transmitter to the spectrum analyzer via coaxial cable while ensuring proper impedance matching.
- b) Tune the analyzer to the nominal center frequency of the emission bandwidth (EBW).
- c) Set the resolution bandwidth (RBW) $\geq 1\%$ EBW in the 1MHz band immediately outside and adjacent to the band edge.
- d) Beyond the 1MHz band from the band edge, RBW=1MHz was used.
- e) Set the video bandwidth (VBW) to $\geq 3 \times$ RBW.
- f) Select the average power (RMS) display detector.
- g) Set the number of measurement points to ≥ 1001 .
- h) Use auto-coupled sweep time.
- i) Perform the measurement over an interval of time when the transmission is continuous and at its maximum power level.
- j) The RF fundamental frequency should be excluded against the limit line in the operating frequency band and use RBW is 10KHz or 100KHz.
- k) Record the max trace plot into the test report.

3.4.4 TEST RESULTS

Please Refer to Appendix of this test report.



3.5 CONDUCTED SPURIOUS EMISSIONS

3.5.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT


(1) The power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least $43 + 10 \log_{10}(P)$ dB. The limit of emission equal to -13dBm

(2) For operations in the 763–775 MHz and 793–805 MHz bands, all emissions including harmonics in the band 1559–1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth. For the purpose of equipment authorization, a transmitter shall be tested with an antenna that is representative of the type that will be used with the equipment in normal operation.

3.5.2 TEST PROCEDURE

- a. The EUT makes a phone call to the communication simulator. All measurements were done at middle operational frequency range.
- b. Measuring frequency range is from 9kHz up to a frequency including its 10th harmonic. 10dB attenuation pad is connected with spectrum. RBW=1MHz and VBW=3MHz is used for conducted emission measurement.

3.5.3 TEST SETUP





3.5.4 TEST RESULTS

NOTE : The 9K~30MHz amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required in the report.

Please Refer to Appendix of this test report.



3.6 RADIATED EMISSION MEASUREMENT

3.6.1 LIMITS OF RADIATED EMISSION MEASUREMENT

(1) The power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least $43 + 10 \log_{10}(P)$ dB. The limit of emission equal to -13dBm

(2) For operations in the 763–775 MHz and 793–805 MHz bands, all emissions including harmonics in the band 1559–1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth. For the purpose of equipment authorization, a transmitter shall be tested with an antenna that is representative of the type that will be used with the equipment in normal operation.

3.6.2 TEST PROCEDURES

- a. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The “Read Value” is the spectrum reading the maximum power value.
- b. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to “Read Value” of step a. Record the power level of S.G
- c. $\text{EIRP} = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}.$
- d. E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole,
 $\text{E.R.P power} = \text{E.I.P.R power} - 2.15\text{dBi}.$

NOTE: The resolution bandwidth of spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz.


3.6.3 DEVIATION FROM TEST STANDARD

No deviation




3.6.4 TEST SETUP

<Below 30MHz>




< Frequency Range 30MHz~1GHz >





< Frequency Range above 1GHz >




For the actual test configuration, please refer to the attached file (Test Setup Photo).



3.6.5 TEST RESULTS

BELOW 1GHz WORST-CASE DATA

NOTE : The 9K~30MHz amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required in the report.






MODE	TX channel 26740	FREQUENCY RANGE	30 MHz ~ 1GHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V 60HZ
TESTED BY	Hanwen Xu		


ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Polarity	Detector	Verdict
1	30	-47.70	-55.66	-7.96	-13.00	42.66	Vertical	PK	PASS
2	84.7189	-45.76	-60.63	-14.87	-13.00	47.63	Vertical	PK	PASS
3	112.2725	-49.99	-61.17	-11.18	-13.00	48.17	Vertical	PK	PASS
4	148.5577	-48.28	-58.18	-9.90	-13.00	45.18	Vertical	PK	PASS
5	328.2376	-63.35	-71.48	-8.13	-13.00	58.48	Vertical	PK	PASS
6	536.6353	-65.24	-65.16	0.08	-13.00	52.16	Vertical	PK	PASS



**ABOVE 1GHz**

Note: For higher frequency, the emission is too low to be detected.






CHANNEL BANDWIDTH	5MHz / QPSK	MODE	TX channel 23305
FREQUENCY RANGE	Above 1000MHz	ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH
INPUT POWER	AC 120V 60HZ	TESTED BY	Hanwen Xu

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Polarity	Detector	Verdict
1	1576.5153	-50.25	-59.67	-9.42	-40.00	19.67	Vertical	PK	PASS
2	2364.6729	-47.34	-53.74	-6.40	-13.00	40.74	Vertical	PK	PASS






CHANNEL BANDWIDTH	5MHz / QPSK	MODE	TX channel 23330
FREQUENCY RANGE	Above 1000MHz	ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH
INPUT POWER	AC 120V 60HZ	TESTED BY	Hanwen Xu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Polarity	Detector	Verdict
1	1581.7163	-43.54	-52.91	-9.37	-40.00	12.91	Horizontal	PK	PASS
2	2372.6745	-34.00	-40.55	-6.55	-13.00	27.55	Horizontal	PK	PASS






CHANNEL BANDWIDTH	5MHz / QPSK	MODE	TX channel 23330
FREQUENCY RANGE	Above 1000MHz	ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH
INPUT POWER	AC 120V 60HZ	TESTED BY	Hanwen Xu

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Polarity	Detector	Verdict
1	1581.7163	-50.46	-59.89	-9.43	-40.00	19.89	Vertical	PK	PASS
2	2372.2745	-42.51	-48.90	-6.39	-13.00	35.90	Vertical	PK	PASS






CHANNEL BANDWIDTH	5MHz / QPSK	MODE	TX channel 23355
FREQUENCY RANGE	Above 1000MHz	ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH
INPUT POWER	AC 120V 60HZ	TESTED BY	Hanwen Xu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Polarity	Detector	Verdict
1	1586.5173	-45.15	-54.51	-9.36	-40.00	14.51	Horizontal	PK	PASS
2	2380.2761	-33.79	-40.32	-6.53	-13.00	27.32	Horizontal	PK	PASS






CHANNEL BANDWIDTH	5MHz / QPSK	MODE	TX channel 23355
FREQUENCY RANGE	Above 1000MHz	ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH
INPUT POWER	AC 120V 60HZ	TESTED BY	Hanwen Xu

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Polarity	Detector	Verdict
1	1586.1172	-51.60	-61.04	-9.44	-40.00	21.04	Vertical	PK	PASS
2	2379.876	-44.63	-51.01	-6.38	-13.00	38.01	Vertical	PK	PASS






CHANNEL BANDWIDTH	10MHz / QPSK	MODE	TX channel 23330
FREQUENCY RANGE	Above 1000MHz	ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH
INPUT POWER	AC 120V 60HZ	TESTED BY	Hanwen Xu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Polarity	Detector	Verdict
1	1577.3155	-41.88	-51.25	-9.37	-40.00	11.25	Horizontal	PK	PASS
2	2365.8732	-33.02	-39.58	-6.56	-13.00	26.58	Horizontal	PK	PASS







CHANNEL BANDWIDTH	10MHz / QPSK	MODE	TX channel 23330
FREQUENCY RANGE	Above 1000MHz	ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH
INPUT POWER	AC 120V 60HZ	TESTED BY	Hanwen Xu

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Polarity	Detector	Verdict
1	1577.3155	-49.20	-58.62	-9.42	-40.00	18.62	Vertical	PK	PASS
2	2365.8732	-44.97	-51.37	-6.40	-13.00	38.37	Vertical	PK	PASS








CHANNEL BANDWIDTH	1.4MHz / QPSK	MODE	TX channel 26740
FREQUENCY RANGE	Above 1000MHz	ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH
INPUT POWER	AC 120V 60HZ	TESTED BY	Hanwen Xu

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Polarity	Detector	Verdict
1	1636.9274	-49.39	-58.91	-9.52	-13.00	45.91	Vertical	PK	PASS
2	2455.4911	-45.30	-51.40	-6.10	-13.00	38.40	Vertical	PK	PASS






CHANNEL BANDWIDTH	3MHz / QPSK	MODE	TX channel 26705
FREQUENCY RANGE	Above 1000MHz	ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH
INPUT POWER	AC 120V 60HZ	TESTED BY	Hanwen Xu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Polarity	Detector	Verdict
1	1628.5257	-44.06	-53.49	-9.43	-13.00	40.49	Horizontal	PK	PASS
2	2442.6885	-36.01	-42.31	-6.30	-13.00	29.31	Horizontal	PK	PASS






CHANNEL BANDWIDTH	3MHz / QPSK	MODE	TX channel 26705
FREQUENCY RANGE	Above 1000MHz	ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH
INPUT POWER	AC 120V 60HZ	TESTED BY	Hanwen Xu

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Polarity	Detector	Verdict
1	1670.134	-44.73	-54.32	-9.59	-13.00	41.32	Vertical	PK	PASS
2	2443.0886	-47.71	-53.86	-6.15	-13.00	40.86	Vertical	PK	PASS






BUREAU VERITAS Test Report No.: PSU-QBJ2512030110RF05

CHANNEL BANDWIDTH	3MHz / QPSK	MODE	TX channel 26740
FREQUENCY RANGE	Above 1000MHz	ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH
INPUT POWER	AC 120V 60HZ	TESTED BY	Hanwen Xu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Polarity	Detector	Verdict
1	1635.3271	-43.38	-52.83	-9.45	-13.00	39.83	Horizontal	PK	PASS
2	2453.0906	-33.93	-40.18	-6.25	-13.00	27.18	Horizontal	PK	PASS






CHANNEL BANDWIDTH	3MHz / QPSK	MODE	TX channel 26740
FREQUENCY RANGE	Above 1000MHz	ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH
INPUT POWER	AC 120V 60HZ	TESTED BY	Hanwen Xu

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Polarity	Detector	Verdict
1	1635.3271	-50.08	-59.60	-9.52	-13.00	46.60	Vertical	PK	PASS
2	2453.0906	-47.88	-53.99	-6.11	-13.00	40.99	Vertical	PK	PASS






BUREAU VERITAS Test Report No.: PSU-QBJ2512030110RF05

CHANNEL BANDWIDTH	3MHz / QPSK	MODE	TX channel 26783
FREQUENCY RANGE	Above 1000MHz	ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH
INPUT POWER	AC 120V 60HZ	TESTED BY	Hanwen Xu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Polarity	Detector	Verdict
1	1642.1284	-46.47	-55.94	-9.47	-13.00	42.94	Horizontal	PK	PASS
2	2463.8928	-35.11	-41.31	-6.20	-13.00	28.31	Horizontal	PK	PASS






CHANNEL BANDWIDTH	3MHz / QPSK	MODE	TX channel 26783
FREQUENCY RANGE	Above 1000MHz	ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH
INPUT POWER	AC 120V 60HZ	TESTED BY	Hanwen Xu

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Polarity	Detector	Verdict
1	1642.1284	-52.30	-61.83	-9.53	-13.00	48.83	Vertical	PK	PASS
2	2463.4927	-47.45	-53.52	-6.07	-13.00	40.52	Vertical	PK	PASS






CHANNEL BANDWIDTH	5MHz / QPSK	MODE	TX channel 26740
FREQUENCY RANGE	Above 1000MHz	ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH
INPUT POWER	AC 120V 60HZ	TESTED BY	Hanwen Xu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Polarity	Detector	Verdict
1	1633.7267	-43.85	-53.30	-9.45	-13.00	40.30	Horizontal	PK	PASS
2	2450.2901	-34.84	-41.11	-6.27	-13.00	28.11	Horizontal	PK	PASS






CHANNEL BANDWIDTH	5MHz / QPSK	MODE	TX channel 26740
FREQUENCY RANGE	Above 1000MHz	ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH
INPUT POWER	AC 120V 60HZ	TESTED BY	Hanwen Xu

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Polarity	Detector	Verdict
1	1633.3267	-50.43	-59.95	-9.52	-13.00	46.95	Vertical	PK	PASS
2	2450.2901	-47.77	-53.90	-6.13	-13.00	40.90	Vertical	PK	PASS






CHANNEL BANDWIDTH	10MHz / QPSK	MODE	TX channel 26740
FREQUENCY RANGE	Above 1000MHz	ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH
INPUT POWER	AC 120V 60HZ	TESTED BY	Hanwen Xu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Polarity	Detector	Verdict
1	1629.3259	-44.03	-53.46	-9.43	-13.00	40.46	Horizontal	PK	PASS
2	2443.4887	-35.64	-41.94	-6.30	-13.00	28.94	Horizontal	PK	PASS







CHANNEL BANDWIDTH	10MHz / QPSK	MODE	TX channel 26740
FREQUENCY RANGE	Above 1000MHz	ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH
INPUT POWER	AC 120V 60HZ	TESTED BY	Hanwen Xu

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Polarity	Detector	Verdict
1	1628.9258	-50.69	-60.20	-9.51	-13.00	47.20	Vertical	PK	PASS
2	2443.4887	-46.94	-53.09	-6.15	-13.00	40.09	Vertical	PK	PASS








CHANNEL BANDWIDTH	5MHz/QPSK	MODE	TX channel 158100
FREQUENCY RANGE	Above 1000MHz	ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH
INPUT POWER	120Vac 60HZ	TESTED BY	Hanwen Xu

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Polarity	Detector	Verdict
1	1581.3163	-50.26	-59.69	-9.43	-40.00	19.69	Vertical	PK	PASS
2	2371.8744	-53.91	-60.30	-6.39	-13.00	47.30	Vertical	PK	PASS






CHANNEL BANDWIDTH	5MHz/QPSK	MODE	TX channel 158600
FREQUENCY RANGE	Above 1000MHz	ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH
INPUT POWER	120Vac 60HZ	TESTED BY	Hanwen Xu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Polarity	Detector	Verdict
1	1581.7163	-46.88	-56.25	-9.37	-40.00	16.25	Horizontal	PK	PASS
2	2372.2745	-31.95	-38.50	-6.55	-13.00	25.50	Horizontal	PK	PASS






CHANNEL BANDWIDTH	5MHz/QPSK	MODE	TX channel 158600
FREQUENCY RANGE	Above 1000MHz	ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH
INPUT POWER	120Vac 60HZ	TESTED BY	Hanwen Xu

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Polarity	Detector	Verdict
1	1581.7163	-50.64	-60.07	-9.43	-40.00	20.07	Vertical	PK	PASS
2	2372.6745	-45.27	-51.66	-6.39	-13.00	38.66	Vertical	PK	PASS






CHANNEL BANDWIDTH	5MHz/QPSK	MODE	TX channel 159100
FREQUENCY RANGE	Above 1000MHz	ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH
INPUT POWER	120Vac 60HZ	TESTED BY	Hanwen Xu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Polarity	Detector	Verdict
1	1591.3183	-52.46	-61.81	-9.35	-40.00	21.81	Horizontal	PK	PASS
2	2386.6773	-54.79	-61.32	-6.53	-13.00	48.32	Horizontal	PK	PASS






CHANNEL BANDWIDTH	5MHz/QPSK	MODE	TX channel 159100
FREQUENCY RANGE	Above 1000MHz	ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH
INPUT POWER	120Vac 60HZ	TESTED BY	Hanwen Xu

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Polarity	Detector	Verdict
1	1591.3183	-52.54	-61.99	-9.45	-40.00	21.99	Vertical	PK	PASS
2	2386.6773	-54.93	-61.29	-6.36	-13.00	48.29	Vertical	PK	PASS






CHANNEL BANDWIDTH	10MHz/QPSK	MODE	TX channel 158600
FREQUENCY RANGE	Above 1000MHz	ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH
INPUT POWER	120Vac 60HZ	TESTED BY	Hanwen Xu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Polarity	Detector	Verdict
1	1576.9154	-47.77	-57.14	-9.37	-40.00	17.14	Horizontal	PK	PASS
2	2365.4731	-32.23	-38.79	-6.56	-13.00	25.79	Horizontal	PK	PASS






CHANNEL BANDWIDTH	10MHz/QPSK	MODE	TX channel 167300
FREQUENCY RANGE	Above 1000MHz	ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH
INPUT POWER	120Vac 60HZ	TESTED BY	Hanwen Xu

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Polarity	Detector	Verdict
1	1576.9154	-50.73	-60.15	-9.42	-40.00	20.15	Vertical	PK	PASS
2	2365.073	-44.87	-51.27	-6.40	-13.00	38.27	Vertical	PK	PASS






N26			
CHANNEL BANDWIDTH	5MHz/QPSK	MODE	TX channel 163800
FREQUENCY RANGE	Above 1000MHz	ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH
INPUT POWER	120Vac 60HZ	TESTED BY	Hanwen Xu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Polarity	Detector	Verdict
1	1638.5277	-55.88	-65.34	-9.46	-13.00	52.34	Horizontal	PK	PASS
2	2457.8916	-60.12	-66.34	-6.22	-13.00	53.34	Horizontal	PK	PASS






CHANNEL BANDWIDTH	5MHz/QPSK	MODE	TX channel 163800
FREQUENCY RANGE	Above 1000MHz	ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH
INPUT POWER	120Vac 60HZ	TESTED BY	Hanwen Xu

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Polarity	Detector	Verdict
1	1633.7267	-41.93	-51.45	-9.52	-13.00	38.45	Vertical	PK	PASS
2	2449.89	-31.25	-37.38	-6.13	-13.00	24.38	Vertical	PK	PASS






CHANNEL BANDWIDTH	10MHz/QPSK	MODE	TX channel 163800
FREQUENCY RANGE	Above 1000MHz	ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH
INPUT POWER	120Vac 60HZ	TESTED BY	Hanwen Xu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Polarity	Detector	Verdict
1	1638.5277	-56.96	-66.43	-9.47	-13.00	53.43	Horizontal	PK	PASS
2	2457.8916	-61.47	-67.69	-6.22	-13.00	54.69	Horizontal	PK	PASS






CHANNEL BANDWIDTH	10MHz/QPSK	MODE	TX channel 163800
FREQUENCY RANGE	Above 1000MHz	ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH
INPUT POWER	120Vac 60HZ	TESTED BY	Hanwen Xu

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Polarity	Detector	Verdict
1	1638.5277	-56.61	-66.14	-9.53	-13.00	53.14	Vertical	PK	PASS
2	2457.8916	-61.51	-67.59	-6.08	-13.00	54.59	Vertical	PK	PASS






3.7 PEAK TO AVERAGE RATIO

3.7.1 LIMITS OF PEAK TO AVERAGE RATIO MEASUREMENT

In measuring transmissions in this band using an average power technique, the peak to-average ratio (PAR) of the transmission may not exceed 13 dB

3.7.2 TEST SETUP



3.7.3 TEST PROCEDURES

1. Set resolution/measurement bandwidth $\geq$ signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Record the maximum PAPR level associated with a probability of 0.1%.

3.7.4 TEST RESULTS

Please Refer to Appendix of this test report.



4 INFORMATION ON THE TESTING LABORATORIES

We, Huarui 7layers High Technology (Suzhou) Co., Ltd. ,were founded in 2020 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

Huarui 7Layers High Technology (Suzhou) Co., Ltd.

Lab Address:

Tower N, Innovation Center, 88 Zuyi Road, High-tech District, Suzhou City, Anhui Province, China

Accredited Test Lab Cert 6613.01

If you have any comments, please feel free to contact us at the following:

Suzhou EMC/RF Lab:

Tel: +86 (0557) 368 1008



5 MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No modifications were made to the EUT by the lab during the test.



6 APPENDIX

LTE BAND 14


Peak-to-Average Ratio(CCDF)


Test Result


Band	Bandwidth	Modulation	Channel	RB Configuration	Result(dB)	Limit(dB)	Verdict
Band14	5MHz	QPSK	23305	1RB#0	4.30	13	PASS
Band14	5MHz	QPSK	23305	25RB#0	5.12	13	PASS
Band14	5MHz	QPSK	23330	1RB#0	4.22	13	PASS
Band14	5MHz	QPSK	23330	25RB#0	5.00	13	PASS
Band14	5MHz	QPSK	23355	1RB#0	4.18	13	PASS
Band14	5MHz	QPSK	23355	25RB#0	5.09	13	PASS
Band14	5MHz	64QAM	23305	1RB#0	6.13	13	PASS
Band14	5MHz	64QAM	23305	25RB#0	6.38	13	PASS
Band14	5MHz	64QAM	23330	1RB#0	6.00	13	PASS
Band14	5MHz	64QAM	23330	25RB#0	6.32	13	PASS
Band14	5MHz	64QAM	23355	1RB#0	5.97	13	PASS
Band14	5MHz	64QAM	23355	25RB#0	6.46	13	PASS
Band14	5MHz	16QAM	23305	1RB#0	5.24	13	PASS
Band14	5MHz	16QAM	23305	25RB#0	5.96	13	PASS
Band14	5MHz	16QAM	23330	1RB#0	5.18	13	PASS
Band14	5MHz	16QAM	23330	25RB#0	5.91	13	PASS
Band14	5MHz	16QAM	23355	1RB#0	5.12	13	PASS
Band14	5MHz	16QAM	23355	25RB#0	5.99	13	PASS
Band14	10MHz	QPSK	23330	1RB#0	4.28	13	PASS
Band14	10MHz	QPSK	23330	50RB#0	5.05	13	PASS
Band14	10MHz	64QAM	23330	1RB#0	6.13	13	PASS
Band14	10MHz	64QAM	23330	50RB#0	6.30	13	PASS
Band14	10MHz	16QAM	23330	1RB#0	5.26	13	PASS
Band14	10MHz	16QAM	23330	50RB#0	5.94	13	PASS





Test Graphs














26dB Bandwidth and Occupied Bandwidth

Test Result


Band	Bandwidth	Modulation	Channel	RB Configuration	Occupied Bandwidth (MHz)	26dB Bandwidth (MHz)	Verdict
Band14	5MHz	QPSK	23305	25RB#0	4.5205	5.170	PASS
Band14	5MHz	QPSK	23330	25RB#0	4.5160	5.212	PASS
Band14	5MHz	QPSK	23355	25RB#0	4.5199	5.134	PASS
Band14	5MHz	64QAM	23305	25RB#0	4.5242	5.191	PASS
Band14	5MHz	64QAM	23330	25RB#0	4.5116	5.215	PASS
Band14	5MHz	64QAM	23355	25RB#0	4.5149	5.144	PASS
Band14	5MHz	16QAM	23305	25RB#0	4.5203	5.135	PASS
Band14	5MHz	16QAM	23330	25RB#0	4.5173	5.157	PASS
Band14	5MHz	16QAM	23355	25RB#0	4.5322	5.180	PASS
Band14	10MHz	QPSK	23330	50RB#0	8.9877	9.964	PASS
Band14	10MHz	64QAM	23330	50RB#0	8.9733	9.928	PASS
Band14	10MHz	16QAM	23330	50RB#0	8.9907	9.977	PASS

Test Graphs







BUREAU VERITAS Test Report No.: PSU-QBJ2512030110RF05




Band14-5MHz-64QAM-23330-25RB#0-PASS




Band14-5MHz-64QAM-23355-25RB#0-PASS




Band14-5MHz-16QAM-23305-25RB#0-PASS



Band14-5MHz-16QAM-23330-25RB#0-PASS



Band14-5MHz-16QAM-23355-25RB#0-PASS



Band14-10MHz-QPSK-23330-50RB#0-PASS