

TEST REPORT

Application No.: SZCR2601000213AT
Applicant: FOXX Development Inc.
Address of Applicant: 3480 Preston Ridge Road, Suite500, Alpharetta, Georgia 30005, United States
Manufacturer: FOXX Development Inc.
Address of Manufacturer: 3480 Preston Ridge Road, Suite500, Alpharetta, Georgia 30005, United States
Equipment Under Test (EUT):
EUT Name: 4G LTE Dual-View Dash Cam
Model No.: VI03
Trade Mark: MIRO
FCC ID: 2AQRM-VI03
Standard(s) : 47 CFR Part 15, Subpart C 15.247
Date of Receipt: 2026-01-14
Date of Test: 2026-03-10 to 2026-06-03
Date of Issue: 2026-06-04

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.

Keny Xu

Keny Xu
EMC Laboratory Manager



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch EMC Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.ssgsgroup.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR260100021302

Page: 2 of 125

Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2026-06-04		Original

Authorized for issue by:				
		Martin Tang		
		Martin Tang/Project Engineer		
		Eric Fu		
		Eric Fu/Reviewer		



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2020) Section 6.10.5 & 11.12	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions Below 1GHz		ANSI C63.10 (2020) Section 6.4,6.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions Above 1GHz		ANSI C63.10 (2020) Section 6.6 & 11.12	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Maximum Conducted Output Power		ANSI C63.10 (2020) Section 11.9.2	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass
Minimum 6dB Bandwidth		ANSI C63.10 (2020) Section 11.8.1	47 CFR Part 15, Subpart C 15.247a(2)	Pass
Power Spectral Density		ANSI C63.10 (2020) Section 11.10.3	47 CFR Part 15, Subpart C 15.247(e)	Pass
Conducted Band Edges Measurement		ANSI C63.10 (2020) Section 6.10.4	47 CFR Part 15, Subpart C 15.247(d)	Pass
Conducted Spurious Emissions		ANSI C63.10 (2020) Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass

Remark: This product has two types of power supply, USB-C with voltage converter, OBD only the USB-C with voltage converter was tested in this report, Considering to the difference, there is no impact on RF characteristics.



3 Contents

	Page
1 Cover Page	1
2 Test Summary	3
3 Contents	4
4 General Information	6
4.1 Details of E.U.T.	6
4.2 Description of Support Units	6
4.3 Measurement Uncertainty	7
4.4 Test Location	8
4.5 Test Facility	8
4.6 Deviation from Standards	8
4.7 Abnormalities from Standard Conditions	8
5 Equipment List	9
6 Radio Spectrum Technical Requirement	11
6.1 Antenna Requirement	11
6.1.1 Test Requirement:	11
6.1.2 Conclusion	11
7 Radio Spectrum Matter Test Results	12
7.1 Radiated Emissions which fall in the restricted bands	12
7.1.1 E.U.T. Operation	12
7.1.2 Test Mode Description	12
7.1.3 Test Setup Diagram	13
7.1.4 Measurement Procedure and Data	14
7.2 Radiated Spurious Emissions Below 1GHz	27
7.2.1 E.U.T. Operation	27
7.2.2 Test Mode Description	28
7.2.3 Test Setup Diagram	28
7.2.4 Measurement Procedure and Data	29
7.3 Radiated Spurious Emissions Above 1GHz	36
7.3.1 E.U.T. Operation	36
7.3.2 Test Mode Description	36
7.3.3 Test Setup Diagram	37
7.3.4 Measurement Procedure and Data	38
7.4 Maximum Conducted Output Power	46
7.4.1 E.U.T. Operation	46
7.4.2 Test Mode Description	46
7.4.3 Test Setup Diagram	47
7.4.4 Measurement Procedure and Data	47
7.5 Minimum 6dB Bandwidth	48
7.5.1 E.U.T. Operation	48
7.5.2 Test Mode Description	48



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR260100021302

Page: 5 of 125

7.5.3	Test Setup Diagram	48
7.5.4	Measurement Procedure and Data.....	48
7.6	Power Spectral Density	49
7.6.1	E.U.T. Operation	49
7.6.2	Test Mode Description	49
7.6.3	Test Setup Diagram	49
7.6.4	Measurement Procedure and Data.....	49
7.7	Conducted Band Edges Measurement	50
7.7.1	E.U.T. Operation	50
7.7.2	Test Mode Description	50
7.7.3	Test Setup Diagram	51
7.7.4	Measurement Procedure and Data.....	51
7.8	Conducted Spurious Emissions	52
7.8.1	E.U.T. Operation	52
7.8.2	Test Mode Description	52
7.8.3	Test Setup Diagram	53
7.8.4	Measurement Procedure and Data.....	53
8	Test Setup Photo	54
9	EUT Constructional Details (EUT Photos)	54
10	Appendix.....	55



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing Center (CCTC) Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

4 General Information

4.1 Details of E.U.T.

Power supply:	Input: DC 5V, 1A, 5W via USB-C port OBD model: OBDII-G Input: DC 12V-24V, 1.2A; Output: DC 5V, 2.5A
Cable(s):	USB-C cable : about 3.3m unshielded with voltage converter(Input: DC 12-30V; Output: DC 5V, 2.4A) DC cable(OBD): about 3.5m unshielded
Cable Loss (for RF conducted test):	0.5dB
Operation Frequency:	802.11b/g/n(HT20)/ax(HEW20): 2412MHz to 2462MHz; 802.11n(HT40)/ax(HEW40): 2422MHz to 2452MHz
Modulation Type:	802.11b: DSSS (DBPSK, DQPSK, CCK); 802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM); 802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024-QAM)
Number of Channels:	802.11b/g/n(HT20)/ax(HEW20):11; 802.11n(HT40)/ax(HEW40):7
Channel Spacing:	5MHz
Antenna Type:	FPC Antenna
Antenna Gain:	1.11dBi

Remark: The information in this section is provided by the applicant or manufacturer, SGS is not liable to the accuracy, suitability, reliability or/and integrity of the information.

4.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
--	--	--	--
The EUT has been tested as an independent unit.			



4.3 Measurement Uncertainty

Test Item	Measurement Uncertainty
Radiated Emissions which fall in the restricted bands	$\pm 6.0\text{dB}$ (Below 1GHz); $\pm 4.6\text{dB}$ (Above 1GHz)
Radiated Spurious Emissions Below 1GHz	$\pm 6.0\text{dB}$ for 3m; $\pm 5.0\text{dB}$ for 10m
Radiated Spurious Emissions Above 1GHz	$\pm 4.6\text{dB}$ (1-18GHz); $\pm 4.8\text{dB}$ (18-40GHz)
Maximum Conducted Output Power	$\pm 0.4\text{dB}$
Minimum 6dB Bandwidth	$\pm 0.3\%$
Power Spectral Density	$\pm 0.4\text{dB}$
Conducted Band Edges Measurement	$\pm 2.7\text{dB}$
Conducted Spurious Emissions	$\pm 2.7\text{dB}$

Remark:

The U_{lab} (lab Uncertainty) is less than $U_{\text{CISPR/ETSI}}$ (CISPR/ETSI Uncertainty), so the test results

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR260100021302

Page: 8 of 125

4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

• VCCI (Member No. 1937)

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen EMC laboratory have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

• FCC –Designation Number: CN1336

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1336. Test Firm Registration Number: 787754.

• Innovation, Science and Economic Development Canada

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.

4.6 Deviation from Standards

None

4.7 Abnormalities from Standard Conditions

None



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch EMC Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

5 Equipment List

Radiated Emissions which fall in the restricted bands					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Signal & Spectrum Analyzer	Rohde & Schwarz	FSV	SZ-WRG-M-048	2025-12-16	2026-12-15
Low Noise Amplifier 30M-8GHz	Tonscend	TAP30M8G30	SZ-WRG-M-050	2025-12-16	2026-12-15
Double Ridge Horn Antenna 1GHz-18GHz	SCHWARZBECK	BBHA 9120 D	SZ-WRG-M-055	2025-12-13	2026-12-12
RSE Test Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Chamber	CRTSGSSAC966	N/A	SZ-WRG-C-063	2025-01-06	2028-01-05
Humidity and Temperature Indicator	deli	8838	SEM002-46	2025-07-23	2026-07-22
Coaxial Cable	SGS	N/A	SEM039-01	2025-07-05	2026-07-04

Radiated Spurious Emissions Below 30MHz					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
10m Semi-Anechoic Chamber	SAEMC	FSAC1018	SEM001-03	2025-03-21 2026-03-21	2026-03-20 2027-03-20
MXE EMI receiver	KEYSIGHT	N9038A	SEM004-16	2025-07-25	2026-07-24
Trilog-Broadband Antenna	Schwarzbeck	VULB9168	SEM003-18	2025-08-29	2027-08-28
Pre-amplifier	Sonoma Instrument Co	310N	SEM005-04	2026-02-02	2027-02-01
Loop Antenna	ETS-Lindgren	6502	SEM003-08	2025-11-17	2027-11-16
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM029-01	2025-07-05	2026-07-04

Radiated Spurious Emissions 30MHz-1GHz					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Loop Antenna	ETS-Lindgren	6502	SEM003-08	2025-11-17	2027-11-16
3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEM001-01	2023-06-19	2026-06-18
MXE EMI Receiver	Agilent Technologies	N9038A	SEM004-15	2025-07-25	2026-07-24
BiConiLog Antenna	ETS-LINDGREN	3142C	SEM003-01	2025-08-29	2027-08-28
Pre-Amplifier	Agilent Technologies	8447D	SEM005-01	2026-02-02	2027-02-01
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM025-01	2025-07-05	2026-07-04



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR260100021302

Page: 10 of 125

Radiated Spurious Emissions Above 1GHz					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Signal & Spectrum Analyzer	Rohde & Schwarz	FSV	SZ-WRG-M-048	2025-12-16	2026-12-15
Low Noise Amplifier 1G-18GHz	Tonscend	TAP01018050	SZ-WRG-M-051	2025-12-16	2026-12-15
Low Noise Amplifier 18G-40GHz	Tonscend	TAP18040048	SZ-WRG-M-052	2025-12-16	2026-12-15
Double Ridge Horn Antenna 1GHz-18GHz	SCHWARZBECK	BBHA 9120 D	SZ-WRG-M-055	2025-12-13	2026-12-12
SHF-EHF Horn 15GHz-40GHz	SCHWARZBECK	BBHA 9170	SZ-WRG-M-056	2025-12-13	2026-12-12
RSE Test Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Chamber	CRTSGSSAC966	N/A	SZ-WRG-C-063	2025-01-06	2028-01-05
Humidity and Temperature Indicator	deli	8838	SEM002-46	2025-07-23	2026-07-22
Coaxial Cable	SGS	N/A	SEM039-01	2025-07-05	2026-07-04

RF Conducted Test					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Power Sensor	TST PASS	TSPS2023R	SEM009-26	2026-02-04	2027-02-03
Power Sensor	KEYSIGHT	U2021XA	SEM009-16	2026-02-04	2027-02-03
DC Power Supply	Chroma	62012P-80-60	SEM011-11	2025-07-24	2026-07-23
MXA Signal Analyzer	KEYSIGHT	N9020A	SEM004-19	2026-02-03	2027-02-02
Measurement Software	TST PASS	TST PASS V2.0	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-01	2025-07-05	2026-07-04
Attenuator	Huber+Suhner	6620_SMA-50-1	SEM021-09	2026-02-02	2027-02-01

General used equipment					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Humidity/ Temperature Indicator	deli	8838	SEM002-32	2025-07-23	2026-07-22
Humidity/ Temperature Indicator	deli	8838	SEM002-33	2025-07-23	2026-07-22
Barometer	Changchun Meteorological Industry Factory	DYM3	SEM002-01	2026-02-14	2027-02-13



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch Testing and Calibration Laboratory
 No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)

6.1.2 Conclusion

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement.

Antenna location: Refer to internal photo.



7 Radio Spectrum Matter Test Results

7.1 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209
 Test Method: ANSI C63.10 (2020) Section 6.10.5 & 11.12
 Measurement Distance: 3m
 Test Engineer: Xing Guo

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.1.1 E.U.T. Operation


Operating Environment:
 Temperature: 24.5 °C Humidity: 50.8 % RH Atmospheric Pressure: 1020 mbar

7.1.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20)/ax(HEW20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40)/ax(HEW40), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.



7.1.3 Test Setup Diagram



7.1.4 Measurement Procedure and Data


- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor

Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.




11b_TX_CH_01_Horizontal-Peak



Condition: 3m HORIZONTAL
Job No : 00213AT
Mode : 2412 Band edge
: 2.4G Wi-Fi 11b

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1	2375.612	6.82	27.65	30.60	48.43	52.30	74.00	-21.70	Peak	0.00
2	2390.000	6.83	27.68	30.60	46.89	50.08	74.00	-23.20	Peak	0.00
3 pp	2412.000	6.91	27.72	30.60	97.86	101.89	74.00	27.89	Peak	0.00


11b_TX_CH_01_Horizontal-Avg



Condition: 3m HORIZONTAL
Job No : 00213AT
Mode : 2412 Band edge
: 2.4G Wi-Fi 11b

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1	2375.729	6.82	27.65	30.60	35.67	39.54	54.00	-14.46	Average	0.00
2	2390.000	6.83	27.68	30.60	34.58	38.49	54.00	-15.51	Average	0.00
3 pp	2412.000	6.91	27.72	30.60	94.77	98.80	54.00	44.80	Average	0.00


11b_TX_CH_01_Vertical-Peak



Condition: 3m VERTICAL
Job No : 00213AT
Mode : 2412 Band edge
: 2.4G Wi-Fi 11b

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1	2375.869	6.81	27.62	30.60	47.84	51.67	74.00	-22.33	Peak	0.00
2	2390.000	6.83	27.68	30.60	46.20	50.11	74.00	-23.89	Peak	0.00
3 pp	2412.000	6.91	27.72	30.60	94.96	98.99	74.00	24.99	Peak	0.00

11b_TX_CH_01_Vertical-Avg




Condition: 3m VERTICAL
Job No : 00213AT
Mode : 2412 Band edge
: 2.4G Wi-Fi 11b

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1	2375.608	6.82	27.65	30.60	33.99	37.86	54.00	-16.14	Average	0.00
2	2390.000	6.83	27.68	30.60	33.34	37.25	54.00	-16.75	Average	0.00
3 pp	2412.000	6.91	27.72	30.60	91.72	95.75	54.00	41.75	Average	0.00



11b_TX_CH_11_Horizontal-Peak



Condition: 3m HORIZONTAL


Job No : 00213AT

Mode : 2462 Band edge

: 2.4G Wi-Fi 11b

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1	pp 2462.000	7.25	27.85	30.60	95.10	99.60	74.00	25.60	Peak	0.00
2	2483.500	7.40	27.93	30.60	47.47	52.20	74.00	-21.80	Peak	0.00
3	2487.305	7.43	27.95	30.60	48.15	52.93	74.00	-21.07	Peak	0.00

11b_TX_CH_11_Horizontal-Avg



Condition: 3m HORIZONTAL


Job No : 00213AT

Mode : 2462 Band edge

: 2.4G Wi-Fi 11b

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1	pp 2462.000	7.25	27.85	30.60	91.94	96.44	54.00	42.44	Average	0.00
2	2483.500	7.40	27.93	30.60	34.19	38.92	54.00	-15.08	Average	0.00
3	2483.990	7.40	27.94	30.60	34.37	39.11	54.00	-14.89	Average	0.00

11b_TX_CH_11_Vertical-Peak



Condition: 3m VERTICAL


Job No : 00213AT

Mode : 2462 Band edge

: 2.4G Wi-Fi 11b

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1	pp 2462.000	7.25	27.85	30.60	94.91	99.41	74.00	25.41	Peak	0.00
2	2483.500	7.40	27.93	30.60	46.26	50.99	74.00	-23.01	Peak	0.00
3	2487.305	7.43	27.95	30.60	47.49	52.27	74.00	-21.73	Peak	0.00

11b_TX_CH_11_Vertical-Avg



Condition: 3m VERTICAL

Job No : 00213AT


Mode : 2462 Band edge

: 2.4G Wi-Fi 11b

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1	pp 2462.000	7.25	27.85	30.60	91.49	95.99	54.00	41.99	Average	0.00
2	2483.500	7.40	27.93	30.60	33.04	37.77	54.00	-16.23	Average	0.00
3	2483.940	7.40	27.94	30.60	33.12	37.86	54.00	-16.14	Average	0.00




11g_TX_CH_01_Horizontal-Peak



Condition: 3m HORIZONTAL
Job No : 00213AT
Mode : 2412 Band edge
: 2.4G Wi-Fi 11g

	Freq	Cable Loss	Factor	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB		dB
1	2325.494	6.79	27.68	30.60	65.77	69.56	74.00	-4.44	Peak		0.00
2	2390.000	6.83	27.68	30.60	63.64	67.55	74.00	-6.45	Peak		0.00
3 pp	2412.000	6.91	27.72	30.60	105.16	109.19	74.00	35.19	Peak		0.00


11g_TX_CH_01_Horizontal-Avg



Condition: 3m HORIZONTAL
Job No : 00213AT
Mode : 2412 Band edge
: 2.4G Wi-Fi 11g

	Freq	Cable Loss	Factor	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB		dB
1	2389.968	6.83	27.68	30.60	44.40	48.31	54.00	-5.69	Average		0.00
2	2390.000	6.83	27.68	30.60	44.40	48.31	54.00	-5.69	Average		0.00
3 pp	2412.000	6.91	27.72	30.60	94.30	98.33	54.00	44.33	Average		0.00


11g_TX_CH_01_Vertical-Peak



Condition: 3m VERTICAL
Job No : 00213AT
Mode : 2412 Band edge
: 2.4G Wi-Fi 11g

	Freq	Cable Loss	Factor	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB		dB
1	2389.968	6.83	27.68	30.60	64.07	67.98	74.00	-6.02	Peak		0.00
2	2390.000	6.83	27.68	30.60	64.07	67.98	74.00	-6.02	Peak		0.00
3 pp	2412.000	6.91	27.72	30.60	102.10	106.13	74.00	32.13	Peak		0.00

11g_TX_CH_01_Vertical-Avg




Condition: 3m VERTICAL
Job No : 00213AT
Mode : 2412 Band edge
: 2.4G Wi-Fi 11g

	Freq	Cable Loss	Factor	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB		dB
1	2389.968	6.83	27.68	30.60	41.72	45.63	54.00	-8.37	Average		0.00
2	2390.000	6.83	27.68	30.60	41.72	45.63	54.00	-8.37	Average		0.00
3 pp	2412.000	6.91	27.72	30.60	91.77	95.80	54.00	41.80	Average		0.00




11g_TX_CH_11_Horizontal-Peak



Condition: 3m HORIZONTAL
Job No : 00213AT
Mode : 2462 Band edge
: 2.4G Wi-Fi 11g

	Freq	Cable Loss	Factor	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
	MHz	dB	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1	pp 2462.000	7.25	27.85	30.60	101.48	105.98	74.00	31.98	Peak		0.00
2	2483.500	7.40	27.93	30.60	59.59	64.32	74.00	-9.68	Peak		0.00
3	2483.790	7.40	27.94	30.60	60.67	65.41	74.00	-8.59	Peak		0.00


11g_TX_CH_11_Horizontal-Avg



Condition: 3m HORIZONTAL
Job No : 00213AT
Mode : 2462 Band edge
: 2.4G Wi-Fi 11g

	Freq	Cable Loss	Factor	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
	MHz	dB	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1	pp 2462.000	7.25	27.85	30.60	90.77	95.27	54.00	41.27	Average		0.00
2	2483.500	7.40	27.93	30.60	39.73	44.46	54.00	-9.54	Average		0.00
3	2483.890	7.40	27.94	30.60	39.43	44.17	54.00	-9.83	Average		0.00


11g_TX_CH_11_Vertical-Peak



Condition: 3m VERTICAL
Job No : 00213AT
Mode : 2462 Band edge
: 2.4G Wi-Fi 11g

	Freq	Cable Loss	Factor	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
	MHz	dB	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1	pp 2462.000	7.25	27.85	30.60	100.80	105.30	74.00	31.30	Peak		0.00
2	2483.500	7.40	27.93	30.60	58.86	63.59	74.00	-10.41	Peak		0.00
3	2483.840	7.40	27.94	30.60	58.54	63.28	74.00	-10.72	Peak		0.00

11g_TX_CH_11_Vertical-Avg



Condition: 3m VERTICAL
Job No : 00213AT
Mode : 2462 Band edge
: 2.4G Wi-Fi 11g


	Freq	Cable Loss	Factor	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
	MHz	dB	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1	pp 2462.000	7.25	27.85	30.60	90.18	94.68	54.00	40.68	Average		0.00
2	2483.500	7.40	27.93	30.60	37.95	42.68	54.00	-11.32	Average		0.00
3	2483.790	7.40	27.94	30.60	37.54	42.28	54.00	-11.72	Average		0.00



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

11n_HT(20M)_TX_CH_01_Horizontal-Peak



Condition: 3m HORIZONTAL


Job No : 00213AT

Mode : 2412 Band edge

: 2.4G Wi-Fi 11n20

	Freq	Cable Loss	Factor	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB		dB
1	2389.484	6.82	27.68	30.60	66.56	70.46	74.00	-3.54	Peak		0.00
2	2390.000	6.83	27.68	30.60	62.05	65.96	74.00	-8.04	Peak		0.00
3 pp	2412.000	6.91	27.72	30.60	103.09	107.12	74.00	33.12	Peak		0.00

11n_HT(20M)_TX_CH_01_Horizontal-Avg



Condition: 3m HORIZONTAL


Job No : 00213AT

Mode : 2412 Band edge

: 2.4G Wi-Fi 11n20

	Freq	Cable Loss	Factor	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB		dB
1	2389.968	6.83	27.68	30.60	43.01	46.92	54.00	-7.08	Average		0.00
2	2390.000	6.83	27.68	30.60	43.01	46.92	54.00	-7.08	Average		0.00
3 pp	2412.000	6.91	27.72	30.60	92.40	96.43	54.00	42.43	Average		0.00

11n_HT(20M)_TX_CH_01_Vertical-Peak



Condition: 3m VERTICAL


Job No : 00213AT

Mode : 2412 Band edge

: 2.4G Wi-Fi 11n20

	Freq	Cable Loss	Factor	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB		dB
1	2389.363	6.82	27.68	30.60	60.80	64.70	74.00	-9.30	Peak		0.00
2	2390.000	6.83	27.68	30.60	60.03	63.94	74.00	-10.06	Peak		0.00
3 pp	2412.000	6.91	27.72	30.60	100.32	104.35	74.00	30.35	Peak		0.00

11n_HT(20M)_TX_CH_01_Vertical-Avg



Condition: 3m VERTICAL


Job No : 00213AT

Mode : 2412 Band edge


: 2.4G Wi-Fi 11n20

	Freq	Cable Loss	Factor	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB		dB
1	2389.968	6.83	27.68	30.60	40.32	44.23	54.00	-9.77	Average		0.00
2	2390.000	6.83	27.68	30.60	40.32	44.23	54.00	-9.77	Average		0.00
3 pp	2412.000	6.91	27.72	30.60	89.81	93.84	54.00	39.84	Average		0.00






11n_HT(40M)_TX_CH_03_Horizontal-Peak



Condition: 3m HORIZONTAL
Job No : 00213AT
Mode : 2422 Band edge
: 2.4G Wi-Fi 11n40

	Freq	Cable Loss	Factor	Ant Factor	Preamp	Read Level	Level	Limit	Over	Remark	Aux Factor
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB		dB
1	2389.526	6.82	27.68	30.60	65.93	69.83	74.00	-4.17	Peak		0.00
2	2390.000	6.83	27.68	30.60	65.66	69.57	74.00	-4.43	Peak		0.00
3 pp	2422.000	6.98	27.74	30.60	100.60	104.00	74.00	30.00	Peak		0.00


11n_HT(40M)_TX_CH_03_Horizontal-Avg



Condition: 3m HORIZONTAL
Job No : 00213AT
Mode : 2422 Band edge
: 2.4G Wi-Fi 11n40

	Freq	Cable Loss	Factor	Ant Factor	Preamp	Read Level	Level	Limit	Over	Remark	Aux Factor
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB		dB
1	2389.677	6.82	27.68	30.60	45.44	49.34	54.00	-4.66	Average		0.00
2	2390.000	6.83	27.68	30.60	45.77	49.68	54.00	-4.32	Average		0.00
3 pp	2422.000	6.98	27.74	30.60	88.94	93.06	54.00	39.06	Average		0.00


11n_HT(40M)_TX_CH_03_Vertical-Peak



Condition: 3m VERTICAL
Job No : 00213AT
Mode : 2422 Band edge
: 2.4G Wi-Fi 11n40

	Freq	Cable Loss	Factor	Ant Factor	Preamp	Read Level	Level	Limit	Over	Remark	Aux Factor
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB		dB
1	2389.827	6.83	27.68	30.60	63.05	66.96	74.00	-7.04	Peak		0.00
2	2390.000	6.83	27.68	30.60	62.59	66.50	74.00	-7.50	Peak		0.00
3 pp	2422.000	6.98	27.74	30.60	97.50	101.62	74.00	27.62	Peak		0.00


11n_HT(40M)_TX_CH_03_Vertical-Avg




Condition: 3m VERTICAL
Job No : 00213AT
Mode : 2422 Band edge
: 2.4G Wi-Fi 11n40

	Freq	Cable Loss	Factor	Ant Factor	Preamp	Read Level	Level	Limit	Over	Remark	Aux Factor
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB		dB
1	2389.677	6.82	27.68	30.60	42.81	46.71	54.00	-7.29	Average		0.00
2	2390.000	6.83	27.68	30.60	42.04	46.75	54.00	-7.25	Average		0.00
3 pp	2422.000	6.98	27.74	30.60	86.17	90.29	54.00	36.29	Average		0.00





11ax_20M_TX_CH_01_Horizontal-Peak



Condition: 3m HORIZONTAL


Job No : 00213AT

Mode : 2412 Band edge

: 2.4G Wi-Fi 11ax20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Aux
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB
1	2389.605	6.82	27.68	30.60	65.33	69.23	74.00	-4.77 Peak	0.00
2	2390.000	6.83	27.68	30.60	64.38	68.29	74.00	-5.71 Peak	0.00
3 pp	2412.000	6.91	27.72	30.60	104.35	108.38	74.00	34.38 Peak	0.00

11ax_20M_TX_CH_01_Horizontal-Avg



Condition: 3m HORIZONTAL


Job No : 00213AT

Mode : 2412 Band edge

: 2.4G Wi-Fi 11ax20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Aux
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB
1	2389.968	6.83	27.68	30.60	41.40	45.31	54.00	-8.69 Average	0.00
2	2390.000	6.83	27.68	30.60	41.40	45.31	54.00	-8.69 Average	0.00
3 pp	2412.000	6.91	27.72	30.60	90.53	94.56	54.00	40.56 Average	0.00

11ax_20M_TX_CH_01_Vertical-Peak



Condition: 3m VERTICAL


Job No : 00213AT

Mode : 2412 Band edge

: 2.4G Wi-Fi 11ax20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Aux
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB
1	2389.968	6.83	27.68	30.60	63.44	67.35	74.00	-6.65 Peak	0.00
2	2390.000	6.83	27.68	30.60	63.44	67.35	74.00	-6.65 Peak	0.00
3 pp	2412.000	6.91	27.72	30.60	104.12	108.15	74.00	34.15 Peak	0.00

11ax_20M_TX_CH_01_Vertical-Avg



Condition: 3m VERTICAL

Job No : 00213AT


Mode : 2412 Band edge

: 2.4G Wi-Fi 11ax20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Aux
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB
1	2389.968	6.83	27.68	30.60	40.44	44.35	54.00	-9.65 Average	0.00
2	2390.000	6.83	27.68	30.60	40.44	44.35	54.00	-9.65 Average	0.00
3 pp	2412.000	6.91	27.72	30.60	90.25	94.28	54.00	40.28 Average	0.00




11ax_20M_TX_CH_11_Horizontal-Peak



Condition: 3m HORIZONTAL
Job No : 00213AT
Mode : 2462 Band edge
: 2.4G Wi-Fi 11ax20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Aux
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	Factor
1	pp 2462.000	7.25	27.85	30.60	101.50	104.14	74.00	32.00	Peak 0.00
2	2483.500	7.40	27.93	30.60	57.34	62.07	74.00	-11.93	Peak 0.00
3	2484.241	7.40	27.94	30.60	58.18	62.92	74.00	-11.08	Peak 0.00


11ax_20M_TX_CH_11_Horizontal-Avg



Condition: 3m HORIZONTAL
Job No : 00213AT
Mode : 2462 Band edge
: 2.4G Wi-Fi 11ax20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Aux
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	Factor
1	pp 2462.000	7.25	27.85	30.60	87.56	92.06	54.00	38.06	Average 0.00
2	2483.500	7.40	27.93	30.60	36.68	41.41	54.00	-12.59	Average 0.00
3	2483.990	7.40	27.94	30.60	36.59	41.33	54.00	-12.67	Average 0.00


11ax_20M_TX_CH_11_Vertical-Peak



Condition: 3m VERTICAL
Job No : 00213AT
Mode : 2462 Band edge
: 2.4G Wi-Fi 11ax20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Aux
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	Factor
1	pp 2462.000	7.25	27.85	30.60	99.64	104.14	74.00	30.14	Peak 0.00
2	2483.500	7.40	27.93	30.60	55.17	59.90	74.00	-14.10	Peak 0.00
3	2484.392	7.41	27.94	30.60	55.61	60.36	74.00	-13.64	Peak 0.00

11ax_20M_TX_CH_11_Vertical-Avg




Condition: 3m VERTICAL
Job No : 00213AT
Mode : 2462 Band edge
: 2.4G Wi-Fi 11ax20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Aux
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	Factor
1	pp 2462.000	7.25	27.85	30.60	85.56	90.06	54.00	36.06	Average 0.00
2	2483.500	7.40	27.93	30.60	35.25	39.98	54.00	-14.02	Average 0.00
3	2483.790	7.40	27.94	30.60	35.48	40.22	54.00	-13.78	Average 0.00




11ax_40M_TX_CH_03_Horizontal-Peak



Condition: 3m HORIZONTAL
Job No : 00213AT
Mode : 2422 Band edge
: 2.4G Wi-Fi 11ax40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark	Aux Factor
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1	2389.827	6.83	27.68	30.60	65.39	69.30	74.00	-4.70	Peak	0.00
2	2390.000	6.83	27.68	30.60	65.23	69.14	74.00	-4.86	Peak	0.00
3	2422.000	6.98	27.74	30.60	101.13	105.25	74.00	31.25	Peak	0.00


11ax_40M_TX_CH_03_Horizontal-Avg



Condition: 3m HORIZONTAL
Job No : 00213AT
Mode : 2422 Band edge
: 2.4G Wi-Fi 11ax40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark	Aux Factor
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1	2389.827	6.83	27.68	30.60	45.72	49.63	54.00	-4.37	Average	0.00
2	2390.000	6.83	27.68	30.60	45.38	49.29	54.00	-4.71	Average	0.00
3	2422.000	6.98	27.74	30.60	86.61	90.73	54.00	36.73	Average	0.00


11ax_40M_TX_CH_03_Vertical-Peak



Condition: 3m VERTICAL
Job No : 00213AT
Mode : 2422 Band edge
: 2.4G Wi-Fi 11ax40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark	Aux Factor
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1	2389.827	6.83	27.68	30.60	62.28	66.19	74.00	-7.81	Peak	0.00
2	2390.000	6.83	27.68	30.60	62.08	65.99	74.00	-8.01	Peak	0.00
3	2422.000	6.98	27.74	30.60	101.04	105.16	74.00	31.16	Peak	0.00

11ax_40M_TX_CH_03_Vertical-Avg




Condition: 3m VERTICAL
Job No : 00213AT
Mode : 2422 Band edge
: 2.4G Wi-Fi 11ax40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark	Aux Factor
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1	2389.827	6.83	27.68	30.60	43.13	47.04	54.00	-6.96	Average	0.00
2	2390.000	6.83	27.68	30.60	42.91	46.82	54.00	-7.18	Average	0.00
3	2422.000	6.98	27.74	30.60	86.75	90.87	54.00	36.87	Average	0.00



11ax_40M_TX_CH_09_Horizontal-Peak



Condition: 3m HORIZONTAL


Job No : 00213AT

Mode : 2452 Band edge

: 2.4G Wi-Fi 11ax40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1	pp 2452.000	7.19	27.81	30.60	98.82	104.19	74.00	29.22	Peak	0.00
2	2483.500	7.40	27.93	30.60	58.70	63.43	74.00	-10.57	Peak	0.00
3	2485.276	7.41	27.94	30.60	60.06	64.81	74.00	-9.19	Peak	0.00

11ax_40M_TX_CH_09_Horizontal-Avg



Condition: 3m HORIZONTAL


Job No : 00213AT

Mode : 2452 Band edge

: 2.4G Wi-Fi 11ax40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1	pp 2452.000	7.19	27.81	30.60	85.50	89.90	54.00	35.90	Average	0.00
2	2483.500	7.40	27.93	30.60	39.66	44.39	54.00	-9.61	Average	0.00
3	2484.147	7.40	27.94	30.60	39.73	44.47	54.00	-9.53	Average	0.00

11ax_40M_TX_CH_09_Vertical-Peak



Condition: 3m VERTICAL


Job No : 00213AT

Mode : 2452 Band edge

: 2.4G Wi-Fi 11ax40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1	pp 2452.000	7.19	27.81	30.60	99.79	104.19	74.00	30.19	Peak	0.00
2	2483.500	7.40	27.93	30.60	56.26	60.99	74.00	-13.01	Peak	0.00
3	2484.006	7.40	27.94	30.60	56.90	61.64	74.00	-12.36	Peak	0.00

11ax_40M_TX_CH_09_Vertical-Avg



Condition: 3m VERTICAL

Job No : 00213AT

Mode : 2452 Band edge

: 2.4G Wi-Fi 11ax40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1	pp 2452.000	7.19	27.81	30.60	85.40	89.80	54.00	35.80	Average	0.00
2	2483.500	7.40	27.93	30.60	38.37	43.10	54.00	-10.90	Average	0.00
3	2483.935	7.40	27.94	30.60	38.06	42.80	54.00	-11.20	Average	0.00



7.2 Radiated Spurious Emissions Below 1GHz

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209
 Test Method: ANSI C63.10 (2020) Section 6.4,6.5
 Measurement Distance: 3m
 Test Engineer: Kaito Zeng

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
960-1000	500	3

Note

1: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

2. At frequencies below 1GHz, measurements may be performed at a distance different to specified in the regulations.

Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor+ Aux Factor (if applicable)

The aux factor needs to be added when measurements are performed at a distance other than the limit distance provided.

EX. Below 30MHz, Aux Factor = 40 dB/decade of distance, the aux factor is $40\log(3/300) = -80\text{dB}$ (for 3m test distance).

EX. Above 30MHz, Aux Factor = 20 dB/decade of distance, the aux factor is $20\log(10/3) = 10.46\text{dB}$ (for 10m test distance).

7.2.1 E.U.T. Operation

Operating Environment:

Temperature: 23.5 °C Humidity: 46.8 % RH Atmospheric Pressure: 1010 mbar



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


SGS-CSTC Standards Technical Services Co., Ltd.
 Shenzhen Branch Inspection & Testing Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

7.2.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20)/ax(HEW20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40)/ax(HEW40), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.

7.2.3 Test Setup Diagram



7.2.4 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8m above the ground at a semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3m or 10m away from the interference-receiving antenna, which was mounted on the variable-height antenna tower.
- c. The antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1m to 4m (for the test frequency of below 30MHz, the antenna was tuned to heights 1m) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using quasi-peak method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:

1. Scan from 9kHz to 30MHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only below points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
2. The disturbance below 1GHz was very low and the harmonics were the highest point could be found when testing, so only the worst-case test curve is displayed.




SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR260100021302

Page: 30 of 125

Test Mode: 00; Polarity: Coaxial



Condition: 3m

Job No. : 00213AT

Test Mode: 00

: coaxial




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Inspection & Testing Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Test Mode: 00; Polarity: Coaxial



Condition: 3m


Job No. : 00213AT

Test Mode: 00

: coaxial



Test Mode: 00; Polarity: Coplanar



Condition: 3m


Job No. : 00213AT

Test Mode: 00

: coplanar



Test Mode: 00; Polarity: Coplanar



Condition: 3m


Job No. : 00213AT

Test Mode: 00

: coplanar



Test Mode: 00; Polarity: Horizontal




Site : chamber
Condition: 3m HORIZONTAL
Job No. : 00213AT
Test Mode: 00

	Ant	Cable	Preamp	Read		Limit	Over	
Freq	Factor	Loss	Factor	Level	Level	Line	Limit	Remark
MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB	
1	30.000	21.45	0.74	27.65	25.28	19.82	40.00	-20.18 QP
2	56.991	11.73	0.91	27.62	29.71	14.73	40.00	-25.27 QP
3	191.745	14.19	1.67	27.79	39.26	27.33	43.50	-16.17 QP
4	392.095	20.40	2.46	27.73	26.70	21.83	46.00	-24.17 QP
5	684.745	25.66	3.37	27.87	25.78	26.94	46.00	-19.06 QP
6 q	942.131	29.01	4.06	26.72	25.11	31.46	46.00	-14.54 QP



Test Mode: 00; Polarity: Vertical



Site : chamber
Condition: 3m VERTICAL
Job No. : 00213AT
Test Mode: 00

		Ant	Cable	Preamp	Read		Limit	Over	
	Freq	Factor	Loss	Factor	Level	Level	Line	Limit	Remark
	MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB	
1	44.275	14.59	0.86	27.64	37.48	25.29	40.00	-14.71	QP
2	89.905	11.79	1.18	27.60	48.24	33.61	43.50	-9.89	QP
3 q	124.133	11.40	1.37	27.66	51.06	36.17	43.50	-7.33	QP
4	227.691	16.33	1.83	27.70	36.03	26.49	46.00	-19.51	QP
5	699.305	25.89	3.41	27.83	26.08	27.55	46.00	-18.45	QP
6	906.482	28.65	3.99	26.93	25.84	31.55	46.00	-14.45	QP



7.3 Radiated Spurious Emissions Above 1GHz

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209
 Test Method: ANSI C63.10 (2020) Section 6.6 & 11.12
 Measurement Distance: 1-18GHz: 3m; Above 18GHz: 1m
 Test Engineer: Xing Guo

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
Above 1000	500	3

Note:

At Above 18GHz, measurements may be performed at a distance shorter than that specified in the regulations

Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor+ Aux Factor (if applicable)

The aux factor needs to be added when measurements are performed at a distance other than the limit distance provided.

EX. Above 18GHz, Aux Factor = 20 dB/decade of distance, the aux factor is $20\log(1/3) = -9.54\text{dB}$ (for 1m test distance).

7.3.1 E.U.T. Operation

Operating Environment:


Temperature: 24.5 °C Humidity: 50.8 % RH Atmospheric Pressure: 1020 mbar

7.3.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20)/ax(HEW20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40)/ax(HEW40), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.



7.3.3 Test Setup Diagram



Above 1GHz



7.3.4 Measurement Procedure and Data


- a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5m above the ground at a 3m fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. The EUT was set 3m away from the interference-receiving antenna from 1GHz to 18GHz, and 1m away from the interference-receiving antenna above 18GHz.
- b. The interference-receiving antenna was mounted on the variable-height antenna tower, with its boresight facing the EUT throughout the test.
- c. The antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1m to 4m and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- g. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- h. Repeat above procedures until all frequencies measured was complete.

Remark:

1. Scan from 1GHz to 10th harmonic of the highest frequency or 40 GHz, whichever is lower.
2. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.
3. For the frequency above 18GHz, testing had been executed under all test modes, only the worst-case test curve is displayed in the report.
4. For devices with multiple operating modes, measurements on the middle channel is used to determine the worst-case mode(s). Only the worst-case mode with the highest output power and the mode with the highest output power spectral density for each modulation family (e.g., OFDM and direct sequence spread spectrum) is recorded in the test report.




11b_TX_CH_01_Horizontal



Condition: 3m HORIZONTAL
Job No : 00213AT
Mode : 2412 TX RSE
: 2.4G Wi-Fi 11b

2.46 MHz 11b										
	Freq	Loss	Cable	Ant	Preamp	Read	Level	Limit	Over	Aux
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB	dB
1	pp	4818.016	8.92	32.67	55.93	67.33	52.99	74.00	-21.01	Peak 0.00
2	pk	7876.516	11.18	36.56	56.45	53.13	44.42	74.00	-29.58	Peak 0.00
3		9613.430	12.40	38.75	54.01	51.37	48.51	74.00	-25.49	Peak 0.00
4		13404.010	15.67	40.50	53.92	48.05	50.30	74.00	-23.70	Peak 0.00
5		16891.040	19.64	38.60	53.88	46.06	50.42	74.00	-23.58	Peak 0.00
6		18000.000	18.64	42.60	54.38	45.38	52.24	74.00	-21.76	Peak 0.00


11b_TX_CH_01_Vertical



Condition: 3m VERTICAL
Job No : 00213AT
Mode : 2412 TX RSE
: 2.4G Wi-Fi 11b

2.46 MHz L-11b											Aux
Cable	Loss	Ant	Preamp	Read	Level	Limit	Over	Remark		Factor	
MHz	dB	dB/m		dBuV	dBuV/m	dBuV/m					
1	pk	4818.016	8.92	32.67	55.93	66.50	52.16	54.00	-1.84 Average	0.00	
2	pk	4818.016	8.92	32.67	55.93	69.35	55.01	74.00	-18.99 Peak	0.00	
3		5269.649	9.31	33.16	56.24	60.11	46.34	74.00	-27.66 Peak	0.00	
4		8969.161	12.15	38.46	54.73	53.08	48.96	74.00	-25.04 Peak	0.00	
5		11940.540	14.52	39.12	53.22	49.47	49.89	74.00	-24.11 Peak	0.00	
6		13326.750	15.92	40.28	53.90	48.51	50.81	74.00	-23.19 Peak	0.00	
7		17896.250	18.87	41.97	54.26	46.10	52.68	74.00	-21.32 Peak	0.00	


11b_TX_CH_06_Horizontal



Condition: 3m HORIZONTAL
Job No : 00213AT
Mode : 2437 TX RSE
: 2.4G Wi-Fi 11b

: 2.46 MHz 11th										
Cable	Freq	Loss	Ant	Preamp	Read	Level	Limit	Over	Remark	Aux
	MHz	dB	dB/m	Factor	Level	dBuV	dBuV/m	dBuV/m	dB	Factor
1	pp	4874.043	8.97	32.85	55.99	68.04	53.87	74.00	-20.13 Peak	0.00
2		8814.957	12.36	38.33	54.91	51.87	47.65	74.00	-26.35 Peak	0.00
3		11335.190	14.29	39.36	53.40	49.37	49.62	74.00	-24.38 Peak	0.00
4		13797.090	15.61	40.30	54.04	49.33	51.20	74.00	-22.80 Peak	0.00
5		15134.000	16.85	39.37	54.04	48.06	50.24	74.00	-23.76 Peak	0.00
6		17948.050	18.75	42.29	54.28	46.39	53.15	74.00	-20.85 Peak	0.00

11b_TX_CH_06_Vertical




Condition: 3m VERTICAL
Job No : 00213AT
Mode : 2437 TX RSE
: 2.4G Wi-Fi 11b

: 2.46 MHz W-Fi 11b										
	Freq	Cable	Ant	Preamp	Read	Level	Limit	Over	Limit	Aux
	MHz	Loss	Factor	Factor	Level	dBuV/m	Line	Limit	Remark	Factor
		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1	pp	4874.043	8.97	32.85	55.99	66.76	52.59	54.00	-1.41 Average	0.00
2	pk	4874.043	8.97	32.85	55.99	69.54	55.37	74.00	-18.63 Peak	0.00
3		5269.649	9.31	33.16	56.24	59.66	45.89	74.00	-28.11 Peak	0.00
4		8814.957	12.36	38.33	54.91	52.35	48.13	74.00	-25.87 Peak	0.00
5		11735.250	14.46	39.10	53.28	49.40	49.68	74.00	-24.32 Peak	0.00
6		13997.930	16.53	40.59	54.10	48.13	51.15	74.00	-22.85 Peak	0.00
7		17948.050	18.75	42.29	54.28	46.53	53.29	74.00	-20.71 Peak	0.00




11b_TX_CH_11_Horizontal



Condition: 3m HORIZONTAL
Job No : 00213AT
Mode : 2462 TX RSE
: 2.4G Wi-Fi 11b

Freq	Cable	Ant	Preamp	Read	Limit	Over	Aux
MHz	Loss	Factor	Factor	Level	Line	Limit	Factor
dB	dB/m	dB	dB	dBuV	dBuV/m	dB	dB
1 pp 4916.490	9.02	32.97	56.02	64.58	50.55	54.00	-3.45 Average 0.00
2 pk 4916.490	9.02	32.97	56.02	68.19	54.16	74.00	-19.84 Peak 0.00
3 8789.516	12.33	38.30	54.94	52.29	47.98	74.00	-26.02 Peak 0.00
4 12290.700	14.68	39.40	53.38	49.22	49.92	74.00	-24.08 Peak 0.00
5 14242.800	16.83	40.46	54.10	47.72	50.91	74.00	-23.09 Peak 0.00
6 16891.040	19.64	38.60	53.88	46.33	50.69	74.00	-23.31 Peak 0.00
7 18000.000	18.64	42.60	54.30	45.99	52.93	74.00	-21.07 Peak 0.00


11b_TX_CH_11_Vertical



Condition: 3m VERTICAL
Job No : 00213AT
Mode : 2462 TX RSE
: 2.4G Wi-Fi 11b

Freq	Cable	Ant	Preamp	Read	Limit	Over	Aux
MHz	Loss	Factor	Factor	Level	Line	Limit	Factor
dB	dB/m	dB	dB	dBuV	dBuV/m	dB	dB
1 pp 4916.490	9.02	32.97	56.02	66.38	52.35	54.00	-1.65 Average 0.00
2 pk 4916.490	9.02	32.97	56.02	69.24	55.21	74.00	-18.79 Peak 0.00
3 5269.649	9.31	33.16	56.24	59.97	46.20	74.00	-27.80 Peak 0.00
4 8891.725	12.28	38.40	54.82	52.35	48.21	74.00	-25.79 Peak 0.00
5 13211.690	15.84	40.11	53.87	48.34	50.42	74.00	-23.58 Peak 0.00
6 14168.710	16.53	40.46	54.10	47.94	50.83	74.00	-23.17 Peak 0.00
7 17948.050	18.75	42.29	54.28	46.12	52.88	74.00	-21.12 Peak 0.00


11g_TX_CH_01_Horizontal



Condition: 3m HORIZONTAL
Job No : 00213AT
Mode : 2412 TX RSE
: 2.4G Wi-Fi 11g

Freq	Cable	Ant	Preamp	Read	Limit	Over	Aux
MHz	Loss	Factor	Factor	Level	Line	Limit	Factor
dB	dB/m	dB	dB	dBuV	dBuV/m	dB	dB
1 pp 4818.016	8.92	32.67	55.93	61.54	47.20	54.00	-6.80 Average 0.00
2 pk 4818.016	8.92	32.67	55.93	76.50	62.16	74.00	-11.84 Peak 0.00
3 5780.300	10.83	33.92	56.50	58.86	46.31	74.00	-27.69 Peak 0.00
4 8713.630	12.01	38.30	55.03	53.45	48.73	74.00	-25.27 Peak 0.00
5 14575.970	16.46	40.20	54.10	48.96	51.52	74.00	-22.48 Peak 0.00
6 16891.040	19.64	38.60	53.88	46.37	50.73	74.00	-23.27 Peak 0.00
7 18000.000	18.64	42.60	54.30	46.19	53.13	74.00	-28.87 Peak 0.00

11g_TX_CH_01_Vertical




Condition: 3m VERTICAL
Job No : 00213AT
Mode : 2412 TX RSE
: 2.4G Wi-Fi 11g

Freq	Cable	Ant	Preamp	Read	Limit	Over	Aux
MHz	Loss	Factor	Factor	Level	Line	Limit	Factor
dB	dB/m	dB	dB	dBuV	dBuV/m	dB	dB
1 pp 4818.016	8.92	32.67	55.93	63.16	48.82	54.00	-5.18 Average 0.00
2 pk 4818.016	8.92	32.67	55.93	77.54	63.20	74.00	-10.80 Peak 0.00
3 5269.649	9.31	33.16	56.24	60.22	46.45	74.00	-27.55 Peak 0.00
4 5797.032	10.07	33.99	56.51	61.61	49.16	74.00	-24.84 Peak 0.00
5 7966.832	11.47	37.27	55.92	57.88	50.70	74.00	-23.30 Peak 0.00
6 10453.970	13.39	39.25	53.55	49.95	49.04	74.00	-24.96 Peak 0.00
7 14533.910	16.36	40.20	54.10	48.53	50.99	74.00	-23.81 Peak 0.00
8 17896.250	18.87	41.97	54.26	46.57	53.15	74.00	-28.85 Peak 0.00




11g_TX_CH_06_Horizontal



Condition: 3m HORIZONTAL
Job No : 00213AT
Mode : 2437 TX RSE
: 2.4G Wi-Fi 11g

Freq	Cable	Loss	Factor	Ant	Preamp	Read	Level	Limit	Over	Aux
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB	dB	dB
1 pp 4874.043	8.97	32.85	55.99	61.60	47.43	54.00	-6.57	Average	0.00	
2 pk 4874.043	8.97	32.85	55.99	76.37	62.20	74.00	-11.80	Peak	0.00	
3 5047.517	10.03	34.19	56.53	60.25	47.94	74.00	-26.06	Peak	0.00	
4 10729.400	13.53	39.33	53.53	50.19	49.52	74.00	-24.48	Peak	0.00	
5 14242.800	16.83	40.46	54.10	47.82	51.01	74.00	-22.99	Peak	0.00	
6 16891.040	19.64	38.60	53.88	46.19	50.55	74.00	-23.45	Peak	0.00	
7 18000.000	18.64	42.60	54.30	45.61	52.55	74.00	-21.45	Peak	0.00	


11g_TX_CH_06_Vertical



Condition: 3m VERTICAL
Job No : 00213AT
Mode : 2437 TX RSE
: 2.4G Wi-Fi 11g

Freq	Cable	Loss	Factor	Ant	Preamp	Read	Level	Limit	Over	Aux
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB	dB	dB
1 pp 4874.043	8.97	32.85	55.99	63.66	49.49	54.00	-4.51	Average	0.00	
2 pk 4874.043	8.97	32.85	55.99	78.47	64.30	74.00	-9.70	Peak	0.00	
3 5269.649	9.31	33.16	56.24	60.98	47.21	74.00	-26.79	Peak	0.00	
4 8891.725	12.28	38.40	54.82	52.40	48.26	74.00	-25.74	Peak	0.00	
5 11500.200	14.23	39.20	53.35	49.08	49.16	74.00	-24.84	Peak	0.00	
6 13997.930	16.53	40.59	54.10	48.53	51.55	74.00	-22.45	Peak	0.00	
7 17896.250	18.87	41.97	54.26	46.07	52.65	74.00	-21.35	Peak	0.00	


11g_TX_CH_11_Horizontal



Condition: 3m HORIZONTAL
Job No : 00213AT
Mode : 2462 TX RSE
: 2.4G Wi-Fi 11g

Freq	Cable	Loss	Factor	Ant	Preamp	Read	Level	Limit	Over	Aux
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB	dB	dB
1 pp 4916.490	9.02	32.97	56.02	60.51	46.48	54.00	-7.52	Average	0.00	
2 pk 4916.490	9.02	32.97	56.02	76.25	62.22	74.00	-11.78	Peak	0.00	
3 5915.516	9.99	34.27	56.56	61.21	48.91	74.00	-25.09	Peak	0.00	
4 11204.900	14.25	39.50	53.44	48.94	49.25	74.00	-24.75	Peak	0.00	
5 14242.800	16.83	40.46	54.10	47.20	50.39	74.00	-23.61	Peak	0.00	
6 16891.040	19.64	38.60	53.88	45.90	50.26	74.00	-23.74	Peak	0.00	
7 17948.050	18.75	42.29	54.28	46.14	52.90	74.00	-21.10	Peak	0.00	

11g_TX_CH_11_Vertical




Condition: 3m VERTICAL
Job No : 00213AT
Mode : 2462 TX RSE
: 2.4G Wi-Fi 11g

Freq	Cable	Loss	Factor	Ant	Preamp	Read	Level	Limit	Over	Aux
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB	dB	dB
1 pp 4916.490	9.02	32.97	56.02	61.77	47.74	54.00	-6.26	Average	0.00	
2 pk 4916.490	9.02	32.97	56.02	76.76	62.73	74.00	-11.27	Peak	0.00	
3 5269.649	9.31	33.16	56.24	60.22	46.45	74.00	-27.55	Peak	0.00	
4 9152.479	12.13	38.69	54.52	52.62	48.92	74.00	-25.08	Peak	0.00	
5 14242.800	16.83	40.46	54.10	47.90	51.09	74.00	-22.91	Peak	0.00	
6 16891.040	19.64	38.60	53.88	46.06	50.42	74.00	-23.58	Peak	0.00	
7 18000.000	18.64	42.60	54.30	45.63	52.57	74.00	-21.43	Peak	0.00	




11n_20M_TX_CH_01_Horizontal



Condition: 3m HORIZONTAL
Job No : 00213AT
Mode : 2412 TX RSE
: 2.4G Wi-Fi 11n20

Freq	Cable	Ant	Preamp	Read	Limit	Over	Aux
MHz	Loss	Factor	Factor	Level	Line	Limit	Factor
	dB	dB/m	dB	dBuV	dBuV/m	dB	dB
1 pp 4831.962	8.93	32.73	55.95	58.05	43.76	54.00	-10.24 Average
2 pk 4831.962	8.93	32.73	55.95	73.46	59.17	74.00	-14.83 Peak
3 8866.962	12.30	38.40	54.85	51.96	47.81	74.00	-26.19 Peak
4 11701.300	14.39	39.10	53.29	48.66	48.86	74.00	-25.14 Peak
5 14119.830	16.40	40.42	54.10	47.91	50.63	74.00	-23.37 Peak
6 16891.040	19.64	38.60	53.88	45.30	49.66	74.00	-24.34 Peak
7 17896.250	18.87	41.97	54.26	45.91	52.49	74.00	-21.51 Peak


11n_20M_TX_CH_01_Vertical



Condition: 3m VERTICAL
Job No : 00213AT
Mode : 2412 TX RSE
: 2.4G Wi-Fi 11n20

Freq	Cable	Ant	Preamp	Read	Limit	Over	Aux
MHz	Loss	Factor	Factor	Level	Line	Limit	Factor
	dB	dB/m	dB	dBuV	dBuV/m	dB	dB
1 pp 4818.016	8.92	32.67	55.93	60.40	46.06	54.00	-7.94 Average
2 pk 4818.016	8.92	32.67	55.93	75.89	61.55	74.00	-12.45 Peak
3 5269.649	9.31	33.16	56.24	60.10	46.33	74.00	-27.67 Peak
4 9232.187	12.17	38.63	54.43	52.01	48.38	74.00	-25.62 Peak
5 11335.190	14.29	39.36	53.40	49.10	49.35	74.00	-24.65 Peak
6 14242.800	16.83	40.46	54.10	47.84	51.03	74.00	-22.97 Peak
7 16891.040	19.64	38.60	53.88	45.39	49.75	74.00	-24.25 Peak
8 17896.250	18.87	41.97	54.26	46.41	52.99	74.00	-21.01 Peak


11n_20M_TX_CH_06_Horizontal



Condition: 3m HORIZONTAL
Job No : 00213AT
Mode : 2437 TX RSE
: 2.4G Wi-Fi 11n20

Freq	Cable	Ant	Preamp	Read	Limit	Over	Aux
MHz	Loss	Factor	Factor	Level	Line	Limit	Factor
	dB	dB/m	dB	dBuV	dBuV/m	dB	dB
1 pp 4859.975	8.96	32.82	55.97	57.80	43.61	54.00	-10.39 Average
2 pk 4859.975	8.96	32.82	55.97	72.12	57.93	74.00	-16.07 Peak
3 7606.788	11.03	36.77	56.13	54.18	45.85	74.00	-28.15 Peak
4 9952.717	12.80	38.71	53.65	50.33	48.19	74.00	-25.81 Peak
5 13717.560	16.02	40.30	54.02	47.81	50.11	74.00	-23.89 Peak
6 16891.040	19.64	38.60	53.88	46.26	50.62	74.00	-23.38 Peak
7 18000.000	18.64	42.60	54.30	46.03	52.97	74.00	-21.03 Peak

11n_20M_TX_CH_06_Vertical




Condition: 3m VERTICAL
Job No : 00213AT
Mode : 2437 TX RSE
: 2.4G Wi-Fi 11n20

Freq	Cable	Ant	Preamp	Read	Limit	Over	Aux
MHz	Loss	Factor	Factor	Level	Line	Limit	Factor
	dB	dB/m	dB	dBuV	dBuV/m	dB	dB
1 pp 4874.043	8.97	32.85	55.99	60.11	45.94	54.00	-8.06 Average
2 pk 4874.043	8.97	32.85	55.99	75.42	61.25	74.00	-12.75 Peak
3 5269.649	9.31	33.16	56.24	60.10	46.33	74.00	-27.67 Peak
4 10018.420	12.90	38.90	53.60	51.10	49.30	74.00	-24.70 Peak
5 14079.000	16.38	40.44	54.10	47.84	50.56	74.00	-23.44 Peak
6 16891.040	19.64	38.60	53.88	46.28	50.64	74.00	-23.36 Peak
7 18000.000	18.64	42.60	54.30	45.83	52.77	74.00	-21.23 Peak




11n_20M_TX_CH_11_Horizontal



Condition: 3m HORIZONTAL
Job No : 00213AT
Mode : 2462 TX RSE
: 2.4G Wi-Fi 11n20

Freq	Cable	Ant	Preamp	Read	Limit	Over	Aux
MHz	Loss	Factor	Factor	Level	Line	Limit	Factor
	dB	dB/m	dB	dBuV	dBuV/m	dB	dB
1 pp 4916.490	9.02	32.97	56.02	56.37	42.34	54.00	-11.66 Average 0.00
2 pk 4916.490	9.02	32.97	56.02	71.17	57.14	74.00	-16.86 Peak 0.00
3 6756.708	10.91	36.19	56.52	53.80	44.38	74.00	-29.62 Peak 0.00
4 8866.962	12.30	38.40	54.85	52.44	48.29	74.00	-25.71 Peak 0.00
5 12184.580	14.48	39.37	53.31	49.02	49.56	74.00	-24.44 Peak 0.00
6 14038.458	16.47	40.52	54.10	47.73	50.62	74.00	-23.38 Peak 0.00
7 17948.050	18.75	42.29	54.28	46.55	53.31	74.00	-20.69 Peak 0.00


11n_20M_TX_CH_11_Vertical



Condition: 3m VERTICAL
Job No : 00213AT
Mode : 2462 TX RSE
: 2.4G Wi-Fi 11n20

Freq	Cable	Ant	Preamp	Read	Limit	Over	Aux
MHz	Loss	Factor	Factor	Level	Line	Limit	Factor
	dB	dB/m	dB	dBuV	dBuV/m	dB	dB
1 pp 4916.490	9.02	32.97	56.02	58.33	44.30	54.00	-9.70 Average 0.00
2 pk 4916.490	9.02	32.97	56.02	74.44	60.41	74.00	-13.59 Peak 0.00
3 5269.649	9.31	33.16	56.24	60.94	47.17	74.00	-26.83 Peak 0.00
4 9258.009	12.13	38.70	54.40	51.67	48.10	74.00	-25.90 Peak 0.00
5 12724.470	14.99	39.75	53.64	48.68	49.78	74.00	-24.22 Peak 0.00
6 14533.910	16.36	40.20	54.10	48.35	50.81	74.00	-23.17 Peak 0.00
7 18000.000	18.64	42.60	54.30	45.63	52.57	74.00	-21.43 Peak 0.00


11ax_20M_TX_CH_01_Horizontal



Condition: 3m HORIZONTAL
Job No : 00213AT
Mode : 2412 TX RSE
: 2.4G Wi-Fi 11ax20

Freq	Cable	Ant	Preamp	Read	Limit	Over	Aux
MHz	Loss	Factor	Factor	Level	Line	Limit	Factor
	dB	dB/m	dB	dBuV	dBuV/m	dB	dB
1 pp 4831.962	8.93	32.73	55.95	57.50	43.21	54.00	-10.79 Average 0.00
2 pk 4831.962	8.93	32.73	55.95	73.00	58.71	74.00	-15.29 Peak 0.00
3 8539.102	12.02	37.00	55.24	53.39	47.97	74.00	-26.03 Peak 0.00
4 11140.310	14.17	39.38	53.46	49.00	49.09	74.00	-24.91 Peak 0.00
5 14160.710	16.53	40.46	54.10	49.19	52.08	74.00	-21.92 Peak 0.00
6 16891.040	19.64	38.60	53.88	46.16	50.52	74.00	-23.48 Peak 0.00
7 18000.000	18.64	42.60	54.30	46.41	53.35	74.00	-20.65 Peak 0.00

11ax_20M_TX_CH_01_Vertical




Condition: 3m VERTICAL
Job No : 00213AT
Mode : 2412 TX RSE
: 2.4G Wi-Fi 11ax20

Freq	Cable	Ant	Preamp	Read	Limit	Over	Aux
MHz	Loss	Factor	Factor	Level	Line	Limit	Factor
	dB	dB/m	dB	dBuV	dBuV/m	dB	dB
1 pp 4818.016	8.92	32.67	55.93	61.33	46.99	54.00	-7.01 Average 0.00
2 pk 4818.016	8.92	32.67	55.93	75.97	61.63	74.00	-12.37 Peak 0.00
3 5269.649	9.31	33.16	56.24	59.67	45.90	74.00	-28.10 Peak 0.00
4 9613.430	12.40	38.75	54.01	51.44	48.58	74.00	-25.42 Peak 0.00
5 13997.930	16.53	40.59	54.10	48.30	51.32	74.00	-22.68 Peak 0.00
6 16891.040	19.64	38.60	53.88	46.47	50.83	74.00	-23.17 Peak 0.00
7 18000.000	18.64	42.60	54.30	46.80	53.74	74.00	-20.26 Peak 0.00




11ax_20M_TX_CH_06_Horizontal



Condition: 3m HORIZONTAL
Job No : 00213AT
Mode : 2437 TX RSE

Freq	Cable	Loss	Factor	Ant	Preamp	Read	Level	Limit	Over	Aux
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB	dB	dB
1 pp 4874.043	8.97	32.85	55.99	56.91	42.74	54.00	-11.26	Average	0.00	
2 pk 4874.043	8.97	32.85	55.99	71.72	57.55	74.00	-16.45	Peak	0.00	
3 8295.823	11.66	37.31	55.53	52.74	46.18	74.00	-27.82	Peak	0.00	
4 11140.310	14.17	39.38	53.46	49.31	49.40	74.00	-24.60	Peak	0.00	
5 14201.690	16.67	40.50	54.10	47.51	50.58	74.00	-23.42	Peak	0.00	
6 16891.040	19.64	38.60	53.88	46.34	50.70	74.00	-23.30	Peak	0.00	
7 17896.250	18.87	41.97	54.26	46.16	52.74	74.00	-21.26	Peak	0.00	


11ax_20M_TX_CH_06_Vertical



Condition: 3m VERTICAL
Job No : 00213AT
Mode : 2437 TX RSE

Freq	Cable	Loss	Factor	Ant	Preamp	Read	Level	Limit	Over	Aux
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB	dB	dB
1 pp 4874.043	8.97	32.85	55.99	59.61	45.44	54.00	-8.56	Average	0.00	
2 pk 4874.043	8.97	32.85	55.99	75.01	60.84	74.00	-13.16	Peak	0.00	
3 5269.649	9.31	33.16	56.24	58.83	45.06	74.00	-28.94	Peak	0.00	
4 8866.062	12.30	38.40	54.85	52.27	48.12	74.00	-25.88	Peak	0.00	
5 11108.160	14.13	39.32	53.47	49.41	49.39	74.00	-24.61	Peak	0.00	
6 14575.970	16.46	40.20	54.10	49.22	51.78	74.00	-22.22	Peak	0.00	
7 18000.000	18.64	42.60	54.30	45.86	52.80	74.00	-21.20	Peak	0.00	


11ax_20M_TX_CH_11_Horizontal



Condition: 3m HORIZONTAL
Job No : 00213AT
Mode : 2462 TX RSE

Freq	Cable	Loss	Factor	Ant	Preamp	Read	Level	Limit	Over	Aux
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB	dB	dB
1 pp 4930.721	9.03	33.02	56.04	55.99	42.00	54.00	-12.00	Average	0.00	
2 pk 4930.721	9.03	33.02	56.04	71.84	57.85	74.00	-16.15	Peak	0.00	
3 7920.911	11.48	37.30	55.94	53.89	46.73	74.00	-27.27	Peak	0.00	
4 11335.100	14.29	39.36	53.40	49.41	49.66	74.00	-24.34	Peak	0.00	
5 14201.690	16.67	40.50	54.10	47.95	51.02	74.00	-22.98	Peak	0.00	
6 16891.040	19.64	38.60	53.88	45.64	50.00	74.00	-24.00	Peak	0.00	
7 17844.590	19.02	41.56	54.24	46.24	52.58	74.00	-21.42	Peak	0.00	

11ax_20M_TX_CH_11_Vertical




Condition: 3m VERTICAL
Job No : 00213AT
Mode : 2462 TX RSE

Freq	Cable	Loss	Factor	Ant	Preamp	Read	Level	Limit	Over	Aux
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB	dB	dB
1 pp 4930.721	9.03	33.02	56.04	57.83	43.84	54.00	-10.16	Average	0.00	
2 pk 4930.721	9.03	33.02	56.04	73.60	59.61	74.00	-14.39	Peak	0.00	
3 5269.649	9.31	33.16	56.24	59.59	45.82	74.00	-28.18	Peak	0.00	
4 8416.584	11.68	37.57	55.38	53.07	46.94	74.00	-27.06	Peak	0.00	
5 11076.100	14.14	39.30	53.48	49.82	49.78	74.00	-24.22	Peak	0.00	
6 14284.030	17.00	40.42	54.10	47.67	50.99	74.00	-23.01	Peak	0.00	
7 18000.000	18.64	42.60	54.30	46.20	53.14	74.00	-20.86	Peak	0.00	




11b_TX_CH_01_Horizontal



Condition: 3m HORIZONTAL
Job No : 00213AT
Mode : 2412 TX RSE

Freq	Cable Loss	Factor	Ant Factor	Preamp	Read Level	Level	Limit Line	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB			dB
1 pp23626.600	6.77	38.55	50.33	52.79	38.24	74.00	-35.76	Peak		-9.54

11b_TX_CH_01_Vertical



Condition: 3m VERTICAL
Job No : 00213AT
Mode : 2412 TX RSE

Freq	Cable Loss	Factor	Ant Factor	Preamp	Read Level	Level	Limit Line	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB			dB
1 pp23502.740	6.76	38.31	50.30	52.03	37.26	74.00	-36.74	Peak		-9.54



7.4 Maximum Conducted Output Power

Test Requirement 47 CFR Part 15, Subpart C 15.247(b)(3)
 Test Method: ANSI C63.10 (2020) Section 11.9.2
 Test Engineer: Mingli Hu

Limit:

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for ≥ 50 hopping channels
	0.25 for $25 \leq$ hopping channels < 50
	1 for digital modulation
2400-2483.5	1 for ≥ 75 non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

7.4.1 E.U.T. Operation

Operating Environment:


Temperature: 25.2 °C Humidity: 62.4 % RH Atmospheric Pressure: 1010 mbar

7.4.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20)/ax(HEW20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40)/ax(HEW40), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.



7.4.3 Test Setup Diagram



7.4.4 Measurement Procedure and Data

Note: Since the verify power the same operating range bandwidth and smaller power can be covered by the higher power.

Please Refer to Appendix for Details



7.5 Minimum 6dB Bandwidth

Test Requirement 47 CFR Part 15, Subpart C 15.247a(2)
 Test Method: ANSI C63.10 (2020) Section 11.8.1
 Test Engineer: Mingli Hu

Limit:
 ≥500 kHz


7.5.1 E.U.T. Operation

Operating Environment:
 Temperature: 25.2 °C Humidity: 62.1 % RH Atmospheric Pressure: 1010 mbar

7.5.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20)/ax(HEW20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40)/ax(HEW40), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.

7.5.3 Test Setup Diagram



7.5.4 Measurement Procedure and Data

Please Refer to Appendix for Details



7.6 Power Spectral Density

Test Requirement 47 CFR Part 15, Subpart C 15.247(e)
 Test Method: ANSI C63.10 (2020) Section 11.10.3
 Test Engineer: Mingli Hu

Limit:

≤8dBm in any 3 kHz band during any time interval of continuous transmission

7.6.1 E.U.T. Operation


Operating Environment:

Temperature: 25.2 °C Humidity: 61.9 % RH Atmospheric Pressure: 1010 mbar

7.6.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20)/ax(HEW20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40)/ax(HEW40), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.

7.6.3 Test Setup Diagram



7.6.4 Measurement Procedure and Data

Please Refer to Appendix for Details



7.7 Conducted Band Edges Measurement

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)
 Test Method: ANSI C63.10 (2020) Section 6.10.4
 Test Engineer: Mingli Hu

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.7.1 E.U.T. Operation

Operating Environment:


Temperature: 25.4 °C Humidity: 59.6 % RH Atmospheric Pressure: 1010 mbar

7.7.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20)/ax(HEW20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40)/ax(HEW40), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.



7.7.3 Test Setup Diagram



7.7.4 Measurement Procedure and Data

Please Refer to Appendix for Details



7.8 Conducted Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)
 Test Method: ANSI C63.10 (2020) Section 11.11
 Test Engineer: Mingli Hu

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.8.1 E.U.T. Operation

Operating Environment:


Temperature: 25.4 °C Humidity: 58.3 % RH Atmospheric Pressure: 1010 mbar

7.8.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20)/ax(HEW20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40)/ax(HEW40), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.



7.8.3 Test Setup Diagram



7.8.4 Measurement Procedure and Data

Please Refer to Appendix for Details

8 Test Setup Photo

Refer to Appendix - Test Setup Photo for SZCR2601000213AT

9 EUT Constructional Details (EUT Photos)

Refer to External and Internal Photos for SZCR2601000213AT



10 Appendix

1. Duty Cycle

1.1 Test Result


1.1.1 Ant1


Ant1									
Mode	Tx Type	Frequency (MHz)	RU	RU Pos	T_on (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	Max. DC Variation (%)
802.11b	SISO	2412	/	/	8.417	8.560	98.33	0.07	0.19
		2437	/	/	8.417	8.637	97.45	0.11	1.14
		2462	/	/	8.417	8.570	98.21	0.08	0.35
802.11g	SISO	2412	/	/	1.397	1.538	90.83	0.42	0.61
		2437	/	/	1.396	1.530	91.24	0.40	0.00
		2462	/	/	1.397	1.547	90.30	0.44	1.07
802.11n (HT20)	SISO	2412	/	/	5.090	5.298	96.07	0.17	1.51
		2437	/	/	5.089	5.305	95.93	0.18	1.65
		2462	/	/	5.088	5.223	97.42	0.11	0.07
802.11n (HT40)	SISO	2422	/	/	4.898	5.124	95.59	0.20	1.92
		2437	/	/	4.898	5.105	95.95	0.18	1.53
		2452	/	/	4.917	5.070	96.98	0.13	0.79
802.11ax (HEW20)	SISO	2412	RU242	Left	3.879	4.104	94.52	0.24	2.32
		2437	RU242	Left	3.878	4.104	94.49	0.25	2.39
		2462	RU242	Left	3.880	4.095	94.75	0.23	2.15
802.11ax (HEW40)	SISO	2422	RU484	Left	3.875	4.081	94.95	0.22	1.89
		2437	RU484	Left	3.874	4.050	95.65	0.19	1.07
		2452	RU484	Left	3.874	4.090	94.72	0.24	2.12




1.2 Test Graph

1.2.1 Ant1







802.11b_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11g_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11g_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_LCH_2422MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_HCH_2452MHz_Ant1 (SISO)_NTNV




802.11ax(HEW20)_LCH_2412MHz_RU242_Left_Ant1 (SISO)_NTNV




802.11ax(HEW20)_MCH_2437MHz_RU242_Left_Ant1 (SISO)_NTNV




802.11ax(HEW20)_HCH_2462MHz_RU242_Left_Ant1 (SISO)_NTNV




802.11ax(HEW40)_LCH_2422MHz_RU484_Left_Ant1 (SISO)_NTNV



802.11ax(HEW40)_MCH_2437MHz_RU484_Left_Ant1 (SISO)_NTNV



802.11ax(HEW40)_HCH_2452MHz_RU484_Left_Ant1 (SISO)_NTNV



2. Bandwidth

2.1 Test Result

2.1.1 OBW

Mode	TX Type	Frequency (MHz)	RU	RU Pos	ANT	99% Occupied Bandwidth (MHz)		Verdict
						Result	Limit	
802.11b	SISO	2412	/	/	1	13.170	/	Pass
		2437	/	/	1	13.788	/	Pass
		2462	/	/	1	13.707	/	Pass
802.11g	SISO	2412	/	/	1	16.786	/	Pass
		2437	/	/	1	16.917	/	Pass
		2462	/	/	1	16.711	/	Pass
802.11n (HT20)	SISO	2412	/	/	1	17.902	/	Pass
		2437	/	/	1	17.908	/	Pass
		2462	/	/	1	17.906	/	Pass
802.11n (HT40)	SISO	2422	/	/	1	37.265	/	Pass
		2437	/	/	1	37.340	/	Pass
		2452	/	/	1	37.328	/	Pass
802.11ax (HEW20)	SISO	2412	RU242	Left	1	19.078	/	Pass
		2437	RU242	Left	1	19.058	/	Pass
		2462	RU242	Left	1	19.070	/	Pass
802.11ax (HEW40)	SISO	2422	RU484	Left	1	38.305	/	Pass
		2437	RU484	Left	1	38.331	/	Pass
		2452	RU484	Left	1	38.326	/	Pass

2.1.2 6dB BW

Mode	TX Type	Frequency (MHz)	RU	RU Pos	ANT	6dB Bandwidth (MHz)		Verdict
						Result	Limit	
802.11b	SISO	2412	/	/	1	9.182	≥ 0.5	Pass
		2437	/	/	1	9.613	≥ 0.5	Pass
		2462	/	/	1	9.209	≥ 0.5	Pass
802.11g	SISO	2412	/	/	1	16.366	≥ 0.5	Pass
		2437	/	/	1	16.338	≥ 0.5	Pass
		2462	/	/	1	16.380	≥ 0.5	Pass
802.11n (HT20)	SISO	2412	/	/	1	17.585	≥ 0.5	Pass
		2437	/	/	1	17.568	≥ 0.5	Pass



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR260100021302

Page: 67 of 125

		2462	/	/	1	17.552	>=0.5	Pass
802.11n (HT40)	SISO	2422	/	/	1	35.714	>=0.5	Pass
		2437	/	/	1	36.310	>=0.5	Pass
		2452	/	/	1	36.093	>=0.5	Pass
802.11ax (HEW20)	SISO	2412	RU242	Left	1	18.988	>=0.5	Pass
		2437	RU242	Left	1	18.970	>=0.5	Pass
		2462	RU242	Left	1	19.001	>=0.5	Pass
802.11ax (HEW40)	SISO	2422	RU484	Left	1	37.615	>=0.5	Pass
		2437	RU484	Left	1	37.333	>=0.5	Pass
		2452	RU484	Left	1	37.670	>=0.5	Pass



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.


Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Inspection & Testing Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com


2.2 Test Graph

2.2.1 OBW







802.11b_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11g_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11g_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_LCH_2422MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_HCH_2452MHz_Ant1 (SISO)_NTNV




802.11ax(HEW20)_LCH_2412MHz_RU242_Left_Ant1 (SISO)_NTNV




802.11ax(HEW20)_MCH_2437MHz_RU242_Left_Ant1 (SISO)_NTNV




802.11ax(HEW20)_HCH_2462MHz_RU242_Left_Ant1 (SISO)_NTNV




802.11ax(HEW40)_LCH_2422MHz_RU484_Left_Ant1 (SISO)_NTNV




802.11ax(HEW40)_MCH_2437MHz_RU484_Left_Ant1 (SISO)_NTNV




802.11ax(HEW40)_HCH_2452MHz_RU484_Left_Ant1 (SISO)_NTNV




2.2.2 6dB BW




802.11b_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11g_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11g_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_LCH_2422MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_HCH_2452MHz_Ant1 (SISO)_NTNV




802.11ax(HEW20)_LCH_2412MHz_RU242_Left_Ant1 (SISO)_NTNV




802.11ax(HEW20)_MCH_2437MHz_RU242_Left_Ant1 (SISO)_NTNV




802.11ax(HEW20)_HCH_2462MHz_RU242_Left_Ant1 (SISO)_NTNV




802.11ax(HEW40)_LCH_2422MHz_RU484_Left_Ant1 (SISO)_NTNV



802.11ax(HEW40)_MCH_2437MHz_RU484_Left_Ant1 (SISO)_NTNV



802.11ax(HEW40)_HCH_2452MHz_RU484_Left_Ant1 (SISO)_NTNV



3. Maximum Conducted Output Power

3.1 Test Result

3.1.1 Power

Mode	TX Type	Frequency (MHz)	RU	RU Pos	Maximum Average Conducted Output Power (dBm)		Verdict
					ANT1	Limit	
802.11b	SISO	2412	/	/	9.93	<=30	Pass
		2437	/	/	10.18	<=30	Pass
		2462	/	/	10.36	<=30	Pass
802.11g	SISO	2412	/	/	14.13	<=30	Pass
		2437	/	/	14.99	<=30	Pass
		2462	/	/	13.72	<=30	Pass
802.11n (HT20)	SISO	2412	/	/	12.85	<=30	Pass
		2437	/	/	13.66	<=30	Pass
		2462	/	/	12.84	<=30	Pass
802.11n (HT40)	SISO	2422	/	/	12.87	<=30	Pass
		2437	/	/	13.59	<=30	Pass
		2452	/	/	13.43	<=30	Pass
802.11ax (HEW20)	SISO	2412	RU242	Left	13.15	<=30	Pass
		2437	RU242	Left	13.98	<=30	Pass
		2462	RU242	Left	13.30	<=30	Pass
802.11ax (HEW40)	SISO	2422	RU484	Left	13.14	<=30	Pass
		2437	RU484	Left	14.02	<=30	Pass
		2452	RU484	Left	14.02	<=30	Pass

Note1: Antenna Gain: Ant1: 1.10dBi;

4. Maximum Power Spectral Density

4.1 Test Result

4.1.1 PSD

Mode	TX Type	Frequency (MHz)	RU	RU Pos	Maximum PSD (dBm)		Verdict
					ANT1	Limit(dBm/3kHz)	
802.11b	SISO	2412	/	/	-7.01dBm/100kHz	<=8	Pass
		2437	/	/	-6.84dBm/100kHz	<=8	Pass
		2462	/	/	-6.93dBm/100kHz	<=8	Pass



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR260100021302

Page: 88 of 125

802.11g	SISO	2412	/	/	-5.23dBm/100kHz	<=8	Pass
		2437	/	/	-4.54dBm/100kHz	<=8	Pass
		2462	/	/	-5.71dBm/100kHz	<=8	Pass
802.11n (HT20)	SISO	2412	/	/	-6.84dBm/100kHz	<=8	Pass
		2437	/	/	-6.11dBm/100kHz	<=8	Pass
		2462	/	/	-6.96dBm/100kHz	<=8	Pass
802.11n (HT40)	SISO	2422	/	/	-9.97dBm/100kHz	<=8	Pass
		2437	/	/	-9.15dBm/100kHz	<=8	Pass
		2452	/	/	-9.45dBm/100kHz	<=8	Pass
802.11ax (HEW20)	SISO	2412	RU242	Left	-8.03dBm/100kHz	<=8	Pass
		2437	RU242	Left	-7.15dBm/100kHz	<=8	Pass
		2462	RU242	Left	-7.82dBm/100kHz	<=8	Pass
802.11ax (HEW40)	SISO	2422	RU484	Left	-10.82dBm/100kHz	<=8	Pass
		2437	RU484	Left	-10.00dBm/100kHz	<=8	Pass
		2452	RU484	Left	-10.14dBm/100kHz	<=8	Pass

Note1: Antenna Gain: Ant1: 1.10dBi;



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing & Calibration Laboratory


Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.


Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com


4.2 Test Graph

4.2.1 PSD







802.11b_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11g_LCH_2412MHz_Ant1 (SISO)_NTNV



802.11g_MCH_2437MHz_Ant1 (SISO)_NTNV



802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing & Calibration Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

802.11n(HT20)_LCH_2412MHz_Ant1 (SISO)_NTNV



802.11n(HT20)_MCH_2437MHz_Ant1 (SISO)_NTNV




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Inspection & Testing Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

802.11n(HT20)_HCH_2462MHz_Ant1 (SISO)_NTNV



802.11n(HT40)_LCH_2422MHz_Ant1 (SISO)_NTNV




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing & Calibration Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com


802.11n(HT40)_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_HCH_2452MHz_Ant1 (SISO)_NTNV



802.11ax(HEW20)_LCH_2412MHz_RU242_Left_Ant1 (SISO)_NTNV



802.11ax(HEW20)_MCH_2437MHz_RU242_Left_Ant1 (SISO)_NTNV




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing & Calibration Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com


802.11ax(HEW20)_HCH_2462MHz_RU242_Left_Ant1 (SISO)_NTNV




802.11ax(HEW40)_LCH_2422MHz_RU484_Left_Ant1 (SISO)_NTNV



802.11ax(HEW40)_MCH_2437MHz_RU484_Left_Ant1 (SISO)_NTNV



802.11ax(HEW40)_HCH_2452MHz_RU484_Left_Ant1 (SISO)_NTNV



5. Unwanted Emissions In Non-restricted Frequency Bands

5.1 Test Result

5.1.1 Ref

Mode	TX Type	Frequency (MHz)	RU	RU Pos	ANT	Level of Reference (dBm)
802.11b	SISO	2412	/	/	1	1.80
		2437	/	/	1	1.93
		2462	/	/	1	2.23
802.11g	SISO	2412	/	/	1	3.81
		2437	/	/	1	4.69
		2462	/	/	1	4.00
802.11n (HT20)	SISO	2412	/	/	1	2.05
		2437	/	/	1	2.75
		2462	/	/	1	2.49
802.11n (HT40)	SISO	2422	/	/	1	-1.20
		2437	/	/	1	-0.10
		2452	/	/	1	-0.55
802.11ax (HEW20)	SISO	2412	RU242	Left	1	2.76
		2437	RU242	Left	1	3.19
		2462	RU242	Left	1	2.17
802.11ax (HEW40)	SISO	2422	RU484	Left	1	-0.78
		2437	RU484	Left	1	0.24
		2452	RU484	Left	1	-0.18

5.1.2 CSE

Mode	TX Type	Frequency (MHz)	RU	RU Pos	ANT	Level of Reference (dBm)	Limit (dBm)	Verdict
802.11b	SISO	2412	/	/	1	2.23	-27.77	Pass
		2437	/	/	1	2.23	-27.77	Pass
		2462	/	/	1	2.23	-27.77	Pass



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR260100021302

Page: 100 of 125

802.11g	SISO	2412	/	/	1	4.69	-25.31	Pass
		2437	/	/	1	4.69	-25.31	Pass
		2462	/	/	1	4.69	-25.31	Pass
802.11n (HT20)	SISO	2412	/	/	1	2.75	-27.25	Pass
		2437	/	/	1	2.75	-27.25	Pass
		2462	/	/	1	2.75	-27.25	Pass
802.11n (HT40)	SISO	2422	/	/	1	-0.10	-30.10	Pass
		2437	/	/	1	-0.10	-30.10	Pass
		2452	/	/	1	-0.10	-30.10	Pass
802.11ax (HEW20)	SISO	2412	RU242	Left	1	3.19	-26.81	Pass
		2437	RU242	Left	1	3.19	-26.81	Pass
		2462	RU242	Left	1	3.19	-26.81	Pass
802.11ax (HEW40)	SISO	2422	RU484	Left	1	0.24	-29.76	Pass
		2437	RU484	Left	1	0.24	-29.76	Pass
		2452	RU484	Left	1	0.24	-29.76	Pass



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.


Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing & Calibration Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com


5.2 Test Graph

5.2.1 Ref







802.11b_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11g_LCH_2412MHz_Ant1 (SISO)_NTNV



802.11g_MCH_2437MHz_Ant1 (SISO)_NTNV



802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing & Calibration Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

802.11n(HT20)_LCH_2412MHz_Ant1 (SISO)_NTNV



802.11n(HT20)_MCH_2437MHz_Ant1 (SISO)_NTNV

