



Antenna Passive TEST REPORT

Applicant	:	Globe Electric Company Inc
Address	:	150 Oneida, Montreal, Quebec, Canada, H9R 1A8
Equipment under Test	:	DR-S2218
Model No.	:	50824
Trade Mark	:	N/A
Report No.	:	DDT-B24112007-1E01
Issue Date	:	Nov. 27, 2024
Issued By	:	Tianjin Dongdian Testing Service Co., Ltd.
Address	:	Building D-1, No. 19, Weisi Road, Microelectronics Industrial Park, Development Area, Tianjin, China. Tel: +86-022-5803803 E-mail: ddt@dgddt.com, http://www.ddttest.com



REPORT

CONMENT

1.	General TEST Information	5
1.1	Description of EUT	5
1.2	Accessories of EUT	5
1.3	Assistant equipment used for test	5
1.4	Block diagram of EUT configuration for test	5
1.5	Measurement uncertainty	5
1.6	Antenna Parameter	6
1.7	Test laboratory	6
2.	Electric performance measurement	7
2.1	General Information	7
2.2	Test Equipment	7
2.3	Block Diagram of Test Setup	7
2.4	Test Procedure	7
2.5	Result	8
Annex A	Test Setup Photo	12
Annex B	EUT Photo	13

Revision History


Rev.	Revisions	Issue Date	Revised By
---	Initial issue	Nov. 27, 2024	

Test Report Declare

Applicant	:	Globe Electric Company Inc
Address	:	150 Oneida, Montreal, Quebec, Canada, H9R 1A8
Equipment under Test	:	DR-S2218
Model No.	:	50824
Trade Mark	:	N/A
Manufacturer	:	Globe Electric Company Inc
Address	:	150 Oneida, Montreal, Quebec, Canada, H9R 1A8

We Declare:

The equipment described above is tested by Tianjin Dongdian Testing Service Co., Ltd and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Tianjin Dongdian Testing Service Co., Ltd is assumed of full responsibility for the accuracy and completeness of these tests.



Report No:	DDT-B24112007-1E01		
Date of Receipt:	Nov. 26, 2024	Date of Test:	Nov. 26, 2024

Prepared By:

Approved By:

Novak Wei

Aaron Zhang

Novak Wei / Engineer

Aaron Zhang / Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Tianjin Dongdian Testing Service Co., Ltd.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

1. General TEST Information

1.1 Description of EUT

EUT Description	:	DR-S2218
Model Number	:	50824
Frequency Band	:	2400MHz-2500MHz
Power Supply	:	N/A
Sample No	:	Y24112007-01
Note	:	N/A

1.2 Accessories of EUT

Description of Accessories	Manufacturer	Model number	Description	Remark
N/A	N/A	N/A	N/A	N/A

1.3 Assistant equipment used for test

Description of Accessories	Manufacturer	Model number	Description	Remark
N/A	N/A	N/A	N/A	N/A


1.4 Block diagram of EUT configuration for test



1.5 Measurement uncertainty

Test Item	uncertainty
Near-field gain measurement	0.44 dB
Near-field pattern measurement	0.44 dB
Note: This uncertainty indicates that the extended uncertainty confidence interval is about 95% and the corresponding inclusion factor k=2 is obtained.	

1.6 Antenna Parameter



1.7 Test laboratory

Tianjin Dongdian Testing Service Co., Ltd.

Address: Building D-1, No. 19, Weisi Road, Microelectronics Industrial Park Development Area, Tianjin, China., 300385

Tel: +86-22-58038033, <http://www.ddttest.com>, Email: ddt@dgddt.com

NVLAP (National Voluntary Laboratory Accreditation Program) CODE: 500036-0

CNAS (China National Accreditation Service for Conformity Assessment) CODE: L13402

FCC Designation Number: CN5004; FCC Test Firm Registration Number: 368676

ISED (Innovation, Science and Economic Development Canada) Company Number: 27768

Conformity Assessment Body Identifier: CN0125

VCCI Facility Registration Number: C-20089, T-20093, R-20125, G-20122

2. Electric performance measurement


2.1 General Information

Test Date	2024-11-26		
Test Condition	Temperature: 20.7±1℃	Humidity: 38±1%	Pressure: 101.4±0.2 kPa
Test Place	OTA Room	Test Engineer	Novak Wei

2.2 Test Equipment

Equipment	Manufacturer	Model No	Serial No	Last Cal.	Cal.Interval
ENA network analyzer	Keysight	E5071C	MY46900684	2024-05-06	1 year
Software	FEITU	ANTESTPRO	N/A	N/A	N/A

2.3 Block Diagram of Test Setup



2.4 Test Procedure

- (1) Set up the antenna to be measured. Set up the antenna and mark the cross reference line at the center of the antenna port surface to be measured.
- (2) Connect the cable connector and adjust the down dip Angle (electrically tuned antenna).
- (3) Open the test software, create the test project, and configure the test port.
- (4) Use test software for automatic testing and save test data of electromagnetic field distribution.
- (5) Change the port, down dip Angle, or test frequency (if necessary), and repeat steps (3) to (4) until all status data to be measured is collected.
- (6) After near and far field exchange, the three-position spherical pattern of the antenna to be tested is obtained, and the Theta and Phi angles of the position where the maximum level of the


three-position spherical pattern is located are found. The horizontal plane pattern curve of the antenna to be tested is obtained by cutting according to equal Theta Angle, and the vertical plane pattern of the antenna to be tested is cancelled by cutting according to equal Phi Angle. Then the radiation parameters of the horizontal plane and vertical plane pattern of the antenna to be measured are obtained by using the processing method similar to that of the far field.

2.5 Result


Fre. (MHz)	Eff. (dBi)	Gain (dBi)	Eff. (%)	Directivity (dB)	Peak Gain Position (Theta)	Peak Gain Position (Phi)	Eff. ThetaPol (%)	Eff. PhiPol (%)	Upper Hem. Eff. (%)	Lower Hem. Eff. (%)
2400.0	-2.47	3.17	56.63	5.64	165.00	330.00	27.27	29.36	29.57	27.06
2410.0	-2.47	3.31	56.58	5.78	165.00	330.00	27.10	29.48	29.09	27.49
2420.0	-2.36	3.49	58.03	5.86	165.00	330.00	27.77	30.26	29.51	28.52
2430.0	-2.31	3.68	58.69	6.00	165.00	330.00	28.25	30.45	29.45	29.24
2440.0	-2.27	3.78	59.24	6.05	165.00	330.00	28.75	30.49	29.47	29.77
2450.0	-2.22	3.94	60.05	6.15	165.00	330.00	29.51	30.54	29.87	30.17
2460.0	-2.23	3.98	59.78	6.22	165.00	330.00	29.78	30.00	29.74	30.04
2470.0	-2.27	4.02	59.31	6.29	165.00	330.00	29.89	29.42	29.58	29.73
2480.0	-2.27	4.01	59.25	6.28	165.00	330.00	30.04	29.22	29.72	29.53
2490.0	-2.18	4.12	60.58	6.29	165.00	330.00	30.72	29.86	30.17	30.41
2500.0	-2.27	3.92	59.28	6.20	165.00	330.00	29.93	29.35	29.38	29.90

2400.0MHz H+V, Eff: 56.6%



Back View




2410.0MHz H+V, Eff: 56.6%




Back View




2420.0MHz H+V, Eff: 58.0%




Back View




2430.0MHz H+V, Eff: 58.7%





Back View




2440.0MHz H+V, Eff: 59.2%





Back View




2450.0MHz H+V, Eff: 60.0%





Back View




2460.0MHz H+V, Eff: 59.8%





Back View




2470.0MHz H+V, Eff: 59.3%





Back View




2480.0MHz H+V, Eff: 59.3%





Back View




2490.0MHz H+V, Eff: 60.6%





Back View




2500.0MHz H+V, Eff: 59.3%




Back View



Annex A Test Setup Photo



Annex B EUT Photo



-----END-----