



RADIO TEST REPORT

Applicant	:	GLOBE ELECTRIC COMPANY INC.
Address of Applicant	:	150 Oneida, Montreal, Quebec, Canada, H9R 1A8
Manufacturer	:	Satellite Electronics (Zhong shan) Co Ltd.
Address of Manufacturer	:	No.8, Chuang Ye Road, Torch Development Zone, Zhongshan, Guangdong, China
Equipment under Test	:	Ceiling Fan
Model No.	:	37000119
HVIN	:	GL37000119
FCC ID	:	2AQUQGL37119
IC	:	8290A-GL37119
Test Standard(s)	:	FCC Rules and Regulations Part 15 Subpart C, ANSI C63.10-2020+Cor.1-2023, RSS-247 Issue 4 July 24, 2025, RSS-Gen Issue 5, Apr. 2018, Amendment 2 (February 2021), ANSI C63.10-2020+Cor.1-2023+C63.10a-2024+Errata to C63.10a-2024
Report No.	:	DDT-RE26060401-2E02
Issue Date	:	2026/09/08
Issue By	:	Guangdong Dongdian Testing Service Co., Ltd. Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808

REPORT

Table of Contents

1.	Summary of Test Results	7
2.	General Test Information.....	8
2.1.	Description of EUT	8
2.2.	Accessories of EUT	8
2.3.	Block diagram of EUT configuration for test.....	8
2.4.	Decision of final test mode	9
2.5.	Deviations of test standard	9
2.6.	Test environment conditions	9
2.7.	Test laboratory	10
2.8.	Measurement uncertainty	10
3.	Equipment Used During Conductive Test	11
4.	6dB Bandwidth	12
4.1.	Block diagram of test setup	12
4.2.	Limits	12
4.3.	Test procedure	12
4.4.	Test result.....	13
4.5.	Test graphs	14
5.	99% Bandwidth	17
5.1.	Block diagram of test setup	17
5.2.	Limits	17
5.3.	Test procedure	17
5.4.	Test result.....	18
5.5.	Test graphs	19
6.	Conducted Output Power	22
6.1.	Block diagram of test setup	22
6.2.	Limits	22
6.3.	Test procedure	22
6.4.	Test result average.....	23
7.	Power Spectral Density	24
7.1.	Block diagram of test setup	24
7.2.	Limits	24
7.3.	Test procedure	24
7.4.	Test result.....	25
7.5.	Test graphs	26
8.	Band Edge Compliance (Conducted Method).....	29
8.1.	Block diagram of test setup	29

8.2.	Limits	29
8.3.	Test procedure	29
8.4.	Test result.....	30
8.5.	Test graphs	31
9.	RF Conducted Spurious Emissions.....	33
9.1.	Block diagram of test setup	33
9.2.	Limits	33
9.3.	Test procedure	33
9.4.	Test result.....	34
9.5.	Test graphs	35
10.	Duty Cycle	44
10.1.	Block diagram of test setup	44
10.2.	Limit.....	44
10.3.	Test procedure	44
10.4.	Test result.....	45
10.5.	Test graphs	46
11.	Antenna Requirements.....	49
11.1.	Limit.....	49
11.2.	Result	49
12.	Radiated Emission	50
12.1.	Test equipment.....	50
12.2.	Block diagram of test setup	51
12.3.	Limits	52
12.4.	Assistant equipment used for test	54
12.5.	Test procedure	54
12.6.	Test result.....	56
12.7.	Test data	57
13.	Band Edge Compliance.....	65
13.1.	Test equipment.....	65
13.2.	Block diagram of test setup	65
13.3.	Limits	66
13.4.	Assistant equipment used for test	66
13.5.	Test procedure	66
13.6.	Test result.....	66
13.7.	Test data	67
14.	Power Line Conducted Emissions.....	79
14.1.	Test equipment.....	79
14.2.	Block diagram of test setup	79

14.3. Limits79

14.4. Assistant equipment used for test79

14.5. Test procedure79

14.6. Test result.....80

14.7. Test data81

15. Test Setup Photograph83

16. Photos of the EUT86

Test Report Declare

Applicant	:	GLOBE ELECTRIC COMPANY INC.
Address of Applicant	:	150 Oneida, Montreal, Quebec, Canada, H9R 1A8
Equipment under Test	:	Ceiling Fan
Model No.	:	37000119
Manufacturer	:	Satellite Electronics (Zhong shan) Co Ltd.
Address of Manufacturer	:	No.8, Chuang Ye Road, Torch Development Zone, Zhongshan, Guangdong, China

Test Standard Used:

FCC Rules and Regulations Part 15 Subpart C,
ANSI C63.10-2020+Cor.1-2023,
RSS-247 Issue 4 July 24, 2025,
RSS-Gen Issue 5, Apr. 2018, Amendment 2 (February 2021),
ANSI C63.10-2020+Cor.1-2023+C63.10a-2024+Errata to C63.10a-2024

We Declare:

The equipment described above is tested by Guangdong Dongdian Testing Service Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Guangdong Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

Report No.:	DDT-RE26060401-2E02		
Date of Receipt:	2026/06/04	Date of Test:	2026/06/22 - 2026/08/04

Created: Bobo Chen	Reviewed: Tiger Mo	Approved: Ella Gong
		
2026/07/30	2026/09/08	2026/09/08

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Guangdong Dongdian Testing Service Co., Ltd.

Revision History

Version	Revision Content	Issue Date	Approved
V0	Initial issue	2026/09/08	Ella Gong

1. Summary of Test Results

No.	Test Parameter	Clause No.	Condition	Result
1	6 dB Bandwidth and 99% Bandwidth	47 CFR Part 15 15.247(a)(2), RSS-247 clause 6.3.1(a), RSS-Gen clause 6.7	/	Pass
2	Peak Output Power	47 CFR Part 15 15.247(b)(3), RSS-247 clause 6.3.2	/	Pass
3	Power Spectral Density	47 CFR Part 15 15.247(e), RSS-247 clause 6.3.1(b)	/	Pass
4	RF Conducted Spurious Emissions	47 CFR Part 15 15.247(d), RSS-247 clause 6.6	/	Pass
5	Radiated Emission	47 CFR Part 15 15.205, 47 CFR Part 15 15.209, 47 CFR Part 15 15.247(d), RSS-247 clause 6.6, RSS-Gen clause 8.9, RSS-Gen clause 8.10	/	Pass
6	Band Edge Compliance	47 CFR Part 15 15.205, 47 CFR Part 15 15.209, 47 CFR Part 15 15.247(d), RSS-247 clause 6.6, RSS-Gen clause 8.9, RSS-Gen clause 8.10	/	Pass
7	Antenna Requirement	47 CFR Part 15 15.203, RSS-Gen clause 6.8	/	Pass
8	Power Line Conducted Emissions	47 CFR Part 15 15.207(a), RSS-Gen clause 8.8	/	Pass

Note: N/A is an abbreviation for Not Applicable, and means this item is not applicable for this device or no need to test according to standard.

2. General Test Information

2.1. Description of EUT

EUT Name	:	Ceiling Fan
Model Number	:	37000119
EUT Function Description	:	Please reference user manual of this device
Power Supply	:	AC 120V/60Hz
Antenna Type	:	PCB Antenna
Max Antenna Gain(dBi)	:	-0.23

Radio Technology	:	IEEE 802.11b/g/n
Operation frequency	:	IEEE 802.11b: 2412MHz to 2462MHz IEEE 802.11g: 2412MHz to 2462MHz IEEE 802.11n HT20: 2412MHz to 2462MHz
Modulation	:	IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK)

Channel information					
CH	Frequency (MHz)	CH	Frequency (MHz)	CH	Frequency (MHz)
1	2412	5	2432	9	2452
2	2417	6	2437	10	2457
3	2422	7	2442	11	2462
4	2427	8	2447	/	/


Note: The above EUT information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications or User's Manual. The above Antenna information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

“☑” means to be chosen or applicable; “☐” means don't to be chosen or not applicable; This note applies to entire report.

2.2. Accessories of EUT

Accessories	Manufacturer	Model number	Description
/	/	/	/

2.3. Block diagram of EUT configuration for test



2.4. Decision of final test mode

According pre-test, the worst test modes were reported as below:

Test software: Wifi Test Tool v1.7.4.exe

The test software was used to control EUT work in Continuous Tx mode and select test channel, wireless mode as below table.

The pathloss of external cable: 0.5dB (According to the manufacturer's claims)

Tested mode, Tx Power Setting, Data rate, Channel, and Frequency				
Tested mode	Tx Power Setting	Data rate (Mbps) (see Note)	Test Channel	Frequency (MHz)
	ANT1			
IEEE 802.11b	60	1	LCH: CH1	2412
	60	1	MCH: CH6	2437
	60	1	HCH: CH11	2462
IEEE 802.11g	55	6	LCH: CH1	2412
	55	6	MCH: CH6	2437
	55	6	HCH: CH11	2462
IEEE 802.11n HT20	50	MCS 0	LCH: CH1	2412
	50	MCS 0	MCH: CH6	2437
	50	MCS 0	HCH: CH11	2462
Note: According exploratory test, EUT will have maximum output power in those data rate, so those data rate were used for all test.				

2.5. Deviations of test standard

No deviation.

2.6. Test environment conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature range:	+15°C to +35 °C
Humidity range:	20% to 75%
Pressure range:	86 kPa to106 kPa

Note: The specific temperature and humidity information of each test item refers to the temperature and humidity record in the corresponding test data.

2.7. Test laboratory

Guangdong Dongdian Testing Service Co., Ltd.

Add.: Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808.

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: ddt@dgddt.com.

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, R-20240, G-20118

2.8. Measurement uncertainty


Test Item	Uncertainty
Bandwidth	1.9%
Peak Output Power (Conducted) (Spectrum analyzer)	0.98 dB
Peak Output Power (Conducted) (Power Sensor)	1.18 dB
Power Spectral Density (Base EIRP)	1.51 dB
Power Spectral Density (Spectrum analyzer)	0.98 dB
Frequencies Stability	1.9 kHz
Conducted spurious emissions	1.21 dB ($9 \text{ kHz} \leq f < 7 \text{ GHz}$);
	3.31 dB ($7 \text{ GHz} \leq f < 40 \text{ GHz}$)
Uncertainty for radio frequency (RBW < 20 kHz)	5.5×10^{-8}
Time	0.11%
Temperature	0.3 °C
Humidity	2 %
Uncertainty for Radiation Emission test (9 kHz – 30 MHz)	3.44 dB
Uncertainty for Radiation Emission test (30 MHz - 1 GHz)	4.28 dB (Antenna Polarize: V)
	4.14 dB (Antenna Polarize: H)
Uncertainty for Radiation Emission test (1 GHz - 40 GHz)	4.22 dB (1 - 6 GHz)
	4.52 dB (6 GHz - 18 GHz)
	4.58 dB (18 GHz - 40 GHz)
Uncertainty for Power line conduction emission test	3.32dB (150KHz-30MHz)
	3.72dB (9KHz-150KHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

3. Equipment Used During Conductive Test

Equipment	Manufacturer	Model No.	Serial Number	Due Date
☒ RF Connected Test (RF Measurement System 3#)				
SIGNAL ANALYZER	R&S	FSV40	101407	2027/07/10
Wideband Radio Communication Tester	R&S	CMW500	120259	2027/07/10
EXG Analog Signal Generator	KEYSIGHT	N5173B	MY62153058	2027/06/21
MXG Vector Signal Generator	Agilent	N5182A	MY48180912	2027/02/27
RF Control Unit	Tonscend	JS0806-2	20C8060230	2027/03/17
TEMP&HUMI Programmable Chamber	ZHIXIANG	ZXGDJS-150L	ZX170110-A	2027/02/27
Test Software	Tonscend	JS1120-3	V3.6.21	N/A

4. 6dB Bandwidth

4.1. Block diagram of test setup



4.2. Limits

For direct sequence systems, the minimum 6 dB bandwidth shall be at least 500 kHz

4.3. Test procedure

- (1) The test according to ANSI C63.10 clause 11.8.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously
- (4) Use the following spectrum analyzer settings for 6 dB Bandwidth:

RBW:	100 kHz
VBW:	$\geq [3 \times \text{RBW}]$
Detector Mode:	peak
Sweep time:	auto
Trace mode	max hold


Allow the trace to stabilize, measure the 6 dB bandwidth of signal, and record the results in the report


4.4. Test result

Test Engineer:	Zora Zhang	Test Site:	RF Measurement System 3#
Ambient Condition:	27.3℃,52.7%RH	Test Date:	2026.8.3
Test Power Supply:	DC3.3V	Sample Number:	S26060401-002

Test Mode	Antenna	Frequency [MHz]	DTS BW [MHz]	FL [MHz]	FH [MHz]	Limit [MHz]	Verdict
11B	Ant1	2412	8.68	2407.84	2416.52	0.5	PASS
		2437	8.28	2432.84	2441.12	0.5	PASS
		2462	8.72	2457.80	2466.52	0.5	PASS
11G	Ant1	2412	17.40	2403.28	2420.68	0.5	PASS
		2437	16.12	2428.12	2444.24	0.5	PASS
		2462	17.48	2453.12	2470.60	0.5	PASS
11N20SISO	Ant1	2412	15.36	2404.20	2419.56	0.5	PASS
		2437	15.32	2429.16	2444.48	0.5	PASS
		2462	15.32	2454.20	2469.52	0.5	PASS

4.5. Test graphs








5. 99% Bandwidth

5.1. Block diagram of test setup



5.2. Limits

Just for Report.

5.3. Test procedure

- (1) The test according to ANSI C63.10 clause 6.9.3.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously
- (4) Use the following spectrum analyzer settings for the 99% Bandwidth:

RBW:	1% to 5% of the OBW
VBW:	approximately three times RBW
Span:	between 1.5 times and 5.0 times the OBW
Detector Mode:	peak
Sweep time:	auto
Trace mode	max hold


Allow the trace to stabilize, measure the 99% bandwidth of signal, and record the results in the report.


5.4. Test result

Test Engineer:	Zora Zhang	Test Site:	RF Measurement System 3#
Ambient Condition:	27.3℃,52.7%RH	Test Date:	2026.8.3
Test Power Supply:	DC 3.3V	Sample Number:	S26060401-002

Test Mode	Antenna	Channel Frequency[MHz]	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	13.946	2404.7273	2418.7133	---	---
		2437	13.906	2429.7273	2443.7133	---	---
		2462	13.906	2454.7672	2468.7932	---	---
11G	Ant1	2412	17.662	2403.0889	2420.8312	---	---
		2437	17.702	2428.0889	2445.8312	---	---
		2462	17.702	2453.1289	2470.8312	---	---
11N20SISO	Ant1	2412	17.822	2402.6893	2421.2308	---	---
		2437	17.822	2427.6893	2446.3107	---	---
		2462	17.742	2452.6094	2471.3506	---	---

5.5. Test graphs








6. Conducted Output Power

6.1. Block diagram of test setup



6.2. Limits

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

6.3. Test procedure

- (1) The test according to ANSI C63.10 clause 11.9.2.3.
- (2) Connect EUT's antenna output to RF power meter by RF cable, the path loss was compensated to the results.
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously, If the transmitter does not transmit continuously, measure the duty cycle, D, of the transmitter output signal.
- (4) Measure the average power of the transmitter. This measurement is an average over both the ON and OFF periods of the transmitter.
- (5) Adjust the measurement in dBm by adding $[10 \log (1 / D)]$, where D is the duty cycle.
- (6) Record the RF average power of each antenna port.

6.4. Test result average


Test Engineer:	Zora Zhang	Test Site:	RF Measurement System 3#
Ambient Condition:	27.3℃,52.7%RH	Test Date:	2026.8.3
Test Power Supply:	DC 3.3V	Sample Number:	#snvalue

Test Mode	Antenna	Frequency [MHz]	Average power [dBm]	Duty Cycle [%]	DC Factor [dB]	Result [dBm]	Limit [dBm]	EIRP [dBm]	EIRP Limit [dBm]	Verdict
11B	Ant1	2412	9.59	98.94	0.05	9.64	≤30.00	9.41	≤36.00	PASS
		2437	9.21	98.94	0.05	9.26	≤30.00	9.03	≤36.00	PASS
		2462	9.37	98.94	0.05	9.42	≤30.00	9.19	≤36.00	PASS
11G	Ant1	2412	4.33	98.92	0.05	4.38	≤30.00	4.15	≤36.00	PASS
		2437	4.12	98.92	0.05	4.17	≤30.00	3.94	≤36.00	PASS
		2462	4.36	98.92	0.05	4.41	≤30.00	4.18	≤36.00	PASS
11N20SISO	Ant1	2412	4.05	100.00	0.00	4.05	≤30.00	3.82	≤36.00	PASS
		2437	3.87	100.00	0.00	3.87	≤30.00	3.64	≤36.00	PASS
		2462	4.07	100.00	0.00	4.07	≤30.00	3.84	≤36.00	PASS

Note: EIRP (dBm)=Conducted Output Power (dBm)+ Antenna Gain (dBi)

7. Power Spectral Density

7.1. Block diagram of test setup



7.2. Limits

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

7.3. Test procedure

- (1) The test according to ANSI C63.10 clause 11.10.5.
- (2) Connect EUT’s antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results.
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously.
- (4) Use the following spectrum analyzer settings for Power Spectral Density measurement:

Center frequency	DTS Channel center frequency
RBW:	3 kHz ≤ RBW ≤ 100 kHz
VBW:	≥ 3RBW
Span	1.5 times the DTS bandwidth
Detector Mode:	RMS
Sweep time:	auto
Trace mode	max hold
	Employ trace averaging (rms)
Trace	mode over a minimum of 100 traces.

- (5) Add [10 log (1 / D)], where D is the duty cycle measured in step a), to the measured PSD to compute the average PSD during the actual transmission time.
If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.


7.4. Test result


Test Engineer:	Zora Zhang	Test Site:	RF Measurement System 3#
Ambient Condition:	27.3℃,52.7%RH	Test Date:	2026.8.3
Test Power Supply:	DC 3.3V	Sample Number:	S26060401-002


Test Mode	Antenna	Frequency [MHz]	Result[dBm/3-100kHz]	Limit[dBm/3kHz]	Verdict
11B	Ant1	2412	-16.19	≤8.00	PASS
		2437	-16.50	≤8.00	PASS
		2462	-15.58	≤8.00	PASS
11G	Ant1	2412	-16.03	≤8.00	PASS
		2437	-15.65	≤8.00	PASS
		2462	-15.10	≤8.00	PASS
11N20SISO	Ant1	2412	-15.65	≤8.00	PASS
		2437	-15.74	≤8.00	PASS
		2462	-15.21	≤8.00	PASS

Note: The Duty Cycle Factor is compensated in the graph.

7.5. Test graphs








8. Band Edge Compliance (Conducted Method)

8.1. Block diagram of test setup



8.2. Limits

In any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 30 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.

8.3. Test procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Establish a reference level by using the following procedure:

RBW:	100 kHz
VBW:	300 kHz
Span	Encompass frequency range to be measured
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(3) Allow the trace to stabilize, use the peak marker function to determine the maximum peak power level to establish the reference level.


Then mark the maximum amplitude of all unwanted emissions outside of the authorized frequency band.


8.4. Test result

Test Engineer:	Zora Zhang	Test Site:	RF Measurement System 3#
Ambient Condition:	27.3℃,52.7%RH	Test Date:	2026.8.3
Test Power Supply:	DC 3.3V	Sample Number:	S26060401-002

EUT Set Mode	CH or Frequency	Result(dBm)	EUT Set Mode	CH or Frequency	Result (dBm)
11b	CH1	Pass	11g	CH1	Pass
	CH11	Pass		CH11	Pass
11n HT 20	CH1	Pass	/	/	/
	CH11	Pass		/	/


8.5. Test graphs





9. RF Conducted Spurious Emissions

9.1. Block diagram of test setup



9.2. Limits

In any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 30 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.

9.3. Test procedure

- (1) Connect EUT’s antenna output to spectrum analyzer by RF cable.

(2) Establish a reference level by using the following procedure:

Center frequency	Test frequency
RBW:	100 kHz
VBW:	300 kHz
Span	Wide enough to capture the peak level of the in-band emission
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(3) Allow the trace to stabilize, use the peak marker function to determine the maximum peak power level to establish the reference level.

(4) Set the spectrum analyzer as follows:

RBW:	100 kHz
VBW:	300 kHz
Span	Encompass frequency range to be measured
Number of measurement points	≥Span/RBW
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(5) Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude of all unwanted emissions outside of the authorized frequency band

9.4. Test result

Test Engineer:	Zora Zhang	Test Site:	RF Measurement System 3#
Ambient Condition:	27.3℃,52.7%RH	Test Date:	2026.8.3
Test Power Supply:	DC 3.3V	Sample Number:	S26060401-002

EUT Set Mode	CH or Frequency	Result(dBm)	EUT Set Mode	CH or Frequency	Result (dBm)
11b	CH1	Pass	11g	CH1	Pass
	CH6	Pass		CH6	Pass
	CH11	Pass		CH11	Pass
11n HT 20	CH1	Pass	/	/	/
	CH6	Pass		/	/
	CH11	Pass		/	/

9.5. Test graphs

