



## MEASUREMENT REPORT

**FCC ID** : 2AQVB-DN2458G

**APPLICANT** : Taisync Technology Inc.

**Application Type** : Certification

**Product** : 2.4&5.8GHz HD Wireless Link

**Model No.** : WVL-A2458J28TTVX32\_I\_US

**Series Model No.** : WVL-A2458J28TTVX32\_S\_US

**Brand Name** : Viulinx

**FCC Classification** : Unlicensed National Information Infrastructure (UNII)

**FCC Rule Part(s)** : Part 15 Subpart E (Section 15.407)

**Test Procedure(s)** : ANSI C63.10-2020+Cor 1-2023+C63.10a-2024 + Errata to C63.10a-2024

**Received Date** : October 22, 2025

**Test Date** : October 23, 2025~November 26, 2025

**Tested By** : *Kaunaz Lee*  
( Kaunaz Lee )

**Reviewed By** : *Paddy Chen*  
( Paddy Chen )

**Approved By** : *Chenz Ker*  
( Chenz Ker )



The test results only relate to the tested samples.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10 Test results reported herein relate only to the item(s) tested.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Taiwan) Co., Ltd.

## Revision History

| Report No.    | Version | Description     | Issue Date | Note |
|---------------|---------|-----------------|------------|------|
| 2510TW0109-U2 | 1.0     | Original Report | 2025-12-03 |      |

## CONTENTS

| Description                                                  | Page      |
|--------------------------------------------------------------|-----------|
| <b>1. INTRODUCTION .....</b>                                 | <b>6</b>  |
| 1.1. Scope .....                                             | 6         |
| 1.2. MRT Test Location .....                                 | 6         |
| <b>2. PRODUCT INFORMATION .....</b>                          | <b>7</b>  |
| 2.1. Equipment Description.....                              | 7         |
| 2.2. Product Specification Subjective to this Standard ..... | 8         |
| 2.3. Operation Frequencies and Channel List.....             | 9         |
| 2.4. Test Mode .....                                         | 10        |
| 2.5. Test Configuration .....                                | 11        |
| 2.6. Test System Details.....                                | 11        |
| 2.7. Test Software.....                                      | 11        |
| 2.8. Duty Cycles .....                                       | 12        |
| 2.9. Test Configuration .....                                | 12        |
| 2.10. EMI Suppression Device(s)/Modifications .....          | 12        |
| 2.11. Labeling Requirements.....                             | 12        |
| <b>3. DESCRIPTION OF TEST .....</b>                          | <b>13</b> |
| 3.1. Evaluation Procedure .....                              | 13        |
| 3.2. AC Line Conducted Emissions .....                       | 13        |
| 3.3. Radiated Emissions.....                                 | 14        |
| <b>4. ANTENNA REQUIREMENTS.....</b>                          | <b>15</b> |
| <b>5. TEST EQUIPMENT CALIBRATION DATE.....</b>               | <b>16</b> |
| <b>6. MEASUREMENT UNCERTAINTY.....</b>                       | <b>17</b> |
| <b>7. TEST RESULT .....</b>                                  | <b>18</b> |
| 7.1. Summary.....                                            | 18        |
| 7.2. 26dB Bandwidth Measurement.....                         | 19        |
| 7.2.1. Test Limit .....                                      | 19        |
| 7.2.2. Test Procedure used.....                              | 19        |
| 7.2.3. Test Setting.....                                     | 19        |
| 7.2.4. Test Setup .....                                      | 19        |
| 7.2.5. Test Result.....                                      | 20        |
| 7.3. 6dB Bandwidth Measurement.....                          | 22        |
| 7.3.1. Test Limit .....                                      | 22        |

---

|                                                      |           |
|------------------------------------------------------|-----------|
| 7.3.2. Test Procedure used.....                      | 22        |
| 7.3.3. Test Setting.....                             | 22        |
| 7.3.4. Test Setup .....                              | 22        |
| 7.3.5. Test Result.....                              | 23        |
| 7.4. Output Power Measurement.....                   | 25        |
| 7.4.1. Test Limit .....                              | 25        |
| 7.4.2. Test Procedure Used .....                     | 25        |
| 7.4.3. Test Setting.....                             | 26        |
| 7.4.4. Test Setup .....                              | 26        |
| 7.4.5. Test Result.....                              | 27        |
| 7.5. Power Spectral Density Measurement.....         | 29        |
| 7.5.1. Test Limit .....                              | 29        |
| 7.5.2. Test Procedure Used .....                     | 29        |
| 7.5.3. Test Setting.....                             | 30        |
| 7.5.4. Test Setup .....                              | 30        |
| 7.5.5. Test Result.....                              | 31        |
| 7.6. Radiated Spurious Emission Measurement .....    | 34        |
| 7.6.1. Test Limit .....                              | 34        |
| 7.6.2. Test Procedure Used .....                     | 34        |
| 7.6.3. Test Setting.....                             | 34        |
| 7.6.4. Test Setup .....                              | 36        |
| 7.6.5. Test Result.....                              | 38        |
| 7.7. Radiated Restricted Band Edge Measurement ..... | 58        |
| 7.7.1. Test Limit .....                              | 58        |
| 7.7.2. Test Result.....                              | 61        |
| 7.8. AC Conducted Emissions Measurement .....        | 73        |
| 7.8.1. Test Limit .....                              | 73        |
| 7.8.2. Test Procedure .....                          | 73        |
| 7.8.3. Test Setup .....                              | 74        |
| 7.8.4. Test Result.....                              | 75        |
| <b>8. CONCLUSION .....</b>                           | <b>79</b> |
| <b>Appendix A : Test Photograph .....</b>            | <b>80</b> |
| <b>Appendix B : External Photograph.....</b>         | <b>80</b> |
| <b>Appendix C : Internal Photograph.....</b>         | <b>80</b> |

## General Information

|                                 |                                                                                                                                  |
|---------------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| <b>Applicant</b>                | Taisync Technology Inc.                                                                                                          |
| <b>Applicant Address</b>        | 2051 Junction Ave. Ste 115, San Jose, CA 95131                                                                                   |
| <b>Manufacturer</b>             | Taisync Technology Inc.                                                                                                          |
| <b>Manufacturer Address</b>     | 2051 Junction Ave. Ste 115, San Jose, CA 95131                                                                                   |
| <b>Test Site</b>                | MRT Technology (Taiwan) Co., Ltd                                                                                                 |
| <b>Test Site Address</b>        | No. 38, Fuxing Second Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C)                                                       |
| <b>MRT FCC Registration No.</b> | 291082                                                                                                                           |
| <b>Test Device Serial No.</b>   | #1-1 <input type="checkbox"/> Production <input checked="" type="checkbox"/> Pre-Production <input type="checkbox"/> Engineering |

## Test Facility / Accreditations

Measurements were performed at MRT Laboratory located in Fuxing Rd., Taoyuan, Taiwan ( R.O.C )

- MRT facility is a FCC registered (Reg. No. 291082) test facility with the site description report on file and is designated by the FCC as an Accredited Test Firm.
- MRT facility is an IC registered (MRT Reg. No. 21723) test laboratory with the site description on file at Industry Canada.
- MRT Lab is accredited to ISO 17025 by the Taiwan Accreditation Foundation (TAF Cert. No. 3261) in EMC, Telecommunications and Radio testing for FCC (Designation Number: TW3261), Industry Canada, EU and TELEC Rules.


# 1. INTRODUCTION

## 1.1. Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

## 1.2. MRT Test Location

The map below shows the location of the MRT LABORATORY, its proximity to the Taoyuan City. These measurement tests were conducted at the MRT Technology (Taiwan) Co., Ltd. Facility located at No.38, Fuxing 2nd Rd., Guishan Dist., Taoyuan City 33377, Taiwan (R.O.C).



## 2. PRODUCT INFORMATION

### 2.1. Equipment Description

|                  |                             |
|------------------|-----------------------------|
| Product Name     | 2.4&5.8GHz HD Wireless Link |
| Model No.        | WVL-A2458J28TTVX32_I_US     |
| Series Model No. | WVL-A2458J28TTVX32_S_US     |
| Specification    | SRD 2.4GHz & 5.8GHz         |

Note:

1. Model Difference: WVL-A2458J28TTVX32\_S\_US is SMA connector, WVL-A2458J28TTVX32\_I\_US is IPEX connector, the other hardware was the same. (declared by the manufacturer)
2. The test was performed base on WVL-A2458J28TTVX32\_I\_US.

## 2.2. Product Specification Subjective to this Standard

|                     |                     |
|---------------------|---------------------|
| Operating Frequency | 5731~5799MHz        |
| Channel Number      | 4                   |
| Type of modulation  | OFDM                |
| Channel Bandwidth   | 10MHz               |
| Data Rate           | 2.08Mbps ~ 6.57Mbps |
| RF Port             | 2                   |

Note: The product works with only one port at a time.

### 2.3. Operation Frequencies and Channel List

| Channel | Frequency | Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|---------|-----------|
| 01      | 5731 MHz  | 02      | 5765 MHz  | 03      | 5782 MHz  |
| 04      | 5799 MHz  | --      | --        | --      | --        |


## 2.4. Test Mode

|           |                                                                                |
|-----------|--------------------------------------------------------------------------------|
| Test Mode | Mode 1: Transmit by 5.8GHz with Ant 1<br>Mode 2: Transmit by 5.8GHz with Ant 2 |
|-----------|--------------------------------------------------------------------------------|

Note: Regarding to the operation frequency, the lowest, middle and highest frequency are selected to perform the test.

## 2.5. Test Configuration

This device was tested per the guidance of ANSI C63.10-2020. ANSI C63.10-2020 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing.



## 2.6. Test System Details

The types for all equipments, plus descriptions of all cables used in the tested system (including inserted cards) are:

|   | Product     | Manufacturer | Model No. | Serial No. | Power Cord         |
|---|-------------|--------------|-----------|------------|--------------------|
| 1 | Notebook PC | Lenovo       | T450      | N/A        | Non-shielded, 0.8m |

## 2.7. Test Software

The test utility software used during testing was "calibration.html".

## 2.8. Duty Cycles

| Test Mode | Duty Cycle |
|-----------|------------|
| 5.8GHz    | 90.50%     |

## 2.9. Test Configuration

This device was tested per the guidance of KDB 789033 D02v02r01. ANSI C63.10-2020 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing.

## 2.10. EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

## 2.11. Labeling Requirements

Per 2.1074 & 15.19; Docket 95-19

The label shall be permanently affixed at a conspicuous location on the device; instruction manual or pamphlet supplied to the user and be readily visible to the purchaser at the time of purchase. However, when the device is so small wherein placement of the label with specified statement is not practical, only the FCC ID must be displayed on the device per Section 15.19(a)(5). Please see attachment for FCC ID label and label location.

### **3. DESCRIPTION OF TEST**

#### **3.1. Evaluation Procedure**

The measurement procedures described in the American National Standard for Testing Unlicensed Wireless Devices (ANSI C63.10-2020+Cor 1-2023+C63.10a-2024 + Errata to C63.10a-2024), and the guidance provided in KDB 789033 were used in the measurement of the device.

#### **3.2. AC Line Conducted Emissions**

The line-conducted facility is located inside an 9'x4'x3' shielded enclosure. A 1m x 2m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50 $\Omega$ /50uH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference ground-plane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the receiver and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The receiver was scanned from 150kHz to 30MHz. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 9kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Each emission was also maximized by varying: power lines, the mode of operation or data exchange speed, or support equipment whichever determined the worst-case emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions are used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

An extension cord was used to connect to a single LISN which powered by EUT. The extension cord was calibrated with LISN, the impedance and insertion loss are compliance with the requirements as stated in ANSI C63.10-2020.

Line conducted emissions test results are shown in Section 7.10.

### 3.3. Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. For measurements above 1GHz absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1GHz, the absorbers are removed. A turntable is used for radiated measurement. It is a continuously rotatable, remote controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm high PVC support structure is placed on top of the turntable.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33(b)(1) depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up for frequencies below 1GHz was placed on top of the 0.8 meter high, 1 x 1.5 meter table; and test set-up for frequencies 1-40GHz was placed on top of the 1.5 meter high, 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, clock speed, mode of operation or video resolution, if applicable, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions. According to 3dB Beam-Width of horn antenna, the horn antenna should be always directed to the EUT when rising height.

## 4. ANTENNA REQUIREMENTS

### Excerpt from §15.203 of the FCC Rules/Regulations:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antenna of the **2.4&5.8GHz HD Wireless Link**, is permanently attached.
- There are no provisions for connection to an external antenna.

### Conclusion:

The EUT unit complies with the requirement of §15.203.

### Antenna List

| No. | Manufacturer   | Part No.     | Antenna Type | Peak Gain                      |
|-----|----------------|--------------|--------------|--------------------------------|
| 1   | Be-Comfortable | N12-7419-R0A | Dipole       | 2.4G: 5.02dBi<br>5.8G: 4.95dBi |

Note: Ant1, Ant2 have the same gain.

## 5. TEST EQUIPMENT CALIBRATION DATE

### Conducted Emissions

| Instrument         | Manufacturer | Type No. | Asset No.   | Cali. Interval | Cali. Due Date |
|--------------------|--------------|----------|-------------|----------------|----------------|
| Two-Line V-Network | R&S          | ENV216   | MRTTWA00019 | 1 year         | 2026/3/5       |
| Two-Line V-Network | R&S          | ENV216   | MRTTWA00020 | 1 year         | 2026/4/14      |
| EMI Test Receiver  | R&S          | ESR3     | MRTTWA00045 | 1 year         | 2026/5/13      |

### Radiated Emissions

| Instrument                 | Manufacturer | Type No.                  | Asset No.   | Cali. Interval | Cali. Due Date |
|----------------------------|--------------|---------------------------|-------------|----------------|----------------|
| Active Loop Antenna        | SCHWARZBECK  | FMZB 1519B                | MRTTWA00002 | 1 year         | 2026/4/16      |
| Broadband TRILOG Antenna   | SCHWARZBECK  | VULB 9162                 | MRTTWA00086 | 1 year         | 2025/12/4      |
| Broadband Hornantenna      | SCHWARZBECK  | BBHA 9120D                | MRTTWA00003 | 1 year         | 2026/2/11      |
| Broadband Preamplifier     | SCHWARZBECK  | BBV 9718                  | MRTTWA00005 | 1 year         | 2026/2/11      |
| Breitband Hornantenna      | SCHWARZBECK  | BBHA 9170                 | MRTTWA00004 | 1 year         | 2026/3/27      |
| Broadband Amplifier        | SCHWARZBECK  | BBV 9721                  | MRTTWA00006 | 1 year         | 2026/3/20      |
| EMI Test Receiver          | R&S          | ESR3                      | MRTTWA00009 | 1 year         | 2026/3/4       |
| Signal Analyzer            | R&S          | FSV40                     | MRTTWA00007 | 1 year         | 2026/5/20      |
| Antenna Cable              | HUBERSUHNER  | SF106                     | MRTTWE00010 | 1 year         | 2026/6/13      |
| Cable                      | Rosnol       | K1K50-UP0264-<br>K1K50-4M | MRTTWE00012 | 1 year         | 2026/6/13      |
| Temperature/Humidity Meter | TFA          | 35.1083                   | MRTTWA00032 | 1 year         | 2026/6/5       |

### Conducted Test Equipment

| Instrument                | Manufacturer | Type No. | Asset No.   | Cali. Interval | Cali. Due Date |
|---------------------------|--------------|----------|-------------|----------------|----------------|
| EXA Signal Analyzer       | KEYSIGHT     | N9010A   | MRTTWA00012 | 1 year         | 2026/10/20     |
| EXA Signal Analyzer       | KEYSIGHT     | N9010B   | MRTTWA00074 | 1 year         | 2026/7/14      |
| USB Wideband Power Sensor | KEYSIGHT     | U2021XA  | MRTTWA00014 | 1 year         | 2026/4/15      |

| Software | Manufacturer | Version No. |
|----------|--------------|-------------|
| e3       | Audix        | 9.160520a   |

## 6. MEASUREMENT UNCERTAINTY

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k = 2$ .

|                                                                                                                                                                                                                      |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Conducted Emission- Power Line                                                                                                                                                                                       |
| Measuring Uncertainty for a Level of Confidence of 95% ( $U=2U_c(y)$ ):<br>0.15MHz~30MHz: $\pm 2.53\text{dB}$                                                                                                        |
| Conducted Measurement                                                                                                                                                                                                |
| Measuring Uncertainty for a Level of Confidence of 95% ( $U=2U_c(y)$ ): $\pm 1.3\text{dB}$                                                                                                                           |
| Radiated Spurious Emission                                                                                                                                                                                           |
| Measuring Uncertainty for a Level of Confidence of 95% ( $U=2U_c(y)$ ):<br>9kHz~30MHz: $\pm 3.92\text{dB}$<br>30MHz~1GHz: $\pm 4.25\text{dB}$<br>1GHz~18GHz: $\pm 4.40\text{dB}$<br>18GHz~40GHz: $\pm 4.45\text{dB}$ |

## 7. TEST RESULT

### 7.1. Summary

**Company Name:** 2.4&5.8GHz HD Wireless Link

| FCC Section(s)                            | Test Description                                                              | Test Limit                                                                     | Test Condition | Test Result | Reference         |
|-------------------------------------------|-------------------------------------------------------------------------------|--------------------------------------------------------------------------------|----------------|-------------|-------------------|
| 15.407(a)                                 | 26dB Bandwidth                                                                | N/A                                                                            | Conducted      | Pass        | Section 7.2       |
| 15.407(e)                                 | 6dB Bandwidth                                                                 | $\geq 500\text{kHz}$                                                           |                | Pass        | Section 7.3       |
| 15.407(3)                                 | Maximum Conducted Output Power                                                | Refer to Section 7.5                                                           |                | Pass        | Section 7.4       |
| 15.407(3)                                 | Power Spectral Density                                                        | Refer to Section 7.7                                                           |                | Pass        | Section 7.5       |
| 15.407(b), (4)                            | Undesirable Emissions                                                         | $\leq -27\text{dBm/MHz EIRP}$<br>$\leq -17\text{dBm/MHz EIRP}$                 | Radiated       | Pass        | Section 7.6 & 7.7 |
| 15.205, 15.209<br>15.407(b)(8), (9), (10) | General Field Strength Limits (Restricted Bands and Radiated Emission Limits) | Emissions in restricted bands must meet the radiated limits detailed in 15.209 |                | Pass        |                   |
| 15.207                                    | AC Conducted Emissions<br>150kHz - 30MHz                                      | < FCC 15.207 limits                                                            | Line Conducted | Pass        | Section 7.8       |

**Notes:**

- Determining compliance is based on the test results met the regulation limits or requirements declared by clients, and the test results don't take into account the value of measurement uncertainty.

## 7.2. 26dB Bandwidth Measurement

### 7.2.1. Test Limit

N/A


### 7.2.2. Test Procedure used

KDB 789033 D02v02r01 - Section C.1

### 7.2.3. Test Setting

1. The analyzers' automatic bandwidth measurement capability was used to perform the 26dB bandwidth measurement. The "X" dB bandwidth parameter was set to  $X = 26$ . The automatic bandwidth measurement function also has the capability of simultaneously measuring the 99% occupied bandwidth. The bandwidth measurement was not influenced by any intermediated power nulls in the fundamental emission.
2. RBW = approximately 1% of the emission bandwidth.
3. VBW  $\geq 3 \times$  RBW.
4. Detector = Peak.
5. Trace mode = max hold.

### 7.2.4. Test Setup




### 7.2.5. Test Result

|               |                             |                   |                       |
|---------------|-----------------------------|-------------------|-----------------------|
| Product       | 2.4&5.8GHz HD Wireless Link | Temperature       | 25°C                  |
| Test Engineer | Aby                         | Relative Humidity | 54%                   |
| Test Site     | SR6                         | Test Date         | 2025/11/18~2025/11/25 |


| Test Mode    | Channel No. | Frequency (MHz) | 26dB Bandwidth (MHz) | 99% Bandwidth (MHz) | Limit (MHz) | Result |
|--------------|-------------|-----------------|----------------------|---------------------|-------------|--------|
| 5.8GHz_Ant 1 | CH01        | 5731            | 9.458                | 9.0000              | N/A         | Pass   |
|              | CH02        | 5765            | 9.439                | 9.0083              | N/A         | Pass   |
|              | CH03        | 5782            | 9.516                | 9.0147              | N/A         | Pass   |
|              | CH04        | 5799            | 13.620               | 9.0384              | N/A         | Pass   |

## Ant 1


### CH01 (5731MHz)




### CH02 (5765MHz)



### CH03 (5782MHz)



### CH04 (5799MHz)



### 7.3. 6dB Bandwidth Measurement

#### 7.3.1. Test Limit

The minimum 6dB bandwidth shall be at least 500 kHz.


#### 7.3.2. Test Procedure used

KDB 789033 D02v02r01 - Section C.2

#### 7.3.3. Test Setting

1. Set center frequency to the nominal EUT channel center frequency.
2. RBW = 100 kHz.
3. VBW  $\geq 3 \times$  RBW.
4. Detector = Peak.
5. Trace mode = max hold.
6. Sweep = auto couple.
7. Allow the trace to stabilize.
8. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

#### 7.3.4. Test Setup




### 7.3.5. Test Result

|               |                             |                   |                       |
|---------------|-----------------------------|-------------------|-----------------------|
| Product       | 2.4&5.8GHz HD Wireless Link | Temperature       | 25°C                  |
| Test Engineer | Aby                         | Relative Humidity | 54%                   |
| Test Site     | SR6                         | Test Date         | 2025/10/23~2025/11/26 |


| Test Mode    | Channel No. | Frequency (MHz) | 6dB Bandwidth (MHz) | 99% Bandwidth (MHz) | Limit (MHz) | Result |
|--------------|-------------|-----------------|---------------------|---------------------|-------------|--------|
| 5.8GHz_Ant 1 | CH01        | 5731            | 9.100               | 9.0736              | ≥ 0.5       | Pass   |
|              | CH02        | 5765            | 9.057               | 9.0086              | ≥ 0.5       | Pass   |
|              | CH03        | 5782            | 9.113               | 9.0151              | ≥ 0.5       | Pass   |
|              | CH04        | 5799            | 9.003               | 9.0618              | ≥ 0.5       | Pass   |

## Ant 1


### CH01 (5731MHz)




### CH02 (5765MHz)



### CH03 (5782MHz)



### CH04 (5799MHz)



## **7.4. Output Power Measurement**

### **7.4.1. Test Limit**

#### **For FCC Power Measurement Limit**

For client operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 250mW.

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW (23.98dBm) or 11dBm +10 log (26dB BW).

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W (30dBm).

If transmitting antennas of directional gain greater than 6dBi are used, the maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.


### **7.4.2. Test Procedure Used**

KDB 789033 D02v02r01 - Section E) 3) b) Method PM-G

### 7.4.3. Test Setting

Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter. The trace was averaged over 100 traces to obtain the final measured average power.

### 7.4.4. Test Setup



### 7.4.5. Test Result

|               |                             |                   |                       |
|---------------|-----------------------------|-------------------|-----------------------|
| Product       | 2.4&5.8GHz HD Wireless Link | Temperature       | 25°C                  |
| Test Engineer | Yang                        | Relative Humidity | 54%                   |
| Test Site     | SR6                         | Test Date         | 2025/10/23~2025/11/18 |

WVL-A2458J28TTVX32\_I\_US:

| Test Mode    | Channel No. | Frequency (MHz) | Average Power (dBm) | Power Limit (dBm) |
|--------------|-------------|-----------------|---------------------|-------------------|
| 5.8GHz_Ant 1 | CH01        | 5731            | 23.34               | < 30              |
|              | CH02        | 5765            | 23.25               | < 30              |
|              | CH03        | 5782            | 23.28               | < 30              |
|              | CH04        | 5799            | 21.25               | < 30              |
| 5.8GHz_Ant 2 | CH01        | 5731            | 23.88               | < 30              |
|              | CH02        | 5765            | 23.66               | < 30              |
|              | CH03        | 5782            | 23.62               | < 30              |
|              | CH04        | 5799            | 23.58               | < 30              |

Note1: Average Power =Reading value on power meter + cable loss.

## WVL-A2458J28TTVX32\_S\_US:

| Test Mode    | Channel No. | Frequency (MHz) | Average Power (dBm) | Power Limit (dBm) |
|--------------|-------------|-----------------|---------------------|-------------------|
| 5.8GHz_Ant 1 | CH01        | 5731            | 23.33               | < 30              |
|              | CH02        | 5765            | 23.21               | < 30              |
|              | CH03        | 5782            | 23.19               | < 30              |
|              | CH04        | 5799            | 21.21               | < 30              |
| 5.8GHz_Ant 2 | CH01        | 5731            | 23.78               | < 30              |
|              | CH02        | 5765            | 23.58               | < 30              |
|              | CH03        | 5782            | 23.51               | < 30              |
|              | CH04        | 5799            | 23.43               | < 30              |

Note1: Average Power =Reading value on power meter + cable loss.

## **7.5. Power Spectral Density Measurement**

### **7.5.1. Test Limit**

#### **For FCC Power Spectral Density Limit**

For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band.

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band.

For the band 5.725-5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band.

If transmitting antennas of directional gain greater than 6dBi are used, the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.


### **7.5.2. Test Procedure Used**

KDB 789033 D02v02r01 - Section F

### 7.5.3. Test Setting

1. Analyzer was set to the center frequency of the UNII channel under investigation
2. Span was set to encompass the entire 26dB EBW of the signal.
3. RBW = 1MHz, if measurement bandwidth of Maximum PSD is specified in 500 kHz,
4. RBW = 100 kHz
5. VBW = 3MHz
6. Number of sweep points  $\geq 2 \times (\text{span} / \text{RBW})$
7. Detector = power averaging (Average)
8. Sweep time = auto
9. Trigger = free run
10. Use the peak search function on the instrument to find the peak of the spectrum and record its value.
11. Add  $10 \cdot \log(1/x)$ , where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times (because the measurement represents an average over both the on and off times of the transmission). For example, add  $10 \cdot \log(1/0.25) = 6$  dB if the duty cycle is 25 percent.
12. When the measurement bandwidth of Maximum PSD is specified in 500 kHz, add a constant factor  $10 \cdot \log(500\text{kHz}/100\text{kHz}) = 7$  dB to the measured result

### 7.5.4. Test Setup



### 7.5.5. Test Result


|               |                             |                   |                      |
|---------------|-----------------------------|-------------------|----------------------|
| Product       | 2.4&5.8GHz HD Wireless Link | Temperature       | 25°C                 |
| Test Engineer | Aby                         | Relative Humidity | 54%                  |
| Test Site     | SR6                         | Test Date         | 2025/11/5~2025/11/18 |

| Test Mode    | Ch. No. | Freq.<br>(MHz) | Average PSD<br>(dBm/510KHz) | Duty<br>Cycle<br>(%) | Total PSD<br>(dBm/<br>510kHz) | Limit<br>(dBm/<br>500kHz) | Result |
|--------------|---------|----------------|-----------------------------|----------------------|-------------------------------|---------------------------|--------|
| 5.8GHz_Ant 1 | CH01    | 5731           | 12.326                      | 90.50%               | 12.760                        | ≤ 30                      | Pass   |
|              | CH02    | 5765           | 12.094                      | 90.50%               | 12.528                        | ≤ 30                      | Pass   |
|              | CH03    | 5782           | 12.194                      | 90.50%               | 12.628                        | ≤ 30                      | Pass   |
|              | CH04    | 5799           | 12.698                      | 90.50%               | 13.132                        | ≤ 30                      | Pass   |
| 5.8GHz_Ant 2 | CH01    | 5731           | 13.436                      | 90.50%               | 13.870                        | ≤ 30                      | Pass   |
|              | CH02    | 5765           | 12.892                      | 90.50%               | 13.326                        | ≤ 30                      | Pass   |
|              | CH03    | 5782           | 13.031                      | 90.50%               | 13.465                        | ≤ 30                      | Pass   |
|              | CH04    | 5799           | 11.988                      | 90.50%               | 12.422                        | ≤ 30                      | Pass   |


Note: Total PSD= Average PSD + 10\*log (1/Duty Cycle).

## Ant 1


### CH01 (5731MHz)




### CH02 (5765MHz)



### CH03 (5782MHz)




### CH04 (5799MHz)




## Ant 2


### CH01 (5731MHz)




### CH02 (5765MHz)



### CH03 (5782MHz)



### CH04 (5799MHz)



## 7.6. Radiated Spurious Emission Measurement

### 7.6.1. Test Limit

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table per Section 15.209.

| FCC Part 15 Subpart C Paragraph 15.209 |                         |                               |
|----------------------------------------|-------------------------|-------------------------------|
| Frequency<br>[MHz]                     | Field Strength<br>[V/m] | Measured Distance<br>[Meters] |
| 0.009 – 0.490                          | 2400/F (kHz)            | 300                           |
| 0.490 – 1.705                          | 24000/F (kHz)           | 30                            |
| 1.705 - 30                             | 30                      | 30                            |
| 30 - 88                                | 100                     | 3                             |
| 88 - 216                               | 150                     | 3                             |
| 216 - 960                              | 200                     | 3                             |
| Above 960                              | 500                     | 3                             |

### 7.6.2. Test Procedure Used

KDB 789033 D02v02r01 – Section G

### 7.6.3. Test Setting

#### **Peak Measurements above 1GHz**

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

**Quasi-Peak Measurements below 1GHz**

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. Span was set greater than 1MHz
3. RBW = 120 kHz
4. Detector = CISPR quasi-peak
5. Sweep time = auto couple
6. Trace was allowed to stabilize

**Average Measurements above 1GHz (Method AD)**


1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = power average (Average)
5. Number of measurement points = 1001 (Number of points must be  $> 2 \times \text{span/RBW}$ )
6. Sweep time = auto
7. Trace was averaged over at 100 sweeps

**Quasi-Peak & Average Measurements below 30MHz**


1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. Span was set greater than 1MHz
3. RBW = 200Hz for 9kHz to 150kHz frequency; RBW = 9kHz for 0.15MHz to 30MHz frequency
4. Detector = CISPR quasi-peak or power average (Average)
5. Sweep time = auto couple
6. Trace was allowed to stabilize

### 7.6.4. Test Setup


#### 9kHz ~ 30MHz Test Setup:




#### 30MHz ~ 1GHz Test Setup:



### 1GHz ~18GHz Test Setup:




### 18GHz ~40GHz Test Setup:



### 7.6.5. Test Result

|           |                             |                      |              |
|-----------|-----------------------------|----------------------|--------------|
| EUT       | 2.4&5.8GHz HD Wireless Link | Date of Test         | 2025-10-30   |
| Factor    | VULB 9162                   | Temp. / Humidity     | 24°C /65%    |
| Polarity  | Horizontal                  | Site / Test Engineer | AC1 / James  |
| Test Mode | SRD 5.8G_TX_5765MHz_ANT 1   | Test Voltage         | AC 120V/60Hz |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB/m) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Height (cm) | Angle (deg) | Remark (QP/PK/AV) |
|----|-----------------|----------------|------------|----------------------|-------------|----------------|-------------|-------------|-------------------|
| 1  | 102.108         | 19.67          | 18.86      | 38.53                | -4.97       | 43.50          | 150         | 360         | QP                |
| 2  | 159.924         | 10.75          | 16.03      | 26.78                | -16.72      | 43.50          | 100         | 295         | QP                |
| 3  | 225.779         | 13.02          | 19.29      | 32.32                | -13.68      | 46.00          | 100         | 315         | QP                |
| 4  | * 248.846       | 22.77          | 20.37      | 43.14                | -2.86       | 46.00          | 100         | 300         | QP                |
| 5  | 424.898         | 5.39           | 24.05      | 29.45                | -16.55      | 46.00          | 150         | 260         | QP                |
| 6  | 732.213         | 2.74           | 29.28      | 32.02                | -13.98      | 46.00          | 100         | 254         | QP                |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.
5. The amplitude of radiated emissions (frequency range from 9kHz to 30MHz) is that proximity to ambient noise, which also are attenuated more than 20dB below the permissible value. Therefore, the data is not presented in the report.

|           |                             |                      |              |
|-----------|-----------------------------|----------------------|--------------|
| EUT       | 2.4&5.8GHz HD Wireless Link | Date of Test         | 2025-10-30   |
| Factor    | VULB 9162                   | Temp. / Humidity     | 24°C /65%    |
| Polarity  | Vertical                    | Site / Test Engineer | AC1 / James  |
| Test Mode | SRD 5.8G_TX_5765MHz_ANT 1   | Test Voltage         | AC 120V/60Hz |




| No |   | Frequency (MHz) | Reading (dBuV) | C.F (dB/m) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Height (cm) | Angle (deg) | Remark (QP/PK/AV) |
|----|---|-----------------|----------------|------------|----------------------|-------------|----------------|-------------|-------------|-------------------|
| 1  | * | 31.875          | 18.05          | 17.75      | 35.81                | -4.20       | 40.00          | 100         | 210         | QP                |
| 2  |   | 98.948          | 10.90          | 18.71      | 29.61                | -13.89      | 43.50          | 150         | 50          | QP                |
| 3  |   | 161.442         | 7.88           | 16.08      | 23.96                | -19.54      | 43.50          | 100         | 255         | QP                |
| 4  |   | 248.226         | 17.14          | 20.34      | 37.48                | -8.52       | 46.00          | 150         | 280         | QP                |
| 5  |   | 422.647         | 10.07          | 24.03      | 34.11                | -11.89      | 46.00          | 100         | 215         | QP                |
| 6  |   | 731.274         | 3.57           | 29.26      | 32.83                | -13.17      | 46.00          | 150         | 250         | QP                |

Note:

- "\*", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB).
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- The emission levels of other frequencies are very lower than the limit and not show in test report.
- The amplitude of radiated emissions (frequency range from 9kHz to 30MHz) is that proximity to ambient noise, which also are attenuated more than 20dB below the permissible value. Therefore, the data is not presented in the report.

|           |                             |                      |              |
|-----------|-----------------------------|----------------------|--------------|
| EUT       | 2.4&5.8GHz HD Wireless Link | Date of Test         | 2025-10-30   |
| Factor    | VULB 9162                   | Temp. / Humidity     | 24°C /65%    |
| Polarity  | Horizontal                  | Site / Test Engineer | AC1 / James  |
| Test Mode | SRD 5.8G_TX_5765MHz_ANT 2   | Test Voltage         | AC 120V/60Hz |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB/m) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Height (cm) | Angle (deg) | Remark (QP/PK/AV) |
|----|-----------------|----------------|------------|----------------------|-------------|----------------|-------------|-------------|-------------------|
| 1  | * 106.784       | 21.20          | 18.78      | 39.99                | -3.51       | 43.50          | 150         | 360         | QP                |
| 2  | 159.941         | 10.55          | 16.03      | 26.58                | -16.92      | 43.50          | 100         | 295         | QP                |
| 3  | 221.957         | 14.34          | 19.05      | 33.39                | -12.61      | 46.00          | 100         | 315         | QP                |
| 4  | 248.396         | 21.91          | 20.34      | 42.25                | -3.75       | 46.00          | 100         | 300         | QP                |
| 5  | 424.676         | 5.12           | 24.05      | 29.17                | -16.83      | 46.00          | 150         | 260         | QP                |
| 6  | 732.694         | 2.52           | 29.29      | 31.80                | -14.20      | 46.00          | 100         | 254         | QP                |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.
5. The amplitude of radiated emissions (frequency range from 9kHz to 30MHz) is that proximity to ambient noise, which also are attenuated more than 20dB below the permissible value. Therefore, the data is not presented in the report.

|           |                             |                      |              |
|-----------|-----------------------------|----------------------|--------------|
| EUT       | 2.4&5.8GHz HD Wireless Link | Date of Test         | 2025-10-30   |
| Factor    | VULB 9162                   | Temp. / Humidity     | 24°C /65%    |
| Polarity  | Vertical                    | Site / Test Engineer | AC1 / James  |
| Test Mode | SRD 5.8G_TX_5765MHz_ANT 2   | Test Voltage         | AC 120V/60Hz |




| No |   | Frequency (MHz) | Reading (dBuV) | C.F (dB/m) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Height (cm) | Angle (deg) | Remark (QP/PK/AV) |
|----|---|-----------------|----------------|------------|----------------------|-------------|----------------|-------------|-------------|-------------------|
| 1  | * | 30.540          | 18.52          | 17.53      | 36.05                | -3.96       | 40.00          | 100         | 210         | QP                |
| 2  |   | 99.051          | 10.75          | 18.72      | 29.48                | -14.02      | 43.50          | 150         | 50          | QP                |
| 3  |   | 161.743         | 7.79           | 16.09      | 23.87                | -19.63      | 43.50          | 100         | 255         | QP                |
| 4  |   | 248.834         | 16.79          | 20.37      | 37.16                | -8.84       | 46.00          | 150         | 280         | QP                |
| 5  |   | 422.314         | 11.14          | 24.03      | 35.17                | -10.83      | 46.00          | 100         | 215         | QP                |
| 6  |   | 730.834         | 3.71           | 29.25      | 32.96                | -13.04      | 46.00          | 150         | 250         | QP                |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.
5. The amplitude of radiated emissions (frequency range from 9kHz to 30MHz) is that proximity to ambient noise, which also are attenuated more than 20dB below the permissible value. Therefore, the data is not presented in the report.

|           |                             |                      |              |
|-----------|-----------------------------|----------------------|--------------|
| EUT       | 2.4&5.8GHz HD Wireless Link | Date of Test         | 2025-10-29   |
| Factor    | DRH18-E & BBHA 9170         | Temp. / Humidity     | 24°C /65%    |
| Polarity  | Horizontal                  | Site / Test Engineer | AC1 / James  |
| Test Mode | SRD 5.8G_TX_5731MHz_ANT 1   | Test Voltage         | AC 120V/60Hz |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB/m) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Height (cm) | Angle (deg) | Remark (QP/PK/AV) |
|----|-----------------|----------------|------------|----------------------|-------------|----------------|-------------|-------------|-------------------|
| 1  | 11462.000       | 46.11          | 9.04       | 55.15                | -18.85      | 74.00          | 200         | 60          | Peak              |
| 2  | * 11462.000     | 37.51          | 9.04       | 46.55                | -7.45       | 54.00          | 200         | 60          | Average           |
| 3  | * 17193.000     | 43.60          | 9.70       | 53.31                | -14.89      | 68.20          | 200         | 220         | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                             |                      |              |
|-----------|-----------------------------|----------------------|--------------|
| EUT       | 2.4&5.8GHz HD Wireless Link | Date of Test         | 2025-10-29   |
| Factor    | DRH18-E & BBHA 9170         | Temp. / Humidity     | 24°C /65%    |
| Polarity  | Vertical                    | Site / Test Engineer | AC1 / James  |
| Test Mode | SRD 5.8G_TX_5731MHz_ANT 1   | Test Voltage         | AC 120V/60Hz |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB/m) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Height (cm) | Angle (deg) | Remark (QP/PK/AV) |
|----|-----------------|----------------|------------|----------------------|-------------|----------------|-------------|-------------|-------------------|
| 1  | 11462.000       | 51.24          | 9.04       | 60.28                | -13.72      | 74.00          | 200         | 138         | Peak              |
| 2  | * 11462.000     | 42.84          | 9.04       | 51.88                | -2.12       | 54.00          | 200         | 138         | Average           |
| 3  | * 17193.000     | 50.12          | 9.70       | 59.82                | -8.38       | 68.20          | 200         | 141         | Peak              |

Note:

- "\*" means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                             |                      |              |
|-----------|-----------------------------|----------------------|--------------|
| EUT       | 2.4&5.8GHz HD Wireless Link | Date of Test         | 2025-10-29   |
| Factor    | DRH18-E & BBHA 9170         | Temp. / Humidity     | 24°C /65%    |
| Polarity  | Horizontal                  | Site / Test Engineer | AC1 / James  |
| Test Mode | SRD 5.8G_TX_5765MHz_ANT 1   | Test Voltage         | AC 120V/60Hz |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB/m) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Height (cm) | Angle (deg) | Remark (QP/PK/AV) |
|----|-----------------|----------------|------------|----------------------|-------------|----------------|-------------|-------------|-------------------|
| 1  | 11530.000       | 43.09          | 9.05       | 52.14                | -21.86      | 74.00          | 200         | 34          | Peak              |
| 2  | * 17295.000     | 44.35          | 9.60       | 53.95                | -14.25      | 68.20          | 200         | 52          | Peak              |

Note:

- "\*", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                             |                      |              |
|-----------|-----------------------------|----------------------|--------------|
| EUT       | 2.4&5.8GHz HD Wireless Link | Date of Test         | 2025-10-29   |
| Factor    | DRH18-E & BBHA 9170         | Temp. / Humidity     | 24°C /65%    |
| Polarity  | Vertical                    | Site / Test Engineer | AC1 / James  |
| Test Mode | SRD 5.8G_TX_5765MHz_ANT 1   | Test Voltage         | AC 120V/60Hz |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB/m) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Height (cm) | Angle (deg) | Remark (QP/PK/AV) |
|----|-----------------|----------------|------------|----------------------|-------------|----------------|-------------|-------------|-------------------|
| 1  | 11530.000       | 50.17          | 9.05       | 59.22                | -14.78      | 74.00          | 200         | 137         | Peak              |
| 2  | * 11530.000     | 40.83          | 9.05       | 49.88                | -4.12       | 54.00          | 200         | 137         | Average           |
| 3  | * 17295.000     | 48.60          | 9.60       | 58.20                | -10.00      | 68.20          | 200         | 305         | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                             |                      |              |
|-----------|-----------------------------|----------------------|--------------|
| EUT       | 2.4&5.8GHz HD Wireless Link | Date of Test         | 2025-10-29   |
| Factor    | DRH18-E & BBHA 9170         | Temp. / Humidity     | 24°C /65%    |
| Polarity  | Horizontal                  | Site / Test Engineer | AC1 / James  |
| Test Mode | SRD 5.8G_TX_5782MHz_ANT 1   | Test Voltage         | AC 120V/60Hz |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB/m) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Height (cm) | Angle (deg) | Remark (QP/PK/AV) |
|----|-----------------|----------------|------------|----------------------|-------------|----------------|-------------|-------------|-------------------|
| 1  | 11564.000       | 43.03          | 9.06       | 52.09                | -21.91      | 74.00          | 200         | 114         | Peak              |
| 2  | * 17346.000     | 43.42          | 9.49       | 52.91                | -15.29      | 68.20          | 200         | 231         | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                             |                      |              |
|-----------|-----------------------------|----------------------|--------------|
| EUT       | 2.4&5.8GHz HD Wireless Link | Date of Test         | 2025-10-29   |
| Factor    | DRH18-E & BBHA 9170         | Temp. / Humidity     | 24°C /65%    |
| Polarity  | Vertical                    | Site / Test Engineer | AC1 / James  |
| Test Mode | SRD 5.8G_TX_5782MHz_ANT 1   | Test Voltage         | AC 120V/60Hz |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB/m) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Height (cm) | Angle (deg) | Remark (QP/PK/AV) |
|----|-----------------|----------------|------------|----------------------|-------------|----------------|-------------|-------------|-------------------|
| 1  | 11564.000       | 50.08          | 9.06       | 59.14                | -14.86      | 74.00          | 200         | 318         | Peak              |
| 2  | * 11564.000     | 38.43          | 9.06       | 47.49                | -6.51       | 54.00          | 200         | 318         | Average           |
| 3  | * 17346.000     | 48.08          | 9.49       | 57.57                | -10.63      | 68.20          | 200         | 1           | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                             |                      |              |
|-----------|-----------------------------|----------------------|--------------|
| EUT       | 2.4&5.8GHz HD Wireless Link | Date of Test         | 2025-11-18   |
| Factor    | DRH18-E & BBHA 9170         | Temp. / Humidity     | 24°C /65%    |
| Polarity  | Horizontal                  | Site / Test Engineer | AC1 / James  |
| Test Mode | SRD 5.8G_TX_5799MHz_ANT 1   | Test Voltage         | AC 120V/60Hz |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB/m) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Height (cm) | Angle (deg) | Remark (QP/PK/AV) |
|----|-----------------|----------------|------------|----------------------|-------------|----------------|-------------|-------------|-------------------|
| 1  | 11598.000       | 44.39          | 9.08       | 53.47                | -20.53      | 74.00          | 200         | 342         | Peak              |
| 2  | * 17397.000     | 44.96          | 9.38       | 54.34                | -13.86      | 68.20          | 200         | 359         | Peak              |

Note:

- "\*", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                             |                      |              |
|-----------|-----------------------------|----------------------|--------------|
| EUT       | 2.4&5.8GHz HD Wireless Link | Date of Test         | 2025-11-18   |
| Factor    | DRH18-E & BBHA 9170         | Temp. / Humidity     | 24°C /65%    |
| Polarity  | Vertical                    | Site / Test Engineer | AC1 / James  |
| Test Mode | SRD 5.8G_TX_5799MHz_ANT 1   | Test Voltage         | AC 120V/60Hz |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB/m) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Height (cm) | Angle (deg) | Remark (QP/PK/AV) |
|----|-----------------|----------------|------------|----------------------|-------------|----------------|-------------|-------------|-------------------|
| 1  | 11598.000       | 51.60          | 9.08       | 60.67                | -13.33      | 74.00          | 200         | 339         | Peak              |
| 2  | * 11598.000     | 44.28          | 9.08       | 53.36                | -0.64       | 54.00          | 200         | 339         | Average           |
| 3  | * 17397.000     | 47.00          | 9.38       | 56.38                | -11.82      | 68.20          | 200         | 87          | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                             |                      |              |
|-----------|-----------------------------|----------------------|--------------|
| EUT       | 2.4&5.8GHz HD Wireless Link | Date of Test         | 2025-10-29   |
| Factor    | DRH18-E & BBHA 9170         | Temp. / Humidity     | 24°C /65%    |
| Polarity  | Horizontal                  | Site / Test Engineer | AC1 / James  |
| Test Mode | SRD 5.8G_TX_5731MHz_ANT 2   | Test Voltage         | AC 120V/60Hz |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB/m) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Height (cm) | Angle (deg) | Remark (QP/PK/AV) |
|----|-----------------|----------------|------------|----------------------|-------------|----------------|-------------|-------------|-------------------|
| 1  | 11462.000       | 45.70          | 9.04       | 54.74                | -19.26      | 74.00          | 200         | 63          | Peak              |
| 2  | * 11462.000     | 36.27          | 9.04       | 45.31                | -8.69       | 54.00          | 200         | 63          | Average           |
| 3  | * 17193.000     | 43.84          | 9.70       | 53.54                | -14.66      | 68.20          | 200         | 72          | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                             |                      |              |
|-----------|-----------------------------|----------------------|--------------|
| EUT       | 2.4&5.8GHz HD Wireless Link | Date of Test         | 2025-10-29   |
| Factor    | DRH18-E & BBHA 9170         | Temp. / Humidity     | 24°C /65%    |
| Polarity  | Vertical                    | Site / Test Engineer | AC1 / James  |
| Test Mode | SRD 5.8G_TX_5731MHz_ANT 2   | Test Voltage         | AC 120V/60Hz |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB/m) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Height (cm) | Angle (deg) | Remark (QP/PK/AV) |
|----|-----------------|----------------|------------|----------------------|-------------|----------------|-------------|-------------|-------------------|
| 1  | 11462.000       | 51.87          | 9.04       | 60.90                | -13.10      | 74.00          | 200         | 140         | Peak              |
| 2  | * 11462.000     | 42.74          | 9.04       | 51.78                | -2.22       | 54.00          | 200         | 140         | Average           |
| 3  | * 17193.000     | 50.55          | 9.70       | 60.25                | -7.95       | 68.20          | 200         | 143         | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                             |                      |              |
|-----------|-----------------------------|----------------------|--------------|
| EUT       | 2.4&5.8GHz HD Wireless Link | Date of Test         | 2025-10-29   |
| Factor    | DRH18-E & BBHA 9170         | Temp. / Humidity     | 24°C /65%    |
| Polarity  | Horizontal                  | Site / Test Engineer | AC1 / James  |
| Test Mode | SRD 5.8G_TX_5765MHz_ANT 2   | Test Voltage         | AC 120V/60Hz |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB/m) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Height (cm) | Angle (deg) | Remark (QP/PK/AV) |
|----|-----------------|----------------|------------|----------------------|-------------|----------------|-------------|-------------|-------------------|
| 1  | 11530.000       | 43.34          | 9.05       | 52.39                | -21.61      | 74.00          | 200         | 31          | Peak              |
| 2  | * 17295.000     | 44.08          | 9.60       | 53.68                | -14.52      | 68.20          | 200         | 11          | Peak              |

Note:

- "\*" means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                             |                      |              |
|-----------|-----------------------------|----------------------|--------------|
| EUT       | 2.4&5.8GHz HD Wireless Link | Date of Test         | 2025-10-29   |
| Factor    | DRH18-E & BBHA 9170         | Temp. / Humidity     | 24°C /65%    |
| Polarity  | Vertical                    | Site / Test Engineer | AC1 / James  |
| Test Mode | SRD 5.8G_TX_5765MHz_ANT 2   | Test Voltage         | AC 120V/60Hz |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB/m) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Height (cm) | Angle (deg) | Remark (QP/PK/AV) |
|----|-----------------|----------------|------------|----------------------|-------------|----------------|-------------|-------------|-------------------|
| 1  | 11530.000       | 48.82          | 9.05       | 57.87                | -16.13      | 74.00          | 200         | 136         | Peak              |
| 2  | * 11530.000     | 40.70          | 9.05       | 49.75                | -4.25       | 54.00          | 200         | 136         | Average           |
| 3  | * 17295.000     | 47.25          | 9.60       | 56.85                | -11.35      | 68.20          | 200         | 299         | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                             |                      |              |
|-----------|-----------------------------|----------------------|--------------|
| EUT       | 2.4&5.8GHz HD Wireless Link | Date of Test         | 2025-10-29   |
| Factor    | DRH18-E & BBHA 9170         | Temp. / Humidity     | 24°C /65%    |
| Polarity  | Horizontal                  | Site / Test Engineer | AC1 / James  |
| Test Mode | SRD 5.8G_TX_5782MHz_ANT 2   | Test Voltage         | AC 120V/60Hz |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB/m) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Height (cm) | Angle (deg) | Remark (QP/PK/AV) |
|----|-----------------|----------------|------------|----------------------|-------------|----------------|-------------|-------------|-------------------|
| 1  | 11564.000       | 39.61          | 9.06       | 48.67                | -25.33      | 74.00          | 200         | 78          | Peak              |
| 2  | * 17346.000     | 44.03          | 9.49       | 53.52                | -14.68      | 68.20          | 200         | 195         | Peak              |

Note:

- "\*", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                             |                      |              |
|-----------|-----------------------------|----------------------|--------------|
| EUT       | 2.4&5.8GHz HD Wireless Link | Date of Test         | 2025-10-29   |
| Factor    | DRH18-E & BBHA 9170         | Temp. / Humidity     | 24°C /65%    |
| Polarity  | Vertical                    | Site / Test Engineer | AC1 / James  |
| Test Mode | SRD 5.8G_TX_5782MHz_ANT 2   | Test Voltage         | AC 120V/60Hz |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB/m) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Height (cm) | Angle (deg) | Remark (QP/PK/AV) |
|----|-----------------|----------------|------------|----------------------|-------------|----------------|-------------|-------------|-------------------|
| 1  | 11564.000       | 42.67          | 9.06       | 51.73                | -22.27      | 74.00          | 200         | 84          | Peak              |
| 2  | * 17346.000     | 44.06          | 9.49       | 53.55                | -14.65      | 68.20          | 200         | 242         | Peak              |

Note:

- "\*" means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                             |                      |              |
|-----------|-----------------------------|----------------------|--------------|
| EUT       | 2.4&5.8GHz HD Wireless Link | Date of Test         | 2025-11-18   |
| Factor    | DRH18-E & BBHA 9170         | Temp. / Humidity     | 24°C /65%    |
| Polarity  | Horizontal                  | Site / Test Engineer | AC1 / James  |
| Test Mode | SRD 5.8G_TX_5799MHz_ANT 2   | Test Voltage         | AC 120V/60Hz |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB/m) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Height (cm) | Angle (deg) | Remark (QP/PK/AV) |
|----|-----------------|----------------|------------|----------------------|-------------|----------------|-------------|-------------|-------------------|
| 1  | 11598.000       | 41.06          | 9.08       | 50.13                | -23.87      | 74.00          | 200         | 14          | Peak              |
| 2  | * 17397.000     | 44.36          | 9.38       | 53.74                | -14.46      | 68.20          | 200         | 284         | Peak              |

Note:

- "\*", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                             |                      |              |
|-----------|-----------------------------|----------------------|--------------|
| EUT       | 2.4&5.8GHz HD Wireless Link | Date of Test         | 2025-11-18   |
| Factor    | DRH18-E & BBHA 9170         | Temp. / Humidity     | 24°C /65%    |
| Polarity  | Vertical                    | Site / Test Engineer | AC1 / James  |
| Test Mode | SRD 5.8G_TX_5799MHz_ANT 2   | Test Voltage         | AC 120V/60Hz |



| No | Frequency (MHz) | Reading (dBuV) | C.F (dB/m) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Height (cm) | Angle (deg) | Remark (QP/PK/AV) |
|----|-----------------|----------------|------------|----------------------|-------------|----------------|-------------|-------------|-------------------|
| 1  | 11598.000       | 46.33          | 9.08       | 55.41                | -18.59      | 74.00          | 200         | 283         | Peak              |
| 2  | * 11598.000     | 37.30          | 9.08       | 46.38                | -7.62       | 54.00          | 200         | 283         | Average           |
| 3  | * 17397.000     | 44.93          | 9.38       | 54.32                | -13.88      | 68.20          | 200         | 16          | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

## 7.7. Radiated Restricted Band Edge Measurement

### 7.7.1. Test Limit

#### For 15.205 requirement:

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a) of FCC part 15, must also comply with the radiated emission limits specified in Section 15.209(a).

| Frequency<br>(MHz)         | Frequency<br>(MHz)  | Frequency<br>(MHz) | Frequency<br>(GHz) |
|----------------------------|---------------------|--------------------|--------------------|
| 0.090 - 0.110              | 16.42 - 16.423      | 399.9 - 410        | 4.5 - 5.15         |
| <sup>1</sup> 0.495 - 0.505 | 16.69475 - 16.69525 | 608 - 614          | 5.35 - 5.46        |
| 2.1735 - 2.1905            | 16.80425 - 16.80475 | 960 - 1240         | 7.25 - 7.75        |
| 4.125 - 4.128              | 25.5 - 25.67        | 1300 - 1427        | 8.25 - 8.5         |
| 4.17725 - 4.17775          | 37.5 - 38.25        | 1435 - 1626.5      | 9.0 - 9.2          |
| 4.20725 - 4.20775          | 73 - 74.6           | 1645.5 - 1646.5    | 9.3 - 9.5          |
| 6.215 - 6.218              | 74.8 - 75.2         | 1660 - 1710        | 10.6 - 12.7        |
| 6.26775 - 6.26825          | 108 - 121.94        | 1718.8 - 1722.2    | 13.25 - 13.4       |
| 6.31175 - 6.31225          | 123 - 138           | 2200 - 2300        | 14.47 - 14.5       |
| 8.291 - 8.294              | 149.9 - 150.05      | 2310 - 2390        | 15.35 - 16.2       |
| 8.362 - 8.366              | 156.52475 - 156.525 | 2483.5 - 2500      | 17.7 - 21.4        |
| 8.37625 - 8.38675          | 156.7 - 156.9       | 2690 - 2900        | 22.01 - 23.12      |
| 8.41425 - 8.41475          | 162.0125 - 167.17   | 3260 - 3267        | 23.6 - 24.0        |
| 12.29 - 12.293             | 167.72 - 173.2      | 3332 - 3339        | 31.2 - 31.8        |
| 12.51975 - 12.52025        | 240 - 285           | 3345.8 - 3358      | 36.43 - 36.5       |
| 12.57675 - 12.57725        | 322 - 335.4         | 3600 - 4400        | ( <sup>2</sup> )   |
| 13.36 - 13.41              | --                  | --                 | --                 |

**For 15.407(b) requirement:**

For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

**For FCC transmitters operating in the 5.725-5.85 GHz band:** All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

**For IC transmitters operating in the 5.725-5.85 GHz band:** All emissions within the frequency range from the band edge to 10 MHz above or below the band edge shall not exceed an e.i.r.p. of -17 dBm/MHz; for frequencies 10 MHz or greater above or below the band edge, emissions shall not exceed an e.i.r.p. of -27 dBm/MHz.

Refer to KDB 789033 D02v02r01 G)2)c), as specified in § 15.407(b), emissions above 1000 MHz that are outside of the restricted bands are subject to a maximum emission limit of -27 dBm/MHz (or -17 dBm/MHz as specified in § 15.407(b)(4)). However, an out-of-band emission that complies with both the peak and average limits of § 15.209 is not required to satisfy the -27 dBm/MHz or -17 dBm/MHz maximum emission limit.


All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table per Section 15.209.

**FCC-Radiated emission limits; general requirements**

| <b>FCC Part 15 Subpart C Paragraph 15.209</b> |                                 |                                       |
|-----------------------------------------------|---------------------------------|---------------------------------------|
| <b>Frequency<br/>[MHz]</b>                    | <b>Field Strength<br/>[V/m]</b> | <b>Measured Distance<br/>[Meters]</b> |
| 0.009 ~ 0.490                                 | 2400/F (kHz)                    | 300                                   |
| 0.490 ~ 1.705                                 | 24000/F (kHz)                   | 30                                    |
| 1.705 ~ 30                                    | 30                              | 30                                    |
| 30 ~ 88                                       | 100                             | 3                                     |
| 88 ~ 216                                      | 150                             | 3                                     |
| 216 ~ 960                                     | 200                             | 3                                     |
| Above 960                                     | 500                             | 3                                     |

### 7.7.2. Test Result

|           |                             |                      |              |
|-----------|-----------------------------|----------------------|--------------|
| EUT       | 2.4&5.8GHz HD Wireless Link | Date of Test         | 2025-10-29   |
| Factor    | DRH18-E                     | Temp. / Humidity     | 24°C /65%    |
| Polarity  | Horizontal                  | Site / Test Engineer | AC1 / James  |
| Test Mode | SRD 5.8G_TX_5731MHz_ANT 1   | Test Voltage         | AC 120V/60Hz |




| No |   | Frequency (MHz) | Reading (dBuV) | C.F (dB/m) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Height (cm) | Angle (deg) | Remark (QP/PK/AV) |
|----|---|-----------------|----------------|------------|----------------------|-------------|----------------|-------------|-------------|-------------------|
| 1  | * | 5643.520        | 50.57          | 5.90       | 56.47                | -11.73      | 68.20          | 150         | 305         | Peak              |
| 2  |   | 5650.000        | 48.99          | 5.93       | 54.93                | -13.27      | 68.20          | 150         | 305         | Peak              |
| 3  |   | 5700.000        | 49.42          | 6.22       | 55.64                | -49.56      | 105.20         | 150         | 305         | Peak              |
| 4  |   | 5720.000        | 71.24          | 6.34       | 77.58                | -33.22      | 110.80         | 150         | 305         | Peak              |
| 5  |   | 5725.000        | 81.80          | 6.37       | 88.17                | -34.03      | 122.20         | 150         | 305         | Peak              |
| 6  |   | 5733.920        | 105.73         | 6.42       | 112.15               | N/A         | N/A            | 150         | 305         | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB) + 10dB Attenuation.
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                             |                      |              |
|-----------|-----------------------------|----------------------|--------------|
| EUT       | 2.4&5.8GHz HD Wireless Link | Date of Test         | 2025-10-29   |
| Factor    | DRH18-E                     | Temp. / Humidity     | 24°C /65%    |
| Polarity  | Vertical                    | Site / Test Engineer | AC1 / James  |
| Test Mode | SRD 5.8G_TX_5731MHz_ANT 1   | Test Voltage         | AC 120V/60Hz |




| No |   | Frequency (MHz) | Reading (dBuV) | C.F (dB/m) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Height (cm) | Angle (deg) | Remark (QP/PK/AV) |
|----|---|-----------------|----------------|------------|----------------------|-------------|----------------|-------------|-------------|-------------------|
| 1  | * | 5607.520        | 51.48          | 5.69       | 57.17                | -11.03      | 68.20          | 155         | 150         | Peak              |
| 2  |   | 5650.000        | 49.11          | 5.93       | 55.04                | -13.16      | 68.20          | 155         | 150         | Peak              |
| 3  |   | 5700.000        | 55.50          | 6.22       | 61.72                | -43.48      | 105.20         | 155         | 150         | Peak              |
| 4  |   | 5720.000        | 81.87          | 6.34       | 88.21                | -22.59      | 110.80         | 155         | 150         | Peak              |
| 5  |   | 5725.000        | 89.07          | 6.37       | 95.44                | -26.76      | 122.20         | 155         | 150         | Peak              |
| 6  |   | 5730.560        | 114.10         | 6.40       | 120.50               | N/A         | N/A            | 155         | 150         | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB) + 10dB Attenuation.
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                             |                      |              |
|-----------|-----------------------------|----------------------|--------------|
| EUT       | 2.4&5.8GHz HD Wireless Link | Date of Test         | 2025-10-29   |
| Factor    | DRH18-E                     | Temp. / Humidity     | 24°C /65%    |
| Polarity  | Horizontal                  | Site / Test Engineer | AC1 / James  |
| Test Mode | SRD 5.8G_TX_5782MHz_ANT 1   | Test Voltage         | AC 120V/60Hz |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB/m) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Height (cm) | Angle (deg) | Remark (QP/PK/AV) |
|----|-----------------|----------------|------------|----------------------|-------------|----------------|-------------|-------------|-------------------|
| 1  | 5784.000        | 107.66         | 6.72       | 114.38               | N/A         | N/A            | 135         | 300         | Peak              |
| 2  | 5850.000        | 48.66          | 6.74       | 55.40                | -66.80      | 122.20         | 135         | 300         | Peak              |
| 3  | 5855.000        | 49.76          | 6.73       | 56.49                | -54.31      | 110.80         | 135         | 300         | Peak              |
| 4  | 5875.000        | 49.00          | 6.69       | 55.69                | -49.51      | 105.20         | 135         | 300         | Peak              |
| 5  | 5925.000        | 48.47          | 6.63       | 55.10                | -13.10      | 68.20          | 135         | 300         | Peak              |
| 6  | * 5930.400      | 50.78          | 6.62       | 57.40                | -10.80      | 68.20          | 135         | 300         | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB) + 10dB Attenuation.
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                             |                      |              |
|-----------|-----------------------------|----------------------|--------------|
| EUT       | 2.4&5.8GHz HD Wireless Link | Date of Test         | 2025-10-29   |
| Factor    | DRH18-E                     | Temp. / Humidity     | 24°C /65%    |
| Polarity  | Vertical                    | Site / Test Engineer | AC1 / James  |
| Test Mode | SRD 5.8G_TX_5782MHz_ANT 1   | Test Voltage         | AC 120V/60Hz |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB/m) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Height (cm) | Angle (deg) | Remark (QP/PK/AV) |
|----|-----------------|----------------|------------|----------------------|-------------|----------------|-------------|-------------|-------------------|
| 1  | 5784.480        | 114.86         | 6.73       | 121.58               | N/A         | N/A            | 155         | 250         | Peak              |
| 2  | 5850.000        | 49.11          | 6.74       | 55.84                | -66.36      | 122.20         | 155         | 250         | Peak              |
| 3  | 5855.000        | 49.42          | 6.73       | 56.15                | -54.65      | 110.80         | 155         | 250         | Peak              |
| 4  | 5875.000        | 48.30          | 6.69       | 55.00                | -50.20      | 105.20         | 155         | 250         | Peak              |
| 5  | 5925.000        | 49.62          | 6.63       | 56.25                | -11.95      | 68.20          | 155         | 250         | Peak              |
| 6  | * 5957.520      | 51.02          | 6.59       | 57.60                | -10.60      | 68.20          | 155         | 250         | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB) + 10dB Attenuation.
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                             |                      |              |
|-----------|-----------------------------|----------------------|--------------|
| EUT       | 2.4&5.8GHz HD Wireless Link | Date of Test         | 2025-11-18   |
| Factor    | DRH18-E                     | Temp. / Humidity     | 24°C /65%    |
| Polarity  | Horizontal                  | Site / Test Engineer | AC1 / James  |
| Test Mode | SRD 5.8G_TX_5799MHz_ANT 1   | Test Voltage         | AC 120V/60Hz |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB/m) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Height (cm) | Angle (deg) | Remark (QP/PK/AV) |
|----|-----------------|----------------|------------|----------------------|-------------|----------------|-------------|-------------|-------------------|
| 1  | 5798.520        | 110.29         | 6.81       | 117.09               | N/A         | N/A            | 150         | 260         | Peak              |
| 2  | 5850.000        | 50.57          | 6.74       | 57.31                | -64.89      | 122.20         | 150         | 260         | Peak              |
| 3  | 5855.000        | 49.25          | 6.73       | 55.98                | -54.82      | 110.80         | 150         | 260         | Peak              |
| 4  | 5875.000        | 49.15          | 6.69       | 55.85                | -49.35      | 105.20         | 150         | 260         | Peak              |
| 5  | 5925.000        | 48.64          | 6.63       | 55.26                | -12.94      | 68.20          | 150         | 260         | Peak              |
| 6  | * 5930.080      | 50.61          | 6.62       | 57.23                | -10.97      | 68.20          | 150         | 260         | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB) + 10dB Attenuation.
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                             |                      |              |
|-----------|-----------------------------|----------------------|--------------|
| EUT       | 2.4&5.8GHz HD Wireless Link | Date of Test         | 2025-11-18   |
| Factor    | DRH18-E                     | Temp. / Humidity     | 24°C /65%    |
| Polarity  | Vertical                    | Site / Test Engineer | AC1 / James  |
| Test Mode | SRD 5.8G_TX_5799MHz_ANT 1   | Test Voltage         | AC 120V/60Hz |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB/m) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Height (cm) | Angle (deg) | Remark (QP/PK/AV) |
|----|-----------------|----------------|------------|----------------------|-------------|----------------|-------------|-------------|-------------------|
| 1  | 5798.750        | 115.67         | 6.81       | 122.48               | N/A         | N/A            | 130         | 80          | Peak              |
| 2  | 5850.000        | 49.68          | 6.74       | 56.41                | -65.79      | 122.20         | 130         | 80          | Peak              |
| 3  | 5855.000        | 49.46          | 6.73       | 56.19                | -54.61      | 110.80         | 130         | 80          | Peak              |
| 4  | 5875.000        | 49.03          | 6.69       | 55.72                | -49.48      | 105.20         | 130         | 80          | Peak              |
| 5  | 5925.000        | 49.65          | 6.63       | 56.27                | -11.93      | 68.20          | 130         | 80          | Peak              |
| 6  | * 5935.600      | 51.02          | 6.61       | 57.64                | -10.56      | 68.20          | 130         | 80          | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB) + 10dB Attenuation.
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                             |                      |              |
|-----------|-----------------------------|----------------------|--------------|
| EUT       | 2.4&5.8GHz HD Wireless Link | Date of Test         | 2025-10-29   |
| Factor    | DRH18-E                     | Temp. / Humidity     | 24°C /65%    |
| Polarity  | Horizontal                  | Site / Test Engineer | AC1 / James  |
| Test Mode | SRD 5.8G_TX_5731MHz_ANT 2   | Test Voltage         | AC 120V/60Hz |




| No |   | Frequency (MHz) | Reading (dBuV) | C.F (dB/m) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Height (cm) | Angle (deg) | Remark (QP/PK/AV) |
|----|---|-----------------|----------------|------------|----------------------|-------------|----------------|-------------|-------------|-------------------|
| 1  | * | 5607.360        | 50.64          | 5.69       | 56.33                | -11.87      | 68.20          | 150         | 305         | Peak              |
| 2  |   | 5650.000        | 49.18          | 5.93       | 55.11                | -13.09      | 68.20          | 150         | 305         | Peak              |
| 3  |   | 5700.000        | 53.84          | 6.22       | 60.06                | -45.14      | 105.20         | 150         | 305         | Peak              |
| 4  |   | 5720.000        | 77.20          | 6.34       | 83.55                | -27.25      | 110.80         | 150         | 305         | Peak              |
| 5  |   | 5725.000        | 86.27          | 6.37       | 92.65                | -29.55      | 122.20         | 150         | 305         | Peak              |
| 6  |   | 5733.760        | 106.65         | 6.42       | 113.07               | N/A         | N/A            | 150         | 305         | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB) + 10dB Attenuation.
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                             |                      |              |
|-----------|-----------------------------|----------------------|--------------|
| EUT       | 2.4&5.8GHz HD Wireless Link | Date of Test         | 2025-10-29   |
| Factor    | DRH18-E                     | Temp. / Humidity     | 24°C /65%    |
| Polarity  | Vertical                    | Site / Test Engineer | AC1 / James  |
| Test Mode | SRD 5.8G_TX_5731MHz_ANT 2   | Test Voltage         | AC 120V/60Hz |




| No |   | Frequency (MHz) | Reading (dBuV) | C.F (dB/m) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Height (cm) | Angle (deg) | Remark (QP/PK/AV) |
|----|---|-----------------|----------------|------------|----------------------|-------------|----------------|-------------|-------------|-------------------|
| 1  | * | 5616.320        | 51.51          | 5.74       | 57.25                | -10.95      | 68.20          | 125         | 345         | Peak              |
| 2  |   | 5650.000        | 49.07          | 5.93       | 55.00                | -13.20      | 68.20          | 125         | 345         | Peak              |
| 3  |   | 5700.000        | 59.82          | 6.22       | 66.04                | -39.16      | 105.20         | 125         | 345         | Peak              |
| 4  |   | 5720.000        | 84.39          | 6.34       | 90.73                | -20.07      | 110.80         | 125         | 345         | Peak              |
| 5  |   | 5725.000        | 92.52          | 6.37       | 98.89                | -23.31      | 122.20         | 125         | 345         | Peak              |
| 6  |   | 5732.480        | 115.04         | 6.42       | 121.46               | N/A         | N/A            | 125         | 345         | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB) + 10dB Attenuation.
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                             |                      |              |
|-----------|-----------------------------|----------------------|--------------|
| EUT       | 2.4&5.8GHz HD Wireless Link | Date of Test         | 2025-10-29   |
| Factor    | DRH18-E                     | Temp. / Humidity     | 24°C /65%    |
| Polarity  | Horizontal                  | Site / Test Engineer | AC1 / James  |
| Test Mode | SRD 5.8G_TX_5782MHz_ANT 2   | Test Voltage         | AC 120V/60Hz |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB/m) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Height (cm) | Angle (deg) | Remark (QP/PK/AV) |
|----|-----------------|----------------|------------|----------------------|-------------|----------------|-------------|-------------|-------------------|
| 1  | 5782.560        | 105.10         | 6.71       | 111.81               | N/A         | N/A            | 145         | 305         | Peak              |
| 2  | 5850.000        | 48.55          | 6.74       | 55.29                | -66.91      | 122.20         | 145         | 305         | Peak              |
| 3  | 5855.000        | 48.14          | 6.73       | 54.87                | -55.93      | 110.80         | 145         | 305         | Peak              |
| 4  | 5875.000        | 48.36          | 6.69       | 55.05                | -50.15      | 105.20         | 145         | 305         | Peak              |
| 5  | 5925.000        | 50.03          | 6.63       | 56.66                | -11.54      | 68.20          | 145         | 305         | Peak              |
| 6  | * 5974.560      | 51.02          | 6.57       | 57.58                | -10.62      | 68.20          | 145         | 305         | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB) + 10dB Attenuation.
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                             |                      |              |
|-----------|-----------------------------|----------------------|--------------|
| EUT       | 2.4&5.8GHz HD Wireless Link | Date of Test         | 2025-10-29   |
| Factor    | DRH18-E                     | Temp. / Humidity     | 24°C /65%    |
| Polarity  | Vertical                    | Site / Test Engineer | AC1 / James  |
| Test Mode | SRD 5.8G_TX_5782MHz_ANT 2   | Test Voltage         | AC 120V/60Hz |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB/m) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Height (cm) | Angle (deg) | Remark (QP/PK/AV) |
|----|-----------------|----------------|------------|----------------------|-------------|----------------|-------------|-------------|-------------------|
| 1  | 5785.680        | 112.86         | 6.73       | 119.59               | N/A         | N/A            | 150         | 255         | Peak              |
| 2  | 5850.000        | 48.85          | 6.74       | 55.59                | -66.61      | 122.20         | 150         | 255         | Peak              |
| 3  | 5855.000        | 50.20          | 6.73       | 56.93                | -53.87      | 110.80         | 150         | 255         | Peak              |
| 4  | 5875.000        | 49.78          | 6.69       | 56.48                | -48.72      | 105.20         | 150         | 255         | Peak              |
| 5  | 5925.000        | 48.49          | 6.63       | 55.12                | -13.08      | 68.20          | 150         | 255         | Peak              |
| 6  | * 5948.880      | 51.05          | 6.60       | 57.65                | -10.55      | 68.20          | 150         | 255         | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB) + 10dB Attenuation.
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                             |                      |              |
|-----------|-----------------------------|----------------------|--------------|
| EUT       | 2.4&5.8GHz HD Wireless Link | Date of Test         | 2025-11-18   |
| Factor    | DRH18-E                     | Temp. / Humidity     | 24°C /65%    |
| Polarity  | Horizontal                  | Site / Test Engineer | AC1 / James  |
| Test Mode | SRD 5.8G_TX_5799MHz_ANT 2   | Test Voltage         | AC 120V/60Hz |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB/m) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Height (cm) | Angle (deg) | Remark (QP/PK/AV) |
|----|-----------------|----------------|------------|----------------------|-------------|----------------|-------------|-------------|-------------------|
| 1  | 5795.070        | 113.18         | 6.79       | 119.96               | N/A         | N/A            | 155         | 260         | Peak              |
| 2  | 5850.000        | 54.49          | 6.74       | 61.22                | -60.98      | 122.20         | 155         | 260         | Peak              |
| 3  | 5855.000        | 50.50          | 6.73       | 57.22                | -53.58      | 110.80         | 155         | 260         | Peak              |
| 4  | 5875.000        | 49.87          | 6.69       | 56.56                | -48.64      | 105.20         | 155         | 260         | Peak              |
| 5  | 5925.000        | 50.47          | 6.63       | 57.10                | -11.10      | 68.20          | 155         | 260         | Peak              |
| 6  | * 5938.820      | 50.98          | 6.61       | 57.59                | -10.61      | 68.20          | 155         | 260         | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB) + 10dB Attenuation.
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                             |                      |              |
|-----------|-----------------------------|----------------------|--------------|
| EUT       | 2.4&5.8GHz HD Wireless Link | Date of Test         | 2025-11-18   |
| Factor    | DRH18-E                     | Temp. / Humidity     | 24°C /65%    |
| Polarity  | Vertical                    | Site / Test Engineer | AC1 / James  |
| Test Mode | SRD 5.8G_TX_5799MHz_ANT 2   | Test Voltage         | AC 120V/60Hz |



| No |   | Frequency (MHz) | Reading (dBUV) | C.F (dB/m) | Measurement (dBUV/m) | Margin (dB) | Limit (dBUV/m) | Height (cm) | Angle (deg) | Remark (QP/PK/AV) |
|----|---|-----------------|----------------|------------|----------------------|-------------|----------------|-------------|-------------|-------------------|
| 1  | * | 5795.760        | 117.51         | 6.79       | 124.31               | N/A         | N/A            | 140         | 85          | Peak              |
| 2  |   | 5850.000        | 57.24          | 6.74       | 63.97                | -58.23      | 122.20         | 140         | 85          | Peak              |
| 3  |   | 5855.000        | 52.99          | 6.73       | 59.72                | -51.08      | 110.80         | 140         | 85          | Peak              |
| 4  |   | 5875.000        | 50.06          | 6.69       | 56.76                | -48.44      | 105.20         | 140         | 85          | Peak              |
| 5  |   | 5925.000        | 49.25          | 6.63       | 55.88                | -12.32      | 68.20          | 140         | 85          | Peak              |
| 6  | * | 5957.910        | 51.67          | 6.59       | 58.26                | -9.94       | 68.20          | 140         | 85          | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB) + 10dB Attenuation.
3. Measurement (dBUV/m) = Reading(dBUV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

## 7.8. AC Conducted Emissions Measurement

### 7.8.1. Test Limit

| FCC Part 15.207 Limits |                    |                    |
|------------------------|--------------------|--------------------|
| Frequency<br>(MHz)     | QP<br>(dB $\mu$ V) | AV<br>(dB $\mu$ V) |
| 0.15 ~ 0.50            | 66 ~ 56            | 56 ~ 46            |
| 0.50 ~ 5.0             | 56                 | 46                 |
| 5.0 ~ 30               | 60                 | 50                 |

Note 1: The lower limit shall apply at the transition frequencies.

Note 2: The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.5MHz.


### 7.8.2. Test Procedure

The EUT was setup according to ANSI C63.4, 2009 and tested according to KDB 789033 for compliance to FCC 47CFR 15.247 requirements. The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface. The EUT and simulators are connected to the main power through a line impedance stabilization network (LISN). The LISN provides a 50 ohm /50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs) Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.

The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.


Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.

### 7.8.3. Test Setup



#### 7.8.4. Test Result

|           |                             |                      |              |
|-----------|-----------------------------|----------------------|--------------|
| EUT       | 2.4&5.8GHz HD Wireless Link | Date of Test         | 2025-11-06   |
| Factor    | CE_ENV216-L1 (Filter ON)    | Temp. / Humidity     | 24°C /54%    |
| Polarity  | Line1                       | Site / Test Engineer | SR2 / Ryan   |
| Test Mode | SRD 5.8G_TX_5731MHz_ANT 1   | Test Voltage         | AC 120V/60Hz |




| No |   | Frequency (MHz) | Reading (dBuV) | C.F (dB) | Measurement (dBuV) | Margin (dB) | Limit (dBuV) | Remark (QP/PK/AV) |
|----|---|-----------------|----------------|----------|--------------------|-------------|--------------|-------------------|
| 1  |   | 0.172           | 26.19          | 9.63     | 35.81              | -29.03      | 64.84        | QP                |
| 2  |   | 0.172           | 4.48           | 9.63     | 14.11              | -40.73      | 54.84        | Average           |
| 3  |   | 0.208           | 24.22          | 9.62     | 33.84              | -29.42      | 63.27        | QP                |
| 4  |   | 0.208           | 9.18           | 9.62     | 18.80              | -34.46      | 53.27        | Average           |
| 5  | * | 0.496           | 24.67          | 9.64     | 34.31              | -21.75      | 56.06        | QP                |
| 6  | * | 0.496           | 20.66          | 9.64     | 30.30              | -15.75      | 46.06        | Average           |
| 7  |   | 1.869           | 10.77          | 9.70     | 20.47              | -35.53      | 56.00        | QP                |
| 8  |   | 1.869           | 5.33           | 9.70     | 15.03              | -30.97      | 46.00        | Average           |
| 9  |   | 8.906           | 15.73          | 9.84     | 25.58              | -34.42      | 60.00        | QP                |
| 10 |   | 8.906           | 7.86           | 9.84     | 17.70              | -32.30      | 50.00        | Average           |
| 11 |   | 10.121          | 13.40          | 9.87     | 23.27              | -36.73      | 60.00        | QP                |
| 12 |   | 10.121          | 7.45           | 9.87     | 17.32              | -32.68      | 50.00        | Average           |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = LISN Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV) = Reading(dBuV) + C.F (Correction Factor).

|           |                             |                      |              |
|-----------|-----------------------------|----------------------|--------------|
| EUT       | 2.4&5.8GHz HD Wireless Link | Date of Test         | 2025-11-06   |
| Factor    | CE_ENV216-N (Filter ON)     | Temp. / Humidity     | 24°C /54%    |
| Polarity  | Neutral                     | Site / Test Engineer | SR2 / Ryan   |
| Test Mode | SRD 5.8G_TX_5731MHz_ANT 1   | Test Voltage         | AC 120V/60Hz |




| No |   | Frequency (MHz) | Reading (dBuV) | C.F (dB) | Measurement (dBuV) | Margin (dB) | Limit (dBuV) | Remark (QP/PK/AV) |
|----|---|-----------------|----------------|----------|--------------------|-------------|--------------|-------------------|
| 1  |   | 0.154           | 29.56          | 9.63     | 39.19              | -26.56      | 65.75        | QP                |
| 2  |   | 0.154           | 14.46          | 9.63     | 24.09              | -31.67      | 55.75        | Average           |
| 3  |   | 0.411           | 21.99          | 9.64     | 31.63              | -26.00      | 57.63        | QP                |
| 4  |   | 0.411           | 13.63          | 9.64     | 23.26              | -24.36      | 47.63        | Average           |
| 5  | * | 0.496           | 27.56          | 9.64     | 37.21              | -18.85      | 56.06        | QP                |
| 6  | * | 0.496           | 22.53          | 9.64     | 32.17              | -13.88      | 46.06        | Average           |
| 7  |   | 2.440           | 12.42          | 9.71     | 22.13              | -33.87      | 56.00        | QP                |
| 8  |   | 2.440           | 7.07           | 9.71     | 16.77              | -29.23      | 46.00        | Average           |
| 9  |   | 8.920           | 20.96          | 9.84     | 30.80              | -29.20      | 60.00        | QP                |
| 10 |   | 8.920           | 12.87          | 9.84     | 22.71              | -27.29      | 50.00        | Average           |
| 11 |   | 9.716           | 18.62          | 9.86     | 28.48              | -31.52      | 60.00        | QP                |
| 12 |   | 9.716           | 11.34          | 9.86     | 21.20              | -28.80      | 50.00        | Average           |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = LISN Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV) = Reading(dBuV) + C.F (Correction Factor).

|           |                             |                      |              |
|-----------|-----------------------------|----------------------|--------------|
| EUT       | 2.4&5.8GHz HD Wireless Link | Date of Test         | 2025-11-06   |
| Factor    | CE_ENV216-L1 (Filter ON)    | Temp. / Humidity     | 24°C /54%    |
| Polarity  | Line1                       | Site / Test Engineer | SR2 / Ryan   |
| Test Mode | SRD 5.8G_TX_5731MHz_ANT 2   | Test Voltage         | AC 120V/60Hz |




| No |   | Frequency (MHz) | Reading (dBuV) | C.F (dB) | Measurement (dBuV) | Margin (dB) | Limit (dBuV) | Remark (QP/PK/AV) |
|----|---|-----------------|----------------|----------|--------------------|-------------|--------------|-------------------|
| 1  |   | 0.150           | 28.47          | 9.63     | 38.10              | -27.90      | 66.00        | QP                |
| 2  |   | 0.150           | 14.22          | 9.63     | 23.85              | -32.15      | 56.00        | Average           |
| 3  |   | 0.199           | 23.47          | 9.62     | 33.10              | -30.54      | 63.63        | QP                |
| 4  |   | 0.199           | 7.09           | 9.62     | 16.71              | -36.92      | 53.63        | Average           |
| 5  | * | 0.492           | 23.62          | 9.64     | 33.26              | -22.88      | 56.13        | QP                |
| 6  | * | 0.492           | 18.86          | 9.64     | 28.50              | -17.63      | 46.13        | Average           |
| 7  |   | 1.675           | 10.03          | 9.69     | 19.72              | -36.28      | 56.00        | QP                |
| 8  |   | 1.675           | 4.30           | 9.69     | 13.99              | -32.01      | 46.00        | Average           |
| 9  |   | 8.893           | 15.88          | 9.84     | 25.73              | -34.27      | 60.00        | QP                |
| 10 |   | 8.893           | 8.34           | 9.84     | 18.18              | -31.82      | 50.00        | Average           |
| 11 |   | 12.065          | 10.38          | 9.88     | 20.27              | -39.73      | 60.00        | QP                |
| 12 |   | 12.065          | 5.37           | 9.88     | 15.25              | -34.75      | 50.00        | Average           |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = LISN Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV) = Reading(dBuV) + C.F (Correction Factor).

|           |                             |                      |              |
|-----------|-----------------------------|----------------------|--------------|
| EUT       | 2.4&5.8GHz HD Wireless Link | Date of Test         | 2025-11-06   |
| Factor    | CE_ENV216-N (Filter ON)     | Temp. / Humidity     | 24°C /54%    |
| Polarity  | Neutral                     | Site / Test Engineer | SR2 / Ryan   |
| Test Mode | SRD 5.8G_TX_5731MHz_ANT 2   | Test Voltage         | AC 120V/60Hz |



| No |   | Frequency (MHz) | Reading (dBuV) | C.F (dB) | Measurement (dBuV) | Margin (dB) | Limit (dBuV) | Remark (QP/PK/AV) |
|----|---|-----------------|----------------|----------|--------------------|-------------|--------------|-------------------|
| 1  |   | 0.154           | 29.48          | 9.63     | 39.10              | -26.65      | 65.75        | QP                |
| 2  |   | 0.154           | 14.08          | 9.63     | 23.71              | -32.04      | 55.75        | Average           |
| 3  |   | 0.190           | 23.77          | 9.62     | 33.40              | -30.62      | 64.01        | QP                |
| 4  |   | 0.190           | 5.15           | 9.62     | 14.78              | -39.24      | 54.01        | Average           |
| 5  |   | 0.411           | 22.28          | 9.64     | 31.92              | -25.71      | 57.63        | QP                |
| 6  |   | 0.411           | 13.82          | 9.64     | 23.45              | -24.18      | 47.63        | Average           |
| 7  | * | 0.496           | 27.16          | 9.64     | 36.80              | -19.26      | 56.06        | QP                |
| 8  | * | 0.496           | 21.75          | 9.64     | 31.39              | -14.66      | 46.06        | Average           |
| 9  |   | 1.261           | 13.41          | 9.68     | 23.09              | -32.91      | 56.00        | QP                |
| 10 |   | 1.261           | 7.41           | 9.68     | 17.09              | -28.91      | 46.00        | Average           |
| 11 |   | 9.145           | 20.71          | 9.85     | 30.56              | -29.44      | 60.00        | QP                |
| 12 |   | 9.145           | 13.17          | 9.85     | 23.02              | -26.98      | 50.00        | Average           |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = LISN Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV) = Reading(dBuV) + C.F (Correction Factor).

## 8. CONCLUSION

The data collected relate only the item(s) tested and show that the **2.4&5.8GHz HD Wireless Link**, is in compliance with Part 15E of the FCC Rules.

## **Appendix A : Test Photograph**

Refer to “2510TW0109-UTfile.

## **Appendix B : External Photograph**

Refer to “2510TW0109-UE file.

## **Appendix C : Internal Photograph**

Refer to “2510TW0109-UI file.

\_\_\_\_\_ The End \_\_\_\_\_