

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

--f(GHz) is the RF channel transmit frequency in GHz

--Power and distance are rounded to the nearest mW and mm before calculation

--The result is rounded to one decimal place for comparison

$$\text{eirp} = \text{pt} \times \text{gt} = (\text{EXd})^2/30$$

where:

pt = transmitter output power in watts,

gt = numeric gain of the transmitting antenna (unitless),

E = electric field strength in V/m, --- $10^{((\text{dBuV/m})/20)}/10^6$

d = measurement distance in meters (m) ---3m

Antenna gain is 0dBi, So gt=1

Maximun conducted output power=13.608dBm=22.951mW

The product has a stand, most time it's used as a mobile device. Because it's also powered by an rechargeable battery, so we evaluate that it can be used on your hand, and consider the 10-g SAR.

$$\text{So } (22.951\text{mW} / 5\text{mm}) \times \sqrt{2.4415} = 7.172 < 7.5$$

Then SAR test is exclusion.