TEST REPORT

Applicant:	ChamSys Ltd
Address of Applicant:	Unit 3B Richmond Works, Pitt Road, Freemantle, Southampton, SO15 3FQ United Kingdom
Manufacturer:	ChamSys Ltd
Address of Manufacturer:	Unit 3B Richmond Works, Pitt Road, Freemantle, Southampton, SO15 3FQ United Kingdom
Product name:	QuickQ Consoles, MagicQ Consoles
Model:	QuickQ Rack, MagicQ Consoles
Rating(s):	100-240V AC, 50/60Hz
Trademark:	CHAMSYS
Standards:	47 CFR PART 15 Subpart C: 2019 section 15.247
FCC ID:	2AQWR-QUICKQR
Data of Receipt:	2024-02-19
Date of Test:	2024-02-19~2024-05-15
Date of Issue:	2024-05-15
Test Result	**Pass***

* In the configuration tested, the test item complied with the standards specified above.

Authorized for issue by:

Test by:			***Reviewed by:***		
May.15,2024	Eleven Liang Project Engineer	Eleven Liang	May.15,2024	Bob Dai Project Manager	Bob Dai
Date	*Name/Position*	*Signature*	*Date*	*Name/Position*	*Signature*

Possible test case verdicts:

test case does not apply to the test object ..:	N/A
test object does meet the requirement .....:	P (Pass)
test object does not meet the requirement ..:	F (Fail)

Testing Laboratory information:

Testing Laboratory Name ..... :	ITL Co., Ltd
Address.....:	No. 8 Jinqianling Street 5, Huangjiang Town, Dongguan, Guangdong, 523757 P.R.C.
Testing location :	Same as above
Tel :	0086-769-39001678
Fax :	0086-20-62824387
E-mail :	itl@i-testlab.com

General remarks:

The test results presented in this report relate only to the object tested.

The results contained in this report reflect the results for this particular model and serial number. It is the responsibility of the manufacturer to ensure that all production models meet the intent of the requirements detailed within this report.

This report would be invalid test report without all the signatures of testing technician and approver.

This report shall not be reproduced, except in full, without the written approval of the Issuing testing laboratory.

General product information:

The model QuickQ Rack, MagicQ Rack is identical to each other except for model names and appearance color.

All tests were performed on the model QuickQ Rack as representative.

Compared with the original product, the new Rack has the following changes:

The product may use three power supplies, their models are MW, XP, MORNSUN, and these three power supplies are not used together, but separately.

Model	Product Description	Differences	Power supply
QuickQ Rack	QuickQ Consoles	Black shell	MW, XP ,MORUNSUN
MagicQ Rack	MagicQ Consoles	Blue shell	MW, XP ,MORUNSUN

The transmitter module itself has not changed. Here are the changes:

Modified the front panel PCB (313-131) to include a power button for the product.

The front of the unit is now an aluminum extruded part, (301-247) change from a steel plate.

External metalwork updated to accommodate the new front extrusion, no change to material or material thickness.

Antenna connector changed due to FCC request.

All cosmetic aluminum extruded parts have been removed.

MagicQ Rack is mechanically and electrically identical to the QuickQ Rack. There is a cosmetic change to the front panel with it being painted blue and screen printed differently.

This application is comply with C2PC, based on original report No.D190807002-2, adding three power supplies model XP, MW, MORUNSUN and its corresponding conducted emission, radiated emissions test results. The rest of the test results are still referring to the original report.

1 Test Summary

Test	Test Requirement	Test method	Result
Antenna Requirement	FCC PART 15 C section 15.247 (c) and Section 15.203	FCC PART 15 C section 15.247 (c) and Section 15.203	PASS
Occupied Bandwidth (-20dB)	FCC PART 15 C section 15.247 (a)(1);	ANSI C63.10:2013	PASS
Carrier Frequencies Separated	FCC PART 15 C section 15.247(a)(1);	ANSI C63.10:2013	PASS
Hopping Channel Number	FCC PART 15 C section 15.247(a)(1)(iii)	ANSI C63.10:2013	PASS
Dwell Time	FCC PART 15 C section 15.247(a)(1)(iii);	ANSI C63.10:2013	PASS
Maximum Peak Output Power	FCC PART 15 C section 15.247(b)(1);	ANSI C63.10:2013	PASS
Conducted Spurious Emission (30 MHz to 25 GHz)	FCC PART 15 C section 15.247(d);	ANSI C63.10:2013	PASS
Radiated Spurious Emission (9 kHz to 25 GHz)	FCC PART 15 C section 15.247(d);	ANSI C63.10:2013	PASS
Band Edges Measurement	FCC PART 15 C section 15.247 (d) &15.205	ANSI C63.10:2013	PASS
Conducted Emissions at Mains Terminals	FCC PART 15 C section 15.207;	ANSI C63.10:2013	PASS
Radiated Emissions which fall in the restricted bands	FCC PART 15 C section 15.209	ANSI C63.10:2013	PASS
Pseudorandom Frequency Hopping Sequence	47 CFR Part 15, Subpart C Section 5.247(b)(4)&TCB Exclusion List	ANSI C63.10:2013	PASS

Remark:

N/A: not applicable. Refer to the relative section for the details.
EUT: In this whole report EUT means Equipment Under Test.
Tx: In this whole report Tx (or tx) means Transmitter.
Rx: In this whole report Rx (or rx) means Receiver.
RF: In this whole report RF means Radio Frequency.
ANSI C63.10:2013 the detail version is ANSI C63.10:2013 in the whole report.

Version

The original Test Report Ref. No. D190807002-2, dated Sept. 02, 2019 was modified on May.08, 2024 to include the following changes and/or additions, which were considered technical modifications:

Considering Remark in this report D240219001-2

Revision Record		
Version	**Date**	**Remark**
D190807002-2	2019-09-02	Original report
D240219001-2	2024-05-08	Add new machine model MagicQ Rack, three power supply model MW, MORNSUN, XP and their Radiated Emissions, Conducted Emissions Test Results.

2 Contents

Page

TEST REPORT 1

1 TEST SUMMARY 4

2 CONTENTS 6

3 GENERAL INFORMATION 7

3.1 CLIENT INFORMATION 7
3.2 GENERAL DESCRIPTION OF E.U.T. 7
3.3 DETAILS OF E.U.T. 7
3.4 DESCRIPTION OF SUPPORT UNITS 7
3.5 TEST LOCATION 8
3.6 DEVIATION FROM STANDARDS 8
3.7 ABNORMALITIES FROM STANDARD CONDITIONS 8
3.8 OTHER INFORMATION REQUESTED BY THE CUSTOMER 8
3.9 TEST FACILITY 8
3.10 MEASUREMENT UNCERTAINTY 8

4 INSTRUMENTS USED DURING TEST 9

5 TEST RESULTS 10

5.1 E.U.T. TEST CONDITIONS 10
5.2 ANTENNA REQUIREMENT 12
5.3 OCCUPIED BANDWIDTH 13
5.4 CARRIER FREQUENCIES SEPARATED 20
5.5 HOPPING CHANNEL NUMBER 28
5.6 DWELL TIME 31
5.7 MAXIMUM PEAK OUTPUT POWER 44
5.8 CONDUCTED SPURIOUS EMISSIONS 51
5.9 RADIATED SPURIOUS EMISSIONS 57
5.9.1 Harmonic and other spurious emission 60
5.10 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS 85
5.11 BAND EDGES REQUIREMENT 87
5.12 CONDUCTED EMISSIONS AT MAINS TERMINALS 150 KHZ TO 30 MHZ 94
5.12.1 Measurement Data 96
5.13 OTHER REQUIREMENTS FREQUENCY HOPPING SPREAD SPECTRUM SYSTEM 102

3 General Information

3.1 Client Information

Applicant:	ChamSys Ltd
Address of Applicant:	Unit 3B Richmond Works, Pitt Road, Freemantle, Southampton, SO15 3FQ United Kingdom

3.2 General Description of E.U.T.

Name:	QuickQ Consoles
Model No.:	QuickQ Rack
Trade Mark:	CHAMSYS
Operating Frequency:	2402 MHz to 2480 MHz for Bluetooth.
Channels:	79 channels with 1MHz step for Bluetooth
Bluetooth Version:	4.0 This report is for classic mode.
Modulation Technique:	Frequency Hopping Spread Spectrum (FHSS)
Type of Modulation	GFSK, (π/4) DQPSK, 8DPSK for Bluetooth
Dwell time	Per channel is less than 0.4s.
Antenna Type	SMA-reverse antenna
Antenna gain:	3 dBi
Function:	QuickQ Consoles

3.3 Details of E.U.T.

EUT Power Supply:	AC 120V 60HZ
Test mode:	The program used to control the EUT for staying in continuous transmitting and receiving mode is programmed. Channel lowest (2402MHz), middle (2441MHz) and highest (2480MHz) are chosen for Bluetooth full testing. Normal mode: the Bluetooth has been tested on the Modulation of GFSK; EDR mode: the Bluetooth has been tested on the Modulation of (π/4)DQPSK and 8DPSK, compliance test and record the worst case on (π/4)DQPSK and 8DPSK
Power cord:	/

3.4 Description of Support Units

The EUT has been tested as an independent unit for fixed frequency by testing lab.

Details of Support Equipment(s)

Description	Manufacturer	Model No.	Connection	Working state
/	/	/	/	/

3.5 Test Location

All tests were performed at:

ITL Co., Ltd
No. 8 Jinqianling Street 5, Huangjiang Town, Dongguan, Guangdong, 523757 P.R.C.
0086-769-39001678
itl@i-testlab.com

No tests were sub-contracted.

3.6 Deviation from Standards

Biconical and log periodic antennas were used instead of dipole antennas.

3.7 Abnormalities from Standard Conditions

None.

3.8 Other Information Requested by the Customer

None.

3.9 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS Lab code:L9342**
- **FCC Designation No.:CN5035**
- **IC Registration NO.: 12593A**
- **NVLAP LAB CODE: 600199-0**

3.10 Measurement Uncertainty

The below measurement uncertainties given below are based on a 95% confidence level (base on a coverage factor (k=2).)

Parameter	Uncertainty
Radio frequency	2.25%
total RF power, conducted	±1.34 dB
RF power density , conducted	±1.49 dB
All emissions, radiated	±2.72 dB
Temperature	±5.02 dB
Humidity	±0.8°C
DC and low frequency voltages	±1.5 %

4 Instruments Used during Test

No.	Test Equipment	Manufacturer	Model	Serial No.	Cal Data	Due Date
DGITL- 301	Semi-Anechoic chamber	ETS•Lindgren	9*6*6	CT000874-1181	2023.08.02	2026.08.02
DGITL- 307	EMI test receiver	SCHWARZBECK	ESVS10	833616/003	2024.03.15	2025.03.15
DGITL-376	Wideband Radio Communication Tester	SCHWARZBECK	CMW500	LR114195	2024.03.15	2025.03.15
DGITL-349a	Vector Signal Generator	ROHDE&SCHWARZ	SMBV100A	259268	2024.03.15	2025.03.15
DGITL- 306	Spectrum Analyzer	Agilent Technologies	N9010A	MY54200334	2024.03.15	2025.03.15
DGITL- 352	Pre Amplifier	MInI-CIrcuits	ZFC-1000HX	SN292801110	2024.03.15	2025.03.15
DGITL-375	Spectrum Analyzer	SCHWARZBECK	FSV40-N	6625-01-588-5515	2024.03.15	2025.03.15
DGITL-309	Horn Antenna	ETS Lindgren	3117	SN00152265	2023.05.14	2025.05.14
DGITL-308	Bilog Antenna	ETS· Lindgren	3142E	156975	2023.05.14	2025.05.14
DGITL-350	Wideband Amplifier Super Ultra	MInI-CIrcuits	ZVA-183X-S+	SN986401426	2024.03.15	2025.03.15
DGITL-371	Pre Amplifier	teramicrowave	TALA-0040G35	18081001	2024.03.15	2025.03.15

5 Test Results

5.1 E.U.T. test conditions

Test Voltage: Input: AC 120V 60HZ

Temperature: 20.0 -25.0 °C

Humidity: 38-50 % RH

Atmospheric Pressure: 1000 -1010 mbar

Test frequencies and frequency range: According to the 15.31(m) Measurements on intentional radiators or receivers, other than TV broadcast receivers, shall be performed and, if required, reported for each band in which the device can be operated with the device operating at the number of frequencies in each band specified in the following table:

According to the 15.33 (a) For an intentional radiator, the spectrum shall be investigated from the lowest radio frequency signal generated in the device, without going below 9 kHz, up to at least the frequency shown in the following table:

Number of fundamental frequencies to be tested in EUT transmit band

Frequency range in which	Number of frequencies	Location in frequency range of operation
1 MHz or less	1	Middle
1 MHz to 10 MHz	2	1 near top and 1 near bottom
More than 10 MHz	3	1 near top, 1 near middle and 1 near bottom

Frequency range of radiated emission measurements

Lowest frequency generated	Upper frequency range of measurement
9 kHz to below 10 GHz	10th harmonic of highest fundamental frequency or to 40 GHz,
At or above 10 GHz to below	5th harmonic of highest fundamental frequency or to 100 GHz,
At or above 30 GHz	5th harmonic of highest fundamental frequency or to 200 GHz,

EUT channels and frequencies list for Bluetooth:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	11	2413	22	2424
1	2403	12	2414	23	2425
2	2404	13	2415	24	2426
3	2405	14	2416	25	2427
4	2406	15	2417	26	2428
5	2407	16	2418	27	2429
6	2408	17	2419	28	2430
7	2409	18	2420	29	2431
8	2410	19	2421	30	2432
9	2411	20	2422	31	2433
10	2412	21	2423	32	2434
33	2435	49	2451	65	2467
34	2436	50	2452	66	2468
35	2437	51	2453	67	2469
36	2438	52	2454	68	2470
37	2439	53	2455	69	2471
38	2440	54	2456	70	2472
39	2441	55	2457	71	2473
40	2442	56	2458	72	2474
41	2443	57	2459	73	2475
42	2444	58	2460	74	2476
43	2445	59	2461	75	2477
44	2446	60	2462	76	2478
45	2447	61	2463	77	2479
46	2448	62	2464	78	2480
47	2449	63	2465		
48	2450	64	2466		

Test frequencies are the Lowest Channel 0 channel (2402 MHz), Middle Channel 39 channel (2441 MHz) and Highest Channel 78 channel (2480 MHz)

5.2 Antenna requirement

Standard requirement

15.203 requirements:

For intentional device. According to 15.203 an intentional radiator shall be designed to Ensure that no antenna other than that furnished by the responsible party shall be used with the device.

15.247(c) (1) (i) requirement:

(i) Systems operating in the 2400-2483.5 MHz bands that are used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna

The antenna is a SMA-reverse antenna and no consideration of replacement. The best case gain of the antenna is 3dBi.

Test result: The unit does meet the FCC requirements.

5.3 Occupied Bandwidth

Test Requirement: FCC Part 15 C section 15.247

(a)(1) Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Method: ANSI C63.10:2013

Test Status: Pre-test the EUT in continuous transmitting mode at the lowest, middle and highest channel with different data package. Compliance test in normal mode (DH5), EDR mode (2DH5) and EDR mode (3DH5) as the worst case was found.

Test Configuration:



Test Procedure:

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: Span = approximately 2 to 3 times the 20dB bandwidth, centring on a hopping channel;
3. Set the spectrum analyzer: RBW >= 1% of the 20dB bandwidth VBW >= RBW. Sweep = auto; Detector Function = Peak. Trace = Max Hold.
4. Mark the peak frequency and -20dB points bandwidth.

Test result (-20dB bandwidth), For Bluetooth

Normal mode:

Test Channel	Bandwidth(MHz)	2/3 bandwidth(MHz)
Lowest	1.011	0.674
Middle	1.014	0.676
Highest	1.008	0.672

EDR mode (2DH5):

Test Channel	Bandwidth(MHz)	2/3 bandwidth(MHz)
Lowest	1.237	0.825
Middle	1.249	0.833
Highest	1.231	0.821

EDR mode (3DH5):

Test Channel	Bandwidth(MHz)	2/3 bandwidth(MHz)
Lowest	1.283	0.855
Middle	1.275	0.850
Highest	1.284	0.856

For Bluetooth

Result plot as follows:

DH5

Lowest Channel



Middle Channel



Highest Channel



2DH5

Lowest Channel



Middle Channel



Highest Channel



3DH5

Lowest Channel



Middle Channel



Highest Channel



5.4 Carrier Frequencies Separated

Test Requirement: FCC Part 15 C section 15.247

(a),(1) Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Method: ANSI C63.10:2013

Test Status: Pre-test the EUT in continuous transmitting mode at the lowest, middle and highest channel with different data package. Compliance test in normal mode (DH5), EDR mode (2DH5) and EDR mode (3DH5) as the worst case was found.

Test Configuration:



Test Procedure:

1. Remove the antenna from the EUT and then connect a low attenuation RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW >= 1% of the span, VBW >= RBW, Sweep = auto; Detector Function = Peak. Trace = Max, hold.
3. Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section. Submit this plot.

Test result:

For Bluetooth

DH5

Test Channel	Carrier Frequencies Separated	Pass/Fail
Lower Channels (channel 0 and channel 1)	1.00MHz	Pass
Middle Channels (channel 39 and channel 40)	1.00MHz	Pass
Upper Channels (channel 77 and channel 78)	1.00MHz	Pass
Remark: The limit is maximum two-thirds of the 20 dB bandwidth: 0.676 MHz		

2DH5

Test Channel	Carrier Frequencies Separated	Pass/Fail
Lower Channels (channel 0 and channel 1)	1.00MHz	Pass
Middle Channels (channel 39 and channel 40)	1.00MHz	Pass
Upper Channels (channel 77 and channel 78)	1.00MHz	Pass
Remark: The limit is maximum two-thirds of the 20 dB bandwidth: 0.833 MHz		

3DH5

Test Channel	Carrier Frequencies Separated	Pass/Fail
Lower Channels (channel 0 and channel 1)	1.00MHz	Pass
Middle Channels (channel 39 and channel 40)	1.00MHz	Pass
Upper Channels (channel 77 and channel 78)	1.00MHz	Pass
Remark: The limit is maximum two-thirds of the 20 dB bandwidth: 0.856 MHz		

For Bluetooth
Carrier Frequencies Separated plot:
DH5

1. Lowest Channels

2. Middle Channels

3. Highest Channels

2DH5

1. Lowest Channels



2. Middle Channels



3. Highest Channels



3DH5

1. Lowest Channels

2. Middle Channels



3. Highest Channels

5.5 Hopping Channel Number

Test Requirement: FCC Part15 C section 15.247
(a)(1)(iii) Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

Test Method: ANSI C63.10:2013

Test Status: Pre-test the EUT in hopping mode with different data packet. Compliance test in hopping with normal mode (DH5), EDR mode (2DH5) and EDR mode (3DH5) as the worst case was found.

Test Configuration:



Test Procedure:

1. Remove the antenna from the EUT and then connect a low attenuation RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 100 kHz. VBW = 300 kHz. Sweep = auto; Detector Function = Peak. Trace = Max hold.
3. Allow the trace to stabilize. It may prove necessary to break the span up to sections. in order to clearly show all of the hopping frequencies. The limit is specified in one of the subparagraphs of this Section.
4. Set the spectrum analyzer: start frequency = 2400 MHz. stop frequency = 2483.5 MHz. Submit the test result graph.

For Bluetooth

Test result: Total channels are 79 channels.
DH5



2DH5



3DH5



Test result: The unit does meet the FCC requirements.

5.6 Dwell Time

Test Requirement: FCC Part 15 C section 15.247

(a)(1)(iii) Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Method: ANSI C63.10:2013

Test Status: Pre-test the EUT in continuous transmitting mode at the lowest, middle and highest channel with different data packet. Compliance test in hopping with Normal mode (DH1, DH3 and DH5) and EDR mode (2DH1, 2DH3 and 2DH5; 3DH1, 3DH3 and 3DH5) as the worst case was found.

Test Configuration:



Test Procedure:

1. Remove the antenna from the EUT and then connect a low attenuation RF cable from the antenna port to the spectrum.

2. Set spectrum analyzer span = 0. centre on a hopping channel;
3. Set RBW = 1 MHz and VBW = 3 MHz. Sweep = as necessary to capture the entire dwell time per hopping channel. Detector Function = Peak. Trace = View;
4. Use the marker-delta function to determine the dwell time. If this value varies with different modes of operation (e.g.. data rate. modulation format. etc.). Repeat this test for each variation.
The limit is specified in one of the subparagraphs of this Section. Submit this plot(s). An oscilloscope may be used instead of a spectrum analyzer.

Test Result:

For Bluetooth

The test period: T= 0.4 Second/Channel x 79 Channel = 31.6 s

1. **Channel 0:** 2.402GHz

DH1 time slot = 0.403 (ms) * (1600/(2*79)) * 31.6 = 129.0ms

DH3 time slot = 1.660 (ms) * (1600/(4*79)) * 31.6 = 265.6ms

DH5 time slot = 2.911 (ms) * (1600/(6*79)) * 31.6 = 310.5ms

2. **Channel 39:** 2.441GHz

DH1 time slot = 0.407 (ms) * (1600/(2*79)) * 31.6 = 130.2ms

DH3 time slot = 1.663 (ms) * (1600/(4*79)) * 31.6 = 266.1ms

DH5 time slot = 2.909 (ms) * (1600/(6*79)) * 31.6 = 310.3ms

3. **Channel 78:** 2.480GHz

DH1 time slot = 0.403 (ms) * (1600/(2*79)) * 31.6 = 129.0ms

DH3 time slot = 1.659 (ms) * (1600/(4*79)) * 31.6 = 265.4ms

DH5 time slot = 2.911 (ms) * (1600/(6*79)) * 31.6 = 310.5ms

4. **Channel 0:** 2.402GHz

3DH1 time slot = 0.419 (ms) * (1600/(2*79)) * 31.6 = 134.1ms

3DH3 time slot = 1.663 (ms) * (1600/(4*79)) * 31.6 = 266.1ms

3DH5 time slot = 2.919 (ms) * (1600/(6*79)) * 31.6 = 311.4ms

5. **Channel 39:** 2.441GHz

3DH1 time slot = 0.411 (ms) * (1600/(2*79)) * 31.6 = 131.5ms

3DH3 time slot = 1.667 (ms) * (1600/(4*79)) * 31.6 = 266.7ms

3DH5 time slot = 2.919 (ms) * (1600/(6*79)) * 31.6 = 311.4ms

6. **Channel 78:** 2.480GHz

3DH1 time slot = 0.415 (ms) * (1600/(2*79)) * 31.6 = 132.8ms

3DH3 time slot = 1.667 (ms) * (1600/(4*79)) * 31.6 = 266.7ms

3DH5 time slot = 2.919 (ms) * (1600/(6*79)) * 31.6 = 311.4ms

The results are not greater than 0.4 seconds

The unit does meet the FCC requirements.

For Bluetooth

Please refer the graph as below:

1. Lowest channel (2.402 GHz):

(1) DH1



(2) DH3



(3) DH5



2. Middle channel (2.441 GHz):

(1) DH1



(2) DH3


Agilent Spectrum Analyzer - Swept SA
Center Freq 2.441000000 GHz
Trig Delay: -500.0 µs
Trig: Video
Atten: 30 dB
Avg Type: Log-Pwr
12:47:22PM Aug 28, 2019
Mkr1 600.0 µs
3.30 dBm
10 dB/div
Ref 15.00 dBm
-40.00 dB
1.663 ms
Center 2.441000000 GHz
Res BW 1.0 MHz
#VBW 3.0 MHz
Span 0 Hz
Sweep 4.000 ms (1001 pts)
Frequency
Auto Tune
Center Freq
2.441000000 GHz
Start Freq
2.441000000 GHz
Stop Freq
2.441000000 GHz
CF Step
1.000000 MHz
Auto
Man
Freq Offset
0 Hz

(3) DH5


Agilent Spectrum Analyzer - Swept SA
Center Freq 2.441000000 GHz
Trig Delay: -500.0 µs
Trig: Video
Atten: 30 dB
Avg Type: Log-Pwr
12:05:00PM Aug 28, 2019
Mkr1 600.0 µs
3.35 dBm
10 dB/div
Ref 15.00 dBm
-40.00 dB
2.909 ms
Center 2.441000000 GHz
Res BW 1.0 MHz
#VBW 3.0 MHz
Span 0 Hz
Sweep 4.000 ms (1001 pts)
Frequency
Auto Tune
Center Freq
2.441000000 GHz
Start Freq
2.441000000 GHz
Stop Freq
2.441000000 GHz
CF Step
1.000000 MHz
Auto
Man
Freq Offset
0 Hz

3. Highest channel (2.480 GHz):

(1) DH1



(2) DH3



(3) DH5

4. Lowest channel (2.402 GHz):

(1) 3DH1



(2) 3DH3


Agilent Spectrum Analyzer - Swept SA
Center Freq 2.402000000 GHz
Trig Delay: -500.0 µs
Trig: Video
Atten: 30 dB
Avg Type: Log-Pwr
PNO: Fast
IFGain:Low
12:51:38PM Aug 28, 2019
Mkr1 600.0 µs
3.35 dBm
10 dB/div
Ref 15.00 dBm
-40.00 dB
1.663 ms
Center 2.402000000 GHz
Res BW 1.0 MHz
#VBW 3.0 MHz
Span 0 Hz
Sweep 4.000 ms (1001 pts)
Frequency
Auto Tune
Center Freq
2.402000000 GHz
Start Freq
2.402000000 GHz
Stop Freq
2.402000000 GHz
CF Step
1.000000 MHz
Auto
Man
Freq Offset
0 Hz

(3) 3DH5


Agilent Spectrum Analyzer - Swept SA
Center Freq 2.402000000 GHz
Trig Delay: -500.0 µs
Trig: Video
Atten: 30 dB
Avg Type: Log-Pwr
PNO: Fast
IFGain:Low
12:16:56PM Aug 28, 2019
Mkr1 600.0 µs
3.36 dBm
10 dB/div
Ref 15.00 dBm
-40.00 dB
2.919 ms
Center 2.402000000 GHz
Res BW 1.0 MHz
#VBW 3.0 MHz
Span 0 Hz
Sweep 4.000 ms (1001 pts)
Frequency
Auto Tune
Center Freq
2.402000000 GHz
Start Freq
2.402000000 GHz
Stop Freq
2.402000000 GHz
CF Step
1.000000 MHz
Auto
Man
Freq Offset
0 Hz

5. Middle channel (2.441 GHz):

(1) 3DH1



(2) 3DH3



(3) 3DH5



6. Highest channel (2.480 GHz):

(1) 3DH1



(2) 3DH3


Agilent Spectrum Analyzer - Swept SA
Center Freq 2.480000000 GHz
Trig Delay: -500.0 µs
Trig: Video
Atten: 30 dB
Avg Type: Log-Pwr
12:53:26 PM Aug 28, 2019
Mkr1 600.0 µs
2.08 dBm
10 dB/div
Ref 15.00 dBm
-40.00 dB
1.667 ms
Center 2.480000000 GHz
Res BW 1.0 MHz
#VBW 3.0 MHz
Span 0 Hz
Sweep 4.000 ms (1001 pts)
Frequency
Auto Tune
Center Freq
2.480000000 GHz
Start Freq
2.480000000 GHz
Stop Freq
2.480000000 GHz
CF Step
1.000000 MHz
Auto
Man
Freq Offset
0 Hz

(3) 3DH5


Agilent Spectrum Analyzer - Swept SA
Center Freq 2.480000000 GHz
Trig Delay: -500.0 µs
Trig: Video
Atten: 30 dB
Avg Type: Log-Pwr
12:27:23 PM Aug 28, 2019
Mkr1 600.0 µs
1.74 dBm
10 dB/div
Ref 15.00 dBm
-40.00 dB
2.919 ms
Center 2.480000000 GHz
Res BW 1.0 MHz
#VBW 3.0 MHz
Span 0 Hz
Sweep 4.000 ms (1001 pts)
Frequency
Auto Tune
Center Freq
2.480000000 GHz
Start Freq
2.480000000 GHz
Stop Freq
2.480000000 GHz
CF Step
1.000000 MHz
Auto
Man
Freq Offset
0 Hz

Remark:
In communication data link mode (expect inquiry or page mode) the hopping rate is 1600 per second, the 79 channels will be randomly selected for RF channel, and each channel have equal probability to be selected. The hop selection scheme is defined in Clause 2.6 of Part B of Volume

2 of core specification of Bluetooth.

The Dwell time must be calculated via following formula:

Dwell time = Pulse wide x (Hopping rate / Number of channels) x Period

Period = 0.4 (seconds/ channel) x 79 (channel) = 31.6 seconds

So

Dwell time DH1= slot time * (1600/2/79) * 31.6

Dwell time DH3= slot time * (1600/4/79) * 31.6

Dwell time DH5= slot time * (1600/6/79) * 31.6
The RF channel will remain fixed for duration of a packet, that means for DH3 packet the RF frequency will remain unchanged during 3 slots (1slot=1/1600=625us), and for DH5 packet the RF frequency will remain unchanged during 5 slots, illustrated the principle as below:



Figure 2.14: Single- and multi-slot packets.

Therefore, in a certain period for different packet types, the quantities of hops (not hopping rate 1600) are different, accurately, the quantity of hops for DH1 is double of DH3's and triples of DH5's. "For DH1 packet, 1 hop in 1 slot; for DH3 packet, ½ hop in 1 slot; for DH5 packet, 1/3 hop in 1 slot." explained as below:

From the illustrated hopping scheme:
For DH1, in two slots, there are two hops, i.e. f(k) in Slot(k), f(k+1) in Slot(k+1), means DH1 1 hop in 1 slot;

For DH3, in four slots, there are two hops, i.e. f (k) in Slot (k) & Slot (k+1) & Slot (k+2), f(k+3) in Slot (k+3), means DH3 2 hops in four slots -> ½ hop in 1 slot;

For DH5, in six slots, there are two hops, i.e. f(k) in Slot(k) & Slot(k+1) & Slot(k+2) & Slot(k+3) & Slot(k+4), f(k+5) in Slot(k+5), means DH3 2 hops in six slots -> 1/3 hop in 1 slot.

The Hopping rate in the formula should not be fixed value, for DH1, it is 1600/2; for DH3, it is 1600/4; for DH5, it is 1600/6.

To calculate Dwell time of data transmission of Bluetooth system, the worst case is for Bluetooth PICONET that contains two devices only (although Bluetooth PICONET can support up to eight devices), and for Bluetooth data transmission, after device A sending a packet to device B, device A must get response packet from device B to continue data transmission;

For DH1 packet: assume device A is EUT, the worst case is after device A sending a DH1 packet to device B, device A gets a DH1 response packet from device B, that means device A needs 1 time slot for transmitting and 1 time slot for receiving, therefore, the actual hopping rate of device A is half of 1600, i.e. 800 hops per second for EUT;

For DH3 packet: assume device A is EUT, the worst case is after device A sending a DH3 packet to device B, device A gets a DH1 response packet from device B, that means device A needs 3 time slots for transmitting and 1 time slot for receiving, therefore, the actual hopping rate of device A is quarter of 1600, i.e. 400 hops per second for EUT;

For DH5 packet: assume device A is EUT, the worst case is after device A sending a DH5 packet to device B, device A gets a DH1 response packet from device B, that means device A needs 5 time slots for transmitting and 1 time slot for receiving, therefore, the actual hopping rate of device A is sixth of 1600, i.e. 1600/6=266.7 hops per second for EUT;

5.7 Maximum Peak Output Power

Test Requirement: FCC Part 15 C section 15.247

(b)(1)For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125W

Refer to the result "Hopping channel number" of this document. The 1 watt (30.0 dBm) limit applies.

Test Method: ANSI C63.10:2013

Test Limit:

Test mode: Pre-test the EUT in continuous transmitting mode at the lowest, middle and highest channel with different data packet. Compliance test in continuous transmitting mode with normal (DH5), EDR mode (2DH5) and EDR mode (3DH5) as the worst case was found.

Test Configuration:



Test Procedure:

1 . Remove the antenna from the EUT and then connect a low attenuation RF cable from the antenna port to the spectrum.

2 . Set the spectrum analyzer: RBW = 1 MHz. VBW = 3 MHz. Sweep = auto; Detector Function = Peak.

3 . Keep the EUT in transmitting at lowest, medium and highest channel individually. Record the max value.

Test Result: (For Bluetooth)

Normal mode(DH5):

Test Channel	Fundamental Frequency (MHz)	Output Power (dBm)	Limit (dBm)	Result
Lowest	2402	4.41	30.0	Pass
Middle	2441	4.49	30.0	Pass
Highest	2480	4.80	30.0	Pass

EDR mode(2DH5):

Test Channel	Fundamental Frequency (MHz)	Output Power (dBm)	Limit (dBm)	Result
Lowest	2402	5.213	21.0	Pass
Middle	2441	5.285	21.0	Pass
Highest	2480	5.596	21.0	Pass

EDR mode(3DH5):

Test Channel	Fundamental Frequency	Output Power (dBm)	Limit (dBm)	Result
Lowest	2402	5.428	21.0	Pass
Middle	2441	5.467	21.0	Pass
Highest	2480	5.808	21.0	Pass

Remark: cable lose=0.5dB

Test result: The unit does meet the FCC requirements.

Test result plot as follows:

For Bluetooth

Normal mode (DH5):

Lowest Channel



Middle Channel



Highest Channel



EDR mode (2DH5):

Lowest Channel



Middle Channel



Highest Channel



EDR mode (3DH5):

Lowest Channel



Middle Channel

Highest Channel



5.8 Conducted Spurious Emissions

Test Requirement: FCC Part15 C section 15.247

(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating. The radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. Based on either an RF conducted or a radiated measurement. Provided the transmitter demonstrates compliance with the peak conducted power limits.

Test Method: ANSI C63.10:2013

Test Status: Pre-test the EUT in continuous transmitting mode at the lowest, middle and highest channel with different data packet. Compliance test in continuous transmitting mode with normal (DH5), EDR mode (2DH5) and EDR mode (3DH5) as the worst case was found.

Test Configuration:



Test Procedure:

1. Remove the antenna from the EUT and then connect a low attenuation RF cable from the antenna port to the spectrum.

2. Set the spectrum analyzer: RBW = 100 kHz. VBW >= RBW. Sweep = auto; Detector Function = Peak (Max. hold).

For Bluetooth

Test result plot as follows (Normal mode DH5):

Lowest Channel

Middle Channel

Highest channel

Test result plot as follows (EDR mode-2DH5):
Lowest Channel

Middle Channel

Highest channel

Test result plot as follows (EDR mode-3DH5):

Lowest Channel

Middle Channel

Highest channel

5.9 Radiated Spurious Emissions

Test Requirement: FCC Part15 C section 15.247

(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating. The radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that Contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, and provided the transmitter demonstrates compliance with the peak conducted power limits.

Test Method: ANSI C63.10:2013

Test Status: Pre-test the EUT in continuous transmitting mode at the lowest, middle and highest channel with different data packet. Compliance test in continuous transmitting mode with normal mode (DH5) as the worst case was found.

Detector: For PK value:

RBW = 1 MHz for f ≥ 1 GHz, 100 kHz for f < 1 GHz, 9kHz for <30MHz

VBW ≥ RBW Sweep = auto

Detector function = peak

Trace = max hold

For AV value:

RBW = 1 MHz for f ≥ 1 GHz, 100 kHz for f < 1 GHz, 9kHz for <30MHz

VBW =10 Hz

Sweep = auto

Detector function = peak

Trace = max hold

15.209 Limit:

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Test Configuration:

1) 9kHz to 30MHz emissions:



2) 30 MHz to 1 GHz emissions:



3) 1 GHz to 40 GHz emissions:



Test Procedure: The receiver was scanned from 9 kHz to 25GHz. When an emission was found, the table was rotated to produce the maximum signal strength. An initial pre-scan was performed for in peak detection mode using the receiver. The EUT was measured for both the Horizontal and Vertical polarities and performed a pre-test three orthogonal planes. For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage. After pre-test, it was found that the worse radiation emission was get at the X position. So the data shown was the X position only. The worst case emissions were reported.

Now set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a "duty cycle correction factor", derived from 20log (dwell time/100 ms), in an effort to demonstrate compliance with the 15.209 limit. Submit this data.

For the radiated emission test above 1GHz:

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

5.9.1 Harmonic and other spurious emission

With Power Supply MW

9 kHz~30MHz Test result

The Low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not report

30 MHz~1 GHz Spurious Emissions .Quasi-Peak Measurement

Horizontal:

Peak scan

Level (dBµV/m)



Quasi-peak measurement

No.	Freq MHz	Read Level dBuV	Antenna Factor dB	Cable Loss dB	Preamp Factor dB	Level dBuV/m	Limit Line dBuV/m	Over Limit dB	Pol/Phase	Remark
1	159.980	39.18	12.00	1.51	28.10	24.59	13.50	-18.91	HORIZONTAL	QP
2	250.190	37.60	17.10	1.93	27.31	29.32	16.00	-16.68	HORIZONTAL	QP
3	280.260	32.36	17.22	2.05	27.69	23.94	16.00	-22.06	HORIZONTAL	QP
4	320.030	34.40	17.76	2.19	27.52	26.83	16.00	-19.17	HORIZONTAL	QP
5	375.320	46.60	19.03	2.36	28.40	39.59	16.00	-6.41	HORIZONTAL	QP
6	749.740	27.93	24.35	3.44	27.50	28.22	46.00	-17.78	HORIZONTAL	QP

Level=Read Level + Antenna Factor + Cable Loss - Preamp Factor

Vertical:

Peak scan

Level (dBμV/m)



Quasi-peak measurement

No.	Freq MHz	Read Level dBuV	Antenna Factor dB	Cable Loss dB	Preamp Factor dB	Level dBuV/m	Limit Line dBuV/m	Over Limit dB	Pol/Phase	Remark
1	54.250	40.23	10.04	0.84	28.42	22.69	40.00	-17.31	VERTICAL	QP
2	159.980	40.99	12.00	1.51	28.10	26.40	43.50	-17.10	VERTICAL	QP
3	239.520	38.11	16.39	1.88	27.21	29.17	46.00	-16.83	VERTICAL	QP
4	280.260	36.57	17.22	2.05	27.69	28.15	46.00	-17.85	VERTICAL	QP
5	375.320	37.04	19.03	2.36	28.40	30.03	46.00	-15.97	VERTICAL	QP
6	593.570	26.35	22.78	3.04	28.33	23.84	46.00	-22.16	VERTICAL	QP

Level=Read Level + Antenna Factor + Cable Loss - Preamp Factor

Test at low Channel in transmitting status

Spurious emissions above 1GHz

Horizontal:

Peak scan

Level (dBμV/m)



Quasi-peak measurement

Freq MHz	Read Level dBuV	Antenna Factor dB	Cable Loss dB	Preamp Factor dB	Level dBuV/m	Limit Line dBuV/m	Over Limit dB	Pol/Phase	Remark
7613.000	20.52	37.15	12.53	27.32	42.88	74.00	-31.12	HORIZONTAL	Peak
7613.000	11.07	37.15	12.53	27.32	33.43	54.00	-20.57	HORIZONTAL	Average
11625.000	16.64	39.60	16.05	26.94	45.35	74.00	-28.65	HORIZONTAL	Peak
11625.000	6.07	39.60	16.05	26.94	34.78	54.00	-19.22	HORIZONTAL	Average
15773.000	13.75	39.45	19.39	25.92	46.67	74.00	-27.33	HORIZONTAL	Peak
15773.000	1.18	39.45	19.39	25.92	37.10	54.00	-16.90	HORIZONTAL	Average

Level=Read Level + Antenna Factor + Cable Loss - Preamp Factor

Vertical:

Peak scan

Level (dBμV/m)



Quasi-peak measurement

Freq MHz	Read Level dBuV	Antenna Factor dB	Cable Loss dB	Preamp Factor dB	Level dBuV/m	Limit Line dBuV/m	Over Limit dB	Pol/Phase	Remark
5998.000	21.26	35.99	10.90	27.42	40.73	74.00	-33.27	VERTICAL	Peak
5998.000	11.26	35.99	10.90	27.42	30.73	54.00	-23.27	VERTICAL	Average
8922.000	16.42	38.64	13.81	27.22	41.65	74.00	-32.35	VERTICAL	Peak
8922.000	6.32	38.64	13.81	27.22	31.55	54.00	-22.45	VERTICAL	Average
12951.000	11.90	40.58	17.14	26.50	43.12	74.00	-30.88	VERTICAL	Peak
12951.000	2.83	40.58	17.14	26.50	34.05	54.00	-19.95	VERTICAL	Average

Level=Read Level + Antenna Factor + Cable Loss - Preamp Factor

Test at Middle Channel in transmitting status

Spurious emissions above 1GHz

Horizontal:

Peak scan

Level (dBμV/m)



Quasi-peak measurement

Freq MHz	Read Level dBuV	Antenna Factor dB	Cable Loss dB	Preamp Factor dB	Level dBuV/m	Limit Line dBuV/m	Over Limit dB	Pol/Phase	Remark
5981.000	21.48	35.92	10.88	27.42	40.86	74.00	-33.14	HORIZONTAL	Peak
5981.000	11.34	35.92	10.88	27.42	30.72	54.00	-23.28	HORIZONTAL	Average
10163.000	15.12	38.87	14.77	27.09	41.67	74.00	-32.33	HORIZONTAL	Peak
10163.000	4.75	38.87	14.77	27.09	31.30	54.00	-22.70	HORIZONTAL	Average
15314.000	13.65	39.66	18.99	26.02	46.28	74.00	-27.72	HORIZONTAL	Peak
15314.000	3.83	39.66	18.99	26.02	36.46	54.00	-17.54	HORIZONTAL	Average

Level=Read Level + Antenna Factor + Cable Loss - Preamp Factor

Vertical:

Peak scan

Level (dBμV/m)



Quasi-peak measurement

Freq MHz	Read Level dBuV	Antenna Factor dB	Cable Loss dB	Preamp Factor dB	Level dBuV/m	Limit Line dBuV/m	Over Limit dB	Pol/Phase	Remark
5998.000	22.73	35.99	10.90	27.42	42.20	74.00	-31.80	VERTICAL	Peak
5998.000	12.49	35.99	10.90	27.42	31.96	54.00	-22.04	VERTICAL	Average
7392.000	20.19	37.03	12.31	27.32	42.21	74.00	-31.79	VERTICAL	Peak
7392.000	10.29	37.03	12.31	27.32	32.31	54.00	-21.69	VERTICAL	Average
13002.000	10.85	40.70	17.18	26.48	42.25	74.00	-31.75	VERTICAL	Peak
13002.000	0.99	40.70	17.18	26.48	32.39	54.00	-21.61	VERTICAL	Average

Level=Read Level + Antenna Factor + Cable Loss - Preamp Factor

Test at high Channel in transmitting status

Spurious emissions above 1GHz

Horizontal:

Peak scan

Level (dBµV/m)



Quasi-peak measurement

Freq MHz	Read Level dBuV	Antenna Factor dB	Cable Loss dB	Preamp Factor dB	Level dBuV/m	Limit Line dBuV/m	Over Limit dB	Pol/Phase	Remark
6083.000	22.29	35.92	10.99	27.41	41.79	74.00	-32.21	HORIZONTAL	Peak
6083.000	12.22	35.92	10.99	27.41	31.72	54.00	-22.28	HORIZONTAL	Average
9534.000	17.06	38.81	14.36	27.15	43.08	74.00	-30.92	HORIZONTAL	Peak
9534.000	7.36	38.81	14.36	27.15	33.38	54.00	-20.62	HORIZONTAL	Average
11846.000	13.83	39.60	16.23	26.88	42.78	74.00	-31.22	HORIZONTAL	Peak
11846.000	4.25	39.60	16.23	26.88	33.20	54.00	-20.80	HORIZONTAL	Average

Level=Read Level + Antenna Factor + Cable Loss - Preamp Factor

Vertical:

Peak scan

Level (dBμV/m)



Quasi-peak measurement

Freq MHz	Read Level dBuV	Antenna Factor dB	Cable Loss dB	Preamp Factor dB	Level dBuV/m	Limit Line dBuV/m	Over Limit dB	Pol/Phase	Remark
6321.000	21.32	35.68	11.23	27.39	40.84	74.00	-33.16	VERTICAL	Peak
6321.000	11.66	35.68	11.23	27.39	31.18	54.00	-22.82	VERTICAL	Average
10095.000	14.50	38.92	14.71	27.09	41.04	74.00	-32.96	VERTICAL	Peak
10095.000	5.09	38.92	14.71	27.09	31.63	54.00	-22.37	VERTICAL	Average
15280.000	11.00	39.71	18.96	26.03	43.64	74.00	-30.36	VERTICAL	Peak
15280.000	0.30	39.71	18.96	26.03	32.94	54.00	-21.06	VERTICAL	Average

Level=Read Level + Antenna Factor + Cable Loss - Preamp Factor

With Power Supply XP

9 kHz~30MHz Test result

The Low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not report

30 MHz~1 GHz Spurious Emissions .Quasi-Peak Measurement

Horizontal:

Peak scan

Level (dBμV/m)



Quasi-peak measurement

No.	Freq MHz	Read Level dBuV	Antenna Factor dB	Cable Loss dB	Preamp Factor dB	Level dBuV/m	Limit Line dBuV/m	Over Limit dB	Pol/Phase	Remark
1	32.910	35.57	21.83	0.66	28.71	32.35	40.00	-7.65	HORIZONTAL	QP
2	115.360	45.92	13.09	1.27	27.21	33.07	43.50	-10.43	HORIZONTAL	QP
3	199.750	45.49	13.70	1.70	26.87	34.02	43.50	-9.48	HORIZONTAL	QP
4	280.260	44.58	17.22	2.05	27.16	36.69	46.00	-9.31	HORIZONTAL	QP
5	418.000	35.63	19.85	2.52	27.65	30.35	46.00	-15.65	HORIZONTAL	QP
6	940.830	32.29	26.44	3.89	27.48	35.14	46.00	-10.86	HORIZONTAL	QP

Level=Read Level + Antenna Factor + Cable Loss - Preamp Factor

Vertical:

Peak scan

Level (dBμV/m)



Quasi-peak measurement

No.	Freq MHz	Read Level dBuV	Antenna Factor dB	Cable Loss dB	Preamp Factor dB	Level dBuV/m	Limit Line dBuV/m	Over Limit dB	Pol/Phase	Remark
1	32.910	37.85	24.83	0.66	28.56	34.78	40.00	-5.22	VERTICAL	QP
2	115.360	44.44	13.09	1.27	28.55	30.25	43.50	-13.25	VERTICAL	QP
3	138.640	49.72	12.18	1.40	28.23	35.07	43.50	-8.43	VERTICAL	QP
4	239.520	41.77	16.39	1.88	27.21	32.83	46.00	-13.17	VERTICAL	QP
5	280.260	39.62	17.22	2.05	27.69	31.20	46.00	-14.80	VERTICAL	QP
6	437.400	36.15	20.12	2.58	28.35	30.50	46.00	-15.50	VERTICAL	QP

Level=Read Level + Antenna Factor + Cable Loss - Preamp Factor

Test at low Channel in transmitting status

Spurious emissions above 1GHz

Horizontal:

Peak scan

Level (dBμV/m)



Quasi-peak measurement

Freq MHz	Read Level dBuV	Antenna Factor dB	Cable Loss dB	Preamp Factor dB	Level dBuV/m	Limit Line dBuV/m	Over Limit dB	Pol/Phase	Remark
7358.000	19.25	36.97	12.28	27.33	41.17	74.00	-32.83	HORIZONTAL	Peak
7358.000	9.07	36.97	12.28	27.33	30.99	54.00	-23.01	HORIZONTAL	Average
11251.000	14.20	39.40	15.77	27.00	42.37	74.00	-31.63	HORIZONTAL	Peak
11251.000	4.87	39.40	15.77	27.00	33.04	54.00	-20.96	HORIZONTAL	Average
13988.000	12.88	39.22	17.95	26.22	43.83	74.00	-30.17	HORIZONTAL	Peak
13988.000	2.73	39.22	17.95	26.22	33.68	54.00	-20.32	HORIZONTAL	Average

Level=Read Level + Antenna Factor + Cable Loss - Preamp Factor

Vertical:

Peak scan

Level (dBμV/m)



Quasi-peak measurement

Freq MHz	Read Level dBuV	Antenna Factor dB	Cable Loss dB	Preamp Factor dB	Level dBuV/m	Limit Line dBuV/m	Over Limit dB	Pol/Phase	Remark
5998.000	20.26	35.99	10.90	27.42	39.73	74.00	-34.27	VERTICAL	Peak
5998.000	10.30	35.99	10.90	27.42	29.77	54.00	-24.23	VERTICAL	Average
10690.000	13.71	38.83	15.26	27.05	40.75	74.00	-33.25	VERTICAL	Peak
10690.000	3.01	38.83	15.26	27.05	30.05	54.00	-23.95	VERTICAL	Average
15399.000	11.29	39.54	19.06	26.01	43.88	74.00	-30.12	VERTICAL	Peak
15399.000	1.70	39.54	19.06	26.01	34.29	54.00	-19.71	VERTICAL	Average

Level=Read Level + Antenna Factor + Cable Loss - Preamp Factor

Test at Middle Channel in transmitting status

Spurious emissions above 1GHz

Horizontal:

Peak scan

Level (dBμV/m)



Quasi-peak measurement

Freq MHz	Read Level dBuV	Antenna Factor dB	Cable Loss dB	Preamp Factor dB	Level dBuV/m	Limit Line dBuV/m	Over Limit dB	Pol/Phase	Remark
5369.000	24.64	33.80	10.21	27.52	41.13	74.00	-32.87	HORIZONTAL	Peak
5369.000	14.73	33.80	10.21	27.52	31.22	54.00	-22.78	HORIZONTAL	Average
10163.000	15.12	38.87	14.77	27.09	41.67	74.00	-32.33	HORIZONTAL	Peak
10163.000	5.29	38.87	14.77	27.09	31.84	54.00	-22.16	HORIZONTAL	Average
12288.000	15.82	39.54	16.60	26.75	45.21	74.00	-28.79	HORIZONTAL	Peak
12288.000	5.81	39.54	16.60	26.75	35.20	54.00	-18.80	HORIZONTAL	Average

Level=Read Level + Antenna Factor + Cable Loss - Preamp Factor

Vertical:

Peak scan

Level (dBμV/m)



Quasi-peak measurement

Freq MHz	Read Level dBuV	Antenna Factor dB	Cable Loss dB	Preamp Factor dB	Level dBuV/m	Limit Line dBuV/m	Over Limit dB	Pol/Phase	Remark
7392.000	20.19	37.03	12.31	27.32	42.21	74.00	-31.79	VERTICAL	Peak
7392.000	10.29	37.03	12.31	27.32	32.31	54.00	-21.69	VERTICAL	Average
11251.000	13.52	39.40	15.77	27.00	41.69	74.00	-32.31	VERTICAL	Peak
11251.000	3.54	39.40	15.77	27.00	31.71	54.00	-22.29	VERTICAL	Average
16170.000	9.20	40.25	19.81	25.68	43.58	74.00	-30.42	VERTICAL	Peak
16170.000	0.20	40.25	19.81	25.68	34.58	54.00	-19.42	VERTICAL	Average

Level=Read Level + Antenna Factor + Cable Loss - Preamp Factor

Test at high Channel in transmitting status

Spurious emissions above 1GHz

Horizontal:

Peak scan

Level (dBµV/m)



Quasi-peak measurement

Freq MHz	Read Level dBuV	Antenna Factor dB	Cable Loss dB	Preamp Factor dB	Level dBuV/m	Limit Line dBuV/m	Over Limit dB	Pol/Phase	Remark
6083.000	22.29	35.92	10.99	27.41	41.79	74.00	-32.21	HORIZONTAL	Peak
6083.000	12.58	35.92	10.99	27.41	32.08	54.00	-21.92	HORIZONTAL	Average
10231.000	15.92	38.82	14.83	27.09	42.48	74.00	-31.52	HORIZONTAL	Peak
10231.000	6.92	38.82	14.83	27.09	33.48	54.00	-20.52	HORIZONTAL	Average
13104.000	9.77	40.55	17.27	26.45	41.14	74.00	-32.86	HORIZONTAL	Peak
13104.000	3.77	40.55	17.27	26.45	35.14	54.00	-18.86	HORIZONTAL	Average

Level=Read Level + Antenna Factor + Cable Loss - Preamp Factor

Vertical:

Peak scan

Level (dBμV/m)



Quasi-peak measurement

Freq MHz	Read Level dBuV	Antenna Factor dB	Cable Loss dB	Preamp Factor dB	Level dBuV/m	Limit Line dBuV/m	Over Limit dB	Pol/Phase	Remark
6083.000	20.29	35.92	10.99	27.41	39.79	74.00	-34.21	VERTICAL	Peak
6083.000	10.80	35.92	10.99	27.41	30.30	54.00	-23.70	VERTICAL	Average
9143.000	15.02	38.80	14.02	27.19	40.65	74.00	-33.35	VERTICAL	Peak
9143.000	5.71	38.80	14.02	27.19	31.34	54.00	-22.66	VERTICAL	Average
13325.000	12.26	40.24	17.45	26.38	43.57	74.00	-30.43	VERTICAL	Peak
13325.000	2.20	40.24	17.45	26.38	33.51	54.00	-20.49	VERTICAL	Average

Level=Read Level + Antenna Factor + Cable Loss - Preamp Factor

With Power Supply MORNSUN

9 kHz~30MHz Test result

The Low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not report

30 MHz~1 GHz Spurious Emissions .Quasi-Peak Measurement

Horizontal:

Peak scan

Level (dBμV/m)



Quasi-peak measurement

No.	Freq MHz	Read Level dBuV	Antenna Factor dB	Cable Loss dB	Preamp Factor dB	Level dBuV/m	Limit Line dBuV/m	Over Limit dB	Pol/Phase	Remark
1	31.940	34.40	25.52	0.65	28.54	32.03	40.00	-7.97	HORIZONTAL	QP
2	89.170	48.86	12.07	1.10	28.38	33.65	43.50	-9.85	HORIZONTAL	QP
3	240.490	48.42	16.45	1.89	27.20	39.56	46.00	-6.44	HORIZONTAL	QP
4	375.320	44.06	19.03	2.36	28.40	37.05	46.00	-8.95	HORIZONTAL	QP
5	624.610	38.58	23.15	3.13	28.59	36.27	46.00	-9.73	HORIZONTAL	QP
6	874.870	36.29	25.85	3.74	27.20	38.68	46.00	-7.32	HORIZONTAL	QP

Level=Read Level + Antenna Factor + Cable Loss - Preamp Factor

Vertical:

Peak scan

Level (dBμV/m)



Quasi-peak measurement

No.	Freq MHz	Read Level dBuV	Antenna Factor dB	Cable Loss dB	Preamp Factor dB	Level dBuV/m	Limit Line dBuV/m	Over Limit dB	Pol/Phase	Remark
1	39.700	36.81	20.01	0.71	28.13	29.40	40.00	-10.60	VERTICAL	QP
2	110.510	46.67	12.87	1.24	28.59	32.19	43.50	-11.31	VERTICAL	QP
3	280.260	39.86	17.22	2.05	27.69	31.44	46.00	-14.56	VERTICAL	QP
4	375.320	41.39	19.03	2.36	28.40	34.38	46.00	-11.62	VERTICAL	QP
5	624.610	32.82	23.15	3.13	28.59	30.51	46.00	-15.49	VERTICAL	QP
6	874.870	30.87	25.85	3.74	27.20	33.26	46.00	-12.74	VERTICAL	QP

Level=Read Level + Antenna Factor + Cable Loss - Preamp Factor

Test at low Channel in transmitting status

Spurious emissions above 1GHz

Horizontal:

Peak scan

Level (dBμV/m)



Quasi-peak measurement

Freq MHz	Read Level dBuV	Antenna Factor dB	Cable Loss dB	Preamp Factor dB	Level dBuV/m	Limit Line dBuV/m	Over Limit dB	Pol/Phase	Remark
5845.000	23.62	35.35	10.73	27.44	42.26	74.00	-31.74	HORIZONTAL	Peak
5845.000	13.42	35.35	10.73	27.41	32.06	54.00	-21.94	HORIZONTAL	Average
10384.000	14.62	38.69	14.97	27.08	41.20	74.00	-32.80	HORIZONTAL	Peak
10384.000	4.40	38.69	14.97	27.08	30.98	54.00	-23.02	HORIZONTAL	Average
13988.000	12.88	39.22	17.95	26.22	43.83	74.00	-30.17	HORIZONTAL	Peak
13988.000	2.50	39.22	17.95	26.22	33.45	54.00	-20.55	HORIZONTAL	Average

Level=Read Level + Antenna Factor + Cable Loss - Preamp Factor

Vertical:

Peak scan

Level (dBμV/m)



Quasi-peak measurement

Freq MHz	Read Level dBuV	Antenna Factor dB	Cable Loss dB	Preamp Factor dB	Level dBuV/m	Limit Line dBuV/m	Over Limit dB	Pol/Phase	Remark
6899.000	17.63	36.22	11.83	27.35	38.33	74.00	-35.67	VERTICAL	Peak
6899.000	7.12	36.22	11.83	27.35	27.82	54.00	-26.18	VERTICAL	Average
9891.000	12.71	38.96	14.56	27.11	39.12	74.00	-34.88	VERTICAL	Peak
9891.000	2.67	38.96	14.56	27.11	29.08	54.00	-24.92	VERTICAL	Average
13478.000	10.58	40.03	17.57	26.33	41.85	74.00	-32.15	VERTICAL	Peak
13478.000	0.30	40.03	17.57	26.33	31.57	54.00	-22.43	VERTICAL	Average

Level=Read Level + Antenna Factor + Cable Loss - Preamp Factor

Test at Middle Channel in transmitting status

Spurious emissions above 1GHz

Horizontal:

Peak scan

Level (dBμV/m)



Quasi-peak measurement

Freq MHz	Read Level dBuV	Antenna Factor dB	Cable Loss dB	Preamp Factor dB	Level dBuV/m	Limit Line dBuV/m	Over Limit dB	Pol/Phase	Remark
5369.000	24.64	33.80	10.21	27.52	41.13	74.00	-32.87	HORIZONTAL	Peak
5369.000	14.73	33.80	10.21	27.52	31.22	54.00	-22.78	HORIZONTAL	Average
12611.000	13.26	39.77	16.87	26.64	43.26	74.00	-30.74	HORIZONTAL	Peak
12611.000	3.35	39.77	16.87	26.64	33.35	54.00	-20.65	HORIZONTAL	Average
17320.000	7.26	42.60	20.43	25.19	45.10	74.00	-28.90	HORIZONTAL	Peak
17320.000	-2.25	42.60	20.43	25.19	35.59	54.00	-18.41	HORIZONTAL	Average

Level=Read Level + Antenna Factor + Cable Loss - Preamp Factor

Vertical:

Peak scan

Level (dBμV/m)



Quasi-peak measurement

Freq MHz	Read Level dBuV	Antenna Factor dB	Cable Loss dB	Preamp Factor dB	Level dBuV/m	Limit Line dBuV/m	Over Limit dB	Pol/Phase	Remark
6287.000	23.68	35.71	11.20	27.39	43.20	74.00	-30.80	VERTICAL	Peak
6287.000	13.97	35.71	11.20	27.39	33.49	54.00	-20.51	VERTICAL	Average
13002.000	10.85	40.70	17.18	26.48	42.25	74.00	-31.75	VERTICAL	Peak
13002.000	0.96	40.70	17.18	26.48	32.36	54.00	-21.64	VERTICAL	Average
16691.000	10.20	40.83	20.01	25.57	45.47	74.00	-28.53	VERTICAL	Peak
16691.000	0.30	40.83	20.01	25.57	35.57	54.00	-18.43	VERTICAL	Average

Level=Read Level + Antenna Factor + Cable Loss - Preamp Factor

Test at high Channel in transmitting status

Spurious emissions above 1GHz

Horizontal:

Peak scan

Level (dBµV/m)



Quasi-peak measurement

Freq MHz	Read Level dBuV	Antenna Factor dB	Cable Loss dB	Preamp Factor dB	Level dBuV/m	Limit Line dBuV/m	Over Limit dB	Pol/Phase	Remark
6083.000	20.29	35.92	10.99	27.41	39.79	74.00	-34.21	HORIZONTAL	Peak
6083.000	9.58	35.92	10.99	27.41	29.08	54.00	-24.92	HORIZONTAL	Average
8837.000	15.52	38.47	13.73	27.22	40.50	74.00	-33.50	HORIZONTAL	Peak
8837.000	5.12	38.47	13.73	27.22	30.10	54.00	-23.90	HORIZONTAL	Average
13104.000	8.77	40.55	17.27	26.45	40.14	74.00	-33.86	HORIZONTAL	Peak
13104.000	-1.23	40.55	17.27	26.45	30.14	54.00	-23.86	HORIZONTAL	Average

Level=Read Level + Antenna Factor + Cable Loss - Preamp Factor

Vertical:

Peak scan

Level (dBμV/m)



Quasi-peak measurement

Freq MHz	Read Level dBuV	Antenna Factor dB	Cable Loss dB	Preamp Factor dB	Level dBuV/m	Limit Line dBuV/m	Over Limit dB	Pol/Phase	Remark
6321.000	20.32	35.68	11.23	27.39	39.84	74.00	-34.16	VERTICAL	Peak
6321.000	10.08	35.68	11.23	27.39	29.60	54.00	-24.10	VERTICAL	Average
10095.000	14.50	38.92	14.71	27.09	41.04	74.00	-32.96	VERTICAL	Peak
10095.000	4.24	38.92	14.71	27.09	30.78	54.00	-23.22	VERTICAL	Average
15280.000	10.00	39.71	18.96	26.03	42.64	74.00	-31.36	VERTICAL	Peak
15280.000	-1.29	39.71	18.96	26.03	31.35	54.00	-22.65	VERTICAL	Average

Level=Read Level + Antenna Factor + Cable Loss - Preamp Factor

Remark:

1). The field strength is calculated by adding the Antenna Factor. Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level =Receiver Reading + Antenna Factor + Cable Loss –Preamplifier Factor.

2). As shown in Section, for frequencies above 1000 MHz. the above field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

3). The test only perform the EUT in transmitting status since the test frequencies were over 1GHz only required transmitting status.

Test result: The unit does meet the FCC requirements.

5.10 Radiated Emissions which fall in the restricted bands

Test Requirement: FCC Part15 C Section 15.247

(d) In addition, radiated emissions which fall in the restricted bands. as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

Test Method: ANSI C63.10:2013 Clause 6.4, 6.5 and 6.6

Test Status: Pre-test the EUT in continuous transmitting mode at the lowest (2402MHz), middle (2441 MHz) and highest (2480 MHz) channel with different data packet. Compliance test in continuous transmitting mode with normal mode (DH5) as the worst case was found.

Measurement Distance: 3m (Semi-Anechoic Chamber)

Limit: Section 15.209(a)

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Detector: For PK value:

RBW = 1 MHz for f ≥ 1 GHz, 100 kHz for f < 1 GHz

VBW ≥ RBW Sweep = auto

Detector function = peak

Trace = max hold

For AV value:

RBW = 1 MHz for f ≥ 1 GHz, 100 kHz for f < 1 GHz

VBW =10 Hz

Sweep = auto

Detector function = peak

Trace = max hold

Test Result:

For Bluetooth

Test mode: DH5

Frequency (MHz)	Reading Level (dBμV/m)	Correct (dB/m)	Emission Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Antenna polarization	Detector
Low Channel							
2310.000	32.14	6.54	38.68	74.00	-35.32	H	PK
2310.000	18.74	6.54	25.28	54.00	-28.72	H	AV
2390.000	32.64	6.61	39.25	74.00	-34.75	V	PK
2390.000	19.05	6.61	25.66	54.00	-28.34	V	AV
High Channel							
2483.500	33.26	6.70	39.96	74.00	-34.04	H	PK
2483.500	19.48	6.70	26.18	54.00	-27.82	H	AV
2500.000	32.67	6.72	39.39	74.00	-34.61	V	PK
2500.000	18.48	6.72	25.20	54.00	-28.80	V	AV

Remark: No any other emission which falls in restricted bands can be detected and be reported.

Test result: The unit does meet the FCC requirements.

5.11 Band Edges Requirement

Test Requirement: FCC Part15 C section 15.247

(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

Frequency Band: 2400 MHz to 2483.5 MHz

Test Method: ANSI C63.10:2013 Clause 6.9

Test Status: Pre-test the EUT in continuous transmitting mode at the lowest (2402 MHz), and highest (2480 MHz) channel and hopping mode with different data packet. Compliance test in continuous transmitting mode with normal (DH5) EDR mode (2DH5) and EDR mode (3DH5) as the worst case was found.

Test Configuration:



Test Procedure: Set RBW of spectrum analyzer to 100 kHz and VBW of spectrum analyzer to 300 kHz with suitable frequency span including 10MHz bandwidth from band edge.

The band edges was measured and recorded Result:

The Lower Edges attenuated more than 20dB.

The Upper Edges attenuated more than 20dB.

The graph as below. Represents the emissions take for this device.

For Bluetooth

DH5

Low channel



High channel



2DH5
Low channel

High channel

3DH5
Low channel

High channel



DH5

Low channel



High channel



2DH5

Low channel

High channel



3DH5

Low channel

High channel

Test result: The unit does meet the FCC requirements.

5.12 Conducted Emissions at Mains Terminals 150 kHz to 30 MHz

Test Requirement: FCC Part 15 C section 15.207

Test Method: ANSI C63.10:2013 Clause 6.2

Test Voltage: 120Vac 60Hz

Frequency Range: 150 kHz to 30 MHz

Detector: Peak for pre-scan (9 kHz Resolution Bandwidth)

Test Limit

Limits for conducted disturbance at the mains ports of class B

Frequency Range	Class B Limit dB(μV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50
NOTE 1 The limit decreases linearly with the logarithm of the frequency in the range 0,15 MHz to 0,50 MHz.		

EUT Operation: Test in normal operating mode. For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage.

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Test Configuration:



Note: 1.Support units were connected to second LISN.
2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

Test procedure:

1. The mains terminal disturbance voltage test was conducted in a shielded room.

2. The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane, but separated from metallic contact with the ground reference plane by 0.1m of insulation.

5.12.1 Measurement Data

An initial pre-scan was performed on the live and neutral lines with peak detector.

Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected. For EUT the communicating was worst case mode.

The following Quasi-Peak and Average measurements were performed on the EUT

With Power Supply MW
Live line:

Peak Scan:

Level (dBµV)



Quasi-peak and Average measurement

NO.	Freq MHz	Level dBuV	Remark	LISN Factor dB	Cable Loss dB	Limit Line dBuV	Margin dB
1	0.154	48.90	QP	9.70	0.20	65.78	-16.88
2	0.154	39.69	Average	9.70	0.20	55.78	-16.09
3	0.585	27.88	QP	9.68	0.28	56.00	-28.12
4	0.585	23.88	Average	9.68	0.28	46.00	-22.12
5	1.191	30.11	QP	9.66	0.32	56.00	-25.89
6	1.191	26.11	Average	9.66	0.32	46.00	-19.89
7	2.448	27.08	QP	9.64	0.36	56.00	-28.92
8	2.448	20.08	Average	9.64	0.36	46.00	-25.92
9	7.446	29.13	QP	9.69	0.42	60.00	-30.87
10	7.446	23.13	Average	9.69	0.42	50.00	-26.87
11	13.267	36.03	QP	9.69	0.45	60.00	-23.97
12	13.267	28.03	Average	9.69	0.45	50.00	-21.97

Level=Read Level + LISN Factor + Cable Loss

Neutral Line

Peak Scan:

Level (dBµV)



Quasi-peak and Average measurement

NO.	Freq MHz	Level dBuV	Remark	LISN Factor dB	Cable Loss dB	Limit Line dBuV	Margin dB
1	0.154	49.69	QP	9.70	0.20	65.78	-16.09
2	0.154	38.69	Average	9.70	0.20	55.78	-17.09
3	0.582	26.23	QP	9.65	0.28	56.00	-29.77
4	0.582	20.23	Average	9.65	0.28	46.00	-25.77
5	1.184	29.22	QP	9.63	0.32	56.00	-26.78
6	1.184	22.22	Average	9.63	0.32	46.00	-23.78
7	3.293	25.53	QP	9.62	0.37	56.00	-30.47
8	3.293	14.53	Average	9.62	0.37	46.00	-31.47
9	7.446	29.13	QP	9.62	0.42	60.00	-30.87
10	7.446	22.13	Average	9.62	0.42	50.00	-27.87
11	13.267	35.03	QP	9.63	0.45	60.00	-24.97
12	13.267	27.03	Average	9.63	0.45	50.00	-22.97

Level=Read Level + LISN Factor + Cable Loss

With Power Supply MORNSUN

Live Line:

Peak Scan:

Level (dBµV)



Quasi-peak and Average measurement

NO.	Freq MHz	Level dBuV	Remark	LISN Factor dB	Cable Loss dB	Limit Line dBuV	Margin dB
1	0.186	51.45	QP	9.68	0.21	64.20	-12.75
2	0.186	39.45	Average	9.68	0.21	54.20	-14.75
3	0.608	43.19	QP	9.68	0.28	56.00	-12.81
4	0.608	34.19	Average	9.68	0.28	46.00	-11.81
5	1.959	39.66	QP	9.65	0.35	56.00	-16.34
6	1.959	22.66	Average	9.65	0.35	46.00	-23.34
7	5.139	36.47	QP	9.61	0.40	60.00	-23.53
8	5.139	17.47	Average	9.61	0.40	50.00	-32.53
9	14.828	33.57	QP	9.71	0.46	60.00	-26.43
10	14.828	20.57	Average	9.71	0.46	50.00	-29.43
11	24.015	33.68	QP	9.67	0.49	60.00	-26.32
12	24.015	24.68	Average	9.67	0.49	50.00	-25.32

Level=Read Level + LISN Factor + Cable Loss

Neutral Line:

Peak Scan:

Level (dBμV)



Quasi-peak and Average measurement

NO.	Freq MHz	Level dBuV	Remark	LISN Factor dB	Cable Loss dB	Limit Line dBuV	Margin dB
1	0.186	50.12	QP	9.65	0.21	64.20	-14.08
2	0.186	34.12	Average	9.65	0.21	54.20	-20.08
3	0.611	41.44	QP	9.64	0.28	56.00	-14.56
4	0.611	29.44	Average	9.64	0.28	46.00	-16.56
5	1.970	43.51	QP	9.62	0.35	56.00	-12.49
6	1.970	24.51	Average	9.62	0.35	46.00	-21.49
7	6.121	38.22	QP	9.62	0.41	60.00	-21.78
8	6.121	33.32	Average	9.62	0.41	50.00	-16.68
9	15.226	32.72	QP	9.63	0.46	60.00	-27.28
10	15.226	18.72	Average	9.63	0.46	50.00	-31.28
11	24.015	35.80	QP	9.63	0.49	60.00	-24.20
12	24.015	24.80	Average	9.63	0.49	50.00	-25.20

Level=Read Level + LISN Factor + Cable Loss

With Power Supply XP

Live Line:

Peak Scan:

Level (dBµV)



Quasi-peak and Average measurement

NO.	Freq MHz	Level dBuV	Remark	LISN Factor dB	Cable Loss dB	Limit Line dBuV	Margin dB
1	0.162	49.28	QP	9.69	0.20	65.34	-16.06
2	0.162	37.28	Average	9.69	0.20	55.34	-18.06
3	0.415	37.82	QP	9.66	0.26	57.55	-19.73
4	0.415	34.82	Average	9.66	0.26	47.55	-12.73
5	1.441	28.95	QP	9.66	0.33	56.00	-27.05
6	1.441	24.95	Average	9.66	0.33	46.00	-21.05
7	3.584	29.25	QP	9.62	0.38	56.00	-26.75
8	3.584	24.25	Average	9.62	0.38	46.00	-21.75
9	15.970	32.16	QP	9.70	0.46	60.00	-27.84
10	15.970	28.16	Average	9.70	0.46	50.00	-21.84
11	20.814	49.50	QP	9.68	0.48	60.00	-10.50
12	20.814	41.50	Average	9.68	0.48	50.00	-8.50

Level=Read Level + LISN Factor + Cable Loss

Neutral Line:

Peak Scan:

Level (dBμV)



Quasi-peak and Average measurement

NO.	Freq MHz	Level dBuV	Remark	LISN Factor dB	Cable Loss dB	Limit Line dBuV	Margin dB
1	0.162	44.17	QP	9.69	0.20	65.34	-21.17
2	0.162	36.17	Average	9.69	0.20	55.34	-19.17
3	0.417	32.01	QP	9.66	0.26	57.51	-25.50
4	0.417	29.01	Average	9.66	0.26	47.51	-18.50
5	2.044	29.58	QP	9.62	0.35	56.00	-26.42
6	2.044	25.58	Average	9.62	0.35	46.00	-20.42
7	12.060	31.27	QP	9.62	0.45	60.00	-28.73
8	12.060	25.22	Average	9.62	0.45	50.00	-24.78
9	15.307	32.69	QP	9.63	0.46	60.00	-27.31
10	15.307	28.24	Average	9.63	0.46	50.00	-21.76
11	20.814	45.33	QP	9.62	0.48	60.00	-14.67
12	20.814	38.33	Average	9.62	0.48	50.00	-11.67

Level=Read Level + LISN Factor + Cable Loss

5.13 Other requirements Frequency Hopping Spread Spectrum System

Test Requirement: 47 CFR Part 15C Section 15.247 (a)(1), (h) requirement

The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals. Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.

The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hop sets to avoid hopping on occupied channels is permitted.

The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

Compliance for section 15.247(a)(1)

According to Bluetooth Core Specification, the pseudorandom sequence may be generated in a nine stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONEs; i.e. the shift register is initialized with nine ones.

• Number of shift registers stages: 9

• Length of pseudo-random sequence: 2^9-1 = 511 bits

• Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence

An example of Pseudorandom Frequency Hopping Sequence as follow:



Each frequency used equally on the average by each transmitter.

According to Bluetooth Core Specification, Bluetooth receivers are designed to have input and IF bandwidths that match the hopping channel bandwidths of any Bluetooth transmitters and shift frequencies in synchronization with the transmitted signals.

Compliance for section 15.247(g)

According to Bluetooth Core Specification, the Bluetooth system transmits the packet with the pseudorandom hopping frequency with a continuous data and the short burst transmission from the Bluetooth system is also transmitted under the frequency hopping system with the pseudorandom hopping frequency system.

Compliance for section 15.247(h)

According to Bluetooth Core specification, the Bluetooth system incorporates with an adaptive system to detect other user within the spectrum band so that it individually and independently to avoid hopping on the occupied channels.

According to the Bluetooth Core specification, the Bluetooth system is designed not have the ability to coordinate with other FHSS System in an effort to avoid the simultaneous occupancy of individual hopping frequencies by multiple transmitter.

--End of Report--