

Test Report

Report No. : CQASZ20220801483E-01
Applicant: Woojer LTD
Address of Applicant: 1 Shenkar Street, Herzelia, Israel, 4672501
Equipment Under Test (EUT):
Product: STRAP 3
Model No.: WJRS3-101
Test Model No.: WJRS3-101
Brand Name: Woojer
FCC ID: 2AQXZ-WJRS3-101
Standards: 47 CFR Part 15, Subpart C
Date of Receipt: 2022-08-24
Date of Test: 2022-08-24 to 2022-09-07
Date of Issue: 2022-11-25
Test Result : **PASS***

*In the configuration tested, the EUT complied with the standards specified above.

Tested By:

Lewis Zhou

(Lewis Zhou)

Reviewed By:

Timo Lei

(Timo Lei)

Approved By:

Jack Ai

(Jack Ai)



Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20220801483E-01	Rev.01	Initial report	2022-11-25

1 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15, Subpart C Section 15.203/15.247 (c)	ANSI C63.10 (2013)	PASS
AC Power Line Conducted Emission	47 CFR Part 15, Subpart C Section 15.207	ANSI C63.10 (2013)	PASS
Conducted Peak Output Power	47 CFR Part 15, Subpart C Section 15.247 (b)(1)	ANSI C63.10 (2013)	PASS
20dB Occupied Bandwidth	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2013)	PASS
Carrier Frequencies Separation	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2013)	PASS
Hopping Channel Number	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2013)	PASS
Dwell Time	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2013)	PASS
Pseudorandom Frequency Hopping Sequence	47 CFR Part 15, Subpart C Section 15.247(b)(4)	ANSI C63.10 (2013)	PASS
Band-edge for RF Conducted Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 (2013)	PASS
RF Conducted Spurious Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 (2013)	PASS
Radiated Spurious emissions	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 (2013)	PASS
Restricted bands around fundamental frequency (Radiated Emission)	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 (2013)	PASS

2 Contents

	Page
VERSION	2
1 TEST SUMMARY	3
2 CONTENTS	4
3 GENERAL INFORMATION	5
3.1 CLIENT INFORMATION	5
3.2 GENERAL DESCRIPTION OF EUT	5
3.3 ADDITIONAL INSTRUCTIONS	7
3.4 TEST ENVIRONMENT	8
3.5 DESCRIPTION OF SUPPORT UNITS	8
3.6 STATEMENT OF THE MEASUREMENT UNCERTAINTY	9
3.7 TEST LOCATION	10
3.8 TEST FACILITY	10
3.9 ABNORMALITIES FROM STANDARD CONDITIONS	10
3.10 OTHER INFORMATION REQUESTED BY THE CUSTOMER	10
3.11 EQUIPMENT LIST	11
4 TEST RESULTS AND MEASUREMENT DATA	12
4.1 ANTENNA REQUIREMENT	12
4.2 CONDUCTED EMISSIONS	13
4.3 CONDUCTED PEAK OUTPUT POWER	17
4.4 20dB OCCUPY BANDWIDTH	28
4.5 CARRIER FREQUENCIES SEPARATION	38
4.6 HOPPING CHANNEL NUMBER	43
4.7 DWELL TIME	47
4.8 BAND-EDGE FOR RF CONDUCTED EMISSIONS	67
4.9 SPURIOUS RF CONDUCTED EMISSIONS	69
4.10 OTHER REQUIREMENTS FREQUENCY HOPPING SPREAD SPECTRUM SYSTEM	97
4.11 RADIATED SPURIOUS EMISSION & RESTRICTED BANDS	99
4.11.1 Radiated Emission below 1GHz	102
4.11.2 Transmitter Emission above 1GHz	106
5 PHOTOGRAPHS - EUT TEST SETUP	112
5.1 RADIATED EMISSION	112
5.2 CONDUCTED EMISSION	113
6 PHOTOGRAPHS - EUT CONSTRUCTIONAL DETAILS	114

3 General Information

3.1 Client Information

Applicant:	Woojer LTD
Address of Applicant:	1 Shenkar Street, Herzelia, Israel, 4672501
Manufacturer:	Woojer LTD
Address of Manufacturer:	1 Shenkar Street, Herzelia, Israel, 4672501
Factory:	Dongguan Zhenyuan Electronics Co., Ltd.
Address of Factory:	No.B1 Workshop, Huaxing Industrial Zone, Hongshi Road, Yantian Village, Fenggang Town, Dongguan City, Guangdong Province, P.R. China

3.2 General Description of EUT

Product Name:	STRAP 3
Model No.:	WJRS3-101
Test Model No.:	WJRS3-101
Trade Mark:	Woojer
Software Version:	V1.0
Hardware Version:	V1.0
Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	V5.3
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Modulation Type:	GFSK, $\pi/4$ DQPSK, 8DPSK
Transfer Rate:	1Mbps/2Mbps/3Mbps
Number of Channel:	79
Hopping Channel Type:	Adaptive Frequency Hopping systems
Product Type:	☐ Mobile ☒ Portable ☐ Fix Location
Test Software of EUT:	BlueTest3
Antenna Type:	Chip antenna
Antenna Gain:	1.75dBi
Power Supply:	Li-ion battery: DC 3.6V 3350mAh, Charge by DC 5V for adapter

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
0	2402MHz	20	2422MHz	40	2442MHz	60	2462MHz
1	2403MHz	21	2423MHz	41	2443MHz	61	2463MHz
2	2404MHz	22	2424MHz	42	2444MHz	62	2464MHz
3	2405MHz	23	2425MHz	43	2445MHz	63	2465MHz
4	2406MHz	24	2426MHz	44	2446MHz	64	2466MHz
5	2407MHz	25	2427MHz	45	2447MHz	65	2467MHz
6	2408MHz	26	2428MHz	46	2448MHz	66	2468MHz
7	2409MHz	27	2429MHz	47	2449MHz	67	2469MHz
8	2410MHz	28	2430MHz	48	2450MHz	68	2470MHz
9	2411MHz	29	2431MHz	49	2451MHz	69	2471MHz
10	2412MHz	30	2432MHz	50	2452MHz	70	2472MHz
11	2413MHz	31	2433MHz	51	2453MHz	71	2473MHz
12	2414MHz	32	2434MHz	52	2454MHz	72	2474MHz
13	2415MHz	33	2435MHz	53	2455MHz	73	2475MHz
14	2416MHz	34	2436MHz	54	2456MHz	74	2476MHz
15	2417MHz	35	2437MHz	55	2457MHz	75	2477MHz
16	2418MHz	36	2438MHz	56	2458MHz	76	2478MHz
17	2419MHz	37	2439MHz	57	2459MHz	77	2479MHz
18	2420MHz	38	2440MHz	58	2460MHz	78	2480MHz
19	2421MHz	39	2441MHz	59	2461MHz		

Note:


In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The Lowest channel	2402MHz
The Middle channel	2441MHz
The Highest channel	2480MHz

3.3 Additional Instructions

EUT Test Software Settings:		
Mode:	☒ Special software is used. ☐ Through engineering command into the engineering mode. engineering command: *##3646633#**	
EUT Power level:	Class2 (Power level is built-in set parameters and cannot be changed and selected)	
Use test software to set the lowest frequency, the middle frequency and the highest frequency keep transmitting of the EUT.		
Mode	Channel	Frequency(MHz)
DH1/DH3/DH5	CH0	2402
	CH39	2441
	CH78	2480
2DH1/2DH3/2DH5	CH0	2402
	CH39	2441
	CH78	2480
3DH1/3DH3/3DH5	CH0	2402
	CH39	2441
	CH78	2480

Run Software:



3.4 Test Environment

Operating Environment:	
Temperature:	25 °C
Humidity:	54% RH
Atmospheric Pressure:	1009mbar
Test Mode:	Use test software to set the lowest frequency, the middle frequency and the highest frequency keep transmitting of the EUT.

3.5 Description of Support Units

The EUT has been tested with associated equipment below.

Description	Manufacturer	Model No.	Remark	FCC certification
/	/	/	/	/

3.6 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate.

The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities.

The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the **Shenzhen Huaxia Testing Technology Co., Ltd.** quality system acc. to DIN EN ISO/IEC 17025.

Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for CQA laboratory is reported:

No.	Item	Uncertainty
1	Radiated Emission (Below 1GHz)	5.12dB
2	Radiated Emission (Above 1GHz)	4.60dB
3	Conducted Disturbance (0.15~30MHz)	3.34dB
4	Radio Frequency	3×10^{-8}
5	Duty cycle	0.6 %
6	Occupied Bandwidth	1.1%
7	RF conducted power	0.86dB
8	RF power density	0.74
9	Conducted Spurious emissions	0.86dB
10	Temperature test	0.8℃
11	Humidity test	2.0%
12	Supply voltages	0.5 %
13	Frequency Error	5.5 Hz

3.7 Test Location

All tests were performed at:

Shenzhen Huaxia Testing Technology Co., Ltd.

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

3.8 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

IC Registration No.: 22984-1

The 3m Semi-anechoic chamber of Shenzhen Huaxia Testing Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing

The test facility is recognized, certified, or accredited by the following organizations:

• **CNAS (No. CNAS L5785)**

CNAS has accredited Shenzhen Huaxia Testing Technology Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

• **A2LA (Certificate No. 4742.01)**

Shenzhen Huaxia Testing Technology Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 4742.01.

• **FCC Registration No.: 522263**

Shenzhen Huaxia Testing Technology Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.:522263

3.9 Abnormalities from Standard Conditions

None.

3.10 Other Information Requested by the Customer

None.

3.11 Equipment List


Test Equipment	Manufacturer	Model No.	Instrument No.	Calibration Date	Calibration Due Date
EMI Test Receiver	R&S	ESR7	CQA-005	2021/9/10	2022/9/9
Spectrum analyzer	R&S	FSU26	CQA-038	2021/9/10	2022/9/9
Preamplifier	MITEQ	AFS4-00010300-18-10P-4	CQA-035	2021/9/10	2022/9/9
Preamplifier	MITEQ	AMF-6D-02001800-29-20P	CQA-036	2021/9/10	2022/9/9
Loop antenna	Schwarzbeck	FMZB1516	CQA-087	2021/9/16	2024/9/15
Bilog Antenna	R&S	HL562	CQA-011	2021/9/16	2024/9/15
Horn Antenna	R&S	HF906	CQA-012	2021/9/16	2024/9/15
Horn Antenna	Schwarzbeck	BBHA 9170	CQA-088	2021/9/16	2024/9/15
Coaxial Cable (Above 1GHz)	CQA	N/A	C019	2021/9/10	2022/9/9
Coaxial Cable (Below 1GHz)	CQA	N/A	C020	2021/9/10	2022/9/9
Antenna Connector	CQA	RFC-01	CQA-080	2021/9/10	2022/9/9
RF cable(9KHz~40GHz)	CQA	RF-01	CQA-079	2021/9/10	2022/9/9
Power divider	MIDWEST	PWD-2533-02-SMA-79	CQA-067	2021/9/10	2022/9/9
EMI Test Receiver	R&S	ESPI3	CQA-013	2021/9/10	2022/9/9
LISN	R&S	ENV216	CQA-003	2021/9/10	2022/9/9
Coaxial cable	CQA	N/A	CQA-C009	2021/9/10	2022/9/9

Note:

The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

4 Test results and Measurement Data


4.1 Antenna Requirement

Standard requirement:	47 CFR Part 15C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(b) (4) requirement: The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.	
EUT Antenna:	
The antenna is Chip antenna. ANT1/ANT2 gain is 1.75 dBi.	

Exploratory Test Mode:	Non-hopping transmitting mode with all kind of modulation and all kind of data type at the lowest, middle, high channel.
Final Test Mode:	Through Pre-scan, find the DH5 of data type and GFSK modulation at the lowest channel is the worst case. Only the worst case is recorded in the report.
Test Voltage:	AC 120V/60Hz
Test Results:	Pass

Measurement Data

Live line:




	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB	dBuV	dBuV	dB		
1	0.170	21.93	9.66	31.59	54.96	-23.37	Average	Line
2	0.170	27.13	9.66	36.79	64.96	-28.17	QP	Line
3	0.310	20.65	9.50	30.15	49.97	-19.82	Average	Line
4	0.310	26.04	9.50	35.54	59.97	-24.43	QP	Line
5 PP	0.625	19.64	9.83	29.47	46.00	-16.53	Average	Line
6 QP	0.625	27.05	9.83	36.88	56.00	-19.12	QP	Line
7	0.855	19.26	9.80	29.06	46.00	-16.94	Average	Line
8	0.855	24.52	9.80	34.32	56.00	-21.68	QP	Line
9	1.465	18.52	10.77	29.29	46.00	-16.71	Average	Line
10	1.465	24.46	10.77	35.23	56.00	-20.77	QP	Line
11	2.045	15.30	11.60	26.90	46.00	-19.10	Average	Line
12	2.045	21.79	11.60	33.39	56.00	-22.61	QP	Line

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

Neutral line:




	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB	dBuV	dBuV	dB		
1	0.190	21.60	9.62	31.22	54.04	-22.82	Average	Neutral
2	0.190	26.72	9.62	36.34	64.04	-27.70	QP	Neutral
3	0.230	21.09	9.56	30.65	52.45	-21.80	Average	Neutral
4	0.230	26.21	9.56	35.77	62.45	-26.68	QP	Neutral
5	0.430	19.06	9.64	28.70	47.25	-18.55	Average	Neutral
6	0.430	23.88	9.64	33.52	57.25	-23.73	QP	Neutral
7 PP	0.630	20.41	9.83	30.24	46.00	-15.76	Average	Neutral
8 QP	0.630	26.58	9.83	36.41	56.00	-19.59	QP	Neutral
9	0.905	19.52	9.76	29.28	46.00	-16.72	Average	Neutral
10	0.905	24.44	9.76	34.20	56.00	-21.80	QP	Neutral
11	1.285	20.01	9.71	29.72	46.00	-16.28	Average	Neutral
12	1.285	25.06	9.71	34.77	56.00	-21.23	QP	Neutral

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

4.3 Conducted Peak Output Power

Test Requirement:	47 CFR Part 15C Section 15.247 (b)(1)
Test Method:	ANSI C63.10:2013
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.
Limit:	21dBm
Exploratory Test Mode:	Non-hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH5 of data type is the worst case of GFSK modulation type, 2-DH5 of data type is the worst case of $\pi/4$ DQPSK modulation type, 3-DH5 of data type is the worst case of 8DPSK modulation type. Only the worst case is recorded in the report.
Test Results:	Pass

Measurement Data


Ant1:

GFSK mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	-3.03	21.00	Pass
Middle	-1.8	21.00	Pass
Highest	-3.07	21.00	Pass
$\pi/4$ DQPSK mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	-3.25	21.00	Pass
Middle	-2.01	21.00	Pass
Highest	-3.17	21.00	Pass
8DPSK mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	-3.37	21.00	Pass
Middle	-2.1	21.00	Pass
Highest	-3.45	21.00	Pass


Ant2:

GFSK mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	-10.38	21.00	Pass
Middle	-8.91	21.00	Pass
Highest	-9.58	21.00	Pass
$\pi/4$ DQPSK mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	-8.55	21.00	Pass
Middle	-6.81	21.00	Pass
Highest	-7.85	21.00	Pass
8DPSK mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	-9.25	21.00	Pass
Middle	-7.18	21.00	Pass
Highest	-8.02	21.00	Pass


Test plot as follows:



DH5_Ant1_2480




2DH5_Ant1_2402



2DH5_Ant1_2441




2DH5_Ant1_2480



3DH5_Ant1_2402



3DH5_Ant1_2441



3DH5_Ant1_2480




DH5_Ant2_2441



DH5_Ant2_2480



2DH5_Ant2_2402




2DH5_Ant2_2441



2DH5_Ant2_2480




3DH5_Ant2_2402




3DH5_Ant2_2441





4.4 20dB Occupy Bandwidth

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.
Limit:	NA
Exploratory Test Mode:	Non-hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH5 of data type is the worst case of GFSK modulation type, 2-DH5 of data type is the worst case of $\pi/4$ DQPSK modulation type, 3-DH5 of data type is the worst case of 8DPSK modulation type. Only the worst case is recorded in the report.
Test Results:	Pass

Measurement Data


Ant1:

Test channel	20dB Occupy Bandwidth (MHz)		
	GFSK	$\pi/4$ DQPSK	8DPSK
Lowest	0.873	1.230	1.248
Middle	0.900	1.263	1.242
Highest	0.948	1.266	1.260


Ant2:

Test channel	20dB Occupy Bandwidth (MHz)		
	GFSK	$\pi/4$ DQPSK	8DPSK
Lowest	0.939	1.344	1.338
Middle	0.942	1.326	1.284
Highest	0.933	1.335	1.356


Test plot as follows:




DH5_Ant1_2480




2DH5_Ant1_2402




2DH5_Ant1_2441




2DH5_Ant1_2480




3DH5_Ant1_2402




3DH5_Ant1_2441




3DH5_Ant1_2480




DH5_Ant2_2402




DH5_Ant2_2441




DH5_Ant2_2480




2DH5_Ant2_2402



2DH5_Ant2_2441




2DH5_Ant2_2480




3DH5_Ant2_2402




3DH5_Ant2_2441



3DH5_Ant2_2480



4.5 Carrier Frequencies Separation

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.
Limit:	2/3 of the 20dB bandwidth
	Remark: the transmission power is less than 0.125W.
Exploratory Test Mode:	Hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH5 of data type is the worst case of GFSK modulation type, 2-DH5 of data type is the worst case of $\pi/4$ DQPSK modulation type, 3-DH5 of data type is the worst case of 8DPSK modulation type. Only the worst case is recorded in the report.
Test Results:	Pass

Measurement Data

Ant1:

TestMode	Antenna	Channel	Result[MHz]	Limit[MHz]	Verdict
DH5	Ant1	Hop	0.687	≥0.632	PASS
2DH5	Ant1	Hop	1.003	≥0.844	PASS
3DH5	Ant1	Hop	1.003	≥0.840	PASS


Mode	20dB bandwidth (MHz) (worse case)	Limit (MHz) (Carrier Frequencies Separation)
GFSK	0.948	0.632
$\pi/4$ DQPSK	1.266	0.844
8DPSK	1.260	0.84



Ant2:

TestMode	Antenna	Channel	Result[MHz]	Limit[MHz]	Verdict
DH5	Ant2	Hop	0.672	≥0.628	PASS
2DH5	Ant2	Hop	1.003	≥0.896	PASS
3DH5	Ant2	Hop	1.003	≥0.904	PASS


Mode	20dB bandwidth (MHz) (worse case)	Limit (MHz) (Carrier Frequencies Separation)
GFSK	0.942	0.628
$\pi/4$ DQPSK	1.344	0.896
8DPSK	1.356	0.904

Test plot as follows:







2DH5_Ant2_Hop



3DH5_Ant2_Hop




4.6 Hopping Channel Number



Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Test Setup:	 <i>Remark: Offset=Cable loss+ attenuation factor.</i>
Limit:	At least 15 channels
Exploratory Test Mode:	hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH5 of data type is the worst case of GFSK modulation type, 2-DH5 of data type is the worst case of $\pi/4$ DQPSK modulation type, 3-DH5 of data type is the worst case of 8DPSK modulation type. Only the worst case is recorded in the report.
Test Results:	Pass

Measurement Data


Mode	Hopping channel numbers	Limit
GFSK	79	≥ 15
$\pi/4$ DQPSK	79	≥ 15
8DPSK	79	≥ 15

Test plot as follows:







2DH5_Ant2_Hop



3DH5_Ant2_Hop



4.7 Dwell Time

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.
Test Mode:	Hopping transmitting with all kind of modulation and all kind of data type.
Limit:	0.4 Second
Test Results:	Pass

Measurement Data**Ant1:**

TestMode	Antenna	Channel	BurstWidth [ms]	TotalHops [Num]	Result[s]	Limit[s]	Verdict
DH1	Ant1	Hop	0.42	330	0.137	≤0.4	PASS
DH3	Ant1	Hop	1.58	190	0.299	≤0.4	PASS
DH5	Ant1	Hop	2.61	120	0.313	≤0.4	PASS
2DH1	Ant1	Hop	0.42	330	0.14	≤0.4	PASS
2DH3	Ant1	Hop	1.62	140	0.226	≤0.4	PASS
2DH5	Ant1	Hop	2.61	80	0.209	≤0.4	PASS
3DH1	Ant1	Hop	0.43	330	0.142	≤0.4	PASS
3DH3	Ant1	Hop	1.41	170	0.24	≤0.4	PASS
3DH5	Ant1	Hop	2.60	90	0.234	≤0.4	PASS


Ant2:

TestMode	Antenna	Channel	BurstWidth [ms]	TotalHops [Num]	Result[s]	Limit[s]	Verdict
DH1	Ant2	Hop	0.39	330	0.1287	≤0.4	PASS
DH3	Ant2	Hop	1.64	170	0.2788	≤0.4	PASS
DH5	Ant2	Hop	2.88	130	0.3744	≤0.4	PASS
2DH1	Ant2	Hop	0.39	330	0.1287	≤0.4	PASS
2DH3	Ant2	Hop	1.63	130	0.2119	≤0.4	PASS
2DH5	Ant2	Hop	2.87	90	0.2583	≤0.4	PASS
3DH1	Ant2	Hop	0.39	320	0.1248	≤0.4	PASS
3DH3	Ant2	Hop	1.63	150	0.2445	≤0.4	PASS
3DH5	Ant2	Hop	2.88	110	0.3168	≤0.4	PASS

Remark:

The test period: $T = 0.4 \text{ Second/Channel} \times 79 \text{ Channel} = 31.6 \text{ s}$

Test plot as follows:



DH3_Ant1_Hop

