TESTING LABORATORY
CERTIFICATE#4323.01

FCC PART 15.247

TEST REPORT

For

Shanghai Ratta Smart Technology Co.,Ltd.

Room 301, Building No.1, 168 Jixin Road, Minhang, Shanghai 201104 China

FCC ID: 2AQZ9-A5X

Report Type:	**Product Type:**
Original Report	SuperNote

Project Engineer:	Chao Gao
Report Number:	RSHA210121001-00A
Report Date:	2021-06-08
Reviewed By:	Oscar Ye EMC Manager
Prepared By:	Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road, Kunshan, Jiangsu province, China Tel: +86-0512-86175000 Fax: +86-0512-88934268 www.baclcorp.com.cn

TABLE OF CONTENTS

GENERAL INFORMATION **4**
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) 4
OBJECTIVE 4
RELATED SUBMITTAL(S)/GRANT(S) 4
TEST METHODOLOGY 5
MEASUREMENT UNCERTAINTY 5
TEST FACILITY 5
SYSTEM TEST CONFIGURATION **6**
DESCRIPTION OF TEST CONFIGURATION 6
EQUIPMENT MODIFICATIONS 6
EUT EXERCISE SOFTWARE 7
SUPPORT EQUIPMENT LIST AND DETAILS 11
EXTERNAL I/O CABLE 11
BLOCK DIAGRAM OF TEST SETUP 11
SUMMARY OF TEST RESULTS **13**
TEST EQUIPMENT LIST **14**
FCC §15.247 (I) & §1.1310 & §2.1093 - RF EXPOSURE **15**
MEASUREMENT RESULT 15
FCC §15.203 - ANTENNA REQUIREMENT **16**
APPLICABLE STANDARD 16
ANTENNA CONNECTOR CONSTRUCTION 16
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS **17**
APPLICABLE STANDARD 17
EUT SETUP 17
EMI TEST RECEIVER SETUP 17
TEST PROCEDURE 18
FACTOR & OVER LIMIT CALCULATION 18
TEST RESULTS SUMMARY 18
TEST DATA 18
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS **25**
APPLICABLE STANDARD 25
EUT SETUP 25
EMI TEST RECEIVER SETUP 26
TEST PROCEDURE 26
CORRECTED AMPLITUDE & MARGIN CALCULATION 26
TEST RESULTS SUMMARY 26
TEST DATA 27
FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH **64**
APPLICABLE STANDARD 64
TEST PROCEDURE 64
TEST DATA 64
FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER **75**
APPLICABLE STANDARD 75
TEST PROCEDURE 75
TEST DATA 76

FCC §15.247(d) – BAND EDGE.....80
APPLICABLE STANDARD 80
TEST PROCEDURE 80
TEST DATA 80
BLE MODE LEFT SIDE 86
BLE MODE RIGHT SIDE 86
FCC §15.247(e) - POWER SPECTRAL DENSITY 87
APPLICABLE STANDARD 87
TEST PROCEDURE 87
TEST DATA 87

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Applicant	Shanghai Ratta Smart Technology Co., Ltd.
Tested Model	A5 X
Product Type	SuperNote
Power Supply	DC 5V from Adapter and DC 3.8V from battery
Maximum Peak Output Power	Wi-Fi: 802.11b:17.03dBm 802.11g:21.24dBm 802.11n20:21.61dBm 802.11n40:16.99dBm BLE(1Mbps): 2.38dBm BLE(2Mbps): 2.45dBm
RF Function	2.4G Wi-Fi, BLE(1Mbps/2Mbps)
Operating Band/Frequency	2.4G Wi-Fi: 2412~2462 MHz (802.11b/g/n20), 2422~2452 MHz (802.11n40) BLE(1Mbps/2Mbps): 2402-2480MHz
Channel Number	2.4G Wi-Fi: 11 (802.11b/g/n20), 7(802.11n40) BLE(1Mbps/2Mbps): 40
Channel Separation	2.4G Wi-Fi: 5MHz, BLE(1Mbps/2Mbps): 2MHz
Modulation Type	Wi-Fi: OFDM, DSSS; BLE(1Mbps/2Mbps): GFSK
Antenna Type	Wi-Fi/BLE: FPC Antenna
*Maximum Antenna Gain	Wi-Fi/BLE: 2.66 dBi

Note: The maximum antenna gain is provided by the applicant.

**All measurement and test data in this report was gathered from production sample serial number: RSHA210121001-1. (Assigned by the BACL. The EUT supplied by the applicant was received on 2021-01-21)*

Objective

This report is prepared on behalf of *Shanghai Ratta Smart Technology Co., Ltd.* in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commission's rules.

The tests were performed in order to determine Compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 15.247 DSS Submittal with FCC ID: 2AQZ9-A5X
FCC Part 15.407 NII Submittal with FCC ID: 2AQZ9-A5X

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices and FCC KDB 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Item		Uncertainty
AC Power Lines Conducted Emissions		3.19dB
RF conducted test with spectrum		0.9dB
RF Output Power with Power meter		0.5dB
Radiated emission	30MHz~1GHz	6.11dB
	1GHz~6GHz	4.45dB
	6GHz~18GHz	5.23dB
	18GHz~40GHz	5.65dB
Occupied Bandwidth		0.5kHz
Temperature		1.0℃
Humidity		6%

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu province, China.

Bay Area Compliance Laboratories Corp. (Kunshan) Lab is accredited to ISO/IEC 17025 by A2LA (Lab code: 4323.01) and the FCC designation No. CN1185 under the FCC KDB 974614 D01 and CAB identifier CN0004 under the ISED requirement. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

Test channel list is as below:

For 802.11b, 802.11g and 802.11n-HT20 mode, EUT was tested with Channel 1, 6 and 11;

For 802.11n-HT40 mode, EUT was tested with Channel 3, 6 and 9.

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/

For BLE mode, EUT was tested with channel 0, 19 and 39.

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404	…	…
…	…	…	…
…	…	…	…
18	2438	38	2478
19	2440	39	2480

Equipment Modifications

No modification was made to the EUT tested.

EUT Exercise Software

RF test tool: QRCT

*Pre-scan with all the data rates, and the worst case was performed as below:

Mode	Data Rate	Power Level Setting
802.11b	1 Mbps	45
802.11g	6 Mbps	42
802.11n-HT20	MCS0	45
802.11n-HT40	MCS0	25
BLE(1Mbps)	1Mbps	Default
BLE(2Mbps)	2Mbps	Default

Note: The power level setting was declared by the applicant.

Duty Cycle:

802.11b Mode Middle Channel



802.11g Mode Middle Channel



802.11n-HT20 Mode Middle Channel



Date: 24.FEB.2021 14:49:43

802.11n-HT40 Mode Middle Channel



Date: 24.FEB.2021 14:50:52

1Mbps:

BLE Mode Middle Channel



2Mbps:

BLE Mode Middle Channel



Mode	Duty Cycle (%)	T(ms)	1/T(kHz)	10log(1/x)
802.11b	100	/	/	0
802.11g	100	/	/	0
802.11n-HT20	100	/	/	0
802.11n-HT40	100	/	/	0
BLE(1Mbps)	65.88	0.417	2.40	1.81
BLE(2Mbps)	37.08	0.234	4.27	4.31

Note: "x" means the Duty Cycle.

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
TIANYIN	Adapter	TPA-67C050100VU01	/

External I/O Cable

Cable Description	Length (m)	From Port	To Port
Power Cable 1	1.0	EUT	Adapter
Power Cable 2	1.0	Adapter	LISN/AC source

Block Diagram of Test Setup

For Conducted Emissions:



For Radiated Emissions (Below 1GHz):



For Radiated Emissions (Above 1GHz):



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (I), §1.1310 & §2.1093	RF Exposure	Compliant
§15.203	Antenna Requirement	Compliant
§15.207 (a)	AC Line Conducted Emissions	Compliant
§15.247(d)	Spurious Emissions at Antenna Port	Compliant
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliant
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliant
§15.247(b)(3)	Maximum Conducted Output Power	Compliant
§15.247(d)	Band Edge	Compliant
§15.247(e)	Power Spectral Density	Compliant

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test（Chamber 1#）					
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2020-11-27	2021-11-26
Sunol Sciences	Broadband Antenna	JB3	A090314-2	2020-01-07	2023-01-06
Sonoma Instrument	Pre-amplifier	310N	171205	2020-08-14	2021-08-13
Rohde & Schwarz	Auto test Software	EMC32	100361	/	/
MICRO-COAX	Coaxial Cable	Cable-8	008	2020-08-15	2021-08-14
MICRO-COAX	Coaxial Cable	Cable-9	009	2020-08-15	2021-08-14
MICRO-COAX	Coaxial Cable	Cable-10	010	2020-08-15	2021-08-14
Radiated Emission Test（Chamber 2#）					
Rohde & Schwarz	EMI Test Receiver	ESU40	100207	2020-08-15	2021-08-14
ETS-LINDGREN	Horn Antenna	3115	9311-4159	2020-07-15	2023-07-14
ETS-LINDGREN	Horn Antenna	3116	2516	2020-01-07	2023-01-06
A.H.Systems,inc	Amplifier	PAM-0118P	512	2020-08-14	2021-08-13
EM Electronics Corporation	Amplifier	EM18G40G	060726	2020-08-05	2021-08-04
MICRO-TRONICS	Band Reject Filter	BRM50702	G024	2020-08-05	2021-08-04
Narda	Attenuator	10dB	010	2020-08-15	2021-08-14
Rohde & Schwarz	Auto test Software	EMC32	100361	/	/
MICRO-COAX	Coaxial Cable	Cable-11	011	2020-08-15	2021-08-14
MICRO-COAX	Coaxial Cable	Cable-12	012	2020-08-15	2021-08-14
MICRO-COAX	Coaxial Cable	Cable-13	013	2020-08-15	2021-08-14
RF Conducted Test					
Rohde & Schwarz	EMI Test Receiver	ESIB26	100146	2020-11-27	2021-11-26
Agilent	Power Meter	N1912A	MY5000492	2020-11-18	2021-11-17
Agilent	Power Sensor	N1921A	MY54210024	2020-11-18	2021-11-17
Narda	Attenuator	10dB	010	2020-08-15	2021-08-14
Shanghai Ratta Smart Technology Co.,Ltd.	RF Cable	Shanghai Ratta Smart Technology Co.,Ltd. C01	C01	Each Time	/
Conducted Emission Test					
Rohde & Schwarz	EMI Test Receiver	ESR	1316.3003K03 -101746-zn	2020-08-05	2021-08-04
Rohde & Schwarz	LISN	ENV216	101115	2020-11-27	2021-11-26
Audix	Test Software	e3	V9	/	/
Rohde & Schwarz	Pulse limiter	ESH3-Z2	357.8810.52	2020-08-10	2021-08-09
MICRO-COAX	Coaxial Cable	Cable-15	015	2020-08-15	2021-08-14

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §15.247 (I) & §1.1310 & §2.1093 - RF EXPOSURE

Applicable Standard

According to§15.247(i) and §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB447498 D01 General RF Exposure Guidance v06:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:
[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] · [√f(GHz)] ≤ 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Measurement Result

BLE:

Mode	Frequency Range (MHz)	Max. Tune-up Power including Tune-up Tolerance (dBm)		Calculated Distance (mm)	Calculated Value	Threshold (1-g SAR)	SAR Test Exclusion
		(dBm)	(mW)				
BLE	2402-2480	3.0	2.0	5	0.6	3.0	Yes

Result: So the stand-alone SAR evaluation is not necessary.

2.4G WiFi:

Compliance, please refer to SAR Report: RSHA210121001-20C

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine Compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

a. Antenna must be permanently attached to the unit.
b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.
And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has an FPC antenna for Wi-Fi and BLE, and the antenna gain is 2.66 dBi, the antenna is permanently attached to the unit, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliant.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207(a)

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with ANSI C63.10-2013. The related limit was specified in FCC Part 15.207.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

ANSI C63.10-2013 clause 6.2

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Factor & Over Limit Calculation

The Factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

Factor (dB) = LISN VDF (dB) + Cable Loss (dB) + Transient Limiter Attenuation (dB)

The "**Over Limit**" column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit of 7 dB means the emission is 7 dB above the limit. The equation for Over Limit calculation is as follows:

Over Limit (dB) = Read level (dBμV) + Factor (dB) - Limit (dBμV)

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207.

Test Data

Environmental Conditions

Temperature:	23.2 ℃
Relative Humidity:	50 %
ATM Pressure:	101.5 kPa

The testing was performed by Chao Gao on 2021-01-27.

Test Result: Compliant.

For Wi-Fi Mode:

EUT operation mode: Transmitting in 802.11n-HT20 mode high channel (worst case)

AC 120V/60 Hz, Line



	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.440	16.10	19.75	35.85	47.07	-11.22	Average
2	0.440	29.30	19.75	49.05	57.07	-8.02	QP
3	0.614	18.40	19.75	38.15	46.00	-7.85	Average
4	0.614	30.20	19.75	49.95	56.00	-6.05	QP
5	1.054	15.80	19.82	35.62	46.00	-10.38	Average
6	1.054	30.00	19.82	49.82	56.00	-6.18	QP
7	1.229	17.71	19.81	37.52	46.00	-8.48	Average
8	1.229	29.71	19.81	49.52	56.00	-6.48	QP
9	1.403	17.81	19.83	37.64	46.00	-8.36	Average
10	1.403	28.01	19.83	47.84	56.00	-8.16	QP
11	2.809	9.50	19.47	28.97	46.00	-17.03	Average
12	2.809	24.50	19.47	43.97	56.00	-12.03	QP
13	3.964	8.80	19.47	28.27	46.00	-17.73	Average
14	3.964	26.20	19.47	45.67	56.00	-10.33	QP

AC 120V/60 Hz, Neutral



	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.440	22.00	19.75	41.75	47.07	-5.32	Average
2	0.440	28.30	19.75	48.05	57.07	-9.02	QP
3	0.614	22.80	19.75	42.55	46.00	-3.45	Average
4	0.614	28.60	19.75	48.35	56.00	-7.65	QP
5	0.792	21.31	19.70	41.01	46.00	-4.99	Average
6	0.792	26.31	19.70	46.01	56.00	-9.99	QP
7	0.968	20.00	19.79	39.79	46.00	-6.21	Average
8	0.968	27.40	19.79	47.19	56.00	-8.81	QP
9	1.229	20.61	19.81	40.42	46.00	-5.58	Average
10	1.229	27.81	19.81	47.62	56.00	-8.38	QP
11	1.403	21.71	19.83	41.54	46.00	-4.46	Average
12	1.403	27.51	19.83	47.34	56.00	-8.66	QP

Note:
1) Factor (dB) = LISN VDF (dB) + Cable Loss (dB) + Transient Limiter Attenuation (dB)
2) Over Limit (dB) = Read level (dBµV) + Factor (dB) - Limit (dBµV)

For BLE Mode(1Mbps):

EUT operation mode: Transmitting in high channel (worst case)

AC 120V/60 Hz, Line



	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.440	16.40	19.75	36.15	47.07	-10.92	Average
2	0.440	29.10	19.75	48.85	57.07	-8.22	QP
3	0.617	18.40	19.75	38.15	46.00	-7.85	Average
4	0.617	30.20	19.75	49.95	56.00	-6.05	QP
5	0.788	14.90	19.71	34.61	46.00	-11.39	Average
6	0.788	27.70	19.71	47.41	56.00	-8.59	QP
7	1.054	15.70	19.82	35.52	46.00	-10.48	Average
8	1.054	30.90	19.82	50.72	56.00	-5.28	QP
9	1.236	16.41	19.81	36.22	46.00	-9.78	Average
10	1.236	28.41	19.81	48.22	56.00	-7.78	QP
11	1.411	17.31	19.83	37.14	46.00	-8.86	Average
12	1.411	29.81	19.83	49.64	56.00	-6.36	QP
13	2.824	9.49	19.47	28.96	46.00	-17.04	Average
14	2.824	19.19	19.47	38.66	56.00	-17.34	QP
15	3.258	0.30	19.46	19.76	46.00	-26.24	Average
16	3.258	15.40	19.46	34.86	56.00	-21.14	QP
17	4.049	7.60	19.47	27.07	46.00	-18.93	Average
18	4.049	26.20	19.47	45.67	56.00	-10.33	QP

AC 120V/60 Hz, Neutral



	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.440	22.10	19.75	41.85	47.07	-5.22	Average
2	0.440	28.40	19.75	48.15	57.07	-8.92	QP
3	0.614	23.20	19.75	42.95	46.00	-3.05	Average
4	0.614	28.70	19.75	48.45	56.00	-7.55	QP
5	0.968	20.10	19.79	39.89	46.00	-6.11	Average
6	0.968	27.40	19.79	47.19	56.00	-8.81	QP
7	1.141	22.10	19.81	41.91	46.00	-4.09	Average
8	1.141	27.40	19.81	47.21	56.00	-8.79	QP
9	1.229	20.91	19.81	40.72	46.00	-5.28	Average
10	1.229	28.41	19.81	48.22	56.00	-7.78	QP
11	1.403	22.11	19.83	41.94	46.00	-4.06	Average
12	1.403	26.01	19.83	45.84	56.00	-10.16	QP

Note:
1) Factor (dB) = LISN VDF (dB) + Cable Loss (dB) + Transient Limiter Attenuation (dB)
2) Over Limit (dB) = Read level (dBµV) + Factor (dB) - Limit (dBµV)

2Mbps:

EUT operation mode: Transmitting in high channel (worst case)

AC 120V/60 Hz, Line



	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.440	16.30	19.75	36.05	47.07	-11.02	Average
2	0.440	29.30	19.75	49.05	57.07	-8.02	QP
3	0.614	18.30	19.75	38.05	46.00	-7.95	Average
4	0.614	30.00	19.75	49.75	56.00	-6.25	QP
5	1.054	15.50	19.82	35.32	46.00	-10.68	Average
6	1.054	30.70	19.82	50.52	56.00	-5.48	QP
7	1.236	16.81	19.81	36.62	46.00	-9.38	Average
8	1.236	28.61	19.81	48.42	56.00	-7.58	QP
9	1.411	18.11	19.83	37.94	46.00	-8.06	Average
10	1.411	30.11	19.83	49.94	56.00	-6.06	QP
11	2.213	9.90	19.67	29.57	46.00	-16.43	Average
12	2.213	23.40	19.67	43.07	56.00	-12.93	QP
13	3.964	7.20	19.47	26.67	46.00	-19.33	Average
14	3.964	25.50	19.47	44.97	56.00	-11.03	QP

AC 120V/60 Hz, Neutral



	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.440	22.00	19.75	41.75	47.07	-5.32	Average
2	0.440	28.30	19.75	48.05	57.07	-9.02	QP
3	0.614	23.20	19.75	42.95	46.00	-3.05	Average
4	0.614	28.70	19.75	48.45	56.00	-7.55	QP
5	0.792	21.41	19.70	41.11	46.00	-4.89	Average
6	0.792	26.31	19.70	46.01	56.00	-9.99	QP
7	0.968	20.10	19.79	39.89	46.00	-6.11	Average
8	0.968	27.40	19.79	47.19	56.00	-8.81	QP
9	1.229	21.41	19.81	41.22	46.00	-4.78	Average
10	1.229	28.01	19.81	47.82	56.00	-8.18	QP
11	1.403	22.11	19.83	41.94	46.00	-4.06	Average
12	1.403	26.21	19.83	46.04	56.00	-9.96	QP

Note:
1) Factor (dB) = LISN VDF (dB) + Cable Loss (dB) + Transient Limiter Attenuation (dB)
2) Over Limit (dB) = Read level (dBµV) + Factor (dB) - Limit (dBµV)

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard

FCC §15.247 (d); §15.209; §15.205;

EUT Setup

Below 1 GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

EMI Test Receiver Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver Setup was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1GHz	1MHz	3 MHz	/	PK
	1MHz	3 MHz	1MHz	Ave.

Test Procedure

According to ANSI C63.10-2013 clause 6.5, 6.6 and 6.7.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection mode for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude (dBμV/m) = Meter Reading (dBμV) + Antenna Factor (dB/m) + Cable Loss (dB) - Amplifier Gain (dB)

The "**Margin**" column of the following data tables indicates the degree of Compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin (dB) = Limit (dBμV/m) – Corrected Amplitude (dBμV/m)

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.

Test Data

Environmental Conditions

Temperature:	24.6-25.3 ℃
Relative Humidity:	48-54 %
ATM Pressure:	101.1-101.5 kPa

The testing was performed by Chao Gao from 2021-02-22 to 2021-06-05.

Test Result: Compliant.

EUT operation mode: Transmitting

For Wi-Fi Mode:

Spurious Emission Test:

30MHz-1GHz:

Pre-scan with 802.11b, 802.11g, 802.11n-HT20 and 802.11n-HT40 modes of operation in the X, Y and Z axes of orientation, the worst case ***high channel of 802.11n-HT20 mode in Z-axis of orientation*** *was recorded*



Frequency (MHz)	Corrected Amplitude QuasiPeak (dBµV/m)	Rx Antenna Height (cm)	Rx Antenna Polar (H/V)	Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
30.403245	35.13	100.0	V	36.0	-4.1	40.00	4.87
36.996050	26.49	100.0	V	352.0	-8.5	40.00	13.51
41.647450	20.17	100.0	V	216.0	-11.6	40.00	19.83
58.426800	14.33	200.0	V	35.0	-17.2	40.00	25.67
124.951950	17.04	100.0	V	326.0	-10.4	43.50	26.46
200.749300	18.25	100.0	V	53.0	-10.8	43.50	25.25

1GHz-18GHz:

802.11b Mode:
*(Pre-scan in the X,Y and Z axes of orientation, the worst case **Z-axis of orientation** was recorded)*

Note:
1. This test was performed with the 2.4-2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
   Corrected Amplitude (dBµV/m) = Corrected Factor (dB/m) + Reading (dBµV)
   Margin (dB) = Limit (dBµV/m) – Corrected Amplitude (dBµV/m)

Low Channel: 2412MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
1442.000000	---	27.85	200.0	H	302.0	-6.8	54.00	26.15
1442.000000	37.14	---	200.0	H	302.0	-6.8	74.00	36.86
3607.800000	---	38.30	150.0	H	2.0	-1.2	54.00	15.70
3607.800000	44.39	---	150.0	H	2.0	-1.2	74.00	29.61
4824.000000	---	33.90	150.0	H	290.0	0.6	54.00	20.10
4824.000000	42.27	---	150.0	H	290.0	0.6	74.00	31.73
6654.200000	---	39.11	200.0	H	78.0	5.5	54.00	14.89
6654.200000	48.00	---	200.0	H	78.0	5.5	74.00	26.00
10402.700000	---	40.93	150.0	H	328.0	8.5	54.00	13.07
10402.700000	50.00	---	150.0	H	328.0	8.5	74.00	24.00
17573.300000	---	45.29	200.0	V	112.0	14.3	54.00	8.71
17573.300000	54.07	---	200.0	V	112.0	14.3	74.00	19.93

Middle Channel: 2437MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
1226.100000	---	26.49	200.0	H	359.0	-7.9	54.00	27.51
1226.100000	36.23	---	200.0	H	359.0	-7.9	74.00	37.77
1688.500000	---	28.19	150.0	H	324.0	-5.9	54.00	25.81
1688.500000	37.93	---	150.0	H	324.0	-5.9	74.00	36.07
2999.200000	---	32.08	200.0	V	256.0	-2.1	54.00	21.92
2999.200000	42.54	---	200.0	V	256.0	-2.1	74.00	31.46
4874.000000	---	34.21	150.0	V	310.0	0.5	54.00	19.79
4874.000000	43.62	---	150.0	V	310.0	0.5	74.00	30.38
6836.100000	---	39.27	200.0	H	80.0	5.6	54.00	14.73
6836.100000	47.66	---	200.0	H	80.0	5.6	74.00	26.34
11796.700000	---	40.94	150.0	V	126.0	10.2	54.00	13.06
11796.700000	50.79	---	150.0	V	126.0	10.2	74.00	23.21
17575.000000	---	44.86	200.0	H	0.0	14.3	54.00	9.14
17575.000000	54.48	---	200.0	H	0.0	14.3	74.00	19.52

High Channel: 2462MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
1136.000000	34.68	---	150.0	H	70.0	-8.4	74.00	39.32
1136.000000	---	26.89	150.0	H	70.0	-8.4	54.00	27.11
2023.400000	41.22	---	200.0	H	43.0	-4.8	74.00	32.78
2023.400000	---	34.09	200.0	H	43.0	-4.8	54.00	19.91
3444.600000	42.51	---	150.0	H	253.0	-1.7	74.00	31.49
3444.600000	---	34.52	150.0	H	253.0	-1.7	54.00	19.48
4924.000000	43.26	---	150.0	V	94.0	0.4	74.00	30.74
4924.000000	---	34.87	150.0	V	94.0	0.4	54.00	19.13
8996.800000	---	41.90	200.0	V	187.0	9.5	54.00	12.10
8996.800000	50.85	---	200.0	V	187.0	9.5	74.00	23.15
17432.200000	---	44.48	150.0	H	202.0	14.2	54.00	9.52
17432.200000	54.11	---	150.0	H	202.0	14.2	74.00	19.89

802.11g Mode:
*(Pre-scan in the X, Y and Z axes of orientation, the worst case **Z-axis of orientation** was recorded)*

Note:
1. This test was performed with the 2.4-2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
   Corrected Amplitude (dBµV/m) = Corrected Factor (dB/m) + Reading (dBµV)
   Margin (dB) = Limit (dBµV/m) – Corrected Amplitude (dBµV/m)

Low Channel: 2412MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
1578.000000	---	29.59	200.0	V	191.0	-6.2	54.00	24.41
1578.000000	36.79	---	200.0	V	191.0	-6.2	74.00	37.21
3162.400000	---	31.47	150.0	H	334.0	-1.9	54.00	22.53
3162.400000	41.39	---	150.0	H	334.0	-1.9	74.00	32.61
4824.000000	---	34.36	200.0	V	244.0	0.6	54.00	19.64
4824.000000	44.11	---	200.0	V	244.0	0.6	74.00	29.89
8898.200000	---	41.46	150.0	H	169.0	9.1	54.00	12.54
8898.200000	50.55	---	150.0	H	169.0	9.1	74.00	23.45
12162.200000	---	42.10	150.0	V	257.0	10.2	54.00	11.90
12162.200000	50.49	---	150.0	V	257.0	10.2	74.00	23.51
17651.500000	---	45.83	150.0	V	128.0	14.1	54.00	8.17
17651.500000	54.62	---	150.0	V	128.0	14.1	74.00	19.38

Middle Channel: 2437MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
1589.900000	---	29.39	150.0	H	37.0	-6.2	54.00	24.61
1589.900000	37.09	---	150.0	V	0.0	-6.2	74.00	36.91
3204.900000	---	33.47	150.0	H	160.0	-1.9	54.00	20.53
3204.900000	42.54	---	150.0	H	160.0	-1.9	74.00	31.46
4874.000000	41.87	---	200.0	H	174.0	0.5	74.00	32.13
4874.000000	---	35.22	200.0	H	292.0	0.5	54.00	18.78
7087.700000	---	39.29	200.0	V	204.0	5.5	54.00	14.71
7087.700000	49.91	---	150.0	V	204.0	5.5	74.00	24.09
11650.500000	---	41.20	150.0	H	355.0	10.4	54.00	12.80
11650.500000	51.41	---	200.0	V	45.0	10.4	74.00	22.59
17654.900000	---	46.53	200.0	V	0.0	14.1	54.00	7.47
17654.900000	54.68	---	200.0	V	0.0	14.1	74.00	19.32

High Channel: 2462MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
1844.900000	---	29.50	150.0	V	165.0	-5.4	54.00	24.50
1844.900000	38.51	---	150.0	V	165.0	-5.4	74.00	35.49
3607.800000	---	36.97	200.0	H	16.0	-1.2	54.00	17.03
3607.800000	43.01	---	200.0	H	16.0	-1.2	74.00	30.99
4924.000000	42.39	---	200.0	H	336.0	0.3	74.00	31.61
4924.000000	---	35.28	200.0	H	336.0	0.3	54.00	18.72
7291.700000	---	37.89	150.0	V	1.0	5.2	54.00	16.11
7291.700000	47.52	---	150.0	V	1.0	5.2	74.00	26.48
11203.400000	---	42.67	150.0	V	38.0	10.0	54.00	11.33
11203.400000	53.56	---	150.0	V	38.0	10.0	74.00	20.44
17687.200000	---	44.88	150.0	H	0.0	14.0	54.00	9.12
17687.200000	53.49	---	150.0	H	0.0	14.0	74.00	20.51

802.11n-HT20 Mode:
*(Pre-scan in the X,Y and Z axes of orientation, the worst case **Z-axis of orientation** was recorded)*

Note:
1. This test was performed with the 2.4-2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
   Corrected Amplitude (dBµV/m) = Corrected Factor (dB/m) + Reading (dBµV)
   Margin (dB) = Limit (dBµV/m) – Corrected Amplitude (dBµV/m)

Low Channel: 2412MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
1508.300000	38.07	---	150.0	V	259.0	-6.5	74.00	35.93
1508.300000	---	28.78	150.0	V	259.0	-6.5	54.00	25.22
3558.500000	---	33.05	200.0	H	347.0	-1.5	54.00	20.95
3558.500000	42.77	---	200.0	H	347.0	-1.5	74.00	31.23
4824.000000	44.71	---	150.0	H	96.0	0.6	74.00	29.29
4824.000000	---	34.72	150.0	H	96.0	0.6	54.00	19.28
7990.400000	---	40.44	150.0	H	70.0	6.0	54.00	13.56
7990.400000	49.26	---	150.0	H	70.0	6.0	74.00	24.74
11545.100000	---	42.28	200.0	V	283.0	10.5	54.00	11.72
11545.100000	52.43	---	200.0	V	283.0	10.5	74.00	21.57
17687.200000	55.32	---	200.0	V	160.0	14.0	74.00	18.68
17687.200000	---	47.45	200.0	V	160.0	14.0	54.00	6.55

Middle Channel: 2437MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
1176.800000	---	26.02	200.0	H	250.0	-8.1	54.00	27.98
1176.800000	35.76	---	200.0	H	250.0	-8.1	74.00	38.24
2023.400000	---	34.74	150.0	V	8.0	-4.8	54.00	19.26
2023.400000	43.48	---	150.0	V	8.0	-4.8	74.00	30.52
3070.600000	---	33.41	150.0	H	216.0	-2.0	54.00	20.59
3070.600000	41.97	---	150.0	H	216.0	-2.0	74.00	32.03
4874.000000	---	35.22	150.0	V	273.0	0.6	54.00	18.78
4874.000000	44.87	---	150.0	V	273.0	0.6	74.00	29.13
9255.200000	---	42.05	150.0	H	189.0	9.3	54.00	11.95
9255.200000	52.25	---	150.0	H	189.0	9.3	74.00	21.75
17661.700000	---	46.26	150.0	H	176.0	14.1	54.00	7.74
17661.700000	55.23	---	150.0	H	176.0	14.1	74.00	18.77

High Channel: 2462MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
1493.000000	---	27.86	200.0	V	0.0	-6.5	54.00	26.14
1493.000000	37.80	---	200.0	V	0.0	-6.5	74.00	36.20
3357.900000	---	33.70	200.0	H	0.0	-1.8	54.00	20.30
3357.900000	42.26	---	200.0	H	0.0	-1.8	74.00	31.74
4924.000000	---	34.70	150.0	V	303.0	0.3	54.00	19.30
4924.000000	43.17	---	150.0	V	303.0	0.3	74.00	30.83
8896.500000	---	42.25	150.0	H	358.0	9.1	54.00	11.75
8896.500000	51.53	---	150.0	H	358.0	9.1	74.00	22.47
12580.400000	---	42.82	200.0	H	0.0	10.5	54.00	11.18
12580.400000	51.18	---	200.0	H	0.0	10.5	74.00	22.82
17617.500000	---	45.62	150.0	H	62.0	14.2	54.00	8.38
17617.500000	55.58	---	150.0	H	62.0	14.2	74.00	18.42

802.11n-HT40 Mode:
*(Pre-scan in the X, Y and Z axes of orientation, the worst case **Z-axis of orientation** was recorded)*

Note:
1. This test was performed with the 2.4-2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
   Corrected Amplitude (dBµV/m) = Corrected Factor (dB/m) + Reading (dBµV)
   Margin (dB) = Limit (dBµV/m) – Corrected Amplitude (dBµV/m)

Low Channel: 2422MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
1440.300000	---	27.82	150.0	V	155.0	-6.8	54.00	26.18
1440.300000	36.96	---	150.0	V	155.0	-6.8	74.00	37.04
3427.600000	---	32.46	200.0	V	3.0	-1.8	54.00	21.54
3427.600000	42.60	---	200.0	V	3.0	-1.8	74.00	31.40
4844.000000	---	36.27	150.0	H	345.0	0.5	54.00	17.73
4844.000000	44.10	---	150.0	H	345.0	0.5	74.00	29.90
7137.000000	48.99	---	200.0	H	116.0	5.5	74.00	25.01
7137.000000	---	39.71	200.0	H	116.0	5.5	54.00	14.29
11662.400000	---	43.01	200.0	V	173.0	10.4	54.00	10.99
11662.400000	52.47	---	200.0	V	173.0	10.4	74.00	21.53
17649.800000	---	47.88	150.0	V	181.0	14.1	54.00	6.12
17649.800000	55.89	---	150.0	V	181.0	14.1	74.00	18.11

Middle Channel: 2437MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
1581.400000	---	29.03	150.0	H	27.0	-6.2	54.00	24.97
1581.400000	37.91	---	150.0	H	27.0	-6.2	74.00	36.09
2021.700000	---	33.54	150.0	V	2.0	-4.9	54.00	20.46
2023.400000	41.86	---	150.0	V	2.0	-4.8	74.00	32.14
3352.800000	---	34.54	150.0	V	134.0	-1.8	54.00	19.46
3352.800000	42.32	---	150.0	V	134.0	-1.8	74.00	31.68
4874.000000	41.98	---	150.0	H	116.0	0.5	74.00	32.02
4874.000000	---	35.10	150.0	H	116.0	0.5	54.00	18.90
8888.000000	---	43.23	150.0	V	275.0	9.1	54.00	10.77
8888.000000	51.19	---	150.0	V	275.0	9.1	74.00	22.81
17704.200000	---	45.57	200.0	V	89.0	14.0	54.00	8.43
17704.200000	56.43	---	200.0	V	89.0	14.0	74.00	17.57

High Channel: 2452MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
1584.800000	---	29.57	150.0	H	15.0	-6.2	54.00	24.43
1584.800000	38.22	---	150.0	H	15.0	-6.2	74.00	35.78
2023.400000	41.42	---	150.0	V	332.0	-4.8	74.00	32.58
2023.400000	---	33.22	150.0	V	332.0	-4.8	54.00	20.78
3616.300000	42.00	---	150.0	V	350.0	-1.2	74.00	32.00
3616.300000	---	32.88	150.0	V	350.0	-1.2	54.00	21.12
4904.000000	41.27	---	200.0	V	37.0	0.4	74.00	32.73
4904.000000	---	34.58	200.0	V	37.0	0.4	54.00	19.42
6637.200000	49.00	---	200.0	V	334.0	5.5	74.00	25.00
6637.200000	---	39.74	200.0	V	334.0	5.5	54.00	14.26
11550.200000	---	40.57	150.0	V	95.0	10.5	54.00	13.43
11550.200000	51.98	---	150.0	V	95.0	10.5	74.00	22.02
17571.600000	55.45	---	150.0	H	207.0	14.3	74.00	18.55
17571.600000	---	46.32	150.0	H	207.0	14.3	54.00	7.68

18GHz-25GHz:

Pre-scan with 802.11b, 802.11g, 802.11n-HT20 and 802.11n-HT40 modes of operation in the X,Y and Z axes of orientation, the worst case ***high channel of 802.11n-HT20 mode in Z-axis of orientation*** *was recorded*

Horizontal



Date: 9.MAR.2021 20:58:13

Vertical



Date: 9.MAR.2021 21:58:59

Restricted Bands Emissions Test:

Note:
1. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
   Corrected Amplitude (dBμV/m) = Corrected Factor (dB/m) + Reading (dBμV)
   Margin (dB) = Limit (dBμV/m) – Corrected Amplitude (dBμV/m)

802.11b Mode: *(Pre-scan in the X,Y and Z axes of orientation, the worst case Z-axis of orientation was recorded)*

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
Low Channel: 2412MHz								
2390.000000	49.03	---	150.0	V	6.0	3.7	74.00	24.97
2390.000000	---	46.27	150.0	V	6.0	3.7	54.00	7.73
High Channel: 2462MHz								
2483.500000	49.82	---	200.0	H	165.0	4.2	74.00	24.18
2483.500000	---	47.50	200.0	H	165.0	4.2	54.00	6.50

802.11g Mode: *(Pre-scan in the X,Y and Z axes of orientation, the worst case Z-axis of orientation was recorded)*

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
Low Channel: 2412MHz								
2390.000000	50.28	---	150.0	H	0.0	3.8	74.00	23.72
2390.000000	---	46.27	150.0	H	0.0	3.8	54.00	7.73
High Channel: 2462MHz								
2483.500000	51.16	---	150.0	V	1.0	4.2	74.00	22.84
2483.500000	---	46.87	150.0	V	1.0	4.2	54.00	7.13

802.11n-HT20 Mode: *(Pre-scan in the X,Y and Z axes of orientation, the worst case Z-axis of orientation was recorded)*

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
Low Channel: 2412MHz								
2390.000000	50.30	---	150.0	V	156.0	3.8	74.00	23.70
2390.000000	---	46.67	150.0	V	156.0	3.8	54.00	7.33
High Channel: 2462MHz								
2483.500000	51.45	---	150.0	H	100.0	4.2	74.00	22.55
2483.500000	---	47.41	150.0	H	100.0	4.2	54.00	6.59

802.11n-HT40 Mode: *(Pre-scan in the X,Y and Z axes of orientation, the worst case Z-axis of orientation was recorded)*

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
Low Channel: 2422MHz								
2390.00	49.71	---	150.0	V	0.0	3.8	74.00	24.29
2390.00	---	46.51	150.0	V	0.0	3.8	54.00	7.49
High Channel: 2452MHz								
2483.50	52.12	---	200.0	H	80.0	4.2	74.00	21.88
2483.50	---	47.56	200.0	H	80.0	4.2	54.00	6.44

For BLE Mode(1Mbps):

Spurious Emission Test:

30MHz-1GHz

(Pre-scan with low, middle and high channels of operation in the X,Y and Z axes of orientation, the worst case ***high channel of operation in the Z axis of orientation*** *was recorded)*



Frequency (MHz)	Corrected Amplitude QuasiPeak (dBµV/m)	Rx Antenna Height (cm)	Rx Antenna Polar (H/V)	Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
30.657557	33.99	100.0	V	296.0	-4.3	40.00	6.01
36.708100	25.18	100.0	V	339.0	-8.3	40.00	14.82
39.084200	21.70	100.0	V	10.0	-9.9	40.00	18.30
65.015700	13.56	100.0	V	41.0	-16.6	40.00	26.44
123.718600	11.64	200.0	V	265.0	-10.6	43.50	31.86
199.115950	16.99	100.0	V	308.0	-10.8	43.50	26.51

1GHz-18GHz

*(Pre-scan in the X,Y and Z axes of orientation, the worst case **Z-axis of orientation** was recorded)*

Note:
1. This test was performed with the 2.4-2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
   Corrected Amplitude (dBµV/m) = Corrected Factor (dB/m) + Reading (dBµV)
   Margin (dB) = Limit (dBµV/m) – Corrected Amplitude (dBµV/m)

Low Channel: 2402MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
1778.600000	---	29.55	150.0	V	2.0	-5.6	54.00	24.45
1778.600000	38.08	---	150.0	V	2.0	-5.6	74.00	35.92
2995.800000	---	32.81	200.0	H	169.0	-2.1	54.00	21.19
2995.800000	41.68	---	200.0	H	169.0	-2.1	74.00	32.32
4768.900000	---	35.84	150.0	V	220.0	0.7	54.00	18.16
4768.900000	44.78	---	150.0	V	220.0	0.7	74.00	29.22
6616.800000	---	38.77	150.0	H	243.0	5.5	54.00	15.23
6616.800000	48.12	---	150.0	H	243.0	5.5	74.00	25.88
10919.500000	---	42.45	150.0	H	97.0	9.5	54.00	11.55
10919.500000	51.78	---	150.0	H	97.0	9.5	74.00	22.22
17614.100000	---	46.48	150.0	H	59.0	14.2	54.00	7.52
17614.100000	55.14	---	150.0	H	59.0	14.2	74.00	18.86

Middle Channel: 2440MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
1902.700000	---	29.13	150.0	V	0.0	-5.2	54.00	24.87
1902.700000	38.29	---	150.0	V	0.0	-5.2	74.00	35.71
3247.400000	---	32.62	200.0	V	232.0	-1.9	54.00	21.38
3247.400000	42.82	---	200.0	V	232.0	-1.9	74.00	31.18
6310.800000	---	37.49	200.0	H	149.0	4.9	54.00	16.51
6310.800000	48.11	---	200.0	H	149.0	4.9	74.00	25.89
8886.300000	---	42.60	200.0	V	15.0	9.0	54.00	11.40
8886.300000	51.80	---	200.0	V	15.0	9.0	74.00	22.20
15249.400000	---	43.95	200.0	H	34.0	10.9	54.00	10.05
15249.400000	53.01	---	200.0	H	34.0	10.9	74.00	20.99
17653.200000	---	47.45	200.0	V	77.0	14.1	54.00	6.55
17653.200000	55.85	---	200.0	V	77.0	14.1	74.00	18.15

High Channel: 2480MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
1987.700000	---	29.29	150.0	V	213.0	-4.9	54.00	24.71
1987.700000	39.09	---	150.0	V	213.0	-4.9	74.00	34.91
3708.100000	---	33.89	200.0	V	15.0	-0.8	54.00	20.11
3708.100000	42.89	---	200.0	V	15.0	-0.8	74.00	31.11
6033.700000	---	37.89	150.0	H	63.0	4.2	54.00	16.11
6033.700000	48.02	---	150.0	H	63.0	4.2	74.00	25.98
9020.600000	---	42.52	200.0	H	149.0	9.5	54.00	11.48
9020.600000	51.44	---	200.0	H	149.0	9.5	74.00	22.56
11217.000000	---	42.53	200.0	H	85.0	10.1	54.00	11.47
11217.000000	51.71	---	200.0	H	85.0	10.1	74.00	22.29
17719.500000	---	47.22	200.0	H	335.0	13.9	54.00	6.78
17719.500000	55.76	---	200.0	H	335.0	13.9	74.00	18.24

18GHz-25GHz

*(Pre-scan with low, middle and high channels of operation in the X,Y and Z axes of orientation, the worst case **high channel of operation in the Z axis of orientation** was recorded)*

Horizontal



Date: 9.MAR.2021 21:51:36

Vertical



Date: 9.MAR.2021 21:45:09

Restricted Bands Emissions Test:
*(Pre-scan in the X,Y and Z axes of orientation, the worst case **Z-axis of orientation** was recorded)*

Note:
1. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
   Corrected Amplitude (dBμV/m) = Corrected Factor (dB/m) + Reading (dBμV)
   Margin (dB) = Limit (dBμV/m) – Corrected Amplitude (dBμV/m)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
Low Channel: 2402MHz								
2390.000000	49.66	---	200.0	V	62.0	3.8	74.00	24.34
2390.000000	---	45.70	200.0	V	62.0	3.8	54.00	8.30
High Channel: 2480MHz								
2483.500000	50.27	---	200.0	V	88.0	4.2	74.00	23.73
2483.500000	---	46.96	200.0	V	88.0	4.2	54.00	7.04

For BLE Mode(2Mbps):

Spurious Emission Test:

30MHz-1GHz

*(Pre-scan with low, middle and high channels of operation in the X,Y and Z axes of orientation, the worst case **high channel of operation in the Z axis of orientation** was recorded)*



Frequency (MHz)	Corrected Amplitude QuasiPeak (dBµV/m)	Rx Antenna Height (cm)	Rx Antenna Polar (H/V)	Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
30.052381	32.46	100.0	V	109.0	-3.9	40.00	7.54
37.042850	24.98	100.0	V	79.0	-8.6	40.00	15.02
66.038900	12.29	100.0	V	19.0	-16.5	40.00	27.71
87.328100	11.40	199.0	V	355.0	-16.8	40.00	28.60
127.570300	16.98	199.0	V	173.0	-10.4	43.50	26.52
201.298050	18.03	100.0	V	186.0	-10.9	43.50	25.47

1GHz-18GHz

*(Pre-scan in the X,Y and Z axes of orientation, the worst case **Z-axis of orientation** was recorded)*

Note:
1. This test was performed with the 2.4-2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
   Corrected Amplitude (dBµV/m) = Corrected Factor (dB/m) + Reading (dBµV)
   Margin (dB) = Limit (dBµV/m) – Corrected Amplitude (dBµV/m)

Low Channel: 2402MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
1703.800000	37.63	---	150.0	V	217.0	-5.8	74.00	36.37
1703.800000	---	28.91	150.0	V	217.0	-5.8	54.00	25.09
2995.800000	41.60	---	150.0	V	6.0	-2.1	74.00	32.40
2995.800000	---	34.16	150.0	V	6.0	-2.1	54.00	19.84
4374.500000	45.29	---	150.0	V	166.0	1.1	74.00	28.71
4374.500000	---	35.71	150.0	V	166.0	1.1	54.00	18.29
6667.800000	---	38.64	200.0	V	143.0	5.5	54.00	15.36
6667.800000	48.68	---	200.0	V	143.0	5.5	74.00	25.32
11854.500000	---	41.99	200.0	V	15.0	10.2	54.00	12.01
11854.500000	50.96	---	200.0	V	15.0	10.2	74.00	23.04
17575.000000	---	46.46	150.0	V	0.0	14.3	54.00	7.54
17575.000000	55.94	---	150.0	V	0.0	14.3	74.00	18.06

Middle Channel: 2440MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
2247.800000	---	30.05	200.0	V	325.0	-4.5	54.00	23.95
2247.800000	39.95	---	200.0	V	325.0	-4.5	74.00	34.05
3325.600000	---	33.68	150.0	V	73.0	-1.8	54.00	20.32
3325.600000	42.32	---	150.0	V	73.0	-1.8	74.00	31.68
4880.000000	---	36.82	200.0	H	358.0	0.6	54.00	17.18
4880.000000	43.86	---	200.0	H	358.0	0.6	74.00	30.14
8002.300000	---	40.53	150.0	V	284.0	6.1	54.00	13.47
8002.300000	49.44	---	150.0	V	284.0	6.1	74.00	24.56
13297.800000	---	41.59	200.0	V	274.0	9.9	54.00	12.41
13297.800000	51.94	---	200.0	V	274.0	9.9	74.00	22.06
17671.900000	---	47.40	150.0	H	198.0	14.0	54.00	6.60
17671.900000	55.93	---	150.0	H	198.0	14.0	74.00	18.07

High Channel: 2480MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
1996.200000	---	33.86	150.0	V	352.0	-4.9	54.00	20.14
1996.200000	40.95	---	150.0	V	352.0	-4.9	74.00	33.05
3298.400000	---	33.29	150.0	V	143.0	-1.8	54.00	20.71
3298.400000	42.50	---	150.0	V	143.0	-1.8	74.00	31.50
4639.700000	---	34.98	150.0	V	92.0	1.0	54.00	19.02
4639.700000	45.14	---	150.0	V	92.0	1.0	74.00	28.86
6589.600000	---	39.85	150.0	H	103.0	5.5	54.00	14.15
6589.600000	49.26	---	150.0	H	103.0	5.5	74.00	24.74
11353.000000	---	42.84	200.0	H	149.0	10.3	54.00	11.16
11353.000000	51.78	---	200.0	H	149.0	10.3	74.00	22.22
17600.500000	---	47.04	200.0	V	237.0	14.2	54.00	6.96
17600.500000	55.57	---	200.0	V	237.0	14.2	74.00	18.43

18GHz-25GHz

*(Pre-scan with low, middle and high channels of operation in the X,Y and Z axes of orientation, the worst case **high channel of operation in the Z axis of orientation** was recorded)*

Horizontal



Date: 9.MAR.2021 21:36:53

Vertical



Date: 9.MAR.2021 21:30:26

Restricted Bands Emissions Test:
*(Pre-scan in the X,Y and Z axes of orientation, the worst case **Z-axis of orientation** was recorded)*

Note:
1. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
   Corrected Amplitude (dBµV/m) = Corrected Factor (dB/m) + Reading (dBµV)
   Margin (dB) = Limit (dBµV/m) – Corrected Amplitude (dBµV/m)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
Low Channel: 2402MHz								
2390.000000	51.83	---	150.0	V	325.0	3.8	74.00	22.17
2390.000000	---	45.98	150.0	V	325.0	3.8	54.00	8.02
High Channel: 2480MHz								
2483.500000	50.72	---	200.0	V	125.0	4.2	74.00	23.28
2483.500000	---	47.36	200.0	V	125.0	4.2	54.00	6.64

Conducted Spurious Emissions at Antenna Port

802.11b Mode Low Channel



802.11b Mode Middle Channel



802.11b Mode High Channel



802.11g Mode Low Channel



802.11g Mode Middle Channel



Date: 24.FEB.2021 13:59:39

802.11g Mode High Channel



Date: 24.FEB.2021 14:01:23

802.11n-HT20 Mode Low Channel



802.11n-HT20 Mode Middle Channel



802.11n-HT20 Mode High Channel



802.11n-HT40 Mode Low Channel



802.11n-HT40 Mode Middle Channel



802.11n-HT40 Mode High Channel



1Mbps:

BLE Mode Low Channel



BLE Mode Middle Channel



BLE Mode High Channel



2Mbps:

BLE Mode Low Channel



BLE Mode Middle Channel



Date: 22.FEB.2021 14:14:45

BLE Mode High Channel



Date: 22.FEB.2021 14:20:59

FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH

Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

According to ANSI C63.10-2013 sub-clause 11.8.1

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) ≥ 3 x RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



Test Data

Environmental Conditions

Temperature:	24.6-25.3 ℃
Relative Humidity:	48-54 %
ATM Pressure:	101.1-101.5 kPa

The testing was performed by Chao Gao from 2021-02-22 to 2021-02-24.

Test Result: Compliant.

EUT operation mode: Transmitting

Channel	Frequency (MHz)	6 dB Emission Bandwidth (MHz)	Limit (MHz)
802.11b Mode			
Low	2412	8.12	≥0.5
Middle	2437	8.12	≥0.5
High	2462	8.12	≥0.5
802.11g Mode			
Low	2412	15.87	≥0.5
Middle	2437	15.87	≥0.5
High	2462	15.33	≥0.5
802.11n-HT20 Mode			
Low	2412	16.89	≥0.5
Middle	2437	16.23	≥0.5
High	2462	15.63	≥0.5
802.11n-HT40 Mode			
Low	2422	35.59	≥0.5
Middle	2437	35.59	≥0.5
High	2452	35.59	≥0.5
BLE Mode(1Mbps)			
Low	2402	0.739	≥0.5
Middle	2440	0.745	≥0.5
High	2480	0.745	≥0.5
BLE Mode(2Mbps)			
Low	2402	1.132	≥0.5
Middle	2440	1.132	≥0.5
High	2480	1.132	≥0.5

802.11b Mode Low Channel



802.11b Mode Middle Channel



802.11b Mode High Channel



802.11g Mode Low Channel



802.11g Mode Middle Channel



Date: 24.FEB.2021 10:22:45

802.11g Mode High Channel



Date: 24.FEB.2021 10:24:33

802.11n-HT20 Mode Low Channel



802.11n-HT20 Mode Middle Channel



802.11n-HT20 Mode High Channel



Date: 24.FEB.2021 10:43:44

802.11n-HT40 Mode Low Channel



Date: 24.FEB.2021 10:52:31

802.11n-HT40 Mode Middle Channel



802.11n-HT40 Mode High Channel



1Mbps:

BLE Mode Low Channel



BLE Mode Middle Channel



BLE Mode High Channel



2Mbps:

BLE Mode Low Channel



BLE Mode Middle Channel



BLE Mode High Channel



FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, Compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

For Wi-Fi:

According to ANSI C63.10-2013 sub-clause 11.9.1.3

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast-responding diode detector.



For BLE:

According to ANSI C63.10-2013 sub-clause 11.9.1.1

1. Set the RBW ≥ DTS bandwidth.
2. Set VBW ≥ 3 x RBW.
3. Set span ≥ 3 x RBW
4. Sweep time = auto couple.
5. Detector = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use peak marker function to determine the peak amplitude level.



Test Data

Environmental Conditions

Temperature:	25.0-25.3 ℃
Relative Humidity:	48-50 %
ATM Pressure:	101.1-101.3 kPa

The testing was performed by Chao Gao from 2021-02-22 to 2021-02-24.

Test Result: Compliant.

EUT operation mode: Transmitting

Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Max Conducted Average Output Power (dBm)	Limit (dBm)	Result
802.11b Mode					
Low	2412	16.37	12.43	30	Pass
Middle	2437	16.64	13.15	30	Pass
High	2462	17.03	13.31	30	Pass
802.11g Mode					
Low	2412	20.52	10.94	30	Pass
Middle	2437	20.75	11.38	30	Pass
High	2462	21.24	11.67	30	Pass
802.11n-HT20 Mode					
Low	2412	20.78	10.99	30	Pass
Middle	2437	21.15	11.44	30	Pass
High	2462	21.61	11.96	30	Pass
802.11n-HT40 Mode					
Low	2422	16.58	5.84	30	Pass
Middle	2437	16.85	6.23	30	Pass
High	2452	16.99	6.39	30	Pass
BLE Mode(1Mbps)					
Low	2402	1.07	/	30	Pass
Middle	2440	2.19	/	30	Pass
High	2480	2.38	/	30	Pass
BLE Mode(2Mbps)					
Low	2402	1.15	/	30	Pass
Middle	2440	2.33	/	30	Pass
High	2480	2.45	/	30	Pass

1Mbps:

BLE Mode Low Channel



BLE Mode Middle Channel



BLE Mode High Channel



2Mbps:

BLE Mode Low Channel



BLE Mode Middle Channel



BLE Mode High Channel



FCC §15.247(d) – BAND EDGE

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates Compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

According to ANSI C63.10-2013 sub-clause 6.10.

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Data

Environmental Conditions

Temperature:	24.6-25.3 ℃
Relative Humidity:	48-54 %
ATM Pressure:	101.1-101.5 kPa

The testing was performed by Chao Gao from 2021-02-22 to 2021-02-24.

Test Result: Compliant.

EUT operation mode: Transmitting

802.11b Mode Left Side



802.11b Mode Right Side



802.11g Mode Left Side



802.11g Mode Right Side



802.11n-HT20 Mode Left Side



802.11n-HT20 Mode Right Side



802.11n-HT40 Mode Left Side



Date: 24.FEB.2021 11:56:42

802.11n-HT40 Mode Right Side



Date: 24.FEB.2021 11:58:28

1Mbps:

BLE Mode Left Side



BLE Mode Right Side



2Mbps:

BLE Mode Left Side



BLE Mode Right Side



FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

According to ANSI C63.10-2013 sub-clause 11.10.2

The following procedure shall be used if maximum peak conducted output power was used to determine compliance, and it is optional if the maximum conducted (average) output power was used to determine compliance:

1. Set the RBW to: 3kHz≤ RBW≤100 kHz.
2. Set the VBW ≥ 3xRBW.
3. Set the span to 1.5 times the DTS bandwidth.
4. Detector = peak.
5. Sweep time = auto couple.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use the peak marker function to determine the maximum amplitude level within the RBW.
9. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

Test Data

Environmental Conditions

Temperature:	24.6-25.3 ℃
Relative Humidity:	48-54 %
ATM Pressure:	101.1-101.5 kPa

The testing was performed by Chao Gao from 2021-02-22 to 2021-02-24.

Test Result: Compliant.

EUT operation mode: Transmitting

Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)
802.11b Mode			
Low	2412	-8.18	≤8
Middle	2437	-7.61	≤8
High	2462	-7.31	≤8
802.11g Mode			
Low	2412	-10.85	≤8
Middle	2437	-10.83	≤8
High	2462	-10.02	≤8
802.11n-HT20 mode			
Low	2412	-11.11	≤8
Middle	2437	-10.40	≤8
High	2462	-9.86	≤8
802.11n-HT40 mode			
Low	2422	-17.11	≤8
Middle	2437	-17.01	≤8
High	2452	-16.12	≤8
BLE Mode(1Mbps)			
Low	2402	-13.32	≤8
Middle	2440	-12.27	≤8
High	2480	-12.01	≤8
BLE Mode(2Mbps)			
Low	2402	-16.24	≤8
Middle	2440	-15.05	≤8
High	2480	-14.76	≤8

802.11b Mode Low Channel



802.11b Mode Middle Channel



802.11b Mode High Channel



802.11g Mode Low Channel



802.11g Mode Middle Channel



802.11g Mode High Channel



802.11n-HT20 Mode Low Channel



Date: 24.FEB.2021 15:34:47

802.11n-HT20 Mode Middle Channel



Date: 24.FEB.2021 15:37:00

802.11n-HT20 Mode High Channel



Date: 24.FEB.2021 15:39:15

802.11n-HT40 Mode Low Channel



Date: 24.FEB.2021 15:42:27

802.11n-HT40 Mode Middle Channel



802.11n-HT40 Mode High Channel



1Mbps:

BLE Mode Low Channel



BLE Mode Middle Channel



BLE Mode High Channel



2Mbps:

BLE Mode Low Channel



BLE Mode Middle Channel



Date: 22.FEB.2021 14:25:00

BLE Mode High Channel



Date: 22.FEB.2021 14:23:39

Declarations

1: BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk '*'. Customer model name, addresses, names, trademarks etc. are not considered data.

2: Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

3: Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

4: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

5: This report cannot be reproduced except in full, without prior written approval of the Company.

6: This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

******* END OF REPORT *******