

TEST REPORT

Report No.:SHATBL2603036W01

Applicant : Satellite Electronic(Zhong Shan)Ltd.

Product Name : CEILING FAN REMOTE CONTROL

Brand Name : N/A

Model Name : TRD070M1Z

Series Model : TRA070M2Z, TRA070M3Z

FCC ID : 2AQZU-18081

Test Standard : 47 CFR Part 15 Subpart C, Section 15.231

Date of Sample Arrival : Mar.25, 2026

Date of Test : Mar.25, 2026~Mar.28, 2026


Issue Date : Apr.22, 2026

Report Prepared by :



(Emily)

Report Approved by :



(Guozheng Li)

Authorized Signatory :



(Terry Yang)



"Shanghai ATBL Technology Co., Ltd." hereby certifies that according to actual testing conditions. The test results or observations are provided in accordance with measured value, without taking risks caused by uncertainty into account. Without explicit stipulation in special agreements, standards or regulations, ATBL shall not assume any responsibility. The test results or observations are applicable only to tested sample. Client shall be responsible for representativeness of the sample and authenticity of the material. This report will be void without authorized signature or special seal for testing report. Do not copied without authorization.

Table of Contents

REVISION HISTORY	3
DECLARATION OF REPORT	4
SUMMARY OF TEST RESULT	5
1. GENERAL DESCRIPTION	6
1.1. APPLICANT	6
1.2. MANUFACTURER	6
1.3. FACTORY	6
1.4. GENERAL INFORMATION OF EUT	7
1.5. ENVIRONMENTAL CONDITIONS	7
1.6. DESCRIPTION OF THE TEST MODES	8
1.7. BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	8
1.8. TEST SOFTWARE AND POWER LEVEL	8
1.9. DESCRIPTION OF SUPPORT UNITS	8
1.10. LABORATORY INFORMATION	9
1.11. MEASUREMENT UNCERTAINTY	9
1.12. EQUIPMENT LIST	10
2. TEST RESULT	12
2.1. CONDUCTED EMISSION MEASUREMENT	12
2.2. RADIATED EMISSION MEASUREMENT	16
2.3. BANDWIDTH TEST	25
2.4. DUTY CYCLE	27
2.5. AUTOMATICALLY DEACTIVATE	29
2.6. ANTENNA REQUIREMENT	30
3. TEST SETUP PHOTOGRAPHS	30
4. EXTERNAL AND INTERNAL PHOTOS OF THE EUT	30

Revision History

Rev.	Issue Date	Report No.	Effect Page	Contents
00	Apr.22, 2026	SHATBL2603036W01	ALL	Initial Release

DECLARATION OF REPORT

1. The device has been tested by ATBL, and the test results show that the equipment under test (EUT) is in compliance with the requirements of 47 CFR 15.231. And it is applicable only to the tested sample identified in the report.
2. This report shall not be reproduced except in full, without the written approval of ATBL, this document only be altered or revised by ATBL, personal only, and shall be noted in the revision of the document.
3. The general information of EUT in this report is provided by the customer or manufacture, ATBL is only responsible for the test data but not for the information provided by the customer or manufacture.
4. The results in this report is only apply to the sample as tested under conditions. The customer or manufacturer is responsible for ensuring that the additional production units of this model have the same electrical and mechanical components.
5. In this report, '☐' indicates that EUT does not support content after '☐', and '☑' indicates that it supports content after '☑'

Summary of Test Result

Standard Section	Test Item	Result	Remark
15.207	Conducted Emission	PASS	--
15.209/ 15.231.(b)	Radiated Spurious Emission	PASS	--
15.231.(b)	Field Strength of Fundamental Emissions	PASS	--
15.231(a)(1)	Transmission requirement	PASS	--
15.231(C)	20dB&99% Bandwidth	PASS	--
15.203	Antenna Requirement	PASS	--
15.35	Duty Cycle	PASS	--

NOTE:

- (1). 'N/A' denotes test is not applicable in this Test Report.
- (2). All tests are according to ANSI C63.10-2020.

1. General Description

1.1. Applicant

Name : Satellite Electronic(Zhong Shan)Ltd.

Address : No.8, Chuang Ye Road, Torch Development Zone, Zhongshan, Guangdong, China

1.2. Manufacturer

Name : Satellite Electronic(Zhong Shan)Ltd.

Address : No.8, Chuang Ye Road, Torch Development Zone, Zhongshan, Guangdong, China

1.3. Factory

Name : CHUNGEAR INDUSTRIAL CO., LTD.

Address : No.12, Jingke 8th Rd., Nantun Dist., Taichung City 40852, Taiwan (R.O.C.)

1.4. General Information of EUT

Product Name	CEILING FAN REMOTE CONTROL
Trade Name	N/A
Model Name	TRD070M1Z
Series Model	TRA070M2Z, TRA070M3Z
Model Difference	Only button count, screen printing, and software version differ; other aspects remain the same
Frequency band	303.875MHz
Power supply	AC 120V
Modulation Type	ASK
Antenna type	PCB Antenna
Antenna gain	-6dBi
Hardware version number	260204
Software version number	TRD070M1Z: 25-P-313-3092-04576ADF-TRD070M1Z-20260312 TRA070M2Z,TRA070M3Z: 26-P-001-3092-2B3E6ADF-TRA070M3Z-20260313

Note:

For a more detailed features description, please refer to the manufacturer's specifications or the User Manual.

1.5. Environmental Conditions

Temperature	Normal Temperature:	25°C
Voltage	Normal Voltage:	AC 120V
Other	Relative Humidity:	54%
	Air Pressure:	100kPa

1.6. Description of the test modes

For Conducted test items and Radiated spurious emissions:

Each of these EUT operation mode(s) or test configuration mode(s) mentioned below was evaluated respectively.

Pretest Mode	Description
Mode 1	TX Mode

Note:


For the test results, the EUT had been tested with all conditions, but only the worst case was shown in test report.

For AC Power-Line Conducted Emission

Pretest Mode	Description
Mode 1	TX Mode

1.7. Block diagram showing the configuration of system tested

During test, Keep EUT is in continuous transmission mode, Both open button and closed button have been tested, The two keys were tested to assess and only record the worst case in the report (Open button).



1.8. Test Software and Power Level

RF power setting value	
Channel	Power setting
303.875MHz	Default- Level 2

Note:

1.For the test results, the EUT had been tested with all conditions, and the worst-case mode of data will record in the report.

2.Fixed frequency is triggered by pressing a button.

1.9. Description of Support Units

NO.	Unit	Brand	Model	Description
1	AC Line	N/A	N/A	N/A
2	N/A	N/A	N/A	N/A

1.10. Laboratory Information

Company Name	:	Shanghai ATBL Technology Co., Ltd.
Address	:	5-6/F., Unit 1, No 8, Free Trade One Life Science and Sci-Tech Industrial Park No. 160, Basheng Road, Pudong New District Shanghai City, People's Republic of China
Telephone	:	+86(0)21-51298625
FCC-Registration No	:	485917
Designation Number	:	CN1306
A2LA-Lab Cert. No.	:	6184.01

1.11. Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	RF output power, conducted	$\pm 0.68\text{dB}$
2	Unwanted Emissions, conducted	$\pm 2.988\text{dB}$
3	All emissions, radiated 9K-30MHz	$\pm 2.84\text{dB}$
4	All emissions, radiated 30M- 1GHz	$\pm 4.39\text{dB}$
5	All emissions, radiated 1G-6GHz	$\pm 5.10\text{dB}$
6	All emissions, radiated > 6G	$\pm 5.48\text{dB}$
7	Conducted Emission (9kHz- 150kHz)	$\pm 2.79\text{dB}$
8	Conducted Emission (150kHz-30MHz)	$\pm 2.80\text{dB}$

1.12. Equipment List

1.12.1. For AC Power-Line Conducted Emission

Kind of Equipment	Manufacturer	Type No.	Serial No.	equipment number	Calibrated until	Calibrated due until	Cal. Interval
EMI Test Receiver	R&S	ESPI	100679	SHATBL-E012	2025.05.20	2026.05.19	1 year
LISN	R&S	ENV216	101300	SHATBL-E013	2025.05.20	2026.05.19	1 year
LISN	R&S	ENV216	100333	SHATBL-E041	2025.05.20	2026.05.19	1 year
CE Cable	Chuangcexing	2M	EMI0014	SHATBL-E014	N/A	N/A	N/A
Temperature & Humidity	Deli	Deli	EMI0015	SHATBL-E015	2025.08.01	2026.07.31	1 year
Testing Software	FALA	EZ-EMC(Ver.EMC-CON 3A1.1)	EMI0044	SHATBL-E044	N/A	N/A	N/A

1.12.2. For Radiated Spurious Emission

Kind of Equipment	Manufacturer	Type No.	Serial No.	equipment number	Calibrated until	Calibrated due until	Cal. Interval
Signal analyzer	Agilent	N9020A	MY50200811	SHATBL-E017	2025.05.20	2026.05.19	1 year
Amplifier	JPT	JPA0118-55-303A	1910001800055000	SHATBL-E006	2025.05.20	2026.05.19	1 year
Amplifier	JPT	JPA-10M1G32	21010100035001	SHATBL-E005	2025.05.20	2026.05.19	1 year
Antenna/Turn table Controller	Brilliant	N/A	N/A	SHATBL-E007	N/A	N/A	N/A
Loop Antenna(9kHz-30MHz)	Daze	ZN30900C	20077	SHATBL-E042	2025.05.20	2026.05.19	1 year
Bilog Antenna	SCHWARZBECK	VULB 9168	01174	SHATBL-E008	2025.05.20	2026.05.19	1 year
Broad-band Horn Antenna	SCHWARZBECK	BBHA 9120D	02334	SHATBL-E009	2025.05.20	2026.05.19	1 year
Horn Antenna	COM-POWER	AH-1840	10100008	SHATBL-E043	2025.07.27	2026.07.26	1 year
Thermometer	DeLi	N/A	N/A	SHATBL-E015	2025.08.01	2026.07.31	1 year
Test Software	FALA	EMC-RI(Ver.4A2)	N/A	N/A	N/A	N/A	N/A
Wideband radio communication tester	R&S	CMW500	101331	SHATBL-W044	2025.07.28	2026.07.27	1 year
Spectrum analyzer	R&S	FSV40-N	101761	SHATBL-W036	2025.07.28	2026.07.27	1 year
Filter box	XH microwave	RSE01	N/A	SHATBL-W030	N/A	N/A	N/A
Coaxial cable (9kHz~26.5GHz)	XINQY	XINQYCT 26PE	CT26PE	SHATBL-W037	2025.07.28	2026.07.27	1 year
Coaxial cable (18~40GHz)	XINQY	CXN3506	CLB220E	SHATBL-W037	2025.07.28	2026.07.27	1 year

1.12.3. For Conducted Test

Kind of Equipment	Manufacturer	Type No.	Serial No.	equipment number	Calibrated until	Calibrated due until	Cal. Interval
Power sensor	DARE	RPR3006W	16I00054SN016	SHATBL-W008	2025.07.28	2026.07.27	1 year
Adjustable Attenuator	Agilent	8494B	MY42144015	SHATBL-W009	2025.07.28	2026.07.27	1 year
Adjustable Attenuator	Agilent	8496B	MY42143776	SHATBL-W010	2025.07.28	2026.07.27	1 year
Environmental Test Chamber	KSON	THS-B6C-150	9159K	SHATBL-W019	2025.07.28	2026.07.27	1 year
Signal analyzer	Keysight	N9020A	MY50510136	SHATBL-W003	2025.07.18	2026.07.17	1 year
Vector signal generator	Agilent	N5182A	MY48180764	SHATBL-W043	2025.07.18	2026.07.17	1 year
Analog signal generator	Keysight	N5182B	MY57300196	SHATBL-W005	2025.07.18	2026.07.17	1 year
Wideband radio communication tester	R&S	CMW500	101331	SHATBL-W007	2025.07.28	2026.07.27	1 year
Switch Box	Cesheng	smu 1003	WCS20221215	SHATBL-W046	2025.05.20	2026.05.19	1 year
Thermometer	DeLi	N/A	N/A	SHATBL-W011	2025.08.01	2026.07.31	1 year
Test Software	Cesheng	WCS-WC N	N/A	SHATBL-W021	N/A	N/A	N/A
Attenuator	Xupu	2W	100024644897	SHATBL-W026	N/A	N/A	N/A

Remark:

Calibration duration for above equipment is 1 year.

2. Test Result

2.1. Conducted emission measurement

2.1.1. power line conducted emission limits

The radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table.

FREQUENCY (MHz)	Class B (dBuV)		Standard
	Quasi- peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	Part 15.207
0.50 -5.0	56.00	46.00	Part 15.207
5.0 -30.0	60.00	50.00	Part 15.207

Note:

(1) .The tighter limit applies at the band edges.

(2) .The limit of “ * ” marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

2.1.2. Test Procedure


a.The EUT is 0.8 m from the horizontal ground plane and 0.4 m from the vertical ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipment are powered from additional LISN(s). The LISN provides 50 Ohm/ 50uH of coupling impedance for the measuring instrument.

b.Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.

c.I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.

d.LISN is at least 80 cm from the nearest part of EUT chassis.

e.For the actual test configuration, please refer to the related Item – EUT Test Photos.




2.1.4. EUT operating conditions

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.


2.1.5. Test Results

Note:

- 1.Emission Level = Reading Value+ Correction Factor.
- 2.Correction Factor= Insertion loss + Cable loss.
- 3.Margin value = Emission level-Limit value.



Temperature:	25°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz	Phase :	N
Test Mode:	TX Mode		



No.	Frequency (MHz)	Read_Level (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Det.
1	0.2020	18.81	20.02	38.83	63.53	-24.70	peak
2	0.2020	7.91	20.02	27.93	53.53	-25.60	AVG
3	0.2420	6.74	19.95	26.69	52.03	-25.34	AVG
4	0.2860	16.74	19.91	36.65	60.64	-23.99	peak
5	0.6540	8.30	19.70	28.00	46.00	-18.00	AVG
6	0.6620	21.48	19.71	41.19	56.00	-14.81	peak
7	1.2380	13.14	19.83	32.97	56.00	-23.03	peak
8	1.2780	2.88	19.84	22.72	46.00	-23.28	AVG
9	2.2060	10.81	20.07	30.88	56.00	-25.12	peak
10	2.2180	0.74	20.07	20.81	46.00	-25.19	AVG
11	4.8900	11.94	20.18	32.12	56.00	-23.88	peak
12	4.9780	1.65	20.19	21.84	46.00	-24.16	AVG

2.2. Radiated emission measurement

2.2.1. Radiated Emission Limits

In case the emission fall within the restricted band specified on Part 15.205(a), then the Part 15.209(a) and Part 15.231(b) limit in the table below has to be followed.

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

According to § 15.231(b), the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental frequency (MHz)	Field strength of fundamental (microvolts/meter)	Field strength of spurious emissions (microvolts/meter)
40.66-40.70	2,250	225
70-130	1,250	125
130-174	¹ 1,250 to 3,750	¹ 125 to 375
174-260	3,750	375
260-470	¹ 3,750 to 12,500	¹ 375 to 1,250
Above 470	12,500	1,250

Note:

- 1.Linear interpolations.
- 2.The lower limit shall apply at the transition frequencies.
- 3.Emission level (dBuV/m) = 20 log Emission level (uV/m).
- 4.As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

Limits of restricted frequency bands:

FREQUENCY (MHz)	FREQUENCY (MHz)	FREQUENCY (MHz)	FREQUENCY (GHz)
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41			

Spectrum Parameter	Setting
Detector	Peak
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1MHz / 3MHz


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~90kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	90kHz~110kHz / RB 200Hz for QP
Start ~ Stop Frequency	110kHz~490kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	490kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

2.2.2. Test Procedure


- The measuring distance of at 3 m shall be used for measurements at frequency 0.009MHz up to 1GHz, and above 1GHz.
- The EUT was placed on the top of a rotating table 0.8 meters (above 1GHz is 1.5 m) above the ground at a 3 meter anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the equipment shall be 0.8 m (above 1GHz is 1.5 m); the height of the test antenna shall vary between 1 m to 4 m. Horizontal and vertical polarization of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- For the actual test configuration, please refer to the related Item - EUT Test Photos:
- Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported.

2.2.3. Test Setup


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



2.2.4.EUT operating conditions

The EUT tested system was configured as the statements of 1.7 Unless otherwise a special operating condition is specified in the follows during the testing.

2.2.5.Field strength calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where

FS = Field Strength

CL = Cable Attenuation Factor (Cable Loss)

RA = Reading Amplitude

AG = Amplifier Gain

AF = Antenna Factor

For example

$$\text{Factor} = AF + CL - AG$$

2.2.6. Test Results

Field Strength of Fundamental Emissions and Field strength of spurious emissions Value					
Operating Frequency (MHz)	Field Strength (dBuV/m)	Detector	Limit @3m (dBuV/m)	Margin (dB)	Antenna
304.25	62.0	Peak	94.93	-32.93	Horizontal
	62.1	Peak	94.93	-32.83	Vertical
608.50	43.6	Peak	74.93	-31.33	Horizontal
	41.3	Peak	74.93	-33.63	Vertical
912.75	39.7	Peak	74.93	-35.23	Horizontal
	35.8	Peak	74.93	-39.13	Vertical
304.25	53.25	Avg	74.93	-21.68	Horizontal
	53.35	Avg	74.93	-21.58	Vertical
608.50	34.85	Avg	54.93	-20.08	Horizontal
	32.55	Avg	54.93	-22.38	Vertical
912.75	30.95	Avg	54.93	-23.98	Horizontal
	27.05	Avg	54.93	-27.88	Vertical

Note:

Fundamental AV value =PK Emission +20*log(duty cycle)Where the duty factor is calculated from following formula:20 log (Duty cycle) =20Log(36.51%)=-8.75dB, Please see page 27.

(Radiated Emission<30MHz (9kHz-30MHz, H-field))

Temperature:	25°C	Relative Humidity	54%RH
Test Voltage:	AC 120V/60Hz	Polarization:	N/A
Test Mode:	TX Mode		

Note:


- 1.The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
- 2.Distance extrapolation factor =40 log (specific distance/test distance)(dB);
Limit line = specific limits(dBuV) + distance extrapolation factor.
3. The verdict please refer to the A.6 field strength of fundamental emissions and field strength of spurious emissions value.
- 4.Limit field strength of fundamental:
 $20 \cdot \log(((12500-3750) \cdot ((f_c-260)/(470-260)) + 3750) \text{dBuV/m} + 20\text{dB} = 94.93\text{dBuV/m}@3\text{m (PK)}.$
5. Limit field strength of harmonics: $20 \cdot \log(((1250-375) \cdot ((f_c-260)/(470-260)) + 375) \text{dBuV/m} + 20\text{dB} = 74.93\text{dBuV/m}@3\text{m (PK)}.$

For 30MHz -1000MHz:

Remark:


1. Margin = Result (Result =Reading + Factor)-Limit
2. Factor= Antenna factor+Cable attenuation factor(cable loss)-Amplifier gain
3. " * ": Fundamental frequency.
4. " # ": Harmonic frequency.

Temperature:	25°C	Relative Humidity:	55%RH
Test Voltage:	AC 120V/60Hz	Phase:	Horizontal
Test Mode:	TX Mode		



Mk.	Freq.(MHz)	Level(dBuV/m)	Limit(dBuV/m)	Margin(dB)
Peak:				
1	51.031	31.9	40.0	8.1
2	107.888	34.5	43.5	9.0
3	137.661	30.4	43.5	13.1
4	199.986	18.9	43.5	24.6
5*	303.875	62.0	94.93	32.93
6	475.499	20.9	46.0	25.1
7#	607.75	43.6	74.93	31.33
8	789.234	24.7	46.0	21.3
9#	911.625	39.7	74.93	35.23

Temperature:	25°C	Relative Humidity:	55%RH
Test Voltage:	AC 120V/60Hz	Phase:	Vertical
Test Mode:	TX Mode		



Mk.	Freq.(MHz)	Level(dBuV/m)	Limit(dBuV/m)	Margin(dB)
Peak:				
1	51.571	27.5	40.0	12.5
2	101.823	31.6	43.5	11.9
3	153.739	23.3	43.5	20.2
4	237.476	21.4	46.0	24.6
5	303.875	62.1	94.93	32.93
6	495.066	22.3	46.0	23.7
7	607.75	41.3	74.93	33.63
8	793.396	24.0	46.0	22.0
9	911.625	35.8	74.93	39.13


For 1000MHz -18000MHz:

Remark:

1. Margin = Result (Result =Reading + Factor)–Limit


2. Factor= Antenna factor+Cable attenuation factor(cable loss)-Amplifier gain

Temperature:	25℃	Relative Humidity:	55%RH
Test Voltage:	AC 120V/60Hz	Phase:	Horizontal
Test Mode:	TX Mode		



Mk.	Freq.(MHz)	Level(dBuV/m)	Limit(dBuV/m)	Margin(dB)
Peak:				
1	1825.000	53.3	74.0	20.7
2	2737.500	54.0	74.0	20.0
3	13608.000	61.1	74.0	12.9
Avg				
1	1825.000	46.9	54.0	7.1
2	2737.500	48.6	54.0	5.4
3	13608.000	52.7	54.0	1.3

Temperature:	25°C	Relative Humidity:	55%RH
Test Voltage:	AC 120V/60Hz	Phase:	Vertical
Test Mode:	TX Mode		



Mk.	Freq.(MHz)	Level(dBuV/m)	Limit(dBuV/m)	Margin(dB)
Peak:				
1	1825.000	50.6	74.0	23.4
2	2737.500	56.1	74.0	17.9
3	10428.000	61.9	74.0	12.1
Avg				
1	1825.000	44.2	54.0	9.8
2	2737.500	49.7	54.0	4.3
3	10428.000	52.5	54.0	1.5


2.3. Bandwidth Test

2.3.1.Limit

The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20 dB down from the modulated carrier.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth
RB	10 kHz
VB	30 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

2.3.2.Test Setup




2.3.3.EUT operating conditions

The EUT tested system was configured as the statements of 1.7 Unless otherwise a special operating condition is specified in the follows during the testing.

2.3.4. Test Results

Centre Frequency (MHz)	20dB Bandwidth (kHz)	Limit(kHz)	Results
303.875	53.21	760.625	PASS



2.4. Duty Cycle

2.4.1. Test Procedure


The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.

The Duty Cycle Was Determined By The Following Equation: To Calculate The Actual Field Intensity, The Duty Cycle Correction Factor In Decibel Is Needed For Later Use And Can Be Obtained From Following Conversion.

Duty Cycle(%)=Total On Interval In A Complete Pulse Train/ Length Of A Complete Pulse Train * %

Duty Cycle Correction Factor(Db)=20 * Log10(Duty Cycle(%))

2.4.2. Test Setup



2.4.3. EUT operating conditions

TX mode.

2.4.4. Test Results

$T_{on}(ms)$	$12 \times 0.764 + 13 \times 0.38 = 14.108$
T period(ms)	38.64
Duty Cycle (%)	36.51
Duty Cycle Correction Factor(dB)	-8.75

Test photo:



2.5. Automatically Deactivate

2.5.1. Standard requirement

A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.


2.5.2. Test Procedure

The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.


Spectrum Setting: RBW= 1MHz, VBW=3MHz, Sweep time = 15s.

Set the EUT to transmit by manually operated. Use the “View” function of SPA to find the transmission time of being released.

2.5.3. Test Setup



2.5.4. Test Results



2.6. Antenna Requirement

2.6.1. Standard requirement

FCC Part 15 Paragraph 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

The use of a permanently attached antenna to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

2.6.2. EUT Antenna

The EUT antenna is PCB Antenna. It conforms to the standard requirements.

3. Test Setup Photographs

Please refer to the Appendix F.

4. External and Internal photos of the EUT

Please refer to the Appendix G.

Please refer to the Appendix H.

*****END OF THE REPORT*****