

Company: Shoof Technologies, Inc.

Evaluation of: Strix Wireless Tag

To: FCC CFR 47 Part 1.1310

Report No.: SHOO03-U8 Rev A FCC MPE

MPE/RF EXPOSURE TEST REPORT



MPE/RF EXPOSURE REPORT



Evaluation of: Shoof Technologies, Inc. Strix Wireless Tag

To: FCC CFR 47 Part 1.1310

Report Serial No.: SHOO03-U8 Rev A FCC MPE

This report supersedes: NONE

Applicant: Shoof Technologies, Inc.
440 N. Wolfe Rd, Suite E112
Sunnyvale, California 94085
USA

Product Function; Wireless Tag

Issue Date; 23rd January 2019

This Test Report is Issued Under the Authority of:

MiCOM Labs, Inc.
575 Boulder Court
Pleasanton California 94566
USA
Phone: +1 (925) 462-0304
Fax: +1 (925) 462-0306
www.micomlabs.com



MiCOM Labs is an ISO 17025 Accredited Testing Laboratory



1. MAXIMUM PERMISSABLE EXPOSURE

Calculations for Maximum Permissible Exposure Levels

$$\text{Power Density} = P_d (\text{mW/cm}^2) = \text{EIRP} / (4 * \pi * d^2)$$

$$\text{EIRP} = P * G$$

P = Peak output power (mW)

G = Antenna numeric gain (numeric)

d = Separation distance (cm)

$$\text{Numeric Gain} = 10 ^ (G (\text{dBi}) / 10)$$

The calculations in the table below use the highest measured conducted power values together with the antenna gain specified for the EUT. These calculations represent worst case in terms of the exposure levels.

Specification - Maximum Permissible Exposure Limits.

The Limit is defined in Table 1 of FCC §1.1310.

Freq. Band (MHz)	Ant Gain (dBi)	Numeric Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Calculated Power Density (mW/cm ²) @ 20cm	Power Density Limit (mW/cm ²)	Min Calculated safe distance for Limit (cm)
434	-5.00	0.32	-4.22	0.38	0.000	0.28933	0.18
900 FHSS	3.00	2.00	26.76	474.24	0.188	0.6	11.20
2.4 BLE	4.00	2.51	15.21	33.19	0.017	1	2.58
2.4 DTS	4.00	2.51	16.88	48.75	0.024	1	3.12
2.4 FHSS	4.00	2.51	20.56	113.76	0.057	1	4.77

Note: for mobile or fixed location transmitters the minimum separation distance is 20cm, even if calculations indicate the MPE distance to be less.

Worst Case Simultaneous Operation

Assessment for simultaneous operation: 434 MHz, 900 MHz FHSS, 2.4GHz BLE, 2.4GHz FHSS:

Freq. Band (MHz)	Ant Gain (dBi)	Numeric Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Calculated Safe Distance for Summation (cm)	Power Density Limit (mW/cm ²) @ 20cm E _{ref}	Calculated Power Density (mW/cm ²) E _i	E _i /E _{ref} @ 20 cm
434	-5.00	0.32	-4.22	0.38	20	0.28933	0.00	0.00
900 FHSS	3.00	2.00	26.76	474.24	20	0.6	0.19	0.32
2400.0 - 2483.5 BLE	4.00	2.51	15.21	33.19	20	1	0.02	0.02
2400.0 - 2483.5 FHSS	4.00	2.51	20.56	113.76	20	1	0.06	0.06
Summation E _i /E _{ref} @ 20 cm distance:								0.40



575 Boulder Court
Pleasanton, California 94566, USA
Tel: +1 (925) 462 0304
Fax: +1 (925) 462 0306
www.micomlabs.com