

TEST REPORT



Product Name: Multimedia Speaker

Trade Mark:



PHILIPS or

Model No. /HVIN: SPA4000

SPA4000BK/00, SPA4000BK/98,
SPA4000/00, SPA4000BK/61,
SPA4000BK/79, SPA4000BK/10,

Add. Model No.: SPA4000BK/12, SPA4000/37,
SPA4000BK/37, SPA4000xx/yy(xx=AA-ZZ
or Nil for different color; yy=00-99 or Nil, for
different country code)

Report Number: 25111520816RFC-2

Test Standards: FCC 47 CFR Part 15 Subpart C
RSS-247 Issue 4
RSS-Gen Issue 5

FCC ID: 2AR2SSPA4000

IC: 24589-SPA4000

Test Result: PASS

Date of Issue: December 11, 2025

Prepared for:

MMD Hong Kong Holding Limited

**Units 1208-11, 12th Floor, C-Bons International Center, 108 Wai Yip Street,
Kwun Tong, Kowloon, Hong Kong**

Prepared by:

Shenzhen UnionTrust Quality and Technology Co., Ltd.

**16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua
Street, Longhua District, Shenzhen, China**

TEL: +86-755-2823 0888

FAX: +86-755-2823 0886

Prepared by:

David Chen

David Chen
Senior Project Engineer

Reviewed by:

Kevin Liang

Kevin Liang
Assistant Manager

Approved by:



Billy Li
Technical Director

Date:

December 11, 2025

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1

Version

Version No.	Date	Description
V1.0	December 11, 2025	Original



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1

CONTENTS

1. GENERAL INFORMATION	4
1.1 CLIENT INFORMATION	4
1.2 EUT INFORMATION	4
1.2.1 GENERAL DESCRIPTION OF EUT	4
1.2.2 DESCRIPTION OF ACCESSORIES	4
1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD	4
1.4 OTHER INFORMATION	5
1.5 DESCRIPTION OF SUPPORT UNITS	5
1.6 TEST LOCATION	5
1.7 TEST FACILITY	5
1.8 DEVIATION FROM STANDARDS	6
1.9 ABNORMALITIES FROM STANDARD CONDITIONS	6
1.10 OTHER INFORMATION REQUESTED BY THE CUSTOMER	6
1.11 MEASUREMENT UNCERTAINTY	6
2. TEST SUMMARY	7
3. EQUIPMENT LIST	8
4. TEST CONFIGURATION	9
4.1 ENVIRONMENTAL CONDITIONS FOR TESTING	9
4.1.1 NORMAL OR EXTREME TEST CONDITIONS	9
4.1.2 RECORD OF NORMAL ENVIRONMENT AND TEST SAMPLE	9
4.2 TEST CHANNELS	9
4.3 EUT TEST STATUS	9
4.4 TEST SETUP	10
4.4.1 FOR RADIATED EMISSIONS TEST SETUP	10
4.4.2 FOR CONDUCTED EMISSIONS TEST SETUP	11
4.4.3 FOR CONDUCTED RF TEST SETUP	12
4.5 SYSTEM TEST CONFIGURATION	12
4.6 DUTY CYCLE	13
5. RADIO TECHNICAL REQUIREMENTS SPECIFICATION	16
5.1 REFERENCE DOCUMENTS FOR TESTING	16
5.2 ANTENNA REQUIREMENT	16
5.3 CONDUCTED OUTPUT POWER AND E.I.R.P.	17
5.4 6 DB BANDWIDTH & OCCUPIED BANDWIDTH	18
5.5 POWER SPECTRAL DENSITY	19
5.6 CONDUCTED OUT OF BAND EMISSION	20
5.7 RADIATED SPURIOUS EMISSIONS	21
5.8 BAND EDGE MEASUREMENTS (RADIATED)	27
5.9 CONDUCTED EMISSION	36
APPENDIX A RF TEST DATA	39
A.1 MAXIMUM CONDUCTED OUTPUT POWER AND E.I.R.P.	39
A.2 6DB BANDWIDTH	46
A.3 OCCUPIED CHANNEL BANDWIDTH	53
A.4 MAXIMUM POWER SPECTRAL DENSITY	60
A.5 BAND EDGE MEASUREMENTS	67
A.6 CONDUCTED SPURIOUS EMISSION	72
APPENDIX 1 PHOTOS OF TEST SETUP	91
APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS	91

1. GENERAL INFORMATION

1.1 CLIENT INFORMATION

Applicant:	MMD Hong Kong Holding Limited
Address of Applicant:	Units 1208-11, 12th Floor, C-Bons International Center, 108 Wai Yip Street, Kwun Tong, Kowloon, Hong Kong
Manufacturer:	MMD Hong Kong Holding Limited
Address of Manufacturer:	Units 1208-11, 12th Floor, C-Bons International Center, 108 Wai Yip Street, Kwun Tong, Kowloon, Hong Kong

1.2 EUT INFORMATION

1.2.1 General Description of EUT

Product Name:	Multimedia Speaker	
Model No./ HVIN:	SPA4000	
Add. Model No.:	SPA4000BK/00, SPA4000BK/98, SPA4000/00, SPA4000BK/61, SPA4000BK/79, SPA4000BK/10, SPA4000BK/12, SPA4000/37, SPA4000BK/37, SPA4000xx/yy(xx=AA-ZZ or Nil for different color; yy=00-99 or Nil, for different country code)	
Trade Mark:	 PHILIPS or	
DUT Stage:	Identical Prototype	
EUT Supports Function: (Provided by the customer)	2.4 GHz ISM Band:	Bluetooth V5.4
Sample Received Date:	November 14, 2025	
Sample Tested Date:	November 17, 2025 to December 2, 2025	
Note: 1. The additional model SPA4000BK/00, SPA4000BK/98, SPA4000/00, SPA4000BK/61, SPA4000BK/79, SPA4000BK/10, SPA4000BK/12, SPA4000/37, SPA4000BK/37, SPA4000xx/yy(xx=AA-ZZ or Nil for different color; yy=00-99 or Nil, for different country code) is identical with the test model SPA4000 except the product color and model number for marketing purpose. 2. The ISED certification is only for the main model.		

Remark: The above EUT's information was provided by customer. Please refer to the specifications or user's manual for more detailed description.

1.2.2 Description of Accessories

Refer to Report 25111520816EMC-1 for accessories.

1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD

Frequency Band:	2400 MHz to 2483.5 MHz
Frequency Range:	2402 MHz to 2480 MHz
Bluetooth Version:	Bluetooth LE/2LE/LE Code
Type of Modulation:	GFSK
Number of Channels:	40
Channel Separation:	2 MHz
Antenna Type:	PCB Antenna
Antenna Gain: (Provided by the customer)	-0.58 dBi
Maximum Peak Power:	-2.23 dBm
Normal Test Voltage:	3.7 Vdc

1.4 OTHER INFORMATION

Operation Frequency Each of Channel	
$f = 2402 + 2k \text{ MHz, } k = 0, \dots, 39$	
Note:	
f	is the operating frequency (MHz);
k	is the operating channel.

1.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested with associated equipment below.

1) Support Equipment

Description	Manufacturer	Model No.	Serial Number	Supplied by
Notebook	DELL	Latitude 3400	16238087894	UnionTrust
Mouse	DELL	MS111	CN-011D3V-738	UnionTrust
AC/DC ADAPTER	KEYU	KA06E-0501000EU	D/C:2035	UnionTrust

2) Support Cable

Cable No.	Description	Connector	Length	Supplied by
1	Antenna Cable	SMA	0.1 Meter	Applicant

1.6 TEST LOCATION

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Telephone: +86 (0) 755 2823 0888

Fax: +86 (0) 755 2823 0886

1.7 TEST FACILITY

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L9069

The measuring equipment utilized to perform the tests documented in this report has been calibrated once a year or in accordance with the manufacturer's recommendations, and is traceable under the ISO/IEC 17025 to international or national standards. Equipment has been calibrated by accredited calibration laboratories.

A2LA-Lab Certificate No.: 4312.01

Shenzhen UnionTrust Quality and Technology Co., Ltd. has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

ISED Wireless Device Testing Laboratories

CAB identifier: CN0032

FCC Accredited Lab.

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1

Designation Number: CN1194
Test Firm Registration Number: 259480

1.8 DEVIATION FROM STANDARDS

None.

1.9 ABNORMALITIES FROM STANDARD CONDITIONS

None.

1.10 OTHER INFORMATION REQUESTED BY THE CUSTOMER

None.

1.11 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

No.	Item	Measurement Uncertainty
1	Conducted emission 9kHz-150kHz	±3.2 dB
2	Conducted emission 150kHz-30MHz	±2.7 dB
3	Radiated emission 9kHz-30MHz	± 4.7 dB
4	Radiated emission 30MHz-1GHz	± 4.9 dB
5	Radiated emission 1GHz-18GHz	± 4.8 dB
6	Radiated emission 18GHz-26GHz	± 5.1 dB
7	Radiated emission 26GHz-40GHz	± 5.1 dB
8	Conducted spurious emissions	± 2.7 dB
9	RF Power, Conducted	± 0.68 dB
10	Occupied Bandwidth	± 1.86 %
11	Radio Frequency	2.4 GHz: ± 6.5 × 10 ⁻⁸
12	Transmission Time	± 0.19 %

2. TEST SUMMARY

Test Cases			
Test Item	Test Requirement	Test Method	Result
Antenna Requirement	FCC 47 CFR Part 15 Subpart C Section 15.203/15.247 (b)(4) RSS-Gen Issue 5, Section 6.8	N/A	PASS
AC Power Line Conducted Emission	FCC 47 CFR Part 15 Subpart C Section 15.207 RSS-Gen Issue 5, Section 8.8	ANSI C63.10-2020+COR. 1-2023+C63.10A-2024 + ERRATA TO C63.10A-2024 Clause 6.2	PASS
Conducted Output Power and E.I.R.P	FCC 47 CFR Part 15 Subpart C Section 15.247 (b)(3) RSS-247 Issue 4, Section 6.3.2	ANSI C63.10-2020+COR. 1-2023+C63.10A-2024 + ERRATA TO C63.10A-2024 Clause 11.9.1.2	PASS
6dB Bandwidth	FCC 47 CFR Part 15 Subpart C Section 15.247 (a)(2) RSS-247 Issue 4, Section 6.3.1	ANSI C63.10-2020+COR. 1-2023+C63.10A-2024 + ERRATA TO C63.10A-2024 Clause 11.8.1	PASS
Occupied Bandwidth	RSS-Gen Issue 5, Section 6.7	RSS-Gen Issue 5, Section 6.7	PASS
Power Spectral Density	FCC 47 CFR Part 15 Subpart C Section 15.247 (e) RSS-247 Issue 4, Section 6.3.1	ANSI C63.10-2020+COR. 1-2023+C63.10A-2024 + ERRATA TO C63.10A-2024 Clause 11.10.2	PASS
Conducted Out of Band Emission	FCC 47 CFR Part 15 Subpart C Section 15.247(d) RSS-247 Issue 4, Section 6.6	ANSI C63.10-2020+COR. 1-2023+C63.10A-2024 + ERRATA TO C63.10A-2024 Clause 11.11	PASS
Radiated Spurious Emissions	FCC 47 CFR Part 15 Subpart C Section 15.205/15.209 RSS-Gen Issue 5, Section 6.13/8.9/8.10	ANSI C63.10-2020+COR. 1-2023+C63.10A-2024 + ERRATA TO C63.10A-2024 Clause 11.11 & Clause 11.12	PASS
Band Edge Measurements (Radiated)	FCC 47 CFR Part 15 Subpart C Section 15.205/15.209 RSS-247 Issue 4, Section 5.5	ANSI C63.10-2020+COR. 1-2023+C63.10A-2024 + ERRATA TO C63.10A-2024 Clause 11.13	PASS
Disclaimer and Explanations: The declared of product specification and data (e.g. antenna gain, RF specification, etc) for EUT presented in the report are provided by the customer, and the customer takes all the responsibilities for the accuracy of product specification.			

3. EQUIPMENT LIST

Radiated Emission Test Equipment List						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date	Cal. Due date
☒	3m SAC	ETS-LINDGREN	3M	Euroshiedpn-CT001270-1317	11-Nov-2023	10-Nov-2026
☒	Receiver	R&S	ESIB26	100114	24-Oct-2025	23-Oct-2026
☒	EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY51440197	28-Mar-2025	27-Mar-2026
☒	Loop Antenna	ETS-LINDGREN	6502	00202525	26-Oct-2025	25-Oct-2026
☒	Broadband Antenna	ETS-LINDGREN	3142E	00201566	27-Mar-2025	28-Mar-2026
☒	6dB Attenuator	Talent	RA6A5-N-18	18103001	24-Oct-2025	23-Oct-2026
☒	Preamplifier	HP	8447F	2805A02960	24-Oct-2025	23-Oct-2026
☒	Double-Ridged Waveguide Horn Antenna (Pre-amplifier)	ETS-LINDGREN	3116C-PA	00202652	24-Oct-2025	23-Oct-2026
☒	Pre-amplifier	ETS-Lindgren	00118384	00202652	24-Oct-2025	23-Oct-2026
☒	Double-Ridged Waveguide Horn Antenna (Pre-amplifier)	ETS-LINDGREN	3117-PA	00201541	29-Mar-2025	28-Mar-2026
☒	Pre-amplifier	ETS-Lindgren	00118385	00201874	28-Mar-2025	27-Mar-2026
☒	Band Reject Filter (2400MHz~2500MHz)	Micro-Tronics	BRM50702	G590	21-Feb-2025	20-Feb-2026
☒	Multi device Controller	ETS-LINDGREN	7006-001	00160105	N/A	N/A
☒	Test Software	Audix	e3	Software Version: 9.160323		

Conducted Emission Test Equipment List						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date	Cal. Due date
☒	Receiver	R&S	ESC13	1166.5950.03	24-Oct-2025	23-Oct-2026
☒	LISN	R&S	EVN216	3560.6550.12	26-Sep-2025	25-Sep-2026
☐	LISN	ETS-Lindgren	3816/2SH	00201088	24-Oct-2025	23-Oct-2026
☒	Test Software	EZ-EMC	EZ-CON	Software Version: EMC-CON 3A1.1		

Conducted RF test Equipment List						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date	Cal. Due date
☒	Spectrum Analyzer	KEYSIGHT	N9020A	MY51286807	24-Oct-2025	23-Oct-2026
☒	USB Wideband Power Sensor	KEYSIGHT	U2021XA	MY55430035	24-Oct-2025	23-Oct-2026
☐	MXG X-Series RF Vector Signal Generator	KEYSIGHT	N5182B	MY51350267	24-Oct-2025	23-Oct-2026

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1

4. TEST CONFIGURATION

4.1 ENVIRONMENTAL CONDITIONS FOR TESTING

4.1.1 Normal or Extreme Test Conditions

Environment Parameter	Selected Values During Tests		
Test Condition	Ambient		
	Temperature (°C)	Voltage (V)	Relative Humidity (%)
NT/NV	+15 to +35	3.7	20 to 75
Remark: 1) NV: Normal Voltage; NT: Normal Temperature			

4.1.2 Record of Normal Environment and Test Sample

Test Item	Temperature (°C)	Relative Humidity (%)	Pressure (kPa)	Sample No.	Tested by
AC Power Line Conducted Emission	23.5	51.1	100.8	S202511147180-ZJA04/7	Fire Huo
Conducted Output Power and E.I.R.P	21.7	38.2	101.7	S202511147180-ZJA06/7	David Du
6dB Bandwidth & Occupied Bandwidth					
Power Spectral Density					
Conducted Out of Band Emission	23.1	60.1	100.3	S202511147180-ZJA05/7	Leo Li
Radiated Spurious Emissions					
Band Edge Measurements (Radiated)					

4.2 TEST CHANNELS

Type of Modulation	Tx/Rx Frequency	Test RF Channel Lists		
GFSK	2402 MHz to 2480 MHz	Lowest(L)	Middle(M)	Highest(H)
		Channel 0	Channel 19	Channel 39
		2402 MHz	2440 MHz	2480 MHz

4.3 EUT TEST STATUS

Type of Modulation	Tx Function	Description
GFSK	1Tx	1. Keep the EUT in continuously transmitting with modulation test single.

Power Setting(Provided by the customer)

Power Setting: Default

Test Software(Provided by the customer)

Test software name: FCC Assist 1.0.2.2

4.4 TEST SETUP

4.4.1 For Radiated Emissions test setup




Figure 1. Below 30MHz







Figure 2. 30MHz to 1GHz



4.4.2 For Conducted Emissions test setup



4.4.3 For Conducted RF test setup



4.5 SYSTEM TEST CONFIGURATION

For emissions testing, the equipment under test (EUT) setup to transmit continuously to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing. During testing, radiated emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario. Only the worst case data were recorded in this test report.

The signal is maximized through rotation and placement in the three orthogonal axes. The antenna height and polarization are varied during the search for maximum signal level. The antenna height is varied from 1 to 4 meters. Radiated emissions are taken at three meters unless the signal level is too low for measurement at that distance. If necessary, a pre-amplifier is used and/or the test is conducted at a closer distance. Therefore, all final radiated testing was performed with the EUT in (see table below) orientation.

Frequency	Mode	Antenna Port	Worst-case axis positioning
Above 1GHz	1TX	Chain 0	Z axis

All readings are extrapolated back to the equivalent three meter reading using inverse scaling with distance. Analyzer resolution is 100 kHz or greater for frequencies below 1000 MHz. The resolution is 1 MHz or greater for frequencies above 1000 MHz. The spurious emissions more than 20 dB below the permissible value are not reported.

Radiated emission measurement were performed from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

4.6 DUTY CYCLE

Test Procedure: ANSI C63.10-2020+COR. 1-2023+C63.10A-2024 + ERRATA TO C63.10A-2024 Clause 11.6.


Test Results


Test Mode	Antenna	Frequency [MHz]	ON Time [ms]	Period [ms]	Duty Cycle [%]	Duty Cycle Factor [dB]
BLE_1M	Ant1	2402	2.13	2.50	85.20	0.70
BLE_2M	Ant1	2402	1.06	2.49	42.57	3.71
BLE_125K	Ant1	2402	17.01	17.50	97.20	0.12
BLE_500K	Ant1	2402	17.01	17.50	97.20	0.12


Remark:

- 1) Duty cycle= On Time/ Period;
- 2) Duty Cycle factor = $10 * \log(1/\text{Duty cycle})$;
- 3) Average factor = $20 \log_{10} \text{Duty Cycle}$.

The test plot as follows







Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China
Tel: +86-755-28230888 Fax: +86-755-28230886 E-mail: info@uttlab.com <http://www.uttlab.com>
UTTR-RF-RSS247-V1.1

5. RADIO TECHNICAL REQUIREMENTS SPECIFICATION

5.1 REFERENCE DOCUMENTS FOR TESTING

No.	Identity	Document Title
1	FCC 47 CFR Part 2	Frequency allocations and radio treaty matters; general rules and regulations
2	FCC 47 CFR Part 15	Radio Frequency Devices
3	RSS-247 Issue 4	Digital Transmission Systems, Frequency Hopping Systems and Licence-Exempt Local Area Network Devices in 902-928 MHz, 2400-2483.5 MHz, 5150-5350 MHz, and 5470-5895 MHz bands
4	RSS-Gen Issue 5	General Requirements for Compliance of Radio Apparatus
5	ANSI C63.10-2020+COR. 1-2023+C63.10A-2024 + ERRATA TO C63.10A-2024	American National Standard for Testing Unlicensed Wireless Devices
6	KDB 558074 D01 15.247 Meas Guidance v05r02	Guidance for compliance measurements on Digital Transmission Systems, Frequency Hopping Spread Spectrum system, and Hybrid system devices operating under Section 15.247 of the FCC rules

5.2 ANTENNA REQUIREMENT

Standard Requirement
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(b) (4) requirement: The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi. RSS-Gen Issue 5, Section 6.8 requirement: According to RSS-Gen Issue 5, Section 6.8, a transmitter can only be sold or operated with antennas with which it was certified. A transmitter may be certified with multiple antenna types. An antenna type comprises antennas having similar in-band and out-of-band radiation patterns. EUT Antenna: Antenna in the interior of the equipment and no consideration of replacement. The gain of the antenna is -0.58 dBi.

5.3 CONDUCTED OUTPUT POWER AND E.I.R.P

Test Requirement:	FCC 47 CFR Part 15 Subpart C Section 15.247 (b)(3) RSS-247 Issue 4, Section 6.3.2
Test Method:	ANSI C63.10-2020+COR. 1-2023+C63.10A-2024 + ERRATA TO C63.10A-2024 Clause 11.9.1.3
Limit:	For DTSSs employing digital modulation techniques operating in the band 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1W.
Test Procedure:	1. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the power meter. 2. Measure out each test modes' peak or average output power, record the power level. Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.
Test Setup:	Refer to section 4.4.3 for details.
Instruments Used:	Refer to section 3 for details
Test Results:	Please refer to Appendix A

Note:

1. The antenna gain of -0.58 dBi less than 6dBi maximum permission antenna gain value based on 1 watt peak output power limit.
2. The maximum EIRP is calculated from max output power and antenna gain, the antenna gain provided by the customer, and the customer takes all the responsibilities for the accuracy of antenna gain.

5.46 DB BANDWIDTH & OCCUPIED BANDWIDTH

Test Requirement:	FCC 47 CFR Part 15 Subpart C Section 15.247 (a)(2) RSS-247 Issue 4, Section 6.3.1 RSS-Gen Issue 5, Section 6.7 ANSI C63.10-2020+COR. 1-2023+C63.10A-2024 + ERRATA TO C63.10A-2024
Test Method:	Clause 11.8.1 RSS-Gen Issue 5, Section 6.7
Limit:	For digital transmission systems, the minimum 6 dB bandwidth shall be 500 kHz.
Test Procedure:	Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer. Use the following spectrum analyzer settings:

6dB Bandwidth

- Set RBW = 100 kHz.
- Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Allow the trace to stabilize.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Occupied Bandwidth

- Set RBW = 1% to 5% of the occupied bandwidth
- Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Allow the trace to stabilize.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

Test Setup:	Refer to section 4.4.3 for details.
Instruments Used:	Refer to section 3 for details
Test Mode:	Link mode
Test Results:	Please refer to Appendix A

5.5 POWER SPECTRAL DENSITY

Test Requirement:	FCC 47 CFR Part 15 Subpart C Section 15.247 (e) RSS-247 Issue 4, Section 6.3.1
Test Method:	ANSI C63.10-2020+COR. 1-2023+C63.10A-2024 + ERRATA TO C63.10A-2024 Clause 11.10.2
Limit:	For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.
Test Procedure:	Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer. Use the following spectrum analyzer settings: a) Set analyzer center frequency to DTS channel center frequency. b) Set the span to 1.5 times the DTS bandwidth. c) Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$. d) Set the VBW $\geq 3 \times \text{RBW}$. e) Detector = peak. f) Sweep time = auto couple. g) Trace mode = max hold. h) Allow trace to fully stabilize. i) Use the peak marker function to determine the maximum amplitude level within the RBW. j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat. Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.
Test Setup:	Refer to section 4.4.3 for details.
Instruments Used:	Refer to section 3 for details
Test Mode:	Link mode
Test Results:	Please refer to Appendix A

5.6 CONDUCTED OUT OF BAND EMISSION

Test Requirement:	FCC 47 CFR Part 15 Subpart C Section 15.247(d) RSS-247 Issue 2, Section 6.6
Test Method:	ANSI C63.10-2020+COR. 1-2023+C63.10A-2024 + ERRATA TO C63.10A-2024 Clause 11.11
Limit:	In any 100kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.
Test Procedure:	Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer. Use the following spectrum analyzer settings: Step 1: Reference level measurement - Set instrument center frequency to DTS channel center frequency. - Set the span to ≥ 1.5 times the DTS bandwidth. - Set the RBW = 100 kHz. - Set the VBW $\geq 3 \times$ RBW. - Detector = peak. - Sweep time = auto couple. - Trace mode = max hold. - Allow trace to fully stabilize. - Use the peak marker function to determine the maximum PSD level. Note that the channel found to contain the maximum PSD level can be used to establish the reference level. Step 2: Emission level measurement - Set RBW = 100 kHz. - Set VBW ≥ 300 kHz. - Detector = peak. - Sweep = auto couple. - Trace Mode = max hold. - Allow trace to fully stabilize. - Use the peak marker function to determine the maximum amplitude level. Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.
Test Setup:	Refer to section 4.4.3 for details.
Instruments Used:	Refer to section 3 for details
Test Mode:	Link mode
Test Results:	Please refer to Appendix A

5.7 RADIATED SPURIOUS EMISSIONS

Test Requirement: FCC 47 CFR Part 15 Subpart C Section 15.205/15.209
RSS-Gen Issue 5, Section 6.13/8.9/8.10

Test Method: ANSI C63.10-2020+COR. 1-2023+C63.10A-2024 + ERRATA TO C63.10A-2024
Clause 11.11 & Clause 11.12

Receiver Setup:

Frequency	RBW
0.009 MHz-0.150 MHz	200/300 kHz
0.150 MHz -30 MHz	9/10 kHz
30 MHz-1 GHz	100/120 kHz
Above 1 GHz	1 MHz

Limits:

Spurious Emissions

Frequency	Field strength (microvolt/meter)	Limit (dBμV/m)	Remark	Measurement distance (m)
0.009 MHz-0.490 MHz	2400/F(kHz)	--	--	300
0.490 MHz-1.705 MHz	24000/F(kHz)	--	--	30
1.705 MHz-30 MHz	30	--	--	30
30 MHz-88 MHz	100	40.0	Quasi-peak	3
88 MHz-216 MHz	150	43.5	Quasi-peak	3
216 MHz-960 MHz	200	46.0	Quasi-peak	3
960MHz-1GHz	500	54.0	Quasi-peak	3
Above 1 GHz	500	54.0	Average	3

Remark:

- The lower limit shall apply at the transition frequencies.
- Emission level (dBuV/m) = 20 log Emission level (uV/m).
- For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

Test Setup: Refer to section 4.4.1 for details.

Test Procedures:

- From 30 MHz to 1GHz test procedure as below:
 - The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
 - The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
 - The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
 - For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rota table table was turned from 0 degrees to 360 degrees to find the maximum reading.
 - The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
 - If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- Above 1GHz test procedure as below:
 - Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 meter to 1.5 meter(Above 18GHz the distance is 1 meter and table

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1

is 1.5 meter).

- 2) Test the EUT in the lowest channel ,middle channel, the Highest channel
- 3) The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the Z axis positioning which it is worse case.
- 4) Repeat above procedures until all frequencies measured was complete.

Equipment Used: Refer to section 3 for details.

Test Result: Pass

The measurement data as follows:


Radiated Emission Test Data (9 KHz ~ 30 MHz):

The amplitude of spurious emissions attenuated more than 20 dB below the permissible value need not be reported.


Radiated Emission Test Data (30 MHz ~ 1 GHz):

Worst-Case Configuration

Horizontal



No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.000	26.86	-4.08	22.78	40.00	-17.22	QP
2	36.014	28.89	-6.72	22.17	40.00	-17.83	QP
3	50.461	35.86	-13.75	22.11	40.00	-17.89	QP
4	235.135	34.51	-10.73	23.78	46.00	-22.22	QP
5	313.648	39.91	-8.46	31.45	46.00	-14.55	QP
6	615.774	35.17	-0.37	34.80	46.00	-11.20	QP



Radiated Emission Test Data (Above 1GHz):								
No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
BLE_2402 MHz 4804 MHz 7206 MHz								
1	4804	33.84	-2.08	31.76	54.00	-22.24	Average	Horizontal
2	4804	56.68	-2.08	54.60	74.00	-19.40	Peak	Horizontal
3	7206	34.59	1.30	35.89	54.00	-18.11	Average	Horizontal
4	7206	56.91	1.30	58.21	74.00	-15.79	Peak	Horizontal
5	4804	37.35	-2.08	35.27	54.00	-18.73	Average	Vertical
6	4804	55.10	-2.08	53.02	74.00	-20.98	Peak	Vertical
7	7206	38.93	1.30	40.23	54.00	-13.77	Average	Vertical
8	7206	55.18	1.30	56.48	74.00	-17.52	Peak	Vertical
BLE_2440 MHz 4880 MHz 7320 MHz								
1	4880	38.35	-2.05	36.30	54.00	-17.70	Average	Horizontal
2	4880	59.00	-2.05	56.95	74.00	-17.05	Peak	Horizontal
3	7320	38.09	1.31	39.40	54.00	-14.60	Average	Horizontal
4	7320	53.95	1.31	55.26	74.00	-18.74	Peak	Horizontal
5	4880	33.42	-2.05	31.37	54.00	-22.63	Average	Vertical
6	4880	56.99	-2.05	54.94	74.00	-19.06	Peak	Vertical
7	7320	33.86	1.31	35.17	54.00	-18.83	Average	Vertical
8	7320	60.30	1.31	61.61	74.00	-12.39	Peak	Vertical
BLE_2480 MHz 4960 MHz 7440 MHz								
1	4960	36.63	-2.02	34.61	54.00	-19.39	Average	Horizontal
2	4960	52.77	-2.02	50.75	74.00	-23.25	Peak	Horizontal
3	7440	34.99	1.32	36.31	54.00	-17.69	Average	Horizontal
4	7440	52.83	1.32	54.15	74.00	-19.85	Peak	Horizontal
5	4960	39.34	-2.02	37.32	54.00	-16.68	Average	Vertical
6	4960	58.88	-2.02	56.86	74.00	-17.14	Peak	Vertical
7	7440	35.96	1.32	37.28	54.00	-16.72	Average	Vertical
8	7440	54.25	1.32	55.57	74.00	-18.43	Peak	Vertical
2BLE_2402 MHz 4804 MHz 7206 MHz								
1	4804	38.18	-2.08	36.10	54.00	-17.90	Average	Horizontal
2	4804	56.83	-2.08	54.75	74.00	-19.25	Peak	Horizontal
3	7206	37.63	1.30	38.93	54.00	-15.07	Average	Horizontal
4	7206	53.87	1.30	55.17	74.00	-18.83	Peak	Horizontal
5	4804	34.21	-2.08	32.13	54.00	-21.87	Average	Vertical
6	4804	54.97	-2.08	52.89	74.00	-21.11	Peak	Vertical
7	7206	37.95	1.30	39.25	54.00	-14.75	Average	Vertical
8	7206	54.18	1.30	55.48	74.00	-18.52	Peak	Vertical
2BLE_2440 MHz 4880 MHz 7320 MHz								
1	4880	37.48	-2.05	35.43	54.00	-18.57	Average	Horizontal
2	4880	61.39	-2.05	59.34	74.00	-14.66	Peak	Horizontal
3	7320	38.23	1.31	39.54	54.00	-14.46	Average	Horizontal
4	7320	63.23	1.31	64.54	74.00	-9.46	Peak	Horizontal
5	4880	33.10	-2.05	31.05	54.00	-22.95	Average	Vertical
6	4880	56.36	-2.05	54.31	74.00	-19.69	Peak	Vertical
7	7320	34.21	1.31	35.52	54.00	-18.48	Average	Vertical
8	7320	56.63	1.31	57.94	74.00	-16.06	Peak	Vertical
2BLE_2480 MHz 4960 MHz 7440 MHz								
1	4960	36.45	-2.02	34.43	54.00	-19.57	Average	Horizontal
2	4960	52.41	-2.02	50.39	74.00	-23.61	Peak	Horizontal
3	7440	35.19	1.32	36.51	54.00	-17.49	Average	Horizontal
4	7440	52.43	1.32	53.75	74.00	-20.25	Peak	Horizontal
5	4960	33.80	-2.02	31.78	54.00	-22.22	Average	Vertical
6	4960	54.96	-2.02	52.94	74.00	-21.06	Peak	Vertical
7	7440	33.86	1.32	35.18	54.00	-18.82	Average	Vertical

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1

8	7440	51.90	1.32	53.22	74.00	-20.78	Peak	Vertical
BLE_S=2 2402 MHz 4804 MHz 7206 MHz								
1	4804	33.98	-2.08	31.90	54.00	-22.10	Average	Horizontal
2	4804	56.35	-2.08	54.27	74.00	-19.73	Peak	Horizontal
3	7206	34.53	1.30	35.83	54.00	-18.17	Average	Horizontal
4	7206	53.99	1.30	55.29	74.00	-18.71	Peak	Horizontal
5	4804	37.72	-2.08	35.64	54.00	-18.36	Average	Vertical
6	4804	54.88	-2.08	52.80	74.00	-21.20	Peak	Vertical
7	7206	39.36	1.30	40.66	54.00	-13.34	Average	Vertical
8	7206	53.89	1.30	55.19	74.00	-18.81	Peak	Vertical
BLE_S=2 2440 MHz 4880 MHz 7320 MHz								
1	4880	39.29	-2.05	37.24	54.00	-16.76	Average	Horizontal
2	4880	61.13	-2.05	59.08	74.00	-14.92	Peak	Horizontal
3	7320	34.18	1.31	35.49	54.00	-18.51	Average	Horizontal
4	7320	63.70	1.31	65.01	74.00	-8.99	Peak	Horizontal
5	4880	37.54	-2.05	35.49	54.00	-18.51	Average	Vertical
6	4880	56.84	-2.05	54.79	74.00	-19.21	Peak	Vertical
7	7320	37.01	1.31	38.32	54.00	-15.68	Average	Vertical
8	7320	56.80	1.31	58.11	74.00	-15.89	Peak	Vertical
BLE_S=2 2480 MHz 4960 MHz 7440 MHz								
1	4960	36.56	-2.02	34.54	54.00	-19.46	Average	Horizontal
2	4960	53.88	-2.02	51.86	74.00	-22.14	Peak	Horizontal
3	7440	35.29	1.32	36.61	54.00	-17.39	Average	Horizontal
4	7440	53.97	1.32	55.29	74.00	-18.71	Peak	Horizontal
5	4960	39.40	-2.02	37.38	54.00	-16.62	Average	Vertical
6	4960	58.72	-2.02	56.70	74.00	-17.30	Peak	Vertical
7	7440	35.80	1.32	37.12	54.00	-16.88	Average	Vertical
8	7440	54.74	1.32	56.06	74.00	-17.94	Peak	Vertical
BLE_S=8 2402 MHz 4804 MHz 7206 MHz								
1	4804	38.78	-2.08	36.70	54.00	-17.30	Average	Horizontal
2	4804	57.06	-2.08	54.98	74.00	-19.02	Peak	Horizontal
3	7206	37.40	1.30	38.70	54.00	-15.30	Average	Horizontal
4	7206	53.75	1.30	55.05	74.00	-18.95	Peak	Horizontal
5	4804	33.86	-2.08	31.78	54.00	-22.22	Average	Vertical
6	4804	55.07	-2.08	52.99	74.00	-21.01	Peak	Vertical
7	7206	39.22	1.30	40.52	54.00	-13.48	Average	Vertical
8	7206	54.52	1.30	55.82	74.00	-18.18	Peak	Vertical
BLE_S=8 2440 MHz 4880 MHz 7320 MHz								
1	4880	39.81	-2.05	37.76	54.00	-16.24	Average	Horizontal
2	4880	58.26	-2.05	56.21	74.00	-17.79	Peak	Horizontal
3	7320	33.86	1.31	35.17	54.00	-18.83	Average	Horizontal
4	7320	47.81	1.31	49.12	74.00	-24.88	Peak	Horizontal
5	4804	33.86	-2.08	31.78	54.00	-22.22	Average	Vertical
6	4880	56.64	-2.05	54.59	74.00	-19.41	Peak	Vertical
7	7206	39.22	1.30	40.52	54.00	-13.48	Average	Vertical
8	7320	52.95	1.31	54.26	74.00	-19.74	Peak	Vertical
BLE_S=8 2480 MHz 4960 MHz 7440 MHz								
1	4960	39.89	-2.02	37.87	54.00	-16.13	Average	Horizontal
2	4960	47.87	-2.02	45.85	74.00	-28.15	Peak	Horizontal
3	7440	37.54	1.32	38.86	54.00	-15.14	Average	Horizontal
4	7440	58.21	1.32	59.53	74.00	-14.47	Peak	Horizontal
5	4960	38.57	-2.02	36.55	54.00	-17.45	Average	Vertical
6	4960	55.99	-2.02	53.97	74.00	-20.03	Peak	Vertical
7	7440	36.08	1.32	37.40	54.00	-16.60	Average	Vertical
8	7440	54.34	1.32	55.66	74.00	-18.34	Peak	Vertical

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1

Remark:

1. Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain, the value was added to Original Receiver Reading by the software automatically.
2. Result = Reading + Correct Factor.
3. Margin = Result – Limit



5.8 BAND EDGE MEASUREMENTS (RADIATED)

Test Requirement: FCC 47 CFR Part 15 Subpart C Section 15.205/15.209
RSS-247 Issue 4, Section 6.6

Test Method: ANSI C63.10-2020+COR. 1-2023+C63.10A-2024 + ERRATA TO C63.10A-2024
Clause 11.12

Limits:

Radiated emissions which fall in the restricted bands, as defined in section 15.205(a), must also comply with the radiated emission limits specified in section 15.209(a).

Frequency	Limit (dBμV/m @3m)	Remark
30 MHz-88 MHz	40.0	Quasi-peak Value
88 MHz-216 MHz	43.5	Quasi-peak Value
216 MHz-960 MHz	46.0	Quasi-peak Value
960 MHz-1 GHz	54.0	Quasi-peak Value
Above 1 GHz	54.0	Average Value
	74.0	Peak Value

Test Setup: Refer to section 4.4.1 for details.

Test Procedures:



Radiated band edge measurements at 2390 MHz and 2483.5 MHz were made with the unit transmitting in the low end of the channel range and the high end closest to the restricted bands respectively. The emissions were made on the 966 Semi-Chamber. Use (resolution bandwidth (RBW) = 1 MHz, video bandwidth (VBW) = 3 MHz for peak levels and RBW = 1 MHz and VBW = 10 Hz or 1/T for average levels).



1. Use radiated spurious emission test procedure described in clause 5.10. The transmitter output (antenna port) was connected to the test receiver.
2. Set the PK and AV limit line.
3. Record the fundamental emission and emissions out of the band-edge.
4. Determine band-edge compliance as required.



Equipment Used: Refer to section 3 for details.



Test Result: Pass



The measurement data as follows:















Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China



Tel: +86-755-28230888



Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1





5.9 CONDUCTED EMISSION

Test Requirement: 47 CFR Part 15C Section 15.207
RSS-Gen Issue 5, Section 8.8
Test Method: ANSI C63.10-2020+COR. 1-2023+C63.10A-2024 + ERRATA TO C63.10A-2024
Section 6.2

Limits:

Frequency range (MHz)	Limits (dB(μV))	
	Quasi-peak	Average
0,15 to 0,50	66 to 56	56 to 46
0,50 to 5	56	46
5 to 30	60	50

Remark:

1. The lower limit shall apply at the transition frequencies.
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 to 0.50 MHz.

Test Setup: Refer to section 4.4.2 for details.

Test Procedures:

Test frequency range :150KHz-30MHz

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50Ω/50μH + 5Ω linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Equipment Used: Refer to section 3 for details.


Test Result: Pass

The worst measurement data as follows:

Quasi Peak and Average:

Mode: BT Link

Live Line



No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.3480	34.59	9.77	44.36	59.01	-14.65	QP
2	0.3480	24.06	9.77	33.83	49.01	-15.18	AVG
3	0.4334	43.47	9.79	53.26	57.19	-3.93	QP
4	0.4334	32.13	9.79	41.92	47.19	-5.27	AVG
5	0.8745	35.62	9.71	45.33	56.00	-10.67	QP
6	0.8745	23.15	9.71	32.86	46.00	-13.14	AVG
7	1.0680	34.44	9.71	44.15	56.00	-11.85	QP
8	1.0680	23.28	9.71	32.99	46.00	-13.01	AVG
9	2.0985	34.85	9.72	44.57	56.00	-11.43	QP
10	2.0985	23.45	9.72	33.17	46.00	-12.83	AVG
11	3.1740	34.20	9.73	43.93	56.00	-12.07	QP
12	3.1740	22.91	9.73	32.64	46.00	-13.36	AVG

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1

Neutral Line



No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.3480	26.37	9.75	36.12	59.01	-22.89	QP
2	0.3480	13.23	9.75	22.98	49.01	-26.03	AVG
3	0.4334	37.21	9.78	46.99	57.19	-10.20	QP
4	0.4334	24.48	9.78	34.26	47.19	-12.93	AVG
5	0.8610	29.57	9.74	39.31	56.00	-16.69	QP
6	0.8610	16.76	9.74	26.50	46.00	-19.50	AVG
7	1.0680	27.63	9.75	37.38	56.00	-18.62	QP
8	1.0680	17.55	9.75	27.30	46.00	-18.70	AVG
9	2.0985	26.92	9.75	36.67	56.00	-19.33	QP
10	2.0985	16.67	9.75	26.42	46.00	-19.58	AVG
11	3.1110	25.43	9.75	35.18	56.00	-20.82	QP
12	3.1110	15.94	9.75	25.69	46.00	-20.31	AVG

Remark:

1. Correct Factor = LISN Factor + Cable Loss + Pulse Limiter Factor, the value was added to Original Receiver Reading by the software automatically.
2. Result = Reading + Correct Factor.
3. Margin = Result - Limit
4. An initial pre-scan was performed on the Phase and neutral lines with peak detector. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.

APPENDIX A RF TEST DATA

A.1 MAXIMUM CONDUCTED OUTPUT POWER AND E.I.R.P


Test Result Peak.

Test Mode	Antenna	Frequency [MHz]	POWER SETTING	Conducted Peak Power [dBm]	Conducted Limit [dBm]	Gain [dBi]	EIRP [dBm]	EIRP Limit [dBm]	Verdict
BLE 1M	Ant1	2402	NA	-2.71	≤30	-0.58	-3.29	≤36	PASS
BLE 1M	Ant1	2440	NA	-2.36	≤30	-0.58	-2.94	≤36	PASS
BLE 1M	Ant1	2480	NA	-2.32	≤30	-0.58	-2.90	≤36	PASS
BLE 2M	Ant1	2402	NA	-2.61	≤30	-0.58	-3.19	≤36	PASS
BLE 2M	Ant1	2440	NA	-2.28	≤30	-0.58	-2.86	≤36	PASS
BLE 2M	Ant1	2480	NA	-2.37	≤30	-0.58	-2.95	≤36	PASS
BLE 125K	Ant1	2402	NA	-2.68	≤30	-0.58	-3.26	≤36	PASS
BLE 125K	Ant1	2440	NA	-2.34	≤30	-0.58	-2.92	≤36	PASS
BLE 125K	Ant1	2480	NA	-2.35	≤30	-0.58	-2.93	≤36	PASS
BLE 500K	Ant1	2402	NA	-2.65	≤30	-0.58	-3.23	≤36	PASS
BLE 500K	Ant1	2440	NA	-2.23	≤30	-0.58	-2.81	≤36	PASS
BLE 500K	Ant1	2480	NA	-2.39	≤30	-0.58	-2.97	≤36	PASS

Test Result Average.

Test Mode	Ant	Freq [MHz]	Set Power	Result [dBm]	Limit [dBm]	Gain [dBi]	EIRP [dBm]	EIRP Limit [dBm]	Verdict
BLE 1M	Ant1	2402	NA	-3.81	≤30.00	-0.58	-4.39	≤36.00	PASS
BLE 1M	Ant1	2440	NA	-3.15	≤30.00	-0.58	-3.73	≤36.00	PASS
BLE 1M	Ant1	2480	NA	-2.86	≤30.00	-0.58	-3.44	≤36.00	PASS
BLE 2M	Ant1	2402	NA	-3.76	≤30.00	-0.58	-4.34	≤36.00	PASS
BLE 2M	Ant1	2440	NA	-3.07	≤30.00	-0.58	-3.65	≤36.00	PASS
BLE 2M	Ant1	2480	NA	-2.77	≤30.00	-0.58	-3.35	≤36.00	PASS
BLE 125K	Ant1	2402	NA	-3.79	≤30.00	-0.58	-4.37	≤36.00	PASS
BLE 125K	Ant1	2440	NA	-3.15	≤30.00	-0.58	-3.73	≤36.00	PASS
BLE 125K	Ant1	2480	NA	-2.85	≤30.00	-0.58	-3.43	≤36.00	PASS
BLE 500K	Ant1	2402	NA	-3.81	≤30.00	-0.58	-4.39	≤36.00	PASS
BLE 500K	Ant1	2440	NA	-3.15	≤30.00	-0.58	-3.73	≤36.00	PASS
BLE 500K	Ant1	2480	NA	-2.85	≤30.00	-0.58	-3.43	≤36.00	PASS

Test Graphs



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China


Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China


Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China


Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China


Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China


Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com


<http://www.uttlab.com>


UTTR-RF-RSS247-V1.1

A.2 6DB BANDWIDTH

Test Mode	Antenna	Frequency [MHz]	DTS BW [MHz]	Limit [MHz]	Verdict
BLE_1M	Ant1	2402	0.6635	0.5	PASS
BLE_1M	Ant1	2440	0.6982	0.5	PASS
BLE_1M	Ant1	2480	0.7016	0.5	PASS
BLE_2M	Ant1	2402	1.177	0.5	PASS
BLE_2M	Ant1	2440	1.151	0.5	PASS
BLE_2M	Ant1	2480	1.173	0.5	PASS
BLE_125K	Ant1	2402	0.6461	0.5	PASS
BLE_125K	Ant1	2440	0.6777	0.5	PASS
BLE_125K	Ant1	2480	0.6037	0.5	PASS
BLE_500K	Ant1	2402	0.6729	0.5	PASS
BLE_500K	Ant1	2440	0.6199	0.5	PASS
BLE_500K	Ant1	2480	0.6878	0.5	PASS

Test Graphs



**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China


Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1



**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China


Tel: +86-755-28230888


Fax: +86-755-28230886


E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1







Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com


<http://www.uttlab.com>


UTTR-RF-RSS247-V1.1


A.3 Occupied Channel Bandwidth

TestMode	Antenna	Frequency [MHz]	OCB [MHz]	FL [MHz]	FH [MHz]
BLE_1M	Ant1	2402	1.0406	2401.4999	2402.5405
BLE_1M	Ant1	2440	1.0332	2439.5026	2440.5358
BLE_1M	Ant1	2480	1.0352	2479.5017	2480.5369
BLE_2M	Ant1	2402	2.0904	2400.9910	2403.0814
BLE_2M	Ant1	2440	2.0799	2438.9976	2441.0775
BLE_2M	Ant1	2480	2.0661	2479.0057	2481.0718
BLE_125K	Ant1	2402	1.0591	2401.4868	2402.5459
BLE_125K	Ant1	2440	1.0605	2439.4843	2440.5448
BLE_125K	Ant1	2480	1.0590	2479.4880	2480.5470
BLE_500K	Ant1	2402	1.0600	2401.4889	2402.5489
BLE_500K	Ant1	2440	1.0567	2439.4910	2440.5477
BLE_500K	Ant1	2480	1.0620	2479.4874	2480.5494

Test Graphs





**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China


Tel: +86-755-28230888


Fax: +86-755-28230886


E-mail: info@uttlab.com


<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1











A.4 Maximum power spectral density

Test Mode	Antenna	Frequency [MHz]	Result [dBm/3kHz]	Limit [dBm/3kHz]	Verdict
BLE_1M	Ant1	2402	-18.81	≤8.00	PASS
BLE_1M	Ant1	2440	-18.62	≤8.00	PASS
BLE_1M	Ant1	2480	-18.68	≤8.00	PASS
BLE_2M	Ant1	2402	-22.22	≤8.00	PASS
BLE_2M	Ant1	2440	-21.80	≤8.00	PASS
BLE_2M	Ant1	2480	-21.95	≤8.00	PASS
BLE_125K	Ant1	2402	-8.98	≤8.00	PASS
BLE_125K	Ant1	2440	-8.73	≤8.00	PASS
BLE_125K	Ant1	2480	-8.82	≤8.00	PASS
BLE_500K	Ant1	2402	-8.89	≤8.00	PASS
BLE_500K	Ant1	2440	-8.63	≤8.00	PASS
BLE_500K	Ant1	2480	-8.79	≤8.00	PASS

Test Graphs





Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China


Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China


Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China


Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China


Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China


Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com


<http://www.uttlab.com>


UTTR-RF-RSS247-V1.1


A.5 BAND EDGE MEASUREMENTS

Test Mode	Antenna	Ch Name	Frequency [MHz]	Ref Level [dBm]	Result [dBm]	Limit [dBm]	Verdict
BLE_1M	Ant1	Low	2402	-3.71	-40.5	≤-23.71	PASS
BLE_1M	Ant1	High	2480	-3.42	-46.74	≤-23.42	PASS
BLE_2M	Ant1	Low	2402	-6.67	-38.2	≤-26.67	PASS
BLE_2M	Ant1	High	2480	-5.85	-47.39	≤-25.85	PASS
BLE_125K	Ant1	Low	2402	-5.97	-40.29	≤-25.97	PASS
BLE_125K	Ant1	High	2480	-5.76	-45.11	≤-25.76	PASS
BLE_500K	Ant1	Low	2402	-5.90	-42.33	≤-25.9	PASS
BLE_500K	Ant1	High	2480	-5.82	-47.37	≤-25.82	PASS

Test Graphs







Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China


Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China


Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1




Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China
Tel: +86-755-28230888 Fax: +86-755-28230886 E-mail: info@uttlab.com <http://www.uttlab.com>
UTTR-RF-RSS247-V1.1

A.6 CONDUCTED SPURIOUS EMISSION

Test Mode	Antenna	Frequency [MHz]	Freq Range [MHz]	Ref Level [dBm]	Result [dBm]	Limit [dBm]	Verdict
BLE_1M	Ant1	2402	0~Reference	-4.48	-4.48	---	PASS
BLE_1M	Ant1	2402	30~1000	-4.48	-59.23	≤-24.48	PASS
BLE_1M	Ant1	2402	1000~26500	-4.48	-37.4	≤-24.48	PASS
BLE_1M	Ant1	2440	0~Reference	-4.09	-4.09	---	PASS
BLE_1M	Ant1	2440	30~1000	-4.09	-59.38	≤-24.09	PASS
BLE_1M	Ant1	2440	1000~26500	-4.09	-38.63	≤-24.09	PASS
BLE_1M	Ant1	2480	0~Reference	-4.40	-4.40	---	PASS
BLE_1M	Ant1	2480	30~1000	-4.40	-59.51	≤-24.4	PASS
BLE_1M	Ant1	2480	1000~26500	-4.40	-38.67	≤-24.4	PASS
BLE_2M	Ant1	2402	0~Reference	-6.57	-6.57	---	PASS
BLE_2M	Ant1	2402	30~1000	-6.57	-59.42	≤-26.57	PASS
BLE_2M	Ant1	2402	1000~26500	-6.57	-39.52	≤-26.57	PASS
BLE_2M	Ant1	2440	0~Reference	-6.59	-6.59	---	PASS
BLE_2M	Ant1	2440	30~1000	-6.59	-60.15	≤-26.59	PASS
BLE_2M	Ant1	2440	1000~26500	-6.59	-38.64	≤-26.59	PASS
BLE_2M	Ant1	2480	0~Reference	-4.16	-4.16	---	PASS
BLE_2M	Ant1	2480	30~1000	-4.16	-59.75	≤-24.16	PASS
BLE_2M	Ant1	2480	1000~26500	-4.16	-40.93	≤-24.16	PASS
BLE_125K	Ant1	2402	0~Reference	-6.04	-6.04	---	PASS
BLE_125K	Ant1	2402	30~1000	-6.04	-60.01	≤-26.04	PASS
BLE_125K	Ant1	2402	1000~26500	-6.04	-40.47	≤-26.04	PASS
BLE_125K	Ant1	2440	0~Reference	-5.79	-5.79	---	PASS
BLE_125K	Ant1	2440	30~1000	-5.79	-59.79	≤-25.79	PASS
BLE_125K	Ant1	2440	1000~26500	-5.79	-40.31	≤-25.79	PASS
BLE_125K	Ant1	2480	0~Reference	-5.86	-5.86	---	PASS
BLE_125K	Ant1	2480	30~1000	-5.86	-59.3	≤-25.86	PASS
BLE_125K	Ant1	2480	1000~26500	-5.86	-41.13	≤-25.86	PASS
BLE_500K	Ant1	2402	0~Reference	-6.16	-6.16	---	PASS
BLE_500K	Ant1	2402	30~1000	-6.16	-58.76	≤-26.16	PASS
BLE_500K	Ant1	2402	1000~26500	-6.16	-40.4	≤-26.16	PASS
BLE_500K	Ant1	2440	0~Reference	-5.88	-5.88	---	PASS
BLE_500K	Ant1	2440	30~1000	-5.88	-59.98	≤-25.88	PASS
BLE_500K	Ant1	2440	1000~26500	-5.88	-39.74	≤-25.88	PASS
BLE_500K	Ant1	2480	0~Reference	-5.92	-5.92	---	PASS
BLE_500K	Ant1	2480	30~1000	-5.92	-59.49	≤-25.92	PASS
BLE_500K	Ant1	2480	1000~26500	-5.92	-41.15	≤-25.92	PASS

Test Graphs



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China


Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1





Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1

