FCC Radio Test Report

FCC ID: 2AR2STAB7305

This report concerns: Original Grant

Project No.	:	2005C063A
Equipment	:	Soundbar Speaker
Brand Name	:	PHILIPS or
Test Model	:	TAB7305/10
Series Model	:	TAB7305, B7305, TAB7305/98, TAB7305/67, TAB7305/37, B7305/yy, TAB7305/yy(yy=00-99 or blank,for country code)
Applicant	:	MMD Hong Kong Holding Limited
Address	:	Units 1006-1007, 10th Floor, C-Bons International Center, 108 Wai Yip Street, Kwun Tong, Kowloon, Hong Kong
Manufacturer	:	MMD Hong Kong Holding Limited
Address	:	Units 1006-1007, 10th Floor, C-Bons International Center, 108 Wai Yip Street, Kwun Tong, Kowloon, Hong Kong
Factory	:	Shenzhen 3nod Digital Technology Co., Ltd
Address	:	4/F, And Section A, 1/F, Workshop 15, Zhongfu Road, Tangxiayong Community, Songgang Neighbourhood, Bao'An District, Shenzhen City, Guangdong Province, P.R.C
Date of Receipt	:	May 12, 2020
Date of Test	:	May 13, 2020 ~ Sep. 29, 2020
Issued Date	:	Oct. 26, 2020
Report Version	:	R00
Test Sample	:	Engineering Sample No.:DG2020051283 for conducted, DG2020051284 for radiated.
Standard(s)	:	FCC Part15, Subpart C (15.247) ANSI C63.10-2013 FCC KDB 558074 D01 15.247 Meas Guidance v05r02

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

Vincent. Tan

Prepared by : Vincent Tan

Ethan Ma

Approved by : Ethan Ma

Certificate #5123.02

Add: No.3, Jinshagang 1st Road, Shixia, Dalang Town,Dongguan, Guangdong, China.
Tel: +86-769-8318-3000
Web: www.newbtl.com

Declaration

BTL represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with standards traceable to international standard(s) and/or national standard(s).

BTL's reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **BTL** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **BTL** issued reports.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, A2LA, or any agency of the U.S. Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and ourselves, the test report shall not be reproduced, except in full, without our written approval.

BTL's laboratory quality assurance procedures are in compliance with the **ISO/IEC 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

BTL is not responsible for the sampling stage, so the results only apply to the sample as received.

The information, data and test plan are provided by manufacturer which may affect the validity of results, so it is manufacturer's responsibility to ensure that the apparatus meets the essential requirements of applied standards and in all the possible configurations as representative of its intended use.

Limitation

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.
Please note that the measurement uncertainty is provided for informational purpose only and are not use in determining the Pass/Fail results.

Table of Contents Page

REPORT ISSUED HISTORY 6

1 . SUMMARY OF TEST RESULTS 7

1.1 TEST FACILITY 8

1.2 MEASUREMENT UNCERTAINTY 8

1.3 TEST ENVIRONMENT CONDITIONS 9

2 . GENERAL INFORMATION 10

2.1 GENERAL DESCRIPTION OF EUT 10

2.2 DESCRIPTION OF TEST MODES 12

2.3 PARAMETERS OF TEST SOFTWARE 13

2.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED 14

2.5 SUPPORT UNITS 14

3 . AC POWER LINE CONDUCTED EMISSIONS TEST 15

3.1 LIMIT 15

3.2 TEST PROCEDURE 15

3.3 DEVIATION FROM TEST STANDARD 15

3.4 TEST SETUP 16

3.5 EUT OPERATING CONDITIONS 16

3.6 TEST RESULTS 16

4 . RADIATED EMISSION TEST 17

4.1 LIMIT 17

4.2 TEST PROCEDURE 18

4.3 DEVIATION FROM TEST STANDARD 18

4.4 TEST SETUP 19

4.5 EUT OPERATING CONDITIONS 20

4.6 TEST RESULTS - 9 KHZ TO 30 MHZ 20

4.7 TEST RESULTS - 30 MHZ TO 1000 MHZ 20

4.8 TEST RESULTS - ABOVE 1000 MHZ 20

5 . NUMBER OF HOPPING FREQUENCY 21

5.1 LIMIT 21

5.2 TEST PROCEDURE 21

5.3 DEVIATION FROM STANDARD 21

5.4 TEST SETUP 21

Table of Contents Page

5.5 EUT OPERATION CONDITIONS 21
5.6 TEST RESULTS 21
6 . AVERAGE TIME OF OCCUPANCY 22
6.1 LIMIT 22
6.2 TEST PROCEDURE 22
6.3 DEVIATION FROM STANDARD 22
6.4 TEST SETUP 22
6.5 EUT OPERATION CONDITIONS 22
6.6 TEST RESULTS 22
7 . HOPPING CHANNEL SEPARATION MEASUREMENT 23
7.1 LIMIT 23
7.2 TEST PROCEDURE 23
7.3 DEVIATION FROM STANDARD 23
7.4 TEST SETUP 23
7.5 EUT OPERATION CONDITIONS 23
7.6 TEST RESULTS 23
8 . BANDWIDTH TEST 24
8.1 LIMIT 24
8.2 TEST PROCEDURE 24
8.3 DEVIATION FROM STANDARD 24
8.4 TEST SETUP 24
8.5 EUT OPERATION CONDITIONS 24
8.6 TEST RESULTS 24
9 . MAXIMUM OUTPUT POWER 25
9.1 LIMIT 25
9.2 TEST PROCEDURE 25
9.3 DEVIATION FROM STANDARD 25
9.4 TEST SETUP 25
9.5 EUT OPERATION CONDITIONS 25
9.6 TEST RESULTS 25
10 . CONDUCTED SPURIOUS EMISSION 26
10.1 LIMIT 26
10.2 TEST PROCEDURE 26

Table of Contents Page

10.3 DEVIATION FROM STANDARD 26
10.4 TEST SETUP 26
10.5 EUT OPERATION CONDITIONS 26
10.6 TEST RESULTS 26
11 . MEASUREMENT INSTRUMENTS LIST 27
12 . EUT TEST PHOTO 29
APPENDIX A - AC POWER LINE CONDUCTED EMISSIONS 33
APPENDIX B - RADIATED EMISSION - 9 KHZ-30 MHZ 36
APPENDIX C - RADIATED EMISSION - 30 MHZ TO 1000 MHZ 41
APPENDIX D - RADIATED EMISSION - ABOVE 1000 MHZ 44
APPENDIX E - NUMBER OF HOPPING FREQUENCY 69
APPENDIX F - AVERAGE TIME OF OCCUPANCY 71
APPENDIX G - HOPPING CHANNEL SEPARATION MEASUREMENT 76
APPENDIX H - BANDWIDTH 78
APPENDIX I - MAXIMUM OUTPUT POWER 80
APPENDIX J - CONDUCTED SPURIOUS EMISSION 83

REPORT ISSUED HISTORY

Report Version	Description	Issued Date
R00	Original Issue.	Oct. 26, 2020

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standard(s):

FCC Part15, Subpart C (15.247)				
Standard(s) Section	**Test Item**	**Test Result**	**Judgment**	**Remark**
15.207	AC Power Line Conducted Emissions	APPENDIX A	PASS	------
15.247(d) 15.205(a) 15.209(a)	Radiated Emission	APPENDIX B APPENDIX C APPENDIX D	PASS	------
15.247 (a)(1)(iii)	Number of Hopping Frequency	APPENDIX E	PASS	------
15.247 (a)(1)(iii)	Average Time Of Occupancy	APPENDIX F	PASS	------
15.247(a)(1)	Hopping Channel Separation	APPENDIX G	PASS	------
15.247(a)(1)	Bandwidth	APPENDIX H	PASS	------
15.247(a)(1)	Maximum Output Power	APPENDIX I	PASS	------
15.247(d)	Conducted Spurious Emission	APPENDIX J	PASS	------
15.203	Antenna Requirement	------	PASS	Note(2)

Note:

(1) “N/A” denotes test is not applicable in this test report

(2) The device what use a permanently attached antenna were considered sufficient to comply with the provisions of 15.203.

1.1 TEST FACILITY

The test facilities used to collect the test data in this report is at the location of No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan, Guangdong, China
BTL's Test Firm Registration Number for FCC: 357015
BTL's Designation Number for FCC: CN1240

1.2 MEASUREMENT UNCERTAINTY

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))
The BTL measurement uncertainty as below table:

A. AC power line conducted emissions test:

Test Site	Method	Measurement Frequency Range	U, (dB)
DG-C02	CISPR	150kHz ~ 30MHz	2.60

B. Radiated emissions test:

Test Site	Method	Measurement Frequency Range	Ant. H / V	U, (dB)
DG-CB03	CISPR	9kHz ~ 30MHz	V	3.79
		9kHz ~ 30MHz	H	3.57
		30MHz ~ 200MHz	V	4.88
		30MHz ~ 200MHz	H	4.14
		200MHz ~ 1,000MHz	V	4.62
		200MHz ~ 1,000MHz	H	4.80
		1GHz ~ 6GHz	-	4.58
		6GHz ~ 18GHz	-	5.18
		18GHz ~ 26.5GHz	-	3.62
		26.5GHz ~ 40GHz	-	4.00

C. Other Measurement:

Test Item	Uncertainty
Conducted Spurious Emission	2.67 dB
Hopping Channel Separation	53.46 Hz
Maximum Output Power	0.95 dB
Number of Hopping Frequency	53.46 Hz
Temperature	0.08 °C
Humidity	1.5%

Note: Unless specifically mentioned, the uncertainty of measurement has not been taken into account to declare the compliance or non-compliance to the specification.

1.3 TEST ENVIRONMENT CONDITIONS

Test Item	Temperature	Humidity	Test Voltage	Tested By
AC Power Line Conducted Emissions	25°C	55%	AC 120V/60Hz	Kwok Guo
Radiated Emissions-9K-30MHz	25°C	60%	AC 120V/60Hz	Kwok Guo
Radiated Emissions-30 MHz to 1GHz	25°C	60%	AC 120V/60Hz	Kwok Guo
Radiated Emissions-Above 1000 MHz	26°C	52%	AC 120V/60Hz	Kwok Guo
Number of Hopping Frequency	24°C	52%	AC 120V/60Hz	Jesse Wang
Average Time Of Occupancy	24°C	52%	AC 120V/60Hz	Jesse Wang
Hopping Channel Separation	24°C	52%	AC 120V/60Hz	Jesse Wang
Bandwidth	24°C	52%	AC 120V/60Hz	Jesse Wang
Maximum Output Power	24°C	52%	AC 120V/60Hz	Hand Huang
Conducted Spurious Emission	24°C	52%	AC 120V/60Hz	Jesse Wang

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	Soundbar Speaker
Brand Name	PHILIPS or
Test Model	TAB7305/10
Series Model	TAB7305, B7305, TAB7305/98, TAB7305/67, TAB7305/37, B7305/yy, TAB7305/yy(yy=00-99 or blank,for country code)
Model Difference(s)	Only differing in model name to distinguish between different markets.
Power Source	AC Mains.
Power Rating	100-240VAC, 50/60Hz, 84W
Operation Frequency	2402 MHz ~ 2480 MHz
Modulation Technology	GFSK, π/4-DQPSK, 8-DPSK
Bit Rate of Transmitter	1 Mbps, 2 Mbps, 3Mbps
Max. Output Power	0.79 dBm (0.0012 W) For 1Mbps -0.03 dBm (0.0010 W) For 2Mbps 0.21 dBm (0.0010 W) For 3Mbps

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.

2. Channel List:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	27	2429	54	2456
01	2403	28	2430	55	2457
02	2404	29	2431	56	2458
03	2405	30	2432	57	2459
04	2406	31	2433	58	2460
05	2407	32	2434	59	2461
06	2408	33	2435	60	2462
07	2409	34	2436	61	2463
08	2410	35	2437	62	2464
09	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	39	2441	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	78	2480
25	2427	52	2454		
26	2428	53	2455		

3. Table for Filed Antenna:

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	THOT	N/A	FPC	N/A	2.72

2.2 DESCRIPTION OF TEST MODES

The test system was pre-tested based on the consideration of all possible combinations of EUT operation mode.

Pretest Mode	Description
Mode 1	TX Mode **NOTE (1)**
Mode 2	TX Mode Channel 78 _1Mbps

Following mode(s) was (were) found to be the worst case(s) and selected for the final test.

AC power line conducted emissions test	
Final Test Mode	Description
Mode 2	TX Mode Channel 78 _1Mbps

Radiated emissions test - Below 1GHz	
Final Test Mode	Description
Mode 2	TX Mode Channel 78 _1Mbps

Radiated emissions test - Above 1GHz	
Final Test Mode	Description
Mode 1	TX Mode **NOTE (1)**

Conducted test	
Final Test Mode	Description
Mode 1	TX Mode **NOTE (1)**

Note:

(1) The measurements are performed at the high, middle, low available channels.
(2) The measurements for Hopping Channel Separation and Bandwidth were tested during 1Mbps, 2Mbps and 3Mbps, the worst case are 1Mbps and 3Mbps, only worst case was documented except power.
(3) For radiated emission above 1 GHz test, 1GHz~26.5GHz have been pre-tested and in this report only recorded the worst case. The remaining spurious points are all below the limit value of 20dB.
(4) For AC power line conducted emissions and radiated spurious emissions below 1 GHz test, the 1Mbps channel 78 are found to be the worst case and recorded.
(5) This product has the mode of BT AFH, which was considered during testing, but this mode is not the worst case mode, and this report only shows the worst case mode.

2.3 PARAMETERS OF TEST SOFTWARE

During testing, channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of FHSS

Test Software	FCC TOOL V2.00		
Frequency (MHz)	2402	2441	2480
1Mbps	2	2	2
2Mbps	1	1	1
3Mbps	1	1	1

2.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED



2.5 SUPPORT UNITS

Item	Equipment	Brand	Model No.	Series No.
-	-	-	-	-

Item	Cable Type	Shielded Type	Ferrite Core	Length
1	AC Cable	NO	NO	1.5m

3. AC POWER LINE CONDUCTED EMISSIONS TEST

3.1 LIMIT

Frequency of Emission (MHz)	Limit (dBμV)	
	Quasi-peak	Average
0.15 - 0.5	66 to 56*	56 to 46*
0.5 - 5.0	56	46
5.0 - 30.0	60	50

Note:

(1) The tighter limit applies at the band edges.
(2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

3.2 TEST PROCEDURE

a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipment powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
d. LISN at least 80 cm from nearest part of EUT chassis.
e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.3 DEVIATION FROM TEST STANDARD

No deviation

3.4 TEST SETUP



3.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical function (as a customer would normally use it), EUT was programmed to be in continuously transmitting data or hopping on mode.

3.6 TEST RESULTS

Please refer to the APPENDIX A.

Remark:

(1) All readings are QP Mode value unless otherwise stated AVG in column of 『Note』. If the QP Mode Measured value compliance with the QP Limits and lower than AVG Limits, the EUT shall be deemed to meet both QP & AVG Limits and then only QP Mode was measured, but AVG Mode didn't perform in this case, a "*" marked in AVG Mode column of Interference Voltage Measured.

(2) Measuring frequency range from 150 kHz to 30 MHz.

4. RADIATED EMISSION TEST

4.1 LIMIT

In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

LIMITS OF RADIATED EMISSION MEASUREMENT (9 kHz-1000 MHz)

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000 MHz)

Frequency (MHz)	(dBuV/m at 3 m)	
	Peak	Average
Above 1000	74	54

Note:

(1) The limit for radiated test was performed according to FCC PART 15C.

(2) The tighter limit applies at the band edges.

(3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RBW / VBW (Emission in restricted band)	RBW 1 MHz VBW 3 MHz peak detector for Pk value RMS detector for AV value

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9 kHz~90 kHz for PK/AVG detector
Start ~ Stop Frequency	90 kHz~110 kHz for QP detector
Start ~ Stop Frequency	110 kHz~490 kHz for PK/AVG detector
Start ~ Stop Frequency	490 kHz~30 MHz for QP detector
Start ~ Stop Frequency	30 MHz~1000 MHz for QP detector

4.2 TEST PROCEDURE

a. The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(below 1 GHz)
b. The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 1.5 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(above 1 GHz)
c. The height of the equipment or of the substitution antenna shall be 0.8m or 1.5m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights find the maximum reading (used Bore sight function).
e. The receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz.
f. The initial step in collecting radiated emission data is a receiver peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
g. All readings are Peak unless otherwise stated QP in column of Note. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn‘t perform. (below 1 GHz)
h. All readings are Peak Mode value unless otherwise stated AVG in column of Note. If the Peak Mode Measured value compliance with the Peak Limits and lower than AVG Limits, the EUT shall be deemed to meet both Peak & AVG Limits and then only Peak Mode was measured, but AVG Mode didn‘t perform. (above 1 GHz)
i. For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.3 DEVIATION FROM TEST STANDARD

No deviation

4.4 TEST SETUP

9 kHz-30 MHz



30 MHz to 1 GHz



Above 1 GHz



4.5 EUT OPERATING CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

4.6 TEST RESULTS - 9 kHz TO 30 MHz

Please refer to the APPENDIX B

Remark:

(1) Distance extrapolation factor = 40 log (specific distance / test distance) (dB).
(2) Limit line = specific limits (dBuV) + distance extrapolation factor.

4.7 TEST RESULTS - 30 MHz TO 1000 MHz

Please refer to the APPENDIX C.

4.8 TEST RESULTS - ABOVE 1000 MHz

Please refer to the APPENDIX D.

Remark:

(1) No limit: This is fundamental signal, the judgment is not applicable.
For fundamental signal judgment was referred to Peak output test.

5. NUMBER OF HOPPING FREQUENCY

5.1 LIMIT

FCC Part15, Subpart C (15.247)	
Section	Test Item
15.247(a)(1)(iii)	Number of Hopping Frequency

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> Operating Frequency Range
RBW	100 kHz
VBW	100 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

5.2 TEST PROCEDURE

a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.
b. Spectrum Setting: RBW=100 kHz, VBW=100 kHz, Sweep time = Auto.

5.3 DEVIATION FROM STANDARD

No deviation.

5.4 TEST SETUP

5.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 3.5 unless otherwise a special operating condition is specified in the follows during the testing.

5.6 TEST RESULTS

Please refer to the APPENDIX E

6. AVERAGE TIME OF OCCUPANCY

6.1 LIMIT

FCC Part15, Subpart C (15.247)		
Section	Test Item	Limit
15.247(a)(1)(iii)	Average Time of Occupancy	0.4sec

6.2 TEST PROCEDURE

a. The transmitter output (antenna port) was connected to the spectrum analyzer
b. Set RBW of spectrum analyzer to 1 MHz and VBW to 1 MHz
c. Use a video trigger with the trigger level set to enable triggering only on full pulses
d. Sweep Time is more than once pulse time
e. Set the center frequency on any frequency would be measure and set the frequency span to zero span
f. Measure the maximum time duration of one single pulse
g. Set the EUT for DH1, DH3 and DH5 packet transmitting
h. Measure the maximum time duration of one single pulse
i. DH1 Packet permit maximum 1600 / 79 /2 = 10.12 hops per second in each channel (1 time slot TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times 10.12 x 31.6 = 320 within 31.6 seconds
j. DH3 Packet permit maximum 1600 / 79 / 4 = 5.06 hops per second in each channel (3 time slots TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times 5.06 x 31.6 = 160 within 31.6 seconds
k. DH5 Packet permit maximum 1600/ 79 / 6 = 3.37 hops per second in each channel (5 time slots TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times 3.37 x 31.6 = 106.6 within 31.6 seconds

6.3 DEVIATION FROM STANDARD

No deviation.

6.4 TEST SETUP



6.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 3.5 unless otherwise a special operating condition is specified in the follows during the testing.

6.6 TEST RESULTS

Please refer to the APPENDIX F

7. HOPPING CHANNEL SEPARATION MEASUREMENT

7.1 LIMIT

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RBW	30 kHz
VBW	100 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

7.2 TEST PROCEDURE

a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.

b. Span = wide enough to capture the peaks of two adjacent channels
Resolution (or IF) Bandwidth (RBW) ≥ 1% of the span
Video (or Average) Bandwidth (VBW) ≥ RBW
Sweep = Auto
Detector function = Peak
Trace = Max Hold

7.3 DEVIATION FROM STANDARD

No deviation.

7.4 TEST SETUP



7.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 3.5 unless otherwise a special operating condition is specified in the follows during the testing.

7.6 TEST RESULTS

Please refer to the APPENDIX G

8. BANDWIDTH TEST

8.1 LIMIT

FCC Part15, Subpart C (15.247)	
Section	Test Item
15.247(a)(1)	Bandwidth

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth
RBW	30 kHz
VBW	100 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

8.2 TEST PROCEDURE

a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.
b. Spectrum Setting: RBW= 30 kHz, VBW=100 kHz, Sweep Time = Auto.

8.3 DEVIATION FROM STANDARD

No deviation.

8.4 TEST SETUP



8.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 3.5 unless otherwise a special operating condition is specified in the follows during the testing.

8.6 TEST RESULTS

Please refer to the APPENDIX H

9. MAXIMUM OUTPUT POWER

9.1 LIMIT

FCC Part15 , Subpart C (15.247)		
Section	Test Item	Limit
15.247(a)(1)	Maximum Output Power	0.125 Watt or 21 dBm

Note: Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have Hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

9.2 TEST PROCEDURE

a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.
b. Spectrum Setting: RBW= 1 MHz/3 MHz, VBW= 1 MHz/3 MHz, Sweep time = Auto.

9.3 DEVIATION FROM STANDARD

No deviation.

9.4 TEST SETUP



9.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 3.5 unless otherwise a special operating condition is specified in the follows during the testing.

9.6 TEST RESULTS

Please refer to the APPENDIX I

10. CONDUCTED SPURIOUS EMISSION

10.1 LIMIT

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak Output Power limits. If the transmitter complies with the Output Power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required.

10.2 TEST PROCEDURE

a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.
b. Spectrum Setting: RBW= 100 kHz, VBW=100 kHz, Sweep time = Auto.

10.3 DEVIATION FROM STANDARD

No deviation.

10.4 TEST SETUP



10.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 3.5 unless otherwise a special operating condition is specified in the follows during the testing.

10.6 TEST RESULTS

Please refer to the APPENDIX J

11. MEASUREMENT INSTRUMENTS LIST

AC Power Line Conducted Emissions					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	EMI Test Receiver	R&S	ESCI	100382	Feb. 28, 2021
2	LISN	EMCO	3816/2	52765	Mar. 01, 2021
3	TWO-LINE V-NETWORK	R&S	ENV216	101447	Feb. 28, 2021
4	50Ω Terminator	SHX	TF5-3	15041305	Mar. 01, 2021
5	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A
6	Cable	N/A	RG223	12m	Mar. 10, 2021
7	643 Shield Room	ETS	6*4*3m	N/A	N/A

Radiated Emissions - 9 kHz to 30 MHz					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Antenna	EM	EM-6876-1	230	Apr. 16, 2021
2	Cable	N/A	RG 213/U	N/A	May 29, 2021
3	EMI Test Receiver	R&S	ESCI	100895	Feb. 28, 2021
4	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A
5	966 Chambe Room	RM	9*6*6m	N/A	Jul. 25, 2021

Radiated Emissions - 30 MHz to 1 GHz					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Antenna	Schwarzbeck	VULB9160	9160-3232	Mar. 09, 2021
2*	Amplifier	HP	8447D	2944A09673	Aug. 11, 2021
3	Receiver	Agilent	N9038A	MY52130039	Jul. 25, 2021
4	Cable	emci	LMR-400(30MHz-1 GHz)(8m+5m)	N/A	May 22, 2021
5	Controller	CT	SC100	N/A	N/A
6	Controller	MF	MF-7802	MF780208416	N/A
7	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A
8	966 Chambe Room	RM	9*6*6m	N/A	Jul. 25, 2021

Radiated Emissions - Above 1 GHz					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Double Ridged Guide Antenna	ETS	3115	75789	May 12, 2021
2	Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	9170319	Jul. 07, 2021
3	Amplifier	Agilent	8449B	3008A02333	Mar. 01, 2021
4	Microwave Preamplifier With Adaptor	EMC INSTRUMENT	EMC2654045	980039 & HA01	Mar. 07, 2021
5	Receiver	Agilent	N9038A	MY52130039	Jul. 25, 2021
6	Controller	CT	SC100	N/A	N/A
7	Controller	MF	MF-7802	MF780208416	N/A
8	Cable	N/A	EMC104-SM-SM-6 000	N/A	May 09, 2021
9	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A
10	Filter	STI	STI15-9912	N/A	Jul. 25, 2021
11	966 Chambe Room	RM	9*6*6m	N/A	Jul. 25, 2021

Number of Hopping Frequency & Average Time of Occupancy & Hopping Channel Separation Measurement & Bandwidth & Maximum Output Power & Antenna Conducted Spurious Emission					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP40	100185	Jul. 25, 2021
2	DC Block	Mini	N/A	N/A	N/A
3	RF Cable	Tongkaichuan	N/A	N/A	N/A

Remark "N/A" denotes no model name, serial no. or calibration specified.
"*" calibration period of equipment list is three year.
Except * item, all calibration period of equipment list is one year.

12. EUT TEST PHOTO

AC Power Line Conducted Emissions Test Photos



Radiated Emissions Test Photos

9 kHz to 30 MHz





Radiated Emissions Test Photos

30 MHz to 1000 MHz



Radiated Emissions Test Photos

Above 1 GHz





APPENDIX A - AC POWER LINE CONDUCTED EMISSIONS

Test Mode:	TX Mode Channel 78 _1Mbps

Line



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1	0.1500	48.69	9.67	58.36	66.00	-7.64	Peak	
2	0.1500	37.66	9.67	47.33	56.00	-8.67	AVG	
3	0.1860	44.76	9.87	54.63	64.21	-9.58	Peak	
4	0.1860	32.97	9.87	42.84	54.21	-11.37	AVG	
5	0.2714	41.78	9.88	51.66	61.07	-9.41	Peak	
6	0.2714	32.49	9.88	42.37	51.07	-8.70	AVG	
7	0.6402	37.10	9.92	47.02	56.00	-8.98	Peak	
8 *	0.6402	29.65	9.92	39.57	46.00	-6.43	AVG	
9	1.1220	35.70	10.02	45.72	56.00	-10.28	Peak	
10	1.1220	27.63	10.02	37.65	46.00	-8.35	AVG	
11	2.6025	38.52	10.14	48.66	56.00	-7.34	Peak	
12	2.6025	28.66	10.14	38.80	46.00	-7.20	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX Mode Channel 78 _1Mbps

Neutral



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1	0.1500	50.05	9.74	59.79	66.00	-6.21	Peak	
2	0.1500	41.25	9.74	50.99	56.00	-5.01	AVG	
3	0.2220	43.06	9.99	53.05	62.74	-9.69	Peak	
4	0.2220	32.56	9.99	42.55	52.74	-10.19	AVG	
5	0.2625	40.55	9.99	50.54	61.35	-10.81	Peak	
6	0.2625	31.42	9.99	41.41	51.35	-9.94	AVG	
7	0.6404	37.99	10.16	48.15	56.00	-7.85	Peak	
8	0.6404	29.78	10.16	39.94	46.00	-6.06	AVG	
9	2.4900	40.75	10.46	51.21	56.00	-4.79	Peak	
10 *	2.4900	31.11	10.46	41.57	46.00	-4.43	AVG	
11	3.9210	37.40	10.58	47.98	56.00	-8.02	Peak	
12	3.9210	25.70	10.58	36.28	46.00	-9.72	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

APPENDIX B - RADIATED EMISSION - 9 KHZ-30 MHZ

Test Mode:	TX Mode Channel 78 _1Mbps

Ant 0°



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		0.0180	44.35	13.84	58.19	122.50	-64.31	AVG	
2	*	0.0421	38.84	12.63	51.47	115.12	-63.65	AVG	
3		0.1211	19.40	12.73	32.13	105.94	-73.81	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX Mode Channel 78 _1Mbps

Ant 0°



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		0.3465	36.83	12.40	49.23	96.81	-47.58	AVG	
2		0.6720	35.72	11.94	47.66	71.06	-23.40	QP	
3	*	2.1668	36.19	11.22	47.41	69.54	-22.13	QP	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX Mode Channel 78 _1Mbps

Ant 90°



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	*	0.0180	45.37	13.84	59.21	122.50	-63.29	AVG	
2		0.0420	35.88	12.63	48.51	115.14	-66.63	AVG	
3		0.1140	19.47	12.73	32.20	106.47	-74.27	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX Mode Channel 78 _1Mbps

Ant 90°



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		0.3893	30.75	12.29	43.04	95.80	-52.76	AVG	
2		0.6140	28.38	11.96	40.34	71.84	-31.50	QP	
3	*	3.9640	27.94	10.94	38.88	69.54	-30.66	QP	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

APPENDIX C - RADIATED EMISSION - 30 MHZ TO 1000 MHZ

Test Mode:	TX Mode Channel 78 _1Mbps

Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	68.8000	46.97	-15.65	31.32	40.00	-8.68	Peak	
2	148.3400	41.96	-12.06	29.90	43.50	-13.60	Peak	
3	242.4300	41.56	-13.51	28.05	46.00	-17.95	Peak	
4	297.2349	39.27	-11.13	28.14	46.00	-17.86	Peak	
5 *	445.6450	47.73	-7.75	39.98	46.00	-6.02	Peak	
6	763.3200	38.73	-3.03	35.70	46.00	-10.30	Peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX Mode Channel 78 _1Mbps

Horizontal



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	51.8250	37.66	-13.69	23.97	40.00	-16.03	Peak	
2	148.3400	44.94	-12.06	32.88	43.50	-10.62	Peak	
3	297.2349	51.34	-11.13	40.21	46.00	-5.79	Peak	
4	331.6700	47.00	-10.50	36.50	46.00	-9.50	Peak	
5 *	445.6450	50.95	-7.75	43.20	46.00	-2.80	Peak	
6	761.8650	39.25	-3.04	36.21	46.00	-9.79	Peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

APPENDIX D - RADIATED EMISSION - ABOVE 1000 MHZ

Test Mode:	TX 2402 MHz _CH00_1Mbps

Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2390.0000	42.25	8.29	50.54	74.00	-23.46	Peak	
2	2390.0000	30.52	8.29	38.81	54.00	-15.19	AVG	
3	2401.8750	91.63	8.30	99.93	74.00	25.93	Peak	No Limit
4 *	2402.0000	91.21	8.30	99.51	54.00	45.51	AVG	No Limit

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX 2402 MHz _CH00_1Mbps

Vertical

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	4803.9430	46.30	5.27	51.57	74.00	-22.43	Peak	
2 *	4804.0379	42.33	5.27	47.60	54.00	-6.40	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX 2402 MHz _CH00_1Mbps

Horizontal



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2390.0000	41.30	8.29	49.59	74.00	-24.41	Peak	
2	2390.0000	30.80	8.29	39.09	54.00	-14.91	AVG	
3	2401.8750	94.27	8.30	102.57	74.00	28.57	Peak	No Limit
4 *	2401.9750	93.91	8.30	102.21	54.00	48.21	AVG	No Limit

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX 2402 MHz _CH00_1Mbps

Horizontal

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	4803.9480	39.08	5.27	44.35	54.00	-9.65	AVG	
2	4804.2200	43.73	5.27	49.00	74.00	-25.00	Peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX 2441 MHz _CH39_1Mbps

Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	2441.0000	92.50	8.34	100.84	54.00	46.84	AVG	No Limit
2	2441.1750	92.75	8.34	101.09	74.00	27.09	Peak	No Limit

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX 2441 MHz _CH39_1Mbps

Vertical

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	4881.9850	42.46	5.48	47.94	54.00	-6.06	AVG	
2	4882.1020	46.52	5.48	52.00	74.00	-22.00	Peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX 2441 MHz _CH39_1Mbps

Horizontal



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2440.8250	94.04	8.34	102.38	74.00	28.38	Peak	No Limit
2 *	2441.0250	93.73	8.34	102.07	54.00	48.07	AVG	No Limit

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX 2441 MHz _CH39_1Mbps

Horizontal

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	4881.7799	49.53	5.48	55.01	74.00	-18.99	Peak	
2 *	4881.9530	40.55	5.48	46.03	54.00	-7.97	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX 2480 MHz _CH78_1Mbps

Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	2480.0000	93.39	8.38	101.77	54.00	47.77	AVG	No Limit
2	2480.1500	93.68	8.38	102.06	74.00	28.06	Peak	No Limit
3	2483.5000	43.96	8.39	52.35	74.00	-21.65	Peak	
4	2483.5000	33.47	8.39	41.86	54.00	-12.14	AVG	
5	2484.6000	44.49	8.39	52.88	74.00	-21.12	Peak	
6	2484.6750	37.48	8.39	45.87	54.00	-8.13	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX 2480 MHz _CH78_1Mbps

Vertical

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	4959.6250	46.00	5.69	51.69	74.00	-22.31	Peak	
2 *	4960.0330	41.73	5.69	47.42	54.00	-6.58	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX 2480 MHz _CH78_1Mbps

Horizontal



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2479.8250	93.46	8.38	101.84	74.00	27.84	Peak	No Limit
2 *	2480.0000	93.15	8.38	101.53	54.00	47.53	AVG	No Limit
3	2483.5000	45.07	8.39	53.46	74.00	-20.54	Peak	
4	2483.5000	32.92	8.39	41.31	54.00	-12.69	AVG	
5	2484.8250	45.59	8.39	53.98	74.00	-20.02	Peak	
6	2484.8250	36.68	8.39	45.07	54.00	-8.93	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX 2480 MHz _CH78_1Mbps

Horizontal

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	4959.8920	44.85	5.69	50.54	74.00	-23.46	Peak	
2 *	4959.9220	40.12	5.69	45.81	54.00	-8.19	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX 2402 MHz _CH00_3Mbps

Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2390.0000	41.35	8.29	49.64	74.00	-24.36	Peak	
2	2390.0000	30.55	8.29	38.84	54.00	-15.16	AVG	
3 *	2401.9250	89.76	8.30	98.06	54.00	44.06	AVG	No Limit
4	2402.1500	94.30	8.30	102.60	74.00	28.60	Peak	No Limit

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX 2402 MHz _CH00_3Mbps

Vertical

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	4803.9830	40.73	5.27	46.00	54.00	-8.00	AVG	
2	4804.0250	49.51	5.27	54.78	74.00	-19.22	Peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX 2402 MHz _CH00_3Mbps

Horizontal



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2390.0000	42.23	8.29	50.52	74.00	-23.48	Peak	
2	2390.0000	30.46	8.29	38.75	54.00	-15.25	AVG	
3 *	2402.0000	92.38	8.30	100.68	54.00	46.68	AVG	No Limit
4	2402.1250	97.03	8.30	105.33	74.00	31.33	Peak	No Limit

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX 2402 MHz _CH00_3Mbps

Horizontal

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	4803.8900	54.49	5.27	59.76	74.00	-14.24	Peak	
2 *	4804.0250	46.35	5.27	51.62	54.00	-2.38	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX 2441 MHz _CH39_3Mbps

Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2441.0500	96.13	8.34	104.47	74.00	30.47	Peak	No Limit
2 *	2441.0500	91.41	8.34	99.75	54.00	45.75	AVG	No Limit

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX 2441 MHz _CH39_3Mbps

Vertical

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	4881.9270	40.76	5.48	46.24	54.00	-7.76	AVG	
2	4882.0550	49.26	5.48	54.74	74.00	-19.26	Peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX 2441 MHz _CH39_3Mbps

Horizontal



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	2440.9500	91.43	8.34	99.77	54.00	45.77	AVG	No Limit
2	2441.0250	95.93	8.34	104.27	74.00	30.27	Peak	No Limit

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX 2441 MHz _CH39_3Mbps

Horizontal

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	4882.0120	46.20	5.48	51.68	54.00	-2.32	AVG	
2	4882.1250	54.05	5.48	59.53	74.00	-14.47	Peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX 2480 MHz _CH78_3Mbps

Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	2479.9250	91.78	8.38	100.16	54.00	46.16	AVG	No Limit
2	2480.0500	96.01	8.38	104.39	74.00	30.39	Peak	No Limit
3	2483.5000	46.66	8.39	55.05	74.00	-18.95	Peak	
4	2483.5000	33.73	8.39	42.12	54.00	-11.88	AVG	
5	2484.5500	46.59	8.39	54.98	74.00	-19.02	Peak	
6	2484.5500	36.49	8.39	44.88	54.00	-9.12	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX 2480 MHz _CH78_3Mbps

Vertical

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	4959.9750	40.46	5.69	46.15	54.00	-7.85	AVG	
2	4960.2850	48.34	5.69	54.03	74.00	-19.97	Peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX 2480 MHz _CH78_3Mbps

Horizontal



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2479.9750	95.16	8.38	103.54	74.00	29.54	Peak	No Limit
2 *	2479.9750	90.85	8.38	99.23	54.00	45.23	AVG	No Limit
3	2483.5000	44.82	8.39	53.21	74.00	-20.79	Peak	
4	2483.5000	33.07	8.39	41.46	54.00	-12.54	AVG	
5	2484.8000	45.35	8.39	53.74	74.00	-20.26	Peak	
6	2484.8000	35.39	8.39	43.78	54.00	-10.22	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX 2480 MHz _CH78_3Mbps

Horizontal

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	4959.7519	52.55	5.69	58.24	74.00	-15.76	Peak	
2 *	4960.0280	44.87	5.69	50.56	54.00	-3.44	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

APPENDIX E - NUMBER OF HOPPING FREQUENCY

Test Mode	Hopping Mode_1Mbps
Number of Hopping Frequency	79



Date: 8.JUN.2020 17:21:05

Test Mode	Hopping Mode_3Mbps
Number of Hopping Frequency	79



Date: 8.JUN.2020 17:26:31

APPENDIX F - AVERAGE TIME OF OCCUPANCY

Test Mode:	TX Mode_1Mbps

Data Packet	Frequency (MHz)	Pulse Duration (ms)	Dwell Time (s)	Limits (s)	Test Result
DH1	2402	0.3750	0.1200	0.4000	Pass
DH3	2402	1.6200	0.2592	0.4000	Pass
DH5	2402	2.8800	0.3072	0.4000	Pass
DH1	2441	0.3700	0.1184	0.4000	Pass
DH3	2441	1.6400	0.2624	0.4000	Pass
DH5	2441	2.8800	0.3072	0.4000	Pass
DH1	2480	0.3750	0.1200	0.4000	Pass
DH3	2480	1.6400	0.2624	0.4000	Pass
DH5	2480	2.8800	0.3072	0.4000	Pass

CH00-DH1



Date: 8.JUN.2020 16:14:53

CH39-DH1



Date: 8.JUN.2020 17:52:20

CH78-DH1



Date: 8.JUN.2020 17:54:00

CH00-DH3



Date: 8.JUN.2020 17:55:36

CH39-DH3



Date: 8.JUN.2020 17:53:03

CH78-DH3



Date: 8.JUN.2020 17:54:31

CH00-DH5



Date: 8.JUN.2020 17:55:17

CH39-DH5



Date: 8.JUN.2020 17:53:26

CH78-DH5



Date: 8.JUN.2020 17:54:55

Test Mode:	TX Mode_3Mbps

Data Packet	Frequency (MHz)	Pulse Duration (ms)	Dwell Time (s)	Limits (s)	Test Result
3DH1	2402	0.3800	0.1216	0.4000	Pass
3DH3	2402	1.6400	0.2624	0.4000	Pass
3DH5	2402	2.8800	0.3072	0.4000	Pass
3DH1	2441	0.3800	0.1216	0.4000	Pass
3DH3	2441	1.6200	0.2592	0.4000	Pass
3DH5	2441	2.8800	0.3072	0.4000	Pass
3DH1	2480	0.3800	0.1216	0.4000	Pass
3DH3	2480	1.6400	0.2624	0.4000	Pass
3DH5	2480	2.8800	0.3072	0.4000	Pass

CH00-3DH1



Date: 8.JUN.2020 17:46:39

CH39-3DH1



Date: 8.JUN.2020 17:47:21

CH78-3DH1



Date: 8.JUN.2020 17:47:25

CH00-3DH3



Date: 8.JUN.2020 17:49:29

CH39-3DH3



Date: 8.JUN.2020 17:50:10

CH78-3DH3



Date: 8.JUN.2020 17:50:32

CH00-3DH5



Date: 8.JUN.2020 17:51:25

CH39-3DH5



Date: 8.JUN.2020 17:51:46

CH78-3DH5



Date: 8.JUN.2020 17:51:05

APPENDIX G - HOPPING CHANNEL SEPARATION MEASUREMENT

Test Mode:	Hopping on _1Mbps

Channel	Frequency (MHz)	Channel Separation (MHz)	2/3 of 20 dB Bandwidth (MHz)	Test Result
00	2402	0.907	0.617	Pass
39	2441	1.003	0.605	Pass
78	2480	1.002	0.617	Pass

CH00



Date: 8.JUN.2020 16:46:27

CH39



Date: 8.JUN.2020 16:59:42

CH78



Date: 8.JUN.2020 17:08:04

Test Mode:	Hopping on _3Mbps

Channel	Frequency (MHz)	Channel Separation (MHz)	2/3 of 20 dB Bandwidth (MHz)	Test Result
00	2402	1.002	0.868	Pass
39	2441	1.003	0.863	Pass
78	2480	0.996	0.847	Pass

CH00



Date: 8.JUN.2020 17:31:00

CH39



Date: 8.JUN.2020 17:36:06

CH78



Date: 8.JUN.2020 17:37:27

APPENDIX H - BANDWIDTH

Test Mode:	TX Mode _1Mbps

Channel	Frequency (MHz)	20 dB Bandwidth (MHz)	99 % Emission Bandwidth (MHz)
00	2402	0.925	0.884
39	2441	0.908	0.860
78	2480	0.926	0.844

CH00



Date: 8.JUN.2020 16:04:58

CH39



Date: 8.JUN.2020 16:06:50

CH78



Date: 8.JUN.2020 16:07:56

Test Mode:	TX Mode _3Mbps

Channel	Frequency (MHz)	20 dB Bandwidth (MHz)	99 % Emission Bandwidth (MHz)
00	2402	1.302	1.200
39	2441	1.294	1.192
78	2480	1.270	1.196

CH00



Date: 8.JUN.2020 16:34:27

CH39



Date: 8.JUN.2020 16:37:31

CH78



Date: 8.JUN.2020 16:38:33

APPENDIX I - MAXIMUM OUTPUT POWER

Test Mode:	TX Mode _1Mbps

Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)	Max. Limit (dBm)	Max. Limit (W)	Test Result
00	2402	0.22	0.0011	21.00	0.125	Pass
39	2441	0.40	0.0011	21.00	0.125	Pass
78	2480	0.79	0.0012	21.00	0.125	Pass

CH00



Date: 8.JUN.2020 16:09:48

CH39



Date: 8.JUN.2020 16:09:32

CH78



Date: 8.JUN.2020 16:09:00

Test Mode:	TX Mode _2Mbps

Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)	Max. Limit (dBm)	Max. Limit (W)	Test Result
00	2402	-0.73	0.0008	21.00	0.125	Pass
39	2441	-0.29	0.0009	21.00	0.125	Pass
78	2480	-0.03	0.0010	21.00	0.125	Pass

CH00



Date: 8.JUN.2020 16:42:38

CH39



Date: 8.JUN.2020 16:42:55

CH78



Date: 8.JUN.2020 16:42:25

Test Mode:	TX Mode _3Mbps

Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)	Max. Limit (dBm)	Max. Limit (W)	Test Result
00	2402	-0.43	0.0009	21.00	0.125	Pass
39	2441	-0.12	0.0010	21.00	0.125	Pass
78	2480	0.21	0.0010	21.00	0.125	Pass

CH00



CH39



CH78



APPENDIX J - CONDUCTED SPURIOUS EMISSION

Test Mode : TX Mode _1Mbps

Bandedge CH00 (Lower)



Date: 8.JUN.2020 16:10:23

Bandedge CH78 (Upper)



Date: 8.JUN.2020 16:12:19

Hopping on mode (Lower)



Date: 8.JUN.2020 16:57:19

Hopping on mode (Upper)



Date: 8.JUN.2020 17:16:14

CH00 – 10th Harmonic of the fundamental frequency



Date: 8.JUN.2020 16:10:37



Date: 8.JUN.2020 16:10:46



Date: 8.JUN.2020 16:10:55

CH39 – 10th Harmonic of the fundamental frequency



Date: 8.JUN.2020 16:11:37



Date: 8.JUN.2020 16:11:46



Date: 8.JUN.2020 16:11:54

CH78 – 10th Harmonic of the fundamental frequency



Date: 8.JUN.2020 16:12:33



Date: 8.JUN.2020 16:12:43



Date: 8.JUN.2020 16:12:51

Test Mode : TX Mode _3Mbps

Bandedge CH00 (Lower)



Date: 8.JUN.2020 16:33:53

Bandedge CH78 (Upper)



Date: 8.JUN.2020 16:37:57

Hopping on mode (Lower)



Date: 8.JUN.2020 17:40:44

Hopping on mode (Upper)



Date: 8.JUN.2020 17:45:58

CH00 – 10th Harmonic of the fundamental frequency



Date: 8.JUN.2020 16:34:41



Date: 8.JUN.2020 16:34:50



Date: 8.JUN.2020 16:34:58

CH39 – 10th Harmonic of the fundamental frequency



Date: 8.JUN.2020 16:36:39



Date: 8.JUN.2020 16:36:48



Date: 8.JUN.2020 16:36:56

CH78 – 10th Harmonic of the fundamental frequency



Date: 8.JUN.2020 16:38:48



Date: 8.JUN.2020 16:38:57



Date: 8.JUN.2020 16:39:05

End of Test Report