



RF Exposure Report

FCC ID: 2AR2STAH6206

Applicant: MMD Hong Kong Holding Limited

Address: Unit 1006, 10th Floor, C-Bons International Center, 108 Wai Yip Street, Kwun Tong, Kowloon, Hong Kong

Manufacturer: MMD Hong Kong Holding Limited

Address: Unit 1006, 10th Floor, C-Bons International Center, 108 Wai Yip Street, Kwun Tong, Kowloon, Hong Kong

Product(s): Wireless TV headphones

Brand(s): PHILIPS or



Test Model(s): TAH6206

Series Model(s): TAH6206xx/yy (xx=AA-ZZ or blank denoted different color, yy=00-99 denoted different country destination)

Test Date: Apr. 10, 2022~ Apr. 22, 2022

Issued Date: May. 17, 2022

Issued By: Hwa-Hsing (Dongguan) Testing Co., Ltd.

Address: No.101, Bld N1, Yuyuan 2Rd, Yuyuan Industrial Park, HuangJiang Town, Dongguan, China

Test Firm Registration No.: 915896

Standards: FCC Part 2 (Section 2.1093)
KDB 447498 D01 General RF Exposure Guidance v07
KDB 447498 D04 Interim General RF Exposure Guidance v01
IEEE C95.1

The above equipment has been tested by **Hwa-Hsing (Dongguan) Testing Co., Ltd.**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :

Tank Tan

Reviewed by :

Scott He

Approved by :

Harry Li

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by A2LA or any agency of the federal government. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.



Table of contents

Release control record	3
1 General Information	4
1.1 General Description of EUT	4
2 RF exposure limit.....	5
3 Calculation	5
4 Calculation SAR test exclusion thresholds	6
Appendix – Information on the Testing Laboratories	7



HWA-HSING Test Report No.: 220412KH01-1-SE-US-01

Release control record

Issue No.	Reason for change	Date issued
220412KH01-1-SE-US-01	Original Release	May 17, 2022

Lab: [Hwa-Hsing \(Dongguan\) Testing Co., Ltd.](#)
Address: [No.101, Bld N1, Yuyuan 2Rd, Yuyuan Industrial Park,](#)
[HuangJiang Town, Dongguan, China](#)

Tel: [0769-83078199](#)
Web.: [www.hwa-hsing.com](#)
E-Mail: [customerservice.dg@hwa-hsing.com](#)

Release
[Ver. 1.5](#)



1 General Information

1.1 General Description of EUT

Product(s)	Wireless TV headphones
Test Model(s)	TAH6206
Series Model(s)	TAH6206xx/yy (xx=AA-ZZ or blank denoted different color, yy=00-99 denoted different country destination)
Status of EUT	Engineering Prototype
Power Supply Rating	DC 5V from USB port input
Modulation Type	GFSK, $\pi/4$ DQPSK, 8DPSK
Transfer Rate	1/2/3Mbps
Operating Frequency	2402 ~ 2480MHz
Number of Channel	79
Output Power	-0.846dBm
Antenna Type	PCB Antenna
Antenna Gain	0dBi Maximum peak Gain
Antenna Connector	N/A
Accessory Device	N/A
Cable Supplied	USB-A to Type-C Cable: 0.5m; 3.5mm Audio Cable: 1.6m

Note:

1. Please refer to the EUT photo document (Reference No.: 220412KH01-1-01&-02) for detailed product photo.
2. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.
3. Model difference: These models are only different for model name for trade purpose.



2 RF exposure limit

The corresponding SAR Exclusion Threshold condition, listed below:

- 1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, the distance of 5 mm is applied to determine SAR test exclusion.

- 2) At 100 MHz to 6 GHz and for test separation distances > 50 mm, the SAR test exclusion threshold is determined according to the following:

- a) [Threshold at 50 mm in step 1) + (test separation distance - 50 mm) $\cdot$ (f(MHz)/150)] mW, at 100MHz to 1500 MHz
- b) [Threshold at 50 mm in step 1) + (test separation distance - 50 mm) $\cdot$ 10] mW at > 1500 MHz and ≤ 6 GHz

- 3) At frequencies below 100 MHz, the following may be considered for SAR test exclusion.

- a) The threshold at the corresponding test separation distance at 100 MHz in step 2) is multiplied by $[1 + \log(100/f(\text{MHz}))]$ for test separation distances > 50 mm and < 200 mm.
- b) The threshold determined by the equation in a) for 50 mm and 100 MHz is multiplied by $\frac{1}{2}$ for test separation distances ≤ 50 mm.
- c) SAR measurement procedures are not established below 100 MHz. When SAR test exclusion cannot be applied, a KDB inquiry is required to determine SAR evaluation requirements for any test results to be acceptable.

3 Calculation

The antenna of this product, under normal use condition, is at less than 5mm away from the body of the user.



4 Calculation SAR test exclusion thresholds

The measured of Maximum RF Conduted Power

Mode	Frequency (MHz)	Maximum RF Power (dBm)
GFSK	2402-2480	-1.055
8DPSK	2402-2480	-0.846

The tuned Power (declared by client)

Mode	Frequency (MHz)	Target Power (dBm)	Tolerance (dBm)	Lower Tolerance (dBm)	Upper Tolerance (dBm)
GFSK	2402-2480	0	± 2	-2	2
8DPSK	2402-2480	0	± 2	-2	2

SAR Test Exclusion Thresholds

Frequency (MHz)	Maximum source-based time averaged conducted output power(dBm)	Minimum separation distance (mm)	Result of Eq. 1	Limit for 1-g SAR	Limit for 10-g extremity SAR	Verdict
2402-2480	2	5	0.499	3.0	7.5	Exempt from SAR

Conclusion: Therefore this device complies with FCC's RF radiation exposure limits for general population without SAR evaluation.



Appendix – Information on the Testing Laboratories

We, [Hwa-Hsing \(Dongguan\) Co., Ltd.](#), A global provider of TESTING and CERTIFICATION services for consumer products, electronic products and wireless information technology products. Adhering to the core values “HONEST and TRUSTWORTHY, OBJECTIVE and IMPARTIALITY, RIGOROUS and AFFICIENT”, commitment to provide professional, perfect and efficient comprehensive ONE-STOP solution of TESTING and CERTIFICATION services for Manufacturers, Buyers, Traders, Brands, Retailers. Assist client to better manage risk, protect their brands, reduce costs and cut time to over 150 markets in global. Our laboratories are FCC recognized accredited test firms and accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lab Address: [No.101, Bld N1, Yuyuan 2Rd, Yuyuan Industrial Park, HuangJiang Town, Dongguan, China](#)

Contact Tel: [0769-83078199](tel:0769-83078199)

Email: Customerservice.dg@hwa-hsing.com

Web Site: www.hwa-hsing.com

--- END ---