Certificate #4312.01

TEST REPORT

Product Name:	Mono Bluetooth headphone
Trade Mark:	PHILIPS or
Model No.:	TAL3000
Add. Model No.:	TAL3000BK/37, TAL3000xx/yy (xx=AA-ZZ or blank denoted different color; yy=00-99 denoted different country destination)
Report Number:	25062418702EMC-1
Test Standards:	FCC 47 CFR Part 15 Subpart B ICES-003 Issue 7
FCC ID:	2AR2STAL3000
Test Result:	PASS
Date of Issue:	July 24, 2025

Prepared for:

MMD Hong Kong Holding Limited
Units 1208-11, 12th Floor, C-Bons International Center, 108 Wai Yip Street, Kwun Tong, Kowloon, Hong Kong

Prepared by:

Shenzhen UnionTrust Quality and Technology Co., Ltd.
16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

TEL: +86-755-2823 0888
FAX: +86-755-2823 0886

Prepared by:	David Chen Senior Project Engineer	Reviewed by:	Kevin Liang Assistant Manager
Approved by:	Billy Li Technical Director	Date:	July 24, 2025

UnionTrust Laboratories UnionTrust *Certified*

Version

Version No.	Date	Description
V1.0	July 24, 2025	Original

CONTENTS

1. GENERAL INFORMATION 4
   1.1 CLIENT INFORMATION 4
   1.2 EUT INFORMATION 4
      1.2.1 GENERAL DESCRIPTION OF EUT 4
      1.2.2 DESCRIPTION OF ACCESSORIES 5
   1.3 DESCRIPTION OF SUPPORT UNITS 5
   1.4 TEST LOCATION 5
   1.5 TEST FACILITY 5
   1.6 DEVIATION FROM STANDARDS 6
   1.7 ABNORMALITIES FROM STANDARD CONDITIONS 6
   1.8 OTHER INFORMATION REQUESTED BY THE CUSTOMER 6
   1.9 MEASUREMENT UNCERTAINTY 6
2. TEST SUMMARY 7
3. EQUIPMENT LIST 8
4. TEST CONFIGURATION 9
   4.1 ENVIRONMENTAL CONDITIONS FOR TESTING 9
      4.1.1 NORMAL OR EXTREME TEST CONDITIONS 9
      4.1.2 RECORD OF NORMAL ENVIRONMENT AND TEST SAMPLE 9
   4.2 TEST MODES 9
   4.3 TEST SETUP 10
      4.3.1 FOR RADIATED EMISSIONS TEST SETUP 10
      4.3.2 FOR CONDUCTED EMISSIONS TEST SETUP 11
   4.4 SYSTEM TEST CONFIGURATION 11
5. REFERENCE DOCUMENTS FOR TESTING 12
6. EMC REQUIREMENTS SPECIFICATION 12
   6.1 RADIATED EMISSION 12
   6.2 CONDUCTED EMISSION 18

APPENDIX 1 PHOTOS OF TEST SETUP 21
APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS 21

1. GENERAL INFORMATION

1.1 CLIENT INFORMATION

Applicant:	MMD Hong Kong Holding Limited
Address of Applicant:	Units 1208-11, 12th Floor, C-Bons International Center, 108 Wai Yip Street, Kwun Tong, Kowloon, Hong Kong
Manufacturer:	MMD Hong Kong Holding Limited
Address of Manufacturer:	Units 1208-11, 12th Floor, C-Bons International Center, 108 Wai Yip Street, Kwun Tong, Kowloon, Hong Kong

1.2 EUT INFORMATION

1.2.1 General Description of EUT

Product Name:	Mono Bluetooth headphone
Model No.:	TAL3000
Add. Model No.:	TAL3000BK/37, TAL3000xx/yy (xx=AA-ZZ or blank denoted different color; yy=00-99 denoted different country destination)
Trade Mark:	PHILIPS or
DUT Stage:	Identical Prototype
Rated Voltage:	☒ Input: 5V ⎓ 500mA
	☒ 3.7Vdc (1x3.7V Lithium-ion Polymer Rechargeable Battery)
Classification of digital devices:	Class B
Highest Internal Frequency:	2480 MHz
Sample Received Date:	June 24, 2025
Sample Tested Date:	June 26, 2025 to June 30, 2025
Note: The additional model TAL3000BK/37, TAL3000xx/yy (xx=AA-ZZ or blank denoted different color; yy=00-99 denoted different country destination) is identical with the test model TAL3000 except the model number for marketing purpose.	

Remark: The above EUT's information was provided by customer. Please refer to the specifications or user's manual for more detailed description.

1.2.2 Description of Accessories

Car charger	
Model No.:	DLP2511A/00
Input:	DC 12-24 V
Output:	5.0 V ⎓ 2.1 A max

Battery	
Model No.:	501430
Battery Type:	Lithium-ion Polymer Rechargeable Battery
Rated Voltage:	3.7 Vdc
Rated Capacity:	180 mAh

Cable	
Description:	USB Type-C Plug Cable
Cable Type:	Unshielded without ferrite
Length:	0.8 Meter

Other
Charging base

1.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested with associated equipment below.

1) Support Equipment

Description	Manufacturer	Model No.	Serial Number	Supplied by
Tablet	HUAWEI	JDN2-W09	UPK9X20B03003100	UnionTrust
AC/DC ADAPTER	KEYU	KA06E-0501000EU	D/C:2035	UnionTrust
Battery*2	Camel	L2 400 6-QW-60(580)	N/A	UnionTrust

1.4 TEST LOCATION

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China
Telephone: +86 (0) 755 2823 0888
Fax: +86 (0) 755 2823 0886

1.5 TEST FACILITY

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L9069

The measuring equipment utilized to perform the tests documented in this report has been calibrated once a year or in accordance with the manufacturer's recommendations, and is traceable under the ISO/IEC 17025 to

international or national standards. Equipment has been calibrated by accredited calibration laboratories.

A2LA-Lab Certificate No.: 4312.01
Shenzhen UnionTrust Quality and Technology Co., Ltd. has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

ISED Wireless Device Testing Laboratories
CAB identifier: CN0032

FCC Accredited Lab.
Designation Number: CN1194
Test Firm Registration Number: 259480

1.6 DEVIATION FROM STANDARDS

None.

1.7 ABNORMALITIES FROM STANDARD CONDITIONS

None.

1.8 OTHER INFORMATION REQUESTED BY THE CUSTOMER

None.

1.9 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

No.	Item	Measurement Uncertainty
1	Conducted emission 9kHz-150kHz	±3.2 dB
2	Conducted emission 150kHz-30MHz	±2.7 dB
3	Radiated emission 9kHz-30MHz	± 4.7 dB
4	Radiated emission 30MHz-1GHz	± 4.6 dB
5	Radiated emission 1GHz-18GHz	± 4.4 dB
6	Radiated emission 18GHz-26GHz	± 4.6 dB
7	Radiated emission 26GHz-40GHz	± 4.6 dB

2. TEST SUMMARY

Test Cases			
Test Item	**Test Requirement**	**Test Method**	**Result**
Conducted Emission	FCC 47 CFR Part 15.107 ICES-003 Issue 7 Section 3.2.1	ANSI C63.4-2014	PASS
Radiated Emission	FCC 47 CFR Part 15.109 ICES-003 Issue 7 Section 3.2.2	ANSI C63.4-2014	PASS

3. EQUIPMENT LIST

Radiated Emission Test Equipment List						
Used	**Equipment**	**Manufacturer**	**Model No.**	**Serial Number**	**Cal. date**	**Cal. Due date**
☒	3m SAC	ETS-LINDGREN	3m	Euroshiedpn-CT001270-1317	11-Nov-2023	10-Nov-2026
☒	Receiver	R&S	ESIB26	100114	25-Oct-2024	24-Oct-2025
☒	Broadband Antenna	ETS-LINDGREN	3142E	00201566	28-Oct-2024	27-Oct-2025
☒	6dB Attenuator	Talent	RA6A5-N-18	18103001	29-Oct-2024	28-Oct-2025
☒	Preamplifier	HP	8447F	2805A02960	25-Oct-2024	24-Oct-2025
☒	Double-Ridged Waveguide Horn Antenna (Pre-amplifier)	ETS-LINDGREN	3117-PA	00201541	29-Mar-2025	28-Mar-2026
☒	Pre-amplifier	ETS-Lindgren	00118385	00201874	28-Mar-2025	27-Mar-2026
☒	Double-Ridged Waveguide Horn Antenna (Pre-amplifier)	ETS-LINDGREN	3116C-PA	00202652	28-Oct-2024	27-Oct-2025
☒	Pre-amplifier	ETS-Lindgren	00118384	00202652	28-Oct-2024	27-Oct-2025
☒	Multi device Controller	ETS-LINDGREN	7006-001	00160105	N/A	N/A
☒	Test Software	Audix	e3	Software Version: 9.160323		

Conducted Emission Test Equipment List						
Used	**Equipment**	**Manufacturer**	**Model No.**	**Serial Number**	**Cal. date**	**Cal. Due date**
☒	Receiver	R&S	ESCI3	1166.5950.03	25-Oct-2024	24-Oct-2025
☒	Pulse Limiter	R&S	ESH3-Z2	0357.8810.54	25-Oct-2024	24-Oct-2025
☒	LISN	R&S	EVN216	3560.6550.12	26-Sep-2024	25-Sep-2025
☐	LISN	ETS-Lindgren	3816/2SH	00201088	25-Oct-2024	24-Oct-2025
☒	Test Software	EZ-EMC	EZ-CON	Software Version: EMC-CON 3A1.1		

4. TEST CONFIGURATION

4.1 ENVIRONMENTAL CONDITIONS FOR TESTING

4.1.1 Normal or Extreme Test Conditions

Environment Parameter	Selected Values During Tests		
Test Condition	Ambient		
	Temperature (°C)	Voltage (V)	Relative Humidity (%)
NV/NT	+15 to +35	AC 120V~60 Hz or/ DC12-24V and 3.7 V Battery	20 to 75
Remark: 1) NV: Normal Voltage; NT: Normal Temperature			

4.1.2 Record of Normal Environment and Test sample

Test Item	Temperature (°C)	Relative Humidity (%)	Pressure (kPa)	Sample No.	Tested by
Conducted Emission	24.7	51.8	99.8	S202506246351-ZJC04/5	Linson Xie
Radiated Emission	26.4	62.5	99.4		Leo Li

4.2 TEST MODES

Test Item	EMI Test Modes
Radiated Emission	Test Mode 1: Powered by Car charger (12Vdc) + + BT playing + Microphone on **Test Mode 2: Powered by Car charger (24Vdc) + + BT playing + Microphone on** Test Mode 3: Powered by Charging base + BT playing + Microphone on Test Mode 4: Powered by Battery + BT playing + Microphone on
Conducted Emission	**Test Mode 1: Powered by Charging base + BT playing + Microphone on**
Remark: The above test modes in boldface were the worst cases, only the test data of these modes were reported.	

4.3 TEST SETUP

4.3.1 For Radiated Emissions test setup

Figure 1. 30MHz to 1GHz



Figure 2. Above 1GHz



4.3.2 For Conducted Emissions test setup

Figure 3. Conducted Emissions setup



4.4 SYSTEM TEST CONFIGURATION

All readings are extrapolated back to the equivalent three meter reading using inverse scaling with distance. Analyzer resolution is 100 kHz or greater for frequencies below 1000MHz. The resolution is 1 MHz or greater for frequencies above 1000MHz. The spurious emissions more than 20 dB below the permissible value are not reported.

Radiated emission measurement were performed from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic (according to KDB 896810 D02 SDoC FAQ v01r01) of the highest fundamental frequency or to 40 GHz, whichever is lower.

5. REFERENCE DOCUMENTS FOR TESTING

No.	Identity	Document Title
1	FCC 47 CFR Part15 Subpart B	Unintentional Radiators
2	ICES-003 Issue 7	Information Technology Equipment (Including Digital Apparatus)
3	ANSI C63.4-2014	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz
4	KDB 174176 D01 Line Conducted FAQ v01r01	AC power-line conducted emission frequency asked questions
5	KDB 896810 D02 SDoC FAQ v01r02	Supplier's Declaration of Conformity frequency asked questions

6. EMC REQUIREMENTS SPECIFICATION

6.1 RADIATED EMISSION

Test Requirement: FCC 47 CFR Part 15.109
ICES-003 Issue 7 Clause 3.2.2

Test Method: ANSI C63.4-2014

Receiver Setup:

Frequency: (f) (MHz)	Detector type	Measurement receiver bandwidth	
		RBW	VBW
30 ≤ f ≤ 1 000	Quasi Peak	120 kHz	300 kHz
f ≥1000	Peak	1 MHz	3 MHz
	Average	1 MHz	3 MHz

Measured frequency range

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30.
1.705-108	1000.
108-500	2000.
500-1000	5000.
Above 1000	5th harmonic of the highest frequency or 40 GHz, whichever is lower.

Limits:

Limits for Class B devices

FCC 47 CFR Part 15 Subpart B

Frequency (MHz)	limits at 3m (dBμV/m)		
	QP Detector	PK Detector	AV Detector
30 – 88	40.0	--	--
88 – 216	43.5	--	--
216 – 960	46.0		
960 – 1000	54.0	--	--
Above 1000	--	74.0	54.0

ICES-003 Issue 7

Frequency (MHz)	limits at 3m (dBμV/m)		
	QP Detector	PK Detector	AV Detector
30 – 88	40.0	--	--
88 – 216	43.5	--	--
216 – 230	46.0		

230 – 960	47.0	--	--
960 – 1000	54.0	--	--
Above 1000	--	74.0	54.0

Remark:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBμV/m) = 20 log Emission level (μV/m).
3. For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

Test Setup: Refer to section 4.3.1 for details.

Test Procedures:

1. From 30 MHz to 1GHz test procedure as below:

1) The Product was placed on the non-conductive turntable 0.8 m above the ground at a chamber.
2) Set the spectrum analyzer/receiver in Peak detector, Max Hold mode, and 120 kHz RBW. Record the maximum field strength of all the pre-scan process in the full band when the antenna is varied between 1~4 m in both horizontal and vertical, and the turntable is rotated from 0 to 360 degrees.
3) For each frequency whose maximum record was higher or close to limit, measure its QP value: vary the antenna's height and rotate the turntable from 0 to 360 degrees to find the height and degree where Product radiated the maximum emission, then set the test frequency analyzer/receiver to QP Detector and specified bandwidth with Maximum Hold Mode, and record the maximum value.

2. Above 1GHz test procedure as below:

1) The Product was placed on the non-conductive turntable 0.8 m above the ground at a chamber.
2) Set the spectrum analyzer/receiver in Peak detector, Max Hold mode, and 1MHz RBW. Record the maximum field strength of all the pre-scan process in the full band when the antenna is varied in both horizontal and vertical, and the turntable is rotated from 0 to 360 degrees.
3) For each frequency whose maximum record was higher or close to limit, measure its AV value: rotate the turntable from 0 to 360 degrees to find the degree where Product radiated the maximum emission, then set the test frequency analyzer/receiver to AV value and specified bandwidth with Maximum Hold Mode, and record the maximum value.

Equipment Used: Refer to section 3 for details.

Test Result: Pass

The measurement data as follows:

The worst measurement data for FCC 47 CFR Part 15 Subpart B as follows:

Below 1GHz(Quasi Peak):
Test Mode2
Horizontal



No.	Frequency (MHz)	Reading (dBµV)	Correction factor (dB/m)	Result (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Detector
1	32.184	29.94	-6.18	23.76	40.00	-16.24	QP
2	47.703	34.98	-13.10	21.88	40.00	-18.12	QP
3	101.893	30.54	-15.67	14.87	43.50	-28.63	QP
4	222.281	34.45	-10.84	23.61	46.00	-22.39	QP
5	355.940	27.81	-6.55	21.26	46.00	-24.74	QP
6	827.179	32.64	3.57	36.21	46.00	-9.79	QP

Vertical



No.	Frequency (MHz)	Reading (dBµV)	Correction factor (dB/m)	Result (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Detector
1	31.735	34.27	-6.08	28.19	40.00	-11.81	QP
2	44.154	41.09	-12.43	28.66	40.00	-11.34	QP
3	60.577	46.74	-16.91	29.83	40.00	-10.17	QP
4	222.281	43.58	-10.84	32.74	46.00	-13.26	QP
5	360.977	33.60	-6.46	27.14	46.00	-18.86	QP
6	838.887	35.48	3.71	39.19	46.00	-6.81	QP

Above 1GHz(Peak & Average)
Test Mode2
Horizontal



No.	Frequency (MHz)	Reading (dBµV)	Correction factor (dB/m)	Result (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Detector
1	5783.884	35.89	-0.21	35.68	54.00	-18.32	Average
2	5783.884	47.89	-0.21	47.68	74.00	-26.32	Peak
3	6723.951	36.00	1.25	37.25	54.00	-16.75	Average
4	6723.951	48.00	1.25	49.25	74.00	-24.75	Peak
5	7462.854	37.00	1.33	38.33	54.00	-15.67	Average
6	7462.854	49.00	1.33	50.33	74.00	-23.67	Peak
7	9193.178	36.32	2.88	39.20	54.00	-14.80	Average
8	9193.178	48.32	2.88	51.20	74.00	-22.80	Peak
9	10322.320	48.01	3.37	51.38	74.00	-22.62	Peak
10	10322.320	36.01	3.37	39.38	54.00	-14.62	Average
11	16406.780	46.83	7.84	54.67	74.00	-19.33	Peak
12	16406.780	34.83	7.84	42.67	54.00	-11.33	Average

Vertical



No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	3969.238	37.04	-3.04	34.00	54.00	-20.00	Average
2	3969.238	49.04	-3.04	46.00	74.00	-28.00	Peak
3	6345.543	35.18	0.95	36.13	54.00	-17.87	Average
4	6345.543	47.18	0.95	48.13	74.00	-25.87	Peak
5	7637.782	36.00	1.28	37.28	54.00	-16.72	Average
6	7637.782	48.00	1.28	49.28	74.00	-24.72	Peak
7	10442.590	35.35	3.39	38.74	54.00	-15.26	Average
8	10442.590	47.35	3.39	50.74	74.00	-23.26	Peak
9	15041.450	45.54	7.92	53.46	74.00	-20.54	Peak
10	15041.450	33.54	7.92	41.46	54.00	-12.54	Average
11	16597.950	34.04	8.13	42.17	54.00	-11.83	Average
12	16597.950	46.04	8.13	54.17	74.00	-19.83	Peak

Remark:

1. Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain, the value was added to Original Receiver Reading by the software automatically.
2. Result = Reading + Correct Factor.
3. Margin = Result – Limit
4. For Radiated Emission above 18GHz, there was not any unwanted emission detected.
5. The limit of ICES-003 in the 230MHz to 960MHz band is higher than that of FCC Part 15B, so the radiation emission test data conform to the limit of ICES-003.

6.2 CONDUCTED EMISSION

Test Requirement: FCC 47 CFR Part 15.107
ICES-003 Issue 7 Section 3.2.1

Test Method: ANSI C63.4-2014

Limits:

Limits for Class B devices

Frequency range (MHz)	Limits (dB(μV)	
	Quasi-peak	Average
0,15 to 0,50	66 to 56	56 to 46
0,50 to 5	56	46
5 to 30	60	50

Remark:

1. The lower limit shall apply at the transition frequencies.
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 to 0.50 MHz.

Test Setup: Refer to section 4.3.2 for details.

Test Procedures:

1) The Product was placed on a nonconductive table 0.8 m above the horizontal ground reference plane, and 0.4 m from the vertical ground reference plane, and connected to the main through Line Impedance Stability Network (L.I.S.N).
2) The RBW of the receiver was set at 9 kHz in 150 kHz ~ 30MHz with Peak and AVG detector in Max Hold mode. Run the receiver's pre-scan to record the maximum disturbance generated from Product in all power lines in the full band.
3) For each frequency whose maximum record was higher or close to limit, measure its QP and AVG values and record.

Equipment Used: Refer to section 3 for details.

Test Result: Pass

The worst measurement data as follows:
Quasi Peak and Average:
Test Mode1

Live Line



No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.1548	42.99	9.86	52.85	65.74	-12.89	QP
2	0.1548	23.56	9.86	33.42	55.74	-22.32	AVG
3	0.1914	40.43	9.80	50.23	63.98	-13.75	QP
4	0.1914	21.93	9.80	31.73	53.98	-22.25	AVG
5	0.2455	36.76	9.76	46.52	61.91	-15.39	QP
6	0.2455	18.63	9.76	28.39	51.91	-23.52	AVG
7	0.3852	34.69	9.78	44.47	58.17	-13.70	QP
8	0.3852	9.88	9.78	19.66	48.17	-28.51	AVG
9	0.5155	39.00	9.79	48.79	56.00	-7.21	QP
10	0.5155	27.99	9.79	37.78	46.00	-8.22	AVG
11	1.2162	25.83	9.71	35.54	56.00	-20.46	QP
12	1.2162	9.00	9.71	18.71	46.00	-27.29	AVG

Neutral Line



No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.1545	42.19	9.82	52.01	65.75	-13.74	QP
2	0.1545	22.38	9.82	32.20	55.75	-23.55	AVG
3	0.1860	40.35	9.77	50.12	64.21	-14.09	QP
4	0.1860	17.86	9.77	27.63	54.21	-26.58	AVG
5	0.2310	40.58	9.78	50.36	62.41	-12.05	QP
6	0.2310	18.06	9.78	27.84	52.41	-24.57	AVG
7	0.5144	36.49	9.76	46.25	56.00	-9.75	QP
8	0.5144	29.81	9.76	39.57	46.00	-6.43	AVG
9	0.7710	25.28	9.74	35.02	56.00	-20.98	QP
10	0.7710	10.28	9.74	20.02	46.00	-25.98	AVG
11	1.1760	24.39	9.75	34.14	56.00	-21.86	QP
12	1.1760	9.95	9.75	19.70	46.00	-26.30	AVG

Remark:

1. Correct Factor = LISN Factor + Cable Loss + Pulse Limiter Factor, the value was added to Original Receiver Reading by the software automatically.
2. Result = Reading + Correct Factor.
3. Margin = Result - Limit
4. An initial pre-scan was performed on the Phase and neutral lines with peak detector. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.

APPENDIX 1 PHOTOS OF TEST SETUP

See test photos attached in Appendix 1 for the actual connections between Product and support equipment.

APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS

Refer to Appendix 2 for EUT external and internal photos.

********** End of Report **********

The test report is effective only with both signature and specialized stamp. The result(s) shown in this report refer only to the sample(s) tested. Without written approval of UnionTrust, this report can't be reproduced except in full.