

Test Report No.: 25112601-SE-US-01

## RF Exposure Report

FCC ID: 2AR2STAM6500

Applicant: MMD Hong Kong Holding Limited

Address: Units 1208-11, 12th Floor, C-Bons International Center, 108 Wai Yip Street, Kwun Tong, Kowloon, Hong Kong

Manufacturer: MMD Hong Kong Holding Limited

Address: Units 1208-11, 12th Floor, C-Bons International Center, 108 Wai Yip Street, Kwun Tong, Kowloon, Hong Kong

Product: Micro Music System

Brand(s): PHILIPS or 

Test Model(s): TAM6500/37

Series Model(s): TAM6500, TAM6500/10, TAM6500/05, TAM6500/yy (yy=00-99 or nil, for country code)

Test Date: Dec. 01, 2025 ~ Dec. 24, 2025

Issued Date: Dec. 25, 2025

Issued By: Hwa-Hsing (Dongguan) Testing Co., Ltd.

Address: No.101, Building N1, Yuyuan 2 Road, Yuyuan Industrial Park, HuangJiang Town, Dongguan City, People's Republic of China


Test Firm Registration No.: 915896

Designation No.: CN1255

Standards: FCC Part 2 (Section 2.1091)  
KDB 447498 D01  
IEEE C95.1

The above equipment has been tested by **Hwa-Hsing (Dongguan) Testing Co., Ltd.**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :



Nature Lee

Reviewed by :



Sye Yang

Approved by :



Scott He

"This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. Our report includes all the tests requested by you and the results thereof based upon the information that you provided to us. The report would be invalid without specific stamp of test institute and the signatures of tester and approver."

Lab: [Hwa-Hsing \(Dongguan\) Testing Co., Ltd.](#)Address: [No.101, Building N1, Yuyuan 2 Road, Yuyuan Industrial Park, HuangJiang Town, Dongguan City, People's Republic of China](#)Tel: [0769-85598986](#)Web.: [www.lyns-tci.com](#)E-Mail: [service-hs@lyns-tci.com](#)Release  
[Ver. 1.5](#)

**Table of contents**

|                                                          |   |
|----------------------------------------------------------|---|
| Release control record .....                             | 3 |
| 1 General Information .....                              | 4 |
| 1.1 General Description of EUT .....                     | 4 |
| 2 RF exposure limit .....                                | 5 |
| 2.1 MPE calculation formula .....                        | 5 |
| 3 Calculation result of maximum conducted power .....    | 6 |
| Appendix - Information on the Testing Laboratories ..... | 7 |

Test Report No.: 25112601-SE-US-01

**Release control record**

| Issue No.         | Reason for change | Date issued   |
|-------------------|-------------------|---------------|
| 25112601-SE-US-01 | Original Release  | Dec. 25, 2025 |

**1 General Information****1.1 General Description of EUT**

|                               |                                                                                 |
|-------------------------------|---------------------------------------------------------------------------------|
| Product                       | Micro Music System                                                              |
| Sample No.                    | HX2511260101, HX2511260102                                                      |
| Test Model(s)                 | TAM6500/37                                                                      |
| Series Model(s)               | TAM6500, TAM6500/10, TAM6500/05, TAM6500/yy (yy=00-99 or nil, for country code) |
| Status of EUT                 | Engineering Prototype                                                           |
| Power Supply Rating           | AC 100-240V 50/60Hz 40W                                                         |
| Modulation Type               | GFSK, $\pi/4$ DQPSK, 8DPSK for FHSS<br>GFSK for DTS                             |
| Transfer Rate                 | 1Mbps, 2Mbps, 3Mbps                                                             |
| Operating Frequency           | 2402 ~ 2480MHz                                                                  |
| Number of Channel             | 79 for FHSS<br>40 for DTS                                                       |
| Maximum Output Power          | 7.28dBm (Peak)                                                                  |
| Antenna Type and Antenna Gain | FPC Antenna, 4.27dBi                                                            |
| Antenna Connector             | N/A                                                                             |
| Accessory Device              | AC cable 140cm                                                                  |

**Note:**

1. Please refer to the EUT photo document (Reference No.: 25112601-01&02) for detailed product photo.
2. Hwa-Hsing (Dongguan) Testing Co., Ltd. is not responsible for the accuracy of the information provided by the manufacturer.
3. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.
4. Model differences: These models are only different from model name for trade purpose.

**2 RF exposure limit**

Limits for maximum permissible exposure (MPE)

| Limits for general population / uncontrolled exposure |                                  |                                  |                                        |                           |
|-------------------------------------------------------|----------------------------------|----------------------------------|----------------------------------------|---------------------------|
| Frequency range<br>(MHz)                              | Electric field strength<br>(V/m) | Magnetic field strength<br>(A/m) | Power density<br>(mW/cm <sup>2</sup> ) | Average time<br>(minutes) |
| 300-1500                                              | ...                              | ...                              | F/1500                                 | 30                        |
| 1500-100,000                                          | ...                              | ...                              | 1.0                                    | 30                        |
| Note: F = Frequency in MHz                            |                                  |                                  |                                        |                           |

**2.1 MPE calculation formula**

$$Pd = (Pout * G) / (4 * \pi * r^2)$$

*Where:*Pd = power density in mW/cm<sup>2</sup>

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

**Classification:**

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user.

Test Report No.: 25112601-SE-US-01

**3 Calculation result of maximum conducted power**

The antennas provided to the EUT, please refer to the following table:

| Function | Frequency (MHz) | Antenna Gain (dBi) | Antenna Type | Transmit and Receive Chain | Maximum Power |
|----------|-----------------|--------------------|--------------|----------------------------|---------------|
| BT       | 2402-2480       | 4.27               | FPC          | 1TX,1RX                    | 7.28dBm       |
| BLE      | 2402-2480       | 4.27               | FPC          | 1TX,1RX                    | 4.21dBm       |

| Frequency (MHz) | Max power (mW) | Antenna gain (dBi) | Distance (cm) | Power density (mW/cm <sup>2</sup> ) | Limit (mW/cm <sup>2</sup> ) |
|-----------------|----------------|--------------------|---------------|-------------------------------------|-----------------------------|
| 2402-2480       | 5.3456         | 4.27               | 20            | 0.002843                            | 1.0                         |
| 2402-2480       | 2.6363         | 4.27               | 20            | 0.001402                            | 1.0                         |

**Conclusion:**

Therefore, the worst-case situation is 0.002843mW/cm<sup>2</sup>, which is less than "1". This confirmed that the device compliance with FCC 1.1310 MPE limit.

Test Report No.: 25112601-SE-US-01

**Appendix – Information on the Testing Laboratories**

We, [Hwa-Hsing \(Dongguan\) Testing Co., Ltd.](#), A global provider of TESTING and CERTIFICATION services for consumer products, electronic products and wireless information technology products. Adhering to the core values "HONEST and TRUSTWORTHY, OBJECTIVE and IMPARTIALITY, RIGOROUS and AFFICIENT", commitment to provide professional, perfect and efficient comprehensive ONE-STOP solution of TESTING and CERTIFICATION services for Manufacturers, Buyers, Traders, Brands, Retailers. Assist client to better manage risk, protect their brands, reduce costs and cut time to over 150 markets in global. Our laboratories are FCC recognized accredited test firms and accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lab Address: [No.101, Building N1, Yuyuan 2 Road, Yuyuan Industrial Park, HuangJiang Town, Dongguan City, People's Republic of China](#)

Contact Tel: [0769-85598986](tel:0769-85598986)

Email: [service-hs@lyns-tci.com](mailto:service-hs@lyns-tci.com)

Web Site: [www.lyns-tci.com](http://www.lyns-tci.com)

--- END ---