

# RF EXPOSURE EVALUATION REPORT

**Product Name:** Party Speaker

**Trade Mark:**



PHILIPS or

**Model No.:** TAX200T

**Add. Model No.:**

TAX200T/10, TAX200T/37, TAX200T/61,  
TAX200T/98, TAX200T/78, TAX200T/73,  
TAX200T/yy(yy=00-99 or Nil, for country  
code)

**Report Number:** 26041323828RFC-2

**Test Standards:** FCC 47 CFR Part 2.1091

**FCC ID:** 2AR2STAX200T

**Test Result:** PASS

**Date of Issue:** April 27, 2026

Prepared for:

**MMD Hong Kong Holding Limited**  
**Units 1208-11, 12th Floor, C-Bons International Center, 108 Wai Yip**  
**Street, Kwun Tong, Kowloon, Hong Kong**

Prepared by:

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**  
**16/F., Block A, Building 6, Baoneng Science and Technology Park,**  
**Longhua Street, Longhua District, Shenzhen, Guangdong, China**

**TEL: +86-755-2823 0888**

**FAX: +86-755-2823 0886**

Prepared by:

*David Chen*

David Chen  
Senior Project Engineer

Reviewed by:

*Kevin Liang*

Kevin Liang  
Assistant Manager

Approved by:



Date:

April 27, 2026

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: 16/F., Block A, Building 6, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, Guangdong, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: [info@uttlab.com](mailto:info@uttlab.com)

<http://www.uttlab.com>

UTTR-RF-FCCPART2.1091-V2.0

**Version**

| Version No. | Date           | Description |
|-------------|----------------|-------------|
| V1.0        | April 27, 2026 | Original    |

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: 16/F., Block A, Building 6, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, Guangdong, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: [info@uttlab.com](mailto:info@uttlab.com)<http://www.uttlab.com>UTTR-RF-FCCPART2.1091-V2.0

## CONTENTS

|                                                        |          |
|--------------------------------------------------------|----------|
| <b>1. GENERAL INFORMATION</b>                          | <b>4</b> |
| 1.1 CLIENT INFORMATION                                 | 4        |
| 1.2 EUT INFORMATION                                    | 4        |
| 1.2.2 DESCRIPTION OF ACCESSORIES                       | 4        |
| 1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD  | 4        |
| 1.4 OTHER INFORMATION                                  | 4        |
| 1.5 GENERAL DESCRIPTION OF APPLIED STANDARDS           | 4        |
| 1.6 TEST LOCATION                                      | 5        |
| 1.7 TEST FACILITY                                      | 5        |
| 1.8 DEVIATION FROM STANDARDS                           | 5        |
| 1.9 ABNORMALITIES FROM STANDARD CONDITIONS             | 5        |
| 1.10 OTHER INFORMATION REQUESTED BY THE CUSTOMER       | 5        |
| <b>2. EQUIPMENT LIST</b>                               | <b>5</b> |
| <b>3. RF EXPOSURE EVALUATION</b>                       | <b>6</b> |
| 3.1 REFERENCE DOCUMENTS FOR EVALUATION                 | 6        |
| 3.2 RF EXPOSURE COMPLIANCE REQUIREMENT                 | 6        |
| 3.2.1 DEFINITIONS                                      | 6        |
| 3.2.2 LIMITS                                           | 6        |
| 3.2.3 TEST PROCEDURE                                   | 7        |
| 3.3 RF EXPOSURE EVALUATION CALCULATION RESULTS         | 8        |
| 3.3.1 SINGLE RF SOURCES CALCULATION                    | 8        |
| <b>APPENDIX 1 PHOTOS OF TEST SETUP</b>                 | <b>9</b> |
| <b>APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS</b> | <b>9</b> |

## 1. GENERAL INFORMATION

### 1.1 CLIENT INFORMATION

|                                 |                                                                                                           |
|---------------------------------|-----------------------------------------------------------------------------------------------------------|
| <b>Applicant:</b>               | MMD Hong Kong Holding Limited                                                                             |
| <b>Address of Applicant:</b>    | Units 1208-11, 12th Floor, C-Bons International Center, 108 Wai Yip Street, Kwun Tong, Kowloon, Hong Kong |
| <b>Manufacturer:</b>            | MMD Hong Kong Holding Limited                                                                             |
| <b>Address of Manufacturer:</b> | Units 1208-11, 12th Floor, C-Bons International Center, 108 Wai Yip Street, Kwun Tong, Kowloon, Hong Kong |

### 1.2 EUT INFORMATION

#### 1.2.1 General Description of EUT

|                                                                                                                                                                                                                                                                                                                |                                                                                                                       |                |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------|----------------|
| Product Name:                                                                                                                                                                                                                                                                                                  | Party Speaker                                                                                                         |                |
| Model No.:                                                                                                                                                                                                                                                                                                     | TAX200T                                                                                                               |                |
| Add. Model No.:                                                                                                                                                                                                                                                                                                | TAX200T/10, TAX200T/37, TAX200T/61, TAX200T/98, TAX200T/78, TAX200T/73, TAX200T/yy(yy=00-99 or Nil, for country code) |                |
| Trade Mark:                                                                                                                                                                                                                                                                                                    | <br>PHILIPS or                       |                |
| DUT Stage:                                                                                                                                                                                                                                                                                                     | Identical Prototype                                                                                                   |                |
| Product Category:                                                                                                                                                                                                                                                                                              | Mobile devices                                                                                                        |                |
| EUT Supports Function:<br>(Provided by the customer)                                                                                                                                                                                                                                                           | 2.4 GHz ISM Band:                                                                                                     | Bluetooth V6.0 |
| Sample Received Date:                                                                                                                                                                                                                                                                                          | April 13, 2026                                                                                                        |                |
| <b>Note:</b><br>1. The additional model TAX200T/10, TAX200T/37, TAX200T/61, TAX200T/98, TAX200T/78, TAX200T/73, TAX200T/yy(yy=00-99 or Nil, for country code) is identical with the test model TAX200T except the model number for marketing purpose.<br>2. The ISED certification is only for the main model. |                                                                                                                       |                |

**Remark:** The above EUT's information was provided by customer. Please refer to the specifications or user's manual for more detailed description.

#### 1.2.2 Description of Accessories

Refer to Report 26041323828EMC-1 for accessories.

### 1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD

| EUT Supports Function |                | RF Test Report   |
|-----------------------|----------------|------------------|
| 2.4 GHz ISM Band:     | Bluetooth V6.0 | 26041323828RFC-1 |

### 1.4 OTHER INFORMATION

None.

### 1.5 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product, according to the specifications of the manufacturers. It must comply with the requirements of the following standards:

#### FCC 47 CFR Part 2.1091

All test items have been performed and recorded as per the above standards

#### **Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: 16/F., Block A, Building 6, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, Guangdong, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART2.1091-V2.0

## 1.6 TEST LOCATION

---

### **Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, Guangdong, China  
Telephone: +86 (0) 755 2823 0888  
Fax: +86 (0) 755 2823 0886

---

## 1.7 TEST FACILITY

---

The test facility is recognized, certified, or accredited by the following organizations:

### **CNAS-Lab Code: L9069**

The measuring equipment utilized to perform the tests documented in this report has been calibrated once a year or in accordance with the manufacturer's recommendations, and is traceable under the ISO/IEC 17025 to international or national standards. Equipment has been calibrated by accredited calibration laboratories.

### **A2LA-Lab Certificate No.: 4312.01**

Shenzhen UnionTrust Quality and Technology Co., Ltd. has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

### **ISED Wireless Device Testing Laboratories**

CAB identifier: CN0032

### **FCC Accredited Lab.**

Designation Number: CN1194

Test Firm Registration Number: 259480

---

## 1.8 DEVIATION FROM STANDARDS

None.

## 1.9 ABNORMALITIES FROM STANDARD CONDITIONS

None.

## 1.10 OTHER INFORMATION REQUESTED BY THE CUSTOMER

None.

## 2. EQUIPMENT LIST

Please refer to the RF test report.

### **Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: 16/F., Block A, Building 6, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, Guangdong, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: [info@uttlab.com](mailto:info@uttlab.com)

<http://www.uttlab.com>

UTTR-RF-FCCPART2.1091-V2.0

### 3. RF EXPOSURE EVALUATION

#### 3.1 REFERENCE DOCUMENTS FOR EVALUATION

| No. | Identity                                                | Document Title                                                                                                        |
|-----|---------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------|
| 1   | FCC 47 CFR Part 2.1091                                  | Radiofrequency radiation exposure evaluation: mobile devices.                                                         |
| 2   | FCC 47 CFR Part 1.1307                                  | Actions that may have a significant environmental effect, for which Environmental Assessments (EAs) must be prepared. |
| 3   | FCC 47 CFR Part 1.1310                                  | Radiofrequency radiation exposure limits.                                                                             |
| 4   | KDB 447498 D04 Interim General RF Exposure Guidance v01 | RF EXPOSURE PROCEDURES AND EQUIPMENT AUTHORIZATION POLICIES FOR MOBILE AND PORTABLE DEVICES                           |

#### 3.2 RF EXPOSURE COMPLIANCE REQUIREMENT

##### 3.2.1 Definitions

**Mobile devices:** For purposes of this section, the definitions in § 1.1307(b)(2) of this chapter shall apply. A mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the RF source's radiating structure(s) and the body of the user or nearby persons. In this context, the term "fixed location" means that the device is physically secured at one location and is not able to be easily moved to another location while transmitting. Transmitting devices designed to be used by consumers or workers that can be easily re-located, such as wireless devices associated with a personal desktop computer, are considered to be mobile devices if they meet the 20-centimeter separation requirement.

##### 3.2.2 Limits

###### 3.2.2.1 FCC 47 CFR Part 2.1091

###### ➤ Single RF sources

Evaluation of compliance with the exposure limits in § 1.1310 of this chapter, and preparation of an EA if the limits are exceeded, is necessary for mobile devices with single RF sources having either more than an available maximum time-averaged power of 1 mW or more than the ERP listed in Table 1 to § 1.1307(b)(3)(i)(C), whichever is greater. For mobile devices not exempt by § 1.1307(b)(3)(i)(C) at distances from 20 centimeters to 40 centimeters and frequencies from 0.3 GHz to 6 GHz, evaluation of compliance with the exposure limits in § 1.1310 of this chapter is necessary if the ERP of the device is greater than  $ERP_{20cm}$  in the formula below. If the ERP of a single RF source at distances from 20 centimeters to 40 centimeters and frequencies from 0.3 GHz to 6 GHz is not easily obtained, then the available maximum time-averaged power may be used (i.e., without consideration of ERP) in comparison with the following formula only if the physical dimensions of the radiating structure(s) do not exceed the electrical length of  $\lambda/4$  or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B.1})$$

$d$  = the minimum separation distance (cm) in any direction from any part of the device antenna(s) or radiating structure(s) to the body of the device user.

###### ➤ Multiple mobile or portable RF sources

For multiple mobile or portable RF sources within a device operating in the same time averaging period, routine environmental evaluation is required if the formula in § 1.1307(b)(3)(ii)(B) of this chapter is applied to determine the exemption ratio and the result is greater than 1.

$$\sum_{i=0}^a \frac{P_i}{P_{th,i}} + \sum_{j=0}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=0}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

Where:

a = number of fixed, mobile, or portable RF sources claiming exemption using paragraph (b)(3)(i)(B) of this section for  $P_{th}$ , including existing exempt transmitters and those being added.

b = number of fixed, mobile, or portable RF sources claiming exemption using paragraph (b)(3)(i)(C) of this section for Threshold ERP, including existing exempt transmitters and those being added.

c = number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance including existing evaluated transmitters.

$P_i$  = the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source i at a distance between 0.5 cm and 40 cm (inclusive).

$P_{th,i}$  = the exemption threshold power ( $P_{th}$ ) according to paragraph (b)(3)(i)(B) of this section for fixed, mobile, or portable RF source i.

$ERP_j$  = the ERP of fixed, mobile, or portable RF source j.

$ERP_{th,j}$  = exemption threshold ERP for fixed, mobile, or portable RF source j, at a distance of at least  $\lambda/2\pi$  according to the applicable formula of paragraph (b)(3)(i)(C) of this section.

$Evaluated_k$  = the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation at the location of exposure.

$Exposure\ Limit_k$  = either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable RF source k, as applicable from § 1.1310 of this chapter.

### 3.2.2.2 KDB 447498 D04 V01

**MPE-based Exemption:** General frequency and separation-distance dependent MPE-based effective radiated power (ERP) thresholds are in Table B.1 [Table 1 of § 1.1307(b)(1)(i)(C)] to support an exemption from further evaluation from 300 kHz through 100 GHz.

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B.1})$$

### 3.2.3 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

### 3.3 RF EXPOSURE EVALUATION CALCULATION RESULTS

**Note:**

1. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.

#### 3.3.1 Single RF sources Calculation

| Operating Mode | Freq.     | Tune-up Power (Average) | Tolerance | Antenna Gain | Calculated maximum ERP ( $P_{ant}$ ) |        | RF Exposure limit ( $P_{th}$ ) | Results |
|----------------|-----------|-------------------------|-----------|--------------|--------------------------------------|--------|--------------------------------|---------|
|                | (MHz)     | (dBm)                   | (dB)      | (dBi)        | (dBm)                                | (mW)   | (mW)                           |         |
| Bluetooth      | 2402-2480 | -6.0                    | +1.5/-1.5 | 4.44         | -2.21                                | 0.6012 | 3060.00                        | PASS    |

**Note:**

1). The EIRP and ERP calculated method is shown as below:

EIRP = Average Power + Antenna Gain

ERP = EIRP – 2.15dB

2). The RF Exposure evaluation distance is 20cm.

## APPENDIX 1 PHOTOS OF TEST SETUP

N/A

## APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS

Refer to Appendix 2 for EUT external and internal Photos.

\*\*\* End of Report \*\*\*

---

The test report is effective only with both signature and specialized stamp. The result(s) shown in this report refer only to the sample(s) tested. Without written approval of UnionTrust, this report can't be reproduced except in full.

---