

# 小米生态链产品包装图纸

图纸提供单位

北京米物科技有限公司

项目名称

W05-说明书

版本号

W05 Instructions 20220113

## 设计时间

2022 年 01 月 13 日

设计师

## 材质工艺要求

材质要求:

105g哑粉纸

制作工序:

## 印刷+哑油+模切

### 工艺要求:

模切走位 $\leq \pm 0.5\text{mm}$

颜色及 专色: pantone Cool Gray 11C

## 纹理要求

纹理方向

选择正确的  
方向图标拖  
动到图纸里

如有其它特殊要求，请写明

比例 1:1 单位 mm



## 折叠方式

## 字体

中文  
大标题: 方正兰亭准黑简体 9pt  
内 容: 方正兰亭细黑简体 6pt

英文  
大标题: 方正兰亭准黑简体 9pt  
小标题: 方正兰亭中粗黑简体 6pt  
内 容: 方正兰亭细黑简体 6pt



**FCC Caution:**

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Any Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

**Note:** This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

The device has been evaluated to meet general RF exposure requirement. The device can be used in portable exposure condition without restriction.