

CALEX TECH INC.

10F.-5, NO.2, FUXING 4TH RD., QIANZHEN DIST.,Kaohsiung
City,80761,Taiwan

Declaration of the Modular Approval

Applicant / Grantee	CALEX TECH INC.
FCC ID:	2AR5FDONGLEBLE5
Model:	DongleBLE5

The single module transmitter has been evaluated then tested meeting the requirements under Part 15C Section 2.12 as below:

Modular approval requirement	EUT Condition	Comply
(a) The radio elements of the modular transmitter must have their own shielding. The physical crystal and tuning capacitors may be located external to the shielded radio elements.	No shielded	NA
(b) The modular transmitter must have buffered modulation/data inputs (if such inputs are provided) to ensure that the module will comply with part 15 requirements under conditions of excessive data rates or over-modulation.	Buffers are within the SoC chip nRF52840	V
(c)The modular transmitter must have its own powersupply regulation.	The power regulation is integrated within the SoC chip nRF52840	V
(d) The modular transmitter must comply with the antenna and transmission system requirements of Sections 15.203, 15.204(b) and 15.204(c). The antenna must either be permanently attached or employ a "unique" antenna coupler (at all connections between the module and the antenna, including the cable). The "professional installation" provision of Section 15.203 is not applicable to modules but can apply to limited modular approvals under paragraph (b) of this section.	The antenna is a PCB antenna and permanently printed on the circuit board.	V
(e)The modular transmitter must be tested in a stand-alone configuration, i.e., the module must not be inside another device during testing for compliance with part 15 requirements. Unless	No stand-alone Host information: Product Name : LED Driver Box Brand name: CALEX TECH	NA

CALEX TECH INC.

10F.-5, NO.2, FUXING 4TH RD., QIANZHEN DIST.,Kaohsiung
City,80761,Taiwan

the transmitter module will be battery powered, it must comply with the AC line conducted requirements found in Section 15.207. AC or DC power lines and data input/output lines connected to the module must not contain ferrites, unless they will be marketed with the module (see Section 15.27(a)). The length of these lines shall be the length typical of actual use or, if that length is unknown, at least 10 centimeters to insure that there is no coupling between the case of the module and supporting equipment. Any accessories, peripherals, or support equipment connected to the module during testing shall be unmodified and commercially available (see Section 15.31(i)) must not be inside another device during testing.	Model Name: DongleBLE5	
(f)The modular transmitter must be equipped with either a permanently affixed label or must be capable of electronically displaying its FCC identification number.	We will make FCC label sticker. The FCC label will stick on the transmitter.	V
(g) The modular transmitter must comply with any specific rules or operating requirements that ordinarily apply to a complete transmitter and the manufacturer must provide adequate instructions along with the module to explain any such requirements. A copy of these instructions must be included in the application for equipment authorization requirements, which are based on the intended use/configurations.	Operation manual is included	V
(h)The modular transmitter must comply with any applicable RF exposure requirements in its final configuration.	The modular transmitter complies all the RF exposure requirements in its final configuration	V

CALEX TECH INC.

10F.-5, NO.2, FUXING 4TH RD., QIANZHEN DIST.,Kaohsiung
City,80761,Taiwan

Dated **2019**
 /3/18

By: Mabel Chen **Mabel Chen**
 Signature **Printed**

Title: **N/A**
 CALEX TECH INC.

On behalf of : **(Company Name)**

Telephone: **+886 7 3385372**