

Calibration Laboratory of
Schmid & Partner
Engineering AG
 Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
 Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
 The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Glossary:

TSL	tissue simulating liquid
NORM _{x,y,z}	sensitivity in free space
ConvF	sensitivity in TSL / NORM _{x,y,z}
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A, B, C, D	modulation dependent linearization parameters
Polarization ϕ	ϕ rotation around probe axis
Polarization θ	θ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\theta = 0$ is normal to probe axis
Connector Angle	information used in DASY system to align probe sensor X to the robot coordinate system

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Measurement procedure for the assessment of Specific Absorption Rate (SAR) from hand-held and body-mounted devices used next to the ear (frequency range of 300 MHz to 6 GHz)", July 2016
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Methods Applied and Interpretation of Parameters:

- NORM_{x,y,z}:** Assessed for E-field polarization $\theta = 0$ ($f \leq 900$ MHz in TEM-cell; $f > 1800$ MHz: R22 waveguide). NORM_{x,y,z} are only intermediate values, i.e., the uncertainties of NORM_{x,y,z} does not affect the E²-field uncertainty inside TSL (see below ConvF).
- NORM(f)_{x,y,z} = NORM_{x,y,z} * frequency_response** (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP_{x,y,z}:** DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- PAR:** PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- A_{x,y,z}; B_{x,y,z}; C_{x,y,z}; D_{x,y,z}; VR_{x,y,z}:** A, B, C, D are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters:** Assessed in flat phantom using E-field (or Temperature Transfer Standard for $f \leq 800$ MHz) and inside waveguide using analytical field distributions based on power measurements for $f > 800$ MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM_{x,y,z} * ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz.
- Spherical isotropy (3D deviation from isotropy):** in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset:** The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle:** The angle is assessed using the information gained by determining the NORM_x (no uncertainty required).

EX3DV4 – SN:7346

February 28, 2018

Probe EX3DV4

SN:7346

Manufactured:	October 13, 2014
Repaired:	February 19, 2018
Calibrated:	February 28, 2018

Calibrated for DASY/EASY Systems
(Note: non-compatible with DASY2 system!)

EX3DV4- SN:7346

February 28, 2018

DASY/EASY - Parameters of Probe: EX3DV4 - SN:7346**Basic Calibration Parameters**

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm ($\mu\text{V}/(\text{V}/\text{m})^2$) ^A	0.46	0.47	0.48	$\pm 10.1 \%$
DCP (mV) ^B	100.0	102.9	99.7	

Modulation Calibration Parameters

UID	Communication System Name		A dB	B dB $\sqrt{\mu\text{V}}$	C	D dB	VR mV	Unc ^E (k=2)
0	CW	X	0.0	0.0	1.0	0.00	148.2	$\pm 3.0 \%$
		Y	0.0	0.0	1.0		139.8	
		Z	0.0	0.0	1.0		139.3	

Note: For details on UID parameters see Appendix.

Sensor Model Parameters

	C1 fF	C2 fF	α V^{-1}	T1 $\text{ms}\cdot\text{V}^{-2}$	T2 $\text{ms}\cdot\text{V}^{-1}$	T3 ms	T4 V^{-2}	T5 V^{-1}	T6
X	35.30	261.2	35.06	7.248	0.016	5.034	1.798	0.079	1.006
Y	34.75	261.4	35.94	6.021	0.263	5.073	0.000	0.421	1.007
Z	48.88	364.7	35.56	12.29	0.261	5.100	0.367	0.451	1.005

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

^A The uncertainties of Norm X,Y,Z do not affect the E^2 -field uncertainty inside TSL (see Pages 5 and 6).^B Numerical linearization parameter: uncertainty not required.^E Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

EX3DV4- SN:7346

February 28, 2018

DASY/EASY - Parameters of Probe: EX3DV4 - SN:7346**Calibration Parameter Determined in Head Tissue Simulating Media**

f (MHz) ^c	Relative Permittivity ^f	Conductivity (S/m) ^f	ConvF X	ConvF Y	ConvF Z	Alpha ^g	Depth (mm) ^g	Unc (k=2)
750	41.9	0.89	10.36	10.36	10.36	0.55	0.80	± 12.0 %
835	41.5	0.90	10.02	10.02	10.02	0.46	0.80	± 12.0 %
900	41.5	0.97	9.79	9.79	9.79	0.34	1.04	± 12.0 %
1450	40.5	1.20	8.83	8.83	8.83	0.33	0.80	± 12.0 %
1750	40.1	1.37	8.81	8.81	8.81	0.45	0.81	± 12.0 %
1900	40.0	1.40	8.46	8.46	8.46	0.38	0.85	± 12.0 %
2000	40.0	1.40	8.33	8.33	8.33	0.37	0.85	± 12.0 %
2300	39.5	1.67	7.87	7.87	7.87	0.30	0.89	± 12.0 %
2450	39.2	1.80	7.49	7.49	7.49	0.34	0.91	± 12.0 %
2600	39.0	1.96	7.35	7.35	7.35	0.42	0.87	± 12.0 %
3500	37.9	2.91	7.40	7.40	7.40	0.20	1.20	± 13.1 %
5250	35.9	4.71	5.49	5.49	5.49	0.40	1.80	± 13.1 %
5600	35.5	5.07	4.97	4.97	4.97	0.40	1.80	± 13.1 %
5750	35.4	5.22	5.12	5.12	5.12	0.40	1.80	± 13.1 %

^c Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.

^f At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

^g Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

EX3DV4- SN:7346

February 28, 2018

DASY/EASY - Parameters of Probe: EX3DV4 - SN:7346**Calibration Parameter Determined in Body Tissue Simulating Media**

f (MHz) ^c	Relative Permittivity ^f	Conductivity (S/m) ^f	ConvF X	ConvF Y	ConvF Z	Alpha ^g	Depth ^d (mm)	Unc (k=2)
750	55.5	0.96	10.16	10.16	10.16	0.69	0.80	± 12.0 %
835	55.2	0.97	9.95	9.95	9.95	0.65	0.80	± 12.0 %
900	55.0	1.05	9.79	9.79	9.79	0.58	0.80	± 12.0 %
1450	54.0	1.30	8.95	8.95	8.95	0.30	0.80	± 12.0 %
1750	53.4	1.49	8.45	8.45	8.45	0.40	0.80	± 12.0 %
1900	53.3	1.52	8.04	8.04	8.04	0.40	0.85	± 12.0 %
2000	53.3	1.52	8.20	8.20	8.20	0.42	0.80	± 12.0 %
2300	52.9	1.81	7.89	7.89	7.89	0.36	0.88	± 12.0 %
2450	52.7	1.95	7.78	7.78	7.78	0.34	0.87	± 12.0 %
2600	52.5	2.16	7.44	7.44	7.44	0.24	0.99	± 12.0 %
3500	51.3	3.31	7.21	7.21	7.21	0.30	1.20	± 13.1 %
5250	48.9	5.36	5.06	5.06	5.06	0.50	1.90	± 13.1 %
5600	48.5	5.77	4.35	4.35	4.35	0.50	1.90	± 13.1 %
5750	48.3	5.94	4.52	4.52	4.52	0.50	1.90	± 13.1 %

^c Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.


^f At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

^g Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

EX3DV4-- SN:7346

February 28, 2018

Frequency Response of E-Field (TEM-Cell:ifi110 EXX, Waveguide: R22)




Uncertainty of Frequency Response of E-field: $\pm 6.3\%$ ($k=2$)

EX3DV4—SN:7346

February 28, 2018

Receiving Pattern (ϕ), $\theta = 0^\circ$





Uncertainty of Axial Isotropy Assessment: $\pm 0.5\%$ ($k=2$)

EX3DV4- SN:7346

February 28, 2018


Dynamic Range $f(\text{SAR}_{\text{head}})$ (TEM cell, $f_{\text{eval}} = 1900 \text{ MHz}$)

Uncertainty of Linearity Assessment: $\pm 0.6\%$ ($k=2$)


EX3DV4- SN:7346

February 28, 2018

Conversion Factor Assessment



Deviation from Isotropy in Liquid Error (ϕ , θ), f = 900 MHz



EX3DV4- SN:7346

February 28, 2018

DASY/EASY - Parameters of Probe: EX3DV4 - SN:7346**Other Probe Parameters**

Sensor Arrangement	Triangular
Connector Angle (°)	94.5
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	337 mm
Probe Body Diameter	10 mm
Tip Length	9 mm
Tip Diameter	2.5 mm
Probe Tip to Sensor X Calibration Point	1 mm
Probe Tip to Sensor Y Calibration Point	1 mm
Probe Tip to Sensor Z Calibration Point	1 mm
Recommended Measurement Distance from Surface	1.4 mm

EX3DV4- SN:7346

February 28, 2018

Appendix: Modulation Calibration Parameters

UID	Communication System Name		A dB	B dB-μV	C	D dB	VR mV	Max Unc ^E (k=2)
0	CW	X	0.00	0.00	1.00	0.00	148.2	± 3.0 %
		Y	0.00	0.00	1.00		139.8	
		Z	0.00	0.00	1.00		139.3	
10010- CAA	SAR Validation (Square, 100ms, 10ms)	X	1.45	62.36	7.50	10.00	20.0	± 9.6 %
		Y	1.75	63.39	8.41		20.0	
		Z	4.78	74.29	13.78		20.0	
10011- CAB	UMTS-FDD (WCDMA)	X	0.97	67.45	15.08	0.00	150.0	± 9.6 %
		Y	0.79	64.77	12.99		150.0	
		Z	1.01	67.14	15.06		150.0	
10012- CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps)	X	1.11	63.62	15.02	0.41	150.0	± 9.6 %
		Y	1.03	62.69	14.14		150.0	
		Z	1.15	63.81	15.26		150.0	
10013- CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps)	X	4.64	66.70	16.95	1.46	150.0	± 9.6 %
		Y	4.60	66.58	16.85		150.0	
		Z	4.88	66.71	17.15		150.0	
10021- DAC	GSM-FDD (TDMA, GMSK)	X	100.00	105.35	22.47	9.39	50.0	± 9.6 %
		Y	100.00	109.25	24.62		50.0	
		Z	100.00	116.92	28.43		50.0	
10023- DAC	GPRS-FDD (TDMA, GMSK, TN 0)	X	100.00	104.76	22.25	9.57	50.0	± 9.6 %
		Y	100.00	108.58	24.38		50.0	
		Z	100.00	116.29	28.20		50.0	
10024- DAC	GPRS-FDD (TDMA, GMSK, TN 0-1)	X	100.00	105.70	21.57	6.56	60.0	± 9.6 %
		Y	100.00	109.40	23.45		60.0	
		Z	100.00	119.07	28.36		60.0	
10025- DAC	EDGE-FDD (TDMA, 8PSK, TN 0)	X	4.44	75.57	29.75	12.57	50.0	± 9.6 %
		Y	3.69	67.94	25.02		50.0	
		Z	6.34	85.87	35.21		50.0	
10026- DAC	EDGE-FDD (TDMA, 8PSK, TN 0-1)	X	6.05	85.54	30.98	9.56	60.0	± 9.6 %
		Y	5.87	83.75	30.00		60.0	
		Z	10.63	98.33	36.00		60.0	
10027- DAC	GPRS-FDD (TDMA, GMSK, TN 0-1-2)	X	100.00	108.03	21.85	4.80	80.0	± 9.6 %
		Y	100.00	110.36	22.99		80.0	
		Z	100.00	122.50	29.06		80.0	
10028- DAC	GPRS-FDD (TDMA, GMSK, TN 0-1-2-3)	X	100.00	112.09	22.91	3.55	100.0	± 9.6 %
		Y	100.00	110.62	22.34		100.0	
		Z	100.00	127.03	30.23		100.0	
10029- DAC	EDGE-FDD (TDMA, 8PSK, TN 0-1-2)	X	3.98	75.54	25.39	7.80	80.0	± 9.6 %
		Y	3.95	74.85	24.97		80.0	
		Z	6.00	83.77	29.04		80.0	
10030- CAA	IEEE 802.15.1 Bluetooth (GFSK, DH1)	X	100.00	103.91	20.36	5.30	70.0	± 9.6 %
		Y	100.00	106.89	21.82		70.0	
		Z	100.00	118.49	27.64		70.0	
10031- CAA	IEEE 802.15.1 Bluetooth (GFSK, DH3)	X	100.00	103.39	18.21	1.88	100.0	± 9.6 %
		Y	0.23	60.59	4.86		100.0	
		Z	100.00	127.69	28.89		100.0	

Appendix B: DAE and Probe Calibration Certificate

EX3DV4- SN:7346

February 28, 2018

10032-CAA	IEEE 802.15.1 Bluetooth (GFSK, DH5)	X	100.00	108.99	19.60	1.17	100.0	± 9.6 %
		Y	17.88	185.55	8.98		100.0	
		Z	100.00	136.71	31.30		100.0	
10033-CAA	IEEE 802.15.1 Bluetooth (Pi/4-DQPSK, DH1)	X	12.79	96.47	24.86	5.30	70.0	± 9.6 %
		Y	13.57	96.91	24.99		70.0	
		Z	100.00	134.23	36.96		70.0	
10034-CAA	IEEE 802.15.1 Bluetooth (Pi/4-DQPSK, DH3)	X	2.37	74.93	16.07	1.88	100.0	± 9.6 %
		Y	1.68	70.39	13.82		100.0	
		Z	5.54	87.73	22.56		100.0	
10035-CAA	IEEE 802.15.1 Bluetooth (Pi/4-DQPSK, DH5)	X	1.59	70.89	14.19	1.17	100.0	± 9.6 %
		Y	1.12	66.56	11.71		100.0	
		Z	2.66	77.84	18.73		100.0	
10036-CAA	IEEE 802.15.1 Bluetooth (8-DPSK, DH1)	X	24.14	105.98	27.55	5.30	70.0	± 9.6 %
		Y	26.94	107.15	27.86		70.0	
		Z	100.00	134.77	37.21		70.0	
10037-CAA	IEEE 802.15.1 Bluetooth (8-DPSK, DH3)	X	2.07	73.40	15.48	1.88	100.0	± 9.6 %
		Y	1.53	69.38	13.39		100.0	
		Z	4.94	86.18	22.03		100.0	
10038-CAA	IEEE 802.15.1 Bluetooth (8-DPSK, DH5)	X	1.60	71.24	14.48	1.17	100.0	± 9.6 %
		Y	1.13	66.80	11.96		100.0	
		Z	2.70	78.31	19.03		100.0	
10039-CAB	CDMA2000 (1xRTT, RC1)	X	1.31	69.04	12.98	0.00	150.0	± 9.6 %
		Y	0.81	63.61	9.56		150.0	
		Z	1.78	71.59	15.48		150.0	
10042-CAB	IS-54 / IS-136 FDD (TDMA/FDM, Pi/4-DQPSK, Halfrate)	X	100.00	102.07	20.31	7.78	50.0	± 9.6 %
		Y	100.00	104.84	21.79		50.0	
		Z	100.00	113.46	26.10		50.0	
10044-CAA	IS-91/EIA/TIA-553 FDD (FDMA, FM)	X	0.00	106.61	6.98	0.00	150.0	± 9.6 %
		Y	0.08	122.01	6.38		150.0	
		Z	0.00	105.01	6.87		150.0	
10048-CAA	DECT (TDD, TDMA/FDM, GFSK, Full Slot, 24)	X	7.44	74.51	14.94	13.80	25.0	± 9.6 %
		Y	19.01	85.89	19.55		25.0	
		Z	100.00	113.17	28.20		25.0	
10049-CAA	DECT (TDD, TDMA/FDM, GFSK, Double Slot, 12)	X	10.22	80.42	15.97	10.79	40.0	± 9.6 %
		Y	52.51	99.89	22.41		40.0	
		Z	100.00	114.06	27.50		40.0	
10056-CAA	UMTS-TDD (TD-SCDMA, 1.28 Mcps)	X	100.00	119.57	30.50	9.03	50.0	± 9.6 %
		Y	70.07	114.86	29.74		50.0	
		Z	100.00	127.82	35.22		50.0	
10058-DAC	EDGE-FDD (TDMA, 8PSK, TN 0-1-2-3)	X	3.28	71.70	22.78	6.55	100.0	± 9.6 %
		Y	3.25	71.24	22.50		100.0	
		Z	4.54	77.63	25.56		100.0	
10059-CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 2 Mbps)	X	1.11	64.39	15.49	0.61	110.0	± 9.6 %
		Y	1.03	63.44	14.62		110.0	
		Z	1.19	65.01	16.00		110.0	
10060-CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 5.5 Mbps)	X	6.99	102.47	27.83	1.30	110.0	± 9.6 %
		Y	3.10	88.65	22.90		110.0	
		Z	100.00	143.08	37.80		110.0	

Certificate No: EX3-7346_Feb18

Page 13 of 39

Appendix B: DAE and Probe Calibration Certificate

EX3DV4- SN:7346

February 28, 2018

10061-CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps)	X	1.88	75.91	20.78	2.04	110.0	± 9.6 %
		Y	1.76	74.64	20.01		110.0	
		Z	3.51	85.66	24.89		110.0	
10062-CAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 6 Mbps)	X	4.46	66.72	16.40	0.49	100.0	± 9.6 %
		Y	4.38	66.48	16.20		100.0	
		Z	4.68	66.67	16.53		100.0	
10063-CAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 9 Mbps)	X	4.47	66.80	16.49	0.72	100.0	± 9.6 %
		Y	4.40	66.58	16.31		100.0	
		Z	4.70	66.78	16.65		100.0	
10064-CAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 12 Mbps)	X	4.71	67.00	16.69	0.86	100.0	± 9.6 %
		Y	4.64	66.80	16.53		100.0	
		Z	4.99	67.06	16.89		100.0	
10065-CAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 18 Mbps)	X	4.57	66.82	16.75	1.21	100.0	± 9.6 %
		Y	4.52	66.66	16.62		100.0	
		Z	4.86	66.97	17.01		100.0	
10066-CAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 24 Mbps)	X	4.57	66.80	16.89	1.46	100.0	± 9.6 %
		Y	4.53	66.67	16.79		100.0	
		Z	4.88	67.00	17.19		100.0	
10067-CAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 36 Mbps)	X	4.85	67.05	17.36	2.04	100.0	± 9.6 %
		Y	4.82	66.98	17.31		100.0	
		Z	5.17	67.15	17.65		100.0	
10068-CAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 48 Mbps)	X	4.87	66.93	17.51	2.55	100.0	± 9.6 %
		Y	4.85	66.90	17.48		100.0	
		Z	5.22	67.24	17.90		100.0	
10069-CAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 54 Mbps)	X	4.94	66.95	17.69	2.67	100.0	± 9.6 %
		Y	4.92	66.93	17.68		100.0	
		Z	5.30	67.21	18.09		100.0	
10071-CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 9 Mbps)	X	4.72	66.74	17.23	1.99	100.0	± 9.6 %
		Y	4.69	66.66	17.17		100.0	
		Z	4.97	66.80	17.48		100.0	
10072-CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 12 Mbps)	X	4.67	66.95	17.40	2.30	100.0	± 9.6 %
		Y	4.64	66.90	17.36		100.0	
		Z	4.95	67.15	17.72		100.0	
10073-CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 18 Mbps)	X	4.71	67.09	17.72	2.83	100.0	± 9.6 %
		Y	4.70	67.08	17.71		100.0	
		Z	5.01	67.31	18.07		100.0	
10074-CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 24 Mbps)	X	4.71	67.00	17.86	3.30	100.0	± 9.6 %
		Y	4.71	67.03	17.88		100.0	
		Z	4.98	67.18	18.23		100.0	
10075-CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 36 Mbps)	X	4.71	66.97	18.10	3.82	90.0	± 9.6 %
		Y	4.72	67.03	18.14		90.0	
		Z	5.02	67.31	18.57		90.0	
10076-CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 48 Mbps)	X	4.74	66.82	18.25	4.15	90.0	± 9.6 %
		Y	4.76	66.90	18.31		90.0	
		Z	5.02	67.05	18.67		90.0	
10077-CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 54 Mbps)	X	4.77	66.90	18.36	4.30	90.0	± 9.6 %
		Y	4.79	67.00	18.43		90.0	
		Z	5.04	67.10	18.76		90.0	

Certificate No: EX3-7346_Feb18

Page 14 of 39

Appendix B: DAE and Probe Calibration Certificate

EX3DV4- SN:7346

February 28, 2018

10081-CAB	CDMA2000 (1xRTT, RC3)	X	0.63	64.01	10.12	0.00	150.0	± 9.6 %
		Y	0.44	60.72	7.30		150.0	
		Z	0.61	65.60	12.31		150.0	
10082-CAB	IS-54 / IS-136 FDD (TDMA/FDM, PI/4-QPSK, Fullrate)	X	0.59	60.00	3.05	4.77	80.0	± 9.6 %
		Y	0.59	60.00	3.19		80.0	
		Z	0.67	60.00	4.44		80.0	
10090-DAC	GPRS-FDD (TDMA, GMSK, TN 0-4)	X	100.00	105.72	21.60	6.56	60.0	± 9.6 %
		Y	100.00	109.52	23.52		60.0	
		Z	100.00	119.12	28.40		60.0	
10097-CAB	UMTS-FDD (HSDPA)	X	1.79	68.41	15.60	0.00	150.0	± 9.6 %
		Y	1.57	66.45	14.19		150.0	
		Z	1.80	67.50	15.55		150.0	
10098-CAB	UMTS-FDD (HSUPA, Subtest 2)	X	1.75	68.35	15.57	0.00	150.0	± 9.6 %
		Y	1.53	66.38	14.15		150.0	
		Z	1.77	67.46	15.52		150.0	
10099-DAC	EDGE-FDD (TDMA, 8PSK, TN 0-4)	X	6.10	85.72	31.04	9.56	60.0	± 9.6 %
		Y	5.91	83.90	30.06		60.0	
		Z	10.74	98.57	36.08		60.0	
10100-CAD	LTE-FDD (SC-FDMA, 100% RB, 20 MHz, QPSK)	X	2.95	70.13	16.66	0.00	150.0	± 9.6 %
		Y	2.70	68.66	15.71		150.0	
		Z	3.11	70.25	16.60		150.0	
10101-CAD	LTE-FDD (SC-FDMA, 100% RB, 20 MHz, 16-QAM)	X	3.08	67.39	15.84	0.00	150.0	± 9.6 %
		Y	2.93	66.61	15.25		150.0	
		Z	3.23	67.46	15.86		150.0	
10102-CAD	LTE-FDD (SC-FDMA, 100% RB, 20 MHz, 64-QAM)	X	3.19	67.41	15.94	0.00	150.0	± 9.6 %
		Y	3.04	66.68	15.39		150.0	
		Z	3.33	67.43	15.95		150.0	
10103-CAD	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, QPSK)	X	5.10	74.07	19.98	3.98	65.0	± 9.6 %
		Y	5.15	74.22	20.08		65.0	
		Z	6.72	77.66	21.60		65.0	
10104-CAD	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 16-QAM)	X	5.13	71.79	19.66	3.98	65.0	± 9.6 %
		Y	5.05	71.43	19.52		65.0	
		Z	6.22	74.23	20.95		65.0	
10105-CAD	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 64-QAM)	X	4.81	70.26	19.25	3.98	65.0	± 9.6 %
		Y	4.89	70.53	19.40		65.0	
		Z	6.06	73.55	20.96		65.0	
10108-CAE	LTE-FDD (SC-FDMA, 100% RB, 10 MHz, QPSK)	X	2.54	69.46	16.48	0.00	150.0	± 9.6 %
		Y	2.31	67.97	15.47		150.0	
		Z	2.72	69.46	16.42		150.0	
10109-CAE	LTE-FDD (SC-FDMA, 100% RB, 10 MHz, 16-QAM)	X	2.72	67.37	15.70	0.00	150.0	± 9.6 %
		Y	2.57	66.45	15.00		150.0	
		Z	2.88	67.29	15.76		150.0	
10110-CAE	LTE-FDD (SC-FDMA, 100% RB, 5 MHz, QPSK)	X	2.03	68.69	15.97	0.00	150.0	± 9.6 %
		Y	1.81	66.98	14.76		150.0	
		Z	2.20	68.54	16.02		150.0	
10111-CAE	LTE-FDD (SC-FDMA, 100% RB, 5 MHz, 16-QAM)	X	2.47	68.63	15.96	0.00	150.0	± 9.6 %
		Y	2.26	67.23	14.95		150.0	
		Z	2.60	68.06	16.02		150.0	

Certificate No: EX3-7346_Feb18

Page 15 of 39

Appendix B: DAE and Probe Calibration Certificate

EX3DV4- SN:7346

February 28, 2018

10112-CAE	LTE-FDD (SC-FDMA, 100% RB, 10 MHz, 64-QAM)	X	2.85	67.44	15.78	0.00	150.0	± 9.6 %
		Y	2.70	66.58	15.12		150.0	
		Z	3.01	67.29	15.82		150.0	
10113-CAE	LTE-FDD (SC-FDMA, 100% RB, 5 MHz, 64-QAM)	X	2.62	68.82	16.10	0.00	150.0	± 9.6 %
		Y	2.40	67.49	15.14		150.0	
		Z	2.75	68.20	16.16		150.0	
10114-CAC	IEEE 802.11n (HT Greenfield, 13.5 Mbps, BPSK)	X	4.92	67.13	16.37	0.00	150.0	± 9.6 %
		Y	4.84	66.82	16.13		150.0	
		Z	5.11	67.15	16.38		150.0	
10115-CAC	IEEE 802.11n (HT Greenfield, 81 Mbps, 16-QAM)	X	5.17	67.19	16.41	0.00	150.0	± 9.6 %
		Y	5.08	66.90	16.18		150.0	
		Z	5.41	67.30	16.47		150.0	
10116-CAC	IEEE 802.11n (HT Greenfield, 135 Mbps, 64-QAM)	X	5.01	67.32	16.40	0.00	150.0	± 9.6 %
		Y	4.91	67.00	16.15		150.0	
		Z	5.21	67.35	16.41		150.0	
10117-CAC	IEEE 802.11n (HT Mixed, 13.5 Mbps, BPSK)	X	4.92	67.08	16.37	0.00	150.0	± 9.6 %
		Y	4.83	66.76	16.12		150.0	
		Z	5.08	67.02	16.34		150.0	
10118-CAC	IEEE 802.11n (HT Mixed, 81 Mbps, 16-QAM)	X	5.24	67.37	16.50	0.00	150.0	± 9.6 %
		Y	5.15	67.10	16.28		150.0	
		Z	5.49	67.50	16.58		150.0	
10119-CAC	IEEE 802.11n (HT Mixed, 135 Mbps, 64-QAM)	X	5.00	67.31	16.40	0.00	150.0	± 9.6 %
		Y	4.91	67.00	16.16		150.0	
		Z	5.18	67.29	16.39		150.0	
10140-CAD	LTE-FDD (SC-FDMA, 100% RB, 15 MHz, 16-QAM)	X	3.20	67.43	15.85	0.00	150.0	± 9.6 %
		Y	3.06	66.69	15.30		150.0	
		Z	3.37	67.43	15.88		150.0	
10141-CAD	LTE-FDD (SC-FDMA, 100% RB, 15 MHz, 64-QAM)	X	3.33	67.59	16.05	0.00	150.0	± 9.6 %
		Y	3.19	66.89	15.52		150.0	
		Z	3.49	67.53	16.04		150.0	
10142-CAD	LTE-FDD (SC-FDMA, 100% RB, 3 MHz, QPSK)	X	1.79	68.65	15.30	0.00	150.0	± 9.6 %
		Y	1.53	66.43	13.74		150.0	
		Z	1.98	68.50	15.67		150.0	
10143-CAD	LTE-FDD (SC-FDMA, 100% RB, 3 MHz, 16-QAM)	X	2.28	69.10	15.14	0.00	150.0	± 9.6 %
		Y	1.96	66.88	13.65		150.0	
		Z	2.46	68.77	15.73		150.0	
10144-CAD	LTE-FDD (SC-FDMA, 100% RB, 3 MHz, 64-QAM)	X	1.94	65.97	13.06	0.00	150.0	± 9.6 %
		Y	1.73	64.50	11.90		150.0	
		Z	2.23	66.53	14.15		150.0	
10145-CAE	LTE-FDD (SC-FDMA, 100% RB, 1.4 MHz, QPSK)	X	0.78	61.55	8.19	0.00	150.0	± 9.6 %
		Y	0.64	60.00	6.61		150.0	
		Z	1.21	65.05	11.79		150.0	
10146-CAE	LTE-FDD (SC-FDMA, 100% RB, 1.4 MHz, 16-QAM)	X	1.07	61.11	7.04	0.00	150.0	± 9.6 %
		Y	0.91	60.04	6.31		150.0	
		Z	1.79	65.28	11.17		150.0	
10147-CAE	LTE-FDD (SC-FDMA, 100% RB, 1.4 MHz, 64-QAM)	X	1.13	61.56	7.38	0.00	150.0	± 9.6 %
		Y	0.95	60.33	6.56		150.0	
		Z	2.04	66.88	12.09		150.0	

Certificate No: EX3-7346_Feb18

Page 16 of 39

Appendix B: DAE and Probe Calibration Certificate

EX3DV4- SN:7346

February 28, 2018

10149-CAD	LTE-FDD (SC-FDMA, 50% RB, 20 MHz, 16-QAM)	X	2.73	67.44	15.75	0.00	150.0	± 9.6 %
		Y	2.58	66.52	15.05		150.0	
		Z	2.89	67.35	15.80		150.0	
10150-CAD	LTE-FDD (SC-FDMA, 50% RB, 20 MHz, 64-QAM)	X	2.86	67.50	15.83	0.00	150.0	± 9.6 %
		Y	2.71	66.64	15.17		150.0	
		Z	3.02	67.34	15.86		150.0	
10151-CAD	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, QPSK)	X	5.41	77.06	21.27	3.98	65.0	± 9.6 %
		Y	5.28	76.61	21.11		65.0	
		Z	7.06	80.28	22.78		65.0	
10152-CAD	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 16-QAM)	X	4.66	71.71	19.22	3.98	65.0	± 9.6 %
		Y	4.58	71.35	19.06		65.0	
		Z	5.79	74.35	20.76		65.0	
10153-CAD	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 64-QAM)	X	5.02	72.83	20.10	3.98	65.0	± 9.6 %
		Y	4.95	72.53	19.98		65.0	
		Z	6.14	75.24	21.50		65.0	
10154-CAE	LTE-FDD (SC-FDMA, 50% RB, 10 MHz, QPSK)	X	2.08	69.08	16.21	0.00	150.0	± 9.6 %
		Y	1.84	67.31	14.97		150.0	
		Z	2.25	68.95	16.28		150.0	
10155-CAE	LTE-FDD (SC-FDMA, 50% RB, 10 MHz, 16-QAM)	X	2.48	68.67	15.99	0.00	150.0	± 9.6 %
		Y	2.26	67.27	14.98		150.0	
		Z	2.60	68.07	16.04		150.0	
10156-CAE	LTE-FDD (SC-FDMA, 50% RB, 5 MHz, QPSK)	X	1.61	68.38	14.72	0.00	150.0	± 9.6 %
		Y	1.33	65.75	12.89		150.0	
		Z	1.82	68.57	15.47		150.0	
10157-CAE	LTE-FDD (SC-FDMA, 50% RB, 5 MHz, 16-QAM)	X	1.74	66.14	12.73	0.00	150.0	± 9.6 %
		Y	1.50	64.22	11.27		150.0	
		Z	2.07	67.07	14.18		150.0	
10158-CAE	LTE-FDD (SC-FDMA, 50% RB, 10 MHz, 64-QAM)	X	2.63	68.91	16.16	0.00	150.0	± 9.6 %
		Y	2.41	67.57	15.20		150.0	
		Z	2.75	68.26	16.20		150.0	
10159-CAE	LTE-FDD (SC-FDMA, 50% RB, 5 MHz, 64-QAM)	X	1.82	66.50	12.94	0.00	150.0	± 9.6 %
		Y	1.56	64.46	11.44		150.0	
		Z	2.18	67.54	14.47		150.0	
10160-CAD	LTE-FDD (SC-FDMA, 50% RB, 15 MHz, QPSK)	X	2.58	68.77	16.27	0.00	150.0	± 9.6 %
		Y	2.38	67.56	15.39		150.0	
		Z	2.72	68.50	16.19		150.0	
10161-CAD	LTE-FDD (SC-FDMA, 50% RB, 15 MHz, 16-QAM)	X	2.75	67.48	15.71	0.00	150.0	± 9.6 %
		Y	2.59	66.55	15.00		150.0	
		Z	2.91	67.27	15.79		150.0	
10162-CAD	LTE-FDD (SC-FDMA, 50% RB, 15 MHz, 64-QAM)	X	2.86	67.71	15.86	0.00	150.0	± 9.6 %
		Y	2.70	66.80	15.16		150.0	
		Z	3.02	67.42	15.90		150.0	
10166-CAE	LTE-FDD (SC-FDMA, 50% RB, 1.4 MHz, QPSK)	X	3.32	70.00	19.39	3.01	150.0	± 9.6 %
		Y	3.05	68.29	18.45		150.0	
		Z	3.49	69.03	18.74		150.0	
10167-CAE	LTE-FDD (SC-FDMA, 50% RB, 1.4 MHz, 16-QAM)	X	4.24	74.22	20.32	3.01	150.0	± 9.6 %
		Y	3.51	70.51	18.61		150.0	
		Z	4.24	71.69	19.11		150.0	

Certificate No: EX3-7346_Feb18

Page 17 of 39

Appendix B: DAE and Probe Calibration Certificate

EX3DV4- SN:7346

February 28, 2018

10168-CAE	LTE-FDD (SC-FDMA, 50% RB, 1.4 MHz, 64-QAM)	X	5.00	77.74	22.20	3.01	150.0	± 9.6 %
		Y	3.95	73.17	20.22		150.0	
		Z	4.68	73.81	20.39		150.0	
10169-CAD	LTE-FDD (SC-FDMA, 1 RB, 20 MHz, QPSK)	X	2.77	69.24	19.08	3.01	150.0	± 9.6 %
		Y	2.47	66.53	17.61		150.0	
		Z	2.88	68.44	18.48		150.0	
10170-CAD	LTE-FDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM)	X	4.28	78.26	22.68	3.01	150.0	± 9.6 %
		Y	3.04	71.04	19.55		150.0	
		Z	3.85	73.86	20.62		150.0	
10171-AAD	LTE-FDD (SC-FDMA, 1 RB, 20 MHz, 64-QAM)	X	3.23	72.31	19.08	3.01	150.0	± 9.6 %
		Y	2.55	67.43	16.82		150.0	
		Z	3.20	70.03	17.98		150.0	
10172-CAD	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK)	X	3.81	80.74	25.45	6.02	65.0	± 9.6 %
		Y	3.76	79.03	24.69		65.0	
		Z	9.82	96.03	30.71		65.0	
10173-CAD	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM)	X	14.86	103.42	30.72	6.02	65.0	± 9.6 %
		Y	6.40	87.10	25.86		65.0	
		Z	21.03	105.82	31.58		65.0	
10174-CAD	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 64-QAM)	X	7.49	90.23	26.03	6.02	65.0	± 9.6 %
		Y	5.34	83.09	23.84		65.0	
		Z	16.77	100.11	29.26		65.0	
10175-CAE	LTE-FDD (SC-FDMA, 1 RB, 10 MHz, QPSK)	X	2.73	68.91	18.81	3.01	150.0	± 9.6 %
		Y	2.44	66.27	17.37		150.0	
		Z	2.85	68.15	18.25		150.0	
10176-CAE	LTE-FDD (SC-FDMA, 1 RB, 10 MHz, 16-QAM)	X	4.29	78.29	22.69	3.01	150.0	± 9.6 %
		Y	3.05	71.06	19.56		150.0	
		Z	3.86	73.88	20.63		150.0	
10177-CAG	LTE-FDD (SC-FDMA, 1 RB, 5 MHz, QPSK)	X	2.75	69.05	18.90	3.01	150.0	± 9.6 %
		Y	2.46	66.38	17.45		150.0	
		Z	2.87	68.29	18.34		150.0	
10178-CAE	LTE-FDD (SC-FDMA, 1 RB, 5 MHz, 16-QAM)	X	4.25	78.06	22.58	3.01	150.0	± 9.6 %
		Y	3.03	70.92	19.48		150.0	
		Z	3.82	73.68	20.52		150.0	
10179-CAE	LTE-FDD (SC-FDMA, 1 RB, 10 MHz, 64-QAM)	X	3.69	75.08	20.72	3.01	150.0	± 9.6 %
		Y	2.76	69.10	18.04		150.0	
		Z	3.49	71.83	19.16		150.0	
10180-CAE	LTE-FDD (SC-FDMA, 1 RB, 5 MHz, 64-QAM)	X	3.22	72.25	19.04	3.01	150.0	± 9.6 %
		Y	2.55	67.39	16.79		150.0	
		Z	3.19	69.97	17.93		150.0	
10181-CAD	LTE-FDD (SC-FDMA, 1 RB, 15 MHz, QPSK)	X	2.75	69.03	18.89	3.01	150.0	± 9.6 %
		Y	2.45	66.37	17.44		150.0	
		Z	2.87	68.28	18.33		150.0	
10182-CAD	LTE-FDD (SC-FDMA, 1 RB, 15 MHz, 16-QAM)	X	4.24	78.03	22.56	3.01	150.0	± 9.6 %
		Y	3.02	70.90	19.47		150.0	
		Z	3.82	73.66	20.51		150.0	
10183-AAC	LTE-FDD (SC-FDMA, 1 RB, 15 MHz, 64-QAM)	X	3.22	72.22	19.03	3.01	150.0	± 9.6 %
		Y	2.54	67.37	16.78		150.0	
		Z	3.19	69.94	17.92		150.0	

Certificate No: EX3-7346_Feb18

Page 18 of 39

Appendix B: DAE and Probe Calibration Certificate

EX3DV4- SN:7346

February 28, 2018

10184-CAD	LTE-FDD (SC-FDMA, 1 RB, 3 MHz, QPSK)	X	2.76	69.08	18.91	3.01	150.0	± 9.6 %
		Y	2.46	66.40	17.46		150.0	
		Z	2.88	68.32	18.35		150.0	
10185-CAD	LTE-FDD (SC-FDMA, 1 RB, 3 MHz, 16-QAM)	X	4.27	78.13	22.61	3.01	150.0	± 9.6 %
		Y	3.04	70.96	19.50		150.0	
		Z	3.83	73.72	20.54		150.0	
10186-AAD	LTE-FDD (SC-FDMA, 1 RB, 3 MHz, 64-QAM)	X	3.23	72.30	19.07	3.01	150.0	± 9.6 %
		Y	2.55	67.43	16.81		150.0	
		Z	3.20	70.01	17.95		150.0	
10187-CAE	LTE-FDD (SC-FDMA, 1 RB, 1.4 MHz, QPSK)	X	2.77	69.16	19.00	3.01	150.0	± 9.6 %
		Y	2.47	66.48	17.54		150.0	
		Z	2.88	68.37	18.41		150.0	
10188-CAE	LTE-FDD (SC-FDMA, 1 RB, 1.4 MHz, 16-QAM)	X	4.45	79.03	23.08	3.01	150.0	± 9.6 %
		Y	3.11	71.50	19.85		150.0	
		Z	3.95	74.33	20.90		150.0	
10189-AAE	LTE-FDD (SC-FDMA, 1 RB, 1.4 MHz, 64-QAM)	X	3.32	72.84	19.40	3.01	150.0	± 9.6 %
		Y	2.60	67.76	17.06		150.0	
		Z	3.27	70.40	18.22		150.0	
10193-CAC	IEEE 802.11n (HT Greenfield, 6.5 Mbps, BPSK)	X	4.34	66.80	16.09	0.00	150.0	± 9.6 %
		Y	4.24	66.43	15.78		150.0	
		Z	4.51	66.56	16.09		150.0	
10194-CAC	IEEE 802.11n (HT Greenfield, 39 Mbps, 16-QAM)	X	4.48	67.04	16.22	0.00	150.0	± 9.6 %
		Y	4.38	66.66	15.92		150.0	
		Z	4.68	66.88	16.22		150.0	
10195-CAC	IEEE 802.11n (HT Greenfield, 65 Mbps, 64-QAM)	X	4.51	67.05	16.23	0.00	150.0	± 9.6 %
		Y	4.41	66.68	15.94		150.0	
		Z	4.73	66.91	16.23		150.0	
10196-CAC	IEEE 802.11n (HT Mixed, 6.5 Mbps, BPSK)	X	4.32	66.80	16.07	0.00	150.0	± 9.6 %
		Y	4.22	66.42	15.76		150.0	
		Z	4.52	66.63	16.11		150.0	
10197-CAC	IEEE 802.11n (HT Mixed, 39 Mbps, 16-QAM)	X	4.49	67.04	16.22	0.00	150.0	± 9.6 %
		Y	4.38	66.67	15.92		150.0	
		Z	4.70	66.90	16.23		150.0	
10198-CAC	IEEE 802.11n (HT Mixed, 65 Mbps, 64-QAM)	X	4.51	67.05	16.23	0.00	150.0	± 9.6 %
		Y	4.40	66.68	15.94		150.0	
		Z	4.73	66.93	16.25		150.0	
10219-CAC	IEEE 802.11n (HT Mixed, 7.2 Mbps, BPSK)	X	4.28	66.84	16.05	0.00	150.0	± 9.6 %
		Y	4.17	66.45	15.73		150.0	
		Z	4.47	66.64	16.07		150.0	
10220-CAC	IEEE 802.11n (HT Mixed, 43.3 Mbps, 16-QAM)	X	4.48	67.00	16.21	0.00	150.0	± 9.6 %
		Y	4.38	66.63	15.91		150.0	
		Z	4.69	66.87	16.22		150.0	
10221-CAC	IEEE 802.11n (HT Mixed, 72.2 Mbps, 64-QAM)	X	4.52	67.00	16.22	0.00	150.0	± 9.6 %
		Y	4.42	66.63	15.93		150.0	
		Z	4.74	66.86	16.23		150.0	
10222-CAC	IEEE 802.11n (HT Mixed, 15 Mbps, BPSK)	X	4.89	67.06	16.35	0.00	150.0	± 9.6 %
		Y	4.80	66.75	16.10		150.0	
		Z	5.06	67.03	16.34		150.0	

Certificate No: EX3-7346_Feb18

Page 19 of 39

Appendix B: DAE and Probe Calibration Certificate

EX3DV4- SN:7346

February 28, 2018

10223-CAC	IEEE 802.11n (HT Mixed, 90 Mbps, 16-QAM)	X	5.15	67.25	16.45	0.00	150.0	± 9.6 %
		Y	5.06	66.95	16.22		150.0	
		Z	5.36	67.22	16.45		150.0	
10224-CAC	IEEE 802.11n (HT Mixed, 150 Mbps, 64-QAM)	X	4.93	67.18	16.34	0.00	150.0	± 9.6 %
		Y	4.84	66.86	16.08		150.0	
		Z	5.10	67.14	16.32		150.0	
10225-CAB	UMTS-FDD (HSPA+)	X	2.62	66.28	14.90	0.00	150.0	± 9.6 %
		Y	2.48	65.45	14.20		150.0	
		Z	2.79	66.05	15.26		150.0	
10226-CAA	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 16-QAM)	X	17.02	106.09	31.60	6.02	65.0	± 9.6 %
		Y	6.83	88.41	26.41		65.0	
		Z	23.09	107.72	32.22		65.0	
10227-CAA	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 64-QAM)	X	17.19	104.09	30.15	6.02	65.0	± 9.6 %
		Y	7.01	87.79	25.52		65.0	
		Z	21.47	104.45	30.57		65.0	
10228-CAA	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, QPSK)	X	5.07	86.64	27.72	6.02	65.0	± 9.6 %
		Y	4.22	81.74	25.87		65.0	
		Z	10.68	98.13	31.48		65.0	
10229-CAB	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 16-QAM)	X	15.04	103.61	30.78	6.02	65.0	± 9.6 %
		Y	6.45	87.21	25.90		65.0	
		Z	21.21	105.95	31.62		65.0	
10230-CAB	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 64-QAM)	X	14.90	101.50	29.32	6.02	65.0	± 9.6 %
		Y	6.53	86.49	25.00		65.0	
		Z	19.68	102.78	30.01		65.0	
10231-CAB	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, QPSK)	X	4.85	85.66	27.28	6.02	65.0	± 9.6 %
		Y	4.07	80.95	25.48		65.0	
		Z	10.14	96.98	31.03		65.0	
10232-CAD	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 16-QAM)	X	15.00	103.58	30.77	6.02	65.0	± 9.6 %
		Y	6.43	87.19	25.89		65.0	
		Z	21.18	105.94	31.62		65.0	
10233-CAD	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 64-QAM)	X	14.82	101.43	29.31	6.02	65.0	± 9.6 %
		Y	6.51	86.44	24.99		65.0	
		Z	19.62	102.75	30.00		65.0	
10234-CAD	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, QPSK)	X	4.69	84.90	26.87	6.02	65.0	± 9.6 %
		Y	3.96	80.34	25.11		65.0	
		Z	9.72	95.94	30.57		65.0	
10235-CAD	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 16-QAM)	X	15.03	103.64	30.79	6.02	65.0	± 9.6 %
		Y	6.44	87.21	25.91		65.0	
		Z	21.22	105.99	31.64		65.0	
10236-CAD	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 64-QAM)	X	15.16	101.76	29.39	6.02	65.0	± 9.6 %
		Y	6.58	86.61	25.04		65.0	
		Z	19.96	103.02	30.07		65.0	
10237-CAD	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK)	X	4.84	85.69	27.29	6.02	65.0	± 9.6 %
		Y	4.07	80.96	25.48		65.0	
		Z	10.17	97.07	31.07		65.0	
10238-CAD	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 16-QAM)	X	14.95	103.54	30.76	6.02	65.0	± 9.6 %
		Y	6.42	87.16	25.88		65.0	
		Z	21.13	105.92	31.61		65.0	

Certificate No: EX3-7346_Feb18

Page 20 of 39

Appendix B: DAE and Probe Calibration Certificate

EX3DV4- SN:7346

February 28, 2018

10239-CAD	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 64-QAM)	X	14.73	101.35	29.28	6.02	65.0	± 9.6 %
		Y	6.48	86.39	24.97		65.0	
		Z	19.55	102.71	30.00		65.0	
10240-CAD	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, QPSK)	X	4.83	85.66	27.28	6.02	65.0	± 9.6 %
		Y	4.06	80.94	25.48		65.0	
		Z	10.14	97.02	31.05		65.0	
10241-CAA	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 16-QAM)	X	6.96	81.77	25.84	6.98	65.0	± 9.6 %
		Y	6.28	78.87	24.66		65.0	
		Z	7.85	81.13	25.69		65.0	
10242-CAA	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 64-QAM)	X	5.98	78.66	24.50	6.98	65.0	± 9.6 %
		Y	5.88	77.52	24.01		65.0	
		Z	7.56	80.32	25.29		65.0	
10243-CAA	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, QPSK)	X	4.77	74.09	23.42	6.98	65.0	± 9.6 %
		Y	4.87	74.03	23.36		65.0	
		Z	6.05	76.69	24.67		65.0	
10244-CAB	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 16-QAM)	X	3.65	70.15	14.65	3.98	65.0	± 9.6 %
		Y	3.47	69.48	14.50		65.0	
		Z	6.32	77.76	19.63		65.0	
10245-CAB	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 64-QAM)	X	3.52	69.40	14.24	3.98	65.0	± 9.6 %
		Y	3.36	68.78	14.11		65.0	
		Z	6.11	76.93	19.23		65.0	
10246-CAB	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, QPSK)	X	3.43	73.14	16.63	3.98	65.0	± 9.6 %
		Y	3.26	72.33	16.22		65.0	
		Z	7.46	84.64	22.66		65.0	
10247-CAD	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 16-QAM)	X	3.61	70.52	16.22	3.98	65.0	± 9.6 %
		Y	3.52	70.09	15.97		65.0	
		Z	5.33	75.84	19.89		65.0	
10248-CAD	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 64-QAM)	X	3.55	69.80	15.86	3.98	65.0	± 9.6 %
		Y	3.46	69.36	15.61		65.0	
		Z	5.25	75.02	19.51		65.0	
10249-CAD	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, QPSK)	X	4.97	79.17	20.46	3.98	65.0	± 9.6 %
		Y	4.79	78.54	20.18		65.0	
		Z	8.54	87.26	24.53		65.0	
10250-CAD	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 16-QAM)	X	4.65	74.18	20.11	3.98	65.0	± 9.6 %
		Y	4.59	73.95	20.01		65.0	
		Z	5.96	77.30	22.07		65.0	
10251-CAD	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 64-QAM)	X	4.38	71.87	18.64	3.98	65.0	± 9.6 %
		Y	4.30	71.50	18.46		65.0	
		Z	5.65	74.97	20.70		65.0	
10252-CAD	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, QPSK)	X	5.42	79.78	22.18	3.98	65.0	± 9.6 %
		Y	5.28	79.30	22.00		65.0	
		Z	7.67	84.37	24.40		65.0	
10253-CAD	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 16-QAM)	X	4.60	71.36	18.95	3.98	65.0	± 9.6 %
		Y	4.53	71.02	18.79		65.0	
		Z	5.64	73.72	20.48		65.0	
10254-CAD	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 64-QAM)	X	4.91	72.32	19.70	3.98	65.0	± 9.6 %
		Y	4.84	72.03	19.58		65.0	
		Z	5.97	74.57	21.15		65.0	

Certificate No: EX3-7346_Feb18

Page 21 of 39

Appendix B: DAE and Probe Calibration Certificate

EX3DV4- SN:7346

February 28, 2018

10255-CAD	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, QPSK)	X	5.13	76.26	21.09	3.98	65.0	± 9.6 %
		Y	5.02	75.85	20.94		65.0	
		Z	6.58	79.20	22.59		65.0	
10256-CAA	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 16-QAM)	X	2.39	64.77	10.70	3.98	65.0	± 9.6 %
		Y	2.35	64.52	10.73		65.0	
		Z	4.88	73.56	16.84		65.0	
10257-CAA	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 64-QAM)	X	2.34	64.21	10.30	3.98	65.0	± 9.6 %
		Y	2.31	63.99	10.34		65.0	
		Z	4.66	72.51	16.28		65.0	
10258-CAA	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, QPSK)	X	2.18	66.52	12.36	3.98	65.0	± 9.6 %
		Y	2.09	65.91	11.97		65.0	
		Z	5.41	78.96	19.67		65.0	
10259-CAB	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 16-QAM)	X	4.05	72.12	17.74	3.98	65.0	± 9.6 %
		Y	3.97	71.77	17.54		65.0	
		Z	5.59	76.39	20.68		65.0	
10260-CAB	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 64-QAM)	X	4.06	71.80	17.58	3.98	65.0	± 9.6 %
		Y	3.99	71.45	17.38		65.0	
		Z	5.59	75.99	20.51		65.0	
10261-CAB	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, QPSK)	X	4.91	78.61	20.83	3.98	65.0	± 9.6 %
		Y	4.77	78.08	20.60		65.0	
		Z	7.47	84.56	23.98		65.0	
10262-CAD	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 16-QAM)	X	4.64	74.10	20.05	3.98	65.0	± 9.6 %
		Y	4.58	73.87	19.95		65.0	
		Z	5.95	77.25	22.03		65.0	
10263-CAD	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 64-QAM)	X	4.38	71.84	18.63	3.98	65.0	± 9.6 %
		Y	4.30	71.48	18.45		65.0	
		Z	5.64	74.94	20.69		65.0	
10264-CAD	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, QPSK)	X	5.36	79.54	22.06	3.98	65.0	± 9.6 %
		Y	5.21	79.06	21.88		65.0	
		Z	7.59	84.14	24.29		65.0	
10265-CAD	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 16-QAM)	X	4.66	71.72	19.22	3.98	65.0	± 9.6 %
		Y	4.58	71.35	19.06		65.0	
		Z	5.78	74.35	20.76		65.0	
10266-CAD	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 64-QAM)	X	5.01	72.82	20.09	3.98	65.0	± 9.6 %
		Y	4.94	72.52	19.97		65.0	
		Z	6.13	75.23	21.49		65.0	
10267-CAD	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, QPSK)	X	5.40	77.00	21.24	3.98	65.0	± 9.6 %
		Y	5.27	76.56	21.09		65.0	
		Z	7.04	80.22	22.75		65.0	
10268-CAD	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 16-QAM)	X	5.30	71.80	19.74	3.98	65.0	± 9.6 %
		Y	5.23	71.47	19.62		65.0	
		Z	6.34	73.95	20.93		65.0	
10269-CAD	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 64-QAM)	X	5.32	71.45	19.62	3.98	65.0	± 9.6 %
		Y	5.25	71.13	19.49		65.0	
		Z	6.30	73.46	20.76		65.0	
10270-CAD	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, QPSK)	X	5.39	74.29	20.26	3.98	65.0	± 9.6 %
		Y	5.30	73.95	20.15		65.0	
		Z	6.60	76.59	21.38		65.0	

Certificate No: EX3-7346_Feb18

Page 22 of 39

Appendix B: DAE and Probe Calibration Certificate

EX3DV4- SN:7346

February 28, 2018

10274-CAB	UMTS-FDD (HSUPA, Subtest 5, 3GPP Rel8.10)	X	2.47	66.89	14.96	0.00	150.0	± 9.6 %
		Y	2.30	65.86	14.15		150.0	
		Z	2.57	66.40	15.16		150.0	
10275-CAB	UMTS-FDD (HSUPA, Subtest 5, 3GPP Rel8.4)	X	1.52	68.12	15.36	0.00	150.0	± 9.6 %
		Y	1.30	65.95	13.79		150.0	
		Z	1.59	67.73	15.40		150.0	
10277-CAA	PHS (QPSK)	X	1.31	58.98	4.23	9.03	50.0	± 9.6 %
		Y	1.52	59.53	4.93		50.0	
		Z	2.02	61.76	7.29		50.0	
10278-CAA	PHS (QPSK, BW 884MHz, Rolloff 0.5)	X	2.56	65.28	10.47	9.03	50.0	± 9.6 %
		Y	2.85	65.93	11.06		50.0	
		Z	10.53	85.66	20.98		50.0	
10279-CAA	PHS (QPSK, BW 884MHz, Rolloff 0.38)	X	2.65	65.57	10.69	9.03	50.0	± 9.6 %
		Y	2.93	66.19	11.25		50.0	
		Z	10.77	85.93	21.14		50.0	
10290-AAB	CDMA2000, RC1, SO55, Full Rate	X	0.98	65.56	11.05	0.00	150.0	± 9.6 %
		Y	0.70	62.12	8.48		150.0	
		Z	1.41	68.34	13.76		150.0	
10291-AAB	CDMA2000, RC3, SO55, Full Rate	X	0.61	63.82	10.00	0.00	150.0	± 9.6 %
		Y	0.43	60.63	7.23		150.0	
		Z	0.80	65.38	12.18		150.0	
10292-AAB	CDMA2000, RC3, SO32, Full Rate	X	0.89	68.79	12.78	0.00	150.0	± 9.6 %
		Y	0.48	62.16	8.40		150.0	
		Z	1.03	69.61	14.61		150.0	
10293-AAB	CDMA2000, RC3, SO3, Full Rate	X	2.58	81.76	18.19	0.00	150.0	± 9.6 %
		Y	0.65	65.04	10.35		150.0	
		Z	1.64	76.25	17.89		150.0	
10295-AAB	CDMA2000, RC1, SO3, 1/8th Rate 25 fr.	X	18.03	94.98	25.39	9.03	50.0	± 9.6 %
		Y	22.10	97.43	26.12		50.0	
		Z	12.57	93.15	27.41		50.0	
10297-AAC	LTE-FDD (SC-FDMA, 50% RB, 20 MHz, QPSK)	X	2.55	69.57	16.56	0.00	150.0	± 9.6 %
		Y	2.32	68.07	15.54		150.0	
		Z	2.73	69.56	16.49		150.0	
10298-AAC	LTE-FDD (SC-FDMA, 50% RB, 3 MHz, QPSK)	X	1.16	65.30	11.68	0.00	150.0	± 9.6 %
		Y	0.92	62.73	9.68		150.0	
		Z	1.54	67.46	13.97		150.0	
10299-AAC	LTE-FDD (SC-FDMA, 50% RB, 3 MHz, 16-QAM)	X	1.74	65.37	10.61	0.00	150.0	± 9.6 %
		Y	1.35	62.98	9.30		150.0	
		Z	2.38	68.29	13.60		150.0	
10300-AAC	LTE-FDD (SC-FDMA, 50% RB, 3 MHz, 64-QAM)	X	1.31	62.00	8.16	0.00	150.0	± 9.6 %
		Y	1.13	60.87	7.43		150.0	
		Z	1.86	64.44	11.00		150.0	
10301-AAA	IEEE 802.16e WiMAX (29:18, 5ms, 10MHz, QPSK, PUSC)	X	4.34	65.17	17.05	4.17	50.0	± 9.6 %
		Y	4.31	65.11	16.85		50.0	
		Z	4.82	65.71	17.56		50.0	
10302-AAA	IEEE 802.16e WiMAX (29:18, 5ms, 10MHz, QPSK, PUSC, 3 CTRL symbols)	X	4.77	65.60	17.67	4.96	50.0	± 9.6 %
		Y	4.81	65.67	17.50		50.0	
		Z	5.27	66.23	18.23		50.0	

Certificate No: EX3-7346_Feb18

Page 23 of 39

Appendix B: DAE and Probe Calibration Certificate

EX3DV4- SN:7346

February 28, 2018

10303-AAA	IEEE 802.16e WiMAX (31:15, 5ms, 10MHz, 64QAM, PUSC)	X	4.52	65.19	17.43	4.96	50.0	± 9.6 %
		Y	4.57	65.31	17.28		50.0	
		Z	5.02	65.87	18.07		50.0	
10304-AAA	IEEE 802.16e WiMAX (29:18, 5ms, 10MHz, 64QAM, PUSC)	X	4.37	65.21	17.02	4.17	50.0	± 9.6 %
		Y	4.39	65.22	16.81		50.0	
		Z	4.82	65.71	17.53		50.0	
10305-AAA	IEEE 802.16e WiMAX (31:15, 10ms, 10MHz, 64QAM, PUSC, 15 symbols)	X	3.77	65.78	18.01	6.02	35.0	± 9.6 %
		Y	4.03	67.11	18.37		35.0	
		Z	4.43	67.64	19.71		35.0	
10306-AAA	IEEE 802.16e WiMAX (29:18, 10ms, 10MHz, 64QAM, PUSC, 18 symbols)	X	4.18	65.43	18.08	6.02	35.0	± 9.6 %
		Y	4.36	66.34	18.31		35.0	
		Z	4.75	66.67	19.28		35.0	
10307-AAA	IEEE 802.16e WiMAX (29:18, 10ms, 10MHz, QPSK, PUSC, 18 symbols)	X	4.05	65.37	17.93	6.02	35.0	± 9.6 %
		Y	4.24	66.33	18.18		35.0	
		Z	4.65	66.84	19.25		35.0	
10308-AAA	IEEE 802.16e WiMAX (29:18, 10ms, 10MHz, 16QAM, PUSC)	X	4.02	65.52	18.06	6.02	35.0	± 9.6 %
		Y	4.22	66.54	18.32		35.0	
		Z	4.63	67.04	19.39		35.0	
10309-AAA	IEEE 802.16e WiMAX (29:18, 10ms, 10MHz, 16QAM, AMC 2x3, 18 symbols)	X	4.20	65.51	18.17	6.02	35.0	± 9.6 %
		Y	4.38	66.41	18.40		35.0	
		Z	4.82	66.92	19.44		35.0	
10310-AAA	IEEE 802.16e WiMAX (29:18, 10ms, 10MHz, QPSK, AMC 2x3, 18 symbols)	X	4.13	65.45	18.04	6.02	35.0	± 9.6 %
		Y	4.31	66.39	18.29		35.0	
		Z	4.70	66.73	19.25		35.0	
10311-AAC	LTE-FDD (SC-FDMA, 100% RB, 15 MHz, QPSK)	X	2.92	68.81	16.22	0.00	150.0	± 9.6 %
		Y	2.67	67.41	15.31		150.0	
		Z	3.09	68.86	16.15		150.0	
10313-AAA	IDEN 1:3	X	2.64	72.44	15.90	6.99	70.0	± 9.6 %
		Y	2.47	71.20	15.36		70.0	
		Z	5.97	82.06	19.94		70.0	
10314-AAA	IDEN 1:6	X	5.14	84.42	23.42	10.00	30.0	± 9.6 %
		Y	5.61	84.61	23.25		30.0	
		Z	10.51	95.64	27.63		30.0	
10315-AAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 96pc duty cycle)	X	1.03	63.68	15.01	0.17	150.0	± 9.6 %
		Y	0.95	62.61	14.00		150.0	
		Z	1.06	63.65	15.10		150.0	
10316-AAB	IEEE 802.11g WiFi 2.4 GHz (ERP-OFDM, 6 Mbps, 96pc duty cycle)	X	4.36	66.72	16.17	0.17	150.0	± 9.6 %
		Y	4.27	66.42	15.93		150.0	
		Z	4.57	66.65	16.28		150.0	
10317-AAC	IEEE 802.11a WiFi 5 GHz (OFDM, 6 Mbps, 96pc duty cycle)	X	4.36	66.72	16.17	0.17	150.0	± 9.6 %
		Y	4.27	66.42	15.93		150.0	
		Z	4.57	66.65	16.28		150.0	
10400-AAD	IEEE 802.11ac WiFi (20MHz, 64-QAM, 99pc duty cycle)	X	4.44	67.03	16.19	0.00	150.0	± 9.6 %
		Y	4.33	66.65	15.88		150.0	
		Z	4.68	66.94	16.21		150.0	
10401-AAD	IEEE 802.11ac WiFi (40MHz, 64-QAM, 99pc duty cycle)	X	5.10	66.83	16.20	0.00	150.0	± 9.6 %
		Y	5.00	66.52	15.96		150.0	
		Z	5.37	67.12	16.38		150.0	

Certificate No: EX3-7346_Feb18

Page 24 of 39

Appendix B: DAE and Probe Calibration Certificate

EX3DV4- SN:7346

February 28, 2018

10402-AAD	IEEE 802.11ac WiFi (80MHz, 64-QAM, 99pc duty cycle)	X	5.44	67.40	16.38	0.00	150.0	± 9.6 %
		Y	5.36	67.10	16.15		150.0	
		Z	5.62	67.43	16.39		150.0	
10403-AAB	CDMA2000 (1xEV-DO, Rev. 0)	X	0.98	65.56	11.05	0.00	115.0	± 9.6 %
		Y	0.70	62.12	8.48		115.0	
		Z	1.41	68.34	13.76		115.0	
10404-AAB	CDMA2000 (1xEV-DO, Rev. A)	X	0.98	65.56	11.05	0.00	115.0	± 9.6 %
		Y	0.70	62.12	8.48		115.0	
		Z	1.41	68.34	13.76		115.0	
10406-AAB	CDMA2000, RC3, SO32, SCH0, Full Rate	X	100.00	111.96	25.11	0.00	100.0	± 9.6 %
		Y	25.42	102.66	24.60		100.0	
		Z	19.30	99.68	24.97		100.0	
10410-AAD	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9, Subframe Conf=4)	X	100.00	124.70	30.39	3.23	80.0	± 9.6 %
		Y	35.57	114.34	29.10		80.0	
		Z	100.00	125.51	31.78		80.0	
10415-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 99pc duty cycle)	X	0.99	63.16	14.59	0.00	150.0	± 9.6 %
		Y	0.90	62.05	13.50		150.0	
		Z	0.99	62.85	14.49		150.0	
10416-AAA	IEEE 802.11g WiFi 2.4 GHz (ERP-OFDM, 6 Mbps, 99pc duty cycle)	X	4.33	66.79	16.15	0.00	150.0	± 9.6 %
		Y	4.23	66.42	15.85		150.0	
		Z	4.51	66.60	16.16		150.0	
10417-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 6 Mbps, 99pc duty cycle)	X	4.33	66.79	16.15	0.00	150.0	± 9.6 %
		Y	4.23	66.42	15.85		150.0	
		Z	4.51	66.60	16.16		150.0	
10418-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps, 99pc duty cycle, Long preamble)	X	4.33	66.99	16.21	0.00	150.0	± 9.6 %
		Y	4.22	66.61	15.90		150.0	
		Z	4.50	66.76	16.18		150.0	
10419-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps, 99pc duty cycle, Short preamble)	X	4.34	66.92	16.20	0.00	150.0	± 9.6 %
		Y	4.24	66.55	15.89		150.0	
		Z	4.52	66.71	16.18		150.0	
10422-AAB	IEEE 802.11n (HT Greenfield, 7.2 Mbps, BPSK)	X	4.45	66.90	16.20	0.00	150.0	± 9.6 %
		Y	4.35	66.53	15.91		150.0	
		Z	4.64	66.71	16.19		150.0	
10423-AAB	IEEE 802.11n (HT Greenfield, 43.3 Mbps, 16-QAM)	X	4.57	67.15	16.29	0.00	150.0	± 9.6 %
		Y	4.47	66.79	16.00		150.0	
		Z	4.81	67.03	16.31		150.0	
10424-AAB	IEEE 802.11n (HT Greenfield, 72.2 Mbps, 64-QAM)	X	4.51	67.11	16.27	0.00	150.0	± 9.6 %
		Y	4.40	66.73	15.97		150.0	
		Z	4.73	66.96	16.28		150.0	
10425-AAB	IEEE 802.11n (HT Greenfield, 15 Mbps, BPSK)	X	5.12	67.27	16.44	0.00	150.0	± 9.6 %
		Y	5.03	66.97	16.21		150.0	
		Z	5.32	67.27	16.45		150.0	
10426-AAB	IEEE 802.11n (HT Greenfield, 90 Mbps, 16-QAM)	X	5.14	67.35	16.48	0.00	150.0	± 9.6 %
		Y	5.05	67.07	16.25		150.0	
		Z	5.33	67.29	16.46		150.0	

Certificate No: EX3-7346_Feb18

Page 25 of 39

Appendix B: DAE and Probe Calibration Certificate

EX3DV4- SN:7346

February 28, 2018

10427-AAB	IEEE 802.11n (HT Greenfield, 150 Mbps, 64-QAM)	X	5.10	67.15	18.37	0.00	150.0	± 9.6 %
		Y	5.01	66.85	18.14		150.0	
		Z	5.34	67.28	16.45		150.0	
10430-AAB	LTE-FDD (OFDMA, 5 MHz, E-TM 3.1)	X	4.22	72.32	18.33	0.00	150.0	± 9.6 %
		Y	4.00	71.43	17.69		150.0	
		Z	4.22	70.65	18.06		150.0	
10431-AAB	LTE-FDD (OFDMA, 10 MHz, E-TM 3.1)	X	3.95	67.38	16.03	0.00	150.0	± 9.6 %
		Y	3.82	66.87	15.62		150.0	
		Z	4.20	67.15	16.15		150.0	
10432-AAB	LTE-FDD (OFDMA, 15 MHz, E-TM 3.1)	X	4.27	67.21	16.20	0.00	150.0	± 9.6 %
		Y	4.16	66.79	15.86		150.0	
		Z	4.50	67.02	16.23		150.0	
10433-AAB	LTE-FDD (OFDMA, 20 MHz, E-TM 3.1)	X	4.52	67.14	16.29	0.00	150.0	± 9.6 %
		Y	4.42	66.77	15.99		150.0	
		Z	4.74	67.01	16.30		150.0	
10434-AAA	W-CDMA (BS Test Model 1, 64 DPCH)	X	4.34	73.22	18.13	0.00	150.0	± 9.6 %
		Y	4.01	71.90	17.27		150.0	
		Z	4.32	71.50	18.03		150.0	
10435-AAC	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	100.00	124.35	30.23	3.23	80.0	± 9.6 %
		Y	30.49	112.00	28.47		80.0	
		Z	100.00	125.29	31.68		80.0	
10447-AAB	LTE-FDD (OFDMA, 5 MHz, E-TM 3.1, Clipping 44%)	X	3.19	67.18	14.89	0.00	150.0	± 9.6 %
		Y	3.01	66.34	14.22		150.0	
		Z	3.49	67.13	15.46		150.0	
10448-AAB	LTE-FDD (OFDMA, 10 MHz, E-TM 3.1, Clipping 44%)	X	3.82	67.18	15.91	0.00	150.0	± 9.6 %
		Y	3.69	66.66	15.49		150.0	
		Z	4.04	66.92	16.01		150.0	
10449-AAB	LTE-FDD (OFDMA, 15 MHz, E-TM 3.1, Clipping 44%)	X	4.11	67.04	16.10	0.00	150.0	± 9.6 %
		Y	4.00	66.61	15.75		150.0	
		Z	4.31	66.85	16.13		150.0	
10450-AAB	LTE-FDD (OFDMA, 20 MHz, E-TM 3.1, Clipping 44%)	X	4.32	66.93	16.15	0.00	150.0	± 9.6 %
		Y	4.22	66.54	15.84		150.0	
		Z	4.50	66.78	16.16		150.0	
10451-AAA	W-CDMA (BS Test Model 1, 64 DPCH, Clipping 44%)	X	2.98	66.91	14.13	0.00	150.0	± 9.6 %
		Y	2.78	65.91	13.34		150.0	
		Z	3.37	67.29	15.07		150.0	
10456-AAB	IEEE 802.11ac WiFi (160MHz, 64-QAM, 99pc duty cycle)	X	6.03	67.77	16.58	0.00	150.0	± 9.6 %
		Y	5.96	67.52	16.39		150.0	
		Z	6.18	67.82	16.61		150.0	
10457-AAA	UMTS-FDD (DC-HSDPA)	X	3.69	65.54	15.88	0.00	150.0	± 9.6 %
		Y	3.60	65.19	15.57		150.0	
		Z	3.77	65.25	15.87		150.0	
10458-AAA	CDMA2000 (1xEV-DO, Rev. B, 2 carriers)	X	3.71	71.26	16.68	0.00	150.0	± 9.6 %
		Y	3.34	69.57	15.58		150.0	
		Z	3.96	70.76	17.42		150.0	
10459-AAA	CDMA2000 (1xEV-DO, Rev. B, 3 carriers)	X	4.84	69.16	17.85	0.00	150.0	± 9.6 %
		Y	4.71	68.81	17.54		150.0	
		Z	5.06	68.29	18.06		150.0	

Certificate No: EX3-7346_Feb18

Page 26 of 39

Appendix B: DAE and Probe Calibration Certificate

EX3DV4- SN:7346

February 28, 2018

10460-AAA	UMTS-FDD (WCDMA, AMR)	X	0.87	68.57	16.07	0.00	150.0	± 9.6 %
		Y	0.68	65.20	13.52		150.0	
		Z	0.87	67.82	15.83		150.0	
10461-AAA	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	100.00	131.24	33.42	3.29	80.0	± 9.6 %
		Y	35.87	117.39	30.79		80.0	
		Z	100.00	130.05	33.95		80.0	
10462-AAA	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	0.66	60.00	7.14	3.23	80.0	± 9.6 %
		Y	0.79	61.10	8.71		80.0	
		Z	8.69	83.27	17.68		80.0	
10463-AAA	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	0.68	60.00	6.41	3.23	80.0	± 9.6 %
		Y	0.71	60.00	7.47		80.0	
		Z	2.00	67.52	11.81		80.0	
10464-AAA	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	100.00	127.01	31.31	3.23	80.0	± 9.6 %
		Y	22.40	108.37	27.69		80.0	
		Z	100.00	127.29	32.50		80.0	
10465-AAA	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	0.66	60.00	7.05	3.23	80.0	± 9.6 %
		Y	0.73	60.44	8.30		80.0	
		Z	4.63	76.72	15.62		80.0	
10466-AAA	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	0.69	60.00	6.36	3.23	80.0	± 9.6 %
		Y	0.71	60.00	7.41		80.0	
		Z	1.67	65.70	11.02		80.0	
10467-AAC	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	100.00	127.52	31.53	3.23	80.0	± 9.6 %
		Y	31.48	113.23	28.92		80.0	
		Z	100.00	127.61	32.64		80.0	
10468-AAC	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	0.65	60.00	7.08	3.23	80.0	± 9.6 %
		Y	0.75	60.65	8.44		80.0	
		Z	5.35	78.25	16.12		80.0	
10469-AAC	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	0.69	60.00	6.36	3.23	80.0	± 9.6 %
		Y	0.71	60.00	7.41		80.0	
		Z	1.67	65.74	11.03		80.0	
10470-AAC	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	100.00	127.55	31.53	3.23	80.0	± 9.6 %
		Y	32.51	113.69	29.02		80.0	
		Z	100.00	127.65	32.64		80.0	
10471-AAC	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	0.65	60.00	7.06	3.23	80.0	± 9.6 %
		Y	0.74	60.60	8.40		80.0	
		Z	5.27	78.07	16.05		80.0	
10472-AAC	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	0.69	60.00	6.34	3.23	80.0	± 9.6 %
		Y	0.71	60.00	7.40		80.0	
		Z	1.66	65.66	10.98		80.0	
10473-AAC	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	100.00	127.50	31.51	3.23	80.0	± 9.6 %
		Y	31.93	113.42	28.95		80.0	
		Z	100.00	127.61	32.62		80.0	
10474-AAC	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	0.65	60.00	7.06	3.23	80.0	± 9.6 %
		Y	0.74	60.58	8.38		80.0	
		Z	5.19	77.93	16.01		80.0	
10475-AAC	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	0.69	60.00	6.34	3.23	80.0	± 9.6 %
		Y	0.71	60.00	7.40		80.0	
		Z	1.65	65.61	10.97		80.0	

Certificate No: EX3-7346_Feb18

Page 27 of 39

Appendix B: DAE and Probe Calibration Certificate

EX3DV4- SN:7346

February 28, 2018

10477-AAC	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	0.65	60.00	7.03	3.23	80.0	± 9.6 %
		Y	0.73	60.41	8.27		80.0	
		Z	4.63	76.73	15.60		80.0	
10478-AAC	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	0.69	60.00	6.32	3.23	80.0	± 9.6 %
		Y	0.71	60.00	7.39		80.0	
		Z	1.63	65.53	10.92		80.0	
10479-AAA	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	16.00	99.74	26.44	3.23	80.0	± 9.6 %
		Y	11.93	95.50	25.33		80.0	
		Z	7.94	87.98	23.97		80.0	
10480-AAA	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	6.79	80.48	17.75	3.23	80.0	± 9.6 %
		Y	4.94	77.21	17.06		80.0	
		Z	8.84	84.07	20.72		80.0	
10481-AAA	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	3.30	71.66	14.25	3.23	80.0	± 9.6 %
		Y	2.92	70.45	14.14		80.0	
		Z	6.89	79.97	18.98		80.0	
10482-AAA	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	1.71	66.57	13.32	2.23	80.0	± 9.6 %
		Y	1.47	64.69	12.19		80.0	
		Z	3.77	76.31	18.90		80.0	
10483-AAA	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	1.97	64.83	11.62	2.23	80.0	± 9.6 %
		Y	1.80	63.81	11.12		80.0	
		Z	4.65	74.88	17.60		80.0	
10484-AAA	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	1.88	64.05	11.24	2.23	80.0	± 9.6 %
		Y	1.74	63.14	10.78		80.0	
		Z	4.29	73.52	17.08		80.0	
10485-AAC	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	2.42	70.99	16.75	2.23	80.0	± 9.6 %
		Y	2.20	69.63	15.96		80.0	
		Z	3.80	76.41	19.93		80.0	
10486-AAC	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	2.25	66.38	13.82	2.23	80.0	± 9.6 %
		Y	2.07	65.25	13.10		80.0	
		Z	3.45	71.18	17.22		80.0	
10487-AAC	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	2.24	65.94	13.58	2.23	80.0	± 9.6 %
		Y	2.07	64.88	12.89		80.0	
		Z	3.42	70.64	16.97		80.0	
10488-AAC	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	2.77	70.73	17.86	2.23	80.0	± 9.6 %
		Y	2.65	70.03	17.45		80.0	
		Z	3.79	74.17	19.68		80.0	
10489-AAC	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	2.87	67.90	16.40	2.23	80.0	± 9.6 %
		Y	2.78	67.42	16.09		80.0	
		Z	3.52	69.75	17.81		80.0	
10490-AAC	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	2.95	67.76	16.33	2.23	80.0	± 9.6 %
		Y	2.86	67.30	16.03		80.0	
		Z	3.60	69.51	17.71		80.0	
10491-AAC	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	3.06	69.47	17.55	2.23	80.0	± 9.6 %
		Y	2.96	68.94	17.24		80.0	
		Z	3.91	72.06	18.89		80.0	
10492-AAC	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	3.23	67.24	16.58	2.23	80.0	± 9.6 %
		Y	3.15	66.90	16.36		80.0	
		Z	3.81	68.69	17.61		80.0	

Certificate No: EX3-7346_Feb18

Page 28 of 39

Appendix B: DAE and Probe Calibration Certificate

EX3DV4- SN:7346

February 28, 2018

10493-AAC	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	3.29	67.13	16.53	2.23	80.0	± 9.6 %
		Y	3.21	66.80	16.31		80.0	
		Z	3.87	68.53	17.55		80.0	
10494-AAC	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	3.27	70.74	18.00	2.23	80.0	± 9.6 %
		Y	3.15	70.13	17.67		80.0	
		Z	4.33	73.95	19.50		80.0	
10495-AAC	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	3.24	67.47	16.79	2.23	80.0	± 9.6 %
		Y	3.17	67.13	16.58		80.0	
		Z	3.85	69.12	17.83		80.0	
10496-AAC	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	3.33	67.29	16.73	2.23	80.0	± 9.6 %
		Y	3.26	66.97	16.53		80.0	
		Z	3.92	68.78	17.71		80.0	
10497-AAA	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	0.97	60.40	8.81	2.23	80.0	± 9.6 %
		Y	0.92	60.00	8.26		80.0	
		Z	2.78	71.82	16.09		80.0	
10498-AAA	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	1.11	60.00	7.28	2.23	80.0	± 9.6 %
		Y	1.10	60.00	7.02		80.0	
		Z	1.82	63.65	11.31		80.0	
10499-AAA	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	1.13	60.00	7.10	2.23	80.0	± 9.6 %
		Y	1.12	60.00	6.85		80.0	
		Z	1.74	62.87	10.77		80.0	
10500-AAA	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	2.56	70.86	17.19	2.23	80.0	± 9.6 %
		Y	2.39	69.84	16.59		80.0	
		Z	3.69	74.97	19.64		80.0	
10501-AAA	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	2.57	67.44	15.02	2.23	80.0	± 9.6 %
		Y	2.42	66.58	14.46		80.0	
		Z	3.48	70.59	17.44		80.0	
10502-AAA	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	2.61	67.24	14.84	2.23	80.0	± 9.6 %
		Y	2.45	66.39	14.29		80.0	
		Z	3.53	70.40	17.29		80.0	
10503-AAC	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	2.74	70.53	17.76	2.23	80.0	± 9.6 %
		Y	2.61	69.82	17.34		80.0	
		Z	3.74	73.96	19.58		80.0	
10504-AAC	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	2.85	67.79	16.34	2.23	80.0	± 9.6 %
		Y	2.76	67.31	16.02		80.0	
		Z	3.50	69.66	17.75		80.0	
10505-AAC	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	2.93	67.66	16.27	2.23	80.0	± 9.6 %
		Y	2.84	67.20	15.96		80.0	
		Z	3.58	69.42	17.66		80.0	
10506-AAC	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	3.25	70.60	17.92	2.23	80.0	± 9.6 %
		Y	3.13	69.98	17.59		80.0	
		Z	4.29	73.80	19.43		80.0	
10507-AAC	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	3.23	67.41	16.75	2.23	80.0	± 9.6 %
		Y	3.16	67.06	16.53		80.0	
		Z	3.84	69.06	17.79		80.0	

Certificate No: EX3-7346_Feb18

Page 29 of 39

Appendix B: DAE and Probe Calibration Certificate

EX3DV4- SN:7346

February 28, 2018

10508-AAC	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	3.32	67.22	16.68	2.23	80.0	± 9.6 %
		Y	3.25	66.89	16.48		80.0	
		Z	3.91	68.71	17.66		80.0	
10509-AAC	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	3.67	69.70	17.56	2.23	80.0	± 9.6 %
		Y	3.56	69.21	17.30		80.0	
		Z	4.55	72.10	18.70		80.0	
10510-AAC	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	3.71	67.18	16.82	2.23	80.0	± 9.6 %
		Y	3.64	66.88	16.65		80.0	
		Z	4.30	68.66	17.68		80.0	
10511-AAC	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	3.78	67.02	16.78	2.23	80.0	± 9.6 %
		Y	3.71	66.74	16.61		80.0	
		Z	4.34	68.36	17.58		80.0	
10512-AAC	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	3.75	70.91	17.94	2.23	80.0	± 9.6 %
		Y	3.61	70.30	17.63		80.0	
		Z	4.87	74.09	19.36		80.0	
10513-AAC	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	3.59	67.30	16.88	2.23	80.0	± 9.6 %
		Y	3.52	66.98	16.70		80.0	
		Z	4.20	68.99	17.82		80.0	
10514-AAC	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	3.64	66.98	16.78	2.23	80.0	± 9.6 %
		Y	3.58	66.69	16.62		80.0	
		Z	4.20	68.49	17.65		80.0	
10515-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 2 Mbps, 99pc duty cycle)	X	0.95	63.34	14.65	0.00	150.0	± 9.6 %
		Y	0.86	62.15	13.49		150.0	
		Z	0.95	63.02	14.53		150.0	
10516-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 5.5 Mbps, 99pc duty cycle)	X	0.59	70.82	17.39	0.00	150.0	± 9.6 %
		Y	0.41	65.72	13.46		150.0	
		Z	0.57	69.76	16.78		150.0	
10517-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps, 99pc duty cycle)	X	0.79	65.16	15.25	0.00	150.0	± 9.6 %
		Y	0.68	63.22	13.51		150.0	
		Z	0.80	64.83	15.08		150.0	
10518-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 9 Mbps, 99pc duty cycle)	X	4.32	66.89	16.15	0.00	150.0	± 9.6 %
		Y	4.22	66.51	15.84		150.0	
		Z	4.51	66.68	16.14		150.0	
10519-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 12 Mbps, 99pc duty cycle)	X	4.47	67.05	16.23	0.00	150.0	± 9.6 %
		Y	4.36	66.68	15.93		150.0	
		Z	4.69	66.91	16.26		150.0	
10520-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 18 Mbps, 99pc duty cycle)	X	4.33	66.99	16.15	0.00	150.0	± 9.6 %
		Y	4.22	66.59	15.83		150.0	
		Z	4.54	66.87	16.18		150.0	
10521-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 24 Mbps, 99pc duty cycle)	X	4.26	66.96	16.13	0.00	150.0	± 9.6 %
		Y	4.15	66.55	15.81		150.0	
		Z	4.48	66.86	16.16		150.0	
10522-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 36 Mbps, 99pc duty cycle)	X	4.31	67.07	16.22	0.00	150.0	± 9.6 %
		Y	4.20	66.66	15.89		150.0	
		Z	4.54	66.96	16.25		150.0	

Certificate No: EX3-7346_Feb18

Page 30 of 39

Appendix B: DAE and Probe Calibration Certificate

EX3DV4- SN:7346

February 28, 2018

10523-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 48 Mbps, 99pc duty cycle)	X	4.24	67.09	16.15	0.00	150.0	± 9.6 %
		Y	4.13	66.68	15.83		150.0	
		Z	4.42	66.83	16.10		150.0	
10524-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 54 Mbps, 99pc duty cycle)	X	4.26	67.04	16.22	0.00	150.0	± 9.6 %
		Y	4.15	66.64	15.89		150.0	
		Z	4.48	66.87	16.21		150.0	
10525-AAB	IEEE 802.11ac WiFi (20MHz, MCS0, 99pc duty cycle)	X	4.30	66.16	15.85	0.00	150.0	± 9.6 %
		Y	4.19	65.75	15.53		150.0	
		Z	4.47	65.93	15.81		150.0	
10526-AAB	IEEE 802.11ac WiFi (20MHz, MCS1, 99pc duty cycle)	X	4.41	66.43	15.96	0.00	150.0	± 9.6 %
		Y	4.30	66.01	15.64		150.0	
		Z	4.63	66.29	15.95		150.0	
10527-AAB	IEEE 802.11ac WiFi (20MHz, MCS2, 99pc duty cycle)	X	4.35	66.40	15.90	0.00	150.0	± 9.6 %
		Y	4.23	65.98	15.57		150.0	
		Z	4.56	66.25	15.89		150.0	
10528-AAB	IEEE 802.11ac WiFi (20MHz, MCS3, 99pc duty cycle)	X	4.36	66.42	15.93	0.00	150.0	± 9.6 %
		Y	4.25	65.99	15.61		150.0	
		Z	4.57	66.27	15.93		150.0	
10529-AAB	IEEE 802.11ac WiFi (20MHz, MCS4, 99pc duty cycle)	X	4.36	66.42	15.93	0.00	150.0	± 9.6 %
		Y	4.25	65.99	15.61		150.0	
		Z	4.57	66.27	15.93		150.0	
10531-AAB	IEEE 802.11ac WiFi (20MHz, MCS6, 99pc duty cycle)	X	4.32	66.43	15.91	0.00	150.0	± 9.6 %
		Y	4.21	66.00	15.57		150.0	
		Z	4.56	66.37	15.94		150.0	
10532-AAB	IEEE 802.11ac WiFi (20MHz, MCS7, 99pc duty cycle)	X	4.21	66.30	15.84	0.00	150.0	± 9.6 %
		Y	4.09	65.86	15.50		150.0	
		Z	4.42	66.22	15.87		150.0	
10533-AAB	IEEE 802.11ac WiFi (20MHz, MCS8, 99pc duty cycle)	X	4.37	66.50	15.94	0.00	150.0	± 9.6 %
		Y	4.25	66.07	15.60		150.0	
		Z	4.58	66.32	15.92		150.0	
10534-AAB	IEEE 802.11ac WiFi (40MHz, MCS0, 99pc duty cycle)	X	4.92	66.39	15.99	0.00	150.0	± 9.6 %
		Y	4.82	66.05	15.73		150.0	
		Z	5.10	66.37	15.98		150.0	
10535-AAB	IEEE 802.11ac WiFi (40MHz, MCS1, 99pc duty cycle)	X	4.96	66.51	16.05	0.00	150.0	± 9.6 %
		Y	4.86	66.16	15.78		150.0	
		Z	5.17	66.54	16.06		150.0	
10536-AAB	IEEE 802.11ac WiFi (40MHz, MCS2, 99pc duty cycle)	X	4.85	66.52	16.03	0.00	150.0	± 9.6 %
		Y	4.75	66.15	15.75		150.0	
		Z	5.04	66.49	16.02		150.0	
10537-AAB	IEEE 802.11ac WiFi (40MHz, MCS3, 99pc duty cycle)	X	4.91	66.52	16.03	0.00	150.0	± 9.6 %
		Y	4.82	66.17	15.77		150.0	
		Z	5.10	66.46	16.01		150.0	
10538-AAB	IEEE 802.11ac WiFi (40MHz, MCS4, 99pc duty cycle)	X	4.98	66.47	16.05	0.00	150.0	± 9.6 %
		Y	4.88	66.13	15.79		150.0	
		Z	5.19	66.48	16.06		150.0	
10540-AAB	IEEE 802.11ac WiFi (40MHz, MCS6, 99pc duty cycle)	X	4.91	66.43	16.04	0.00	150.0	± 9.6 %
		Y	4.81	66.08	15.78		150.0	
		Z	5.12	66.49	16.08		150.0	

Certificate No: EX3-7346_Feb18

Page 31 of 39

Appendix B: DAE and Probe Calibration Certificate

EX3DV4- SN:7346

February 28, 2018

10541-AAB	IEEE 802.11ac WiFi (40MHz, MCS7, 99pc duty cycle)	X	4.90	66.36	15.99	0.00	150.0	± 9.6 %
		Y	4.80	66.01	15.73		150.0	
		Z	5.09	66.37	16.01		150.0	
10542-AAB	IEEE 802.11ac WiFi (40MHz, MCS8, 99pc duty cycle)	X	5.05	66.46	16.06	0.00	150.0	± 9.6 %
		Y	4.95	66.12	15.80		150.0	
		Z	5.24	66.44	16.06		150.0	
10543-AAB	IEEE 802.11ac WiFi (40MHz, MCS9, 99pc duty cycle)	X	5.12	66.53	16.12	0.00	150.0	± 9.6 %
		Y	5.03	66.22	15.89		150.0	
		Z	5.32	66.47	16.09		150.0	
10544-AAB	IEEE 802.11ac WiFi (80MHz, MCS0, 99pc duty cycle)	X	5.27	66.47	15.98	0.00	150.0	± 9.6 %
		Y	5.17	66.14	15.74		150.0	
		Z	5.41	66.49	15.98		150.0	
10545-AAB	IEEE 802.11ac WiFi (80MHz, MCS1, 99pc duty cycle)	X	5.43	66.88	16.14	0.00	150.0	± 9.6 %
		Y	5.34	66.58	15.92		150.0	
		Z	5.60	66.88	16.13		150.0	
10546-AAB	IEEE 802.11ac WiFi (80MHz, MCS2, 99pc duty cycle)	X	5.29	66.59	16.01	0.00	150.0	± 9.6 %
		Y	5.20	66.26	15.77		150.0	
		Z	5.48	66.69	16.05		150.0	
10547-AAB	IEEE 802.11ac WiFi (80MHz, MCS3, 99pc duty cycle)	X	5.37	66.69	16.06	0.00	150.0	± 9.6 %
		Y	5.29	66.39	15.83		150.0	
		Z	5.54	66.73	16.06		150.0	
10548-AAB	IEEE 802.11ac WiFi (80MHz, MCS4, 99pc duty cycle)	X	5.50	67.26	16.32	0.00	150.0	± 9.6 %
		Y	5.41	66.94	16.08		150.0	
		Z	5.76	67.57	16.45		150.0	
10550-AAB	IEEE 802.11ac WiFi (80MHz, MCS6, 99pc duty cycle)	X	5.35	66.76	16.11	0.00	150.0	± 9.6 %
		Y	5.27	66.47	15.89		150.0	
		Z	5.50	66.70	16.07		150.0	
10551-AAB	IEEE 802.11ac WiFi (80MHz, MCS7, 99pc duty cycle)	X	5.29	66.55	15.97	0.00	150.0	± 9.6 %
		Y	5.19	66.22	15.73		150.0	
		Z	5.51	66.75	16.05		150.0	
10552-AAB	IEEE 802.11ac WiFi (80MHz, MCS8, 99pc duty cycle)	X	5.28	66.60	15.99	0.00	150.0	± 9.6 %
		Y	5.18	66.26	15.74		150.0	
		Z	5.43	66.56	15.97		150.0	
10553-AAB	IEEE 802.11ac WiFi (80MHz, MCS9, 99pc duty cycle)	X	5.33	66.54	15.99	0.00	150.0	± 9.6 %
		Y	5.23	66.21	15.75		150.0	
		Z	5.51	66.59	16.01		150.0	
10554-AAC	IEEE 802.11ac WiFi (160MHz, MCS0, 99pc duty cycle)	X	5.68	66.80	16.06	0.00	150.0	± 9.6 %
		Y	5.60	66.49	15.83		150.0	
		Z	5.82	66.85	16.07		150.0	
10555-AAC	IEEE 802.11ac WiFi (160MHz, MCS1, 99pc duty cycle)	X	5.77	67.01	16.15	0.00	150.0	± 9.6 %
		Y	5.68	66.70	15.92		150.0	
		Z	5.94	67.13	16.19		150.0	
10556-AAC	IEEE 802.11ac WiFi (160MHz, MCS2, 99pc duty cycle)	X	5.81	67.11	16.19	0.00	150.0	± 9.6 %
		Y	5.73	66.82	15.98		150.0	
		Z	5.96	67.18	16.21		150.0	
10557-AAC	IEEE 802.11ac WiFi (160MHz, MCS3, 99pc duty cycle)	X	5.77	67.00	16.15	0.00	150.0	± 9.6 %
		Y	5.68	66.69	15.93		150.0	
		Z	5.93	67.09	16.19		150.0	

Certificate No: EX3-7346_Feb18

Page 32 of 39

Appendix B: DAE and Probe Calibration Certificate

EX3DV4- SN:7346

February 28, 2018

10558-AAC	IEEE 802.11ac WiFi (160MHz, MCS4, 99pc duty cycle)	X	5.78	67.05	16.19	0.00	150.0	± 9.6 %
		Y	5.68	66.72	15.96		150.0	
		Z	5.98	67.25	16.28		150.0	
10560-AAC	IEEE 802.11ac WiFi (160MHz, MCS6, 99pc duty cycle)	X	5.80	66.98	16.20	0.00	150.0	± 9.6 %
		Y	5.70	66.67	15.98		150.0	
		Z	5.97	67.11	16.25		150.0	
10561-AAC	IEEE 802.11ac WiFi (160MHz, MCS7, 99pc duty cycle)	X	5.73	66.96	16.22	0.00	150.0	± 9.6 %
		Y	5.64	66.66	16.00		150.0	
		Z	5.90	67.07	16.26		150.0	
10562-AAC	IEEE 802.11ac WiFi (160MHz, MCS8, 99pc duty cycle)	X	5.78	67.12	16.30	0.00	150.0	± 9.6 %
		Y	5.68	66.80	16.07		150.0	
		Z	6.01	67.43	16.44		150.0	
10563-AAC	IEEE 802.11ac WiFi (160MHz, MCS9, 99pc duty cycle)	X	5.88	67.11	16.26	0.00	150.0	± 9.6 %
		Y	5.80	66.82	16.05		150.0	
		Z	6.21	67.65	16.51		150.0	
10564-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 9 Mbps, 99pc duty cycle)	X	4.83	66.89	16.27	0.46	150.0	± 9.6 %
		Y	4.54	66.57	16.00		150.0	
		Z	4.83	66.77	16.31		150.0	
10565-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 12 Mbps, 99pc duty cycle)	X	4.83	67.31	16.59	0.46	150.0	± 9.6 %
		Y	4.73	66.98	16.33		150.0	
		Z	5.06	67.21	16.62		150.0	
10566-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 18 Mbps, 99pc duty cycle)	X	4.66	67.11	16.39	0.46	150.0	± 9.6 %
		Y	4.57	66.78	16.12		150.0	
		Z	4.90	67.06	16.44		150.0	
10567-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 24 Mbps, 99pc duty cycle)	X	4.70	67.53	16.77	0.46	150.0	± 9.6 %
		Y	4.60	67.20	16.51		150.0	
		Z	4.92	67.44	16.79		150.0	
10568-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 36 Mbps, 99pc duty cycle)	X	4.55	66.82	16.11	0.46	150.0	± 9.6 %
		Y	4.45	66.47	15.82		150.0	
		Z	4.81	66.84	16.23		150.0	
10569-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 48 Mbps, 99pc duty cycle)	X	4.69	67.77	16.92	0.46	150.0	± 9.6 %
		Y	4.59	67.44	16.66		150.0	
		Z	4.88	67.54	16.86		150.0	
10570-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 54 Mbps, 99pc duty cycle)	X	4.69	67.54	16.80	0.46	150.0	± 9.6 %
		Y	4.59	67.20	16.53		150.0	
		Z	4.91	67.38	16.78		150.0	
10571-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 90pc duty cycle)	X	1.08	63.88	15.15	0.46	130.0	± 9.6 %
		Y	1.00	62.92	14.25		130.0	
		Z	1.14	64.25	15.52		130.0	
10572-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 2 Mbps, 90pc duty cycle)	X	1.08	64.40	15.50	0.46	130.0	± 9.6 %
		Y	1.00	63.37	14.56		130.0	
		Z	1.15	64.80	15.87		130.0	
10573-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 5.5 Mbps, 90pc duty cycle)	X	1.29	80.57	21.65	0.46	130.0	± 9.6 %
		Y	0.81	72.73	17.38		130.0	
		Z	1.91	85.72	23.49		130.0	
10574-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps, 90pc duty cycle)	X	1.13	69.56	18.30	0.46	130.0	± 9.6 %
		Y	0.99	67.49	16.76		130.0	
		Z	1.24	70.37	18.75		130.0	

Certificate No: EX3-7346_Feb18

Page 33 of 39

Appendix B: DAE and Probe Calibration Certificate

EX3DV4-- SN:7346

February 28, 2018

10575-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps, 90pc duty cycle)	X	4.40	66.63	16.27	0.46	130.0	± 9.6 %
		Y	4.32	66.34	16.03		130.0	
		Z	4.62	66.57	16.38		130.0	
10576-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 9 Mbps, 90pc duty cycle)	X	4.44	66.84	16.36	0.46	130.0	± 9.6 %
		Y	4.35	66.55	16.13		130.0	
		Z	4.65	66.73	16.45		130.0	
10577-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 12 Mbps, 90pc duty cycle)	X	4.60	67.07	16.50	0.46	130.0	± 9.6 %
		Y	4.51	66.79	16.28		130.0	
		Z	4.85	67.02	16.61		130.0	
10578-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 18 Mbps, 90pc duty cycle)	X	4.50	67.22	16.62	0.46	130.0	± 9.6 %
		Y	4.42	66.93	16.38		130.0	
		Z	4.75	67.17	16.71		130.0	
10579-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 24 Mbps, 90pc duty cycle)	X	4.25	66.37	15.84	0.46	130.0	± 9.6 %
		Y	4.17	66.06	15.59		130.0	
		Z	4.51	66.47	16.03		130.0	
10580-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 36 Mbps, 90pc duty cycle)	X	4.28	66.41	15.86	0.46	130.0	± 9.6 %
		Y	4.20	66.10	15.60		130.0	
		Z	4.56	66.52	16.06		130.0	
10581-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 48 Mbps, 90pc duty cycle)	X	4.41	67.30	16.59	0.46	130.0	± 9.6 %
		Y	4.33	67.01	16.36		130.0	
		Z	4.64	67.21	16.66		130.0	
10582-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 54 Mbps, 90pc duty cycle)	X	4.18	66.12	15.61	0.46	130.0	± 9.6 %
		Y	4.09	65.81	15.35		130.0	
		Z	4.45	66.23	15.83		130.0	
10583-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 6 Mbps, 90pc duty cycle)	X	4.40	66.63	16.27	0.46	130.0	± 9.6 %
		Y	4.32	66.34	16.03		130.0	
		Z	4.62	66.57	16.38		130.0	
10584-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 9 Mbps, 90pc duty cycle)	X	4.44	66.84	16.36	0.46	130.0	± 9.6 %
		Y	4.35	66.55	16.13		130.0	
		Z	4.65	66.73	16.45		130.0	
10585-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 12 Mbps, 90pc duty cycle)	X	4.60	67.07	16.50	0.46	130.0	± 9.6 %
		Y	4.51	66.79	16.28		130.0	
		Z	4.85	67.02	16.61		130.0	
10586-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 18 Mbps, 90pc duty cycle)	X	4.50	67.22	16.62	0.46	130.0	± 9.6 %
		Y	4.42	66.93	16.38		130.0	
		Z	4.75	67.17	16.71		130.0	
10587-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 24 Mbps, 90pc duty cycle)	X	4.25	66.37	15.84	0.46	130.0	± 9.6 %
		Y	4.17	66.06	15.59		130.0	
		Z	4.51	66.47	16.03		130.0	
10588-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 36 Mbps, 90pc duty cycle)	X	4.28	66.41	15.86	0.46	130.0	± 9.6 %
		Y	4.20	66.10	15.60		130.0	
		Z	4.56	66.52	16.06		130.0	
10589-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 48 Mbps, 90pc duty cycle)	X	4.41	67.30	16.59	0.46	130.0	± 9.6 %
		Y	4.33	67.01	16.36		130.0	
		Z	4.64	67.21	16.66		130.0	
10590-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 54 Mbps, 90pc duty cycle)	X	4.18	66.12	15.61	0.46	130.0	± 9.6 %
		Y	4.09	65.81	15.35		130.0	
		Z	4.45	66.23	15.83		130.0	

Certificate No: EX3-7346_Feb18

Page 34 of 39

Appendix B: DAE and Probe Calibration Certificate

EX3DV4- SN:7346

February 28, 2018

10591-AAB	IEEE 802.11n (HT Mixed, 20MHz, MCS0, 90pc duty cycle)	X	4.56	66.73	16.40	0.46	130.0	± 9.6 %
		Y	4.49	66.46	16.18		130.0	
		Z	4.77	66.63	16.48		130.0	
10592-AAB	IEEE 802.11n (HT Mixed, 20MHz, MCS1, 90pc duty cycle)	X	4.68	67.01	16.52	0.46	130.0	± 9.6 %
		Y	4.60	66.74	16.30		130.0	
		Z	4.93	66.97	16.61		130.0	
10593-AAB	IEEE 802.11n (HT Mixed, 20MHz, MCS2, 90pc duty cycle)	X	4.60	66.88	16.37	0.46	130.0	± 9.6 %
		Y	4.51	66.60	16.15		130.0	
		Z	4.85	66.88	16.49		130.0	
10594-AAB	IEEE 802.11n (HT Mixed, 20MHz, MCS3, 90pc duty cycle)	X	4.65	67.06	16.54	0.46	130.0	± 9.6 %
		Y	4.57	66.79	16.33		130.0	
		Z	4.90	67.04	16.65		130.0	
10595-AAB	IEEE 802.11n (HT Mixed, 20MHz, MCS4, 90pc duty cycle)	X	4.62	67.04	16.45	0.46	130.0	± 9.6 %
		Y	4.53	66.76	16.23		130.0	
		Z	4.87	66.99	16.54		130.0	
10596-AAB	IEEE 802.11n (HT Mixed, 20MHz, MCS5, 90pc duty cycle)	X	4.55	66.99	16.44	0.46	130.0	± 9.6 %
		Y	4.46	66.71	16.21		130.0	
		Z	4.80	66.99	16.55		130.0	
10597-AAB	IEEE 802.11n (HT Mixed, 20MHz, MCS6, 90pc duty cycle)	X	4.50	66.86	16.29	0.46	130.0	± 9.6 %
		Y	4.41	66.57	16.05		130.0	
		Z	4.75	66.89	16.43		130.0	
10598-AAB	IEEE 802.11n (HT Mixed, 20MHz, MCS7, 90pc duty cycle)	X	4.49	67.11	16.57	0.46	130.0	± 9.6 %
		Y	4.41	66.82	16.34		130.0	
		Z	4.74	67.12	16.69		130.0	
10599-AAB	IEEE 802.11n (HT Mixed, 40MHz, MCS0, 90pc duty cycle)	X	5.24	67.17	16.64	0.46	130.0	± 9.6 %
		Y	5.18	66.96	16.48		130.0	
		Z	5.44	67.18	16.69		130.0	
10600-AAB	IEEE 802.11n (HT Mixed, 40MHz, MCS1, 90pc duty cycle)	X	5.32	67.47	16.76	0.46	130.0	± 9.6 %
		Y	5.27	67.29	16.61		130.0	
		Z	5.56	67.53	16.84		130.0	
10601-AAB	IEEE 802.11n (HT Mixed, 40MHz, MCS2, 90pc duty cycle)	X	5.24	67.29	16.69	0.46	130.0	± 9.6 %
		Y	5.18	67.09	16.53		130.0	
		Z	5.46	67.32	16.75		130.0	
10602-AAB	IEEE 802.11n (HT Mixed, 40MHz, MCS3, 90pc duty cycle)	X	5.32	67.29	16.61	0.46	130.0	± 9.6 %
		Y	5.26	67.08	16.44		130.0	
		Z	5.55	67.35	16.68		130.0	
10603-AAB	IEEE 802.11n (HT Mixed, 40MHz, MCS4, 90pc duty cycle)	X	5.39	67.60	16.90	0.46	130.0	± 9.6 %
		Y	5.33	67.39	16.74		130.0	
		Z	5.63	67.64	16.96		130.0	
10604-AAB	IEEE 802.11n (HT Mixed, 40MHz, MCS5, 90pc duty cycle)	X	5.27	67.22	16.69	0.46	130.0	± 9.6 %
		Y	5.20	66.98	16.50		130.0	
		Z	5.45	67.16	16.70		130.0	
10605-AAB	IEEE 802.11n (HT Mixed, 40MHz, MCS6, 90pc duty cycle)	X	5.32	67.35	16.75	0.46	130.0	± 9.6 %
		Y	5.25	67.14	16.59		130.0	
		Z	5.55	67.45	16.85		130.0	
10606-AAB	IEEE 802.11n (HT Mixed, 40MHz, MCS7, 90pc duty cycle)	X	5.11	66.82	16.34	0.46	130.0	± 9.6 %
		Y	5.05	66.61	16.17		130.0	
		Z	5.31	66.83	16.40		130.0	

Certificate No: EX3-7346_Feb18

Page 35 of 39

Appendix B: DAE and Probe Calibration Certificate

EX3DV4- SN:7346

February 28, 2018

10607-AAB	IEEE 802.11ac WiFi (20MHz, MCS0, 90pc duty cycle)	X	4.41	66.09	16.05	0.46	130.0	± 9.6 %
		Y	4.33	65.79	15.81		130.0	
		Z	4.61	65.96	16.11		130.0	
10608-AAB	IEEE 802.11ac WiFi (20MHz, MCS1, 90pc duty cycle)	X	4.55	66.40	16.19	0.46	130.0	± 9.6 %
		Y	4.46	66.10	15.95		130.0	
		Z	4.80	66.36	16.28		130.0	
10609-AAB	IEEE 802.11ac WiFi (20MHz, MCS2, 90pc duty cycle)	X	4.45	66.24	16.01	0.46	130.0	± 9.6 %
		Y	4.36	65.92	15.76		130.0	
		Z	4.69	66.21	16.12		130.0	
10610-AAB	IEEE 802.11ac WiFi (20MHz, MCS3, 90pc duty cycle)	X	4.50	66.41	16.19	0.46	130.0	± 9.6 %
		Y	4.41	66.10	15.95		130.0	
		Z	4.74	66.37	16.28		130.0	
10611-AAB	IEEE 802.11ac WiFi (20MHz, MCS4, 90pc duty cycle)	X	4.41	66.20	16.02	0.46	130.0	± 9.6 %
		Y	4.32	65.88	15.78		130.0	
		Z	4.65	66.17	16.12		130.0	
10612-AAB	IEEE 802.11ac WiFi (20MHz, MCS5, 90pc duty cycle)	X	4.40	66.31	16.06	0.46	130.0	± 9.6 %
		Y	4.30	65.98	15.80		130.0	
		Z	4.66	66.33	16.17		130.0	
10613-AAB	IEEE 802.11ac WiFi (20MHz, MCS6, 90pc duty cycle)	X	4.39	66.13	15.90	0.46	130.0	± 9.6 %
		Y	4.30	65.80	15.64		130.0	
		Z	4.67	66.21	16.05		130.0	
10614-AAB	IEEE 802.11ac WiFi (20MHz, MCS7, 90pc duty cycle)	X	4.37	66.38	16.16	0.46	130.0	± 9.6 %
		Y	4.27	66.05	15.91		130.0	
		Z	4.61	66.39	16.28		130.0	
10615-AAB	IEEE 802.11ac WiFi (20MHz, MCS8, 90pc duty cycle)	X	4.40	66.02	15.78	0.46	130.0	± 9.6 %
		Y	4.31	65.70	15.53		130.0	
		Z	4.66	66.02	15.91		130.0	
10616-AAB	IEEE 802.11ac WiFi (40MHz, MCS0, 90pc duty cycle)	X	5.05	66.37	16.23	0.46	130.0	± 9.6 %
		Y	4.97	66.11	16.03		130.0	
		Z	5.26	66.43	16.30		130.0	
10617-AAB	IEEE 802.11ac WiFi (40MHz, MCS1, 90pc duty cycle)	X	5.09	66.48	16.26	0.46	130.0	± 9.6 %
		Y	5.01	66.22	16.06		130.0	
		Z	5.33	66.60	16.36		130.0	
10618-AAB	IEEE 802.11ac WiFi (40MHz, MCS2, 90pc duty cycle)	X	5.00	66.56	16.31	0.46	130.0	± 9.6 %
		Y	4.92	66.28	16.11		130.0	
		Z	5.21	66.61	16.38		130.0	
10619-AAB	IEEE 802.11ac WiFi (40MHz, MCS3, 90pc duty cycle)	X	5.02	66.38	16.16	0.46	130.0	± 9.6 %
		Y	4.95	66.13	15.97		130.0	
		Z	5.23	66.42	16.22		130.0	
10620-AAB	IEEE 802.11ac WiFi (40MHz, MCS4, 90pc duty cycle)	X	5.09	66.37	16.20	0.46	130.0	± 9.6 %
		Y	5.01	66.12	16.01		130.0	
		Z	5.32	66.46	16.29		130.0	
10621-AAB	IEEE 802.11ac WiFi (40MHz, MCS5, 90pc duty cycle)	X	5.10	66.50	16.39	0.46	130.0	± 9.6 %
		Y	5.02	66.25	16.20		130.0	
		Z	5.32	66.59	16.47		130.0	
10622-AAB	IEEE 802.11ac WiFi (40MHz, MCS6, 90pc duty cycle)	X	5.09	66.58	16.42	0.46	130.0	± 9.6 %
		Y	5.01	66.32	16.23		130.0	
		Z	5.33	66.74	16.54		130.0	

Certificate No: EX3-7346_Feb18

Page 36 of 39

Appendix B: DAE and Probe Calibration Certificate

EX3DV4- SN:7346

February 28, 2018

10623-AAB	IEEE 802.11ac WiFi (40MHz, MCS7, 90pc duty cycle)	X	4.98	66.14	16.06	0.46	130.0	± 9.6 %
		Y	4.90	65.88	15.86		130.0	
		Z	5.21	66.29	16.19		130.0	
10624-AAB	IEEE 802.11ac WiFi (40MHz, MCS8, 90pc duty cycle)	X	5.17	66.40	16.26	0.46	130.0	± 9.6 %
		Y	5.10	66.15	16.07		130.0	
		Z	5.40	66.48	16.34		130.0	
10625-AAB	IEEE 802.11ac WiFi (40MHz, MCS9, 90pc duty cycle)	X	5.26	66.52	16.38	0.46	130.0	± 9.6 %
		Y	5.18	66.28	16.20		130.0	
		Z	5.75	67.39	16.85		130.0	
10626-AAB	IEEE 802.11ac WiFi (80MHz, MCS0, 90pc duty cycle)	X	5.38	66.40	16.18	0.46	130.0	± 9.6 %
		Y	5.31	66.15	16.00		130.0	
		Z	5.56	66.50	16.26		130.0	
10627-AAB	IEEE 802.11ac WiFi (80MHz, MCS1, 90pc duty cycle)	X	5.60	66.96	16.44	0.46	130.0	± 9.6 %
		Y	5.53	66.75	16.28		130.0	
		Z	5.79	67.03	16.48		130.0	
10628-AAB	IEEE 802.11ac WiFi (80MHz, MCS2, 90pc duty cycle)	X	5.37	66.37	16.07	0.46	130.0	± 9.6 %
		Y	5.30	66.11	15.88		130.0	
		Z	5.59	66.59	16.20		130.0	
10629-AAB	IEEE 802.11ac WiFi (80MHz, MCS3, 90pc duty cycle)	X	5.47	66.54	16.15	0.46	130.0	± 9.6 %
		Y	5.41	66.33	15.99		130.0	
		Z	5.66	66.63	16.22		130.0	
10630-AAB	IEEE 802.11ac WiFi (80MHz, MCS4, 90pc duty cycle)	X	5.68	67.37	16.57	0.46	130.0	± 9.6 %
		Y	5.61	67.15	16.41		130.0	
		Z	6.05	68.00	16.90		130.0	
10631-AAB	IEEE 802.11ac WiFi (80MHz, MCS5, 90pc duty cycle)	X	5.68	67.48	16.82	0.46	130.0	± 9.6 %
		Y	5.60	67.24	16.65		130.0	
		Z	5.98	67.87	17.02		130.0	
10632-AAB	IEEE 802.11ac WiFi (80MHz, MCS6, 90pc duty cycle)	X	5.60	67.16	16.68	0.46	130.0	± 9.6 %
		Y	5.54	66.97	16.53		130.0	
		Z	5.76	67.09	16.65		130.0	
10633-AAB	IEEE 802.11ac WiFi (80MHz, MCS7, 90pc duty cycle)	X	5.40	66.46	16.15	0.46	130.0	± 9.6 %
		Y	5.32	66.20	15.96		130.0	
		Z	5.66	66.76	16.32		130.0	
10634-AAB	IEEE 802.11ac WiFi (80MHz, MCS8, 90pc duty cycle)	X	5.43	66.66	16.30	0.46	130.0	± 9.6 %
		Y	5.36	66.40	16.12		130.0	
		Z	5.64	66.78	16.39		130.0	
10635-AAB	IEEE 802.11ac WiFi (80MHz, MCS9, 90pc duty cycle)	X	5.29	65.89	15.64	0.46	130.0	± 9.6 %
		Y	5.21	65.62	15.45		130.0	
		Z	5.52	66.14	15.81		130.0	
10636-AAC	IEEE 802.11ac WiFi (160MHz, MCS0, 90pc duty cycle)	X	5.81	66.74	16.26	0.46	130.0	± 9.6 %
		Y	5.75	66.51	16.10		130.0	
		Z	5.97	66.86	16.34		130.0	
10637-AAC	IEEE 802.11ac WiFi (160MHz, MCS1, 90pc duty cycle)	X	5.92	67.03	16.39	0.46	130.0	± 9.6 %
		Y	5.86	66.80	16.23		130.0	
		Z	6.12	67.23	16.51		130.0	
10638-AAC	IEEE 802.11ac WiFi (160MHz, MCS2, 90pc duty cycle)	X	5.96	67.11	16.41	0.46	130.0	± 9.6 %
		Y	5.89	66.88	16.25		130.0	
		Z	6.12	67.21	16.48		130.0	

Certificate No: EX3-7346_Feb18

Page 37 of 39

Appendix B: DAE and Probe Calibration Certificate

EX3DV4- SN:7346

February 28, 2018

10639-AAC	IEEE 802.11ac WiFi (160MHz, MCS3, 90pc duty cycle)	X	5.91	66.98	16.39	0.46	130.0	± 9.6 %
		Y	5.84	66.75	16.23		130.0	
		Z	6.10	67.16	16.50		130.0	
10640-AAC	IEEE 802.11ac WiFi (160MHz, MCS4, 90pc duty cycle)	X	5.87	66.86	16.27	0.46	130.0	± 9.6 %
		Y	5.79	66.60	16.09		130.0	
		Z	6.10	67.18	16.45		130.0	
10641-AAC	IEEE 802.11ac WiFi (160MHz, MCS5, 90pc duty cycle)	X	5.96	66.94	16.33	0.46	130.0	± 9.6 %
		Y	5.90	66.72	16.18		130.0	
		Z	6.15	67.08	16.42		130.0	
10642-AAC	IEEE 802.11ac WiFi (160MHz, MCS6, 90pc duty cycle)	X	5.99	67.15	16.61	0.46	130.0	± 9.6 %
		Y	5.92	66.92	16.45		130.0	
		Z	6.19	67.33	16.71		130.0	
10643-AAC	IEEE 802.11ac WiFi (160MHz, MCS7, 90pc duty cycle)	X	5.84	66.83	16.34	0.46	130.0	± 9.6 %
		Y	5.77	66.59	16.17		130.0	
		Z	6.03	67.02	16.45		130.0	
10644-AAC	IEEE 802.11ac WiFi (160MHz, MCS8, 90pc duty cycle)	X	5.89	67.02	16.45	0.46	130.0	± 9.6 %
		Y	5.82	66.76	16.27		130.0	
		Z	6.18	67.50	16.71		130.0	
10645-AAC	IEEE 802.11ac WiFi (160MHz, MCS9, 90pc duty cycle)	X	6.01	67.04	16.43	0.46	130.0	± 9.6 %
		Y	5.95	66.83	16.28		130.0	
		Z	6.48	67.98	16.92		130.0	
10646-AAD	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, QPSK, UL Subframe=2,7)	X	7.70	95.53	33.78	9.30	60.0	± 9.6 %
		Y	6.86	91.23	32.03		60.0	
		Z	21.92	116.52	40.27		60.0	
10647-AAC	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK, UL Subframe=2,7)	X	6.53	92.04	32.66	9.30	60.0	± 9.6 %
		Y	6.02	88.67	31.21		60.0	
		Z	18.18	112.72	39.29		60.0	
10648-AAA	CDMA2000 (1x Advanced)	X	0.49	61.53	8.17	0.00	150.0	± 9.6 %
		Y	0.39	60.00	6.31		150.0	
		Z	0.66	63.15	10.45		150.0	
10652-AAB	LTE-TDD (OFDMA, 5 MHz, E-TM 3.1, Clipping 44%)	X	3.19	66.37	15.95	2.23	80.0	± 9.6 %
		Y	3.09	65.90	15.62		80.0	
		Z	3.59	66.99	16.74		80.0	
10653-AAB	LTE-TDD (OFDMA, 10 MHz, E-TM 3.1, Clipping 44%)	X	3.74	65.68	16.24	2.23	80.0	± 9.6 %
		Y	3.66	65.37	16.03		80.0	
		Z	4.09	66.23	16.79		80.0	
10654-AAB	LTE-TDD (OFDMA, 15 MHz, E-TM 3.1, Clipping 44%)	X	3.76	65.29	16.28	2.23	80.0	± 9.6 %
		Y	3.69	65.01	16.09		80.0	
		Z	4.06	65.86	16.78		80.0	
10655-AAB	LTE-TDD (OFDMA, 20 MHz, E-TM 3.1, Clipping 44%)	X	3.83	65.21	16.31	2.23	80.0	± 9.6 %
		Y	3.77	64.93	16.13		80.0	
		Z	4.12	65.84	16.81		80.0	
10658-AAA	Pulse Waveform (200Hz, 10%)	X	5.18	73.54	13.48	10.00	50.0	± 9.6 %
		Y	12.90	83.93	17.73		50.0	
		Z	100.00	112.89	26.88		50.0	
10659-AAA	Pulse Waveform (200Hz, 20%)	X	100.00	100.82	19.67	6.99	60.0	± 9.6 %
		Y	100.00	104.30	21.46		60.0	
		Z	100.00	113.27	26.00		60.0	

Certificate No: EX3-7346_Feb18

Page 38 of 39

Appendix B: DAE and Probe Calibration Certificate

EX3DV4- SN:7346

February 28, 2018

10660- AAA	Pulse Waveform (200Hz, 40%)	X	100.00	100.08	18.20	3.98	80.0	± 9.6 %
		Y	100.00	101.00	18.65		80.0	
		Z	100.00	116.39	26.02		80.0	
10661- AAA	Pulse Waveform (200Hz, 60%)	X	100.00	99.50	17.02	2.22	100.0	± 9.6 %
		Y	100.00	91.55	13.76		100.0	
		Z	100.00	121.08	26.66		100.0	
10662- AAA	Pulse Waveform (200Hz, 80%)	X	100.00	89.20	12.01	0.97	120.0	± 9.6 %
		Y	12.37	204.34	5.78		120.0	
		Z	100.00	125.71	26.63		120.0	

^c Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.