



10. BAND EDGE EMISSION


10.1. MEASUREMENT PROCEDURE

1. The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100kHz. The video bandwidth is set to 300kHz.
2. Transmitter set to the normal hopping mode at 2.4 and 2.4835 GHz.

10.2. TEST SET-UP

Radiated same as 10.2

Conducted set up



**10.3. RADIATED TEST RESULT**

Frequency	Emission Level	Limits	Margin	Detector	Comment
(MHz)	(dBμV/m)	(dBμV/m)	(dB)	Type	
GFSK					
2399.9	51.69	74	-22.31	peak	Vertical
2399.9	37.42	54	-16.58	AVG	Vertical
2399.9	45.33	74	-28.67	peak	Horizontal
2399.9	40.42	54	-13.58	AVG	Horizontal
2483.6	52.21	74	-21.79	peak	Vertical
2483.6	36.39	54	-17.61	AVG	Vertical
2483.6	53.48	74	-20.52	peak	Horizontal
2483.6	38.38	54	-15.62	AVG	Horizontal
π/4-DQPSK					
2399.9	49.36	74	-24.64	peak	Vertical
2399.9	39.42	54	-14.58	AVG	Vertical
2399.9	50.19	74	-23.81	peak	Horizontal
2399.9	39.42	54	-14.58	AVG	Horizontal
2483.6	51.12	74	-22.88	peak	Vertical
2483.6	39.33	54	-14.67	AVG	Vertical
2483.6	49.18	74	-24.82	peak	Horizontal
2483.6	38.27	54	-15.73	AVG	Horizontal
8DPSK					
2399.9	52.03	74	-21.97	peak	Vertical
2399.9	37.36	54	-16.64	AVG	Vertical
2399.9	49.46	74	-24.54	peak	Horizontal
2399.9	39.19	54	-14.81	AVG	Horizontal
2483.6	52.49	74	-21.51	peak	Vertical
2483.6	37.23	54	-16.77	AVG	Vertical
2483.6	52.25	74	-21.75	peak	Horizontal
2483.6	39.13	54	-14.87	AVG	Horizontal

RESULT: PASS


Note: The other modes radiation emission have enough 20dB margin.


Margin = Emission Level – Limit



10.4 CONDUCTED TEST RESULT

Test Graph





Note: All modes were tested, only the worst case record in the report.



12. TIME OF OCCUPANCY (DWELL TIME)

12.1. MEASUREMENT PROCEDURE

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

1. Span: Zero span, centered on a hopping channel.
2. RBW shall be $\leq$ channel spacing and where possible RBW should be set $\gg 1/T$, where T is the expected dwell time per channel.
3. Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel.
4. Detector function: Peak. Trace: Max hold.
5. Use the marker-delta function to determine the transmit time per hop.
6. Using the following equation:

The dwell time is calculated with the following formula:

$$\text{Dwell time} = t_{\text{pulse}} \times n_{\text{hops}} / \text{number of channels} \times 31.6 \text{ s}$$

Where:

t_{pulse} is the measured pulse time (pls. refer the plots of the spectrum analyser above) [s],

n_{hops} is the number of hops per second in the actual operating mode of the transmitter [1/s].

The hopping rate of the system is 1600 hops per second and the system uses 79 channels. For this reason one time slot has a length of 625 μs .

With the used hopping mode (DH5) a packet need 5 timeslots for transmitting and the next timeslot for receiving. So the system makes in worst case 266,67 hops per second in transmit mode ($n_{\text{hops}} = 266.667 \text{ 1/s}$)

12.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)

Same as described in section 8.2


12.3. MEASUREMENT EQUIPMENT USED

The same as described in section 6

**12.4. LIMITS AND MEASUREMENT RESULT**

Channel.	Burst Width [ms/hop/ch]	Dwell Time[ms]	Verdict	Limit (ms)
LCH	2.883	307.5204	PASS	400
MCH	2.883	307.5204	PASS	400
HCH	2.883	307.5204	PASS	400

Note: The DH5 for GFSK modulation is the worst case and recorded in the report.

Test Graph



14. FCC LINE CONDUCTED EMISSION TEST


14.1. LIMITS OF LINE CONDUCTED EMISSION TEST

Frequency	Maximum RF Line Voltage	
	Q.P.(dBuV)	Average(dBuV)
150kHz~500kHz	66-56	56-46
500kHz~5MHz	56	46
5MHz~30MHz	60	50

Note:

1. The lower limit shall apply at the transition frequency.
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

14.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST






14.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
2. Support equipment, if needed, was placed as per ANSI C63.10.
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
4. All support equipments received AC120V/60Hz power from a LISN, if any.
5. The EUT received DC charging voltage by adapter which received 120V/60Hz power by a LISN..
6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
8. During the above scans, the emissions were maximized by cable manipulation.
9. The test mode(s) were scanned during the preliminary test.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

14.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST

1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less -2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
3. The test data of the worst case condition(s) was reported on the Summary Data page.

**14.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST****LINE CONDUCTED EMISSION TEST LINE 1-L****Suspected List**


NO.	Freq. [MHz]	Level [dBμV]	Factor [dB]	Limit [dBμV]	Margin [dB]	Detector
1	0.1950	41.87	10.03	63.82	21.95	PK
2	0.4965	43.64	10.04	56.06	12.42	PK
3	0.9915	34.28	10.06	56.00	21.72	PK
4	1.4505	33.62	10.10	56.00	22.38	PK
5	1.9635	34.79	10.14	56.00	21.21	PK
6	3.3450	32.68	10.24	56.00	23.32	PK

Final Data List

NO.	Freq. [MHz]	Factor [dB]	QP Value [dBμV]	QP Limit [dBμV]	QP Margin [dB]	AV Value [dBμV]	AV Limit [dBμV]	AV Margin [dB]
1	0.1931	10.04	38.28	63.90	25.62	25.69	53.90	28.21
2	0.4974	10.04	42.70	56.04	13.34	32.81	46.04	13.23
3	0.9882	10.06	28.46	56.00	27.54	20.93	46.00	25.07
4	1.4450	10.10	29.30	56.00	26.70	21.09	46.00	24.91
5	1.9439	10.14	28.64	56.00	27.36	20.79	46.00	25.21
6	3.3421	10.24	26.90	56.00	29.10	20.16	46.00	25.84



LINE CONDUCTED EMISSION TEST LINE 2-N



Suspected List

NO.	Freq. [MHz]	Level [dBμV]	Factor [dB]	Limit [dBμV]	Margin [dB]	Detector
1	0.1545	43.86	10.03	65.75	21.89	PK
2	0.4965	43.57	10.04	56.06	12.49	PK
3	1.0185	34.74	10.07	56.00	21.26	PK
4	2.4180	34.31	10.18	56.00	21.69	PK
5	6.2115	33.49	10.22	60.00	26.51	PK
6	16.2060	32.74	9.98	60.00	27.26	PK

Final Data List

NO.	Freq. [MHz]	Factor [dB]	QP Value [dBμV]	QP Limit [dBμV]	QP Margin [dB]	AV Value [dBμV]	AV Limit [dBμV]	AV Margin [dB]
1	0.1544	10.03	37.14	65.76	28.62	25.29	55.76	30.47
2	0.4974	10.04	40.68	56.04	15.36	28.87	46.04	17.17
3	1.0180	10.07	28.67	56.00	27.33	20.76	46.00	25.24
4	2.3939	10.18	25.75	56.00	30.25	19.52	46.00	26.48
5	6.1694	10.23	26.74	60.00	33.26	19.44	50.00	30.56
6	16.0916	9.98	24.99	60.00	35.01	19.04	50.00	30.96




APPENDIX A: PHOTOGRAPHS OF TEST SETUP

LINE CONDUCTED EMISSION TEST SETUP



RADIATED EMISSION TEST SETUP





RADIATED EMISSION ABOVE 1G TEST SETUP



----END OF REPORT----