

TEST REPORT

Reference No. : WTS18S11130442W
FCC ID..... : 2AR6M-WPLCLED
Applicant..... : ShenZhen LiCheng Technology Co.,Ltd.
Address : Xinghe World Phase I, Bantian Street, Longgang District, Shenzhen, Guangdong, China
Manufacturer : Shenzhen Lixin Technology Co., Ltd.
Address : Tongyi Industrial Park, No. 351, Jihua Road, Longgang District, Shenzhen, China
Product..... : Wireless Presenter
Model(s)..... : WP01001
Standards..... : FCC CFR47 Part 15 C Section 15.247:2018
Date of Receipt sample.. : 2018-11-23
Date of Test..... : 2018-11-24 to 2019-01-25
Date of Issue : 2019-01-28
Test Result..... : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company.

The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

Prepared By:

Waltek Services (Shenzhen) Co., Ltd.

Address: 1/F., Fukangtai Building, West Baima Road, Songgang Street, Baoan District, Shenzhen, Guangdong, China

Test Site/Test Location:

Waltek Services (Shenzhen) Co., Ltd.

Address: 1/F., Fukangtai Building, West Baima Road, Songgang Street, Baoan District, Shenzhen, Guangdong, China

Tel :+86-755-83551033

Fax:+86-755-83552400

Compiled by:

Robin.Zhou

Robin Zhou / Test Engineer

Approved by:




Philo Zhong

Philo Zhong / Manager

1 Laboratories Introduction

Waltek Services (Shenzhen) Co., Ltd is a professional third-party testing and certification laboratory with multi-year product testing and certification experience, established strictly in accordance with ISO/IEC 17025 requirements, and accredited by ILAC (International Laboratory Accreditation Cooperation) member. A2LA (American Association for Laboratory Accreditation, the certification number is 4243.01) of USA, CNAS (China National Accreditation Service for Conformity Assessment, the registration number is L3110) of China. Meanwhile, Waltek has got recognition as registration and accreditation laboratory from EMSD (Electrical and Mechanical Services Department), and American Energy star, FCC (The Federal Communications Commission), CEC (California energy efficiency), ISED Canada (Innovation, Science and Economic Development Canada). It's the strategic partner and data recognition laboratory of international authoritative organizations, such as Intertek (ETL-SEMKO), TÜV Rheinland, TÜV SÜD, etc.



Waltek Services (Shenzhen) Co., Ltd is one of the largest and the most comprehensive third party testing laboratory in China. Our test capability covered four large fields: safety test. Electro Magnetic Compatibility (EMC), and energy performance, wireless radio. As a professional, comprehensive, justice international test organization, we still keep the scientific and rigorous work attitude to help each client satisfy the international standards and assist their product enter into globe market smoothly.

1.1 Test Facility

A. Accreditations for Conformity Assessment (International)

Country/Region	Scope Covered By	Scope	Note
USA	ISO/IEC 17025	FCC ID \ SDoC(VOC/DOC)	1
Canada		IC ID \ VOC	2
Japan		MIC-T \ MIC-R	-
Europe		EMCD \ RED	-
Taiwan		NCC	-
Hong Kong		OFCA	-
Australia		RCM	-
India		WPC	-
Thailand		NTC	-
Singapore		IDA	-
Note:			
1. FCC Designation No.: CN1201. Test Firm Registration No.: 523476.			
2. ISED CAB identifier: CN0013			

B.TCBs and Notify Bodies Recognized Testing Laboratory.

Recognized Testing Laboratory of ...	Notify body number
TUV Rheinland	Optional.
Intertek	
TUV SUD	
SGS	
Phoenix Testlab GmbH	0700
Element Materials Technology Warwick Ltd.	0891
Timco Engineering, Inc.	1177
Eurofins Product Service GmbH	0681

2 Contents

	Page
COVER PAGE.....	1
1 LABORATORIES INTRODUCTION	2
1.1 TEST FACILITY.....	3
2 CONTENTS	4
3 REPORT REVISION HISTORY	6
4 GENERAL INFORMATION.....	7
4.1 GENERAL DESCRIPTION OF E.U.T.	7
4.2 DETAILS OF E.U.T.	7
4.3 CHANNEL LIST.....	7
4.4 TEST MODE	7
5 EQUIPMENT USED DURING TEST	8
5.1 EQUIPMENT'S LIST	8
5.2 MEASUREMENT UNCERTAINTY	9
5.3 SUBCONTRACTED.....	9
6 TEST SUMMARY	10
7 CONDUCTED EMISSION	11
7.1 E.U.T. OPERATION	11
7.2 EUT SETUP.....	11
7.3 MEASUREMENT DESCRIPTION	11
7.4 CONDUCTED EMISSION TEST RESULT	12
8 RADIATED SPURIOUS EMISSIONS.....	14
8.1 EUT OPERATION.....	14
8.2 TEST SETUP	15
8.3 SPECTRUM ANALYZER SETUP	16
8.4 TEST PROCEDURE	17
8.5 CORRECTED AMPLITUDE & MARGIN CALCULATION	17
8.6 SUMMARY OF TEST RESULTS	18
9 BAND EDGE MEASUREMENT	21
9.1 TEST PRODUCE.....	21
9.2 TEST SETUP	22
9.3 TEST RESULT	22
10 BANDWIDTH MEASUREMENT.....	24
10.1 TEST PROCEDURE:.....	24
10.2 TEST SETUP	24
10.3 TEST RESULT:	24
11 MAXIMUM CONDUCTED PEAK OUTPUT POWER.....	26
11.1 TEST PROCEDURE:.....	26
11.2 TEST SETUP	26
11.3 TEST RESULT:	26
12 POWER SPECTRAL DENSITY	29
12.1 TEST PROCEDURE:.....	29
12.2 TEST SETUP	29
12.3 TEST RESULT:	29
13 ANTENNA REQUIREMENT	32
14 FCC ID: 2AR6M-WPLCLED RF EXPOSURE REPORT	33

14.1	REQUIREMENTS.....	33
14.2	THE PROCEDURES / LIMIT	33
14.3	RESULT: COMPLIANCE	33
15	PHOTOGRAPHS-MODEL WP01001 TEST SETUP PHOTOS.....	34
15.1	RADIATED SPURIOUS EMISSIONS	34
15.2	CONDUCTED EMISSION	35
16	PHOTOGRAPHS - CONSTRUCTIONAL DETAILS	36
16.1	MODEL WP01001- EXTERNAL PHOTOS	36
16.2	MODEL WP01001- INTERNAL PHOTOS.....	40

3 Report Revision History

Test report No.	Date of Receipt sample	Date of Test	Date of Issue	Purpose	Comment	Approved
WTS18S11130442W	2018-11-23	2018-11-24 to 2019-01-25	2019-01-28	original	-	Valid

4 General Information

4.1 General Description of E.U.T.

Product: Wireless Presenter

Model(s): WP01001

4.2 Details of E.U.T.

Operation Frequency: 2406-2476MHz

Antenna installation: PCB Printed Antenna

Antenna Gain: 1.75dBi

Type of modulation: GFSK

Ratings: DC 3.6V, 2600mAh, 9.36Wh by Rechargeable Li-ion Cell
Charging: DC 5V by USB

4.3 Channel List

Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
1	2406	2	2424	3	2447	4	2476

4.4 Test Mode

All test mode(s) and condition(s) mentioned were considered and evaluated respectively by performing full tests.

Test Items	Mode	Test Channel	Test Frequency
Maximum conducted peak output power	Transmitting	Low/Middle/High	2406/2447/2476MHz
Power Spectral Density	Transmitting	Low/Middle/High	2406/2447/2476MHz
Band Edge	Transmitting	Low/High	2406/2476MHz
Transmitter Spurious Emissions	Transmitting	Low/Middle/High	2406/2447/2476MHz

Note :Parameters set by test software during channel & power tests, the software provided by the customer was used to set the operating channels as well as the output power level. The RF output power set is the power expected by the manufacturer and is going to be fixed on the firmware of the final product.

5 Equipment Used during Test

5.1 Equipment's List

Conducted Emissions						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1.	EMI Test Receiver	R&S	ESCI	101155	2018-09-15	2019-09-14
2.	LISN	SCHWARZBECK	NSLK 8128	8128-289	2018-09-15	2019-09-14
3.	Limiter	York	MTS-IMP-136	261115-001-0024	2018-09-15	2019-09-14
4.	Cable	LARGE	RF300	-	2018-07-18	2019-07-17
3m Semi-anechoic Chamber for Radiation Emissions						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1	Spectrum Analyzer	R&S	FSP30	100091	2018-04-29	2019-04-28
2	Broad-band Horn Antenna(1-18GHz)	SCHWARZBECK	BBHA 9120 D	667	2018-04-29	2019-04-28
3	Broadband Preamplifier	COMPLIANCE DIRECTION	PAP-1G18	2004	2018-04-29	2019-04-28
4	Coaxial Cable (above 1GHz)	Top	1GHz-18GHz	EW02014-7	2018-04-29	2019-04-28
5	Spectrum Analyzer	R&S	FSP40	100501	2018-10-20	2019-10-19
6	Broad-band Horn Antenna(18-40GHz)	SCHWARZBECK	BBHA 9170	BBHA917065 1	2018-10-25	2019-10-24
7	Microwave Broadband Preamplifier (18-40GHz)	SCHWARZBECK	BBV 9721	100472	2018-10-25	2019-10-24
8	Cable	Top	18-40GHz	-	2018-10-25	2019-10-24
3m Semi-anechoic Chamber for Radiation Emissions						
Item	Equipment	Manufacturer	Model No.	Serial No	Last Calibration Date	Calibration Due Date
1	Test Receiver	R&S	ESCI	101296	2018-04-29	2019-04-28
2	Trilog Broadband Antenna	SCHWARZBECK	VULB9160	9160-3325	2018-04-29	2019-04-28
3	Active Loop Antenna	Com-power	AL-130R	10160007	2018-04-17	2019-04-16
4	Amplifier	ANRITSU	MH648A	M43381	2018-04-29	2019-04-28
5	Cable	HUBER+SUHNER	CBL2	525178	2018-04-29	2019-04-28

6	Coaxial Cable (below 1GHz)	Top	TYPE16 (13M)	-	2018-09-12	2019-09-11
RF Conducted Testing						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1.	Spectrum Analyzer	R&S	FSL6	100959	2018-09-12	2019-09-11
2	Coaxial Cable	Top	10Hz-30GHz	-	2018-09-12	2019-09-11
3	Antenna Connector*	Realacc	45RSm	-	2018-09-12	2019-09-11
4	DC Block	Gwave	GDCB-3G-N-SMA	140307001	2018-09-12	2019-09-11
“*” : The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.						

5.2 Measurement Uncertainty

Parameter	Uncertainty
Radio Frequency	$\pm 1 \times 10^{-6}$
RF Power	± 1.0 dB
RF Power Density	± 2.2 dB
Radiated Spurious Emissions test	± 5.03 dB (30M~1000MHz)
	± 5.47 dB (1000M~25000MHz)
Conducted Emissions test	± 3.64 dB (AC mains 150KHz~30MHz)
Confidence interval: 95%. Confidence factor:k=2	

5.3 Subcontracted

Whether parts of tests for the product have been subcontracted to other labs:

☐ Yes ☒ No

If Yes, list the related test items and lab information:

Test Lab: N/A

Lab address: N/A

Test items: N/A

6 Test Summary

Test Items	Test Requirement	Result
Radiated Spurious Emissions	15.247(d) 15.205(a) 15.209(a)	Pass
Conducted Emissions	15.207(a)	Pass
Bandwidth	15.247(a)(2)	Pass
Maximum conducted peak output power	15.247(b)(3),(4)	Pass
Power Spectral Density	15.247(e)	Pass
Band Edge	15.247(d)	Pass
Antenna Requirement	15.203	Pass
RF Exposure	1.1307(b)(1)	Pass
Note: Pass=Compliance; NC=Not Compliance; NT=Not Tested; N/A=Not Applicable.		

7 Conducted Emission

Test Requirement: FCC CFR 47 Part 15 Section 15.207

Test Method: ANSI C63.10:2013

Test Result: PASS

Frequency Range: 150kHz to 30MHz

Class/Severity: Class B

Limit:

Frequency (MHz)	Limit (dBμV)	
	Quasi-peak	Average
0.15 to 0.5	66 to 56	56 to 46
0.5 to 5	56	46
5 to 30	60	50

7.1 E.U.T. Operation

Operating Environment :

Temperature: 21.5 °C

Humidity: 51.9 % RH

Atmospheric Pressure: 101.2kPa


Test Voltage: AC 120V/60Hz

EUT Operation :

The test was performed in Transmitting mode, the worst data (Low channel) were shown in the report.

7.2 EUT Setup

The conducted emission tests were performed using the setup accordance with the ANSI C63.10:2013.




7.3 Measurement Description

The maximised peak emissions from the EUT was scanned and measured for both the Live and Neutral Lines. Quasi-peak & average measurements were performed if peak emissions were within 6dB of the average limit line.

7.4 Conducted Emission Test Result


An initial pre-scan was performed on the live and neutral lines.

Live line:



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Margin (dB)	Detector	Remark
1	0.1900	46.49	10.31	56.80	64.03	-7.23	QP	
2	0.1900	35.59	10.31	45.90	54.03	-8.13	AVG	
3	0.2500	39.42	10.39	49.81	61.75	-11.94	QP	
4	0.2500	29.89	10.39	40.28	51.75	-11.47	AVG	
5	0.3140	34.45	10.41	44.86	59.86	-15.00	QP	
6	0.3140	26.08	10.41	36.49	49.86	-13.37	AVG	
7	0.6900	31.73	10.44	42.17	56.00	-13.83	QP	
8	0.6900	22.48	10.44	32.92	46.00	-13.08	AVG	
9	2.9700	28.30	10.69	38.99	56.00	-17.01	QP	
10	2.9700	17.19	10.69	27.88	46.00	-18.12	AVG	
11	11.3020	29.62	11.14	40.76	60.00	-19.24	QP	
12	11.3020	23.44	11.14	34.58	50.00	-15.42	AVG	

Neutral line:



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Margin (dB)	Detector	Remark
1	0.1860	47.21	10.31	57.52	64.21	-6.69	QP	
2	0.1860	37.08	10.31	47.39	54.21	-6.82	AVG	
3	0.2460	40.65	10.38	51.03	61.89	-10.86	QP	
4	0.2460	32.39	10.38	42.77	51.89	-9.12	AVG	
5	0.3100	36.28	10.41	46.69	59.97	-13.28	QP	
6	0.3100	29.53	10.41	39.94	49.97	-10.03	AVG	
7	0.6220	35.64	10.48	46.12	56.00	-9.88	QP	
8	0.6220	26.24	10.48	36.72	46.00	-9.28	AVG	
9	2.4820	30.65	10.66	41.31	56.00	-14.69	QP	
10	2.4820	19.25	10.66	29.91	46.00	-16.09	AVG	
11	20.2780	27.06	10.74	37.80	60.00	-22.20	QP	
12	20.2780	19.92	10.74	30.66	50.00	-19.34	AVG	

8 Radiated Spurious Emissions

Test Requirement: FCC CFR47 Part 15 Section 15.209 & 15.247

Test Method: ANSI C63.10:2013

Test Result: PASS

Measurement Distance: 3m

Limit:

Frequency (MHz)	Field Strength		Field Strength Limit at 3m Measurement Dist	
	uV/m	Distance (m)	uV/m	dBuV/m
0.009 ~ 0.490	$2400/F(\text{kHz})$	300	$10000 * 2400/F(\text{kHz})$	$20\log^{(2400/F(\text{kHz}))} + 80$
0.490 ~ 1.705	$24000/F(\text{kHz})$	30	$100 * 24000/F(\text{kHz})$	$20\log^{(24000/F(\text{kHz}))} + 40$
1.705 ~ 30	30	30	$100 * 30$	$20\log^{(30)} + 40$
30 ~ 88	100	3	100	$20\log^{(100)}$
88 ~ 216	150	3	150	$20\log^{(150)}$
216 ~ 960	200	3	200	$20\log^{(200)}$
Above 960	500	3	500	$20\log^{(500)}$

8.1 EUT Operation

Operating Environment :

Temperature: 23.5 °C

Humidity: 52.1 % RH

Atmospheric Pressure: 101.2kPa

Test Voltage: AC 120V/60Hz


EUT Operation :

The test was performed in Transmitting mode. the test data were shown in the report.


8.2 Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site, using the setup accordance with the ANSI C63.10:2013.


The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1 GHz.



8.3 Spectrum Analyzer Setup

Below 30MHz

Sweep Speed Auto
IF Bandwidth.....10kHz
Video Bandwidth.....10kHz
Resolution Bandwidth.....10kHz

30MHz ~ 1GHz

Sweep Speed Auto
DetectorPK
Resolution Bandwidth.....100kHz
Video Bandwidth.....300kHz

Above 1GHz

Sweep Speed Auto
DetectorPK
Resolution Bandwidth.....1MHz
Video Bandwidth.....3MHz
DetectorAve.
Resolution Bandwidth.....1MHz
Video Bandwidth.....10Hz

8.4 Test Procedure

1. The EUT is placed on a turntable. For below 1GHz, the EUT is 0.8m above ground plane;
For above 1GHz, the EUT is 1.5m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is moved from 1m to 4m to find out the maximum emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. The radiation measurements are performed in X,Y and Z axis positioning(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand),the worst condition was tested putting the eut in X axis,so the worst data were shown as follow.
8. A 2.4GHz high –pass filter is used during radiated emissions above 1GHz measurement.

8.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Amplifier Gain}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB means the emission is 7dB below the maximum limit for Class B. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{Limit}$$

8.6 Summary of Test Results

Test Frequency : 9 kHz to 30 MHz

The measurements were more than 20 dB below the limit and not reported.

Test Frequency : 30 MHz ~ 18 GHz

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
GFSK Low Channel 2406MHz									
463.97	37.63	QP	21	1.2	H	-11.07	26.56	46.00	-19.44
463.97	35.01	QP	136	1.5	V	-11.07	23.94	46.00	-22.06
4812.00	55.96	PK	94	1.4	V	-1.06	54.90	74.00	-19.10
4812.00	49.18	Ave	94	1.4	V	-1.06	48.12	54.00	-5.88
7218.00	55.99	PK	158	2.0	H	1.33	57.32	74.00	-16.68
7218.00	45.02	Ave	158	2.0	H	1.33	46.35	54.00	-7.65
2341.64	42.17	PK	145	1.6	V	-13.19	28.98	74.00	-45.02
2341.64	33.83	Ave	145	1.6	V	-13.19	20.64	54.00	-33.36
2383.31	43.03	PK	125	1.9	H	-13.14	29.89	74.00	-44.11
2383.31	32.70	Ave	125	1.9	H	-13.14	19.56	54.00	-34.44
2489.20	44.49	PK	201	1.7	V	-13.08	31.41	74.00	-42.59
2489.20	34.11	Ave	201	1.7	V	-13.08	21.03	54.00	-32.97

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
GFSK Middle Channel 2447MHz									
463.97	36.90	QP	159	1.5	H	-11.07	25.83	46.00	-20.17
463.97	35.17	QP	133	1.6	V	-11.07	24.10	46.00	-21.90
4894.00	55.95	PK	100	1.1	V	-0.62	55.33	74.00	-18.67
4894.00	47.75	Ave	100	1.1	V	-0.62	47.13	54.00	-6.87
7341.00	55.50	PK	87	1.4	H	2.21	57.71	74.00	-16.29
7341.00	45.42	Ave	87	1.4	H	2.21	47.63	54.00	-6.37
2314.10	45.65	PK	49	1.7	V	-13.19	32.46	74.00	-41.54
2314.10	33.35	Ave	49	1.7	V	-13.19	20.16	54.00	-33.84
2371.53	44.90	PK	12	1.2	H	-13.14	31.76	74.00	-42.24
2371.53	34.83	Ave	12	1.2	H	-13.14	21.69	54.00	-32.31
2484.89	44.99	PK	327	1.8	V	-13.08	31.91	74.00	-42.09
2484.89	34.33	Ave	327	1.8	V	-13.08	21.25	54.00	-32.75

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
GFSK High Channel 2476MHz									
463.97	36.94	QP	93	1.3	H	-11.07	25.87	46.00	-20.13
463.97	35.85	QP	50	2.0	V	-11.07	24.78	46.00	-21.22
4952.00	55.79	PK	224	1.2	V	-0.24	55.55	74.00	-18.45
4952.00	47.65	Ave	224	1.2	V	-0.24	47.41	54.00	-6.59
7428.00	55.61	PK	289	1.9	H	2.84	58.45	74.00	-15.55
7428.00	45.58	Ave	289	1.9	H	2.84	48.42	54.00	-5.58
2339.59	46.38	PK	6	1.9	V	-13.19	33.19	74.00	-40.81
2339.59	33.79	Ave	6	1.9	V	-13.19	20.60	54.00	-33.40
2360.56	42.13	PK	270	1.8	H	-13.14	28.99	74.00	-45.01
2360.56	32.60	Ave	270	1.8	H	-13.14	19.46	54.00	-34.54
2494.48	43.91	PK	288	1.2	V	-13.08	30.83	74.00	-43.17
2494.48	32.76	Ave	288	1.2	V	-13.08	19.68	54.00	-34.32

Test Frequency: 18GHz~25GHz

The measurements were more than 20 dB below the limit and not reported.


9 Band Edge Measurement

Test Requirement:	FCC CFR47 Part 15 Section 15.247
Test Method:	558074 D01 15.247 Meas Guidance v05 August 24, 2018
Test Limit:	Regulation 15.247 (d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
Test Mode:	Transmitting

9.1 Test Produce

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.


9.2 Test Setup




9.3 Test Result

Test result plots shown as follows:

GFSK Band edge-left side



GFSK Band edge-right side




10 Bandwidth Measurement

Test Requirement: FCC CFR47 Part 15 Section 15.247
Test Method: 558074 D01 15.247 Meas Guidance v05 August 24, 2018

10.1 Test Procedure:

- 1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
- 2. Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz


10.2 Test Setup





10.3 Test Result:

6dB Bandwidth (MHz)			99% Bandwidth (MHz)		
Low	Middle	High	Low	Middle	High
0.784	0.784	0.784	1.299	1.329	1.383

Test result plot as follows:





11 Maximum conducted peak Output Power

Test Requirement:

FCC CFR47 Part 15 Section 15.247

Test Method:


558074 D01 15.247 Meas Guidance v05 August 24, 2018

11.1 Test Procedure:

558074 D01 15.247 Meas Guidance v05 August 24, 2018

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 1 MHz. VBW = 3 MHz. Sweep = auto; Detector Function = Peak, Set the span to fully encompass the DTS bandwidth.
3. Keep the EUT in transmitting at lowest, medium and highest channel individually. Record the max value.



11.2 Test Setup




11.3 Test Result:

Maximum conducted Peak Output Power (dBm)		
Low	Middle	High
2.80	2.77	0.88
Limit: 1W/30dBm		

Test result plot as follows:





12 Power Spectral density

Test Requirement: FCC CFR47 Part 15 Section 15.247


Test Method: 558074 D01 15.247 Meas Guidance v05 August 24, 2018

12.1 Test Procedure:

558074 D01 15.247 Meas Guidance v05 August 24, 2018

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 3kHz. VBW = 10kHz , Span = 1.5 times the DTS channel bandwidth(6 dB bandwidth). Sweep = auto; Detector Function = Peak. Trace = Max hold.
3. Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section Submit this plot.

12.2 Test Setup




12.3 Test Result:


Power Spectral (dBm per 3kHz)		
Low	Middle	High
-7.29	-6.88	-10.40
Limit: 8dBm per 3kHz		


Test Plot

Low



Middle






13 Antenna Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

Result:

The EUT has one PCB Printed Antenna, the gain is 1.75dBi. meets the requirements of FCC 15.203.



14 FCC ID: 2AR6M-WPLCLED RF Exposure Report

Test Requirement: FCC Part 1.1307

Evaluation Method FCC Part2.1093 & KDB 447498 D01 General RF Exposure Guidance v06

14.1 Requirements

1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR where}$$

1. $f(\text{GHz})$ is the RF channel transmit frequency in GHz
2. Power and distance are rounded to the nearest mW and mm before calculation
3. The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

14.2 The procedures / limit

Conducted Peak power(dBm)	Conducted Peak power(mW)	Source-based time-averaged maximum conducted output power(mW)	Minimum test separation distance required for the exposure conditions (mm)	SAR Test Exclusion Thresholds Calculation Value	SAR Test Exclusion Thresholds Limit	Result
2.80	1.91	1.91	5	0.602	3.0	Compliance

Remark: Max. duty factor is 100%

Low Chanel: $f=2402\text{MHz}=2.402\text{GHz}$, so $\sqrt{f(\text{GHz})}=1.550$

High Chanel: $f=2480\text{MHz}=2.480\text{GHz}$, so $\sqrt{f(\text{GHz})}=1.575$


14.3 Result: Compliance

No SAR measurement is required.

15 Photographs–Model WP01001 Test Setup Photos

15.1 Radiated Spurious Emissions


Test frequency from 9kHz to 30MHz



Test frequency from 30 MHz to 1 GHz



Test frequency Above 1 GHz



15.2 Conducted Emission



16 Photographs - Constructional Details

16.1 Model WP01001- External Photos












16.2 Model WP01001- Internal Photos









=====End of Report=====