

onn.™

36"5.1 Soundbar

User Manual



We'd love to hear from you. Scan with your Walmart app and let us know what you think.

Battery Replacement for the Remote Control the First Step	01	Battery Replacement for the Remote Control the Second Step	02	Battery Replacement for the Remote Control the Third Step	03	Remote Control Operation Range
1. Lift up the back cover to open the battery compartment of the remote control.	1. Insert two AAA-size batteries. Make sure the (+) and (-) ends of the batteries match the (+) and (-) ends indicated in the battery compartment.	2. Close the battery compartment cover.	2. Close the battery compartment cover.	3. The remote control operates on the front and is sensitive to the distance of 10m. The remote control operates on the back and is sensitive to the distance of 10m.	3. The remote control operates on the front and is sensitive to the distance of 10m. The remote control operates on the back and is sensitive to the distance of 10m.	3. The remote control operates on the front and is sensitive to the distance of 10m. The remote control operates on the back and is sensitive to the distance of 10m.

What's in the Box?	Check to make sure you have everything below.	Get to Know Your 36" 5.1 SOUNDBAR	Get to Know Your 36" 5.1 SOUNDBAR	Remote Control Overview
1. Main unit 2. Subwoofer 3. Satellite 4. Power Cord 5. Optical Cable 6. HDMI Cable 7. User Manual	1. Main unit 2. Subwoofer 3. Satellite 4. Power Cord 5. Optical Cable 6. HDMI Cable 7. User Manual	1. Main unit 2. Subwoofer 3. Satellite 4. Power Cord 5. Optical Cable 6. HDMI Cable 7. User Manual	1. Main unit 2. Subwoofer 3. Satellite 4. Power Cord 5. Optical Cable 6. HDMI Cable 7. User Manual	1. Main unit 2. Subwoofer 3. Satellite 4. Power Cord 5. Optical Cable 6. HDMI Cable 7. User Manual

User Manual_Ver.02 Rev 08/18/19
Unfold dimension : 287,5X290mm
fold dimension : 143,5X72,5mm
Material : 80g writing paper
Printing : 2C , double sides
FW1816 说明书 80g书写纸 287,5*290 T=0,2mm 白底黑字 双面印刷

For manually Press and hold down on the remote for 10 seconds. Current LED will start blink with a red light.
If the remote control is not working, please check the battery level and the remote control is not working. If the remote control is not working, please check the battery level and the remote control is not working. If the remote control is not working, please check the battery level and the remote control is not working.

Using the HDMI IN or HDMI ARC connection	Using the AUX or Optical Connection	Bluetooth Connection and 5.1 System Connection	Using the Bluetooth Connection
1. Use a 3.5mm to RCA stereo audio cable (not included) to connect the TV's audio output Port to the soundbar's AUX IN Port. 2. Use a 3.5mm to RCA stereo audio cable (not included) to connect the TV's audio output Port to the soundbar's AUX IN Port. 3. Use a 3.5mm to RCA stereo audio cable (not included) to connect the TV's audio output Port to the soundbar's AUX IN Port.	1. Use a 3.5mm to RCA stereo audio cable (not included) to connect the TV's audio output Port to the soundbar's AUX IN Port. 2. Use a 3.5mm to RCA stereo audio cable (not included) to connect the TV's audio output Port to the soundbar's AUX IN Port. 3. Use a 3.5mm to RCA stereo audio cable (not included) to connect the TV's audio output Port to the soundbar's AUX IN Port.	1. Use a 3.5mm to RCA stereo audio cable (not included) to connect the TV's audio output Port to the soundbar's AUX IN Port. 2. Use a 3.5mm to RCA stereo audio cable (not included) to connect the TV's audio output Port to the soundbar's AUX IN Port. 3. Use a 3.5mm to RCA stereo audio cable (not included) to connect the TV's audio output Port to the soundbar's AUX IN Port.	1. Use a 3.5mm to RCA stereo audio cable (not included) to connect the TV's audio output Port to the soundbar's AUX IN Port. 2. Use a 3.5mm to RCA stereo audio cable (not included) to connect the TV's audio output Port to the soundbar's AUX IN Port. 3. Use a 3.5mm to RCA stereo audio cable (not included) to connect the TV's audio output Port to the soundbar's AUX IN Port.

Connecting to the Power Outlet	Product Wall Mounting the First Step	Product Wall Mounting the Second Step	Product Wall Mounting the Third Step
1. Connect the AC Plug to the power outlet by power cable.	1. Use the 1/4" x 1/4" x 1/4" screws to secure the subwoofer to the wall.	2. Use the 1/4" x 1/4" x 1/4" screws to secure the subwoofer to the wall.	3. Use the 1/4" x 1/4" x 1/4" screws to secure the subwoofer to the wall.

Specifications	Important Safety Instructions
1. Main unit 2. Subwoofer 3. Satellite 4. Power Cord 5. Optical Cable 6. HDMI Cable 7. User Manual	1. Main unit 2. Subwoofer 3. Satellite 4. Power Cord 5. Optical Cable 6. HDMI Cable 7. User Manual