



**CFR 47 FCC PART 15 SUBPART C
ISED RSS-247 ISSUE 2**

TEST REPORT

For

IEEE 802.11b/g/n 1T1R USB WiFi Module

MODEL NUMBER: SKI.W7601.2

FCC ID: 2AR82-SKIW7601201

IC: 24728-SKIW7601201

REPORT NUMBER: 4788880268-1

ISSUE DATE: March 19, 2019

Prepared for

**Guangzhou Shikun Electronics Co., Ltd
NO.192 KEZHU ROAD, SCIENCE PARK GUANGZHOU, GUANGDONG, CHINA**

Prepared by

**UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch
Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake
Hi-Tech Development Zone Dongguan, People's Republic of China**

Tel: +86 769 22038881

Fax: +86 769 33244054

Website: www.ul.com



Revision History

Rev.	Issue Date	Revisions	Revised By
V0	3/19/2019	Initial Issue	



Summary of Test Results			
Clause	Test Items	FCC/IC Rules	Test Results
1	6dB Bandwidth and 99% Occupied Bandwidth	FCC Part 15.247 (a) (2) RSS-247 Clause 5.2 (a) ISED RSS-Gen Clause 6.7	Pass
2	Peak Conducted Output Power	FCC Part 15.247 (b) (3) RSS-247 Clause 5.4 (e)	Pass
3	Power Spectral Density	FCC Part 15.247 (e) RSS-247 Clause 5.2 (b)	Pass
4	Conducted Bandedge and Spurious Emission	FCC Part 15.247 (d) RSS-247 Clause 5.5	Pass
5	Radiated Bandedge and Spurious Emission	FCC Part 15.247 (d) FCC Part 15.209 FCC Part 15.205 RSS-247 Clause 5.5 RSS-GEN Clause 8.9	Pass
6	Conducted Emission Test For AC Power Port	FCC Part 15.207 RSS-GEN Clause 8.8	Pass
7	Antenna Requirement	FCC Part 15.203 RSS-GEN Clause 8.3	Pass



TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	6
2. TEST METHODOLOGY	7
3. FACILITIES AND ACCREDITATION	7
4. CALIBRATION AND UNCERTAINTY	8
4.1. MEASURING INSTRUMENT CALIBRATION	8
4.2. MEASUREMENT UNCERTAINTY.....	8
5. EQUIPMENT UNDER TEST	9
5.1. DESCRIPTION OF EUT	9
5.2. MAXIMUM OUTPUT POWER.....	9
5.3. CHANNEL LIST	10
5.4. TEST CHANNEL CONFIGURATION.....	10
5.5. THE WORSE CASE CONFIGURATIONS	10
5.6. DESCRIPTION OF AVAILABLE ANTENNAS	11
5.7. DESCRIPTION OF TEST SETUP.....	12
6. MEASURING INSTRUMENT AND SOFTWARE USED	13
7. MEASUREMENT METHODS	14
8. ANTENNA PORT TEST RESULTS	15
8.1. ON TIME AND DUTY CYCLE.....	15
8.2. 6 dB DTS BANDWIDTH AND 99% OCCUPIED BANDWIDTH	18
8.2.1. 802.11b MODE	19
8.2.2. 802.11g MODE	23
8.2.3. 802.11n HT20 MODE	27
8.2.4. 802.11n HT40 MODE	31
8.3. PEAK CONDUCTED OUTPUT POWER.....	35
8.3.1. 802.11b MODE	36
8.3.2. 802.11g MODE	36
8.3.3. 802.11n HT20 MODE	36
8.3.4. 802.11n HT40 MODE	36
8.4. POWER SPECTRAL DENSITY	37
8.4.1. 802.11b MODE	38
8.4.2. 802.11g MODE	40
8.4.3. 802.11n HT20 MODE	42
8.4.4. 802.11n HT40 MODE	44
8.5. CONDUCTED BANDEDGE AND SPURIOUS EMISSIONS.....	46
8.5.1. 802.11b MODE	47
8.5.2. 802.11g MODE	52



8.5.3.	802.11n HT20 MODE	57
8.5.4.	802.11n HT40 MODE	62
9.	RADIATED TEST RESULTS.....	67
9.1.	<i>RESTRICTED BANDEDGE FOR ANTENNA 1.....</i>	<i>73</i>
9.1.1.	802.11b MODE	73
9.1.2.	802.11g MODE	77
9.1.3.	802.11n HT20 MODE	85
9.1.4.	802.11n HT40 MODE	93
9.2.	<i>RESTRICTED BANDEDGE FOR ANTENNA 2.....</i>	<i>101</i>
9.2.1.	802.11b MODE	101
9.2.2.	802.11g MODE	105
9.2.3.	802.11n HT20 MODE	113
9.2.4.	802.11n HT40 MODE	121
9.3.	<i>SPURIOUS EMISSIONS (3~18GHz) FOR ANTENNA 1.....</i>	<i>129</i>
9.3.1.	802.11b MODE	129
9.3.2.	802.11g MODE	135
9.3.3.	802.11n HT20 MODE	141
9.3.4.	802.11n HT40 MODE	147
9.4.	<i>SPURIOUS EMISSIONS (3~18GHz) FOR ANTENNA 2.....</i>	<i>153</i>
9.4.1.	802.11b MODE	153
9.4.2.	802.11g MODE	159
9.4.3.	802.11n HT20 MODE	165
9.4.4.	802.11n HT40 MODE	171
9.5.	<i>SPURIOUS EMISSIONS (1~3GHz) FOR ANTENNA 2.....</i>	<i>177</i>
9.5.1.	802.11b MODE	177
9.5.2.	802.11g MODE	183
9.5.3.	802.11n HT20 MODE	189
9.5.5.	802.11n HT40 MODE	195
9.6.	<i>PURIOUS EMISSIONS (18~26GHz) FOR ANTENNA 2.....</i>	<i>201</i>
9.6.1.	802.11b MODE	201
9.7.	<i>SPURIOUS EMISSIONS (0.03 ~ 1 GHz) FOR ANTENNA 2.....</i>	<i>203</i>
9.7.1.	802.11b MODE	203
9.8.	<i>SPURIOUS EMISSIONS BELOW 30M FOR ANTENNA 2.....</i>	<i>205</i>
9.8.1.	802.11b MODE	205
10.	AC POWER LINE CONDUCTED EMISSIONS FOR ANTENNA 2.....	211
10.1.	802.11b MODE.....	212
11.	ANTENNA REQUIREMENTS	214



1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name: Guangzhou Shikun Electronics Co., Ltd
Address: NO.192 KEZHU ROAD, SCIENCE PARK
GUANGZHOU, GUANGDONG, CHINA

Manufacturer Information

Company Name: Guangzhou Shikun Electronics Co., Ltd
Address: NO.192 KEZHU ROAD, SCIENCE PARK
GUANGZHOU, GUANGDONG, CHINA

EUT Description

EUT Name: IEEE 802.11b/g/n 1T1R USB WiFi Module
Model: SKI.W7601.2
Sample Status: Normal
Sample Received Date: January 29, 2019
Date of Tested: January 30 ~ March 15, 2019

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 FCC PART 15 SUBPART C	PASS
ISED RSS-247 Issue 2	PASS
ISED RSS-GEN Issue 5	PASS

Prepared By:

Checked By:

Kebo Zhang
Engineer Project Associate
Approved By:

Shawn Wen
Laboratory Leader

Stephen Guo
Laboratory Manager



2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with KDB 558074 D01 Meas Guidance v05r01, KDB 414788 D01 Radiated Test Site v01r01, CFR 47 FCC Part 2, CFR 47 FCC Part 15, ANSI C63.10-2013, ISED RSS-247 Issue 2 and ISED RSS-GEN Issue 5.

3. FACILITIES AND ACCREDITATION

Accreditation Certificate	A2LA (Certificate No.: 4102.01) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA. FCC (FCC Designation No.: CN1187) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules IC(Company No.: 21320) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. The Company Number is 21320. VCCI (Registration No.: G-20019, R-20004, C-20012 and T-20011) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793. Facility Name: Chamber D, the VCCI registration No. is G-20019 and R-20004 Shielding Room B, the VCCI registration No. is C-20012 and T-20011
---------------------------	--

Note 1: All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China

Note 2: The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

Note 3: For below 30MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30MHz had been correlated to measurements performed on an OFS.



4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognize national standards.

4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Uncertainty
Conduction emission	3.62dB
Radiation Emission test(include Fundamental emission) (9kHz-30MHz)	2.2dB
Radiation Emission test(include Fundamental emission) (30MHz-1GHz)	4.00dB
Radiation Emission test (1GHz to 26GHz)(include Fundamental emission)	5.78dB (1GHz-18Gz)
	5.23dB (18GHz-26Gz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	



5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

EUT Name	IEEE 802.11b/g/n 1T1R USB WiFi Module
Model	SKI.W7601.2
Radio Technology	IEEE802.11b/g/n HT20/n HT40
Operation frequency	IEEE 802.11b: 2412MHz—2462MHz IEEE 802.11g: 2412MHz—2462MHz IEEE 802.11n HT20: 2412MHz—2462MHz IEEE 802.11n HT40: 2422MHz—2452MHz
Modulation	IEEE 802.11b: DSSS(CCK) IEEE 802.11g: OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT20: OFDM (64QAM, 16QAM, QPSK,BPSK) IEEE 802.11n HT40: OFDM (64QAM, 16QAM, QPSK,BPSK)
Rated Input	DC 5V

5.2. MAXIMUM OUTPUT POWER

Number of Transmit Chains (NTX)	IEE Std. 802.11	Frequency (MHz)	Channel Number	Max PK Conducted Power (dBm)
1	IEEE 802.11b	2412-2462	1-11[11]	18.89
1	IEEE 802.11g	2412-2462	1-11[11]	22.27
1	IEEE 802.11nHT20	2412-2462	1-11[11]	22.34
1	IEEE 802.11nHT40	2422-2452	3-9[7]	22.44



5.3. CHANNEL LIST

Channel List for 802.11b/g/n (20 MHz)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	4	2427	7	2442	10	2457
2	2417	5	2432	8	2447	11	2462
3	2422	6	2437	9	2452	/	/

Channel List for 802.11n (40 MHz)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	5	2432	7	2442	9	2452
4	2427	6	2437	8	2447	/	/

5.4. TEST CHANNEL CONFIGURATION

Test Mode	Test Channel	Frequency
WiFi TX(802.11b)	CH 1, CH 6, CH 11	2412MHz, 2437MHz, 2462MHz
WiFi TX(802.11g)	CH 1, CH 6, CH 11	2412MHz, 2437MHz, 2462MHz
WiFi TX(802.11n HT20)	CH 1, CH 6, CH 11	2412MHz, 2437MHz, 2462MHz
WiFi TX(802.11n HT40)	CH 3, CH 6, CH 9	2422MHz, 2437MHz, 2452MHz

5.5. THE WORSE CASE CONFIGURATIONS

The Worse Case Power Setting Parameter under 2400 ~ 2483.5MHz Band							
Test Software		MTK					
Modulation Mode	Transmit Antenna Number	Test Channel					
		NCB: 20MHz			NCB: 40MHz		
		CH 1	CH 6	CH 11	CH 3	CH 6	CH 9
802.11b	1	OE	OE	OE	/		
802.11g	1	OD	OD	OD			
802.11n HT20	1	OC	OB	OB			
802.11n HT40	1	/			OD	OD	OD

**5.6. DESCRIPTION OF AVAILABLE ANTENNAS**

Antenna	Customer 's Part No.	Frequency (MHz)	Antenna Type	Antenna Gain (dBi)
1	0460-5001-3550	2412-2462	FPC	3.32
2	0460-5200-0252	2412-2462	PIFA	3.52
3	0460-5001-2751	2412-2462	FPC	2.91

Note:

- 1.The equipment has three antennas but only one antenna will be use in the end product.
- 2.The three antennas have the same power setting and antenna 1 and antenna 3 have the same antenna type, so antenna 1 and antenna 2 test data record in the report which has the max antenna gain.

Test Mode	Transmit and Receive Mode	Description
IEEE 802.11b	☒ 1TX, 1RX	Antenna 1 can be used as transmitting/receiving antenna.
IEEE 802.11g	☒ 1TX, 1RX	Antenna 1 can be used as transmitting/receiving antenna.
IEEE 802.11n HT20	☒ 1TX, 1RX	Antenna 1 can be used as transmitting/receiving antenna.
IEEE 802.11n HT40	☒ 1TX, 1RX	Antenna 1 can be used as transmitting/receiving antenna.



5.7. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Item	Equipment	Brand Name	Model Name	Remarks
1	Laptop	ThinkPad	T460S	SL10K24796 JS
2	Test fixture	/	/	/
3	AC/DC adapter	HUAWEI	HW-120150E2W	Input: AC 100-240V,50/60Hz, 0.5A

I/O CABLES

Item	Port	Connector Type	Cable Type	Cable Length(m)	Remarks
1	USB	NA	NA	1	/


ACCESSORIES

Item	Accessory	Brand Name	Model Name	Description
1	/	/	/	/

TEST SETUP

The EUT can work in engineering mode with a software through a Laptop.

SETUP DIAGRAM FOR TESTS





6. MEASURING INSTRUMENT AND SOFTWARE USED

Conducted Emissions						
Instrument						
Used	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
☒	EMI Test Receiver	R&S	ESR3	101961	Dec.10,2018	Dec.10,2019
☒	Two-Line V-Network	R&S	ENV216	101983	Dec.10,2018	Dec.10,2019
☒	Artificial Mains Networks	Schwarzbeck	NSLK 8126	8126465	Dec.10,2018	Dec.10,2019
Software						
Used	Description		Manufacturer	Name		Version
☒	Test Software for Conducted disturbance		Farad	EZ-EMC		Ver. UL-3A1
Radiated Emissions						
Instrument						
Used	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
☒	MXE EMI Receiver	KESIGHT	N9038A	MY56400036	Dec.10,2018	Dec.10,2019
☒	Hybrid Log Periodic Antenna	TDK	HLP-3003C	130960	Sep.17, 2018	Sep.17, 2021
☒	Preamplifier	HP	8447D	2944A09099	Dec.10,2018	Dec.10,2019
☒	EMI Measurement Receiver	R&S	ESR26	101377	Dec.10,2018	Dec.10,2019
☒	Horn Antenna	TDK	HRN-0118	130939	Sep.17, 2018	Sep.17, 2021
☒	High Gain Horn Antenna	Schwarzbeck	BBHA-9170	691	Aug.11, 2018	Aug.11, 2021
☒	Preamplifier	TDK	PA-02-0118	TRS-305-00066	Dec.10,2018	Dec.10,2019
☒	Preamplifier	TDK	PA-02-2	TRS-307-00003	Dec.10,2018	Dec.10,2019
☒	Loop antenna	Schwarzbeck	1519B	00008	Mar.26,2016	Mar.25, 2019
☒	Band Reject Filter	Wainwright	WRCJV8-2350-2400-2483.5-2533.5-40SS	4	Dec.10,2018	Dec.10,2019
☒	High Pass Filter	Wi	WHKX10-2700-3000-18000-40SS	23	Dec.10,2018	Dec.10,2019
Software						
Used	Description		Manufacturer	Name		Version
☒	Test Software for Radiated disturbance		Farad	EZ-EMC		Ver. UL-3A1



Other instruments						
Used	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
☒	Spectrum Analyzer	Keysight	N9030A	MY55410512	Dec.10,2018	Dec.10,2019
☒	Power Meter	Keysight	N1911A	MY55416024	Dec.10,2018	Dec.10,2019
☒	Power Sensor	Keysight	U2021XA	MY5100022	Dec.10,2018	Dec.10,2019

7. MEASUREMENT METHODS

No.	Test Item	KDB Name	Section
1	6dB Bandwidth	KDB 558074 D01 15.247 Meas Guidance v05r01	8.2
2	Peak Output Power	KDB 558074 D01 15.247 Meas Guidance v05r01	8.3.1.3/8.3.2.3
3	Power Spectral Density	KDB 558074 D01 15.247 Meas Guidance v05r01	8.4
4	Out-of-band emissions in non-restricted bands	KDB 558074 D01 15.247 Meas Guidance v05r01	8.5
5	Out-of-band emissions in restricted bands	KDB 558074 D01 15.247 Meas Guidance v05r01	8.6
6	Band-edge	KDB 558074 D01 15.247 Meas Guidance v05r01	8.7
7	Conducted Emission Test For AC Power Port	ANSI C63.10-2013	6.2
8	99% Bandwidth	ANSI C63.10-2013	6.9.3



8. ANTENNA PORT TEST RESULTS

8.1. ON TIME AND DUTY CYCLE


LIMITS

None; for reporting purposes only

PROCEDURE

KDB 558074 Zero-Span Spectrum Analyzer Method

TEST SETUP



TEST ENVIRONMENT

Temperature	22.6°C	Relative Humidity	58%
Atmosphere Pressure	101kPa	Test Voltage	DC 5V

RESULTS

Mode	On Time (msec)	Period (msec)	Duty Cycle x (Linear)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	1/T Minimum VBW (KHz)	Final setting For VBW (KHz)
11b	127.8	127.8	1	100	0	0.008	0.01
11g	128.5	128.5	1	100	0	0.008	0.01
11n20	128.3	128.3	1	100	0	0.008	0.01
11n40	126.7	126.7	1	100	0	0.008	0.01

Note:

Duty Cycle Correction Factor=10log (1/x).

Where: x is Duty Cycle (Linear)

Where: T is On Time

If that calculated VBW is not available on the analyzer then the next higher value should be used.





11b ON TIME AND DUTY CYCLE MID CH



11g ON TIME AND DUTY CYCLE MID CH







8.2. 6 dB DTS BANDWIDTH AND 99% OCCUPIED BANDWIDTH

LIMITS

CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 2			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247(a)(2) ISED RSS-247 5.2 (a)	6 dB Bandwidth	$\geq 500\text{KHz}$	2400-2483.5
ISED RSS-Gen Clause 6.7	99% Occupied Bandwidth	For reporting purposes only.	2400-2483.5


TEST PROCEDURE

Connect the UUT to the spectrum analyser and use the following settings:

Center Frequency	The centre frequency of the channel under test
Detector	Peak
RBW	For 6dB Bandwidth :100K For 99% Occupied Bandwidth :1% to 5% of the occupied bandwidth
VBW	For 6dB Bandwidth : $\geq 3 \times \text{RBW}$ For 99% Occupied Bandwidth : approximately $3 \times \text{RBW}$
Trace	Max hold
Sweep	Auto couple

Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB and 99% relative to the maximum level measured in the fundamental emission.

TEST SETUP






TEST ENVIRONMENT



Temperature	22.6°C	Relative Humidity	58%
Atmosphere Pressure	101kPa	Test Voltage	DC 5V



RESULTS


8.2.1. 802.11b MODE

Channel	6dB bandwidth (MHz)	99% bandwidth (MHz)	Limit (kHz)	Result
Low	10.07	12.212	≥500	Pass
Middle	10.06	12.186	≥500	Pass
High	10.05	12.187	≥500	Pass

















8.2.2. 802.11g MODE

Channel	6dB bandwidth (MHz)	99% bandwidth (MHz)	Limit (kHz)	Result
Low	16.37	16.778	≥500	Pass
Middle	16.36	16.694	≥500	Pass
High	16.31	16.721	≥500	Pass

















8.2.3. 802.11n HT20 MODE

Channel	6dB bandwidth (MHz)	99% bandwidth (MHz)	Limit (kHz)	Result
Low	17.05	17.661	≥500	Pass
Middle	17.30	17.592	≥500	Pass
High	16.44	17.614	≥500	Pass

















8.2.4. 802.11n HT40 MODE

Channel	6dB bandwidth (MHz)	99% bandwidth (MHz)	Limit (kHz)	Result
Low	36.05	36.356	≥500	Pass
Middle	35.66	36.258	≥500	Pass
High	36.31	36.444	≥500	Pass











8.3. PEAK CONDUCTED OUTPUT POWER


LIMITS

CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 2			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247(b)(3) ISED RSS-247 5.4 (e)	Peak Output Power	1 watt or 30dBm	2400-2483.5

TEST PROCEDURE

Place the EUT on the table and set it in the transmitting mode.
Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the Power sensor.
Measure the power of each channel.
Peak Detector use for Peak result.
AVG Detector use for AVG result.

TEST SETUP



TEST ENVIRONMENT

Temperature	22.6°C	Relative Humidity	58%
Atmosphere Pressure	101kPa	Test Voltage	DC 5V



RESULTS

8.3.1. 802.11b MODE

Test Channel	Maximum Conducted Output Power(PK)	Maximum Conducted Output Power(AV)	LIMIT
	(dBm)	(dBm)	dBm
Low	18.89	17.85	30
Middle	18.83	17.83	30
High	18.85	17.87	30

8.3.2. 802.11g MODE

Test Channel	Maximum Conducted Output Power(PK)	Maximum Conducted Output Power(AV)	LIMIT
	(dBm)	(dBm)	dBm
Low	21.79	15.27	30
Middle	22.23	15.27	30
High	22.27	15.27	30

8.3.3. 802.11n HT20 MODE

Test Channel	Maximum Conducted Output Power(PK)	Maximum Conducted Output Power(AV)	LIMIT
	(dBm)	(dBm)	dBm
Low	21.80	15.12	30
Middle	22.34	14.88	30
High	22.14	15.01	30

8.3.4. 802.11n HT40 MODE

Test Channel	Maximum Conducted Output Power(PK)	Maximum Conducted Output Power(AV)	LIMIT
	(dBm)	(dBm)	dBm
Low	22.43	15.07	30
Middle	22.44	15.03	30
High	22.25	15.13	30



8.4. POWER SPECTRAL DENSITY

LIMITS

CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 2			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC §15.247 (e) ISED RSS-247 5.2 (b)	Power Spectral Density	8 dBm/3 kHz	2400-2483.5

TEST PROCEDURE


Connect the UUT to the spectrum analyser and use the following settings:

Center Frequency	The centre frequency of the channel under test
Detector	Peak
RBW	$3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
VBW	$\geq 3 \times \text{RBW}$
Span	1.5 x DTS bandwidth
Trace	Max hold
Sweep time	Auto couple.

Allow trace to fully stabilize and use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

TEST SETUP



TEST ENVIRONMENT


Temperature	22.6°C	Relative Humidity	58%
Atmosphere Pressure	101kPa	Test Voltage	DC 5V



RESULTS




8.4.1. 802.11b MODE


Test Channel	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
Low	5.232	8	PASS
Middle	5.166	8	PASS
High	5.215	8	PASS









Test Channel	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
Low	-9.807	8	PASS
Middle	-10.587	8	PASS
High	-10.040	8	PASS










8.4.3. 802.11n HT20 MODE

Test Channel	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
Low	-11.608	8	PASS
Middle	-11.324	8	PASS
High	-11.171	8	PASS










8.4.4. 802.11n HT40 MODE

Test Channel	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
Low	-11.447	8	PASS
Middle	-11.762	8	PASS
High	-13.367	8	PASS







8.5. CONDUCTED BANDEGE AND SPURIOUS EMISSIONS

LIMITS

CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 2		
Section	Test Item	Limit
CFR 47 FCC §15.247 (d) ISED RSS-247 5.5	Conducted Bandedge and Spurious Emissions	at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power

TEST PROCEDURE

Connect the UUT to the spectrum analyser and use the following settings:

Center Frequency	The centre frequency of the channel under test
Detector	Peak
RBW	100K
VBW	$\geq 3 \times \text{RBW}$
Span	1.5 x DTS bandwidth
Trace	Max hold
Sweep time	Auto couple.


Use the peak marker function to determine the maximum PSD level.

Span	Set the center frequency and span to encompass frequency range to be measured
Detector	Peak
RBW	100K
VBW	$\geq 3 \times \text{RBW}$
measurement points	$\geq \text{span}/\text{RBW}$
Trace	Max hold
Sweep time	Auto couple.

Use the peak marker function to determine the maximum amplitude level.



TEST SETUP






TEST ENVIRONMENT



Temperature	22.6°C	Relative Humidity	58%
Atmosphere Pressure	101kPa	Test Voltage	DC 5V



RESULTS



8.5.1. 802.11b MODE




















8.5.2. 802.11g MODE






















8.5.3. 802.11n HT20 MODE



















8.5.4. 802.11n HT40 MODE












HIGH CH SPURIOUS EMISSIONS 10GHz-26GHz





9. RADIATED TEST RESULTS

LIMITS

Please refer to CFR 47 FCC §15.205 and §15.209

Please refer to ISED RSS-GEN Clause 8.9 (Transmitter)

Radiation Disturbance Test Limit for FCC (Class B)(9KHz-1GHz)

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
960~1000	500	3

Note: 1) At frequencies at or above 30 MHz, measurements may be performed at a distance other than what is specified provided: measurements are not made in the near field except where it can be shown that near field measurements are appropriate due to the characteristics of the device; and it can be demonstrated that the signal levels needed to be measured at the distance employed can be detected by the measurement equipment. Measurements shall not be performed at a distance greater than 30 meters unless it can be further demonstrated that measurements at a distance of 30 meters or less are impractical. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse linear-distance for field strength measurements; inverse-linear-distance-squared for power density measurements).

(2) At frequencies below 30 MHz, measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field. Pending the development of an appropriate measurement procedure for measurements performed below 30 MHz, when performing measurements at a closer distance than specified, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade). This paragraph (f) shall not apply to Access BPL devices operating below 30 MHz.



Radiation Disturbance Test Limit for FCC (Above 1G)

Frequency (MHz)	dB(uV/m) (at 3 meters)	
	Peak	Average
Above 1000	74	54

IC Restricted bands please refer to ISSED RSS-GEN Clause 8.10


FCC Restricted bands of operation:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

Note: ¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.²Above 38.6c

TEST SETUP AND PROCEDURE

Below 30MHz




The setting of the spectrum analyser

RBW	200Hz (From 9kHz to 0.15MHz)/ 9KHz (From 0.15MHz to 30MHz)
VBW	200Hz (From 9kHz to 0.15MHz)/ 9KHz (From 0.15MHz to 30MHz)
Sweep	Auto
Detector	Peak/QP/ Average
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 0.8 meter above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement below 1GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
6. For the actual test configuration, please refer to the related item in this test report (Photographs of the Test Configuration)
7. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field site based on KDB 414788.

Below 1G




The setting of the spectrum analyser

RBW	120K
VBW	300K
Sweep	Auto
Detector	Peak/QP
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 0.8 meter above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement below 1GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

ABOVE 1G




The setting of the spectrum analyser

RBW	1M
VBW	PEAK: 3M AVG: see note 6
Sweep	Auto
Detector	Peak
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 1.5m above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement above 1GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.
6. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector for average measurements. For the Duty Cycle please refer to clause 8.1.ON TIME AND DUTY CYCLE.



X axis, Y axis, Z axis positions:



Note 1: For below 1GHz radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.

Note 2: The EUT was fully exercised with external accessories during the test. In the case of multiple accessory external ports, an external accessory shall be connected to one of each type of port.

TEST ENVIRONMENT

Temperature	23.7°C	Relative Humidity	57%
Atmosphere Pressure	101kPa	Test Voltage	DC 5V




9.1. RESTRICTED BANDEDGE FOR ANTENNA 1

9.1.1. 802.11b MODE

RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)

PEAK




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2311.150	19.70	32.68	52.38	74.00	-21.62	peak
2	2390.000	15.27	32.94	48.21	74.00	-25.79	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)

PEAK




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2367.385	16.98	32.87	49.85	74.00	-24.15	peak
2	2390.000	15.72	32.94	48.66	74.00	-25.34	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.




RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)

PEAK



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	15.35	33.58	48.93	74.00	-25.07	peak
2	2486.300	16.47	33.61	50.08	74.00	-23.92	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**RESTRICTED BANDEDGE (HIGH CHANNEL, VERTICAL)****PEAK**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	13.47	33.58	47.05	54.00	-6.95	AVG
2	2484.900	12.92	33.59	46.51	54.00	-7.49	AVG

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.


4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



9.1.2. 802.11g MODE

RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)

PEAK




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	34.53	32.94	67.47	74.00	-6.53	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



AVG




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	16.09	32.94	49.03	54.00	-4.97	AVG

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. AVG: $VBW=1/Ton$ where: ton is transmit duration.
4. For transmit duration, please refer to clause 8.1.
5. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.




RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)

PEAK




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	36.89	32.94	69.83	74.00	-4.17	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**AVG**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	17.46	32.94	50.40	54.00	-3.60	AVG

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. AVG: $VBW=1/Ton$ where: ton is transmit duration.
4. For transmit duration, please refer to clause 8.1.
5. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**RESTRICTED BANDEGE (HIGH CHANNEL, HORIZONTAL)****PEAK**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	30.28	33.58	63.86	74.00	-10.14	peak
2	2484.900	31.01	33.59	64.60	74.00	-9.40	peak

Note: 1. Measurement = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



AVG




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	8.20	33.58	41.78	54.00	-12.22	AVG
2	2484.900	7.75	33.59	41.34	54.00	-12.66	AVG

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. AVG: $VBW=1/Ton$ where: ton is transmit duration.
4. For transmit duration, please refer to clause 8.1.
5. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.




RESTRICTED BANDEDGE (HIGH CHANNEL, VERTICAL)

PEAK



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	34.68	33.58	68.26	74.00	-5.74	peak
2	2484.900	36.31	33.59	69.90	74.00	-4.10	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**AVG**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	13.47	33.58	47.05	54.00	-6.95	AVG
2	2484.900	12.92	33.59	46.51	54.00	-7.49	AVG


Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. AVG: $VBW=1/Ton$ where: ton is transmit duration.
4. For transmit duration, please refer to clause 8.1.
5. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



9.1.3. 802.11n HT20 MODE

RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)

PEAK




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	34.12	32.94	67.06	74.00	-6.94	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.




AVG




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	13.82	32.94	46.76	54.00	-7.24	AVG

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. AVG: $VBW=1/T_{on}$ where: t_{on} is transmit duration.
4. For transmit duration, please refer to clause 8.1.
5. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)****PEAK**


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	36.38	32.94	69.32	74.00	-4.68	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**AVG**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	15.11	32.94	48.05	54.00	-5.95	AVG

- Note:
1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. AVG: $VBW=1/Ton$ where: ton is transmit duration.
 4. For transmit duration, please refer to clause 8.1.
 5. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)****PEAK**


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	21.37	33.58	54.95	74.00	-19.05	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Peak: Peak detector.

4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**AVG**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	11.45	33.58	45.03	54.00	-8.97	AVG

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. AVG: $VBW=1/Ton$ where: ton is transmit duration.
4. For transmit duration, please refer to clause 8.1.
5. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**RESTRICTED BANDEDGE (HIGH CHANNEL, VERTICAL)****PEAK**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	25.75	33.58	59.33	74.00	-14.67	peak
2	2483.600	27.25	33.58	60.83	74.00	-13.17	peak

Note: 1. Measurement = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



AVG



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	12.27	33.58	45.85	54.00	-8.15	AVG
2	2483.600	12.28	33.58	45.86	54.00	-8.14	AVG


Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. AVG: $VBW=1/Ton$ where: ton is transmit duration.
4. For transmit duration, please refer to clause 8.1.
5. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



9.1.4. 802.11n HT40 MODE


RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)

PEAK




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2388.680	32.36	32.94	65.30	74.00	-8.70	peak
2	2390.000	30.61	32.94	63.55	74.00	-10.45	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**AVG**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2388.680	15.71	32.94	48.65	54.00	-5.35	AVG
2	2390.000	16.14	32.94	49.08	54.00	-4.92	AVG

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. AVG: $VBW=1/Ton$ where: ton is transmit duration.
4. For transmit duration, please refer to clause 8.1.
5. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.


**RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)****PEAK**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2389.465	27.32	32.94	60.26	74.00	-13.74	peak
2	2390.000	27.07	32.94	60.01	74.00	-13.99	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.




AVG



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2389.465	8.39	32.94	41.33	54.00	-12.67	AVG
2	2390.000	8.73	32.94	41.67	54.00	-12.33	AVG

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. AVG: $VBW=1/Ton$ where: ton is transmit duration.
4. For transmit duration, please refer to clause 8.1.
5. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.


**RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)****PEAK**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	19.46	33.58	53.04	74.00	-20.96	peak
2	2483.900	20.78	33.58	54.36	74.00	-19.64	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.




AVG



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	5.76	33.58	39.34	54.00	-14.66	AVG
2	2483.900	5.65	33.58	39.23	54.00	-14.77	AVG

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. AVG: $VBW=1/Ton$ where: ton is transmit duration.
4. For transmit duration, please refer to clause 8.1.
5. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**RESTRICTED BANDEDGE (HIGH CHANNEL, VERTICAL)****PEAK**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	25.90	33.58	59.48	74.00	-14.52	peak
2	2483.760	28.39	33.58	61.97	74.00	-12.03	peak

Note: 1. Measurement = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



AVG



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	12.58	33.58	46.16	54.00	-7.84	AVG
2	2483.760	12.58	33.58	46.16	54.00	-7.84	AVG

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. AVG: $VBW=1/Ton$ where: ton is transmit duration.
4. For transmit duration, please refer to clause 8.1.
5. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.




9.2. RESTRICTED BANDEDGE FOR ANTENNA 2

9.2.1. 802.11b MODE

RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)

PEAK




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2343.580	17.29	32.79	50.08	74.00	-23.92	peak
2	2390.000	14.75	32.94	47.69	74.00	-26.31	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)

PEAK




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2342.200	16.76	32.79	49.55	74.00	-24.45	peak
2	2390.000	15.00	32.94	47.94	74.00	-26.06	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.




RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)

PEAK



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	14.93	33.58	48.51	74.00	-25.49	peak
2	2498.050	16.51	33.69	50.20	74.00	-23.80	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**RESTRICTED BANDEDGE (HIGH CHANNEL, VERTICAL)****PEAK**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	15.63	33.58	49.21	74.00	-24.79	peak
2	2497.550	18.08	33.69	51.77	74.00	-22.23	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.


4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



9.2.2. 802.11g MODE

RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)

PEAK




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	26.59	32.94	59.53	74.00	-14.47	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



AVG




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	8.38	32.94	41.32	54.00	-12.68	AVG

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. AVG: $VBW=1/Ton$ where: ton is transmit duration.
4. For transmit duration, please refer to clause 8.1.
5. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.




RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)

PEAK




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2389.465	27.32	32.94	60.26	74.00	-13.74	peak
2	2390.000	27.07	32.94	60.01	74.00	-13.99	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**AVG**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2389.465	8.39	32.94	41.33	54.00	-12.67	AVG
2	2390.000	8.73	32.94	41.67	54.00	-12.33	AVG

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. AVG: $VBW=1/Ton$ where: ton is transmit duration.
4. For transmit duration, please refer to clause 8.1.
5. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)****PEAK**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	23.36	33.58	56.94	74.00	-17.06	peak
2	2484.400	25.49	33.59	59.08	74.00	-14.92	peak

Note: 1. Measurement = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



AVG




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	7.14	33.58	40.72	54.00	-13.28	AVG
2	2484.400	5.78	33.59	39.37	54.00	-14.63	AVG

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. AVG: $VBW=1/Ton$ where: ton is transmit duration.
4. For transmit duration, please refer to clause 8.1.
5. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



RESTRICTED BANDEDGE (HIGH CHANNEL, VERTICAL)

PEAK




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	27.53	33.58	61.11	74.00	-12.89	peak
2	2483.650	28.82	33.58	62.40	74.00	-11.60	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



AVG



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	7.33	33.58	40.91	54.00	-13.09	AVG
2	2483.650	7.21	33.58	40.79	54.00	-13.21	AVG


Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. AVG: $VBW=1/Ton$ where: ton is transmit duration.
4. For transmit duration, please refer to clause 8.1.
5. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



9.2.3. 802.11n HT20 MODE

RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)

PEAK




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2388.890	22.17	32.94	55.11	74.00	-18.89	peak
2	2390.000	20.16	32.94	53.10	74.00	-20.90	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.




AVG



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2388.890	3.62	32.94	36.56	54.00	-17.44	AVG
2	2390.000	4.46	32.94	37.40	54.00	-16.60	AVG

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. AVG: $VBW=1/Ton$ where: ton is transmit duration.
4. For transmit duration, please refer to clause 8.1.
5. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.


**RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)****PEAK**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2388.890	23.93	32.94	56.87	74.00	-17.13	peak
2	2390.000	21.99	32.94	54.93	74.00	-19.07	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.




AVG



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2388.890	7.14	32.94	40.08	54.00	-13.92	AVG
2	2390.000	7.76	32.94	40.70	54.00	-13.30	AVG

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. AVG: $VBW=1/Ton$ where: ton is transmit duration.
4. For transmit duration, please refer to clause 8.1.
5. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.


**RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)****PEAK**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	21.48	33.58	55.06	74.00	-18.94	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.




AVG



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	4.27	33.58	37.85	54.00	-16.15	AVG

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. AVG: $VBW=1/Ton$ where: ton is transmit duration.
4. For transmit duration, please refer to clause 8.1.
5. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.


**RESTRICTED BANDEDGE (HIGH CHANNEL, VERTICAL)****PEAK**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	24.80	33.58	58.38	74.00	-15.62	peak

- Note:
1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



AVG



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	4.78	33.58	38.36	54.00	-15.64	AVG


Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. AVG: $VBW=1/Ton$ where: ton is transmit duration.
4. For transmit duration, please refer to clause 8.1.
5. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



9.2.4. 802.11n HT40 MODE

RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)

PEAK




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2387.420	22.31	32.94	55.25	74.00	-18.75	peak
2	2390.000	21.98	32.94	54.92	74.00	-19.08	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.




AVG



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2387.420	5.90	32.94	38.84	54.00	-15.16	AVG
2	2390.000	7.33	32.94	40.27	54.00	-13.73	AVG

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. AVG: $VBW=1/Ton$ where: ton is transmit duration.
4. For transmit duration, please refer to clause 8.1.
5. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.


**RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)****PEAK**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2387.980	22.58	32.94	55.52	74.00	-18.48	peak
2	2390.000	21.58	32.94	54.52	74.00	-19.48	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.




AVG



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2387.980	6.02	32.94	38.96	54.00	-15.04	AVG
2	2390.000	7.02	32.94	39.96	54.00	-14.04	AVG

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. AVG: $VBW=1/Ton$ where: ton is transmit duration.
4. For transmit duration, please refer to clause 8.1.
5. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)****PEAK**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	29.64	33.58	63.22	74.00	-10.78	peak
2	2484.110	31.11	33.58	64.69	74.00	-9.31	peak

Note: 1. Measurement = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.




AVG



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	11.60	33.58	45.18	54.00	-8.82	AVG
2	2484.110	11.41	33.58	44.99	54.00	-9.01	AVG

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. AVG: $VBW=1/Ton$ where: ton is transmit duration.
4. For transmit duration, please refer to clause 8.1.
5. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**RESTRICTED BANDEDGE (HIGH CHANNEL, VERTICAL)****PEAK**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	31.77	33.58	65.35	74.00	-8.65	peak
2	2484.530	33.04	33.59	66.63	74.00	-7.37	peak

Note: 1. Measurement = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



AVG



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	13.16	33.58	46.74	54.00	-7.26	AVG
2	2484.530	12.58	33.59	46.17	54.00	-7.83	AVG


Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. AVG: $VBW=1/Ton$ where: ton is transmit duration.
4. For transmit duration, please refer to clause 8.1.
5. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



9.3. SPURIOUS EMISSIONS (3~18GHz) FOR ANTENNA 1

9.3.1. 802.11b MODE

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3211.375	51.97	-4.51	47.46	74.00	-26.54	peak
2	4823.156	51.33	-0.21	51.12	74.00	-22.88	peak
3	8226.601	38.66	9.33	47.99	74.00	-26.01	peak
4	12245.316	35.79	14.31	50.10	74.00	-23.90	peak
5	13562.027	35.41	15.92	51.33	74.00	-22.67	peak
6	17680.355	30.12	22.07	52.19	74.00	-21.81	peak


Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.


4. The High Pass filter loss factor already add into the correct factor.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3211.375	53.69	-4.51	49.18	74.00	-24.82	peak
2	4823.156	51.83	-0.21	51.62	74.00	-22.38	peak
3	8138.634	38.84	9.25	48.09	74.00	-25.91	peak
4	12311.315	35.99	14.39	50.38	74.00	-23.62	peak
5	14439.758	34.85	16.39	51.24	74.00	-22.76	peak
6	17304.266	30.79	21.88	52.67	74.00	-21.33	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The High Pass filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3251.907	52.30	-4.37	47.93	74.00	-26.07	peak
2	4875.288	51.03	-0.12	50.91	74.00	-23.09	peak
3	7880.337	40.02	8.52	48.54	74.00	-25.46	peak
4	10591.067	37.08	12.69	49.77	74.00	-24.23	peak
5	14006.555	35.14	16.36	51.50	74.00	-22.50	peak
6	17935.612	29.51	23.19	52.70	74.00	-21.30	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The High Pass filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.




HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3251.907	53.97	-4.37	49.60	74.00	-24.40	peak
2	4875.288	52.96	-0.12	52.84	74.00	-21.16	peak
3	8226.601	38.87	9.33	48.20	74.00	-25.80	peak
4	11276.518	37.99	12.94	50.93	74.00	-23.07	peak
5	13441.070	35.51	15.79	51.30	74.00	-22.70	peak
6	17839.462	29.61	23.21	52.82	74.00	-21.18	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The High Pass filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3281.171	54.07	-4.27	49.80	74.00	-24.20	peak
2	4919.161	50.96	0.02	50.98	74.00	-23.02	peak
3	8226.601	38.43	9.33	47.76	74.00	-26.24	peak
4	12245.316	36.31	14.31	50.62	74.00	-23.38	peak
5	13807.216	33.88	16.76	50.64	74.00	-23.36	peak
6	17680.356	30.08	22.07	52.15	74.00	-21.85	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The High Pass filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3281.171	54.31	-4.27	50.04	74.00	-23.96	peak
2	4919.161	53.27	0.02	53.29	74.00	-20.71	peak
3	7880.337	38.84	8.52	47.36	74.00	-26.64	peak
4	12245.316	36.06	14.31	50.37	74.00	-23.63	peak
5	14439.758	35.78	16.39	52.17	74.00	-21.83	peak
6	17967.777	29.15	23.24	52.39	74.00	-21.61	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The High Pass filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.




9.3.2. 802.11g MODE

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3210.000	57.44	-4.51	52.93	74.00	-21.07	peak
2	4815.000	51.87	-0.23	51.64	74.00	-22.36	peak
3	11445.000	36.27	13.68	49.95	74.00	-24.05	peak
4	14340.000	34.73	16.36	51.09	74.00	-22.91	peak
5	17325.000	30.04	21.80	51.84	74.00	-22.16	peak
6	17745.000	29.75	22.68	52.43	74.00	-21.57	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The High Pass filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


**HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3216.054	58.94	-4.48	54.46	74.00	-19.54	peak
2	3216.054	56.49	-4.48	52.01	54.00	-1.99	AVG
3	4815.000	51.86	-0.23	51.63	74.00	-22.37	peak
4	10980.000	36.54	13.06	49.60	74.00	-24.40	peak
5	14250.000	34.75	16.39	51.14	74.00	-22.86	peak
6	17325.000	29.95	21.80	51.75	74.00	-22.25	peak
7	17835.000	29.29	23.20	52.49	74.00	-21.51	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. AVG: $VBW=1/Ton$ where: ton is transmit duration.
5. For transmit duration, please refer to clause 8.1.
6. The High Pass filter loss factor already add into the correct factor.
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.




HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3240.000	54.20	-4.41	49.79	74.00	-24.21	peak
2	4860.000	50.55	-0.15	50.40	74.00	-23.60	peak
3	11550.000	36.57	14.13	50.70	74.00	-23.30	peak
4	14490.000	34.81	16.32	51.13	74.00	-22.87	peak
5	16785.000	32.39	19.90	52.29	74.00	-21.71	peak
6	17835.000	29.00	23.20	52.20	74.00	-21.80	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The High Pass filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3240.000	56.83	-4.41	52.42	74.00	-21.58	peak
2	4005.000	52.39	-2.94	49.45	74.00	-24.55	peak
3	4860.000	49.56	-0.15	49.41	74.00	-24.59	peak
4	11370.000	37.23	13.22	50.45	74.00	-23.55	peak
5	14460.000	35.30	16.35	51.65	74.00	-22.35	peak
6	17715.000	29.46	22.39	51.85	74.00	-22.15	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The High Pass filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3270.000	53.73	-4.31	49.42	74.00	-24.58	peak
2	4920.000	49.50	0.02	49.52	74.00	-24.48	peak
3	11550.000	36.01	14.13	50.14	74.00	-23.86	peak
4	14430.000	35.21	16.39	51.60	74.00	-22.40	peak
5	17025.000	31.69	20.45	52.14	74.00	-21.86	peak
6	17820.000	29.07	23.21	52.28	74.00	-21.72	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The High Pass filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3270.000	56.10	-4.31	51.79	74.00	-22.21	peak
2	3975.000	51.98	-2.98	49.00	74.00	-25.00	peak
3	4920.000	51.56	0.02	51.58	74.00	-22.42	peak
4	8220.000	38.51	9.40	47.91	74.00	-26.09	peak
5	14775.000	35.40	15.71	51.11	74.00	-22.89	peak
6	17820.000	28.79	23.21	52.00	74.00	-22.00	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The High Pass filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.




9.3.3. 802.11n HT20 MODE

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3210.000	57.90	-4.51	53.39	74.00	-20.61	peak
2	4815.000	52.84	-0.23	52.61	74.00	-21.39	peak
3	8145.000	38.44	9.30	47.74	74.00	-26.26	peak
4	13440.000	34.87	15.80	50.67	74.00	-23.33	peak
5	14460.000	35.03	16.35	51.38	74.00	-22.62	peak
6	16635.000	32.04	19.53	51.57	74.00	-22.43	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The High Pass filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)**


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3216.000	59.07	-4.48	54.59	74.00	-19.41	peak
2	3216.090	57.32	-4.48	52.84	54.00	-1.16	AVG
3	4815.000	53.12	-0.23	52.89	74.00	-21.11	peak
4	10590.000	37.20	12.68	49.88	74.00	-24.12	peak
5	14430.000	34.88	16.39	51.27	74.00	-22.73	peak
6	17040.000	31.34	20.51	51.85	74.00	-22.15	peak
7	17745.000	29.60	22.68	52.28	74.00	-21.72	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. AVG: $VBW=1/Ton$ where: ton is transmit duration.
5. For transmit duration, please refer to clause 8.1.
6. The High Pass filter loss factor already add into the correct factor.
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3240.000	54.40	-4.41	49.99	74.00	-24.01	peak
2	4875.000	50.18	-0.12	50.06	74.00	-23.94	peak
3	8175.000	38.80	9.48	48.28	74.00	-25.72	peak
4	13605.000	34.62	16.07	50.69	74.00	-23.31	peak
5	16650.000	32.38	19.60	51.98	74.00	-22.02	peak
6	17820.000	28.71	23.21	51.92	74.00	-22.08	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The High Pass filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3240.000	56.73	-4.41	52.32	74.00	-21.68	peak
2	4860.000	50.77	-0.15	50.62	74.00	-23.38	peak
3	8205.000	38.63	9.57	48.20	74.00	-25.80	peak
4	14220.000	34.50	16.45	50.95	74.00	-23.05	peak
5	16770.000	32.58	19.89	52.47	74.00	-21.53	peak
6	17340.000	30.49	21.73	52.22	74.00	-21.78	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The High Pass filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.




HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3270.000	53.42	-4.31	49.11	74.00	-24.89	peak
2	4920.000	49.98	0.02	50.00	74.00	-24.00	peak
3	8220.000	38.36	9.40	47.76	74.00	-26.24	peak
4	12345.000	36.43	14.36	50.79	74.00	-23.21	peak
5	14370.000	34.69	16.39	51.08	74.00	-22.92	peak
6	17745.000	30.10	22.68	52.78	74.00	-21.22	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The High Pass filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)**


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3270.000	56.53	-4.31	52.22	74.00	-21.78	peak
2	4920.000	51.19	0.02	51.21	74.00	-22.79	peak
3	8175.000	38.39	9.48	47.87	74.00	-26.13	peak
4	13935.000	34.71	16.24	50.95	74.00	-23.05	peak
5	16440.000	33.13	18.69	51.82	74.00	-22.18	peak
6	17430.000	30.92	21.31	52.23	74.00	-21.77	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The High Pass filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.




9.3.4. 802.11n HT40 MODE

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4824.041	56.12	-0.21	55.91	74.00	-18.09	peak
2	4824.041	42.15	-0.21	41.94	54.00	-12.06	AVG
3	9390.000	38.72	10.24	48.96	74.00	-25.04	peak
4	11550.000	36.70	14.13	50.83	74.00	-23.17	peak
5	14235.000	35.08	16.42	51.50	74.00	-22.50	peak
6	16725.000	32.23	19.85	52.08	74.00	-21.92	peak
7	17820.000	29.59	23.21	52.80	74.00	-21.20	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. AVG: VBW=1/Ton where: ton is transmit duration.
5. For transmit duration, please refer to clause 8.1.
6. The High Pass filter loss factor already add into the correct factor.
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)**


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4824.111	56.04	-0.21	55.83	74.00	-18.17	peak
2	4824.111	41.48	-0.21	41.27	54.00	-12.73	AVG
3	8220.000	39.92	9.40	49.32	74.00	-24.68	peak
4	10575.000	37.33	12.52	49.85	74.00	-24.15	peak
5	14400.000	35.05	16.43	51.48	74.00	-22.52	peak
6	16935.000	31.50	20.07	51.57	74.00	-22.43	peak
7	17655.000	30.60	21.87	52.47	74.00	-21.53	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. AVG: $VBW=1/Ton$ where: ton is transmit duration.
5. For transmit duration, please refer to clause 8.1.
6. The High Pass filter loss factor already add into the correct factor.
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)**


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4845.000	52.77	-0.17	52.60	74.00	-21.40	peak
2	7320.000	40.46	7.20	47.66	74.00	-26.34	peak
3	10635.000	37.24	12.59	49.83	74.00	-24.17	peak
4	12330.000	36.07	14.38	50.45	74.00	-23.55	peak
5	14445.000	35.02	16.37	51.39	74.00	-22.61	peak
6	18000.000	29.01	23.27	52.28	74.00	-21.72	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The High Pass filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)**


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3240.000	55.50	-4.41	51.09	74.00	-22.91	peak
2	4854.001	55.67	-0.15	55.52	74.00	-18.48	peak
3	4854.001	42.86	-0.15	42.71	54.00	-11.29	AVG
4	10590.000	36.82	12.68	49.50	74.00	-24.50	peak
5	14445.000	34.71	16.37	51.08	74.00	-22.92	peak
6	16800.000	30.94	19.91	50.85	74.00	-23.15	peak
7	17820.000	28.65	23.21	51.86	74.00	-22.14	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. AVG: $VBW=1/Ton$ where: ton is transmit duration.
5. For transmit duration, please refer to clause 8.1.
6. The High Pass filter loss factor already add into the correct factor.
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3255.000	56.08	-4.36	51.72	74.00	-22.28	peak
2	4875.000	52.31	-0.12	52.19	74.00	-21.81	peak
3	12330.000	36.27	14.38	50.65	74.00	-23.35	peak
4	14445.000	35.57	16.37	51.94	74.00	-22.06	peak
5	17115.000	31.04	20.81	51.85	74.00	-22.15	peak
6	17805.000	28.69	23.22	51.91	74.00	-22.09	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The High Pass filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	52.65	-0.12	52.53	74.00	-21.47	peak
2	9435.000	38.13	10.37	48.50	74.00	-25.50	peak
3	11550.000	36.83	14.13	50.96	74.00	-23.04	peak
4	14430.000	35.45	16.39	51.84	74.00	-22.16	peak
5	16680.000	32.05	19.74	51.79	74.00	-22.21	peak
6	17925.000	29.17	23.18	52.35	74.00	-21.65	peak


Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The High Pass filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



9.4. SPURIOUS EMISSIONS (3~18GHz) FOR ANTENNA 2

9.4.1. 802.11b MODE

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3211.375	51.52	-4.51	47.01	74.00	-26.99	peak
2	4823.156	47.82	-0.21	47.61	74.00	-26.39	peak
3	7230.919	46.14	6.96	53.10	74.00	-20.90	peak
4	10591.067	36.59	12.69	49.28	74.00	-24.72	peak
5	14388.105	35.06	16.42	51.48	74.00	-22.52	peak
6	17871.454	28.98	23.18	52.16	74.00	-21.84	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Peak: Peak detector.

4. The High Pass filter loss factor already add into the correct factor.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.




HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3211.375	52.90	-4.51	48.39	74.00	-25.61	peak
2	4823.156	50.31	-0.21	50.10	74.00	-23.90	peak
3	7243.887	45.29	6.99	52.28	74.00	-21.72	peak
4	9648.857	39.40	10.04	49.44	74.00	-24.56	peak
5	14362.348	35.31	16.38	51.69	74.00	-22.31	peak
6	18000.000	29.04	23.27	52.31	74.00	-21.69	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The High Pass filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.288	50.48	-0.12	50.36	74.00	-23.64	peak
2	7309.075	45.49	7.17	52.66	74.00	-21.34	peak
3	10591.067	36.84	12.69	49.53	74.00	-24.47	peak
4	11521.601	36.85	14.10	50.95	74.00	-23.05	peak
5	14439.758	35.76	16.39	52.15	74.00	-21.85	peak
6	17839.462	29.12	23.21	52.33	74.00	-21.67	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The High Pass filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.




HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.288	53.36	-0.12	53.24	74.00	-20.76	peak
2	7309.075	43.36	7.17	50.53	74.00	-23.47	peak
3	10591.067	37.29	12.69	49.98	74.00	-24.02	peak
4	11337.296	37.05	13.07	50.12	74.00	-23.88	peak
5	14006.555	34.61	16.36	50.97	74.00	-23.03	peak
6	17712.063	29.61	22.36	51.97	74.00	-22.03	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The High Pass filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4919.161	52.30	0.02	52.32	74.00	-21.68	peak
2	8153.229	38.55	9.35	47.90	74.00	-26.10	peak
3	11398.401	36.68	13.35	50.03	74.00	-23.97	peak
4	13906.528	35.72	16.18	51.90	74.00	-22.10	peak
5	14439.758	35.88	16.39	52.27	74.00	-21.73	peak
6	17335.299	30.51	21.75	52.26	74.00	-21.74	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The High Pass filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)**


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4919.161	53.46	0.02	53.48	74.00	-20.52	peak
2	8138.634	39.10	9.25	48.35	74.00	-25.65	peak
3	10591.067	37.46	12.69	50.15	74.00	-23.85	peak
4	12267.276	36.40	14.34	50.74	74.00	-23.26	peak
5	14439.758	35.58	16.39	51.97	74.00	-22.03	peak
6	17807.526	29.10	23.21	52.31	74.00	-21.69	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The High Pass filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.




9.4.2. 802.11g MODE

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4823.871	56.81	-0.21	56.60	74.00	-17.40	peak
2	4823.871	43.87	-0.21	43.66	54.00	-10.34	AVG
3	10995.000	37.25	13.23	50.48	74.00	-23.52	peak
4	14385.000	34.69	16.41	51.10	74.00	-22.90	peak
5	16425.000	33.02	18.65	51.67	74.00	-22.33	peak
6	17100.000	31.66	20.78	52.44	74.00	-21.56	peak
7	17805.000	29.66	23.22	52.88	74.00	-21.12	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. AVG: VBW=1/Ton where: ton is transmit duration.
5. For transmit duration, please refer to clause 8.1.
6. The High Pass filter loss factor already add into the correct factor.
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.


**HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4824.000	57.35	-0.21	57.14	74.00	-16.86	peak
2	4824.000	42.11	-0.21	41.90	54.00	-12.10	AVG
3	10320.000	37.59	11.58	49.17	74.00	-24.83	peak
4	12510.000	35.62	14.76	50.38	74.00	-23.62	peak
5	14370.000	35.06	16.39	51.45	74.00	-22.55	peak
6	16770.000	31.90	19.89	51.79	74.00	-22.21	peak
7	17925.000	28.94	23.18	52.12	74.00	-21.88	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. AVG: $VBW=1/Ton$ where: ton is transmit duration.
5. For transmit duration, please refer to clause 8.1.
6. The High Pass filter loss factor already add into the correct factor.
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.




HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4860.000	50.79	-0.15	50.64	74.00	-23.36	peak
2	8220.000	38.58	9.40	47.98	74.00	-26.02	peak
3	11520.000	36.70	14.10	50.80	74.00	-23.20	peak
4	14460.000	35.03	16.35	51.38	74.00	-22.62	peak
5	16860.000	32.57	19.92	52.49	74.00	-21.51	peak
6	17820.000	29.48	23.21	52.69	74.00	-21.31	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The High Pass filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)**


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4005.000	52.18	-2.94	49.24	74.00	-24.76	peak
2	4860.000	51.92	-0.15	51.77	74.00	-22.23	peak
3	7305.000	40.34	7.15	47.49	74.00	-26.51	peak
4	10590.000	37.10	12.68	49.78	74.00	-24.22	peak
5	13035.000	36.39	14.81	51.20	74.00	-22.80	peak
6	17145.000	31.11	20.88	51.99	74.00	-22.01	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The High Pass filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4924.000	54.28	0.05	54.33	74.00	-19.67	peak
2	4924.000	41.53	0.05	41.58	54.00	-12.42	AVG
3	8220.000	38.72	9.40	48.12	74.00	-25.88	peak
4	12285.000	36.28	14.37	50.65	74.00	-23.35	peak
5	14430.000	34.76	16.39	51.15	74.00	-22.85	peak
6	16935.000	31.54	20.07	51.61	74.00	-22.39	peak
7	17925.000	29.14	23.18	52.32	74.00	-21.68	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. AVG: $VBW=1/Ton$ where: ton is transmit duration.
5. For transmit duration, please refer to clause 8.1.
6. The High Pass filter loss factor already add into the correct factor.
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)**


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4005.000	53.35	-2.94	50.41	74.00	-23.59	peak
2	4924.000	54.98	0.05	55.03	74.00	-18.97	peak
3	4924.000	40.12	0.05	40.17	54.00	-13.83	AVG
4	9375.000	38.61	10.14	48.75	74.00	-25.25	peak
5	12255.000	37.09	14.32	51.41	74.00	-22.59	peak
6	14385.000	34.88	16.41	51.29	74.00	-22.71	peak
7	17115.000	30.83	20.81	51.64	74.00	-22.36	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. AVG: VBW=1/Ton where: ton is transmit duration.
5. For transmit duration, please refer to clause 8.1.
6. The High Pass filter loss factor already add into the correct factor.
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.



9.4.3. 802.11n HT20 MODE

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4815.000	53.03	-0.23	52.80	74.00	-21.20	peak
2	8220.000	39.17	9.40	48.57	74.00	-25.43	peak
3	12300.000	36.05	14.39	50.44	74.00	-23.56	peak
4	14025.000	35.29	16.31	51.60	74.00	-22.40	peak
5	16920.000	31.57	20.01	51.58	74.00	-22.42	peak
6	17940.000	29.05	23.21	52.26	74.00	-21.74	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The High Pass filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.




HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4005.000	53.68	-2.94	50.74	74.00	-23.26	peak
2	4815.000	53.64	-0.23	53.41	74.00	-20.59	peak
3	11415.000	36.60	13.46	50.06	74.00	-23.94	peak
4	13575.000	35.41	15.98	51.39	74.00	-22.61	peak
5	17325.000	29.05	21.80	50.85	74.00	-23.15	peak
6	17820.000	29.17	23.21	52.38	74.00	-21.62	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The High Pass filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3240.000	52.34	-4.41	47.93	74.00	-26.07	peak
2	4860.000	49.45	-0.15	49.30	74.00	-24.70	peak
3	9405.000	38.30	10.30	48.60	74.00	-25.40	peak
4	10590.000	37.60	12.68	50.28	74.00	-23.72	peak
5	14460.000	35.50	16.35	51.85	74.00	-22.15	peak
6	17025.000	31.52	20.45	51.97	74.00	-22.03	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The High Pass filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.




HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4005.000	53.53	-2.94	50.59	74.00	-23.41	peak
2	4860.000	51.76	-0.15	51.61	74.00	-22.39	peak
3	8220.000	38.74	9.40	48.14	74.00	-25.86	peak
4	13965.000	35.24	16.29	51.53	74.00	-22.47	peak
5	16725.000	32.86	19.85	52.71	74.00	-21.29	peak
6	17925.000	28.68	23.18	51.86	74.00	-22.14	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The High Pass filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4920.000	52.22	0.02	52.24	74.00	-21.76	peak
2	8145.000	39.11	9.30	48.41	74.00	-25.59	peak
3	10635.000	38.02	12.59	50.61	74.00	-23.39	peak
4	12225.000	37.64	14.28	51.92	74.00	-22.08	peak
5	14490.000	35.13	16.32	51.45	74.00	-22.55	peak
6	17850.000	29.30	23.19	52.49	74.00	-21.51	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The High Pass filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3990.000	53.32	-2.95	50.37	74.00	-23.63	peak
2	4920.000	51.47	0.02	51.49	74.00	-22.51	peak
3	11310.000	37.50	12.94	50.44	74.00	-23.56	peak
4	14445.000	35.07	16.37	51.44	74.00	-22.56	peak
5	16605.000	32.27	19.40	51.67	74.00	-22.33	peak
6	17775.000	29.30	22.97	52.27	74.00	-21.73	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The High Pass filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



9.4.4. 802.11n HT40 MODE

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4830.000	48.77	-0.20	48.57	74.00	-25.43	peak
2	8145.000	39.17	9.30	48.47	74.00	-25.53	peak
3	12285.000	36.08	14.37	50.45	74.00	-23.55	peak
4	15180.000	35.55	15.54	51.09	74.00	-22.91	peak
5	16875.000	31.94	19.93	51.87	74.00	-22.13	peak
6	17745.000	29.73	22.68	52.41	74.00	-21.59	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The High Pass filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.




HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4005.000	53.36	-2.94	50.42	74.00	-23.58	peak
2	4845.000	50.81	-0.17	50.64	74.00	-23.36	peak
3	11550.000	36.07	14.13	50.20	74.00	-23.80	peak
4	14475.000	34.92	16.33	51.25	74.00	-22.75	peak
5	17295.000	29.29	21.86	51.15	74.00	-22.85	peak
6	17925.000	28.83	23.18	52.01	74.00	-21.99	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The High Pass filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)**


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3240.000	51.33	-4.41	46.92	74.00	-27.08	peak
2	4845.000	47.09	-0.17	46.92	74.00	-27.08	peak
3	8370.000	39.64	8.66	48.30	74.00	-25.70	peak
4	11520.000	36.26	14.10	50.36	74.00	-23.64	peak
5	14445.000	34.98	16.37	51.35	74.00	-22.65	peak
6	16905.000	31.81	19.95	51.76	74.00	-22.24	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The High Pass filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)**


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3975.000	52.74	-2.98	49.76	74.00	-24.24	peak
2	6000.000	43.61	3.76	47.37	74.00	-26.63	peak
3	9420.000	37.94	10.34	48.28	74.00	-25.72	peak
4	13590.000	35.17	16.04	51.21	74.00	-22.79	peak
5	14220.000	35.72	16.45	52.17	74.00	-21.83	peak
6	17925.000	29.86	23.18	53.04	74.00	-20.96	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The High Pass filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3255.000	50.66	-4.36	46.30	74.00	-27.70	peak
2	4905.000	48.55	-0.07	48.48	74.00	-25.52	peak
3	9360.000	39.12	10.05	49.17	74.00	-24.83	peak
4	12285.000	36.12	14.37	50.49	74.00	-23.51	peak
5	15255.000	35.29	15.56	50.85	74.00	-23.15	peak
6	17820.000	29.36	23.21	52.57	74.00	-21.43	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The High Pass filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4005.000	53.75	-2.94	50.81	74.00	-23.19	peak
2	9420.000	38.19	10.34	48.53	74.00	-25.47	peak
3	11535.000	36.37	14.10	50.47	74.00	-23.53	peak
4	14445.000	35.50	16.37	51.87	74.00	-22.13	peak
5	16080.000	33.83	17.59	51.42	74.00	-22.58	peak
6	17940.000	28.99	23.21	52.20	74.00	-21.80	peak


Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The High Pass filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



9.5. SPURIOUS EMISSIONS (1~3GHz) FOR ANTENNA 2


9.5.1. 802.11b MODE

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1078.000	53.65	-12.71	40.94	74.00	-33.06	peak
2	1558.000	48.73	-11.03	37.70	74.00	-36.30	peak
3	1998.000	54.23	-9.77	44.46	74.00	-29.54	peak
4	2144.000	48.85	-8.37	40.48	74.00	-33.52	peak
5	2410.000	47.56	-7.03	40.53	74.00	-33.47	peak
6	2670.000	51.96	-7.24	44.72	74.00	-29.28	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The Band Reject filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)**


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1060.000	60.40	-12.81	47.59	74.00	-26.41	peak
2	1332.000	49.53	-11.43	38.10	74.00	-35.90	peak
3	2002.000	52.95	-9.76	43.19	74.00	-30.81	peak
4	2124.000	51.57	-8.35	43.22	74.00	-30.78	peak
5	2414.000	51.01	-7.00	44.01	74.00	-29.99	peak
6	2664.000	57.13	-7.20	49.93	74.00	-24.07	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The Band Reject filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)**


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1060.000	63.76	-12.81	50.95	74.00	-23.05	peak
2	1202.000	62.92	-12.42	50.50	74.00	-23.50	peak
3	2008.000	60.30	-9.66	50.64	74.00	-23.36	peak
4	2134.000	57.54	-8.36	49.18	74.00	-24.82	peak
5	2434.000	53.64	-6.84	46.80	74.00	-27.20	peak
6	2680.000	57.42	-7.29	50.13	74.00	-23.87	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The Band Reject filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1062.000	60.20	-12.80	47.40	74.00	-26.60	peak
2	2004.000	52.80	-9.72	43.08	74.00	-30.92	peak
3	2126.000	52.55	-8.35	44.20	74.00	-29.80	peak
4	2434.000	51.55	-6.84	44.71	74.00	-29.29	peak
5	2548.000	52.44	-6.56	45.88	74.00	-28.12	peak
6	2672.000	57.25	-7.25	50.00	74.00	-24.00	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The Band Reject filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1062.000	64.45	-12.80	51.65	74.00	-22.35	peak
2	1202.000	56.85	-12.42	44.43	74.00	-29.57	peak
3	2008.000	61.20	-9.66	51.54	74.00	-22.46	peak
4	2140.000	57.27	-8.37	48.90	74.00	-25.10	peak
5	2466.000	55.59	-6.60	48.99	74.00	-25.01	peak
6	2680.000	56.44	-7.29	49.15	74.00	-24.85	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The Band Reject filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1060.000	61.32	-12.81	48.51	74.00	-25.49	peak
2	1202.000	54.76	-12.42	42.34	74.00	-31.66	peak
3	2010.000	59.42	-9.63	49.79	74.00	-24.21	peak
4	2142.000	53.83	-8.37	45.46	74.00	-28.54	peak
5	2550.000	52.85	-6.57	46.28	74.00	-27.72	peak
6	2658.000	58.26	-7.16	51.10	74.00	-22.90	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The Band Reject filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.




9.5.2. 802.11g MODE

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1200.000	56.22	-12.44	43.78	74.00	-30.22	peak
2	1560.000	51.74	-11.01	40.73	74.00	-33.27	peak
3	1998.000	52.84	-9.77	43.07	74.00	-30.93	peak
4	2140.000	49.21	-8.37	40.84	74.00	-33.16	peak
5	2420.000	47.55	-6.95	40.60	74.00	-33.40	peak
6	2672.000	56.30	-7.25	49.05	74.00	-24.95	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The Band Reject filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)**


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1064.000	59.94	-12.78	47.16	74.00	-26.84	peak
2	1500.000	51.82	-11.60	40.22	74.00	-33.78	peak
3	2010.000	56.28	-9.63	46.65	74.00	-27.35	peak
4	2124.000	53.14	-8.35	44.79	74.00	-29.21	peak
5	2372.000	48.27	-7.22	41.05	74.00	-32.95	peak
6	2546.000	53.17	-6.54	46.63	74.00	-27.37	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The Band Reject filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)**


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1200.000	55.76	-12.44	43.32	74.00	-30.68	peak
2	1560.000	52.14	-11.01	41.13	74.00	-32.87	peak
3	1800.000	49.80	-9.42	40.38	74.00	-33.62	peak
4	2002.000	53.24	-9.76	43.48	74.00	-30.52	peak
5	2430.000	50.80	-6.88	43.92	74.00	-30.08	peak
6	2668.000	56.57	-7.22	49.35	74.00	-24.65	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The Band Reject filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)**


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1064.000	59.96	-12.78	47.18	74.00	-26.82	peak
2	1202.000	54.62	-12.42	42.20	74.00	-31.80	peak
3	2010.000	56.53	-9.63	46.90	74.00	-27.10	peak
4	2128.000	52.94	-8.36	44.58	74.00	-29.42	peak
5	2322.000	47.42	-7.40	40.02	74.00	-33.98	peak
6	2552.000	53.12	-6.58	46.54	74.00	-27.46	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The Band Reject filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1200.000	54.66	-12.44	42.22	74.00	-31.78	peak
2	2000.000	52.30	-9.78	42.52	74.00	-31.48	peak
3	2040.000	52.50	-9.20	43.30	74.00	-30.70	peak
4	2144.000	48.89	-8.37	40.52	74.00	-33.48	peak
5	2456.000	48.35	-6.68	41.67	74.00	-32.33	peak
6	2678.000	56.38	-7.28	49.10	74.00	-24.90	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The Band Reject filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)**


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1062.000	59.62	-12.80	46.82	74.00	-27.18	peak
2	1334.000	49.65	-11.45	38.20	74.00	-35.80	peak
3	2010.000	56.86	-9.63	47.23	74.00	-26.77	peak
4	2124.000	52.50	-8.35	44.15	74.00	-29.85	peak
5	2328.000	47.97	-7.38	40.59	74.00	-33.41	peak
6	2554.000	53.38	-6.60	46.78	74.00	-27.22	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The Band Reject filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.




9.5.3. 802.11n HT20 MODE

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1200.000	55.48	-12.44	43.04	74.00	-30.96	peak
2	1560.000	50.54	-11.01	39.53	74.00	-34.47	peak
3	1800.000	48.34	-9.42	38.92	74.00	-35.08	peak
4	1992.000	53.28	-9.74	43.54	74.00	-30.46	peak
5	2420.000	50.93	-6.95	43.98	74.00	-30.02	peak
6	2672.000	55.89	-7.25	48.64	74.00	-25.36	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The Band Reject filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)**


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1060.000	62.04	-12.81	49.23	74.00	-24.77	peak
2	2008.000	59.46	-9.66	49.80	74.00	-24.20	peak
3	2126.000	54.96	-8.35	46.61	74.00	-27.39	peak
4	2292.000	52.42	-7.57	44.85	74.00	-29.15	peak
5	2550.000	54.15	-6.57	47.58	74.00	-26.42	peak
6	2654.000	58.52	-7.14	51.38	74.00	-22.62	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The Band Reject filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1104.000	55.27	-12.59	42.68	74.00	-31.32	peak
2	1560.000	54.54	-11.01	43.53	74.00	-30.47	peak
3	1800.000	55.47	-9.42	46.05	74.00	-27.95	peak
4	1992.000	54.68	-9.74	44.94	74.00	-29.06	peak
5	2430.000	50.71	-6.88	43.83	74.00	-30.17	peak
6	2674.000	52.30	-7.26	45.04	74.00	-28.96	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The Band Reject filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1062.000	61.09	-12.80	48.29	74.00	-25.71	peak
2	2004.000	53.15	-9.72	43.43	74.00	-30.57	peak
3	2126.000	52.96	-8.35	44.61	74.00	-29.39	peak
4	2286.000	51.38	-7.63	43.75	74.00	-30.25	peak
5	2550.000	52.17	-6.57	45.60	74.00	-28.40	peak
6	2668.000	57.32	-7.22	50.10	74.00	-23.90	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The Band Reject filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.




HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1060.000	63.32	-12.81	50.51	74.00	-23.49	peak
2	1200.000	60.73	-12.44	48.29	74.00	-25.71	peak
3	2010.000	60.77	-9.63	51.14	74.00	-22.86	peak
4	2124.000	57.66	-8.35	49.31	74.00	-24.69	peak
5	2296.000	53.83	-7.53	46.30	74.00	-27.70	peak
6	2682.000	59.32	-7.30	52.02	74.00	-21.98	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The Band Reject filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)**


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1062.000	60.71	-12.80	47.91	74.00	-26.09	peak
2	2004.000	53.61	-9.72	43.89	74.00	-30.11	peak
3	2124.000	51.44	-8.35	43.09	74.00	-30.91	peak
4	2336.000	50.67	-7.35	43.32	74.00	-30.68	peak
5	2550.000	53.13	-6.57	46.56	74.00	-27.44	peak
6	2662.000	56.94	-7.19	49.75	74.00	-24.25	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The Band Reject filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.




9.5.5. 802.11n HT40 MODE

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1108.000	55.45	-12.59	42.86	74.00	-31.14	peak
2	1560.000	55.09	-11.01	44.08	74.00	-29.92	peak
3	1800.000	55.95	-9.42	46.53	74.00	-27.47	peak
4	1996.000	54.05	-9.77	44.28	74.00	-29.72	peak
5	2428.000	48.71	-6.89	41.82	74.00	-32.18	peak
6	2678.000	53.02	-7.28	45.74	74.00	-28.26	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The Band Reject filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)**


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1062.000	61.05	-12.80	48.25	74.00	-25.75	peak
2	1200.000	58.16	-12.44	45.72	74.00	-28.28	peak
3	2004.000	55.33	-9.72	45.61	74.00	-28.39	peak
4	2290.000	53.21	-7.59	45.62	74.00	-28.38	peak
5	2550.000	53.06	-6.57	46.49	74.00	-27.51	peak
6	2668.000	57.29	-7.22	50.07	74.00	-23.93	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The Band Reject filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)**


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1064.000	55.17	-12.78	42.39	74.00	-31.61	peak
2	1560.000	55.10	-11.01	44.09	74.00	-29.91	peak
3	1800.000	55.87	-9.42	46.45	74.00	-27.55	peak
4	2000.000	53.70	-9.78	43.92	74.00	-30.08	peak
5	2520.000	49.56	-6.43	43.13	74.00	-30.87	peak
6	2674.000	52.90	-7.26	45.64	74.00	-28.36	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The Band Reject filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)**


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1062.000	60.85	-12.80	48.05	74.00	-25.95	peak
2	1202.000	54.37	-12.42	41.95	74.00	-32.05	peak
3	2006.000	54.44	-9.70	44.74	74.00	-29.26	peak
4	2292.000	51.18	-7.57	43.61	74.00	-30.39	peak
5	2554.000	54.15	-6.60	47.55	74.00	-26.45	peak
6	2666.000	57.05	-7.20	49.85	74.00	-24.15	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The Band Reject filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1106.000	57.30	-12.59	44.71	74.00	-29.29	peak
2	1560.000	54.35	-11.01	43.34	74.00	-30.66	peak
3	1800.000	55.45	-9.42	46.03	74.00	-27.97	peak
4	1996.000	53.54	-9.77	43.77	74.00	-30.23	peak
5	2520.000	49.39	-6.43	42.96	74.00	-31.04	peak
6	2678.000	52.30	-7.28	45.02	74.00	-28.98	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The Band Reject filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1060.000	61.08	-12.81	48.27	74.00	-25.73	peak
2	1198.000	55.64	-12.44	43.20	74.00	-30.80	peak
3	2004.000	54.12	-9.72	44.40	74.00	-29.60	peak
4	2290.000	51.68	-7.59	44.09	74.00	-29.91	peak
5	2550.000	53.46	-6.57	46.89	74.00	-27.11	peak
6	2664.000	56.02	-7.20	48.82	74.00	-25.18	peak


- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The Band Reject filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

Note: All antennas have been tested, only the worst data record in the report.



PURIOUS EMISSIONS (18~26GHz) FOR ANTENNA 2

9.5.6. 802.11b MODE


SPURIOUS EMISSIONS (MID CHANNEL, WORST-CASE CONFIGURATION, HORIZONTAL)

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18544.000	50.76	-4.46	46.30	74.00	-27.70	peak
2	21024.000	51.12	-5.30	45.82	74.00	-28.18	peak
3	22528.000	51.66	-5.79	45.87	74.00	-28.13	peak
4	23400.000	51.92	-4.96	46.96	74.00	-27.04	peak
5	24424.000	50.04	-2.90	47.14	74.00	-26.86	peak
6	25784.000	49.73	-1.49	48.24	74.00	-25.76	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

**SPURIOUS EMISSIONS (MID CHANNEL, WORST-CASE CONFIGURATION, VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18464.000	50.70	-4.39	46.31	74.00	-27.69	peak
2	20192.000	49.87	-4.76	45.11	74.00	-28.89	peak
3	21848.000	52.26	-5.95	46.31	74.00	-27.69	peak
4	24120.000	50.78	-3.81	46.97	74.00	-27.03	peak
5	24688.000	50.39	-2.11	48.28	74.00	-25.72	peak


Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.

Note: All test mode and antennas have been tested, only the worst data record in the report.

9.6. SPURIOUS EMISSIONS (0.03 ~ 1 GHz) FOR ANTENNA 2

9.6.1. 802.11b MODE

SPURIOUS EMISSIONS (MID CHANNEL, WORST-CASE CONFIGURATION, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	216.2400	46.58	-16.31	30.27	46.00	-15.73	QP
2	263.7700	50.35	-15.18	35.17	46.00	-10.83	QP
3	312.2700	47.76	-13.39	34.37	46.00	-11.63	QP
4	408.3000	43.83	-11.83	32.00	46.00	-14.00	QP
5	455.8300	41.38	-11.06	30.32	46.00	-15.68	QP
6	792.4200	35.95	-5.11	30.84	46.00	-15.16	QP

Note: 1. Result Level = Read Level + Correct Factor.

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

**SPURIOUS EMISSIONS (MID CHANNEL, WORST-CASE CONFIGURATION, VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	273.4700	51.17	-14.80	36.37	46.00	-9.63	QP
2	504.3300	42.42	-10.06	32.36	46.00	-13.64	QP
3	551.8600	41.75	-9.06	32.69	46.00	-13.31	QP
4	644.9800	39.54	-7.28	32.26	46.00	-13.74	QP
5	743.9200	37.36	-5.73	31.63	46.00	-14.37	QP
6	792.4200	37.12	-5.11	32.01	46.00	-13.99	QP

Note: 1. Result Level = Read Level + Correct Factor.

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto


Note: All test mode and antennas have been tested, only the worst data record in the report.



9.7. SPURIOUS EMISSIONS BELOW 30M FOR ANTENNA 2

9.7.1. 802.11b MODE

SPURIOUS EMISSIONS (MID CHANNEL, WORST-CASE CONFIGURATION, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.0114	69.95	-101.40	-31.45	46.76	-78.21	peak
2	0.0193	65.65	-101.35	-35.70	42.00	-77.70	peak
3	0.0300	63.18	-101.39	-38.21	38.06	-76.27	peak
4	0.0478	58.50	-101.47	-42.97	34.05	-77.02	peak
5	0.0719	56.34	-101.58	-45.24	30.48	-75.72	peak
6	0.1073	54.30	-101.77	-47.47	27.00	-74.47	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.



150kHz ~ 490kHz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.1565	67.53	-101.65	-34.12	23.72	-57.84	peak
2	0.2051	63.81	-101.73	-37.92	21.40	-59.32	peak
3	0.3019	59.93	-101.85	-41.92	18.01	-59.93	peak
4	0.3286	59.21	-101.88	-42.67	17.34	-60.01	peak
5	0.3662	58.58	-101.93	-43.35	16.40	-59.75	peak
6	0.4823	56.69	-102.04	-45.35	13.95	-59.30	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.



490kHz ~ 30MHz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.6195	59.08	-62.09	-3.01	31.78	-34.79	peak
2	0.9425	53.89	-62.23	-8.34	28.13	-36.47	peak
3	1.9522	52.61	-61.84	-9.23	29.54	-38.77	peak
4	4.9165	50.88	-61.48	-10.60	29.54	-40.14	peak
5	9.6082	49.97	-60.86	-10.89	29.54	-40.43	peak
6	19.7895	51.42	-60.84	-9.42	29.54	-38.96	peak


Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.



SPURIOUS EMISSIONS (MID CHANNEL, WORST-CASE CONFIGURATION, HORIZONTAL)

0.09~ 150kHz




No.	Frequency (KHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.0103	73.18	-101.40	-28.22	47.42	-75.64	peak
2	0.0177	67.35	-101.35	-34.00	42.96	-76.96	peak
3	0.0290	61.86	-101.38	-39.52	38.41	-77.93	peak
4	0.0393	59.61	-101.43	-41.82	35.73	-77.55	peak
5	0.0529	57.18	-101.49	-44.31	33.16	-77.47	peak
6	0.0626	56.59	-101.53	-44.94	31.69	-76.63	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.




150kHz ~ 490kHz



No.	Frequency (KHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.1556	67.02	-101.65	-34.63	23.77	-58.40	peak
2	0.1958	65.48	-101.71	-36.23	21.77	-58.00	peak
3	0.2308	63.75	-101.77	-38.02	20.50	-58.52	peak
4	0.2555	63.09	-101.80	-38.71	19.63	-58.34	peak
5	0.3004	61.51	-101.85	-40.34	18.05	-58.39	peak
6	0.3557	59.65	-101.91	-42.26	16.67	-58.93	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.

490kHz ~ 30MHz

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.5725	58.53	-62.07	-3.54	32.48	-36.02	peak
2	1.6704	55.72	-61.97	-6.25	23.15	-29.40	peak
3	2.6583	49.38	-61.66	-12.28	29.54	-41.82	peak
4	5.0345	50.06	-61.49	-11.43	29.54	-40.97	peak
5	16.7790	51.81	-60.95	-9.14	29.54	-38.68	peak
6	24.3045	49.25	-60.51	-11.26	29.54	-40.80	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.

Note: All test mode and antennas have been tested, only the worst data record in the report.


10. AC POWER LINE CONDUCTED EMISSIONS FOR ANTENNA 2

LIMITS

Please refer to CFR 47 FCC §15.207 (a) and ISED RSS-Gen Clause 8.8

FREQUENCY (MHz)	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

TEST SETUP AND PROCEDURE




The EUT is put on a table of non-conducting material that is 80cm high. The vertical conducting wall of shielding is located 40cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI Measurement Receiver (R&S Test Receiver ESR3) is used to test the emissions from both sides of AC line. According to the requirements in Section 7 and 13 of ANSI C63.10-2013. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-Peak and average detector mode. The bandwidth of EMI test receiver is set at 9kHz.

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application.

TEST ENVIRONMENT

Temperature	22.5°C	Relative Humidity	53%
Atmosphere Pressure	101kPa	Test Voltage	DC 5V

**TEST RESULTS****10.1. 802.11b MODE****LINE N RESULTS (MID CHANNEL, WORST-CASE CONFIGURATION)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.2077	22.04	9.60	31.64	63.30	-31.66	QP
2	0.2077	6.41	9.60	16.01	53.30	-37.29	AVG
3	0.3136	20.33	9.60	29.93	59.87	-29.94	QP
4	0.3136	6.45	9.60	16.05	49.87	-33.82	AVG
5	0.4432	23.66	9.60	33.26	57.00	-23.74	QP
6	0.4432	10.10	9.60	19.70	47.00	-27.30	AVG
7	2.1554	4.12	9.63	13.75	56.00	-42.25	QP
8	2.1554	-0.05	9.63	9.58	46.00	-36.42	AVG
9	3.7242	3.75	9.66	13.41	56.00	-42.59	QP
10	3.7242	-3.73	9.66	5.93	46.00	-40.07	AVG
11	9.0563	0.55	9.75	10.30	60.00	-49.70	QP
12	9.0563	-3.45	9.75	6.30	50.00	-43.70	AVG

Note: 1. Result = Reading +Correct Factor.


2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).

4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.



LINE L RESULTS (HIGH CHANNEL, WORST-CASE CONFIGURATION)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1818	24.08	9.61	33.69	64.40	-30.71	QP
2	0.1818	7.76	9.61	17.37	54.40	-37.03	AVG
3	0.2081	21.20	9.60	30.80	63.28	-32.48	QP
4	0.2081	6.13	9.60	15.73	53.28	-37.55	AVG
5	0.3642	19.03	9.60	28.63	58.63	-30.00	QP
6	0.3642	4.96	9.60	14.56	48.63	-34.07	AVG
7	0.4439	23.52	9.60	33.12	56.99	-23.87	QP
8	0.4439	9.75	9.60	19.35	46.99	-27.64	AVG
9	0.6670	10.17	9.60	19.77	56.00	-36.23	QP
10	0.6670	0.48	9.60	10.08	46.00	-35.92	AVG
11	3.9743	2.68	9.66	12.34	56.00	-43.66	QP
12	3.9743	-3.68	9.66	5.98	46.00	-40.02	AVG

- Note: 1. Result = Reading +Correct Factor.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).
4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

Note: All test mode has been tested, only the worst data record in the report.



11. ANTENNA REQUIREMENTS

APPLICABLE REQUIREMENTS

Please refer to FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Please refer to FCC §15.247(b)(4)

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

RESULTS

Complies

END OF REPORT