



RF EXPOSURE REPORT

Applicant	:	Guangzhou Shikun Electronics Co., Ltd
Address of Applicant	:	NO.6 Liankun Road, Huangpu District, Guangzhou510530, China
Manufacturer	:	Guangzhou Shikun Electronics Co., Ltd
Address of Manufacturer	:	NO.6 Liankun Road, Huangpu District, Guangzhou510530, China
Equipment under Test	:	IEEE 802.11a/b/g/n/ac 2T2R USB Wi-Fi Module Integrated Bluetooth 2.1+EDR/4.2/5.1
Model No.	:	SKI.WB663U.2
FCC ID	:	2AR82-SKIWB663U21
Test Standard(s)	:	KDB447498 D01 General RF Exposure Guidance v06
Report No.	:	DDT-RE26041329-1E05
Issue Date	:	2026/04/30
Issue By	:	Guangdong Dongdian Testing Service Co., Ltd. Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808

Table of Contents

1. General Test Information.....5

1.1. Description of EUT 5

1.2. Accessories of EUT 5

1.3. Test laboratory 5

2. RF Exposure evaluation for FCC 6

2.1. Assessment procedure.....6

2.2. Assess result.....7

Test Report Declare

Applicant	:	Guangzhou Shikun Electronics Co., Ltd
Address of Applicant	:	NO.6 Liankun Road, Huangpu District, Guangzhou510530, China
Equipment under Test	:	IEEE 802.11a/b/g/n/ac 2T2R USB Wi-Fi Module Integrated Bluetooth 2.1+EDR/4.2/5.1
Model No.	:	SKI.WB663U.2
Manufacturer	:	Guangzhou Shikun Electronics Co., Ltd
Address of Manufacturer	:	NO.6 Liankun Road, Huangpu District, Guangzhou510530, China

Test Standard Used:
KDB447498 D01 General RF Exposure Guidance v06

We Declare:
The equipment described above is tested by Guangdong Dongdian Testing Service Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Guangdong Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

Report No.:	DDT-RE26041329-1E05		
Date of Receipt:	2026/04/14	Date of Test:	2026/04/14~2026/04/29

Created: Tiger Mo	Reviewed: Johnson Huang	Approved: Ella Gong
		
2026/04/29	2026/04/30	2026/04/30

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Guangdong Dongdian Testing Service Co., Ltd.

Revision History

Version	Revision Content	Issue Date	Approved
V0	Initial issue	2026/04/30	Ella Gong

1. General Test Information

1.1. Description of EUT

EUT Name	:	IEEE 802.11a/b/g/n/ac 2T2R USB Wi-Fi Module Integrated Bluetooth 2.1+EDR/4.2/5.1
Model Number	:	SKI.WB663U.2
Difference of model number	:	/
EUT Function Description	:	Please reference user manual of this device
Power Supply	:	DC 3.3V

Note: The above EUT information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications or User's Manual.

1.2. Accessories of EUT

Accessories	Manufacturer	Model number	Description
/	/	/	/

1.3. Test laboratory

Guangdong Dongdian Testing Service Co., Ltd.

Add.: Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808.

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: ddt@dgddt.com.

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, R-20240, G-20118

2. RF Exposure evaluation for FCC

2.1. Assessment procedure

Requirement:

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100000			1.0	30
Note: f= frequency in MHz; *Plane-wave equivalent power density				

Calculation method

$$E(\text{V/m}) = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } S(\text{mW/cm}^2) = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Peak RF output power (mW)

G = EUT Antenna numeric gain (numeric)=

d = Separation distance between radiator and human body (m)

The formula can be changed to

We can change the formula to:

$$S = \frac{30 \times P \times G}{377 \times d^2} \quad \text{or, } d = \sqrt{\frac{30 \times P \times G}{377 \times S}}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2 m, as well as the gain of the used antenna, the RF power density can be obtained.

2.2. Assess result

Mode	Antenna	Output power (dBm)	Tune up power (dBm)	Antenna Gain (dBi)	Antenna Gain (linear)	MPE Values (mW/cm ²)	MPE Limit (mW/cm ²)	Sum of the MPE
BT	1	6.65	7	2.96	1.98	0.0020	1	N/A
BLE	1	5.14	6	2.96	1.98	0.0016	1	N/A
2.4G WiFi (N20MIMO 2412MHz)	1	9.92	10	5.97	3.95	0.0079	1	0.0178
	2	10.47	11	5.97	3.95	0.0099	1	
5G WiFi (AC80MIMO 5610MHz)	1	10.43	11	5.96	3.94	0.0099	1	0.0198
	2	10.83	11	5.96	3.94	0.0099	1	

Note: The estimation distance is 20 cm.

For multiband simultaneous transmissions: =BT+5G WIFI=0.0020+0.0198=0.0218<1

Conclusion: MPE evaluation required since transmitter power is below FCC threshold

-----End Report-----