



RADIO TEST REPORT

Applicant	:	Guangzhou Shikun Electronics Co., Ltd
Address of Applicant	:	NO.6 Liankun Road, Huangpu District, Guangzhou510530, China
Manufacturer	:	Guangzhou Shikun Electronics Co., Ltd
Address of Manufacturer	:	NO.6 Liankun Road, Huangpu District, Guangzhou510530, China
Equipment under Test	:	IEEE 802.11a/b/g/n/ac 2T2R USB Wi-Fi Module Integrated Bluetooth 2.1+EDR/4.2/5.1
Model No.	:	SKI.WB663U.2
FCC ID	:	2AR82-SKIWB663U21
Test Standard(s)	:	FCC Rules and Regulations Part 15 Subpart C, ANSI C63.10-2020+Cor.1-2023
Report No.	:	DDT-RE26041329-1E01
Issue Date	:	2026/04/29
Issue By	:	Guangdong Dongdian Testing Service Co., Ltd. Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808

Table of Contents

1.	Summary of Test Results	6
2.	General Test Information.....	7
2.1.	Description of EUT	7
2.2.	Accessories of EUT	8
2.3.	Block diagram of EUT configuration for test.....	8
2.4.	Decision of final test mode	8
2.5.	Deviations of test standard	9
2.6.	Test environment conditions	9
2.7.	Test laboratory	9
2.8.	Measurement uncertainty	10
3.	Equipment Used During Conductive Test	11
4.	Maximum Peak Output Power.....	12
4.1.	Block diagram of test setup	12
4.2.	Limits	12
4.3.	Test procedure	12
4.4.	Test result.....	13
5.	Antenna Requirements.....	14
5.1.	Limit.....	14
5.2.	Result	14
6.	Radiated Emission	15
6.1.	Test equipment.....	15
6.2.	Block diagram of test setup	16
6.3.	Limits	17
6.4.	Assistant equipment used for test	18
6.5.	Test procedure	18
6.6.	Test result.....	20
6.7.	Test data	21
7.	Band Edge Compliance.....	29
7.1.	Test equipment.....	29
7.2.	Block diagram of test setup	29
7.3.	Limits	29
7.4.	Assistant equipment used for test	29
7.5.	Test procedure	30
7.6.	Test result.....	30
7.7.	Test data	31
8.	Test Setup Photograph	43

9.	Photos of the EUT	45
----	-------------------------	----

Test Report Declare

Applicant	:	Guangzhou Shikun Electronics Co., Ltd
Address of Applicant	:	NO.6 Liankun Road, Huangpu District, Guangzhou510530, China
Equipment under Test	:	IEEE 802.11a/b/g/n/ac 2T2R USB Wi-Fi Module Integrated Bluetooth 2.1+EDR/4.2/5.1
Model No.	:	SKI.WB663U.2
Manufacturer	:	Guangzhou Shikun Electronics Co., Ltd
Address of Manufacturer	:	NO.6 Liankun Road, Huangpu District, Guangzhou510530, China

Test Standard Used:
FCC Rules and Regulations Part 15 Subpart C,
ANSI C63.10-2020+Cor.1-2023

We Declare:
The equipment described above is tested by Guangdong Dongdian Testing Service Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Guangdong Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

Report No.:	DDT-RE26041329-1E01		
Date of Receipt:	2026/04/14	Date of Test:	2026/04/14 -2026/04/25

Created: Tiger Mo	Reviewed: Johnson Huang	Approved: Ella Gong
		
2026/04/25	2026/04/29	2026/04/29

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Guangdong Dongdian Testing Service Co., Ltd.

Revision History

Version	Revision Content	Issue Date	Approved
V0	Initial issue	2026/04/29	Ella Gong

1. Summary of Test Results

No.	Test Parameter	Clause No.	Condition	Result
1	Maximum Peak Output Power	47 CFR Part 15 15.247(b)(1)	/	Refer
2	20 dB Bandwidth	47 CFR Part 15 15.247(a)(1)	/	Refer
3	Carrier Frequency Separation	47 CFR Part 15 15.247(a)(1)	/	Refer
4	Number of Hopping Channel	47 CFR Part 15 15.247(a)(1)(iii)	/	Refer
5	Dwell Time	47 CFR Part 15 15.247(a)(1)(iii)	/	Refer
6	RF Conducted Spurious Emissions	47 CFR Part 15 15.247(d)	/	Refer
7	Radiated Emission	47 CFR Part 15 15.205, 47 CFR Part 15 15.209, 47 CFR Part 15 15.247(d)	/	Pass
8	Band Edge Compliance	47 CFR Part 15 15.205, 47 CFR Part 15 15.209, 47 CFR Part 15 15.247(d)	/	Pass
9	Power Line Conducted Emissions	47 CFR Part 15 15.207(a)	/	Refer
10	Antenna Requirement	47 CFR Part 15 15.203	/	Pass
11	Carrier Frequency Separation	47 CFR Part 15 15.247(a)(1)	/	Refer

Note1: N/A is an abbreviation for Not Applicable, and means this item is not applicable for this device or no need to test according to standard.

Note 2: For the Result marked the "Refer" means the test item refer to original report, report number is 4790010773.1-2 from UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

Note 3: This report add three new antennas to the original report. Verified RF output power, Supplements Radiated Emission and Band Edge Compliance tests on the basis of the original certification to verify that the product meets the standards requirements. Please refer to the original report for other test data.

2. General Test Information

2.1. Description of EUT

EUT Name	: IEEE 802.11a/b/g/n/ac 2T2R USB Wi-Fi Module Integrated Bluetooth 2.1+EDR/4.2/5.1
Model Number	: SKI.WB663U.2
Difference of model number	: /
EUT Function Description	: Please reference user manual of this device
Power Supply	: DC 3.3V
Antenna Type	: Steel Sheet Antenna
Max Antenna Gain(dBi)	: 2.96

Operation Frequency	New Antenna (6150-020011), Gain	New Antenna (6150-350001), Gain	New Antenna (6150-010011), Gain
Bluetooth: 2402-2480MHz	Steel sheet antenna, 1.76 dBi	Steel sheet antenna, 2.44 dBi	Steel sheet antenna, 2.96 dBi
802.11b/g/n: 2412-2462MHz	Steel sheet Antenna, 1.76dBi	Steel sheet antenna, 2.44 dBi	Steel sheet antenna, 2.96 dBi
802.11a/n/ac: 5180-5825MHz	Steel sheet Antenna, 2.86dBi	Steel sheet Antenna, 2.60 dBi	Steel sheet Antenna, 2.95dBi

Note: The Radiated test used the (6150-010011) antenna with the maximum gain.

Radio Specification	: Bluetooth BR/EDR
Operation Frequency	: 2402 MHz to 2480 MHz
Modulation	: GFSK, $\pi/4$ -DQPSK, 8DPSK

Bluetooth BR/EDR Channel information					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	27	2429	54	2456
1	2403	28	2430	55	2457
2	2404	29	2431	56	2458
3	2405	30	2432	57	2459
4	2406	31	2433	58	2460
5	2407	32	2434	59	2461
6	2408	33	2435	60	2462
7	2409	34	2436	61	2463
8	2410	35	2437	62	2464
9	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	39	2441	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470

15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	78	2480
25	2427	52	2454	/	
26	2428	53	2455	/	


Note: The above EUT information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications or User's Manual. The above Antenna information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

“☑” means to be chosen or applicable; “☐” means don't to be chosen or not applicable; This note applies to entire report.

2.2. Accessories of EUT

Accessories	Manufacturer	Model number	Description
/	/	/	/

2.3. Block diagram of EUT configuration for test



2.4. Decision of final test mode

According pre-test, the worst test modes were reported as below:

Test software: WCN_Combo_Tool.exe

The test software was used to control EUT work in Continuous Tx mode, and select test channel, wireless mode as below table.

The pathloss of external cable: 0.5 dB (According to the manufacturer's claims)

Tested mode, Tx Power Setting, Channel, and Frequency			
Tested mode	Tx Power Setting	Channel	Frequency (MHz)
GFSK hopping off Tx mode	5	CH0	2402
	6	CH39	2441
	6	CH78	2480
$\pi/4$ -DQPSK hopping off Tx mode	5	CH0	2402
	6	CH39	2441
	6	CH78	2480
8DPSK hopping off Tx mode	5	CH0	2402
	6	CH39	2441
	6	CH78	2480

Note: According exploratory test, EUT will have maximum output power in those data rate, worst-case data rates were: GFSK mode: DH5, $\pi/4$ -DQPSK mode: 2DH5, 8DPSK mode: 3DH5

2.5. Deviations of test standard

No deviation.

2.6. Test environment conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature range:	+15°C to +35 °C
Humidity range:	20% to 75%
Pressure range:	86 kPa to106 kPa

Note: The specific temperature and humidity information of each test item refers to the temperature and humidity record in the corresponding test data.

2.7. Test laboratory

Guangdong Dongdian Testing Service Co., Ltd.

Add.: Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808.

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: ddt@dgddt.com.

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, R-20240, G-20118

2.8. Measurement uncertainty


Test Item	Uncertainty
Bandwidth	1.9%
Peak Output Power (Conducted) (Spectrum analyzer)	0.98 dB
Peak Output Power (Conducted) (Power Sensor)	1.18 dB
Power Spectral Density (Base EIRP)	1.51 dB
Power Spectral Density (Spectrum analyzer)	0.98 dB
Frequencies Stability	1.9 kHz
Conducted spurious emissions	1.21 dB ($9\text{ kHz} \leq f < 7\text{ GHz}$);
	3.31 dB ($7\text{ GHz} \leq f < 40\text{ GHz}$)
Uncertainty for radio frequency (RBW < 20 kHz)	5.5×10^{-8}
Time	0.11%
Temperature	0.3 °C
Humidity	2 %
Uncertainty for Radiation Emission test (9 kHz – 30 MHz)	3.44 dB
Uncertainty for Radiation Emission test (30 MHz - 1 GHz)	4.28 dB (Antenna Polarize: V)
	4.14 dB (Antenna Polarize: H)
Uncertainty for Radiation Emission test (1 GHz - 40 GHz)	4.22 dB (1 - 6 GHz)
	4.52 dB (6 GHz - 18 GHz)
	4.58 dB (18 GHz - 40 GHz)
Uncertainty for Power line conduction emission test	3.32dB (150KHz-30MHz)
	3.72dB (9KHz-150KHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

3. Equipment Used During Conductive Test

Equipment	Manufacturer	Model No.	Serial Number	Due Date
☑RF Connected Test (RF Measurement System 5#)				
Signal &Spectrum analyzer	R&S	FSV40-N	102836	2027/02/27
Wideband Radio Communication Tester	R&S	CMW500	132871	2027/01/15
EXG Vector Generator	Agilent	N5172B	MY53051914	2027/01/07
MXG Vector Signal Generator	Agilent	N5173B	MY62220219	2027/03/19
RF Control Unit	Tonscend	JS0806-2	23180620727	2027/03/17
Electronic thermometer	Youshang	YSWS3020	DDT-ZC02228	2026/08/12
Test Software	Tonscend	JS1120-3	V3.6.21	N/A

4. Maximum Peak Output Power

4.1. Block diagram of test setup



4.2. Limits

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts, the e.i.r.p shall not exceed 4W.

4.3. Test procedure

- (1) The test according to ANSI C63.10 clause 7.8.5.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results.
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously.
- (4) Use the following spectrum analyzer settings for the maximum peak output power measurement:

RBW:	> 20 dB bandwidth of the emission being measured.
VBW:	VBW $\geq$ RBW.
Span:	Approximately five times the 20 dB bandwidth, centered on a hopping channel.
Detector Mode:	Peak
Sweep time:	Auto
Trace mode:	Max hold
- (5) Use the marker-to-peak function to set the marker to the peak of the emission and record the results in the report.

4.4. Test result

Test Engineer:	Tan Shaofeng	Test Site:	RF Test System 5#
Ambient Condition:	24.5℃,44.5%RH	Test Date:	2026.4.22
Test Power Supply:	DC 3.3V	Sample Number:	S26041329-001

Test Mode	Antenna	Frequency [MHz]	Conducted Peak Power[dBm]	Conducted Limit[dBm]	EIRP[dBm]	Verdict
DH5	Ant1	2402	5.02	≤20.97	7.98	PASS
		2441	6.45	≤20.97	9.41	PASS
		2480	4.85	≤20.97	7.81	PASS
3DH5	Ant1	2402	4.56	≤20.97	7.52	PASS
		2441	6.28	≤20.97	9.24	PASS
		2480	4.59	≤20.97	7.55	PASS

5. Antenna Requirements

5.1. Limit

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

5.2. Result


The antenna used for this product as Antenna information described in section 2.1 of the report, and there is no other antenna than that furnished by the responsible party shall be used with the device.


6. Radiated Emission

6.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Cal Due To
Band Reject Filter Group	Tonscend	JS0806-F	DDT-ZC05733	/
Hochgewinn-Hornantenne	SCHWARZBEC K	BBHA 9120 D	DDT-ZC05922	2027/01/06
Broadband Preamplifier	HPX	BP-01G-18G	DDT-ZC05923	2027/01/06
Pre-amplifier	COM-POWER	PAM-840A	DDT-ZC01693	2027/03/05
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	DDT-ZC00506	2027/03/04
Signal & Spectrum analyzer	R&S	FSV40-N	DDT-ZC04979	2026/07/04
SPECTRUM ANALYZER	R&S	FSU26	DDT-ZC00236	2026/07/06
High pass filter	Micro-Tronics	HPM50102	DDT-ZC00561	2027/02/27
RF cable	Zhongke Junchuang	Z805UF-NJ-NJ-10M	DDT-ZC05591	2026/10/10
RF cable	Zhongke Junchuang	Z805UF-NJ-NJ-3M	DDT-ZC05590	2026/10/10
RF cable	Zhongke Junchuang	JCTB510-NJW-NJW-0.6M	DDT-ZC04595	2026/10/10
RF cable	Zhongke Junchuang	JCT40P-2.92J-2.92J-1M	DDT-ZC03802	2026/10/10
RF cable	Yuhu Technology	ZT26S-SMAJ-SMAJ-1M	DDT-ZC02037	2026/10/10
RF cable	Zhongke Junchuang	JCT40P-2.92J-2.92J-5M	DDT-ZC03800	2026/10/10
Radiation disturbance fully automated test software	Tonscend	JS32-RE	DDT-ZC02739	/
Pre-amplifier	SONOMA	310N	DDT-ZC01969	2026/07/06
Pre-amplifier	COM-POWER	PAM-840A	DDT-ZC01693	2027/03/05
Pre-amplifier	COM-POWER	PAM-118A	DDT-ZC01293	2026/08/10
EMI TEST RECEIVER	R&S	ESU26	DDT-ZC01909	2027/02/27
Micro-Tronics filters	REBES	BRM50702	DDT-ZC03242	/
High pass filter	Micro-Tronics	HPM50108	DDT-ZC00560	2027/02/27
High Pass filter	Xi'an Xingbo	XBLBQ-GTA67	DDT-ZC02179	2027/02/27
Micro-Tronics filters	REBES	BRM50716	DDT-ZC03240	/
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	DDT-ZC00506	2027/03/04
Trilog Broadband Antenna	Schwarzbeck	VULB 9163	DDT-ZC02050	2026/07/25
Hochgewinn-Hornantenne	SCHWARZBEC K	BBHA 9120 D	DDT-ZC02129	2026/08/11
Active Loop Antenna	Schwarzbeck	FMZB1519	DDT-ZC00524	2026/08/18
PSA Series Spectrum Analyzer	Agilent	E4447A	DDT-ZC00517	2027/02/27

6.2. Block diagram of test setup





6.3. Limits

(1) FCC 15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.1772&4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.2072&4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz

²Above 38.6

(2) FCC 15.209 Limit

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		uV/m	dBuV/m
0.009 ~ 0.490	300	2400/F(kHz)	67.6-20log(F)
0.490 ~ 1.705	30	24000/F(kHz)	87.6-20log(F)
1.705 ~ 30.0	30	30	29.54
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 dBuV/m (Peak) 54.0 dBuV/m (Average)	

Note:

(1) The emission limits shown in the above table are based on measurements employing a CISPR QP detector except for the frequency bands 9 - 90 kHz, 110 - 490 kHz and above 1000 MHz, radiated emissions limits in these three bands are based on measurements employing an average detector.

(2) At frequencies below 30 MHz, measurement may be performed at a distance closer than that specified, and the limit at closer measurement distance can be extrapolated by below formula:

$$\text{Limit}_{3m}(\text{dBuV/m}) = \text{Limit}_{30m}(\text{dBuV/m}) + 40\text{Log}(30m/3m)$$

(3) Limit for this EUT

The emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20 dB below the fundamental emissions or comply with 15.209 limits.

6.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
/	/	/	/	/

6.5. Test procedure

- (1) EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber for below 1G and 150 cm above the ground plane inside a fully-anechoic chamber for above 1G.
- (2) Test antenna was located 3 m from the EUT on an adjustable mast, and the antenna used as below table.

Test frequency range	Test antenna used	Test antenna distance
9 kHz - 30 MHz	Active Loop antenna	3 m
30 MHz - 1 GHz	Trilog Broadband Antenna	3 m

1 GHz - 18 GHz	Double Ridged Horn Antenna(1 GHz-18 GHz)	3 m
18 GHz - 40 GHz	Horn Antenna(18 GHz-40 GHz)	1 m

According ANSI C63.10 clause 6.4.6 and 6.5.3, for measurements below 30 MHz, Antenna was located 3 m from EUT, the loop antenna was positioned in three antenna orientations (parallel, perpendicular, and round-parallel), for each measurement antenna alignment, the EUT shall be rotated through 0° to 360° on a turntable, and the lowest height of the magnetic antenna shall be 1 m above the ground. For measurement above 30 MHz, the trilog Broadband Antenna or Horn Antenna was located 3m from EUT, Measurements were made with the antenna positioned in both the horizontal and vertical planes of Polarization, and the measurement antenna was varied from 1 m to 4 m. in height above the reference ground plane to obtain the maximum signal strength.

(3) Below pre-scan procedure was first performed in order to find prominent frequency spectrum radiated emissions from 9 kHz to 25 GHz:

(a) Scanning the peak frequency spectrum with the antenna specified in step (3), and the EUT was rotated 360 degree, the antenna height was varied from 1 m to 4 m (Except loop antenna, it's fixed 1 m above ground.)

(b) Change work frequency or channel of device if practicable.

(c) Change modulation type of device if practicable.

(d) Change power supply range from 85% to 115% of the rated supply voltage

(e) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions.

Spectrum frequency from 9 kHz to 25 GHz (tenth harmonic of fundamental frequency) was investigated, and no any obvious emission were detected from 18 GHz to 25 GHz, so below final test was performed with frequency range from 9 kHz to 18 GHz.

(4) For final emissions measurements at each frequency of interest, the EUT was rotated and the antenna height was varied between 1 m and 4 m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipment and all of the interface cables were changed according to ANSI C63.10 on Radiated Emission test.

(5) The emissions from 9 kHz to 1 GHz were measured based on CISPR QP detector except for the frequency bands 9 - 90 kHz, 110 - 490 kHz, for emissions from 9 kHz - 90 kHz, 110 kHz - 490 kHz and above 1 GHz were measured based on average detector, for emissions above 1 GHz, peak emissions also be measured and need comply with Peak limit.

(6) The emissions from 9 kHz to 1 GHz, QP or average values were measured with EMI receiver with below RBW.

Frequency band	RBW
9 kHz - 150 kHz	200 Hz
150 kHz - 30 MHz	9 kHz
30 MHz - 1 GHz	120 kHz

- (7) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1 MHz, VBW is set at 3 MHz for Peak measure; According ANSI C63.10 clause 4.1.5.2.2 procedure for average measure.
- (8) For portable device, X axis, Y axis, Z axis are tested, and worse setup is reported.
- (9) According exploratory test, the emission levels are 20 dB below the limit detected from 9 kHz to 30 MHz and 18 GHz to 25 GHz, so the final test was performed with frequency range from 30 MHz to 18 GHz and recorded in below.
- (10) For 30 MHz ~ 25 GHz: (Scan with GFSK, $\pi/4$ -DQPSK and 8DPSK, the worst case is record and reported)
- (11) For emissions below 1 GHz, according exploratory explorer test, when change Tx mode and channel, have no distinct influence on emissions level, so for emissions below 1 GHz, the final test was only performed with EUT working in worst mode.

6.6. Test result

PASS. (See below detailed test result)

6.7. Test data

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-04-24

Tested By:

Li Xiongbín

Test Mode:

TX DH5 2441MHz Mode

Power Supply:

DC 3.3V

Condition:

Temp:25.5°C;Humi:60.2%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2026 report data\Q26041329-1E\FCC Below 1G\1

Memo:

Sample Number:S26041329-001



Final Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	30.810	36.81	10.34	3.79	18.64	40.00	21.36	QP	Horizontal
2	49.981	29.79	13.40	3.98	14.87	40.00	25.13	QP	Horizontal
3	98.948	26.21	11.39	4.29	9.59	43.50	33.91	QP	Horizontal
4	111.944	25.43	11.99	4.37	9.48	43.50	34.02	QP	Horizontal
5	867.937	27.6	21.45	7.06	24.02	46.00	21.98	QP	Horizontal
6	944.788	28.15	21.70	7.22	25.44	46.00	20.56	QP	Horizontal

Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-04-24

Tested By:

Li Xiongbín

Test Mode:

TX DH5 2441MHz Mode

Power Supply:

DC 3.3V

Condition:

Temp:25.5°C;Humi:60.2%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2026 report data\Q26041329-1E\FCC Below 1G\2

Memo:

Sample Number:S26041329-001



Final Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	30.531	33.81	10.39	3.79	15.69	40.00	24.31	QP	Vertical
2	35.974	33.2	11.88	3.86	16.64	40.00	23.36	QP	Vertical
3	62.510	33.97	12.50	4.09	18.26	40.00	21.74	QP	Vertical
4	84.388	34.26	9.09	4.22	15.27	40.00	24.73	QP	Vertical
5	90.011	33.87	9.70	4.25	15.52	43.50	27.98	QP	Vertical
6	96.009	34.08	11.19	4.28	17.25	43.50	26.25	QP	Vertical

Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result


Test Date:2026-04-20Tested By:Nan Zhong

Test Mode:TX DH5 2402MHz ModePower Supply:DC 3.3V

Condition:Temp:22.4°C;Humi:46.7%Test Site:4# Fully Anechoic Room

File Path:d:\ts\2026 report date\Q26041329-1E\FCC ABOVE 1G BT\24

Memo:Sample Number:S26041329-001 Power setting:7



Suspected Data List									
NO	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4080.000	51.88	30.87	-43.16	39.59	74.00	34.41	PK	Horizontal
2	4930.500	50.78	32.65	-42.58	40.85	74.00	33.15	PK	Horizontal
3	7713.000	49.83	36.57	-41.02	45.38	74.00	28.62	PK	Horizontal
4	8436.000	50.25	37.32	-40.63	46.94	74.00	27.06	PK	Horizontal
5	11145.000	48.33	38.89	-38.20	49.02	74.00	24.98	PK	Horizontal
6	12415.500	47.37	39.17	-37.11	49.43	74.00	24.57	PK	Horizontal

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-04-20

Tested By:

Nan Zhong

Test Mode:

TX DH5 2402MHz Mode

Power Supply:

DC 3.3V

Condition:

Temp:22.4°C;Humi:46.7%

Test Site:


4# Fully Anechoic Room

File Path:

d:\ts\2026 report date\Q26041329-1E\FCC ABOVE 1G BT\25

Memo:

Sample Number:S26041329-001 Power setting:7



Suspected Data List									
NO.	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4062.000	51.58	30.83	-43.13	39.28	74.00	34.72	PK	Vertical
2	4816.500	51.33	32.41	-42.69	41.05	74.00	32.95	PK	Vertical
3	7662.000	50.11	36.53	-41.04	45.60	74.00	28.40	PK	Vertical
4	8320.500	49.59	37.18	-40.80	45.97	74.00	28.03	PK	Vertical
5	11127.000	47.92	38.89	-38.25	48.56	74.00	25.44	PK	Vertical
6	12088.500	47.19	38.88	-36.96	49.11	74.00	24.89	PK	Vertical

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-04-20

Tested By:

Nan Zhong

Test Mode:

TX DH5 2441MHz Mode

Power Supply:

DC 3.3V

Condition:

Temp:22.4°C;Humi:46.7%

Test Site:


4# Fully Anechoic Room

File Path:

d:\ts\2026 report date\Q26041329-1E\FCC ABOVE 1G BT\26

Memo:

Sample Number:S26041329-001 Power setting:7



Suspected Data List									
NO	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3922.500	51.51	30.58	-43.61	38.48	74.00	35.52	PK	Horizontal
2	4881.000	51.41	32.55	-42.72	41.24	74.00	32.76	PK	Horizontal
3	7572.000	49.90	36.46	-41.00	45.36	74.00	28.64	PK	Horizontal
4	8409.000	49.85	37.29	-40.68	46.46	74.00	27.54	PK	Horizontal
5	11127.000	48.29	38.89	-38.25	48.93	74.00	25.07	PK	Horizontal
6	12441.000	46.34	39.20	-37.07	48.47	74.00	25.53	PK	Horizontal

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-04-20

Tested By:

Nan Zhong

Test Mode:

TX DH5 2441MHz Mode

Power Supply:

DC 3.3V

Condition:

Temp:22.4°C;Humi:46.7%

Test Site:


4# Fully Anechoic Room

File Path:

d:\ts\2026 report date\Q26041329-1E\FCC ABOVE 1G BT\27

Memo:

Sample Number:S26041329-001 Power setting:7



Suspected Data List									
NO	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3949.500	51.62	30.62	-43.42	38.82	74.00	35.18	PK	Vertical
2	4834.500	51.20	32.45	-42.70	40.95	74.00	33.05	PK	Vertical
3	7477.500	50.44	36.38	-40.80	46.02	74.00	27.98	PK	Vertical
4	8283.000	49.80	37.14	-40.82	46.12	74.00	27.88	PK	Vertical
5	11119.500	47.66	38.89	-38.27	48.28	74.00	25.72	PK	Vertical
6	12172.500	47.54	38.96	-36.97	49.53	74.00	24.47	PK	Vertical

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-04-20

Tested By:

Nan Zhong

Test Mode:

TX DH5 2480MHz Mode

Power Supply:

DC 3.3V

Condition:

Temp:22.4°C;Humi:46.7%

Test Site:


4# Fully Anechoic Room

File Path:

d:\ts\2026 report date\Q26041329-1E\FCC ABOVE 1G BT\28

Memo:

Sample Number:S26041329-001 Power setting:7



Suspected Data List									
NO	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3999.000	51.00	30.70	-43.07	38.63	74.00	35.37	PK	Horizontal
2	5011.500	51.41	32.81	-42.22	42.00	74.00	32.00	PK	Horizontal
3	7384.500	49.76	36.31	-40.97	45.10	74.00	28.90	PK	Horizontal
4	8163.000	50.39	37.00	-40.77	46.62	74.00	27.38	PK	Horizontal
5	11004.000	47.76	38.90	-38.49	48.17	74.00	25.83	PK	Horizontal
6	12214.500	47.17	38.99	-36.97	49.19	74.00	24.81	PK	Horizontal

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-04-20

Tested By:

Nan Zhong

Test Mode:

TX DH5 2480MHz Mode

Power Supply:

DC 3.3V

Condition:

Temp:22.4°C;Humi:46.7%

Test Site:


4# Fully Anechoic Room

File Path:

d:\ts\2026 report date\Q26041329-1E\FCC ABOVE 1G BT\29

Memo:

Sample Number:S26041329-001 Power setting:7



Suspected Data List									
NO	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4056.000	51.81	30.82	-43.13	39.50	74.00	34.50	PK	Vertical
2	4759.500	50.63	32.29	-42.62	40.30	74.00	33.70	PK	Vertical
3	7536.000	50.31	36.43	-40.88	45.86	74.00	28.14	PK	Vertical
4	8373.000	49.30	37.25	-40.73	45.82	74.00	28.18	PK	Vertical
5	10930.500	48.32	38.85	-38.37	48.80	74.00	25.20	PK	Vertical
6	12103.500	46.98	38.89	-36.89	48.98	74.00	25.02	PK	Vertical

Note:


1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

7. Band Edge Compliance

7.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Cal Due To
Band Reject Filter Group	Tonscend	JS0806-F	DDT-ZC05733	/
Hochgewinn-Hornantenne	SCHWARZBEC K	BBHA 9120 D	DDT-ZC05922	2027/01/06
Broadband Preamplifier	HPX	BP-01G-18G	DDT-ZC05923	2027/01/06
Pre-amplifier	COM-POWER	PAM-840A	DDT-ZC01693	2027/03/05
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	DDT-ZC00506	2027/03/04
Signal & Spectrum analyzer	R&S	FSV40-N	DDT-ZC04979	2026/07/04
SPECTRUM ANALYZER	R&S	FSU26	DDT-ZC00236	2026/07/06

7.2. Block diagram of test setup



7.3. Limits

All restriction band should comply with 15.209 limits, other emission should be at least 20 dB below the fundamental.

7.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
/	/	/	/	/

7.5. Test procedure

Same with Radiated Emission except change investigated frequency range.

Remark: All restriction band have been tested, and only the worst case is shown in report.

7.6. Test result

PASS. (See below detailed test result)

7.7. Test data

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-04-20

Tested By:

Nan Zhong

Test Mode:

TX DH5 2480MHz Mode

Power Supply:

DC 3.3V

Condition:

Temp:22.4°C;Humi:46.7%

Test Site:


4# Fully Anechoic Room

File Path:

d:\ts\2026 report date\Q26041329-1E\FCC ABOVE 1G BT\30

Memo:

Sample Number:S26041329-001 Power setting:7



Suspected Data List									
NO	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	46.52	27.70	-28.53	45.69	74.00	28.31	PK	Horizontal
2	2484.253	49.50	27.70	-28.53	48.67	74.00	25.33	PK	Horizontal

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-04-20

Tested By:

Nan Zhong

Test Mode:

TX DH5 2480MHz Mode

Power Supply:

DC 3.3V

Condition:

Temp:22.4°C;Humi:46.7%

Test Site:


4# Fully Anechoic Room

File Path:

d:\ts\2026 report date\Q26041329-1E\FCC ABOVE 1G BT\31

Memo:

Sample Number:S26041329-001 Power setting:7



Suspected Data List									
NO	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.809	46.28	27.70	-28.53	45.45	74.00	28.55	PK	Vertical
2	2487.244	46.20	27.71	-28.53	45.38	74.00	28.62	PK	Vertical

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-04-20

Tested By:

Nan Zhong

Test Mode:

TX DH5 2402MHz Mode

Power Supply:

DC 3.3V

Condition:

Temp:22.4°C;Humi:46.7%

Test Site:


4# Fully Anechoic Room

File Path:

d:\ts\2026 report date\Q26041329-1E\FCC ABOVE 1G BT\32

Memo:

Sample Number:S26041329-001 Power setting:7



Suspected Data List									
NO	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2383.690	45.59	27.41	-28.58	44.42	74.00	29.58	PK	Horizontal
2	2390.000	42.04	27.43	-28.56	40.91	74.00	33.09	PK	Horizontal

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-04-20

Tested By:

Nan Zhong

Test Mode:

TX DH5 2402MHz Mode

Power Supply:

DC 3.3V

Condition:

Temp:22.4°C;Humi:46.7%

Test Site:


4# Fully Anechoic Room

File Path:

d:\ts\2026 report date\Q26041329-1E\FCC ABOVE 1G BT\33

Memo:

Sample Number:S26041329-001 Power setting:7



Suspected Data List									
NO	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2387.300	44.04	27.42	-28.57	42.89	74.00	31.11	PK	Vertical
2	2390.000	40.91	27.43	-28.56	39.78	74.00	34.22	PK	Vertical

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-04-20

Tested By:

Nan Zhong

Test Mode:

TX 2DH5 2402MHz Mode

Power Supply:

DC 3.3V

Condition:

Temp:22.4°C;Humi:46.7%

Test Site:


4# Fully Anechoic Room

File Path:

d:\ts\2026 report date\Q26041329-1E\FCC ABOVE 1G BT\34

Memo:

Sample Number:S26041329-001 Power setting:7



Suspected Data List									
NO	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2382.410	44.69	27.41	-28.58	43.52	74.00	30.48	PK	Horizontal
2	2390.000	41.78	27.43	-28.56	40.65	74.00	33.35	PK	Horizontal

Note:

- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-04-20

Tested By:

Nan Zhong

Test Mode:

TX 2DH5 2402MHz Mode

Power Supply:

DC 3.3V

Condition:

Temp:22.4°C;Humi:46.7%

Test Site:


4# Fully Anechoic Room

File Path:

d:\ts\2026 report date\Q26041329-1E\FCC ABOVE 1G BT\35

Memo:

Sample Number:S26041329-001 Power setting:7



Suspected Data List									
NO	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2386.720	44.29	27.42	-28.57	43.14	74.00	30.86	PK	Vertical
2	2390.000	42.32	27.43	-28.56	41.19	74.00	32.81	PK	Vertical

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-04-20

Tested By:

Nan Zhong

Test Mode:

TX 2DH5 2480MHz Mode

Power Supply:

DC 3.3V

Condition:

Temp:22.4°C;Humi:46.7%

Test Site:


4# Fully Anechoic Room

File Path:

d:\ts\2026 report date\Q26041329-1E\FCC ABOVE 1G BT\36

Memo:

Sample Number:S26041329-001 Power setting:7



Suspected Data List									
NO	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	45.46	27.70	-28.53	44.63	74.00	29.37	PK	Horizontal
2	2484.112	50.31	27.70	-28.53	49.48	74.00	24.52	PK	Horizontal

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-04-20

Tested By:

Nan Zhong

Test Mode:

TX 2DH5 2480MHz Mode

Power Supply:

DC 3.3V

Condition:

Temp:22.4°C;Humi:46.7%

Test Site:


4# Fully Anechoic Room

File Path:

d:\ts\2026 report date\Q26041329-1E\FCC ABOVE 1G BT\37

Memo:

Sample Number:S26041329-001 Power setting:7



Suspected Data List									
NO	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	44.58	27.70	-28.53	43.75	74.00	30.25	PK	Vertical
2	2486.422	47.39	27.71	-28.53	46.57	74.00	27.43	PK	Vertical

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-04-20

Tested By:

Nan Zhong

Test Mode:

TX 3DH5 2480MHz Mode

Power Supply:

DC 3.3V

Condition:

Temp:22.4°C;Humi:46.7%

Test Site:


4# Fully Anechoic Room

File Path:

d:\ts\2026 report date\Q26041329-1E\FCC ABOVE 1G BT\38

Memo:

Sample Number:S26041329-001 Power setting:7



Suspected Data List									
NO	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	46.28	27.70	-28.53	45.45	74.00	28.55	PK	Horizontal
2	2485.699	49.95	27.71	-28.53	49.13	74.00	24.87	PK	Horizontal

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-04-20

Tested By:

Nan Zhong

Test Mode:

TX 3DH5 2480MHz Mode

Power Supply:

DC 3.3V

Condition:

Temp:22.4°C;Humi:46.7%

Test Site:


4# Fully Anechoic Room

File Path:

d:\ts\2026 report date\Q26041329-1E\FCC ABOVE 1G BT\39

Memo:

Sample Number:S26041329-001 Power setting:7



Suspected Data List									
NO	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	43.63	27.70	-28.53	42.80	74.00	31.20	PK	Vertical
2	2486.260	47.31	27.71	-28.53	46.49	74.00	27.51	PK	Vertical

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-04-20

Tested By:

Nan Zhong

Test Mode:

TX 3DH5 2402MHz Mode

Power Supply:

DC 3.3V

Condition:

Temp:22.4°C;Humi:46.7%

Test Site:


4# Fully Anechoic Room

File Path:

d:\ts\2026 report date\Q26041329-1E\FCC ABOVE 1G BT\40

Memo:

Sample Number:S26041329-001 Power setting:7



Suspected Data List									
NO	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2382.420	44.75	27.41	-28.58	43.58	74.00	30.42	PK	Horizontal
2	2390.000	41.38	27.43	-28.56	40.25	74.00	33.75	PK	Horizontal

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-04-20

Tested By:

Nan Zhong

Test Mode:

TX 3DH5 2402MHz Mode

Power Supply:

DC 3.3V

Condition:

Temp:22.4°C;Humi:46.7%

Test Site:


4# Fully Anechoic Room

File Path:

d:\ts\2026 report date\Q26041329-1E\FCC ABOVE 1G BT\41

Memo:

Sample Number:S26041329-001 Power setting:7



Suspected Data List									
NO	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2377.500	44.83	27.39	-28.60	43.62	74.00	30.38	PK	Vertical
2	2390.000	43.14	27.43	-28.56	42.01	74.00	31.99	PK	Vertical

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

9. Photos of the EUT

Please refer to DDT-Q26041329-1E appendix I

-----End Report-----