

APPROVAL SHEET

Supplier name: Guangzhou Vision enthalpy Technology Co., LTD

Supplier material name: Coaxial cable antenna, 2.4~2.5GHz, 1.98dBi, 5.1~5.9GHz, 3.82dBi, 32.4×11.1mm, 200mm, Gray, IPEX 1, SUS304, 1COAX,, plating Ni, 3M9495LSE Double-sided tape, Grey cable, spring antenna, SHKJ

CVTE Item number: 004.032.0053118

Admission edition: A0

Drawing version number (no drawing): A0

Supplier acknowledgement column		
lay down	examine and verify	ratify
Jack	Lucy	

Supplier Address: Room 202, Building B, No. 238 Spectral East Road, Huangpu District, Guangzhou City

telephone:

portraiture:

Note: Supplier commitment and confirmation, Suppliers to Guangzhou bin electronic technology Co., Ltd., and its affiliated companies (including but not limited to Guangzhou visual source electronic Technology Co., Ltd., Guangzhou electronic Technology Co., Ltd., Guangzhou into information technology Co., Ltd., Guangzhou, medical equipment technology Co., Ltd., Guangzhou yi intelligent electronic technology Co., Ltd., Guangzhou farce ear acoustic technology Co., Ltd., Guangzhou rui xin electronic Technology Co., Ltd., Qingdao source dynamic wisdom sports technology Co., Ltd., Guangzhou radium morning automatic control technology Co., Ltd., Guangzhou Liuhuan Information Technology Co., Ltd.) (known as "CVTE") supply of materials, Are able to meet the standards stipulated in this admission, Without the supplier. The scanned copy, photocopy and faxed copy of this admission letter shall have the same legal effect as the original copy.

Contents Directory


1.Document Revision	1
2.Product Photos.....	4
3.Product Drawings And Specifications.....	4
4.Performance Parameters.....	5
5.Packaging Standard:.....	6
6.Reliability Test Report:.....	7
7.Disabled Material Guarantee.....	8
8.Raw Material Test List:.....	9

Document revision resume form				
Edition	Date	Develop / Modify / Repeal content	Lay Down	Approval
A/0	2025-11-19	New Edition	Yue Ting	Feng Xianqiang

2. Product Photos



3. Product Drawings, Specifications




4. performance Parameter

4-1 Performance Parameters


Electrical Parameters	
Frequency Range	2.4-2.5GHz 5.15-5.85GHz
Input Impedence	50 Ω
Standing-wave Ratio	Refer to samples
Gain	/
Power Capacity	1W
Through The Test	/
Polarization Mode	/
Radiation Direction	/
Connector Model	I-PEX 1
Mechanical Parameters	
Terminal Maintenance Force	/
Antenna Material	SUS 304
Coax	1.13 Coaxial cable (Grey)
Salt Spray Test	24H
Enviromental Parameter	
Working Temperature	-30℃~65℃

4-2 Performance Test

S11



SWR




4-3 Antenna Efficiency


frequency (MHz)	gain (dBi)	efficiency (dB)	efficiency (%)
2400	-1.77	-4.63	34.41
2410	-1.19	-4.26	37.51
2420	-0.91	-4.21	37.89
2430	-0.89	-4.01	39.72
2440	-0.64	-4.03	39.53
2450	-0.26	-4.05	39.32
2460	0.13	-3.31	46.66
2470	0.57	-2.94	50.82
2480	1.04	-2.55	55.6
2490	1.36	-2.17	60.74
2500	1.4	-2.36	58.04

frequency (MHz)	gain (dBi)	efficiency (dB)	efficiency (%)
5100	3.67	-3.4	45.74
5150	3.64	-3.1	48.95
5200	3.32	-3.59	43.7
5250	3.47	-2.91	51.21
5300	3.54	-3.19	47.95
5350	3.13	-3.07	49.31
5400	2.71	-3.18	48.04
5450	2.54	-2.7	53.7
5500	2.63	-2.83	52.15
5550	2.94	-2.9	51.29
5600	3.35	-2.58	55.21
5650	3.25	-2.44	57.07
5700	3.52	-2.27	59.28
5750	3.23	-2.57	55.39
5800	3.59	-2.08	61.96
5850	3.97	-1.79	66.18
5900	4	-2.11	61.46


Phi=90 freq=2400MHz




Phi=0 freq=2400MHz




Theta=90 freq=2400MHz








Phi=90 freq=2450MHz




Phi=0 freq=2450MHz




Theta=90 freq=2450MHz




Phi=90 freq=2480MHz




Phi=0 freq=2480MHz




Theta=90 freq=2480MHz








Phi=90 freq=5100MHz




Phi=0 freq=5100MHz




Theta=90 freq=5100MHz




Phi=90 freq=5400MHz




Phi=0 freq=5400MHz




Theta=90 freq=5400MHz




MAX:2.71dBi
MIN:-22.4dBi




$\Phi=90$ freq=5900MHz




$\Phi=0$ freq=5900MHz



Theta=90 freq=5900MHz



MAX:4dBi
MIN:-20.01dBi



5. Packaging Standard


Product Material No. :004.032.0053118

2.4~2.5GHz, 1.98dBi, 5.1~5.9GHz, 3.82dBi, 32.4×11.1mm, 200mm, Gray, IPEX 1, SUS304, 1COAX, platingNi, 3M9495LSE Double-sided tape, Grey cable, spring antenna, SHKJ

li. Packaging requirements and operation instructions:


1. Internal packaging:

Product 50 PCS into the small PE bag




2. Packaging:

Quantity / box according to the actual packing



纸箱



matters need attention:

1. Whether to add a partition board, pearl cotton;
2. Attachment of labels, such as ROHS;

6. Reliability test report

6-1. Reliability test standards

test item		test method	acceptance standard	Judgment results
1	V . S . W . R	Set the network analyzer parameters for testing	According to the specifications to be tested	P ASS
2	Plug in damage	Set the network analyzer parameters for testing	According to the specifications to be tested	P ASS
3	salt atmosphere	Temperature 35° C humidity 95% saline concentration 5%; test for 24 hours	After 2H, there was no obvious bad appearance: frequency offset of 5%	P ASS
4	constant temperature and humidity	Temperature 80° C test 12H to-40° C Test 12H: Humidity 90%: Test 24 hours	After 2H, there was no obvious bad appearance: frequency offset of 5%	P ASS
5	strain relief test	Tometer test product connector and terminal tension greater than; 1 Kgf	Visual inspection / measurement meets SOP requirements, no shedding, poor contact	PASS

7. Disabled Material Guarantee

禁用物质保证(Certification of Restricted Substance)

我方保证所提供的物料，完全遵守签核的广州视源电子科技股份有限公司/或其子公司的质量和环保协议中的各项条款，物料中禁用物含量，符合最新版《有害物质管理规范》中的各项标准。

We hereby certify that all the Material fully conform to the requirements of the ShiRuan/or its affiliated companies Declaration of Conformity that had been signed, and the maximum concentration value of restricted substance in Materials comply with the latest 《Regulations on the management of hazardous substances.》

公司盖章

8. Raw Material Test List

原材料测试清单 Raw Material Test List																			
客户编码 (Customer F/N): 004.032.0053118				物料名称 (Part Name)		供应商 (Vendor)		供应商标号 (Vendor P/N)				Test Report Number (检测报告号)			Test Date (测试日期)		Remark (备注)		
No (序号)	Raw Material Name (原材料名称)	Raw Material description (原材料描述)	Raw Material Supplier (原材料供应商)	Banned Substance Content/ppm (禁止物质含量/ppm)															
				Pb (铅)	Cd (镉)	Hg (汞)	Cr+6 (六价铬)	PBBs (聚溴化苯)	PBDEs (聚溴二噁英)	邻苯二甲酸二(2-乙基己)酯 (DEHP)	邻苯二甲酸丁酯 (DBP)	邻苯二甲酸丁酯 (BBP)	邻苯二甲酸二异丁酯 (DIBP)						
1	1.13 Cable	RF cable	tian mai	N/D	N/D	N/D	N/D	N/D	N/D	N/D	N/D	N/D	N/D	N/D	CANEC25018034404	SGS	2025/7/30		
	RF Connector	C5210	FUJIAN ZIJIN	4	N/D	N/D	N/D	N/D	N/D	N/D	N/D	N/D	N/D	N/D	N/D	CANEC24029407215	SGS	2025/1/8	
		NI	tonghua	41	N/D	N/D	N/D	N/D	N/D	N/D	N/D	N/D	N/D	N/D	N/D	SZXEC25002636009	SGS	2025/7/28	
		Au	tonghua	15	N/D	N/D	N/D	N/D	N/D	N/D	N/D	N/D	N/D	N/D	N/D	SZXEC25002636001	SGS	2025/7/28	
	Antenna	SUS304	YONG JIN METAL	N/D	N/D	N/D	N/D	N/D	N/D	N/D	N/D	N/D	N/D	N/D	N/D	SHAPH25006741307	SGS	2025/4/2	
	Double-sided tape	9495LSE	3M	N/D	N/D	N/D	N/D	N/D	N/D	N/D	N/D	N/D	N/D	N/D	N/D	SHAEC24027480901	SGS	2024/12/6	
EVA	EVA Black	huan zhong bao	N/D	N/D	N/D	N/D	N/D	N/D	N/D	N/D	N/D	N/D	N/D	N/D	CANEC24028865418	SGS	2025/1/3		

上述均质材料如果属非金属，还需回答三个问题：

①是否含卤素： ☒ 含有YES ☐ 不含有NO

②是否含红磷： ☐ 含有YES ☒ 不含有NO

③是否含三氧化二锡： ☐ 含有YES ☒ 不含有NO