

RF EXPOSURE REPORT

Applicant:	Guangzhou Shikun Electronics Co., Ltd
Address:	NO.6 Liankun Road, Huangpu District, Guangzhou, China
Manufacturer:	Guangzhou Shikun Electronics Co., Ltd
Address:	NO.6 Liankun Road, Huangpu District, Guangzhou, China
Product Description:	IEEE 802.11 a/b/g/n/ac 2T2R USB Wi-Fi Module Integrated Bluetooth 2.1/3.0/4.2/5.0
Brand Name:	N/A
Tested Model:	SKO.WB822CU.15
FCC ID:	2AR82-SKOWB822CU15
Report No.:	JCF251225021-005
Received Date:	Dec. 25, 2025
Tested Date:	Dec. 25, 2025 ~ Jan. 27, 2026
Issued Date:	Jan. 27, 2026
Test Standards:	KDB 447498 D01 General RF Exposure Guidance v06
Test Result:	Pass

Prepared By:  <u>Roger Li/Engineer</u>	Date: Jan. 27, 2026
--	----------------------------

Reviewed By:  <u>Kennys Zhang/Engineer</u>	Date: Jan. 27, 2026
--	----------------------------

Approved By:  <u>Talent Zhang/Engineer</u>	 Date: Jan. 27, 2026
--	--

Note: The test results in this report apply exclusively to the tested model / sample. Without written approval of Guangzhou Jingce Testing Technology Co., Ltd. the test report shall not be reproduced except in full.

Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
--	/	Jan. 27, 2026	Original Report	/

Table of Contents

1. Test Report Declare	4
2. Equipment Under Test	5
2.1. Description of EUT	5
2.2. Description of Available Antennas	5
3. Test Laboratory	6
4. RF Exposure Measurement	7
4.1. Requirement	7
4.2. Limits for Maximum Permissible Exposure (MPE)	7
4.3. MPE Calculation Formula	7
4.4. Classification	7
4.5. Conducted Power	7
5. RF Exposure Calculation	8



1. Test Report Declare

Applicant:	Guangzhou Shikun Electronics Co., Ltd
Address:	NO.6 Liankun Road, Huangpu District, Guangzhou, China
Manufacturer:	Guangzhou Shikun Electronics Co., Ltd
Address:	NO.6 Liankun Road, Huangpu District, Guangzhou, China
Product Name	IEEE 802.11 a/b/g/n/ac 2T2R USB Wi-Fi Module Integrated Bluetooth 2.1/3.0/4.2/5.0
Brand Name:	N/A
Model Name:	SKO.WB822CU.15
Difference Description:	NA

We Declare:

The equipment described above is tested by Guangzhou Jingce Testing Technology Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Guangzhou Jingce Testing Technology Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests except as provided information by clients.

技
ING
测专
esting
CA

2. Equipment Under Test

2.1. Description of EUT

EUT* Name:	IEEE 802.11 a/b/g/n/ac 2T2R USB Wi-Fi Module Integrated Bluetooth 2.1/3.0/4.2/5.0
Model Number:	SKO.WB822CU.15
EUT Function Description:	Please refer to the user manual of this device
Power Supply:	5V+/-0.5
Hardware Version:	NA
Software Version:	NA
Radio Specification:	Bluetooth V5.0, IEEE 802.11a/b/g/n/ac
Operation Frequency:	Bluetooth: 2402MHz-2480MHz IEEE802.11b/g/n/a/ac: 2412MHz-2462MHz, 5180MHz-5825MHz
Modulation:	GFSK, $\pi/4$ -DQPSK, 8DPSK IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11a/g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT20, HT40: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ac (VHT20/40/80): OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)
Antenna Type:	Bluetooth: PCB Antenna, 1.81 dBi 2.4G WIFI: Steel sheet Antenna 1, 1.60 dBi, PCB Antenna 2, 1.68 dBi 5G WIFI: Steel sheet Antenna1, 0.9 dBi, PCB Antenna 2, 2.01 dBi
Product Type:	☐ Portable device ☒ Mobile device ☐ Fixed device

Note 1: EUT is the ab. of equipment under test.

Note 2: The antenna gain is declared by the customer and the laboratory is not responsible for the accuracy of the antenna gain.

2.2. Description of Available Antennas

Test Mode	Transmit and Receive Mode	Description
BT&BLE	☒ 1TX, 1RX	ANT 1 can be used as transmitting/receiving antenna.
2.4G WIFI	☒ 2TX, 2RX	ANT 1 and ANT2 can be used as transmitting/receiving antenna.
5G WIFI	☒ 2TX, 2RX	ANT 1 and ANT2 can be used as transmitting/receiving antenna.

3. Test Laboratory

Guangzhou Jingce Testing Technology Co., Ltd.

Add.: No.10, Hefeng No.1 street, Huangpu District, Guangzhou, Guangdong, People's Republic of China

Association for Laboratory Accreditation(A2LA). Certificate Number: 6594.03

FCC Designation Number: CN1381. Test Firm Registration Number: 486550

IC Test Firm Registration Number: 31808

Conformity Assessment Body identifier: CN0173

Guangzhou Jingce Testing Technology Co., Ltd.
Vices

4. RF Exposure Measurement

4.1. Requirement

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

4.2. Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
Limits For General Population / Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz

* = Plane-wave equivalent power density.

4.3. MPE Calculation Formula

$$P_d = (P_{out} * G) / (4 * \pi * R^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

4.4. Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as Mobile Device.

4.5. Conducted Power

Band	Channel Frequency (MHz)	Average Power (dBm)
BT&BLE	2480	8.80
2.4G WIFI	2462	16.41
5G WIFI	5500	18.77

5. RF Exposure Calculation

We used the maximum power between the conducted power and ERP/EIRP to perform RF exposure exemption evaluation.

Band	Channel Frequency (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	Power Density (mW/cm ²)	Limit (mW/cm ²)	PASS/FAIL
BT&BLE	2480	8.80	1.81	0.002	1	PASS
2.4G WIFI	2462	16.41	1.60	0.013	1	PASS
5G WIFI	5500	18.77	0.90	0.018	1	PASS

Both of the WLAN and plug-in device can transmit simultaneously, the formula of calculated the MPE is:

$$CPD1/LPD1 + CPD2/LPD2 + \dots \text{etc.} < 1$$

CPD = Calculation power density

LPD = Limit of power density

Therefore the worst-case situation is $0.002/1.00 + 0.013/1.00 + 0.018/1.00 = 0.033$, which is less than "1", This confirmed that the device comply with FCC 1.1310 MPE limit.

--END--