


FCC AND ISCED CERTIFICATION TEST REPORT

Applicant:	Guangzhou Shikun Electronics Co., Ltd
Address:	NO.6 Liankun Road, Huangpu District, Guangzhou, China
Manufacturer:	Guangzhou Shikun Electronics Co., Ltd
Address:	NO.6 Liankun Road, Huangpu District, Guangzhou, China
Product Description:	IEEE 802.11 a/b/g/n/ac 2T2R USB Wi-Fi Module Integrated Bluetooth 2.1/3.0/4.2/5.0
Brand Name:	N/A
Tested Model:	SKO.WB822CU.15
FCC ID:	2AR82-SKOWB822CU15
IC:	24728-SKOWB822CU1
Report No.:	JCF251225021-002
Received Date:	Dec. 25, 2025
Tested Date:	Dec. 25, 2025 ~ Jan. 27, 2026
Issued Date:	Jan. 27, 2026
Test Standards:	FCC Rules and Regulations Part 15 Subpart C, RSS-247 Issue 4 July 2025
Test Procedure:	ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024, 558074 D01 15.247 Meas Guidance v05r02, 662911 D01 Multiple Transmitter Output v02r01, RSS-Gen Issue 5 A2, Feb. 2021
Test Result:	Pass
Prepared By:  <u>Roger Li/Engineer</u> Date: Jan. 27, 2026	
Reviewed By:  <u>Kennys Zhang/Engineer</u> Date: Jan. 27, 2026	
Approved By:  <u>Talent Zhang/Engineer</u> Date: Jan. 27, 2026	



Note: The test results in this report apply exclusively to the tested model / sample. Without written approval of Guangzhou Jingce Testing Technology Co., Ltd. the test report shall not be reproduced except in full.

Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
--	/	Jan. 27, 2026	Original Report	/

TABLE OF CONTENTS

1. Test Report Declare	5
2. Summary of Test Results	6
3. Test Laboratory	6
4. Equipment Under Test	7
4.1. Description of EUT	7
4.2. Channel List	7
4.3. Test Channel Configuration	7
4.4. Test environment conditions	8
4.5. The Worse Case Power Setting Parameter	8
4.6. Description of Available Antennas	8
5. Description of Test Setup	8
5.1. Accessory	8
5.2. Support Equipment	8
5.3. Test Setup	8
5.4. Setup Diagram for Tests	8
6. Measurement Uncertainty	9
7. Measuring Instrument and Software Used	9
8. On Time and Duty Cycle	11
8.1. Block diagram of test setup	11
8.2. Limits	11
8.3. Procedure	11
8.4. Results	11
8.5. Original test data	11
9. 6 dB DTS Bandwidth and 99 % Bandwidth	14
9.1. Block diagram of test setup	14
9.2. Limits	14
9.3. Test Procedure	14
9.4. Results	14
9.5. Original test data	14
10. Peak Conducted Output Power	19
10.1. Block diagram of test setup	19
10.2. Limits	19
10.3. Test Procedure	19
10.4. Results	19
10.5. Original test data	20
11. Power Spectral Density	22
11.1. Block diagram of test setup	22
11.2. Limits	22
11.3. Test Procedure	22
11.4. Results	22
11.5. Original test data	23
12. Conducted Bandedge and Spurious Emissions	25
12.1. Block diagram of test setup	25
12.2. Limits	25
12.3. Test Procedure	25
12.4. Results	25
12.5. Original test data	26
13. Radiated Emission	34
13.1. Block diagram of test setup	34
13.2. Limit	35
13.3. Test Procedure	36
13.4. Results	38

13.5. Original test data 38

14. AC Power Line Conducted Emissions 39

14.1. Block diagram of test setup 39

14.2. Limits 39

14.3. Test procedure 39

14.4. Test result 40

14.5. Original test data 40

15. Antenna Requirements 41

15.1. Limits 41

15.2. Result 41

APPENDIX A – Radiated Emission Below 1GHz Test Data 42

APPENDIX B – Radiated Emission Above 1GHz Test Data 44

APPENDIX C – AC Power Line Conducted Emission Test Data 60

1. Test Report Declare

Applicant:	Guangzhou Shikun Electronics Co., Ltd
Address:	NO.6 Liankun Road, Huangpu District, Guangzhou, China
Manufacturer:	Guangzhou Shikun Electronics Co., Ltd
Address:	NO.6 Liankun Road, Huangpu District, Guangzhou, China
Product Name:	IEEE 802.11 a/b/g/n/ac 2T2R USB Wi-Fi Module Integrated Bluetooth 2.1/3.0/4.2/5.0
Brand Name:	N/A
Model Name:	SKO.WB822CU.15
Difference Description:	NA

We Declare:

The equipment described above is tested by Guangzhou Jingce Testing Technology Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Guangzhou Jingce Testing Technology Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests except as provided information by clients.

2. Summary of Test Results

Summary of Test Results			
Clause	Test Items	FCC/ISED Rules	Test Results
1	6 dB Bandwidth and 99 % Occupied Bandwidth	FCC Part 15.247 (a) (2) RSS-247 Clause 6.3.1 (a) ISED RSS-Gen Clause 6.7	Pass
2	Peak Conducted Output Power	FCC Part 15.247 (b) (3) RSS-247 Clause 6.3.2	Pass
3	Power Spectral Density	FCC Part 15.247 (e) RSS-247 Clause 6.3.1 (b)	Pass
4	Conducted Bandedge and Spurious Emission	FCC Part 15.247 (d) RSS-247 Clause 6.6	Pass
5	Radiated Bandedge and Spurious Emission	FCC Part 15.247 (d) FCC Part 15.209 FCC Part 15.205 RSS-247 Clause 6.6 RSS-GEN Clause 8.9	Pass
6	Conducted Emission Test For AC Power Port	FCC Part 15.207 RSS-GEN Clause 8.8	Pass
7	Antenna Requirement	FCC Part 15.203 RSS-GEN Clause 6.8	Pass
Note: This report was tested strictly in accordance with the standards, without any additions, deviations or omissions to the standard content.			

3. Test Laboratory

Guangzhou Jingce Testing Technology Co., Ltd.

Add.: No.10, Hefeng No.1 street, Huangpu District, Guangzhou, Guangdong, People's Republic of China

Association for Laboratory Accreditation(A2LA). Certificate Number: 6594.03

FCC Designation Number: CN1381. Test Firm Registration Number: 486550

IC Test Firm Registration Number: 31808

Conformity Assessment Body identifier: CN0173

4. Equipment Under Test

4.1. Description of EUT

EUT Name:	IEEE 802.11 a/b/g/n/ac 2T2R USB Wi-Fi Module Integrated Bluetooth 2.1/3.0/4.2/5.0
Model Number:	SKO.WB822CU.15
EUT Function Description:	Please refer to user manual of this device
Power Supply:	5V+/-0.5
Sample No.:	251225021-01-01
Hardware Version:	NA
Software Version:	NA
Radio Specification:	Bluetooth V5.0
Operation Frequency:	2402 MHz - 2480 MHz
Modulation:	GFSK
Data Rate:	1Mbps, 2Mbps,
Antenna Type:	PCB Antenna, MAX. Gain: 1.81 dBi

Note 1: EUT is the ab. of equipment under test.

Note 2: The antenna gain is declared by the customer and the laboratory is not responsible for the accuracy of the antenna gain.

4.2. Channel List

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	11	2424	22	2446	33	2468
1	2404	12	2426	23	2448	34	2470
2	2406	13	2428	24	2450	35	2472
3	2408	14	2430	25	2452	36	2474
4	2410	15	2432	26	2454	37	2476
5	2412	16	2434	27	2456	38	2478
6	2414	17	2436	28	2458	39	2480
7	2416	18	2438	29	2460	/	/
8	2418	19	2440	30	2462	/	/
9	2420	20	2442	31	2464	/	/
10	2422	21	2444	32	2468	/	/

4.3. Test Channel Configuration

Tested mode, channel, information		
Mode	Channel	Frequency (MHz)
GFSK	LCH:CH0	2402
	MCH:CH19	2440
	HCH:CH39	2480

4.4. Test environment conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature range:	21-25 °C
Humidity range:	40-75%
Pressure range:	86-106 kPa

4.5. The Worse Case Power Setting Parameter

The Worse Case Power Setting Parameter under 2400 ~ 2483.5MHz Band				
Test Software		MP Tool		
Modulation Type	Transmit Antenna Number	Test Software Setting Value		
		CH 00	CH 19	CH 39
GFSK_1M	1	Default	Default	Default
GFSK_2M	1	Default	Default	Default

4.6. Description of Available Antennas

Test Mode	Transmit and Receive Mode	Description
GFSK	☒ 1TX, 1RX	Antenna 1 can be used as transmitting/receiving antenna.

5. Description of Test Setup

5.1. Accessory

Description of Accessories	Manufacturer	Model Number	Description	Remark
N/A	N/A	N/A	N/A	N/A

5.2. Support Equipment


Equipment	Brand Name	Model Name	P/N
PC	Lenovo	T480	/
Adapter	Lenovo	ADL100YDC3A	0000000413972

5.3. Test Setup


The EUT can work in Fixed Frequency mode.

5.4. Setup Diagram for Tests


RF Connect Test:



Radiated Emission Test:



AC Power Line Conducted Emissions Test:



6. Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Uncertainty
AC Power Conduction emission	1.37 dB
All Radiated emissions	5.4dB
Conducted emissions	3.09 dB
Occupied Channel Bandwidth	1.1%
Conducted Output power	0.82dB
Power Spectral Density	0.82dB

Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95 % confidence level using a coverage factor of $k = 2$.


7. Measuring Instrument and Software Used

TS Test System						
Used	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due. Date
☒	Spectrum Analyzer	Keysight	N9030B	MY56320512	Jul. 31, 2025	Jul. 30, 2026
☒	Vector Signal Generator	Keysight	N5182B	MY57300334	Jul. 31, 2025	Jul. 30, 2026
☒	Signal Generator	Keysight	N5171B	MY57280639	Jul. 31, 2025	Jul. 30, 2026
☒	DC POWER	Keysight	E342A	MY59020356	Jul. 31, 2025	Jul. 30, 2026
☒	Incubator thermometer	GWS	EL-02JA	21107288	Jul. 31, 2025	Jul. 30, 2026
☒	Control unit(Power sensor)	Tonscend	JS0806-2	/	Jul. 31, 2025	Jul. 30, 2026
☒	Spectrum Analyzer	Keysight	N9020B	MY60112206	Jul. 31, 2025	Jul. 30, 2026
☒	Control unit(Power sensor)	Tonscend	JS0806-2	21H8060465	Aug. 01, 2025	Jul. 31, 2026
☒	Spectrum Analyzer	Keysight	N9020B	MY60112811	Jul. 31, 2025	Jul. 30, 2026
☒	Signal Generator	Keysight	N5173B	MY62220145	Jul. 31, 2025	Jul. 30, 2026
☒	Vector Signal Generator	Keysight	N5182B	MY61252859	Jul. 31, 2025	Jul. 30, 2026
☒	DC POWER	Keysight	E3642A	MY40005294	Jul. 31, 2025	Jul. 30, 2026
☒	Control unit(Power sensor)	Tonscend	JS0806-2	24F80620865	Aug. 01, 2025	Jul. 31, 2026
Software						
Used	Description	Manufacturer	Name		Version	
☒	Test software	Tonscend	JS1120-3		V3.3.10	

RSE Test System						
Used	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due. Date
☒	EMI Receiver	R&S	ESR26	101424	Feb. 24, 2025	Feb. 25, 2026
☒	Hybrid Antenna	Schwarzbeck	VULB9163	01361	May. 28, 2025	May. 27, 2026
☒	Horn Antenna 1	Schwarzbeck	BBHA 9120 D	02910	Aug. 31, 2025	Aug. 30, 2026
☒	Horn Antenna 2	ETS	BBHA 9170	1090	Aug. 31, 2025	Aug. 30, 2026
☒	loop-antenna	Schwarzbeck	FMZB 1513-60	00030	Jan. 11, 2026	Jan. 10, 2027
☒	Test path	/	Path2: WIFI-2.4G 1-3GHz	/	Jul. 31, 2025	Jul. 30, 2026
☒	Test path	/	Path7: ALL PASS 1-18GHz	/	Jul. 31, 2025	Jul. 30, 2026
☒	Test path	/	Path9: 3GHz High PASS 3-18GHz	/	Jul. 31, 2025	Jul. 30, 2026
☒	Test path	/	Path16: 30MHz-1GHz ALL PASS NO AMP	/	Jul. 31, 2025	Jul. 30, 2026
☒	Signal Pre-Amplifier	ETS	3116C-PA	00217677	Jul. 31, 2025	Jul. 30, 2026
☒	3m Fully-anechoic Chamber	YIHENG	9m*6m*6m	001	Sep. 05, 2023	Sep. 04, 2026
Software						
Used	Description	Manufacturer	Name		Version	
☒	Test software	Tonscend	TS+		V5.0.0.0	
Conducted Emission Test For AC Power Port						
Used	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due. Date
☒	LISN	R&S	ENV216	102509	Aug. 01, 2025	Jul. 31, 2026
☒	EMI Receiver	R&S	ESR	102154	Aug. 01, 2025	Jul. 31, 2026
Software						
Used	Description	Manufacturer	Name		Version	
☒	Test software	EZ	EZ-EMC		EMEC-3A1	
Other Instrument						
Used	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due. Date
☒	Temperature & Humidity	Temperature	HTC-1	/	Sep. 20, 2025	Sep. 21, 2026

8. On Time and Duty Cycle

8.1. Block diagram of test setup



Note: The EUT is connected to the Control unit, and then the signal is transmitted through internal circuits to the Spectrum Analyzer.

8.2. Limits

None; for reporting purposes only

8.3. Procedure

KDB 558074 Zero-Span Spectrum Analyzer Method

8.4. Results

Test Mode	Ant.	Freq. (MHz)	ON Time (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Factor(dB)
BLE_1M	Ant1	2402	0.40	0.63	63.49	1.97
		2440	0.40	0.63	63.49	1.97
		2480	0.40	0.63	63.49	1.97
BLE_2M	Ant1	2402	0.21	0.63	33.33	4.77
		2440	0.21	0.63	33.33	4.77
		2480	0.21	0.63	33.33	4.77

Note1: Duty Cycle Correction Factor = 10log(1/x).
Note2: Offset=cable loss + Test system insertion loss
Where: x is Duty Cycle(Linear)
Where: T is On Time (transmit duration)
If that calculated VBW is not available on the analyzer, then the next higher value should be used.

8.5. Original test data

BLE_1M_Ant1_2402





9. 6 dB DTS Bandwidth and 99 % Bandwidth

9.1. Block diagram of test setup

Same as section 8.1

9.2. Limits

CFR 47FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 4			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247(a)(2) ISED RSS-247 5.2 (a)	6 dB Bandwidth	≥ 500 kHz	2400-2483.5
ISED RSS-Gen Clause 6.7	99 % Occupied Bandwidth	For reporting purposes only.	2400-2483.5

9.3. Test Procedure

Connect the UUT to the spectrum analyzer and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	For 6 dB Bandwidth : 1 % to 5 % of the occupied bandwidth For 99 % Occupied Bandwidth : 1 % to 5 % of the occupied bandwidth
VBW	For 6 dB Bandwidth : $\geq 3 \times$ RBW For 99 % Occupied Bandwidth : $\geq 3 \times$ RBW
Trace	Max hold
Sweep	Auto couple

Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB/99 % relative to the maximum level measured in the fundamental emission.

9.4. Results

Test Mode	Ant.	Freq. (MHz)	DTS BW (MHz)	FL (MHz)	FH (MHz)	Limit (MHz)	Verdict
BLE_1M	Ant1	2402	0.520	2401.752	2402.272	0.5	PASS
		2440	0.524	2439.676	2440.200	0.5	PASS
		2480	0.520	2479.752	2480.272	0.5	PASS
BLE_2M	Ant1	2402	0.776	2401.632	2402.408	0.5	PASS
		2440	0.748	2439.480	2440.228	0.5	PASS
		2480	1.016	2479.352	2480.368	0.5	PASS

Note: Offset=cable loss + Test system insertion loss

Test Mode	Antenna	Frequency (MHz)	OCB (MHz)	FL(MHz)	FH(MHz)	Limit(MHz)	Verdict
BLE_1M	Ant1	2402	1.0152	2401.5093	2402.5245	---	---
		2440	1.0313	2439.4937	2440.5250	---	---
		2480	1.0299	2479.4925	2480.5224	---	---
BLE_2M	Ant1	2402	2.0711	2400.9879	2403.0590	---	---
		2440	2.0152	2439.0356	2441.0508	---	---
		2480	2.0673	2478.9929	2481.0602	---	---

Note: Offset=cable loss + Test system insertion loss

9.5. Original test data

6 dB bandwidth:

BLE_1M_Ant1_2402





99% bandwidth

BLE 1M Ant1 2402





BLE 2M Ant1 2440



BLE 2M Ant1 2480



10. Peak Conducted Output Power

10.1. Block diagram of test setup

Same as section 8.1

10.2. Limits

CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 4			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247(b)(3) ISED RSS-247 5.4 (d)	Peak Output Power	1 watt or 30 dBm	2400 - 2483.5

10.3. Test Procedure

Connect EUT's antenna output to spectrum analyzer by RF cable.

99% Bandwidth set the spectrum analyzer as follows:

RBW:	30 kHz
VBW:	100 kHz
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

6 dB Bandwidth set the spectrum analyzer as follows:

RBW:	100 kHz
VBW:	300 kHz
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold


Allow the trace to stabilize, measure the 6 dB and 99% bandwidth of signal.

10.4. Results

Test Mode	Ant.	Freq (MHz)	Conducted Peak Power (dBm)	Conducted Limit (dBm)	Gain(dBm)	EIRP (dBm)	EIRP Limit (dBm)	Verdict
BLE_1M	Ant1	2402	1.71	≤30	1.81	3.52	≤36	PASS
		2440	2.20	≤30	1.81	4.01	≤36	PASS
		2480	4.22	≤30	1.81	6.03	≤36	PASS
BLE_2M	Ant1	2402	1.88	≤30	1.81	3.69	≤36	PASS
		2440	2.50	≤30	1.81	4.31	≤36	PASS
		2480	4.43	≤30	1.81	6.24	≤36	PASS

Note: The EIRP = Peak Power + Ant. Gain

10.5. Original test data






BLE 2M Ant1 2440



BLE 2M Ant1 2480



11. Power Spectral Density

11.1. Block diagram of test setup

Same as section 8.1

11.2. Limits

CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 4			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC §15.247 (e) ISED RSS-247 5.2 (b)	Power Spectral Density	8 dBm in any 3 kHz band	2400 - 2483.5

11.3. Test Procedure

Connect the UUT to the spectrum analyzer and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	$3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
VBW	$\geq 3 \times \text{RBW}$
Span	1.5 x DTS bandwidth
Trace	Max hold
Sweep time	Auto couple.

Allow trace to fully stabilize and use the peak marker function to determine the maximum amplitude level within the RBW.


If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

11.4. Results

Test Mode	Ant.	Freq. (MHz)	Result (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
BLE_1M	Ant1	2402	-15.74	≤ 8.00	PASS
		2440	-13.31	≤ 8.00	PASS
		2480	-11.94	≤ 8.00	PASS
BLE_2M	Ant1	2402	-16.68	≤ 8.00	PASS
		2440	-16.06	≤ 8.00	PASS
		2480	-13.11	≤ 8.00	PASS

Note: Offset=cable loss + Test system insertion loss

11.5. Original test data





12. Conducted Bandedge and Spurious Emissions

12.1. Block diagram of test setup

Same as section 8.1

12.2. Limits

CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 4		
Section	Test Item	Limit
CFR 47 FCC §15.247 (d) ISED RSS-247 5.5	Conducted Band edge and Spurious Emissions	at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power

12.3. Test Procedure

Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	100 kHz
VBW	$\geq 3 \times \text{RBW}$
Span	$\geq 1.5 \times \text{DTS bandwidth}$
Trace	Max hold
Sweep time	Auto couple

Connect the UUT to the spectrum analyzer and use the following settings:

Use the peak marker function to determine the maximum peak power level to establish the reference level.

Span	Set the center frequency and span to encompass frequency range to be measured
Detector	Peak
RBW	100 kHz
VBW	$\geq 3 \times \text{RBW}$
measurement points	$\geq \text{span/RBW}$
Trace	Max hold
Sweep time	Auto couple

Use the peak marker function to determine the maximum amplitude level.

12.4. Results

Band edge

Test Mode	Ant.	Ch Name	Freq. (MHz)	Ref Level (dBm)	Result (dBm)	Limit (dBm)	Verdict
BLE_1M	Ant1	Low	2402	0.74	-48.13	≤ -19.26	PASS
		High	2480	3.66	-48.04	≤ -16.34	PASS
BLE_2M	Ant1	Low	2402	0.63	-33.77	≤ -19.37	PASS
		High	2480	3.00	-48.82	≤ -17	PASS

Note: Offset=cable loss + Test system insertion loss

Spurious Emissions


Test Mode	Ant.	Freq. (MHz)	Freq Range (MHz)	Ref Level (dBm)	Result (dBm)	Limit (dBm)	Verdict
-----------	------	-------------	------------------	-----------------	--------------	-------------	---------


BLE_1M	Ant1	2402	Reference	0.45	0.45	---	PASS
			30~1000	0.45	-61.78	≤-19.55	PASS
			1000~26500	0.45	-41.53	≤-19.55	PASS
		2440	Reference	0.45	0.45	---	PASS
			30~1000	0.45	-62.2	≤-19.55	PASS
			1000~26500	0.45	-41.48	≤-19.55	PASS
		2480	Reference	3.77	3.77	---	PASS
			30~1000	3.77	-61.51	≤-16.23	PASS
			1000~26500	3.77	-41.89	≤-16.23	PASS
BLE_2M	Ant1	2402	Reference	0.53	0.53	---	PASS
			30~1000	0.53	-61.81	≤-19.47	PASS
			1000~26500	0.53	-42.44	≤-19.47	PASS
		2440	Reference	-1.95	-1.95	---	PASS
			30~1000	-1.95	-63.07	≤-21.95	PASS
			1000~26500	-1.95	-41.19	≤-21.95	PASS
		2480	Reference	0.74	0.74	---	PASS
			30~1000	0.74	-62.12	≤-19.26	PASS
			1000~26500	0.74	-41.8	≤-19.26	PASS

Note: Offset=cable loss + Test system insertion loss

12.5. Original test data


Band edge:






Spurious Emissions:










BLE 1M Ant1 2480 1000~26500



BLE 2M Ant1 2402 0~Reference



BLE 2M Ant1 2402 30~1000









13. Radiated Emission

13.1. Block diagram of test setup


In 3 m Anechoic Chamber, test setup diagram for 9 kHz - 30 MHz:



In 3 m Anechoic Chamber, test setup diagram for 30 MHz - 1 GHz:



In 3 m Anechoic Chamber, test setup diagram for frequency above 1 GHz:



Note: For harmonic emissions test a band rejection filter was inserted in the input port of AMP.

13.2. Limit

(1) FCC 15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.1772&4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.2072&4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

²Above 38.6

(2) FCC 15.209 Limit.

Frequency MHz	Distance Meters	Field Strengths Limit	
		$\mu\text{V}/\text{m}$	$\text{dB}(\mu\text{V})/\text{m}$
0.009 ~ 0.490	300	2400/F(kHz)	67.6-20log(F)
0.490 ~ 1.705	30	24000/F(kHz)	87.6-20log(F)
1.705 ~ 30.0	30	30	29.54
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216~960	3	200	46.0
960~1000	3	500	54.0
Above 1000	3	74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)	

Note: (1) At frequencies at or above 30 MHz, measurements may be performed at a distance other than what is specified provided: measurements are not made in the near field except where it can be shown that near field measurements are appropriate due to the characteristics of the device; and it can be demonstrated that the signal levels needed to be measured at the distance employed can be detected by the measurement equipment. Measurements shall not be performed at a distance greater than 30 meters unless it can be further demonstrated that measurements at a distance of 30 meters or less are impractical. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse linear-distance for field strength measurements; inverse-linear-distance-squared for power density measurements).

(2) At frequencies below 30 MHz, measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field. Pending the development of an appropriate measurement procedure for measurements performed below 30 MHz, when performing measurements at a closer distance than specified, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade). This paragraph (f) shall not apply to Access BPL devices operating below 30 MHz.

About Restricted bands of operation please refer to RSS-Gen section 8.10 and FCC § 15.205(a),

13.3. Test Procedure

Below 30 MHz:

The setting of the spectrum Analyzer

RBW	300 Hz (From 9 kHz to 0.15 MHz)/ 10 kHz (From 0.15 MHz to 30 MHz)
VBW	1 kHz (From 9 kHz to 0.15 MHz)/ 30 kHz (From 0.15 MHz to 30 MHz)
Sweep	Auto
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2020+Cor.1-2023+C63.10a-2024

2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.

3. The EUT was placed on a turntable with 80 cm meter above ground.

4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of 1 meter height antenna tower.

5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

6. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT

measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

7. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30m open field site. Therefore, sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field site based on KDB 414788.

Below 1 GHz and above 30 MHz:

The setting of the spectrum Analyzer

RBW	100 kHz
VBW	300 kHz
Sweep	Auto
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2020+Cor.1-2023+C63.10a-2024.

2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

3. The EUT was placed on a turntable with 80 cm above ground.

4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.

5. For measurement below 1GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

Above 1 GHz:

RBW	1 MHz
VBW	PEAK: 3 MHz AVG: see note 6
Sweep	Auto
Detector	Peak
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2020+Cor.1-2023+C63.10a-2024.

2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a band rejection filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

3. The EUT was placed on a turntable with 1.5m above ground.

4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.

5. For measurement above 1GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.

6. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector for AVG measurements. For the Duty Cycle please refer to clause 8.1.ON TIME AND DUTY CYCLE.

7. Restriction band: Investigated frequency range from 2310 MHz to 2410 MHz and 2470MHz to 2500 MHz.

All restriction band should comply with 15.209, other emission should be at least 20 dB below the fundamental.

Note 1: For all radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.

Note 2: The EUT does not support simultaneous transmission.

Note 3: The EUT was fully exercised with external accessories during the test. In the case of multiple accessory external ports, an external accessory shall be connected to one of each type of port.

13.4. Results

Pass. (See below detailed test result)

All the emissions except fundamental emission from 9 kHz to 25 GHz were comply with 15.209 limits.

Note1: According exploratory test, the emission levels are 20 dB below the limit detected from 9 kHz to 30 MHz, so the final test was performed with frequency range from 30 MHz to 26 GHz and recorded in below.

Note2: For emissions below 1 GHz, according exploratory explorer test, when change Tx mode and channel, have no distinct influence on emissions level, so for emissions below 1 GHz, the final test was only performed with EUT working in GFSK_2M, Tx 2480 MHz mode.

Note3: For emissions above 1 GHz. If peak results comply with AV limit, AV Result is deemed to comply with AV limit.

Note 4: For emissions Above 18 GHz, the all the emission is ambient noise, so only show the worse case channel and recorded in report.


13.5. Original test data

Below 1 GHz and above 30 MHz test data Refer to appendix A

Above 1 GHz test data Refer to appendix B

14. AC Power Line Conducted Emissions

14.1. Block diagram of test setup



The EUT is put on a table of non-conducting material that is 80 cm high. The vertical conducting wall of shielding is located 40 cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through an Artificial Mains Network (A.M.N.). A EMI Measurement Receiver (R&S Test Receiver ESR3) is used to test the emissions from both sides of AC line. According to the requirements in Section 6.2 of ANSI C63.10-2020+Cor.1-2023+C63.10a-2024. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode. The bandwidth of EMI test receiver is set at 9 kHz.

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application.

14.2. Limits

Please refer to CFR 47 FCC § 15.207 (a) and ISED RSS-Gen Clause 8.8.

Frequency (MHz)	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

Note 1: * Decreasing linearly with logarithm of frequency.

Note 2: The lower limit shall apply at the transition frequencies.

14.3. Test procedure

The EUT and Support equipment, if needed, were put placed on a non-metallic table, 80cm above the ground plane.

Configuration EUT to simulate typical usage as described in clause 2.4 and test equipment as described in clause 10.2 of this report.

All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.

All support equipment power received from a second LISN.

Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.

The Receiver scanned from 150 kHz to 30 MHz for emissions in each of the test modes.

During the above scans, the emissions were maximized by cable manipulation.

The test mode(s) described in clause 2.4 were scanned during the preliminary test.

After the preliminary scan, we found the test mode producing the highest emission level.

The EUT configuration and worse cable configuration of the above highest emission levels were recorded for reference of the final test.

EUT and support equipment were set up on the test bench as per the configuration with highest emission level in the preliminary test.

A scan was taken on both power lines, Neutral and Line, recording at least the six highest emissions.

Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.

The test data of the worst-case condition(s) was recorded.

The bandwidth of test receiver is set at 9 kHz.

14.4. Test result

Pass. (See below detailed test result)

Note1: All emissions not reported below are too low against the prescribed limits.

Note2: Pre-test AC conducted emission at both voltage AC 120V/60Hz and AC 240V/50Hz, recorded worse case.

14.5. Original test data

AC Power Line Conducted Emission Test Data Refer to appendix C

15. Antenna Requirements

15.1. Limits

Please refer to FCC § 15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Please refer to FCC § 15.247(b)(4)

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Please refer to RSS-GEN Clause 6.8

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Please refer to RSS-GEN Clause 6.8

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

15.2. Result

The antenna used for this product is FPC antenna and that no antenna other than that furnished by the responsible party shall be used with the device, the maximum peak gain of the transmit antenna is 0.81 dBi.


APPENDIX A – Radiated Emission Below 1GHz Test Data

Test Report

Project Information			
EUT:			
Customer:			
Model:	SKO.WB822CU.15	SN:	
Mode:	BLE_2M_2480	Voltage:	DC 5V
Environment:	24.2℃ 51%	Engineer:	Soho Liu
Remark:			

Start of Test:2025-12-30 15:55:00

Test Graph



Final Data List										
NO.	Freq. (MHz)	QP Reading (dBµV/m)	Factor (dB)	QP Value (dBµV/m)	QP Limit (dBµV/m)	Margin (dB)	Height (cm)	Angle (°)	Polarity	Verdict
1	49.98	7.05	21.29	28.34	40.00	11.66	100	276	Horizontal	PASS
2	107.70	8.42	19.61	28.03	43.50	15.47	100	104	Horizontal	PASS
3	222.47	13.95	20.73	34.68	46.00	11.32	100	84	Horizontal	PASS
4	276.70	10.75	21.92	32.67	46.00	13.33	100	59	Horizontal	PASS
5	397.38	5.74	25.18	30.92	46.00	15.08	100	185	Horizontal	PASS
6	994.37	3.58	35.12	38.70	54.00	15.30	100	331	Horizontal	PASS


Note: Margin=QP Limit - QP Value, QP Value=Reading + Factor

Test Report

Project Information			
EUT:			
Customer:			
Model:	SKO.WB822CU.15	SN:	
Mode:	BLE_2M_2480	Voltage:	DC 5V
Environment:	24.2℃ 51%	Engineer:	Soho Liu
Remark:			

Start of Test:2025-12-30 15:55:37

Test Graph



Final Data List										
NO.	Freq. (MHz)	QP Reading (dBµV/m)	Factor (dB)	QP Value (dBµV/m)	QP Limit (dBµV/m)	Margin (dB)	Height (cm)	Angle (°)	Polarity	Verdict
1	46.39	10.5	20.91	31.41	40.00	8.59	100	75	Vertical	PASS
2	107.41	12.25	19.63	31.88	43.50	11.62	100	68	Vertical	PASS
3	221.40	7.52	20.71	28.23	46.00	17.77	100	75	Vertical	PASS
4	421.43	8.44	25.56	34.00	46.00	12.00	100	119	Vertical	PASS
5	577.43	4.9	28.92	33.82	46.00	12.18	100	200	Vertical	PASS
6	998.35	3.58	35.12	38.70	54.00	15.30	100	39	Vertical	PASS

Note: Margin=QP Limit - QP Value, QP Value=Reading + Factor


APPENDIX B – Radiated Emission Above 1GHz Test Data

Test Report

Project Information			
Customer:			
EUT:			
Model:	SKO.WB822CU.15	SN:	
Mode:	BLE_2M_2402	Voltage:	DC 5V
Environment:	24.2℃ 51%	Engineer:	Soho Liu
Remark:			

Start of Test:2025-12-30 14:08:01

Test Graph



PK Final Data List									
NO.	Freq. (MHz)	PK Reading (dBµV/m)	Factor (dB)	PK Value (dBµV/m)	PK Limit (dBµV/m)	PK Margin (dB)	Height (cm)	Angle (°)	Polarity
1	1196.01	40.90	3.37	44.27	74.00	29.73	150	345	Horizontal
2	1973.15	38.22	5.69	43.91	74.00	30.09	150	178	Horizontal
3	4804.59	54.29	-8.31	45.98	74.00	28.02	150	319	Horizontal
4	6000.15	49.57	-3.96	45.61	74.00	28.39	150	40	Horizontal
5	10453.87	40.74	6.83	47.57	74.00	26.43	150	311	Horizontal
6	17878.49	35.49	18.57	54.06	74.00	19.94	150	32	Horizontal

AV Final Data List									
NO.	Freq. (MHz)	AV Reading (dBµV/m)	Factor (dB)	AV Value (dBµV/m)	AV Limit (dBµV/m)	AV Margin (dB)	Height (cm)	Angle (°)	Polarity
1	1196.01	36.87	3.37	40.24	54.00	13.76	150	345	Horizontal
2	1973.15	33.83	5.69	39.52	54.00	14.48	150	178	Horizontal
3	4804.59	49.73	-8.31	41.42	54.00	12.58	150	319	Horizontal
4	6000.15	45.42	-3.96	41.46	54.00	12.54	150	40	Horizontal
5	10453.87	35.34	6.83	42.17	54.00	11.83	150	311	Horizontal
6	17878.49	31.22	18.57	49.79	54.00	4.21	150	32	Horizontal


Note1: PK Value=PK Reading + Factor, PK Margin=PK Limit - PK Value
Note2: AV Value=AV Reading + Factor, AV Margin=AV Limit - AV Value

Test Report

Project Information			
Customer:			
EUT:			
Model:	SKO.WB822CU.15	SN:	
Mode:	BLE_2M_2402	Voltage:	DC 5V
Environment:	24.2℃ 51%	Engineer:	Soho Liu
Remark:			

Start of Test:2025-12-30 14:09:23

Test Graph



PK Final Data List									
NO.	Freq. (MHz)	PK Reading (dBμV/m)	Factor (dB)	PK Value (dBμV/m)	PK Limit (dBμV/m)	PK Margin (dB)	Height (cm)	Angle (°)	Polarity
1	1196.51	48.77	3.38	52.15	74.00	21.85	150	80	Vertical
2	2402.07	36.66	7.26	43.92	74.00	30.08	150	103	Vertical
3	6000.15	51.41	-3.96	47.45	74.00	26.55	150	88	Vertical
4	10205.61	38.73	7.03	45.76	74.00	28.24	150	150	Vertical
5	12886.99	39.37	10.62	49.99	74.00	24.01	150	242	Vertical
6	17905.50	35.21	18.59	53.80	74.00	20.20	150	93	Vertical

AV Final Data List									
NO.	Freq. (MHz)	AV Reading (dBμV/m)	Factor (dB)	AV Value (dBμV/m)	AV Limit (dBμV/m)	AV Margin (dB)	Height (cm)	Angle (°)	Polarity
1	1196.51	46.7	3.38	50.08	54.00	3.92	150	80	Vertical
2	2402.07	33.2	7.26	40.46	54.00	13.54	150	103	Vertical
3	6000.15	48.93	-3.96	44.97	54.00	9.03	150	88	Vertical
4	10205.61	35.82	7.03	42.85	54.00	11.15	150	150	Vertical
5	12886.99	35.28	10.62	45.90	54.00	8.10	150	242	Vertical
6	17905.50	31.25	18.59	49.84	54.00	4.16	150	93	Vertical


Note1: PK Value=PK Reading + Factor, PK Margin=PK Limit - PK Value
Note2: AV Value=AV Reading + Factor, AV Margin=AV Limit - AV Value

Test Report

Project Information			
Customer:			
EUT:			
Model:	SKO.WB822CU.15	SN:	
Mode:	BLE_2M_2440	Voltage:	DC 5V
Environment:	24.2℃ 51%	Engineer:	Soho Liu
Remark:			

Start of Test:2025-12-30 14:11:53

Test Graph



PK Final Data List

NO.	Freq. (MHz)	PK Reading (dBμV/m)	Factor (dB)	PK Value (dBμV/m)	PK Limit (dBμV/m)	PK Margin (dB)	Height (cm)	Angle (°)	Polarity
1	1196.11	42.08	3.37	45.45	74.00	28.55	150	163	Horizontal
2	1997.05	36.90	5.87	42.77	74.00	31.23	150	134	Horizontal
3	4879.59	53.57	-7.62	45.95	74.00	28.05	150	328	Horizontal
4	7479.97	45.14	0.71	45.85	74.00	28.15	150	121	Horizontal
5	11620.18	40.60	7.59	48.19	74.00	25.81	150	45	Horizontal
6	17927.25	35.34	18.38	53.72	74.00	20.28	150	242	Horizontal

AV Final Data List

NO.	Freq. (MHz)	AV Reading (dBμV/m)	Factor (dB)	AV Value (dBμV/m)	AV Limit (dBμV/m)	AV Margin (dB)	Height (cm)	Angle (°)	Polarity
1	1196.11	35.34	3.37	38.71	54.00	15.29	150	163	Horizontal
2	1997.05	32.8	5.87	38.67	54.00	15.33	150	134	Horizontal
3	4879.59	51.71	-7.62	44.09	54.00	9.91	150	328	Horizontal
4	7479.97	42.82	0.71	43.53	54.00	10.47	150	121	Horizontal
5	11620.18	36.87	7.59	44.46	54.00	9.54	150	45	Horizontal
6	17927.25	30.83	18.38	49.21	54.00	4.79	150	242	Horizontal


Note1: PK Value=PK Reading + Factor, PK Margin=PK Limit - PK Value
Note2: AV Value=AV Reading + Factor, AV Margin=AV Limit - AV Value

Test Report

Project Information			
Customer:			
EUT:			
Model:	SKO.WB822CU.15	SN:	
Mode:	BLE_2M_2440	Voltage:	DC 5V
Environment:	24.2℃ 51%	Engineer:	Soho Liu
Remark:			

Start of Test:2025-12-30 14:18:18

Test Graph



PK Final Data List

NO.	Freq. (MHz)	PK Reading (dBµV/m)	Factor (dB)	PK Value (dBµV/m)	PK Limit (dBµV/m)	PK Margin (dB)	Height (cm)	Angle (°)	Polarity
1	1197.31	45.50	3.38	48.88	74.00	25.12	150	94	Vertical
2	1599.63	40.48	4.03	44.51	74.00	29.49	150	132	Vertical
3	6000.15	51.83	-3.96	47.87	74.00	26.13	150	92	Vertical
4	9415.82	39.57	6.58	46.15	74.00	27.85	150	227	Vertical
5	10848.39	39.10	8.06	47.16	74.00	26.84	150	296	Vertical
6	17923.50	35.32	18.42	53.74	74.00	20.26	150	250	Vertical

AV Final Data List

NO.	Freq. (MHz)	AV Reading (dBµV/m)	Factor (dB)	AV Value (dBµV/m)	AV Limit (dBµV/m)	AV Margin (dB)	Height (cm)	Angle (°)	Polarity
1	1197.31	41.04	3.38	44.42	54.00	9.58	150	94	Vertical
2	1599.63	36.58	4.03	40.61	54.00	13.39	150	132	Vertical
3	6000.15	49.1	-3.96	45.14	54.00	8.86	150	92	Vertical
4	9415.82	36.54	6.58	43.12	54.00	10.88	150	227	Vertical
5	10848.39	35.8	8.06	43.86	54.00	10.14	150	296	Vertical
6	17923.50	30.86	18.42	49.28	54.00	4.72	150	250	Vertical


Note1: PK Value=PK Reading + Factor, PK Margin=PK Limit - PK Value
Note2: AV Value=AV Reading + Factor, AV Margin=AV Limit - AV Value

Test Report

Project Information			
Customer:			
EUT:			
Model:	SKO.WB822CU.15	SN:	
Mode:	BLE_2M_2480	Voltage:	DC 5V
Environment:	24.2℃ 51%	Engineer:	Soho Liu
Remark:			

Start of Test:2025-12-30 14:21:45

Test Graph



PK Final Data List

NO.	Freq. (MHz)	PK Reading (dBµV/m)	Factor (dB)	PK Value (dBµV/m)	PK Limit (dBµV/m)	PK Margin (dB)	Height (cm)	Angle (°)	Polarity
1	1302.42	39.53	3.57	43.10	74.00	30.90	150	124	Horizontal
2	1599.43	37.83	4.03	41.86	74.00	32.14	150	2	Horizontal
3	4960.60	50.85	-7.22	43.63	74.00	30.37	150	154	Horizontal
4	7440.97	46.51	0.54	47.05	74.00	26.95	150	305	Horizontal
5	10921.90	39.19	8.20	47.39	74.00	26.61	150	257	Horizontal
6	17812.49	34.93	18.31	53.24	74.00	20.76	150	75	Horizontal

AV Final Data List

NO.	Freq. (MHz)	AV Reading (dBµV/m)	Factor (dB)	AV Value (dBµV/m)	AV Limit (dBµV/m)	AV Margin (dB)	Height (cm)	Angle (°)	Polarity
1	1302.42	35.36	3.57	38.93	54.00	15.07	150	124	Horizontal
2	1599.43	34.25	4.03	38.28	54.00	15.72	150	2	Horizontal
3	4960.60	46.4	-7.22	39.18	54.00	14.82	150	154	Horizontal
4	7440.97	41.6	0.54	42.14	54.00	11.86	150	305	Horizontal
5	10921.90	36.22	8.20	44.42	54.00	9.58	150	257	Horizontal
6	17812.49	31.74	18.31	50.05	54.00	3.95	150	75	Horizontal


Note1: PK Value=PK Reading + Factor, PK Margin=PK Limit - PK Value
Note2: AV Value=AV Reading + Factor, AV Margin=AV Limit - AV Value

Test Report

Project Information			
Customer:			
EUT:			
Model:	SKO.WB822CU.15	SN:	
Mode:	BLE_2M_2480	Voltage:	DC 5V
Environment:	24.2℃ 51%	Engineer:	Soho Liu
Remark:			

Start of Test:2025-12-30 14:23:08

Test Graph



PK Final Data List

NO.	Freq. (MHz)	PK Reading (dBµV/m)	Factor (dB)	PK Value (dBµV/m)	PK Limit (dBµV/m)	PK Margin (dB)	Height (cm)	Angle (°)	Polarity
1	1197.41	47.97	3.39	51.36	74.00	22.64	150	82	Vertical
2	1995.55	40.65	5.86	46.51	74.00	27.49	150	133	Vertical
3	4401.07	47.62	-9.56	38.06	74.00	35.94	150	113	Vertical
4	6000.15	51.07	-3.96	47.11	74.00	26.89	150	62	Vertical
5	10948.90	39.90	8.07	47.97	74.00	26.03	150	10	Vertical
6	17867.99	35.60	18.53	54.13	74.00	19.87	150	2	Vertical

AV Final Data List

NO.	Freq. (MHz)	AV Reading (dBµV/m)	Factor (dB)	AV Value (dBµV/m)	AV Limit (dBµV/m)	AV Margin (dB)	Height (cm)	Angle (°)	Polarity
1	1197.41	42.59	3.39	45.98	54.00	8.02	150	82	Vertical
2	1995.55	33.95	5.86	39.81	54.00	14.19	150	133	Vertical
3	4401.07	43.45	-9.56	33.89	54.00	20.11	150	113	Vertical
4	6000.15	48.46	-3.96	44.50	54.00	9.50	150	62	Vertical
5	10948.90	35.01	8.07	43.08	54.00	10.92	150	10	Vertical
6	17867.99	31.39	18.53	49.92	54.00	4.08	150	2	Vertical


Note1: PK Value=PK Reading + Factor, PK Margin=PK Limit - PK Value
Note2: AV Value=AV Reading + Factor, AV Margin=AV Limit - AV Value

Test Report

Project Information			
Customer:			
EUT:			
Model:	SKO.WB822CU.15	SN:	
Mode:	BLE_2M_2480	Voltage:	DC 5V
Environment:	24.8℃/50%	Engineer:	
Remark:			

Start of Test:2026-01-08 19:57:25

Test Graph



PK Final Data List

NO.	Freq. (MHz)	PK Reading (dB μ V/m)	Factor (dB)	PK Value (dB μ V/m)	PK Limit (dB μ V/m)	PK Margin (dB)	Height (cm)	Angle (°)	Polarity
1	19249.850	39.22	2.87	42.09	68.20	26.11	150	140	Horizontal
2	21432.687	36.49	5.08	41.57	68.20	26.63	150	350	Horizontal
3	24940.188	34.48	6.59	41.07	68.20	27.13	150	170	Horizontal
4	27149.430	38.42	3.41	41.83	68.20	26.37	150	60	Horizontal
5	31396.279	33.35	9.98	43.33	68.20	24.87	150	100	Horizontal
6	33125.825	33.25	9.12	42.37	68.20	25.83	150	170	Horizontal

AV Final Data List

NO.	Freq. (MHz)	AV Reading (dB μ V/m)	Factor (dB)	AV Value (dB μ V/m)	AV Limit (dB μ V/m)	AV Margin (dB)	Height (cm)	Angle (°)	Polarity
1	19249.850	27.67	2.87	30.54	54.00	23.46	150	140	Horizontal
2	21432.687	24.87	5.08	29.95	54.00	24.05	150	350	Horizontal
3	24940.188	24.85	6.59	31.44	54.00	22.56	150	170	Horizontal
4	27149.430	28.98	3.41	32.39	54.00	21.61	150	60	Horizontal
5	31396.279	23.97	9.98	33.95	54.00	20.05	150	100	Horizontal
6	33125.825	22.19	9.12	31.31	54.00	22.69	150	170	Horizontal


Note1: PK Value=PK Reading + Factor, PK Margin=PK Limit - PK Value
Note2: AV Value=AV Reading + Factor, AV Margin=AV Limit - AV Value

Test Report

Project Information			
Customer:			
EUT:			
Model:	SKO.WB822CU.15	SN:	
Mode:	BLE_2M_2480	Voltage:	DC 5V
Environment:	24.8℃/50%	Engineer:	
Remark:			

Start of Test:2026-01-08 19:57:43

Test Graph



PK Final Data List

NO.	Freq. (MHz)	PK Reading (dB μ V/m)	Factor (dB)	PK Value (dB μ V/m)	PK Limit (dB μ V/m)	PK Margin (dB)	Height (cm)	Angle (°)	Polarity
1	19126.625	39.44	2.69	42.13	68.20	26.07	150	240	Vertical
2	21670.334	35.48	5.20	40.68	68.20	27.52	150	170	Vertical
3	25327.465	35.04	6.11	41.15	68.20	27.05	150	120	Vertical
4	27219.844	38.38	3.42	41.80	68.20	26.40	150	210	Vertical
5	31581.116	33.46	9.96	43.42	68.20	24.78	150	270	Vertical
6	35621.124	32.43	10.86	43.29	68.20	24.91	150	170	Vertical

AV Final Data List

NO.	Freq. (MHz)	AV Reading (dB μ V/m)	Factor (dB)	AV Value (dB μ V/m)	AV Limit (dB μ V/m)	AV Margin (dB)	Height (cm)	Angle (°)	Polarity
1	19126.625	28.18	2.69	30.87	54.00	23.13	150	240	Vertical
2	21670.334	25.36	5.20	30.56	54.00	23.44	150	170	Vertical
3	25327.465	23.64	6.11	29.75	54.00	24.25	150	120	Vertical
4	27219.844	26.42	3.42	29.84	54.00	24.16	150	210	Vertical
5	31581.116	22.78	9.96	32.74	54.00	21.26	150	270	Vertical
6	35621.124	20.50	10.86	31.36	54.00	22.64	150	170	Vertical


Note1: PK Value=PK Reading + Factor, PK Margin=PK Limit - PK Value
Note2: AV Value=AV Reading + Factor, AV Margin=AV Limit - AV Value

Test Report

Project Information			
Customer:			
EUT:			
Model:	SKO.WB822CU.15	SN:	
Mode:	BLE_1M_2402	Voltage:	DC 5V
Environment:	24.2℃ 51%	Engineer:	Soho Liu
Remark:			

Start of Test:2025-12-30 14:56:02

Test Graph



Suspected Data List									
NO.	Frequency (MHz)	Reading(dBµV/m)	Level (dBµV/m)	Factor (dB)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Angle (°)	Polarity
1	2346.12	39.96	46.51	6.55	74.00	27.49	150	298	Horizontal
2	2390.04	38.08	44.62	6.54	74.00	29.38	150	97	Horizontal


Note1: Level=Reading+Factor, Margin=Limit - Level

Test Report

Project Information			
Customer:			
EUT:			
Model:	SKO.WB822CU.15	SN:	
Mode:	BLE_1M_2402	Voltage:	DC 5V
Environment:	24.2℃ 51%	Engineer:	Soho Liu
Remark:			

Start of Test:2025-12-30 14:56:43

Test Graph



Suspected Data List									
NO.	Frequency (MHz)	Reading(dBµV/m)	Level (dBµV/m)	Factor (dB)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Angle (°)	Polarity
1	2362.38	41.34	47.89	6.55	74.00	26.11	150	88	Vertical
2	2390.04	39.20	45.74	6.54	74.00	28.26	150	110	Vertical


Note1: Level=Reading+Factor, Margin=Limit - Level

Test Report

Project Information			
Customer:			
EUT:			
Model:	SKO.WB822CU.15	SN:	
Mode:	BLE_1M_2480	Voltage:	DC 5V
Environment:	24.2℃ 51%	Engineer:	Soho Liu
Remark:			

Start of Test:2025-12-30 15:00:06

Test Graph



Suspected Data List

NO.	Frequency (MHz)	Reading (dBµV/m)	Level (dBµV/m)	Factor (dB)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Angle (°)	Polarity
1	2483.52	38.78	45.82	7.04	74.00	28.18	150	336	Horizontal
2	2496.22	39.91	47.01	7.10	74.00	26.99	150	12	Horizontal


Note1: Level=Reading+Factor, Margin=Limit - Level

Test Report

Project Information			
Customer:			
EUT:			
Model:	SKO.WB822CU.15	SN:	
Mode:	BLE_1M_2480	Voltage:	DC 5V
Environment:	24.2℃ 51%	Engineer:	Soho Liu
Remark:			

Start of Test:2025-12-30 15:00:45

Test Graph



Suspected Data List									
NO.	Frequency (MHz)	Reading (dBµV/m)	Level (dBµV/m)	Factor (dB)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Angle (°)	Polarity
1	2483.52	39.13	46.17	7.04	74.00	27.83	150	89	Vertical
2	2507.51	40.04	47.20	7.16	74.00	26.80	150	343	Vertical


Note1: Level=Reading+Factor, Margin=Limit - Level

Test Report

Project Information			
Customer:			
EUT:			
Model:	SKO.WB822CU.15	SN:	
Mode:	BLE_2M_2402	Voltage:	DC 5V
Environment:	24.2℃ 51%	Engineer:	Soho Liu
Remark:			

Start of Test:2025-12-30 15:02:37

Test Graph



Suspected Data List

NO.	Frequency (MHz)	Reading(dBµV/m)	Level (dBµV/m)	Factor (dB)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Angle (°)	Polarity
1	2349.12	39.75	46.30	6.55	74.00	27.70	150	212	Horizontal
2	2390.04	37.89	44.43	6.54	74.00	29.57	150	62	Horizontal


Note1: Level=Reading+Factor, Margin=Limit - Level

Test Report

Project Information			
Customer:			
EUT:			
Model:	SKO.WB822CU.15	SN:	
Mode:	BLE_2M_2402	Voltage:	DC 5V
Environment:	24.2℃ 51%	Engineer:	Soho Liu
Remark:			

Start of Test:2025-12-30 15:03:17

Test Graph



Suspected Data List									
NO.	Frequency (MHz)	Reading(dBµV/m)	Level (dBµV/m)	Factor (dB)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Angle (°)	Polarity
1	2341.12	40.91	47.46	6.55	74.00	26.54	150	106	Vertical
2	2390.04	38.98	45.52	6.54	74.00	28.48	150	132	Vertical


Note1: Level=Reading+Factor, Margin=Limit - Level

Test Report

Project Information			
Customer:			
EUT:			
Model:	SKO.WB822CU.15	SN:	
Mode:	BLE_2M_2480	Voltage:	DC 5V
Environment:	24.2℃ 51%	Engineer:	Soho Liu
Remark:			

Start of Test:2025-12-30 15:07:33

Test Graph



Suspected Data List									
NO.	Frequency (MHz)	Reading(dBμV/m)	Level (dBμV/m)	Factor (dB)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Angle (°)	Polarity
1	2483.52	37.44	44.48	7.04	74.00	29.52	150	298	Horizontal
2	2506.65	39.30	46.46	7.16	74.00	27.54	150	60	Horizontal


Note1: Level=Reading+Factor, Margin=Limit - Level

Test Report

Project Information			
Customer:			
EUT:			
Model:	SKO.WB822CU.15	SN:	
Mode:	BLE_2M_2480	Voltage:	DC 5V
Environment:	24.2℃ 51%	Engineer:	Soho Liu
Remark:			

Start of Test:2025-12-30 15:08:13


Test Graph



Suspected Data List									
NO.	Frequency (MHz)	Reading (dBµV/m)	Level (dBµV/m)	Factor (dB)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Angle (°)	Polarity
1	2483.52	37.02	44.06	7.04	74.00	29.94	150	190	Vertical
2	2486.22	39.82	46.87	7.05	74.00	27.13	150	290	Vertical

Note1: Level=Reading+Factor, Margin=Limit - Level

APPENDIX C – AC Power Line Conducted Emission Test Data



Time: 20:16:06