



# FCC PART 15C REPORT FOR CERTIFICATION On Behalf of

Arovast Corporation

Air Purifier

Model Number: Core 200S

Additional Model: LAP-C201S-MUSW, LAP-C201S-AUSR; LAP-C201S-Followed by  
up to 4 characters

FCC ID: 2ARBY-CORE-200S

|                          |                                                                        |
|--------------------------|------------------------------------------------------------------------|
| Applicant:               | Arovast Corporation                                                    |
| Address:                 | 1775 FLIGHT WAY, SUITE 150 TUSTIN. CA 92782, USA                       |
|                          |                                                                        |
| Prepared By:             | EST Technology Co., Ltd.                                               |
|                          | Chilingxiang, Qishantou, Santun, Houjie, Dongguan,<br>Guangdong, China |
| Tel: 86-769-83081888-808 |                                                                        |

|                 |                              |
|-----------------|------------------------------|
| Report Number:  | ESTE-R2106098-3              |
| Date of Test:   | Oct. 18, 2025~ Oct. 28, 2025 |
| Date of Report: | Oct. 30, 2025                |

## TABLE OF CONTENTS

| Description                                        | Page |
|----------------------------------------------------|------|
| TEST REPORT VERIFICATION.....                      | 3    |
| 1. GENERAL INFORMATION.....                        | 4    |
| 1.1. Description of Device (EUT).....              | 4    |
| 1.2. Antenna Information .....                     | 4    |
| 2. SUMMARY OF TEST .....                           | 5    |
| 2.1. Summary of test result .....                  | 5    |
| 2.2. Test Facilities.....                          | 6    |
| 2.3. Measurement uncertainty .....                 | 7    |
| 2.4. Assistant equipment used for test .....       | 7    |
| 2.5. Block Diagram .....                           | 7    |
| 2.6. Test Mode .....                               | 8    |
| 2.7. Power Setting of Test Software .....          | 8    |
| 2.8. Channel List.....                             | 9    |
| 2.9. Test Equipment List.....                      | 10   |
| 3. RADIATED SPURIOUS EMISSIONS AND BAND EDGE ..... | 11   |
| 3.1. Limit.....                                    | 11   |
| 3.2. Test Setup.....                               | 12   |
| 3.3. Spectrum Analyzer Setting.....                | 12   |
| 3.4. Test Procedure .....                          | 13   |
| 3.5. Test Result.....                              | 14   |
| 4. AC POWER LINE CONDUCTED EMISSIONS .....         | 16   |
| 4.1. Limit.....                                    | 16   |
| 4.2. Test Setup.....                               | 16   |
| 4.3. Spectrum Analyzer Setting.....                | 16   |
| 4.4. Test Procedure .....                          | 16   |
| 4.5. Test Result.....                              | 17   |
| 5. TEST SETUP PHOTO.....                           | 19   |
| 6. EUT PHOTO .....                                 | 21   |

|                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |                      |                                 |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------|---------------------------------|
| <b>Applicant:</b>          | Arovast Corporation                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |                      |                                 |
| <b>Address:</b>            | 1775 FLIGHT WAY, SUITE 150 TUSTIN. CA 92782, USA                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |                      |                                 |
| <b>Manufacturer:</b>       | Arovast Corporation                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |                      |                                 |
| <b>Address:</b>            | 1775 FLIGHT WAY, SUITE 150 TUSTIN. CA 92782, USA                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |                      |                                 |
| <b>E.U.T:</b>              | Air Purifier                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                      |                                 |
| <b>Model Number:</b>       | Core 200S                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                      |                                 |
| <b>Additional Model:</b>   | LAP-C201S-MUSW, LAP-C201S-AUSR; LAP-C201S-Followed by up to 4 characters<br>Note: They are identical except model name.                                                                                                                                                                                                                                                                                                                                                                                                                       |                      |                                 |
| <b>Power Supply:</b>       | AC 120V/60Hz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                      |                                 |
| <b>Trade Name:</b>         | Levoit                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | <b>Serial No.:</b>   | -----                           |
| <b>Date of Receipt:</b>    | Oct. 18, 2025                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | <b>Date of Test:</b> | Oct. 18, 2025~<br>Oct. 28, 2025 |
| <b>Test Specification:</b> | FCC Part 15 Subpart C (15.247)<br>ANSI C63.10:2020<br>FCC KDB 558074 D01 15.247 Meas Guidance v05r02                                                                                                                                                                                                                                                                                                                                                                                                                                          |                      |                                 |
| <b>Test Result:</b>        | <p>The device described above is tested by EST Technology Co., Ltd. The measurement results were contained in this test report and EST Technology Co., Ltd. was assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT to be technically compliance with the FCC Rules and Regulations Part 15 Subpart C requirements.</p> <p>This report applies to above tested sample only and shall not be reproduced in part without written approval of EST Technology Co., Ltd.</p> |                      |                                 |

Date: Dec. 19, 2025

Prepared by:

Reviewed by:

Approved by:

Ring Yang / Assistant

Seven Wang / Engineer

Iceman Hu / Manager

**Other Aspects:**

This report base on the previous report with report number: ESTE-R2106098-2, motors were added in this report, the rf module has not changed, so only need re-tested conducted emissions and radiated(30-1000MHz), other test item needn't re-tested. At the same time, update the addresses of the applicant and the manufacturer.

Abbreviations: OK/P=passed    fail/F=failed    n.a/N=not applicable    E.U.T=equipment under tested

This test report is based on a single evaluation of one sample of above mentioned products ,It is not permitted to be duplicated in extracts without written approval of EST Technology Co., Ltd. The statement of compliance in this report is based on the limit in the test standard, the measurement uncertainty is not considered.

## 1. GENERAL INFORMATION

### 1.1. Description of Device (EUT)

|                     |   |                                       |
|---------------------|---|---------------------------------------|
| Product Name        | : | Air Purifier                          |
| Model Number        | : | Core 200S                             |
| Software Version    | : | V1.0.07                               |
| Hardware Version    | : | V1.0                                  |
| Operation frequency | : | IEEE 802.11b/g/n HT20:2412MHz~2462MHz |
| Number of channel   | : | IEEE 802.11b/g/n HT20: 11 Channels    |
| Modulation Type     | : | DSSS<br>OFDM                          |
| Sample Type         | : | Prototype production                  |

Note: The product information is provided by the manufacturer. The laboratory is not responsible for this data.

### 1.2. Antenna Information

| Ant No. | Brand | Model Name | Antenna Type | Connector | Gain (dBi) |
|---------|-------|------------|--------------|-----------|------------|
| 1       | N/A   | N/A        | PCB          | N/A       | 3.7        |

Note:

- 1.The antenna gain is declared by the customer and the laboratory is not responsible for the accuracy of the antenna gain.
- 2.The test results of this report only apply to the sample as received.

## 2.SUMMARY OF TEST

### 2.1.Summary of test result

| No. | Description of Test Item                     | FCC Standard Section          | Results |
|-----|----------------------------------------------|-------------------------------|---------|
| 1   | 6dB Bandwidth                                | 15.247(a)(2)                  | N/A     |
| 2   | Maximum Peak Output Power                    | 15.247(b)(3)                  | N/A     |
| 3   | Power Spectral Density                       | 15.247(e)                     | N/A     |
| 4   | Conducted Band Edge                          | 15.247(d)                     | N/A     |
| 5   | Conducted Spurious Emissions                 | 15.247(d)                     | N/A     |
| 6   | Radiated Spurious Emissions<br>and Band Edge | 15.205<br>15.209<br>15.247(d) | PASS    |
| 7   | AC Power Line Conducted<br>Emissions         | 15.207                        | PASS    |
| 8   | Antenna Requirement                          | 15.203                        | N/A     |

Note: "N/A" denotes test is not applicable in this test report.

## 2.2. Test Facilities

EMC Lab : Accredited by CNAS, CHINA  
Registration No.: L5288  
This Accreditation is valid until: November 12, 2029

Recognized by FCC, USA  
Designation Number: CN1215  
This Recognition is valid until: January 31, 2026

Accredited by A2LA, USA  
Registration No.: 4366.01  
This Accreditation is valid until: January 31, 2026

Recognized by Industry Canada  
CAB identifier No.: CN0035  
This Recognition is valid until: January 31, 2026

Recognized by VCCI, Japan  
Registration No.: C-14103; T-20073; R-13663;  
R-20103; G-20097  
Date of registration: Apr. 20, 2020  
This Recognition is valid until: Apr. 19, 2026

Recognized by TUV Rheinland, Germany  
Registration No.: UA 50413872 0001  
Date of registration: July 31, 2018

Recognized by Intertek  
Registration No.: 2011-RTL-L2-64  
Date of registration: November 08, 2018

Name of Firm : EST Technology Co., Ltd.

Site Location : Chilingxiang, Qishantou, Santun, Houjie, Dongguan,  
Guangdong, China

### 2.3.Measurement uncertainty

| Test Item                                                | Uncertainty                        |
|----------------------------------------------------------|------------------------------------|
| Uncertainty for Conduction emission test                 | $\pm 3.48\text{dB}$                |
| Uncertainty for spurious emissions test<br>(Below 30MHz) | $\pm 2.88\text{ dB}$               |
| Uncertainty for spurious emissions test<br>(30MHz-1GHz)  | $\pm 4.60\text{ dB}$ (Polarize: H) |
|                                                          | $\pm 4.68\text{ dB}$ (Polarize: V) |

Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=2$ .


### 2.4.Assistant equipment used for test

| Item | Equipment | Brand | Model Name/Type No. | FCC ID | Series No. |
|------|-----------|-------|---------------------|--------|------------|
| -    | -         | -     | -                   | -      | -          |

| Item | Shielded Type | Ferrite Core | Length | Note     |
|------|---------------|--------------|--------|----------|
| 1    | NO            | NO           | 1.5m   | AC Cable |

### 2.5.Block Diagram

For radiated emissions test: EUT was placed on a turntable, which is 0.8 meter high above ground. The EUT was set into 2.4G Wi-Fi test mode by software prior to testing.



(EUT: Air Purifier)

## 2.6. Test Mode

The test mode was selected for the final test as listed below.

| Test Item                               | Mode              | Data Rate | Test Channel    |
|-----------------------------------------|-------------------|-----------|-----------------|
| Radiated Spurious Emissions(Below 1GHz) | IEEE 802.11b      | 1Mbps     | Low/Middle/High |
|                                         | IEEE 802.11g      | 6Mbps     | Low/Middle/High |
|                                         | IEEE 802.11n HT20 | MCS0      | Low/Middle/High |
| AC Power Line Conducted Emissions       | IEEE 802.11b      | 1Mbps     | Low/Middle/High |
|                                         | IEEE 802.11g      | 6Mbps     | Low/Middle/High |
|                                         | IEEE 802.11n HT20 | MCS0      | Low/Middle/High |

Note: In radiated measurement, the EUT had been pre-scan on the positioned of each 3 axis(X,Y,Z), the worst case was found when positioned on **X-plane**.

## 2.7. Power Setting of Test Software

| Software Name             | ESP_RF_test_tool_v2.5 |         |         |
|---------------------------|-----------------------|---------|---------|
| Frequency(MHz)            | 2412                  | 2437    | 2462    |
| IEEE 802.11b Setting      | default               | default | default |
| IEEE 802.11g Setting      | default               | default | default |
| IEEE 802.11n HT20 Setting | default               | default | default |

Note: This information is provided by the applicant.

## 2.8.Channel List

| IEEE 802.11b/802.11g/802.11n HT20 |                    |         |                    |         |                    |
|-----------------------------------|--------------------|---------|--------------------|---------|--------------------|
| Channel                           | Frequency<br>(MHz) | Channel | Frequency<br>(MHz) | Channel | Frequency<br>(MHz) |
| 1                                 | 2412               | 6       | 2437               | 11      | 2462               |
| 2                                 | 2417               | 7       | 2442               |         |                    |
| 3                                 | 2422               | 8       | 2447               |         |                    |
| 4                                 | 2427               | 9       | 2452               |         |                    |
| 5                                 | 2432               | 10      | 2457               |         |                    |

## 2.9. Test Equipment List

### For conducted emission test

| Equipment                | Manufacturer    | Model No.    | Serial No. | Calibration Body | Last Cal.  | Next Cal.  |
|--------------------------|-----------------|--------------|------------|------------------|------------|------------|
| EMI Test Receiver        | Rohde & Schwarz | ESRP3        | EST-E070   | LISAI            | June 11,25 | June 10,26 |
| Artificial Mains Network | Rohde & Schwarz | ENV216       | EST-E048   | LISAI            | June 11,25 | June 10,26 |
| Pulse Limiter            | Rohde & Schwarz | ESH3-Z2      | EST-E078   | LISAI            | June 11,25 | June 10,26 |
| Test Software            | Audix           | e3-6.111221a | N/A        | N/A              | N/A        | N/A        |

### For radiated emission test(9kHz-30MHz)

| Equipment           | Manufacturer    | Model No.    | Serial No. | Calibration Body | Last Cal.  | Next Cal.  |
|---------------------|-----------------|--------------|------------|------------------|------------|------------|
| EMI Test Receiver   | Rohde & Schwarz | ESR7         | EST-E047   | LISAI            | June 11,25 | June 10,26 |
| Active Loop Antenna | SCHWABE BECK    | FMZB 1519B   | EST-E054   | LISAI            | June 11,25 | June 10,26 |
| Test Software       | Audix           | e3-6.111221a | N/A        | N/A              | N/A        | N/A        |
| 9kHz-30MHz Cable    | N/A             | EST-001      | N/A        | N/A              | N/A        | N/A        |

### For radiated emissions test (30MHz-1000MHz)

| Equipment         | Manufacturer    | Model No.    | Serial No. | Calibration Body | Last Cal.  | Next Cal.  |
|-------------------|-----------------|--------------|------------|------------------|------------|------------|
| EMI Test Receiver | Rohde & Schwarz | ESR7         | EST-E047   | LISAI            | June 11,25 | June 10,26 |
| Bilog Antenna     | Teseq           | CBL 6111D    | EST-E034   | LISAI            | June 11,25 | June 10,26 |
| Test Software     | Audix           | e3-6.111221a | N/A        | N/A              | N/A        | N/A        |
| 30-1000MHz Cable  | N/A             | EST-002      | N/A        | N/A              | N/A        | N/A        |

### 3.RADIATED SPURIOUS EMISSIONS AND BAND EDGE

#### 3.1.Limit

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

#### 15.205 Restricted frequency band

| MHz                        | MHz                   | MHz             | GHz              |
|----------------------------|-----------------------|-----------------|------------------|
| 0.090 - 0.110              | 16.42 - 16.423        | 399.9 - 410     | 4.5 - 5.15       |
| <sup>1</sup> 0.495 - 0.505 | 16.69475 - 16.69525   | 608 - 614       | 5.35 - 5.46      |
| 2.1735 - 2.1905            | 16.80425 - 16.80475   | 960 - 1240      | 7.25 - 7.75      |
| 4.125 - 4.128              | 25.5 - 25.67          | 1300 - 1427     | 8.025 - 8.5      |
| 4.17725 - 4.17775          | 37.5 - 38.25          | 1435 - 1626.5   | 9.0 - 9.2        |
| 4.20725 - 4.20775          | 73 - 74.6             | 1645.5 - 1646.5 | 9.3 - 9.5        |
| 6.215 - 6.218              | 74.8 - 75.2           | 1660 - 1710     | 10.6 - 12.7      |
| 6.26775 - 6.26825          | 108 - 121.94          | 1718.8 - 1722.2 | 13.25 - 13.4     |
| 6.31175 - 6.31225          | 123 - 138             | 2200 - 2300     | 14.47 - 14.5     |
| 8.291 - 8.294              | 149.9 - 150.05        | 2310 - 2390     | 15.35 - 16.2     |
| 8.362 - 8.366              | 156.52475 - 156.52525 | 2483.5 - 2500   | 17.7 - 21.4      |
| 8.37625 - 8.38675          | 156.7 - 156.9         | 2690 - 2900     | 22.01 - 23.12    |
| 8.41425 - 8.41475          | 162.0125 - 167.17     | 3260 - 3267     | 23.6 - 24.0      |
| 12.29 - 12.293             | 167.72 - 173.2        | 3332 - 3339     | 31.2 - 31.8      |
| 12.51975 - 12.52025        | 240 - 285             | 3345.8 - 3358   | 36.43 - 36.5     |
| 12.57675 - 12.57725        | 322 - 335.4           | 3600 - 4400     | ( <sup>2</sup> ) |


#### 15.209 Limit

| Frequency (MHz) | Field Strength( $\mu$ V/m) | Distance(m) |
|-----------------|----------------------------|-------------|
| 0.009-0.490     | 2400/F(kHz)                | 300         |
| 0.490-1.705     | 24000/F(kHz)               | 30          |
| 1.705-30        | 30                         | 30          |
| 30-88           | 100                        | 3           |
| 88-216          | 150                        | 3           |
| 216-960         | 200                        | 3           |
| Above 960       | 500                        | 3           |

Note:

- (1) Emission level  $\text{dB}\mu\text{V} = 20 \log \text{Emission level } \mu\text{V/m}$ .
- (2) The smaller limit shall apply at the cross point between two frequency bands.
- (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

## 3.2. Test Setup



## 3.3. Spectrum Analyzer Setting

### For 9KHz-150KHz

| Spectrum Parameters | Setting                                 |
|---------------------|-----------------------------------------|
| RBW                 | 300Hz(for Peak&AVG)/CISPR 200Hz(for QP) |
| VBW                 | 300Hz(for Peak&AVG)/CISPR 200Hz(for QP) |
| Start frequency     | 9KHz                                    |
| Stop frequency      | 150KHz                                  |
| Sweep Time          | Auto                                    |
| Detector            | PEAK/QP/AVG                             |
| Trace Mode          | Max Hold                                |

### For 150KHz-30MHz

| Spectrum Parameters | Setting  |
|---------------------|----------|
| RBW                 | 9KHz     |
| VBW                 | 9KHz     |
| Start frequency     | 150KHz   |
| Stop frequency      | 30MHz    |
| Sweep Time          | Auto     |
| Detector            | QP       |
| Trace Mode          | Max Hold |

## For 30MHz-1GHz

| Spectrum Parameters | Setting  |
|---------------------|----------|
| RBW                 | 120KHz   |
| VBW                 | 300KHz   |
| Start frequency     | 30MHz    |
| Stop frequency      | 1GHz     |
| Sweep Time          | Auto     |
| Detector            | QP       |
| Trace Mode          | Max Hold |

Note :T is the on-time time of the duty cycle,when EUT transmit continuously with maximum output power,unit is seconds. reference section 2.8 for the on-time time.

### 3.4.Test Procedure


- EUT was placed on a turn table, which is 0.8 meter high above ground for below 1GHz test.
- EUT is set 3 meters away from the receiving antenna, which is mounted on a antenna tower.
- Set the EUT transmit continuously with maximum output power.
- The turn table can rotate 360 degrees to determine the position of the maximum emission level.
- The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Both horizontal and vertical polarization of the antenna are set on test.
- Spectrum analyzer setting parameters in accordance with section 3.3.
- Repeat above procedures until all channels were measured.
- Record the results in the test report.

## 3.5. Test Result

## Radiated Emissions Below 1GHz

EST Technology

Chilingxiang, Qishantou, Santun,  
Houjie, Dongguan, Guangdong, China  
Tel: +86-769-83081888  
Fax: +86-769-83081878




Site no. : 5# 966 Chamber Data no. : 5  
Dis. / Ant. : 3m 54681 Ant. pol. : HORIZONTAL  
Limit : FCC PART 15 C(3M)  
Env. / Ins. : Temp:21.2°C;Humi:32%;Press:101.1kPa  
Engineer : Wind Li  
EUT : Air Purifier  
Power : AC 120V/60Hz  
M/N : Core 200S  
Test Mode : TX Mode

|   | Freq.<br>(MHz) | ANT<br>Factor<br>(dB/m) | Cable<br>Loss<br>(dB) | Reading<br>(dBuV) | Emission<br>Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Remark |
|---|----------------|-------------------------|-----------------------|-------------------|-------------------------------|-------------------|----------------|--------|
| 1 | 263.77         | 14.78                   | 2.87                  | 2.32              | 19.97                         | 46.00             | 26.03          | QP     |
| 2 | 320.03         | 13.00                   | 3.20                  | 6.50              | 22.70                         | 46.00             | 23.30          | QP     |
| 3 | 481.05         | 17.58                   | 3.98                  | 2.24              | 23.80                         | 46.00             | 22.20          | QP     |
| 4 | 596.48         | 19.61                   | 4.46                  | 1.32              | 25.39                         | 46.00             | 20.61          | QP     |
| 5 | 677.96         | 20.38                   | 4.78                  | 2.40              | 27.56                         | 46.00             | 18.44          | QP     |
| 6 | 844.80         | 22.45                   | 5.40                  | 0.46              | 28.31                         | 46.00             | 17.69          | QP     |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.  
2. Margin= Limit - Emission Level.  
3. The emission levels that are 20dB below the official limit are not reported.

# EST Technology

Chilingxiang, Qishantou, Santun,  
Houjie, Dongguan, Guangdong, China  
Tel: +86-769-83081888  
Fax: +86-769-83081878



Site no. : 5# 966 Chamber Data no. : 6  
Dis. / Ant. : 3m 54681 Ant. pol. : VERTICAL  
Limit : FCC PART 15 C(3M)  
Env. / Ins. : Temp:21.2°C;Humi:32%;Press:101.1kPa  
Engineer : Wind Li  
EUT : Air Purifier  
Power : AC 120V/60Hz  
M/N : Core 200S  
Test Mode : TX Mode

|   | Freq.<br>(MHz) | ANT<br>Factor<br>(dB/m) | Cable<br>Loss<br>(dB) | Reading<br>(dBuV) | Emission<br>Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Remark |
|---|----------------|-------------------------|-----------------------|-------------------|-------------------------------|-------------------|----------------|--------|
| 1 | 60.07          | 6.20                    | 1.32                  | 13.71             | 21.23                         | 40.00             | 18.77          | QP     |
| 2 | 148.34         | 11.50                   | 2.09                  | 1.99              | 15.58                         | 43.50             | 27.92          | QP     |
| 3 | 239.52         | 11.22                   | 2.73                  | 8.55              | 22.50                         | 46.00             | 23.50          | QP     |
| 4 | 399.57         | 15.45                   | 3.62                  | 1.54              | 20.61                         | 46.00             | 25.39          | QP     |
| 5 | 515.00         | 17.55                   | 4.12                  | 0.04              | 21.71                         | 46.00             | 24.29          | QP     |
| 6 | 573.20         | 19.57                   | 4.37                  | 0.60              | 24.54                         | 46.00             | 21.46          | QP     |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.  
2. Margin= Limit - Emission Level.  
3. The emission levels that are 20dB below the official limit are not reported.

## Note:

- The amplitude of 9KHz to 30MHz spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.
- All channels had been pre-test, only the worst case was reported.

## 4.AC POWER LINE CONDUCTED EMISSIONS


### 4.1.Limit

| Frequency       | Maximum RF Line Voltage          |                               |
|-----------------|----------------------------------|-------------------------------|
|                 | Quasi-Peak Level<br>dB( $\mu$ V) | Average Level<br>dB( $\mu$ V) |
| 150kHz ~ 500kHz | 66 ~ 56*                         | 56 ~ 46*                      |
| 500kHz ~ 5MHz   | 56                               | 46                            |
| 5MHz ~ 30MHz    | 60                               | 50                            |

Note:

1. \* Decreasing linearly with logarithm of frequency.
2. The lower limit shall apply at the transition frequencies.

### 4.2.Test Setup



### 4.3.Spectrum Analyzer Setting

| Spectrum Parameters | Setting  |
|---------------------|----------|
| RBW                 | 9KHz     |
| VBW                 | 9KHz     |
| Start frequency     | 150KHz   |
| Stop frequency      | 30MHz    |
| Sweep Time          | Auto     |
| Detector            | QP/AVG   |
| Trace Mode          | Max Hold |

### 4.4.Test Procedure

- a. The EUT was placed on a non-metallic table, 80cm above the ground plane.
- b. The EUT Power connected to the power mains through a line impedance stabilization network.
- c. Provides a 50 ohm coupling impedance for the EUT (Please refer the block diagram of the test setup and photographs).
- d. Set the EUT transmit continuously with maximum output power.
- e. Spectrum analyzer setting parameters in accordance with section 4.3.
- f. The AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.10: 2020 on Conducted Emission Test.
- g. Record the results in the test report.

## 4.5. Test Result


EST Technology

Chilingxiang, Qishantou, Santun,  
Houjie, Dongguan, Guangdong, China  
Tel: +86-769-83081888  
Fax: +86-769-83081878

Data: 10

File: \\EMC-CE1\Test data\2025\RF\C\Chen Bei\Core 200S-10.22.EM6 (24)

Date: 2025-10-21



Trace: 9

Site no : 1#CE Shield Room Data no. : 10  
Env. / Ins. : Temp:26.5°C;Humi:52%;Press:101.20kPa LINE Phase : LINE  
Limit : FCC PART 15C QP  
Engineer : Victor Chen  
EUT : Air Purifier  
Power : AC 120V/60Hz  
M/N : Core 200S  
Test Mode : TX Mode

|    | Freq.<br>(MHz) | LISN<br>Factor<br>(db) | Cable<br>Loss<br>(db) | Reading<br>dBuV) | Emission<br>Level<br>(dBuV) | Limits<br>(dBuV) | Margin<br>(dB) | Remark  |
|----|----------------|------------------------|-----------------------|------------------|-----------------------------|------------------|----------------|---------|
| 1  | 0.16           | 10.02                  | 9.85                  | 2.80             | 22.67                       | 55.38            | 32.71          | Average |
| 2  | 0.16           | 10.02                  | 9.85                  | 21.26            | 41.13                       | 65.38            | 24.25          | QP      |
| 3  | 0.18           | 10.06                  | 9.79                  | 1.65             | 21.50                       | 54.50            | 33.00          | Average |
| 4  | 0.18           | 10.06                  | 9.79                  | 13.30            | 33.15                       | 64.50            | 31.35          | QP      |
| 5  | 0.20           | 10.06                  | 9.79                  | 2.66             | 22.51                       | 53.80            | 31.29          | Average |
| 6  | 0.20           | 10.06                  | 9.79                  | 11.25            | 31.10                       | 63.80            | 32.70          | QP      |
| 7  | 0.23           | 10.07                  | 9.80                  | 1.59             | 21.46                       | 52.61            | 31.15          | Average |
| 8  | 0.23           | 10.07                  | 9.80                  | 11.63            | 31.50                       | 62.61            | 31.11          | QP      |
| 9  | 0.26           | 10.08                  | 9.81                  | 1.85             | 21.74                       | 51.38            | 29.64          | Average |
| 10 | 0.26           | 10.08                  | 9.81                  | 13.25            | 33.14                       | 61.38            | 28.24          | QP      |
| 11 | 0.27           | 10.08                  | 9.81                  | 1.91             | 21.80                       | 51.07            | 29.27          | Average |
| 12 | 0.27           | 10.08                  | 9.81                  | 13.27            | 33.16                       | 61.07            | 27.91          | QP      |

Remarks: 1. Emission Level= LISN Factor + Cable Loss + Reading.  
2. Margin= Limit - Emission Level.  
3. If the average limit is met when using a quasi-peak detector,  
the EUT shall be deemed to meet both limits and measurement  
with average detector is unnecessary.


## EST Technology

Chilingxiang, Qishantou, Santun,  
Houjie, Dongguan, Guangdong, China  
Tel:+86-769-83081888  
Fax:+86-769-83081878

Data: 12

File: \\EMC-CE1\Test data\2025\RFIC\Chen Bei\Core 200S-10.22.EM6 (24)

Date: 2025-10-21



Site no : 1#CE Shield Room Data no. : 12  
Env. / Ins. : Temp:26.5°C;Humi:52%;Press:101.20kPa LINE Phase : NEUTRAL  
Limit : FCC PART 15C QP  
Engineer : Victor Chen  
EUT : Air Purifier  
Power : AC 120V/60Hz  
M/N : Core 200S  
Test Mode : TX Mode

|    | Freq.<br>(MHz) | LISN<br>Factor<br>(db) | Cable<br>Loss<br>(db) | Reading<br>dBuV | Emission<br>Level<br>(dBuV) | Limits<br>(dBuV) | Margin<br>(dB) | Remark  |
|----|----------------|------------------------|-----------------------|-----------------|-----------------------------|------------------|----------------|---------|
| 1  | 0.17           | 10.15                  | 9.85                  | 3.72            | 23.72                       | 55.16            | 31.44          | Average |
| 2  | 0.17           | 10.15                  | 9.85                  | 19.26           | 39.26                       | 65.16            | 25.90          | QP      |
| 3  | 0.22           | 10.15                  | 9.80                  | 1.67            | 21.62                       | 52.83            | 31.21          | Average |
| 4  | 0.22           | 10.15                  | 9.80                  | 14.30           | 34.25                       | 62.83            | 28.58          | QP      |
| 5  | 0.25           | 10.16                  | 9.81                  | 2.06            | 22.03                       | 51.91            | 29.88          | Average |
| 6  | 0.25           | 10.16                  | 9.81                  | 14.75           | 34.72                       | 61.91            | 27.19          | QP      |
| 7  | 0.28           | 10.18                  | 9.81                  | 1.10            | 21.09                       | 50.94            | 29.85          | Average |
| 8  | 0.28           | 10.18                  | 9.81                  | 13.26           | 33.25                       | 60.94            | 27.69          | QP      |
| 9  | 0.30           | 10.19                  | 9.82                  | 1.53            | 21.54                       | 50.37            | 28.83          | Average |
| 10 | 0.30           | 10.19                  | 9.82                  | 13.27           | 33.28                       | 60.37            | 27.09          | QP      |
| 11 | 0.32           | 10.19                  | 9.82                  | 0.76            | 20.77                       | 49.62            | 28.85          | Average |
| 12 | 0.32           | 10.19                  | 9.82                  | 12.26           | 32.27                       | 59.62            | 27.35          | QP      |

Remarks: 1. Emission Level= LISN Factor + Cable Loss + Reading.  
2. Margin= Limit - Emission Level.  
3. If the average limit is met when using a quasi-peak detector,  
the EUT shall be deemed to meet both limits and measurement  
with average detector is unnecessary.

## 5. TEST SETUP PHOTO

### Conducted Test



### Radiated Test (Below 1GHz)



## 6.EUT PHOTO


**External Photos**  
M/N: Core 200S



**External Photos**  
M/N: Core 200S





**External Photos**  
M/N: Core 200S



## Internal Photos



M/N: Core 200S



# Mainboard No.: EH-BY-41916-C-V1.0(SinOne)



## Internal Photos

M/N: Core 200S



## Internal Photos



M/N: Core 200S



# Mainboard No.: EH-BY-41916-C-V1.0(CBM)



## Internal Photos

M/N: Core 200S



## Internal Photos

M/N: Core 200S



## Wi-Fi and Bluetooth Antenna



# Internal Photos

M/N: Core 200S



## Internal Photos



M/N: Core 200S



## New Photos

### Internal Photos

M/N: Core 200S



End of Test Report