



FCC RADIO TEST REPORT

Applicant	: IC Realtime LLC
Address	: 3050 N. Andrews AVE EXT, Pompano Beach, Florida, United States, 33064
Equipment	: Doorsiren
Model No.	: SINGER-3W, SINGER-3B
Trade Name	: N/A
Date of Sample Receipt	: Jul. 06, 202
Date(s) of Test	: Jul. 22, 2026~Jul. 27, 2026
FCC ID.	: 2ARDU-SINGER-3
Standard	: FCC part 15 Subpart C §15.247

I HEREBY CERTIFY THAT:

The test result refers exclusively to the test presented test model / sample. Without written approval of Cerpass Technology Corp., the test report shall not be reproduced except in full.

Approved by:

Leevin Li / Supervisor



CONTENTS

1. Summary of Test Procedure and Test Results	5
1.1 Applicable Standards	5
2. Test Configuration of Equipment under Test	6
2.1 Feature of Equipment under Test	6
2.2 Carrier Frequency of Channels	7
2.3 Test Mode and Test Software	8
2.4 Power Parameter Value of the test software	9
2.5 Description of Test System	10
2.6 General Information of Test	11
2.7 Measurement Uncertainty	11
3. Test Equipment and Ancillaries Used for Tests	12
4. Antenna Requirements	14
4.1 Standard Applicable	14
4.2 Antenna Construction and Directional Gain	14
5. Test of AC Power Line Conducted Emission	15
5.1 Test Limit	15
5.2 Test Procedures	15
5.3 Typical Test Setup	16
5.4 Test Result and Data	17
6. Test of Spurious Emission (Radiated)	19
6.1 Test Limit	19
6.2 Test Procedures	19
6.3 Typical Test Setup	20
6.4 Test Result and Data (9kHz ~ 30MHz)	21
6.5 Test Result and Data (30MHz ~ 1GHz)	21
6.6 Test Result and Data (Bandedge)	23
6.7 Test Result and Data (1GHz ~ 25GHz)	67
6.8 Restricted Bands of Operation	91
7. Test of Conducted Spurious Emission	92
7.1 Test Limit	92
7.2 Test Procedure	92
7.3 Test Setup Layout	92
7.4 Test Result and Data	92
8. On Time, Duty Cycle and Measurement methods	97
8.1 Test Limit	97
8.2 Test Procedure	97
8.3 Test Setup Layout	97
8.4 Test Result and Data	98
9. 6dB Bandwidth Measurement Data	99
9.1 Test Limit	99
9.2 Test Procedures	99
9.3 Test Setup Layout	99
9.4 Test Result and Data	100



10.Maximum Peak Output Power 103

10.1 Test Limit 103

10.2 Test Procedures 103

10.3 Test Setup Layout..... 103

10.4 Test Result and Data 104

11.Power Spectral Density 105

11.1 Test Limit 105

11.2 Test Procedures 105

11.3 Test Setup Layout..... 105

11.4 Test Result and Data 106



History of this test report

Version No.	Report No	Date	Description
Rev.01	26070024-DRFCC02	Jul. 28, 2026	Initial Issue



1. Summary of Test Procedure and Test Results

1.1 Applicable Standards

ANSI C63.10-2020+Cor.1-2023+C63.10a-2024+Errata to C63.10a-2024

FCC Rules and Regulations Part 15 Subpart C §15.247

FCC Rule	Description of Test	Result
FCC CFR Title 47 Part 15 Subpart C: Section 15.203/15.247 (b)	. Antenna Requirement	Pass
FCC CFR Title 47 Part 15 Subpart C: Section 15.207	. AC Power Line Conducted Emission	Pass
FCC CFR Title 47 Part 15 Subpart C: Section 15.205/15.209;	. Spurious Emission(Radiated)	Pass
FCC CFR Title 47 Part 15 Subpart C: Section 15.247(d);	. Spurious Emission(Conducted)	Pass
FCC CFR Title 47 Part 15 Subpart C: Section 15.247(a)(2);	. 6dB Bandwidth	Pass
FCC CFR Title 47 Part 15 Subpart C: Section 15.247(b);	. Maximum Peak Output Power	Pass
FCC CFR Title 47 Part 15 Subpart C: Section 15.247(e)	. Power Spectral Density	Pass

Note: Deviations Yes ☐ No ☒

*The lab has reduced the uncertainty risk factor from test equipment, environment and staff technicians which according to the standard on contract. Therefore, the test result will only be determined by standard requirement, measurement uncertainty evaluation is not considered.



2. Test Configuration of Equipment under Test

2.1 Feature of Equipment under Test

Equipment	Doorsiren
Model Name	SINGER-3W, SINGER-3B
Model Discrepancy	The models are identical to each other except for model name and appearance color. SINGER-3W is the representative for the final test.
Frequency Range	BLE/ Wi-Fi 2.4GHz: 2400-2483.5MHz
Modulation Type	BLE: GFSK Wi-Fi 2.4GHz: 802.11b: CCK, DQPSK, DBPSK 802.11g/n: BPSK, QPSK, 16QAM, 64QAM 802.11ax: BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM
Data Rate	BLE: GFSK: 1Mbps Wi-Fi 2.4GHz: 802.11b: 1, 2, 5.5, 11Mbps 802.11g: 6, 9, 12, 18, 24, 36, 48, 54Mbps 802.11n: MCS0-MCS7, HT20 802.11ax: MCS0-MCS11, HE20
EUT Power Rating	100-240V~ 0.5A

Note:

1. 802.11ax only support full RU.
2. For more details, please refer to the User's manual of the EUT.



2.2 Carrier Frequency of Channels

802.11b, 802.11g, 802.11n HT 20, 802.11ax HE 20 (2412MHz~2462MHz)

Channel	Frequency(MHz)	Channel	Frequency(MHz)
*01	2412	07	2442
02	2417	08	2447
03	2422	09	2452
04	2427	10	2457
05	2432	*11	2462
*06	2437	---	---

Note: Channels remarked * are selected to perform test.



2.3 Test Mode and Test Software

- During testing, the interface cables and equipment positions were varied according to ANSI C63.10.
- The complete test system included support units and EUT for RF test.
- An executive program, "SecureCRT.exe (Ver.: 6.5.0.380)" under WIN10 system was executed to transmit and receive data via Wireless.
- The following test modes were performed for the test:

Conducted Emissions from the AC mains power ports	
Test Mode	Operating Description
1	802.11b (1Mbps) for 120V
2	802.11g (6Mbps) for 120V
3	802.11n HT20 (6.5Mbps) for 120V
4	802.11ax HE20 (7.3Mbps) for 120V
5	802.11ax HE20 (7.3Mbps) for 240V
caused "Test Mode 4 at CH11:2437" generated the worst case, it was reported as the final data.	
Radiated emission (Below 1GHz)	
Test Mode	Operating Description
1	802.11b (1Mbps)
2	802.11g (6Mbps)
3	802.11n HT20 (6.5Mbps)
4	802.11ax HE20 (7.3Mbps)
caused "Test Mode 4 at CH11:2437" generated the worst case, it was reported as the final data.	
Radiated emission (1GHz ~ 25GHz)	
1	802.11b (1Mbps)
2	802.11g (6Mbps)
3	802.11n HT20 (6.5Mbps)
4	802.11ax HE20 (7.3Mbps)
caused "Test Mode 1~4" generated the worst case, it was reported as the final data.	

Modulation Type	TX CONFIGURATION
802.11b	1TX
802.11g	1TX
802.11n HT20	1TX
802.11ax HE20	1TX


**2.4 Power Parameter Value of the test software**

Mode	Frequency (MHz)	Setting level
		Ant 1
802.11b	2412	Default
	2437	Default
	2462	Default
802.11g	2412	Default
	2437	Default
	2462	Default
802.11n (20MHz)	2412	Default
	2437	Default
	2462	Default
802.11ax (20MHz)	2412	Default
	2437	Default
	2462	Default



2.5 Description of Test System

Product	Manufacturer	Model No.	Power Cord
1 Notebook	SONY	PCG-71811P	Non-Shielded, 1.8m





2.6 General Information of Test

Test Site	CerpPASS Technology Corporation(CerpPASS Laboratory) Address: Room 102, No. 5, Xing'an Road, Chang'an Town, Dongguan City, Guangdong Province, China Tel: +86-769-8547-1212 Fax: +86-769-8547-1912
FCC Designation No.:	CN1288
Frequency Range Investigated:	Conducted: from 150kHz to 30 MHz Radiation: from 30 MHz to 25,000MHz
Test Distance:	The test distance of radiated emission from antenna to EUT is 3 M.

Test Item	Test Site	Test period	Environmental Conditions	Tested By
RF Conducted	RFCON01-DG	2026/07/24	24.9℃ / 56%	Amos Zhang
Radiated Emissions	3M01-DG	2026/07/22~2026/07/24	23.2~23.5℃ / 53~54%	Amos Zhang
AC Power Line Conducted Emission	CON02-DG	2026/07/27	21℃ / 60%	Amos Zhang

2.7 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)).

Measurement Item	Uncertainty
AC Power Line Conduction(150kHz~30MHz)	±2.56dB
Radiated Spurious Emission(9kHz~30MHz)	±3.94dB
Radiated Spurious Emission(30MHz~1GHz)	±4.22dB
Radiated Spurious Emission(1GHz~18GHz)	±5.63dB
Radiated Spurious Emission(18GHz~40GHz)	±4.40dB
6dB Bandwidth&20dB Bandwidth	±4.4%
Occupied Bandwidth	±4.5%
Peak Output Power(Conducted Power Meter)	±0.84dB
Power Spectral Density	±0.84dB
Dwell Time / Deactivation Time	±3.5%



3. Test Equipment and Ancillaries Used for Tests

AC Power Line Conducted Emission					
Test Site	CON02-DG				
Instrument/Ancillary	Manufacturer	Model No.	Serial No.	Calibration Date	Valid Date.
ESR·EMI Test Receiver	R&S	ESR3	102728	2026/07/13	2027/07/12
Two-Line V-Network	R&S	ENV216	100325	2026/07/13	2027/07/12
LISN	SCHWARZBECK	NSLK 8127	8127749	2025/12/26	2026/12/25
Cable	Aoda	RG214	Cable-07	2026/07/13	2027/07/12
Temperature/Humidity Meter	GEMLEAD	STH200A	N/A	2026/07/16	2027/07/15
Software	AUDIX	E3	Version: 8.14806b	N/A	N/A
Test Site	Yiheng	AC-DG-005	N/A	2026/04/13	2029/04/12

Radiated Emissions					
Test Site	3M01-DG				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Valid Date
EMI Test Receiver	R&S	ESCI	101183	2025/12/26	2026/12/25
Amplifier	EMCI	EMC330	980082	2025/12/26	2026/12/25
Loop Antenna	R&S	HFH2-Z2	100150	2025/12/27	2027/12/26
Bilog Antenna	Sunol Science	JB1	A072414-3	2025/07/28	2027/07/27
Preamplifier	Agilent	8449B	3008A02342	2026/07/14	2027/07/13
Preamplifier	COM-POWER	PA-840	711885	2025/12/29	2026/12/28
Broad-Band Horn Antenna	Schwarzbeck	BBHA9120D	9120D-619	2025/12/27	2027/12/26
Standard Gain Horn Antenna	TRC	HA-2640	18050	2025/12/27	2027/12/26
Standard Gain Horn Antenna	TRC	HA-1726	18051	2025/12/27	2027/12/26
FSQ Signal Analyzer	R&S	FSQ40	200012	2025/12/26	2026/12/25
Cable	EMCI	EM104-NMS M-8.5M	Cable-03	2025/12/26	2026/12/25
Cable	Jiuzhoubona	T-SMA	SMA48AL-70 00	2025/12/26	2026/12/25
Cable	CH-CoDesigh	CCXA81-SM AMNM-1M	Cable-05	2025/12/26	2026/12/25
Cable	CH-CoDesigh	CCXA40-2.9 2-2.92-1M	21071954	2026/07/15	2027/07/14
Cable	CH-CoDesigh	CCX40-2.92 M-2.92M-9M	21070892	2026/07/15	2027/07/14
Cable	CH-CoDesigh	CCXA40-2.9 2-2.92-1M	21070891	2026/03/11	2027/03/10
Software	AUDIX	E3	Version: 8.14806b	N/A	N/A
Test Site	Yiheng	AC-DG-001	N/A	2026/04/13	2029/04/12



RF Conducted					
Test Site	RFCON01-DG				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Valid Date
MXA Signal Analyzer	KEYSIGHT	N9020A	US46220290	2025/12/26	2026/12/25
EXA Signal Analyzer	KEYSIGHT	N9010A	MY53400169	2025/12/26	2026/12/25
ESG VECTOR SIGNAL GENERATOR	Agilent	E4438C	MY45092582	2025/12/26	2026/12/25
MXG VECTOR SIGNAL GENERATOR	Agilent	N5182B	MY53050127	2025/12/26	2026/12/25
USB Wideband Power Sensor	Boonton	55006	9778	2026/07/14	2027/07/13
Temperature/ Humidity Meter	mingle	ETH529	N/A	2025/12/29	2026/12/28



4. Antenna Requirements

4.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

4.2 Antenna Construction and Directional Gain

Wi-Fi 2.4G:

Antenna Type	FPC Antenna
Antenna Gain	2.66dBi



5. Test of AC Power Line Conducted Emission

5.1 Test Limit

Conducted Emissions were measured from 150 kHz to 30 MHz with a bandwidth of 9 kHz on the 120 VAC power and return leads of the EUT according to the methods defined in ANSI C63.10-2013. The EUT was placed on a nonmetallic stand in a shielded room 0.8 meters above the ground plane as shown in section 6.2.2. The interface cables and equipment positioning were varied within limits of reasonable applications to determine the position produced maximum conducted emissions.

Frequency (MHz)	Quasi Peak (dB μ V)	Average (dB μ V)
0.15 – 0.5	66-56*	56-46*
0.5 – 5.0	56	46
5.0 – 30.0	60	50


*Decreases with the logarithm of the frequency.

5.2 Test Procedures

The EUT was setup according to ANSI C63.10, 2013 and tested according to DTS test procedure of Oct 2014 KDB558074 for compliance to FCC 47CFR 15.247 requirements. The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface. The EUT and simulators are connected to the main power through a line impedance stabilization network (LISN). The LISN provides a 50 ohm /50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs) Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source. The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length. Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9kHz.





5.3 Typical Test Setup





5.4 Test Result and Data







6. Test of Spurious Emission (Radiated)

6.1 Test Limit

In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. If the transmitter measurement is based on the maximum conducted output power, the attenuation required under this paragraph shall be 30dB instead of 20dB. In addition, radiated emissions which fall in section 15.205(a) the restricted bands must also comply with the radiated emission limit specified in section 15.209(a).

FREQUENCIES(MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE(meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

6.2 Test Procedures


- The EUT was placed on a rotatable table top 0.8 meter for frequency below 1GHz and 1.5meter for frequency above 1GHz above ground.
- The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
- The table was rotated 360 degrees to determine the position of the highest radiation.
- The antenna is a broadband antenna and its height is varied between one meter and four meters above ground to find the maximum value of the field strength both horizontal polarization and vertical polarization of the antenna are set to make the measurement.
- For each suspected emission the EUT was arranged to its worst case and then tune the antenna tower (from 1 M to 4 M) and turn table (from 0 degree to 360 degrees) to find the maximum reading.
- Set the test-receiver system to Peak or CISPR quasi-peak Detect Function and specified bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method and reported.
- For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than AVG limit (that means the emission level in peak mode also complies with the limit in AVG mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in AVG mode again and reported.
- "Cone of radiation" has been considered to be 3dB bandwidth of the measurement antenna.
Note: The supporting fixture shall permit orientation of the EUT in each of three orthogonal axis positions sch that emissions from the EUT are maximized.

(X-AXIS is the worst.)




6.3 Typical Test Setup


Below 30MHz test setup



30MHz- 1GHz Test Setup



Above 1GHz Test Setup







6.4 Test Result and Data (9kHz ~ 30MHz)

The 9kHz-30MHz spurious emission is under limit 20dB more.

6.5 Test Result and Data (30MHz ~ 1GHz)








6.6 Test Result and Data (Bandedge)

Power	: AC 120V/60Hz	Pol/Phase	: VERTICAL
Test Mode	: 802.11b, CH01		



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2390.00	6.24	45.51	51.75	74.00	-22.25	Peak	P
2	2390.00	6.24	34.01	40.25	54.00	-13.75	Average	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	AC 120V/60Hz	Pol/Phase	:	HORIZONTAL
Test Mode	:	802.11b, CH01			




No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2390.00	6.24	45.12	51.36	74.00	-22.64	Peak	P
2	2390.00	6.24	33.93	40.17	54.00	-13.83	Average	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	DC 12V from Adapter (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 1, CH06	Detector	:	Peak



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2390.00	6.24	46.80	53.04	74.00	-20.96	Peak	P
2	2483.60	6.58	46.01	52.59	74.00	-21.41	Peak	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	DC 12V from Adapter (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 1, CH06	Detector	:	Average



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2390.00	6.24	34.26	40.50	54.00	-13.50	Average	P
2	2483.60	6.58	33.80	40.38	54.00	-13.62	Average	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	DC 12V from Adapter (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 1, CH06	Detector	:	Peak



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2390.00	6.24	45.86	52.10	74.00	-21.90	Peak	P
2	2483.60	6.58	45.27	51.85	74.00	-22.15	Peak	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	DC 12V from Adapter (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 1, CH06	Detector	:	Average



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2390.00	6.24	35.97	42.21	54.00	-11.79	Average	P
2	2483.60	6.58	34.31	40.89	54.00	-13.11	Average	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: AC 120V/60Hz	Pol/Phase	: VERTICAL
Test Mode	: 802.11b, CH11		



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2483.50	6.58	45.54	52.12	74.00	-21.88	Peak	P
2	2483.50	6.58	34.44	41.02	54.00	-12.98	Average	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	AC 120V/60Hz	Pol/Phase	:	HORIZONTAL
Test Mode	:	802.11b, CH11			




No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2483.50	6.58	45.72	52.30	74.00	-21.70	Peak	P
2	2483.50	6.58	34.97	41.55	54.00	-12.45	Average	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	DC 12V from Adapter (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 2, CH01	Detector	:	Peak




No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2390.00	6.24	47.72	53.96	74.00	-20.04	Peak	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	DC 12V from Adapter (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 2, CH01	Detector	:	Average



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2390.00	6.24	35.46	41.70	54.00	-12.30	Average	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	DC 12V from Adapter (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 2, CH01	Detector	:	Peak



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBUV)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector	P/F
1	2387.60	5.24	51.69	57.93	74.00	-16.07	Peak	P
2	2390.00	5.24	47.17	53.41	74.00	-20.59	Peak	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	DC 12V from Adapter (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 2, CH01	Detector	:	Average



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2390.00	6.24	36.89	43.13	54.00	-10.87	Average	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	DC 12V from Adapter (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 2, CH06	Detector	:	Peak



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2390.00	6.24	53.03	59.27	74.00	-14.73	Peak	P
2	2483.60	6.58	52.39	58.97	74.00	-15.03	Peak	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	DC 12V from Adapter (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 2, CH06	Detector	:	Average



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2390.00	6.24	35.94	42.18	54.00	-11.82	Average	P
2	2483.60	6.58	34.88	41.46	54.00	-12.54	Average	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	DC 12V from Adapter (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 2, CH06	Detector	:	Peak



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2390.00	6.24	49.60	55.84	74.00	-18.16	Peak	P
2	2483.60	6.58	50.26	56.84	74.00	-17.16	Peak	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	DC 12V from Adapter (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 2, CH06	Detector	:	Average



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2390.00	6.24	39.75	45.99	54.00	-8.01	Average	P
2	2483.60	6.58	36.15	42.73	54.00	-11.27	Average	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	DC 12V from Adapter (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 2, CH11	Detector	:	Peak



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2483.50	6.58	46.51	53.09	74.00	-20.91	Peak	P
2	2486.38	6.59	62.24	68.83	74.00	-5.17	Peak	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	DC 12V from Adapter (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 2, CH11	Detector	:	Average



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2483.53	6.58	34.99	41.57	54.00	-12.43	Average	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	DC 12V from Adapter (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 2, CH11	Detector	:	Peak



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2483.50	6.58	45.39	51.97	74.00	-22.03	Peak	P
2	2484.48	6.58	59.64	66.22	74.00	-7.78	Peak	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	DC 12V from Adapter (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 2, CH11	Detector	:	Average



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2463.53	6.58	37.28	43.86	54.00	-10.14	Average	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	DC 12V from Adapter (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 3, CH01	Detector	:	Peak



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2390.00	6.24	53.96	60.20	74.00	-13.80	Peak	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	DC 12V from Adapter (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 3, CH01	Detector	:	Average



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2390.00	6.24	35.71	41.95	54.00	-12.05	Average	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	DC 12V from Adapter (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 3, CH01	Detector	:	Peak



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2375.60	6.27	60.58	66.85	74.00	-7.15	Peak	P
2	2390.00	6.24	50.13	56.37	74.00	-17.63	Peak	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	DC 12V from Adapter (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 3, CH01	Detector	:	Average



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2390.00	6.24	37.64	43.88	54.00	-10.12	Average	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	DC 12V from Adapter (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 3, CH06	Detector	:	Peak



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2390.00	6.24	49.06	55.30	74.00	-18.70	Peak	P
2	2483.60	6.58	46.12	52.70	74.00	-21.30	Peak	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	DC 12V from Adapter (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 3, CH06	Detector	:	Average



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2390.00	5.24	35.87	42.11	54.00	-11.89	Average	P
2	2483.60	5.58	35.36	41.94	54.00	-12.06	Average	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	DC 12V from Adapter (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 3, CH06	Detector	:	Peak



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2390.00	6.24	52.53	58.77	74.00	-15.23	Peak	P
2	2483.60	6.58	47.30	53.88	74.00	-20.12	Peak	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	DC 12V from Adapter (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 3, CH06	Detector	:	Average



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2390.00	6.24	38.64	44.88	54.00	-9.12	Average	P
2	2483.60	6.58	36.13	42.71	54.00	-11.29	Average	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	DC 12V from Adapter (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 3, CH11	Detector	:	Peak




No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2483.50	6.58	48.41	54.99	74.00	-19.01	Peak	P
2	2484.29	6.58	55.92	62.50	74.00	-11.50	Peak	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	DC 12V from Adapter (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 3, CH11	Detector	:	Average



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2483.53	6.58	35.98	42.56	54.00	-11.44	Average	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	DC 12V from Adapter (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 3, CH11	Detector	:	Peak



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2483.50	6.58	45.65	52.23	74.00	-21.77	Peak	P
2	2491.70	6.60	57.83	64.43	74.00	-9.57	Peak	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	DC 12V from Adapter (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 3, CH11	Detector	:	Average



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2483.53	6.58	36.36	42.94	54.00	-11.06	Average	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	DC 12V from Adapter (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 4, CH01	Detector	:	Peak



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2381.15	6.25	63.89	70.15	74.00	-3.85	Peak	P
2	2390.00	6.24	49.12	55.36	74.00	-18.64	Peak	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	DC 12V from Adapter (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 4, CH01	Detector	:	Average



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2390.00	6.24	36.27	42.51	54.00	-11.49	Average	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	DC 12V from Adapter (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 4, CH01	Detector	:	Peak



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2378.60	6.26	58.23	64.49	74.00	-9.51	Peak	P
2	2390.00	6.24	47.25	53.49	74.00	-20.51	Peak	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	DC 12V from Adapter (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 4, CH01	Detector	:	Average



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2390.00	5.24	38.12	44.36	54.00	-9.64	Average	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	DC 12V from Adapter (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 4, CH06	Detector	:	Peak




No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2390.00	6.24	47.95	54.19	74.00	-19.81	Peak	P
2	2483.60	6.58	46.78	53.36	74.00	-20.64	Peak	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	DC 12V from Adapter (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 4, CH06	Detector	:	Average



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBUV)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector	P/F
1	2390.00	6.24	35.75	41.99	54.00	-12.01	Average	P
2	2483.60	6.58	35.10	41.68	54.00	-12.32	Average	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	DC 12V from Adapter (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 4, CH06	Detector	:	Peak




No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2390.00	6.24	50.08	56.32	74.00	-17.68	Peak	P
2	2483.60	6.58	48.05	54.63	74.00	-19.37	Peak	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	DC 12V from Adapter (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 4, CH06	Detector	:	Average



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2390.00	6.24	39.34	45.58	54.00	-8.42	Average	P
2	2483.60	6.58	36.07	42.65	54.00	-11.35	Average	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss + Amplifier Factor



Power	:	DC 12V from Adapter (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 4, CH11	Detector	:	Peak



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2483.50	6.58	49.07	55.65	74.00	-18.35	Peak	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	DC 12V from Adapter (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 4, CH11	Detector	:	Average



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2483.53	6.58	36.19	42.77	54.00	-11.23	Average	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	DC 12V from Adapter (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 4, CH11	Detector	:	Peak



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2483.50	6.58	45.50	52.08	74.00	-21.92	Peak	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	DC 12V from Adapter (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 4, CH11	Detector	:	Average



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2483.53	6.58	36.44	43.02	54.00	-10.98	Average	P


Note: Level=Reading+Factor


Margin=Level-Limit


Factor=Antenna Factor + cable loss - Amplifier Factor





6.7 Test Result and Data (1GHz ~ 25GHz)






































































6.8 Restricted Bands of Operation

Only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.09000 – 0.11000	16.42000 – 16.42300	399.9 – 410.0	4.500 – 5.250
0.49500 – 0.505**	16.69475 – 16.69525	608.0 – 614.0	5.350 – 5.460
2.17350 – 2.19050	16.80425 – 16.80475	960.0 – 1240.0	7.250 – 7.750
4.12500 – 4.12800	25.50000 – 25.67000	1300.0 – 1427.0	8.025 – 8.500
4.17725 – 4.17775	37.50000 – 38.25000	1435.0 – 1626.5	9.000 – 9.200
4.20725 – 4.20775	73.00000 – 74.60000	1645.5 – 1646.5	9.300 – 9.500
6.21500 – 6.21800	74.80000 – 75.20000	1660.0 – 1710.0	10.600 – 12.700
6.26775 – 6.26825	108.00000 – 121.94000	1718.8 – 1722.2	13.250 – 13.400
6.31175 – 6.31225	123.00000 – 138.00000	2200.0 – 2300.0	14.470 – 14.500
8.29100 – 8.29400	149.90000 – 150.05000	2310.0 – 2390.0	15.350 – 16.200
8.36200 – 8.36600	156.52475 – 156.52525	2483.5 – 2500.0	17.700 – 21.400
8.37625 – 8.38675	156.70000 – 156.90000	2655.0 – 2900.0	22.010 – 23.120
8.41425 – 8.41475	162.01250 – 167.17000	3260.0 – 3267.0	23.600 – 24.000
12.29000 – 12.29300	167.72000 – 173.20000	3332.0 – 3339.0	31.200 – 31.800
12.51975 – 12.52025	240.00000 – 285.00000	3345.8 – 3358.0	36.430 – 36.500
12.57675 – 12.57725	322.00000 – 335.40000	3600.0 – 4400.0	Above 38.6
13.36000 – 13.41000			

** : Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz



7. Test of Conducted Spurious Emission


7.1 Test Limit

Below -20dB of the highest emission level of operating band (In 100 kHz Resolution Bandwidth)

7.2 Test Procedure

- The transmitter output was connected to the spectrum analyzer via a low loss cable.
- Set RBW of spectrum analyzer to 100 kHz and VBW of spectrum analyzer to 300 kHz with convenient frequency span including 100 kHz bandwidth from band edge.
- Peak conducted output power measured within any 100 kHz outside the authorized frequency band shall be attenuated by at least 20dB relative to the maximum measured in-band peak PSD level.
- The band edges was measured and recorded.

7.3 Test Setup Layout





7.4 Test Result and Data

Note: Test plots refers to the following pages.









Modulation Standard: 802.11g
Channel: 01



Modulation Standard: 802.11g
Channel: 06





Modulation Standard: 802.11g
Channel: 11









Modulation Standard: 802.11n HT20
Channel: 01



Modulation Standard: 802.11n HT20
Channel: 06



Modulation Standard: 802.11n HT20
Channel: 11





8. On Time, Duty Cycle and Measurement methods


8.1 Test Limit

None; for reporting purposes only.

8.2 Test Procedure

Zero-Span Spectrum Analyzer Method.

8.3 Test Setup Layout







8.4 Test Result and Data

Modulation Type	On Time (ms)	Period Time (ms)	Duty Cycle (%)
11b	8.340	18.810	44.34%
11g	1.420	13.280	10.69%
11n HT20	1.305	11.655	11.20%
11ax HE20	1.035	11.085	9.34%


Modulation Type: 802.11b (1Mbps)




Modulation Type: 802.11g (6Mbps)



Modulation Type: 802.11n HT20 (6.5Mbps)



Modulation Type: 802.11ax HE20 (7.3Mbps)





9. 6dB Bandwidth Measurement Data


9.1 Test Limit

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

9.2 Test Procedures

- The transmitter output was connected to the spectrum analyzer.
- Set RBW of spectrum analyzer to 100 kHz and VBW to 300 kHz.
- Set spectrum analyzer X dB to 6 dB.
- Set spectrum analyzer peak detector with maximum hold.

9.3 Test Setup Layout






9.4 Test Result and Data


Modulation Type	Channel	Frequency (MHz)	6dB Bandwidth (MHz)
IEEE 802.11b	01	2412	9.62
	06	2437	9.63
	11	2462	10.09
IEEE 802.11g	01	2412	15.20
	06	2437	14.03
	11	2462	13.88
IEEE 802.11n HT20	01	2412	15.76
	06	2437	14.52
	11	2462	17.36
IEEE 802.11ax HE20	01	2412	16.79
	06	2437	14.21
	11	2462	15.05



Modulation Type: 802.11b
CH01




Modulation Type: 802.11g
CH01




CH06




CH06




CH11




CH11




Modulation Type: IEEE 802.11n HT20
CH01


CH06



CH11




Modulation Type: IEEE 802.11ax HE20
CH01



CH06



CH11





10. Maximum Peak Output Power


10.1 Test Limit

The Maximum Peak Output Power Measurement is 30dBm.

10.2 Test Procedures

The antenna port (RF output) of the EUT was connected to the input (RF input) of a power meter. Power was read directly from the meter and cable loss connection was added to the reading to obtain power at the EUT antenna terminal. The EUT Output Power was set to maximum to produce the worse case test result.

10.3 Test Setup Layout





10.4 Test Result and Data

Power Setting	Modulation Type	Channel	Frequency (MHz)	Conducted (peak) output power (dBm)	Conducted (peak) output power (mW)	Power Limit (dBm)
Default	IEEE 802.11b	1	2412	15.08	32.211	30.00
Default		2	2417	15.12	32.509	30.00
Default		6	2437	22.32	170.608	30.00
Default		10	2457	16.48	44.463	30.00
Default		11	2462	16.42	43.853	30.00
Default	IEEE 802.11g	1	2412	18.10	64.565	30.00
Default		2	2417	18.15	65.313	30.00
Default		6	2437	25.55	358.922	30.00
Default		10	2457	18.79	75.683	30.00
Default		11	2462	18.73	74.645	30.00
Default	IEEE 802.11n HT20	1	2412	18.01	63.241	30.00
Default		2	2417	18.05	63.826	30.00
Default		6	2437	25.39	345.939	30.00
Default		10	2457	18.33	68.077	30.00
Default		11	2462	18.30	67.608	30.00
Default	IEEE 802.11ax HE20	1	2412	18.08	64.269	30.00
Default		2	2417	18.14	65.163	30.00
Default		6	2437	25.94	392.645	30.00
Default		10	2457	18.63	72.946	30.00
Default		11	2462	18.61	72.611	30.00



11. Power Spectral Density

11.1 Test Limit


The Maximum of Power Spectral Density Measurement is 8dBm.

If transmitting antennas of directional gain greater than 6 dBi are used, the power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi

11.2 Test Procedures

- The transmitter output was connected to spectrum analyzer.
- The spectrum analyzer's resolution bandwidth were set at 3kHz RBW and 10kHz VBW as that of the fundamental frequency. Set the sweep time=auto couple.
- The power spectral density was measured and recorded.



11.3 Test Setup Layout





11.4 Test Result and Data


Modulation Type	Channel	Frequency (MHz)	Maximum Power Density of 3kHz Bandwidth (dBm)	Total PSD (dBm)	Limit (dBm)
11b	1	2412	-8.942	-8.942	8.00
	6	2437	-3.741	-3.741	8.00
	11	2462	-9.397	-9.397	8.00
11g	1	2412	-13.972	-13.972	8.00
	6	2437	-6.932	-6.932	8.00
	11	2462	-12.947	-12.947	8.00
11n HT20	1	2412	-11.445	-11.445	8.00
	6	2437	-7.185	-7.185	8.00
	11	2462	-13.702	-13.702	8.00
11ax HE20	1	2412	-14.752	-14.752	8.00
	6	2437	-8.317	-8.317	8.00
	11	2462	-13.022	-13.022	8.00

Modulation Type: 802.11b
CH01Modulation Type: 802.11g
CH01

CH06




CH06





CH11




CH11




Modulation Type: 802.11n HT20
CH01Modulation Type: 802.11ax HE20
CH01


CH06




CH06



CH11



CH11



----- End of the report -----