

## RF Exposure Requirements

---

Product Description:Bluetooth Body Fat Scale

Model No.:BT952,BT951,BT908,BT928,BT828,BT903,BT904,BT901,BT936,BT950

FCC ID:2ARE8-BT952

According to the KDB 447498 D01 v06 section 4.3.1, for 100 MHz to 6 GHz and test separation distances  $\leq 50$  mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$$\left[ \frac{\text{(max. power of channel, including tune-up tolerance, mW)}}{\text{(min. test separation distance, mm)}} \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where} \right.$$

-  $f(\text{GHz})$  is the RF channel transmit frequency in GHz

- Power and distance are rounded to the nearest mW and mm before calculation<sup>17</sup>

- The result is rounded to one decimal place for comparison

### Calculation Result:

Tx frequency range:2402MHz

Min. test separation distance: 5mm

Maximum Conducted Output Power:-1.71dBm(0.67mW)

Tune-Up output power: 0dBm(1mW)

RF channel transmit frequency:2402MHz

Result: 0.31

Limit: 3.0

Tx frequency range:2442MHz

Min. test separation distance: 5mm

Maximum Conducted Output Power:-0.37dBm(0.92mW)

Tune-Up output power: 0dBm(1mW)

RF channel transmit frequency:2442MHz

Result: 0.31

Limit: 3.0

Tx frequency range:2480MHz

Min. test separation distance: 5mm

Maximum Conducted Output Power:-1.82dBm(0.66mW)

Tune-Up output power: 0dBm(1mW)

RF channel transmit frequency:2480MHz

Result: 0.31

Limit: 3.0

The exclusion thresholds is  $0.31 < 3$ , so the transmitter complies with the RF exposure requirements and the SAR is not required.