



FCC RADIO TEST REPORT

Applicant : TWELVE SOUTH, LLC
Address : 1503 KING ST STE201 Charleston, SC29405, USA
Equipment : airfly view
Model No. : AFVIEW
Trade Name : twelve south
FCC ID : 2AREB-AFVIEW

I HEREBY CERTIFY THAT:

The sample was received on Jul. 28, 2026 and the testing was completed on Aug. 05, 2026 at CerpPASS Technology Corp. The test result refers exclusively to the test presented test model / sample. Without written approval of CerpPASS Technology Corp., the test report shall not be reproduced except in full.

Approved by:

Mark Liao / Supervisor

Laboratory Accreditation:

CerpPASS Technology Corporation Test Laboratory





Contents

1. Summary of Test Procedure and Test Results	5
1.1 Applicable Standards	5
2. Test Configuration of Equipment under Test	6
2.1 Feature of Equipment.....	6
2.2 Carrier Frequency of Channels	7
2.3 Test Mode and Test Software	8
2.4 Description of Test System.....	10
2.5 General Information of Test	11
2.6 Measurement Uncertainty	11
3. Test Equipment and Ancillaries Used for Tests	12
4. Antenna Requirements	14
4.1 Standard Applicable	14
4.2 Antenna Construction and Directional Gain	14
5. Test of Conducted Emission	15
5.1 Test Limit	15
5.2 Test Procedures	15
5.3 Typical Test Setup	16
5.4 Test Result and Data	17
5.5 Test Photographs	19
6. Test of Spurious Emission (Radiated)	20
6.1 Test Limit	20
6.2 Test Procedures	21
6.3 Typical Test Setup	22
6.4 Test Result and Data (9kHz ~ 30MHz).....	23
6.5 Test Result and Data (30MHz ~ 1GHz)	23
6.6 Test Result and Data (Bandedge).....	25
6.7 Test Result and Data (1GHz ~ 3GHz).....	41
6.8 Test Result and Data (3GHz ~ 18GHz).....	53
6.9 Test Result and Data (18GHz ~ 25GHz).....	77
6.10 Restricted Bands of Operation	79
6.11 Test Photographs (30MHz ~ 1GHz)	80
6.12 Test Photographs (1GHz ~ 25GHz)	81
7. Test of Spurious Emission (Conducted).....	83
7.1 Test Limit	83
7.2 Test Procedure	83
7.3 Test Setup Layout	83
7.4 Test Result and Data	83
8. On Time, Duty Cycle and Measurement methods	86
8.1 Test Limit	86
8.2 Test Procedure	86
8.3 Test Setup Layout	86
8.4 Test Result and Data	87



9.	6dB Bandwidth Measurement Data	88
9.1	Test Limit	88
9.2	Test Procedures	88
9.3	Test Setup Layout	88
9.4	Test Result and Data	88
10.	Maximum Peak Output Power	90
10.1	Test Limit	90
10.2	Test Procedures	90
10.3	Test Setup Layout	90
10.4	Test Result and Data	90
11.	Power Spectral Density	91
11.1	Test Limit	91
11.2	Test Procedures	91
11.3	Test Setup Layout	91
11.4	Test Result and Data	91



History of this test report

Report No	Issued Date	Description
26070454-TRDFCC01	Aug. 10, 2026	Initial Issue



1. Summary of Test Procedure and Test Results

1.1 Applicable Standards

**ANSI C63.10-2020+Cor.1-2023+C63.10a-2024+Errata to C63.10a-2024
FCC Rules and Regulations Part 15 Subpart C §15.247**

FCC Rule	Description of Test	Result
15.203	. Antenna Requirement	PASS
15.207	. AC Power Line Conducted Emission	PASS
15.209 15.205	. Radiated Spurious Emission	PASS
15.247(d)	. Conducted Spurious Emission	PASS
15.247(a)(2)	. 6dB Bandwidth	PASS
15.247(b)	. Maximum Peak Output Power	PASS
15.247(e)	. Power Spectral Density	PASS
Note: Deviations Yes ☐ No ☒ *The lab has reduced the uncertainty risk factor from test equipment, environment and staff technicians which according to the standard on contract. Therefore, the test result will only be determined by standard requirement, measurement uncertainty evaluation is not considered.		



2. Test Configuration of Equipment under Test

2.1 Feature of Equipment

Equipment	airfly view
Model Name	AFVIEW
Model Discrepancy	N/A
Frequency Range	BT/BLE: 2400-2483.5MHz
Modulation Type	BT: GFSK, $\pi/4$ -DQPSK, 8DPSK BLE: GFSK
Data Rate	BT: GFSK: 1Mbps, $\pi/4$ -DQPSK: 2Mbps, 8DPSK: 3Mbps BLE: GFSK: 1Mbps, 2Mbps
EUT Power Rating:	INPUT: 5V _{DC} 500mA

Note: For more details, please refer to the User's manual of the EUT.

**2.2 Carrier Frequency of Channels**

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
*00	2402	14	2430	28	2458
01	2404	15	2432	29	2460
02	2406	16	2434	30	2462
03	2408	17	2436	31	2464
04	2410	18	2438	32	2466
05	2412	*19	2440	33	2468
06	2414	20	2442	34	2470
07	2416	21	2444	35	2472
08	2418	22	2446	36	2474
09	2420	23	2448	37	2476
10	2422	24	2450	38	2478
11	2424	25	2452	*39	2480
12	2426	26	2454	--	--
13	2428	27	2456	--	--

Note: Channels remarked * are selected to perform test.



2.3 Test Mode and Test Software

- a. During testing, the interface cables and equipment positions were varied according to ANSI C63.10-2020+Cor.1-2023+C63.10a-2024+Errata to C63.10a-2024.
- b. The complete test system included support units and EUT for RF test.
- c. An executive program, "BlueTest3.exe (Ver.: 3.3.15.1537)" under Win 10 system was executed to transmit and receive data via Wireless.
- d. The following test modes were performed for the test:

Conducted Emissions from the AC mains power ports	
Test Mode	Operating Description
1	Normal mode: Charging+ BT Link
2	GFSK (1Mbps), Transmitter Mode
3	GFSK (2Mbps), Transmitter Mode
caused "Test Mode 3" generated the worst case, it was reported as the final data.	
Radiation Emissions (Below 1GHz)	
Test Mode	Operating Description
1	Normal mode: Charging+ BT Link
2	Normal mode: Battery+ BT Link
3	GFSK (1Mbps), Transmitter Mode
4	GFSK (2Mbps), Transmitter Mode
5	RX Mode: 2402MHz,2440MHz,2480MHz
caused "Test Mode 4" generated the worst case, it was reported as the final data.	
Radiation Emissions (1GHz ~ 25GHz)	
Test Mode	Operating Description
1	GFSK (1Mbps), Transmitter Mode
2	GFSK (2Mbps), Transmitter Mode
caused "Test Mode 1~2" generated the worst case, they were reported as the final data.	



(For Above 1GHz)

Below test Channel generated the worst case, they were reported as the final data.

Modulation Type	Channel	Frequency (MHz)	Bandedge		1GHz~3GHz		3GHz~18GHz		18GHz~25GHz	
			Ver PK/AV	Hor PK/AV	Ver PK/AV	Hor PK/AV	Ver PK/AV	Hor PK/AV	Ver PK/AV	Hor PK/AV
GFSK (1Mbps)	0	2402	V	V	V	V	V	V		
	19	2440	V	V	V	V	V	V		
	39	2480	V	V	V	V	V	V		
GFSK (2Mbps)	0	2402	V	V	V	V	V	V	V	V
	19	2440	V	V	V	V	V	V		
	39	2480	V	V	V	V	V	V		



2.4 Description of Test System

AC Power Line Conducted Emission & Radiated Emissions (Below 1G)					
Equipment	Brand	Model	Serial No	Length/Type	Power cord/Length/Type
Notebook	ASUS	P2430U	GBNXC13M064467	N/A	Adapter / 1.8m / NS
TYPE-C Cable (Blue)	kolin	KEX-DLCP08	N/A	1m / NS	N/A
Type-C Cable	Hengfuxiang	40102000441	N/A	0.2m / NS	N/A
Adapter	hoda	TC-03	N/A	N/A	N/A
Mobile Phone	MI	M1906G7G	26105/09X902856	N/A	N/A
Radiated Emissions (Above 1G) / RF Conducted					
Equipment	Brand	Model	Serial No	Length/Type	Power cord/Length/Type
Notebook	ASUS	P2430U	GBNXC13M064467	N/A	Adapter / 1.8m / NS
TYPE-C Cable (Blue)	kolin	KEX-DLCP08	N/A	1m / NS	N/A
USB Cable (M to F)(Black)	UGREEN	E478371	N/A	3m / NS	N/A



2.5 General Information of Test

Organization	CerpPASS Technology Corp.		
Test Site	CerpPASS Technology Corporation Test Laboratory Address: No.10, Ln. 2, Lianfu St., Luzhu Dist., Taoyuan City 33848, Taiwan (R.O.C.) Tel:+886-3-3226-888 Fax:+886-3-3226-881		
	FCC	TW1439, TW1079	
	IC	4934E-1, 4934E-2	
Frequency Range Investigated:	Conducted: from 150kHz to 30 MHz Radiation: from 9kHz to 25,000MHz		
Test Distance:	The test distance of radiated emission from antenna to EUT is 3 M.		

Test Item	Test Site	Test period	Environmental Conditions	Tested By
RF Conducted	RFCON01-NK	2026/08/02	24.6℃ / 50%	Leon Huang
Radiated Emissions	3M03-NK	2026/08/03~2026/08/05	24.1~24.2℃ / 42~53%	Leon Huang
AC Power Line Conducted Emission	CON02-NK	2026/08/04	21.6℃ / 56%	Leon Huang

2.6 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)).

Measurement Item	Uncertainty
AC Power Line Conduction(150kHz~30MHz)	±3.2dB
Radiated Spurious Emission(9kHz~30MHz)	±3.4dB
Radiated Spurious Emission(30MHz~1GHz)	±5.2dB
Radiated Spurious Emission(1GHz~25GHz)	±5.2dB
Conducted Spurious Emission	±2.1dB
6dB Bandwidth	±4.4%
20dB Bandwidth	±4.5%
Occupied Bandwidth	±4.4%
Peak Output Power(Conducted Power Meter)	±1.1dB
Dwell Time / Deactivation Time	±3.5%
Power Spectral Density	±2.0dB
Duty Cycle	±3.5%



3. Test Equipment and Ancillaries Used for Tests

Test Item	Radiated Emissions				
Test Site	Semi Anechoic Room(3M03-NK)				
Instrument	Manufacturer	Model No	Serial No	Calibration Date	Valid Date
Bilog Antenna	Sunol	JB1	A020514-1	2025/09/08	2026/09/07
Active Loop Antenna	Schwarzbeck	FMZB 1513	00414	2026/02/04	2027/02/03
Horn Antenna	RF SPIN	DRH0844	31974KV2E20 A0844	2026/03/26	2027/03/25
Horn Antenna	EMCO	3115	00031589	2026/03/11	2027/03/10
Spectrum Analyzer 44GHz	ROHDE & SCHWARZ	FSV3044	101744	2026/04/01	2027/03/31
EMI Receiver	ROHDE & SCHWARZ	ESR7	102888	2026/06/15	2027/06/14
Preamplifier	EMC INSTRUMENTS	EMC118A45V1S EE	981070	2026/04/02	2027/04/01
Preamplifier	EMC INSTRUMENTS	EMC184045SEE	981159	2026/04/02	2027/04/01
Preamplifier	EM Electronics corp.	EM330	060611	2026/03/17	2027/03/16
Cable-4m(9k-3G)	EMEC	RG-223	18274M	2026/07/01	2027/06/30
Cable-0.5m(1G-18G)	HUBER SUHNER	SUCOFLEX 104	805443/4	2026/03/09	2027/03/08
Cable-3m(1G-18G)	HUBER SUHNER	SUCOFLEX 104	805796/4	2026/03/09	2027/03/08
Cable-1m(1G-40G)	EMC INSTRUMENTS	EMC104HS-KM- KM-1000	260304	2026/04/10	2027/04/09
Cable-3m(1G-40G)	EMC INSTRUMENTS	EMC104HS-KM- KM-3000	260305	2026/04/10	2027/04/09
Cable-7m(1G-40G)	EMC INSTRUMENTS	EMC104HS-KM- KM-7000	260306	2026/04/10	2027/04/09
Cable-8m(1G-26.5G)	WOKEN	WCBA-WCA203 SM	CCE1374	2026/03/09	2027/03/08
Cable-4m(30M-1G)	HUBER SUHNER	RG-214	02953M	2026/07/06	2027/07/05
Cable-1m(30M-1G)	HUBER SUHNER	RG-214	05094M	2026/07/06	2027/07/05
Cable-9m(30M-1G)	HUBER SUHNER	RG-214	00402M	2026/07/06	2027/07/05
E3	AUDIX	v8.2014-8-6	RK-000529	NA	NA
High Pass Filter	Warison	WFIL-H3000-18 000F-03	WR377WC2B1	2025/10/15	2026/10/14
Highpass Filter	WOKEN	WFIL-H7000-18 000F-01	WR377WC2B2	2025/10/15	2026/10/14

Test Item	RF Conducted				
Test Site	RFCON01-NK				
Instrument	Manufacturer	Model No	Serial No	Calibration Date	Valid Date
EXA Signal Analyzer	KEYSIGHT	N9010A	MY54200207	2026/04/01	2027/03/30
Attenuator	AGILENT	8491B	MY39250703	2026/01/29	2027/01/28
Power Meter	Anritsu	ML2495A	1224005	2026/01/27	2027/01/26
Power Sensor	Anritsu	MA2411B	1207295	2026/01/27	2027/01/26



Test Item	AC Power Line Conducted Emission				
Test Site	CON02-NK				
Instrument	Manufacturer	Model No	Serial No	Calibration Date	Valid Date
EMI Receiver	ROHDE & SCHWARZ	ESR7	102888	2026/06/15	2027/06/14
Two-Line V-Network	ROHDE & SCHWARZ	ENV216	102185	2025/08/28	2026/08/27
Two-Line V-Network	ROHDE & SCHWARZ	ENV216	101584	2026/01/15	2027/01/14
Cable-4m(9k-3G)	EMEC	RG-223	18274M	2026/07/01	2027/06/30
E3	AUDIX	v8.2014-8-6	RK-000536	NA	NA



4. Antenna Requirements

4.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

4.2 Antenna Construction and Directional Gain

Antenna Type	Chip Antenna
Antenna Gain	2.6dBi



5. Test of Conducted Emission

5.1 Test Limit

Conducted Emissions were measured from 150 kHz to 30 MHz with a bandwidth of 9 kHz, according to the methods defined in ANSI C63.10-2020+Cor.1-2023 and ANSI C63.10a-2024. The EUT was placed on a nonmetallic stand in a shielded room 0.8 meters above the ground plane. The interface cables and equipment positioning were varied within limits of reasonable applications to determine the position produced maximum conducted emissions.

Frequency (MHz)	Quasi Peak (dB μ V)	Average (dB μ V)
0.15 – 0.5	66-56*	56-46*
0.5 – 5.0	56	46
5.0 – 30.0	60	50


*Decreases with the logarithm of the frequency.

5.2 Test Procedures

- The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
- Connect EUT to the power mains through a line impedance stabilization network (LISN).
- All the support units are connecting to the other LISN.
- The LISN provides 50 ohm coupling impedance for the measuring instrument.
- The FCC states that a 50 ohm, 50 micro-Henry LISN should be used.
- Both sides of AC line were checked for maximum conducted interference.
- The frequency range from 150 kHz to 30 MHz was searched.
- Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.




5.3 Typical Test Setup





5.4 Test Result and Data

Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	LINE
Test Mode	:	Mode 3		:	



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1522	9.77	30.22	39.99	65.88	-25.89	QP	P
2	0.1522	9.77	12.43	22.20	55.88	-33.68	Average	P
3	0.1671	9.77	28.56	38.33	65.10	-26.77	QP	P
4	0.1671	9.77	10.86	20.63	55.10	-34.47	Average	P
5	0.2893	9.77	26.37	36.14	60.54	-24.40	QP	P
6	0.2893	9.77	18.04	27.81	50.54	-22.73	Average	P
7	0.3303	9.77	30.53	40.30	59.44	-19.14	QP	P
8	0.3303	9.77	23.47	33.24	49.44	-16.20	Average	P
9	0.3631	9.77	32.50	42.27	58.66	-16.39	QP	P
10	0.3631	9.77	27.46	37.23	48.66	-11.43	Average	P
11	0.3943	9.77	26.86	36.63	57.97	-21.34	QP	P
12	0.3943	9.77	15.53	25.30	47.97	-22.67	Average	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=(LISN or ISN or Current Probe)Factor + Cable Loss



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	NEUTRAL
Test Mode	:	Mode 3		:	



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1591	9.78	29.72	39.50	65.51	-26.01	QP	P
2	0.1591	9.78	16.35	26.13	55.51	-29.38	Average	P
3	0.1742	9.79	27.94	37.73	64.76	-27.03	QP	P
4	0.1742	9.79	10.92	20.71	54.76	-34.05	Average	P
5	0.1905	9.79	26.16	35.95	64.02	-28.07	QP	P
6	0.1905	9.79	9.93	19.72	54.02	-34.30	Average	P
7	0.3405	9.78	30.14	39.92	59.19	-19.27	QP	P
8	0.3405	9.78	22.81	32.59	49.19	-16.60	Average	P
9	0.3646	9.78	32.79	42.57	58.62	-16.05	QP	P
10	0.3646	9.78	28.00	37.78	48.62	-10.84	Average	P
11	0.3912	9.78	22.50	32.28	58.04	-25.76	QP	P
12	0.3912	9.78	9.59	19.37	48.04	-28.67	Average	P

Note: Level=Reading+Factor

Margin=Level-Limit

Factor=(LISN or ISN or Current Probe)Factor + Cable Loss



6. Test of Spurious Emission (Radiated)

6.1 Test Limit

In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. If the transmitter measurement is based on the maximum conducted output power, the attenuation required under this paragraph shall be 30dB instead of 20dB. In addition, radiated emissions which fall in section 15.205(a) the restricted bands must also comply with the radiated emission limit specified in section 15.209(a).

Frequency (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3



6.2 Test Procedures

- a. The EUT was placed on a rotatable table top 0.8 meter above ground.
- b. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
- c. The table was rotated 360 degrees to determine the position of the highest radiation.
- d. The antenna is a broadband antenna and its height is varied between one meter and four meters above ground to find the maximum value of the field strength both horizontal polarization and vertical polarization of the antenna are set to make the measurement.
- e. For each suspected emission the EUT was arranged to its worst case and then tune the antenna tower (from 1 M to 4 M) and turn table (from 0 degree to 360 degrees) to find the maximum reading.
- f. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function and specified bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method and reported.
- h. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- i. "Cone of radiation" has been considered to be 3dB bandwidth of the measurement antenna.


Note:

The supporting fixture shall permit orientation of the EUT in each of three orthogonal axis positions such that emissions from the EUT are maximized.(X AXIS is the worst.)




6.3 Typical Test Setup


Below 30MHz test setup



30MHz- 1GHz Test Setup



Above 1GHz Test Setup






6.4 Test Result and Data (9kHz ~ 30MHz)

The 9kHz - 30MHz spurious emission is under limit 20dB more.

6.5 Test Result and Data (30MHz ~ 1GHz)

Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 4		:	



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	58.13	-16.68	49.10	32.42	40.00	-7.58	Peak	100	142	P
2	83.35	-16.35	45.55	29.20	40.00	-10.80	Peak	100	69	P
3	276.38	-9.39	38.40	29.01	46.00	-16.99	Peak	100	212	P
4	623.64	-2.19	31.99	29.80	46.00	-16.20	Peak	100	344	P
5	689.60	-1.43	36.33	34.90	46.00	-11.10	Peak	100	317	P
6	834.13	1.18	29.33	30.51	46.00	-15.49	Peak	100	312	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 4		:	



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	126.03	-9.15	39.38	30.23	43.50	-13.27	Peak	100	26	P
2	205.57	-12.12	45.43	33.31	43.50	-10.19	Peak	100	244	P
3	274.44	-9.38	47.80	38.42	46.00	-7.58	Peak	100	360	P
4	398.60	-6.72	40.07	33.35	46.00	-12.65	Peak	100	356	P
5	693.48	-1.34	31.31	29.97	46.00	-16.03	Peak	100	242	P
6	900.09	2.00	29.22	31.22	46.00	-14.78	Peak	100	230	P

Note: Level=Reading+Factor


Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



6.6 Test Result and Data (Bandedge)

Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 1, CH00		:	



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-4.20	46.05	41.85	74.00	-32.15	Peak	100	72	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 1, CH00		:	




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-4.20	48.83	44.63	74.00	-29.37	Peak	100	74	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 1, CH19		:	




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-4.20	45.81	41.61	74.00	-32.39	Peak	100	19	P
2	2483.50	-3.88	45.30	41.42	74.00	-32.58	Peak	100	329	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 1, CH19		:	



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-4.20	46.48	42.28	74.00	-31.72	Peak	100	86	P
2	2483.50	-3.88	45.53	41.65	74.00	-32.35	Peak	100	227	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 1, CH39	Detector	:	Peak



No.	Frequency (MHz)	Factor (dB)	Reading (dBUV)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2483.52	-3.88	62.46	58.58	74.00	-15.42	Peak	100	313	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 1, CH39	Detector	:	Average



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2483.50	-3.88	43.51	39.63	54.00	-14.37	Average	100	15	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 1, CH39	Detector	:	Peak




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2483.52	-3.88	72.38	68.50	74.00	-5.50	Peak	100	52	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 1, CH39	Detector	:	Average



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2483.50	-3.88	51.99	48.11	54.00	-5.89	Average	100	278	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 2, CH00		:	




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-4.20	46.67	42.47	74.00	-31.53	Peak	100	27	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 2, CH00		:	




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-4.20	47.92	43.72	74.00	-30.28	Peak	100	49	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 2, CH19		:	



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-4.20	45.68	41.48	74.00	-32.52	Peak	100	277	P
2	2483.50	-3.88	45.64	41.76	74.00	-32.24	Peak	100	312	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 2, CH19		:	




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-4.20	45.27	41.07	74.00	-32.93	Peak	100	13	P
2	2483.50	-3.88	45.36	41.48	74.00	-32.52	Peak	100	271	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 2, CH39	Detector	:	Peak



No.	Frequency (MHz)	Factor (dB)	Reading (dBUV)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2483.50	-3.88	63.37	59.49	74.00	-14.51	Peak	100	221	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 2, CH39	Detector	:	Average



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2483.50	-3.88	45.58	41.70	54.00	-12.30	Average	100	356	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 2, CH39	Detector	:	Peak



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2483.52	-3.88	70.98	67.10	74.00	-6.90	Peak	100	57	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 2, CH39	Detector	:	Average




No.	Frequency (MHz)	Factor (dB)	Reading (dBUV)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2483.52	-3.88	53.40	49.52	54.00	-4.48	Average	100	144	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor



6.7 Test Result and Data (1GHz ~ 3GHz)

Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 1, CH00		:	




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2974.00	-1.95	46.06	44.11	74.00	-29.89	Peak	100	14	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 1, CH00		:	



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2902.00	-2.47	47.16	44.69	74.00	-29.31	Peak	100	36	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 1, CH19		:	



No.	Frequency (MHz)	Factor (dB)	Reading (dBUV)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2990.00	-1.88	45.61	43.73	74.00	-30.27	Peak	100	313	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 1, CH19		:	



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2558.00	-3.62	47.36	43.74	74.00	-30.26	Peak	100	356	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 1, CH39		:	



No.	Frequency (MHz)	Factor (dB)	Reading (dBUV)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2960.00	-2.01	46.38	44.37	74.00	-29.63	Peak	100	319	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 1, CH39		:	




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	1008.00	-9.12	54.26	45.14	74.00	-28.86	Peak	100	182	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 2, CH00		:	



No.	Frequency (MHz)	Factor (dB)	Reading (dBUV)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2999.00	-1.87	45.82	43.95	74.00	-30.05	Peak	100	102	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 2, CH00		:	




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	1056.00	-9.15	53.22	44.07	74.00	-29.93	Peak	100	332	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 2, CH19		:	



No.	Frequency (MHz)	Factor (dB)	Reading (dBUV)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2884.00	-2.55	46.52	43.97	74.00	-30.03	Peak	100	325	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 2, CH19		:	



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2958.00	-2.03	46.31	44.28	74.00	-29.72	Peak	100	170	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 2, CH39		:	



No.	Frequency (MHz)	Factor (dB)	Reading (dBUV)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2980.00	-1.89	46.39	44.50	74.00	-29.50	Peak	100	183	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 2, CH39		:	



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	1056.00	-9.15	53.51	44.36	74.00	-29.64	Peak	100	99	P

Note: Level=Reading+Factor


Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



6.8 Test Result and Data (3GHz ~ 18GHz)

Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 1, CH00	Detector	:	Peak




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	17985.00	14.83	44.41	59.24	74.00	-14.76	Peak	100	44	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 1, CH00	Detector	:	Average



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	17999.00	14.85	32.04	46.89	54.00	-7.11	Average	100	173	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 1, CH00	Detector	:	Peak



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	17985.00	14.83	45.52	60.35	74.00	-13.65	Peak	100	261	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 1, CH00	Detector	:	Average




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	17985.00	14.83	32.30	47.13	54.00	-6.87	Average	100	85	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 1, CH19	Detector	:	Peak



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	17985.00	14.83	44.41	59.24	74.00	-14.76	Peak	100	135	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 1, CH19	Detector	:	Average



No.	Frequency (MHz)	Factor (dB)	Reading (dBUV)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	17985.00	14.83	32.10	46.93	54.00	-7.07	Average	100	101	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 1, CH19	Detector	:	Peak



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	17999.00	14.85	43.97	58.82	74.00	-15.18	Peak	100	144	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 1, CH19	Detector	:	Average



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	17985.00	14.83	32.12	46.95	54.00	-7.05	Average	100	154	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 1, CH39	Detector	:	Peak




No.	Frequency (MHz)	Factor (dB)	Reading (dBUV)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	17999.00	14.85	44.86	59.71	74.00	-14.29	Average	100	311	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 1, CH39	Detector	:	Average



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	17985.00	14.83	32.23	47.06	54.00	-6.94	Average	100	248	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 1, CH39	Detector	:	Peak



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	17955.00	14.78	45.24	60.02	74.00	-13.98	Peak	100	114	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 1, CH39	Detector	:	Average



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	17985.00	14.83	32.15	46.98	54.00	-7.02	Average	100	242	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 2, CH00	Detector	:	Peak



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	17955.00	14.78	44.03	58.81	74.00	-15.19	Peak	100	164	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 2, CH00	Detector	:	Average



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	17999.00	14.85	32.10	46.95	54.00	-7.05	Average	100	251	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 2, CH00	Detector	:	Peak



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	17999.00	14.85	44.87	59.72	74.00	-14.28	Average	100	265	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 2, CH00	Detector	:	Average




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	17999.00	14.85	32.10	46.95	54.00	-7.05	Average	100	255	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 2, CH19	Detector	:	Peak




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	17985.00	14.83	44.68	59.51	74.00	-14.49	Peak	100	242	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 2, CH19	Detector	:	Average



No.	Frequency (MHz)	Factor (dB)	Reading (dBUV)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	17999.00	14.85	32.13	46.98	54.00	-7.02	Average	100	303	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 2, CH19	Detector	:	Peak



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	17970.00	14.80	44.85	59.65	74.00	-14.35	Peak	100	19	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 2, CH19	Detector	:	Average



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	17999.00	14.85	32.40	47.25	54.00	-6.75	Average	100	335	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 2, CH39	Detector	:	Peak



No.	Frequency (MHz)	Factor (dB)	Reading (dBUV)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	17985.00	14.83	44.58	59.41	74.00	-14.59	Peak	100	49	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 2, CH39	Detector	:	Average



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	17985.00	14.83	31.95	46.78	54.00	-7.22	Average	100	54	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 2, CH39	Detector	:	Peak



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	17985.00	14.83	44.63	59.46	74.00	-14.54	Peak	100	47	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 2, CH39	Detector	:	Average



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	17985.00	14.83	32.42	47.25	54.00	-6.75	Average	100	335	P

Note: Level=Reading+Factor


Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



6.9 Test Result and Data (18GHz ~ 25GHz)

Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 2, CH00		:	



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	24972.00	1.77	41.91	43.68	74.00	-30.32	Peak	100	281	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 2, CH00		:	



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	24979.00	1.76	41.59	43.35	74.00	-30.65	Peak	100	135	P

Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



6.10 Restricted Bands of Operation

Only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.09000 – 0.11000	16.42000 – 16.42300	399.9 – 410.0	4.500 – 5.250
0.49500 – 0.505**	16.69475 – 16.69525	608.0 – 614.0	5.350 – 5.460
2.17350 – 2.19050	16.80425 – 16.80475	960.0 – 1240.0	7.250 – 7.750
4.12500 – 4.12800	25.50000 – 25.67000	1300.0 – 1427.0	8.025 – 8.500
4.17725 – 4.17775	37.50000 – 38.25000	1435.0 – 1626.5	9.000 – 9.200
4.20725 – 4.20775	73.00000 – 74.60000	1645.5 – 1646.5	9.300 – 9.500
6.21500 – 6.21800	74.80000 – 75.20000	1660.0 – 1710.0	10.600 – 12.700
6.26775 – 6.26825	108.00000 – 121.94000	1718.8 – 1722.2	13.250 – 13.400
6.31175 – 6.31225	123.00000 – 138.00000	2200.0 – 2300.0	14.470 – 14.500
8.29100 – 8.29400	149.90000 – 150.05000	2310.0 – 2390.0	15.350 – 16.200
8.36200 – 8.36600	156.52475 – 156.52525	2483.5 – 2500.0	17.700 – 21.400
8.37625 – 8.38675	156.70000 – 156.90000	2655.0 – 2900.0	22.010 – 23.120
8.41425 – 8.41475	162.01250 – 167.17000	3260.0 – 3267.0	23.600 – 24.000
12.29000 – 12.29300	167.72000 – 173.20000	3332.0 – 3339.0	31.200 – 31.800
12.51975 – 12.52025	240.00000 – 285.00000	3345.8 – 3358.0	36.430 – 36.500
12.57675 – 12.57725	322.00000 – 335.40000	3600.0 – 4400.0	Above 38.6
13.36000 – 13.41000			

** : Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz