



TEST REPORT

Report No. : AB0044478(5) Date : 09 Sep 2022

Application No. : LB019714(0)

Applicant : TWELVE SOUTH LLC
1503 KING ST., SUITE 201, CHARLESTON,
SOUTH CAROLINA, US 29405

Sample Description	Model No.
Bluetooth Transmitter	AirFly

Date Received : Aug 02, 2022

Test Period : Aug 02, 2022 to Aug 14, 2022

Test Requested : FCC Certification for FCC Part 15, subpart C
ISED Certification for License-exempt Device

Test Method : 47 CFR Part 15 (10-1-20 Edition),
ANSI C63.10 – 2013,
ANSI C63.4 – 2014,
RSS-247 Issue 2,
RSS-Gen Issue 5

Test Engineer : Mr. Leung Shu Kan, Ken

Conclusion : The submitted sample was found to comply with technical requirement of FCC
Part 15 Subpart C, section 15.247, and ISED Canada Radio Standards Specification
RSS-247 Issue 2.

For and on behalf of
CMA Industrial Development Foundation Limited

Authorized Signature :  Page 1 of 89
Wong Lap Pong / Andrew
Deputy Technical Manager

FCC ID: 2AREB-AIRFLY
IC: 24385-AIRFLY

The conformity statement stated in Conclusion above is based on the decision made by the test engineer. This document is issued subject to the latest CMA Testing General Terms and Conditions of Testing and Inspection Services, available on request or accessible at website www.cmateesting.org. This document shall not be reproduced except in full without written approval by CMA Testing. The results apply to the sample as received unless otherwise specified. The observations and test results in this report are relevant only to the sample tested.

CMA Industrial Development Foundation Limited

Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, N.T., Hong Kong.

Tel: (852) 2698 8198 Fax: (852) 2695 4177 E-mail: info@cmateesting.org Web Site: <http://www.cmateesting.org>



TEST REPORT

Report No. : AB0044478(5)

Date : 09 Sep 2022

RESULT SUMMARY

Test Item	FCC Requirement	RSS Requirement	Test Method	Result
Number of hopping frequency	§15.247(a)(1)(iii)	RSS-247 §5.1(d)	ANSI C63.10 §7.8.3	PASS
Band-edge	§15.247(d)	RSS-247 §5.5	ANSI C63.10 §7.8.6 and 6.10	PASS
Carrier frequency separation	§15.247(a)	RSS-247 §5.1(b)	ANSI C63.10 §7.8.2	PASS
Time of occupancy (dwell time)	§15.247(a)	RSS-247 §5.1(b)	ANSI C63.10 §7.8.4	PASS
Output power	§15.247(b)(1)	RSS-247 §5.4	ANSI C63.10 §7.8.5	PASS
Occupied bandwidth	§15.247(a)	RSS-247 §5.1(a)	ANSI C63.10 §7.8.7 and 6.9.2	PASS
Conducted spurious emission (Transmitter)	§15.247(d)	RSS-247 §5.5	ANSI C63.10 §7.8.8, and §11.12.2.1	PASS
Radiated spurious emission (Transmitter)	§15.247(d)	RSS-247 §5.5	ANSI C63.10 §6.4 – 6.6	PASS
Radiated spurious emission (Receiver)	§15.109(a)	RSS-Gen, §7.0	ANSI C63.4 §8.3	PASS
Conducted emission on AC mains	§15.207(a)	RSS-Gen, §8.8	ANSI C63.4 §7.3	PASS
Frequency Hopping System Requirement	§15.247(a)(1), (g), (h)	RSS-247 §5.1	N/A	PASS
Frequency Stability	N/A	RSS-Gen, §8.11	ANSI C63.10 §7.8.7 and 6.9.2	PASS

FCC ID: 2AREB-AIRFLY
IC: 24385-AIRFLY



TEST REPORT

Report No. : AB0044478(5)

Date : 09 Sep 2022

Table of Contents

Table of Contents	3
1 Product Information	5
1.1 General Information.....	5
1.2 Technical Information.....	5
1.3 Associated Electric Information.....	6
1.4 Associated Cables	6
2.0 Equipment Units Tested (EUT).....	6
3.0 Location of Test Facility.....	6
4.0 List of test equipment, supporting equipment and cables.....	7
4.1 Test equipment.....	7
4.2 Supporting equipment.....	8
4.3 Cables.....	8
4.4 Software	8
5.0 Measurement Uncertainty.....	8
6.0 Measurement	9
6.1 General Test condition.....	9
6.2 Number of hopping frequency	9
6.2.1 Measurement	9
6.2.2 Final Result	9
6.3 Band-edge measurement	10
6.3.1 Measurement	10
6.3.2 Final Result	11
6.4 Carrier Frequency Separation	12
6.4.1 Measurement	12
6.4.2 Final Result	12
6.5 Time of occupancy (dwell time)	13
6.5.1 Measurement	13
6.5.2 Final Result	13
6.6 Output Power	14
6.6.1 Measurement	14
6.6.2 Final Result	14
6.7 Occupied Bandwidth.....	15
6.7.1 Measurement	15
6.7.2 Final Result	15
6.8 Conducted Spurious emission (Transmitter).....	16
6.8.1 Measurement	16
6.8.2 Final Result	16
6.9 Radiated Spurious emission (Transmitter).....	17
6.9.1 Measurement	17

FCC ID: 2AREB-AIRFLY

IC: 24385-AIRFLY



TEST REPORT

Report No. : AB0044478(5)

Date : 09 Sep 2022

6.9.2 Final Result	18
6.10 Radiated Spurious emission (other mode).....	20
6.10.1 Measurement	20
6.10.2 Final Result	21
6.11 Conducted Emission.....	22
6.11.1 Measurement	22
6.11.2 Final Result	22
7.0 Frequency Hopping System Requirement	23
8.0 External photo, Internal Photo and Test configuration Photo	25
APPENDIX A Test Result	26

FCC ID: 2AREB-AIRFLY
IC: 24385-AIRFLY



TEST REPORT

Report No. : AB0044478(5)

Date : 09 Sep 2022

1 Product Information

1.1 General Information

Product Description:	Model:
Bluetooth Transmitter	AirFly

Primary function : Providing the basic Bluetooth transmitter and receiver function to transmit the audio signal from player without Bluetooth function.

Power supply : DC 3.7V (Li-ion rechargeable)
DC 5.0V (USB-Type C charging port)

RF related function : Bluetooth communication

Electric Accessories sold with : Nil

Interconnection cable associated sold with : 28cm USB to USB Type-C cable

Operating condition : Not specified

Model difference : Not applicable

Remark : Nil

1.2 Technical Information

Operating Frequency : 2402 – 2480MHz

Digital Modulation : FHSS

Modulation : GFSK, $\pi/4$ DQPSK, 8DPSK

Number of Channel : 79

Channel Bandwidth : 1.0MHz

20dB Bandwidth : 1.270MHz

Occupied Bandwidth : 1.170MHz

Signal Type : Data

Number of Antenna : One

Antenna Type : Chip type antenna

Antenna Gain : 3.32dBi

Rated Input Voltage : DC 3.7V (Li-ion rechargeable battery)
DC 5.0V (USB-Type C charging port)

RF Technology Used : Bluetooth 5.0+EDR (non BLE)

Simplex or Duplex : Half-duplex

Adaptivity : FHSS adaptivity

FCC ID: 2AREB-AIRFLY
IC: 24385-AIRFLY



TEST REPORT

Report No. : AB0044478(5)

Date : 09 Sep 2022

1.3 Associated Electric Information

N/A

1.4 Associated Cables

Cable Type	Length	Shielding	Ferrite attached
USB to USB Type C cable	28cm	No	No

2.0 Equipment Units Tested (EUT)

Product Description : Bluetooth Transmitter
Model : AirFly
PMN : AirFly
HVIN : AirFly
FVIN : N/A
HMN : N/A
Serial No. : Not labelled
Sample Type : Pre-production type
Rationale of selection : One single model

3.0 Location of Test Facility

CMA Industrial Development Foundation Ltd.
Room 1302, Yan Hing Centre,
9-13 Wong Chuk Yeung,
Fo Tan, Shatin,
New Territories
Hong Kong.

FCC Accredited Lab (Designation Number: HK0004)
ISED Wireless Test Site (ISED Assigned Code: 4093A)

FCC ID: 2AREB-AIRFLY
IC: 24385-AIRFLY

TEST REPORT

Report No. : AB0044478(5)

Date : 09 Sep 2022

4.0 List of test equipment, supporting equipment and cables

4.1 Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Calibration Due Date	Calibration Period
EMI Test Receiver	Rohde & Schwarz	ESCI	100152	14 Dec 2022	1Year
Spectrum Analyzer	R&S	FSV40	100964	14 Oct 2022	1Year
Log Periodic Antenna	TESEQ	UPA6109	Log Periodic Antenna	27 Oct 2022	2Years
Biconical Antenna	Rohde & Schwarz	HK116	Biconical Antenna	02 Feb 2023	2Years
Horn Antenna	Schwarzbeck	BBHA 9120D	9120D-531	02 Feb 2023	3Years
Broadband Pre-Amplifier	Schwarzbeck	BBV 9718	9718-119	16 Nov 2023	3Years
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170442	08 Dec 2023	2Years
Broadband Pre-Amplifier	Schwarzbeck	BBV 9719	9719-010	03 May 2023	2Years
Coaxial Cable	Suhner	Sucoflex 106	N/A	31 May 2023	1Year
Coaxial Cable	Suhner	Sucoflex_104	N/A	14 Dec 2022	2Years
LISN	Rohde & Schwarz	ENV216	101323	19 Oct 2022	1Year
Coaxial Cable	Tyco Electronics	RG 58C/U	N/A	14 Dec 2022	1Year
Rohde & Schwarz TS8997 Testing System					
Spectrum Analyzer	Rohde & Schwarz	FSV 40	101190	14 Oct 2022	1Year
OSP	Rohde & Schwarz	OSP	OSP-B157W	12 Jul 2023	1Year

FCC ID: 2AREB-AIRFLY
IC: 24385-AIRFLY

TEST REPORT

Report No. : AB0044478(5)

Date : 09 Sep 2022

4.2 Supporting equipment

Equipment Name	Manufacturer	Model	Serial	Provided by
Control board*	DingKun Digital Tech Shenzhen Co. Ltd.	Not labelled	Not labelled	Applicant
USB Charger	Apple	A1299	Not labelled	CMA
iPod 8GB	Apple	A1285	YM9312JE2ME	CMA

Remark: *only used for configure engineering mode

4.3 Cables

Nil

4.4 Software

Software Name	Version	Function	Provided by
Actions BT FCC Tool*	V2.24	Control the engineering mode of the device	Applicant

Remark: *only used for configure engineering mode

5.0 Measurement Uncertainty

The reported uncertainty is based on a standard uncertainty multiplied by a coverage factor $k=2$, providing a level of confidence of approximately 95%.

Radiated emissions

Frequency	Uncertainty (U_{lab})
30MHz ~ 200MHz (Horizontal)	4.59dB
30MHz ~ 200MHz (Vertical)	4.49dB
200MHz ~1000MHz (Horizontal)	4.94dB
200MHz ~1000MHz (Vertical)	4.97dB
1GHz ~6GHz	4.52dB
6GHz ~18GHz	4.58dB
18GHz~40GHz	4.66dB

Line-conducted emissions

Frequency	Uncertainty (U_{lab})
150kHz~30MHz	2.80dB

FCC ID: 2AREB-AIRFLY

IC: 24385-AIRFLY



TEST REPORT

Report No. : AB0044478(5)

Date : 09 Sep 2022

6.0 Measurement

6.1 General Test condition

Temperature : 24.7°C
Test Voltage : DC 3.7V and AC 120V
Humidity : 54.9%
Atmosphere Pressure : 100.6kPa

6.2 Number of hopping frequency

6.2.1 Measurement

Requirement : FCC Part 15 § 15.247(a)(1)(iii) and RSS-247 §5.1(d)
Measuring procedure : ANSI C63.10:2013, clause 7.8.3
Span : 83.5MHz
RBW : 300kHz
VBW : 300kHz
Frequency range : 2.4000 – 2.4835GHz
Modulation tested : GFSK
Packet Type tested : DH5
Additional measuring procedure : Nil

6.2.2 Final Result

No. of hopping channels measured	Limit	Result	Worst case mode
79	≥ 15	PASS	GFSK and DH5

Remark:

1. Detail test result and equipment setting refer to Page 28.

FCC ID: 2AREB-AIRFLY
IC: 24385-AIRFLY



TEST REPORT

Report No. : AB0044478(5)

Date : 09 Sep 2022

6.3 Band-edge measurement

6.3.1 Measurement

Requirement	: FCC Part 15 §15.247(d) and RSS-247 §5.5
Measuring procedure	: ANSI C63.10:2013, section 7.8.6 and 6.10
Hopping mode	: Enabled and Disable
RBW	: 100kHz
VBW	: 300kHz
Frequency range	: 2310 – 2400MHz and 2483.5 – 2500MHz
Modulation tested	: GFSK, $\pi/4$ DQPSK, 8DPSK
Packet Type tested	: DH5, 2DH5, 3DH5
Channel tested for non-hopping mode	: 2402MHz for lowed band edge and 2480MHz for higher band edge
Additional measuring procedure	: For lower band edge (2400MHz) 1. Using the “Measurement 1” setting shown below the scan plot within the frequency span from 2400 – 2483.5MHz to measure the maximum peak value of fundamental 2. Using the “Measurement 2” setting shown below the scan plot within the frequency span from 2310 – 2400MHz to measure the bandedge reading 3. Compare that reading in procedure with the limit which equal to the measured maximum peak in procedure 1 minus 20dB For Upper bandedge (2483.5MHz) 1. Using the “Measurement 1” setting shown below the scan plot within the frequency span from 2400 – 2483.5MHz to measure the maximum peak value of fundamental 2. Using the “Measurement 2” setting shown below the scan plot within the frequency span from 2483.5 – 2500MHz to measure the bandedge reading 3. Compare that reading in procedure with the limit which equal to the measured maximum peak in procedure 1 minus 20dB

FCC ID: 2AREB-AIRFLY
IC: 24385-AIRFLY



TEST REPORT

Report No. : AB0044478(5)

Date : 09 Sep 2022

6.3.2 Final Result

Bandedge frequency for lower bandedge (Worst Case)	Worst case (dBc) ²	Detector	Limit ¹ (dBc)	Result	Worst case
2381.375	49.2	Peak	≥ 20.0	PASS	GFSK and DH5
Bandedge frequency for higher bandedge (Worst Case)	Worst case in (dBc) ²	Detector	Limit ¹	Result	Worst case
2484.475000	48.3	Peak	≥ 20.0	PASS	GFSK and DH5

Remark:

1. The limit is based on the transmitter demonstrated compliance with peak conducted power limit on section 6.6.2 of this report.
2. The Worst case dBc is the peak values measured in procedure 1 minus the worst case bandedge emission.
3. Detail test result and equipment setting refer to Page 56-63.

FCC ID: 2AREB-AIRFLY
IC: 24385-AIRFLY



TEST REPORT

Report No. : AB0044478(5)

Date : 09 Sep 2022

6.4 Carrier Frequency Separation

6.4.1 Measurement

Requirement	: FCC Part 15 §15.247(a) and RSS-247 §5.1(b)
Measuring procedure	: ANSI C63.10:2013, section 7.8.2
Hopping mode	: Enabled
RBW	: 300kHz
VBW	: 300kHz
Frequency range	: 2401-2404MHz, 2440-2443MHz, 2478-2481MHz
Modulation tested	: GFSK ²
Packet Type tested	: DH5 ²
Additional measuring procedure	: Nil
Remark	: 1) Since the measured value is more than 1.5 times of limit, only middle channel is measured. 2) Since the modulation and packet type does not affect the channel separation, GFSK and DH5 are selected as represented modulation and data type

6.4.2 Final Result

Carrier Frequency Separation	Limit ¹	Result	Worst case mode
1.010000MHz	0.846667MHz	PASS	GFSK and DH5

Remark:

1. Limit is 2/3 of the 20dB bandwidth in section 6.7 and conducted peak power is less than 0.125W in section 6.6 of this report.
2. Detail test result and equipment setting refer to Page 53-55.

FCC ID: 2AREB-AIRFLY
IC: 24385-AIRFLY



TEST REPORT

Report No. : AB0044478(5)

Date : 09 Sep 2022

6.5 Time of occupancy (dwell time)

6.5.1 Measurement

Requirement	: FCC Part 15 §15.247(a) and RSS-247 §5.1(a)
Measuring procedure	: ANSI C63.10:2013, section 7.8.4
Hopping mode	: Disable
RBW	: 500kHz
VBW	: 1MHz
Modulation tested	: GFSK ¹
Packet Type tested	: DH1, DH3, DH5
Channel tested for non-hopping mode	: 2441MHz
Additional measuring procedure	: 1) Setup engineering sample to channel 2441MHz and DH1 packet size to perform the measurement according to ANSI C63.10, section 7.8.4 2) Find the worst case packet size 3) Repeat procedure 1 with the worst case packet size for channel 2402MHz and 2480MHz
Remark	: 1) Since the modulation does not affect the dwell time, GFSK is selected as represented modulation.

6.5.2 Final Result

Dwell time (worst case)	Limit	Result	Worst case mode
308.390ms	≤400ms	PASS	GFSK and DH5

Remark:

1. Detail test result and equipment setting refer to Page 29-31.

FCC ID: 2AREB-AIRFLY
IC: 24385-AIRFLY

TEST REPORT

Report No. : AB0044478(5)

Date : 09 Sep 2022

6.6 Output Power

6.6.1 Measurement

Requirement : FCC Part 15 §15.247(b) (1) and RSS-247 §5.4
 Measuring procedure : ANSI C63.10:2013, section 7.8.5
 Hopping mode : Disable
 Modulation tested : GFSK, $\pi/4$ DQPSK, 8DPSK
 Packet Type tested : DH5¹
 Channel tested for non-hopping mode : 2402MHz, 2441MHz, 2480MHz
 Additional measuring procedure : Nil
 Remark : 1) Since the packet size does not affect the output power, DH5 is selected as represented packet size.

6.6.2 Final Result

(a) Maximum peak conducted output power

Maximum peak conducted output power	Limit(s) ¹	Result	Modulation
-1.6dBm	≤21.0dBm	PASS	GFSK

Remark:

- 0.125W (21.0dBm) limit is used for 2/3 20dB bandwidth requirement for channel separation.
- Detail test result and equipment setting refer to Page 32-34.

(b) Maximum peak e.i.r.p.

Maximum peak e.i.r.p. ¹	Limit(s) ²	Result	Modulation
1.72dBm	≤27.0dBm	PASS	GFSK

Remark:

- Maximum peak e.i.r.p. = Maximum peak conducted output power + antenna gain (dBi)
- Maximum peak e.i.r.p. limit = Maximum peak conducted output power limit + 6dBi
- Detail test result and equipment setting refer to Page 32-34.

FCC ID: 2AREB-AIRFLY
 IC: 24385-AIRFLY



TEST REPORT

Report No. : AB0044478(5)

Date : 09 Sep 2022

6.7 Occupied Bandwidth

6.7.1 Measurement

Requirement : FCC Part 15 §15.247(a) and RSS-247 §5.1(a)
Measuring procedure : ANSI C63.10:2013, section 7.8.7 and 6.9.2
Hopping mode : Disable
Modulation tested : GFSK, $\pi/4$ DQPSK
Packet Type tested : DH5¹
Channel tested for non-hopping mode : 2402MHz, 2441MHz, 2480MHz
Additional measuring procedure : Nil
Remark : 1) Since the packet size does not affect the bandwidth, DH5 is selected as represented packet size.

6.7.2 Final Result

20dB bandwidth	99% OBW	Modulation
940.0kHz	880.0kHz	GFSK
1270.0kHz	1170.0kHz	$\pi/4$ DQPSK
1260.0kHz	1160.0kHz	8DPSK

Remark:

1. Detail test result and equipment setting refer to Page 35-52.

FCC ID: 2AREB-AIRFLY
IC: 24385-AIRFLY



TEST REPORT

Report No. : AB0044478(5)

Date : 09 Sep 2022

6.8 Conducted Spurious emission (Transmitter)

6.8.1 Measurement

Requirement	:	FCC Part 15 §15.247(d) and RSS-247 §5.5
Measuring procedure	:	ANSI C63.10:2013, section 5.5, 5.6, 7.8.8 and 11.12.2.1
Hopping mode	:	Disable
RBW	:	Refer to pre-measurement and final measurement setting
Detector	:	Refer to pre-measurement and final measurement setting
Modulation tested	:	GFSK ¹
Packet Type tested	:	DH5 ²
Channel tested for non-hopping mode	:	
Additional measuring procedure	:	1) Setup engineering sample to channel 2402MHz to perform the measurement according to ANSI C63.10, section 7.8.8 with pre-measurement setting 2) If the pre-measurement is over the limit, the final measurement is performed for the specific frequency according to final measurement setting or restricted band frequency 3) For non-restricted band frequency, peak detector and 100kHz RBW will be used for final measurement. 4) Repeat the procedure 1 to 3 for channel frequency of 2441MHz and 2480MHz
Remark	:	1) Since the GFSK generates a higher SPD with power level, GFSK is selected as represented modulation for testing. 2) Since DH5 generates a higher dwell time, DH5 is selected as representative packet size for testing

6.8.2 Final Result

Worst case spurious emission frequency	Worst case spurious emission power ¹	Limit ²	Margin	Result	Worst case mode
7235.MHz	-38.9dBm	-19.7dBm	-19.2dB	PASS	GFSK and DH5

Remark:

1. Spurious emission power = measured conducted power + antenna gain(dBi) +ground reflection factor according to ANSI C63.10 section 11.12.2.2 for restricted band emission.
2. For restricted band emission, limit = restricted band field strength limit (dBuV/m) – 9.54 + 104.75dB according to ANSI C63.10 section 11.12.2.2. For non-restricted band, limit = SPD/100kHz – 20dB.
3. Detail test result and equipment setting refer to Page 64-69.

FCC ID: 2AREB-AIRFLY
IC: 24385-AIRFLY



TEST REPORT

Report No. : AB0044478(5)

Date : 09 Sep 2022

6.9 Radiated Spurious emission (Transmitter)

6.9.1 Measurement

The equipment under test (EUT) was placed on a non-conductive turntable with dimensions of 1.5m x 0.4m and 0.8m high above the ground for below 1GHz measurement and 1.5m high above the ground for above 1GHz measurement. 3m from the EUT, a broadband antenna mounting on the mast received the signal strength. The turntable was rotated to maximize the emission level. The antenna was then moving along the mast from 1m up to 4m until no more higher value was found. Both horizontal and vertical polarization of the antenna were placed and investigated.

For below 30MHz, a loop antenna with its vertical plane is placed 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1 m above the ground.

For 30MHz to 300MHz, biconical antenna with its vertical and horizontal plane is placed 3m from the EUT and rotated about its vertical and horizontal axis for maximum response at each azimuth about the EUT. And the reference point of antenna shall be 1 m above the ground. Same procedure for frequency 300MHz to 1000MHz but Log-periodic antenna is used for final measurements.

For above 1GHz, horn antenna with its vertical and horizontal plane is placed 3m from the EUT and rotated about its vertical and horizontal axis for maximum response at each azimuth about the EUT. Preamplifier and High Pass filter was used for measurements. The reference point of antenna shall be 1 m above the ground.

The device was rotated through three X, Y, Z orthogonal to determine which attitude and configuration produce the highest emission during measurement for Radiated Emission measurement.

The Frequencies from fundamental up to the tenth harmonics were investigated, and emissions more 20dB below limit were not reported.

Bluetooth hopping + charging mode with GFSK modulation and DH5 packet type are selected as worst case mode for spurious radiated emission test from cabinet.

FCC ID: 2AREB-AIRFLY
IC: 24385-AIRFLY

TEST REPORT

Report No. : AB0044478(5)

Date : 09 Sep 2022

6.9.2 Final Result

a) Test mode: Bluetooth + charging

b) c) Polarization	Frequency (MHz)	Reading at 3m (dBμV)	Transducer Factor (dB/m)	Field Strength at 3m ¹ (dBμV/m)	Limit at 3m (dBμV/m)	Margin (dB)	Detector (PK/QP/AV)
H	2398.064	68.9	-6.6	62.3	74.0	-11.7	PK
H	2398.179	60.4	-6.6	53.8	54.0	-0.2	AV
V	2397.977	66.0	-6.6	59.4	74.0	-14.6	PK
V	2398.183	57.0	-6.6	50.4	54.0	-3.6	AV
H	4803.754	52.0	3.1	55.1	74.0	-18.9	PK
H	4804.188	42.9	3.1	46.0	54.0	-8.0	AV
V	4803.768	51.4	3.1	54.5	74.0	-19.5	PK
V	4804.188	42.1	3.1	45.2	54.0	-8.8	AV
H	4881.682	55.8	3.1	58.9	74.0	-15.1	PK
H	4882.180	45.2	3.1	48.3	54.0	-5.7	AV
V	4881.754 ⁴	50.7	3.1	53.8	54.0	-0.2	PK
H	4959.740	58.0	3.1	61.1	74.0	-12.9	PK
H	4960.203	47.8	3.1	50.9	54.0	-3.1	AV
V	4959.855	53.0	3.1	56.1	74.0	-17.9	PK
V	4960.203	39.4	3.1	42.5	54.0	-11.5	AV
H	7205.855 ⁴	37.7	10.7	48.4	54.0	-5.6	PK
V	7206.535 ⁴	39.8	10.7	50.5	54.0	-3.5	PK
H	7322.493 ⁴	40.0	10.7	50.7	54.0	-3.3	PK
V	7322.682 ⁴	41.0	10.7	51.7	54.0	-2.3	PK
H	7439.855	43.5	10.7	54.2	74.0	-19.8	PK
H	7440.188	33.8	10.7	44.5	54.0	-9.5	AV
V	7439.349 ⁴	39.3	10.7	50.0	54.0	-4.0	PK

Remark:

1. Field Strength = Reading + transducer factor.
2. Other emission with more than 20dB margin are not reported in this report.
3. If peak measurement value is lower than average limit, then the measured value will compare with average limit

FCC ID: 2AREB-AIRFLY
IC: 24385-AIRFLY



TEST REPORT

Report No. : AB0044478(5)

Date : 09 Sep 2022

4. The peak measurement value is over the average limit, therefore the peak measurement value is compared with peak limit and need to take average measurement.

FCC ID: 2AREB-AIRFLY
IC: 24385-AIRFLY



TEST REPORT

Report No. : AB0044478(5)

Date : 09 Sep 2022

6.10 Radiated Spurious emission (other mode)

6.10.1 Measurement

The equipment under test (EUT) was placed on a non-conductive turntable with dimensions of 1.5m x 0.4m and 0.8m high above the ground for below 1GHz measurement and 1.5m high above the ground for above 1GHz measurement. 3m from the EUT, a broadband antenna mounting on the mast received the signal strength. The turntable was rotated to maximize the emission level. The antenna was then moving along the mast from 1m up to 4m until no more higher value was found. Both horizontal and vertical polarization of the antenna were placed and investigated.

For below 30MHz, a loop antenna with its vertical plane is placed 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1 m above the ground.

For 30MHz to 300MHz, biconical antenna with its vertical and horizontal plane is placed 3m from the EUT and rotated about its vertical and horizontal axis for maximum response at each azimuth about the EUT. And the reference point of antenna shall be 1 m above the ground. Same procedure for frequency 300MHz to 1000MHz but Log-periodic antenna is used for final measurements.

For above 1GHz, horn antenna with its vertical and horizontal plane is placed 3m from the EUT and rotated about its vertical and horizontal axis for maximum response at each azimuth about the EUT. Preamplifier and High Pass filter was used for measurements. The reference point of antenna shall be 1 m above the ground.

The device was rotated through three X, Y, Z orthogonal to determine which attitude and configuration produce the highest emission during measurement for Radiated Emission measurement.

The Frequencies from fundamental up to the tenth harmonics were investigated, and emissions more 20dB below limit were not reported.

Receiving mode and charging are selected for spurious radiated emission test from cabinet.

FCC ID: 2AREB-AIRFLY
IC: 24385-AIRFLY

TEST REPORT

Report No. : AB0044478(5)

Date : 09 Sep 2022

6.10.2 Final Result

Test mode: Receiving mode + Charging

Polarization	Frequency (MHz)	Reading at 3m (dBμV)	Transducer Factor (dB/m)	Field Strength at 3m ¹ (dBμV/m)	Limit at 3m (dBμV/m)	Margin (dB)	Detector (PK/QP/AV)
H	87.934	8.9	9.0	17.9	40.0	-22.1	QP
V	168.786	6.5	13.3	19.8	43.5	-23.7	QP
H	252.891	10.2	12.5	22.7	46.0	-23.3	QP
V	384.806	14.4	14.6	29.0	46.0	-17.0	QP
H	421.214	12.9	17.3	30.2	46.0	-15.8	QP
V	513.307	10.1	19.4	29.5	46.0	-16.5	QP
H	589.823	11.4	19.4	30.8	46.0	-15.2	QP

Remark:

1. Field Strength = Reading + transducer factor.
2. Other emissions with more than 20dB margin are not reported in this report.

FCC ID: 2AREB-AIRFLY
IC: 24385-AIRFLY



TEST REPORT

Report No. : AB0044478(5)

Date : 09 Sep 2022

6.11 Conducted Emission

6.11.1 Measurement

Requirement : FCC Part 15 §15.207(a) and RSS-Gen, clause 8.8
Measuring procedure : ANSI C63.4:2014, section 7.3
Test mode : Bluetooth + Charging
RBW : 9kHz
VBW : 30kHz
Modulation tested : Nil
Packet Type tested : Nil
Additional measuring procedure : Nil
Remark : Nil

6.11.2 Final Result

Worst case conducted emission frequency	Worst case conducted emission	Limit	Margin	Detector	Lines	Worst case mode	Result
630.5kHz	34.40dBμV	46.00dBμV	-11.60dB	AV	L	Bluetooth + Charging	PASS

Remark:

1. Detail test result and equipment setting refer to Page 70.

FCC ID: 2AREB-AIRFLY
IC: 24385-AIRFLY

TEST REPORT

Report No. : AB0044478(5)

Date : 09 Sep 2022

7.0 Frequency Hopping System Requirement

Test Requirement: Section 15.247(a)(1), (g), (h) and RSS-247, section 5.1 requirement

The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom order list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.


Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmissions bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.

The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hop sets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

Compliance for section 15.247(a)(1)

According to Bluetooth Core Specification, the pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONES; i.e. the shift register is initialized with nine ones.

- Number of shift register stage: 9
- Length of pseudorandom sequence: $2^9-1=511$ bits
- Longest sequence of zero: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence


FCC ID: 2AREB-AIRFLY
IC: 24385-AIRFLY

TEST REPORT

Report No. : AB0044478(5)

Date : 09 Sep 2022

An example of Pseudorandom Frequency Hopping Sequence as following:



Each frequency used equally on the average by each transmitter.

According to Bluetooth Core Specification, Bluetooth receivers are designed to have input and IF bandwidths that match the hopping channel bandwidths of any Bluetooth transmitters and shift frequencies in synchronization with the transmitted signals.

Compliance for section 15.247(g)

According to Bluetooth Core Specification, the Bluetooth system transmits the packet with the pseudorandom hopping frequency with a continuous data and the short burst transmission from the Bluetooth system is also transmitted under the frequency hopping system with the pseudorandom hopping frequency system.

Compliance for section 15.247(h)

According to Bluetooth Core specification, the Bluetooth system incorporates with an adaptive system to detect other user within the spectrum band so that it individually and independently to avoid hopping on the occupied channels.

According to the Bluetooth Core specification, the Bluetooth system is designed not have the ability to coordinate with other FHSS System in effort to avoid the simultaneous occupancy of the individual hopping frequencies by multiple transmitter.

FCC ID: 2AREB-AIRFLY
IC: 24385-AIRFLY



TEST REPORT

Report No. : AB0044478(5)

Date : 09 Sep 2022

8.0 External photo, Internal Photo and Test configuration Photo

The External Photo, Internal Photo and Test Configuration Photo associated with this report for the tested product are saved in separated pdf file listed in the following

File content	File name
External Photo	External photo.pdf
Internal Photo	Internal photo.pdf
Test Configuration Photo	Test setup photo.pdf

FCC ID: 2AREB-AIRFLY
IC: 24385-AIRFLY



TEST REPORT

Report No. : AB0044478(5)

Date : 09 Sep 2022

APPENDIX A Test Result

FCC ID: 2AREB-AIRFLY
IC: 24385-AIRFLY



TEST REPORT

Report No. : AB0044478(5)

Date : 09 Sep 2022

FCC Part 47 §15.247 2400-2483.5 MHz 2020

DUT Information

Frequencies

BT CH 0 (2402 MHz)	BT CH 1 (2403 MHz)	BT CH 2 (2404 MHz)
BT CH 3 (2405 MHz)	BT CH 4 (2406 MHz)	BT CH 5 (2407 MHz)
BT CH 6 (2408 MHz)	BT CH 7 (2409 MHz)	BT CH 8 (2410 MHz)
BT CH 9 (2411 MHz)	BT CH 10 (2412 MHz)	BT CH 11 (2413 MHz)
BT CH 12 (2414 MHz)	BT CH 13 (2415 MHz)	BT CH 14 (2416 MHz)
BT CH 15 (2417 MHz)	BT CH 16 (2418 MHz)	BT CH 17 (2419 MHz)
BT CH 18 (2420 MHz)	BT CH 19 (2421 MHz)	BT CH 20 (2422 MHz)
BT CH 21 (2423 MHz)	BT CH 22 (2424 MHz)	BT CH 23 (2425 MHz)
BT CH 24 (2426 MHz)	BT CH 25 (2427 MHz)	BT CH 26 (2428 MHz)
BT CH 27 (2429 MHz)	BT CH 28 (2430 MHz)	BT CH 29 (2431 MHz)
BT CH 30 (2432 MHz)	BT CH 31 (2433 MHz)	BT CH 32 (2434 MHz)
BT CH 33 (2435 MHz)	BT CH 34 (2436 MHz)	BT CH 35 (2437 MHz)
BT CH 36 (2438 MHz)	BT CH 37 (2439 MHz)	BT CH 38 (2440 MHz)
BT CH 39 (2441 MHz)	BT CH 40 (2442 MHz)	BT CH 41 (2443 MHz)
BT CH 42 (2444 MHz)	BT CH 43 (2445 MHz)	BT CH 44 (2446 MHz)
BT CH 45 (2447 MHz)	BT CH 46 (2448 MHz)	BT CH 47 (2449 MHz)
BT CH 48 (2450 MHz)	BT CH 49 (2451 MHz)	BT CH 50 (2452 MHz)
BT CH 51 (2453 MHz)	BT CH 52 (2454 MHz)	BT CH 53 (2455 MHz)
BT CH 54 (2456 MHz)	BT CH 55 (2457 MHz)	BT CH 56 (2458 MHz)
BT CH 57 (2459 MHz)	BT CH 58 (2460 MHz)	BT CH 59 (2461 MHz)
BT CH 60 (2462 MHz)	BT CH 61 (2463 MHz)	BT CH 62 (2464 MHz)
BT CH 63 (2465 MHz)	BT CH 64 (2466 MHz)	BT CH 65 (2467 MHz)
BT CH 66 (2468 MHz)	BT CH 67 (2469 MHz)	BT CH 68 (2470 MHz)
BT CH 69 (2471 MHz)	BT CH 70 (2472 MHz)	BT CH 71 (2473 MHz)
BT CH 72 (2474 MHz)	BT CH 73 (2475 MHz)	BT CH 74 (2476 MHz)
BT CH 75 (2477 MHz)	BT CH 76 (2478 MHz)	BT CH 77 (2479 MHz)
BT CH 78 (2480 MHz)		

FCC ID: 2AREB-AIRFLY
IC: 24385-AIRFLY



TEST REPORT

Report No. : AB0044478(5)

Date : 09 Sep 2022

Hardware Setup: WMS Measurements\TS8997

Spectrum Analyzer: SA FSV 40 (SA FSV 40) @ VISA (ADR
TCPIP::192.168.48.148::inst0::instr), SN 1321.3008K39/101190,
FW 2.30 SP4

Vector Generator: VG SMBV100A (VG SMBV100A) @ VISA (ADR
TCPIP::192.168.48.149::inst0::instr), SN 262024, FW 3.1.19.8-
3.20.281.28.7

Generator: SMB100A (SMB100A) @ VISA (ADR
TCPIP::192.168.48.152::inst0::instr), SN 103230, FW 3.20.390.24
/ Drv:Rev 2.21.0, 07/2016, CVI 2015

OSP: OSP-B157W (OSP-B157W) @ VISA (ADR
TCPIP::192.168.48.157::inst0::instr), SN 1527.1144.03 / 101057,
FW 1.27.0.0

FCC ID: 2AREB-AIRFLY
IC: 24385-AIRFLY

TEST REPORT

Report No. : AB0044478(5)


Date : 09 Sep 2022

Hopping Frequencies (Hopping; GFSK; DH5)

Channels

Channels	Limit Min	Limit Max	Result
79	15	---	PASS

Sequence



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.40000 GHz	2.40000 GHz
Stop Frequency	2.48350 GHz	2.48350 GHz
Span	83.500 MHz	83.500 MHz
RBW	200.000 kHz	<= 299.000 kHz
VBW	200.000 kHz	>= 200.000 kHz
SweepPoints	418	~ 418
SweepTime	1.060 ms	AUTO
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	132 / max. 150	max. 150
Stable	3 / 3	3

FCC ID: 2AREB-AIRFLY

IC: 24385-AIRFLY



TEST REPORT

Report No. : AB0044478(5)

Date : 09 Sep 2022

Max Stable Difference	0.00 dB	0.50 dB
-----------------------	---------	---------

FCC ID: 2AREB-AIRFLY
IC: 24385-AIRFLY

TEST REPORT

Report No. : AB0044478(5)


Date : 09 Sep 2022

Time of Channel Occupancy (2441 MHz; GFSK; DH1)

Result

DUT Frequency (MHz)	Result	Number of Hops	Average time of occupancy (ms)	Threshold (dBm)
2441.000000	PASS	319	138.720	-20.0

Time of Channel Occupancy



Measurement

Setting	Instrument Value	Target Value
Center Frequency	2.44100 GHz	2.44100 GHz
Span	ZeroSpan	ZeroSpan
RBW	500.000 kHz	~ 500.000 kHz
VBW	1.000 MHz	~ 1.500 MHz
SweepPoints	30001	~ 30001
SweepTime	31.600 s	31.600 s
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	0.000 dB	0.000 dB
Detector	MaxPeak	MaxPeak
SweepCount	1	1
Filter	Channel	Channel
Trace Mode	Clear Write	Clear Write
SweepType	Sweep	AUTO
Preamplifier	off	off
Trigger	External	External
Trigger Offset	0.000 s	0.000 s

OSP

Setting	Instrument Value	Target Value
Measurement Time	31.600 s	31.600 s

FCC ID: 2AREB-AIRFLY

IC: 24385-AIRFLY



TEST REPORT

Report No. : AB0044478(5)

Date : 09 Sep 2022

Tracepoints	31600000	31600000
Time resolution	1.000 μ s	1.000 μ s
Detector	RMS	RMS

FCC ID: 2AREB-AIRFLY
IC: 24385-AIRFLY



TEST REPORT

Report No. : AB0044478(5)


Date : 09 Sep 2022

Time of Channel Occupancy(2) (2441 MHz; GFSK; DH3)

Result

DUT Frequency (MHz)	Result	Number of Hops	Average time of occupancy (ms)	Threshold (dBm)
2441.000000	PASS	153	261.790	-20.0

Time of Channel Occupancy(2)



Measurement

Setting	Instrument Value	Target Value
Center Frequency	2.44100 GHz	2.44100 GHz
Span	ZeroSpan	ZeroSpan
RBW	500.000 kHz	~ 500.000 kHz
VBW	1.000 MHz	~ 1.500 MHz
SweepPoints	30001	~ 30001
SweepTime	31.600 s	31.600 s
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	0.000 dB	0.000 dB
Detector	MaxPeak	MaxPeak
SweepCount	1	1
Filter	Channel	Channel
Trace Mode	Clear Write	Clear Write
SweepType	Sweep	AUTO
Preamp	off	off
Trigger	External	External
Trigger Offset	0.000 s	0.000 s

OSP

Setting	Instrument Value	Target Value
Measurement Time	31.600 s	31.600 s
Tracepoints	31600000	31600000

FCC ID: 2AREB-AIRFLY

IC: 24385-AIRFLY



TEST REPORT

Report No. : AB0044478(5)

Date : 09 Sep 2022

Time resolution	1.000 μ s	1.000 μ s
Detector	RMS	RMS

FCC ID: 2AREB-AIRFLY
IC: 24385-AIRFLY



TEST REPORT

Report No. : AB0044478(5)


Date : 09 Sep 2022

Time of Channel Occupancy(3) (2441 MHz; GFSK; DH5)

Result

DUT Frequency (MHz)	Result	Number of Hops	Average time of occupancy (ms)	Threshold (dBm)
2441.000000	PASS	104	308.390	-20.0

Time of Channel Occupancy(3)



Measurement

Setting	Instrument Value	Target Value
Center Frequency	2.44100 GHz	2.44100 GHz
Span	ZeroSpan	ZeroSpan
RBW	500.000 kHz	~ 500.000 kHz
VBW	1.000 MHz	~ 1.500 MHz
SweepPoints	30001	~ 30001
SweepTime	31.600 s	31.600 s
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	0.000 dB	0.000 dB
Detector	MaxPeak	MaxPeak
SweepCount	1	1
Filter	Channel	Channel
Trace Mode	Clear Write	Clear Write
SweepType	Sweep	AUTO
Preamp	off	off
Trigger	External	External
Trigger Offset	0.000 s	0.000 s

OSP

Setting	Instrument Value	Target Value
Measurement Time	31.600 s	31.600 s
Tracepoints	31600000	31600000

FCC ID: 2AREB-AIRFLY

IC: 24385-AIRFLY



TEST REPORT

Report No. : AB0044478(5)

Date : 09 Sep 2022

Time resolution	1.000 μ s	1.000 μ s
Detector	RMS	RMS

FCC ID: 2AREB-AIRFLY
IC: 24385-AIRFLY



TEST REPORT

Report No. : AB0044478(5)


Date : 09 Sep 2022

RF output power (2402 MHz; GFSK; DH5)

Result

DUT Frequency (MHz)	Peak (dBm)	Limit Max (dBm)	Duty Cycle (%)	Result
2402.000000	-1.5	21.0	76.550	PASS

Gated Trace



FCC ID: 2AREB-AIRFLY
IC: 24385-AIRFLY



TEST REPORT

Report No. : AB0044478(5)


Date : 09 Sep 2022

RF output power (2441 MHz; GFSK; DH5)

Result

DUT Frequency (MHz)	Peak (dBm)	Limit Max (dBm)	DutyCycle (%)	Result
2441.000000	-2.1	21.0	76.550	PASS

Gated Trace



FCC ID: 2AREB-AIRFLY
IC: 24385-AIRFLY



TEST REPORT

Report No. : AB0044478(5)


Date : 09 Sep 2022

RF output power (2480 MHz; GFSK; DH5)

Result

DUT Frequency (MHz)	Peak (dBm)	Limit Max (dBm)	Duty Cycle (%)	Result
2480.000000	-2.5	21.0	76.550	PASS

Gated Trace



FCC ID: 2AREB-AIRFLY
IC: 24385-AIRFLY

TEST REPORT

Report No. : AB0044478(5)


Date : 09 Sep 2022

Emission Bandwidth 20 dB (2402 MHz; GFSK; DH5)

20 dB Bandwidth

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2402.000000	0.935000	---	---	2401.557500	2402.492500

20 dB Bandwidth



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.40100 GHz	2.40100 GHz
Stop Frequency	2.40300 GHz	2.40300 GHz
Span	2.000 MHz	2.000 MHz
RBW	10.000 kHz	>= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	400	~ 400
SweepTime	189.648 μ s	AUTO
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	200	200
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamplifier	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	6 / max. 150	max. 150
Stable	5 / 5	5
Max Stable Difference	0.15 dB	0.50 dB

FCC ID: 2AREB-AIRFLY

IC: 24385-AIRFLY

TEST REPORT

Report No. : AB0044478(5)


Date : 09 Sep 2022

Occupied Channel Bandwidth 99% (2402 MHz; GFSK; DH5)

99 % Bandwidth

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2402.000000	0.880000	---	---	2401.572500	2402.452500

99 % Bandwidth



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.40100 GHz	2.40100 GHz
Stop Frequency	2.40300 GHz	2.40300 GHz
Span	2.000 MHz	2.000 MHz
RBW	10.000 kHz	>= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	400	~ 400
Sweeptime	189.648 μ s	AUTO
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	500	500
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.30 dB	0.30 dB
Run	5 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.16 dB	0.30 dB

FCC ID: 2AREB-AIRFLY

IC: 24385-AIRFLY

TEST REPORT

Report No. : AB0044478(5)


Date : 09 Sep 2022

Emission Bandwidth 20 dB (2441 MHz; GFSK; DH5)

20 dB Bandwidth

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2441.000000	0.940000	---	---	2440.552500	2441.492500

20 dB Bandwidth



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.44000 GHz	2.44000 GHz
Stop Frequency	2.44200 GHz	2.44200 GHz
Span	2.000 MHz	2.000 MHz
RBW	10.000 kHz	>= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	400	~ 400
SweepTime	189.648 μs	AUTO
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	200	200
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	7 / max. 150	max. 150
Stable	5 / 5	5
Max Stable Difference	0.35 dB	0.50 dB

FCC ID: 2AREB-AIRFLY

IC: 24385-AIRFLY



TEST REPORT

Report No. : AB0044478(5)

Date : 09 Sep 2022

FCC ID: 2AREB-AIRFLY
IC: 24385-AIRFLY

TEST REPORT

Report No. : AB0044478(5)


Date : 09 Sep 2022

Occupied Channel Bandwidth 99% (2441 MHz; GFSK; DH5)

99 % Bandwidth

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2441.000000	0.880000	---	---	2440.572500	2441.452500

99 % Bandwidth



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.44000 GHz	2.44000 GHz
Stop Frequency	2.44200 GHz	2.44200 GHz
Span	2.000 MHz	2.000 MHz
RBW	10.000 kHz	>= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	400	~ 400
Sweeptime	189.648 μ s	AUTO
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	500	500
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.30 dB	0.30 dB
Run	6 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.19 dB	0.30 dB

FCC ID: 2AREB-AIRFLY

IC: 24385-AIRFLY

TEST REPORT

Report No. : AB0044478(5)


Date : 09 Sep 2022

Emission Bandwidth 20 dB (2480 MHz; GFSK; DH5)

20 dB Bandwidth

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2480.000000	0.935000	---	---	2479.557500	2480.492500

20 dB Bandwidth



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.47900 GHz	2.47900 GHz
Stop Frequency	2.48100 GHz	2.48100 GHz
Span	2.000 MHz	2.000 MHz
RBW	10.000 kHz	>= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	400	~ 400
SweepTime	189.648 μ s	AUTO
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	200	200
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	8 / max. 150	max. 150
Stable	5 / 5	5
Max Stable Difference	0.17 dB	0.50 dB

FCC ID: 2AREB-AIRFLY

IC: 24385-AIRFLY



TEST REPORT

Report No. : AB0044478(5)

Date : 09 Sep 2022

FCC ID: 2AREB-AIRFLY
IC: 24385-AIRFLY

TEST REPORT

Report No. : AB0044478(5)


Date : 09 Sep 2022

Occupied Channel Bandwidth 99% (2480 MHz; GFSK; DH5)

99 % Bandwidth

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2480.000000	0.880000	---	---	2479.572500	2480.452500

99 % Bandwidth



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.47900 GHz	2.47900 GHz
Stop Frequency	2.48100 GHz	2.48100 GHz
Span	2.000 MHz	2.000 MHz
RBW	10.000 kHz	>= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	400	~ 400
Sweeptime	189.648 μ s	AUTO
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	500	500
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.30 dB	0.30 dB
Run	6 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.11 dB	0.30 dB

FCC ID: 2AREB-AIRFLY

IC: 24385-AIRFLY

TEST REPORT

Report No. : AB0044478(5)


Date : 09 Sep 2022

Emission Bandwidth 20 dB (2402 MHz; $\pi/4$ DQPSK; 2DH5)

20 dB Bandwidth

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2402.000000	1.270000	---	---	2401.375000	2402.645000

20 dB Bandwidth



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.40070 GHz	2.40070 GHz
Stop Frequency	2.40330 GHz	2.40330 GHz
Span	2.600 MHz	2.600 MHz
RBW	20.000 kHz	≥ 13.000 kHz
VBW	100.000 kHz	≥ 60.000 kHz
SweepPoints	260	~ 260
SweepTime	94.727 μ s	AUTO
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	200	200
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	8 / max. 150	max. 150
Stable	5 / 5	5
Max Stable Difference	0.17 dB	0.50 dB

FCC ID: 2AREB-AIRFLY

IC: 24385-AIRFLY



TEST REPORT

Report No. : AB0044478(5)

Date : 09 Sep 2022

FCC ID: 2AREB-AIRFLY
IC: 24385-AIRFLY

TEST REPORT

Report No. : AB0044478(5)


Date : 09 Sep 2022

Occupied Channel Bandwidth 99% (2402 MHz; $\pi/4$ DQPSK; 2DH5)

99 % Bandwidth

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2402.000000	1.170000	---	---	2401.425000	2402.595000

99 % Bandwidth



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.40070 GHz	2.40070 GHz
Stop Frequency	2.40330 GHz	2.40330 GHz
Span	2.600 MHz	2.600 MHz
RBW	20.000 kHz	≥ 13.000 kHz
VBW	100.000 kHz	≥ 60.000 kHz
SweepPoints	260	~ 260
SweepTime	94.727 μ s	AUTO
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	500	500
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamplifier	off	off
Stablemode	Trace	Trace
Stablevalue	0.30 dB	0.30 dB
Run	7 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.09 dB	0.30 dB

FCC ID: 2AREB-AIRFLY

IC: 24385-AIRFLY

TEST REPORT

Report No. : AB0044478(5)


Date : 09 Sep 2022

Emission Bandwidth 20 dB (2441 MHz; $\pi/4$ DQPSK; 2DH5)

20 dB Bandwidth

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2441.000000	1.270000	---	---	2440.375000	2441.645000

20 dB Bandwidth



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.43970 GHz	2.43970 GHz
Stop Frequency	2.44230 GHz	2.44230 GHz
Span	2.600 MHz	2.600 MHz
RBW	20.000 kHz	≥ 13.000 kHz
VBW	100.000 kHz	≥ 60.000 kHz
SweepPoints	260	~ 260
SweepTime	94.727 μ s	AUTO
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	200	200
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	10 / max. 150	max. 150
Stable	5 / 5	5
Max Stable Difference	0.17 dB	0.50 dB

FCC ID: 2AREB-AIRFLY

IC: 24385-AIRFLY



TEST REPORT

Report No. : AB0044478(5)

Date : 09 Sep 2022

FCC ID: 2AREB-AIRFLY
IC: 24385-AIRFLY

TEST REPORT

Report No. : AB0044478(5)


Date : 09 Sep 2022

Occupied Channel Bandwidth 99% (2441 MHz; $\pi/4$ DQPSK; 2DH5)

99 % Bandwidth

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2441.000000	1.170000	---	---	2440.425000	2441.595000

99 % Bandwidth



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.43970 GHz	2.43970 GHz
Stop Frequency	2.44230 GHz	2.44230 GHz
Span	2.600 MHz	2.600 MHz
RBW	20.000 kHz	≥ 13.000 kHz
VBW	100.000 kHz	≥ 60.000 kHz
SweepPoints	260	~ 260
SweepTime	94.727 μ s	AUTO
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	500	500
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.30 dB	0.30 dB
Run	8 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.07 dB	0.30 dB

FCC ID: 2AREB-AIRFLY

IC: 24385-AIRFLY

TEST REPORT

Report No. : AB0044478(5)


Date : 09 Sep 2022

Emission Bandwidth 20 dB (2480 MHz; $\pi/4$ DQPSK; 2DH5)

20 dB Bandwidth

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2480.000000	1.270000	---	---	2479.375000	2480.645000

20 dB Bandwidth



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.47870 GHz	2.47870 GHz
Stop Frequency	2.48130 GHz	2.48130 GHz
Span	2.600 MHz	2.600 MHz
RBW	20.000 kHz	≥ 13.000 kHz
VBW	100.000 kHz	≥ 60.000 kHz
SweepPoints	260	~ 260
SweepTime	94.727 μ s	AUTO
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	200	200
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	9 / max. 150	max. 150
Stable	5 / 5	5
Max Stable Difference	0.07 dB	0.50 dB

FCC ID: 2AREB-AIRFLY

IC: 24385-AIRFLY

TEST REPORT

Report No. : AB0044478(5)


Date : 09 Sep 2022

Occupied Channel Bandwidth 99% (2480 MHz; $\pi/4$ DQPSK; 2DH5)

99 % Bandwidth

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2480.000000	1.170000	---	---	2479.425000	2480.595000

99 % Bandwidth



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.47870 GHz	2.47870 GHz
Stop Frequency	2.48130 GHz	2.48130 GHz
Span	2.600 MHz	2.600 MHz
RBW	20.000 kHz	≥ 13.000 kHz
VBW	100.000 kHz	≥ 60.000 kHz
SweepPoints	260	~ 260
SweepTime	94.727 μ s	AUTO
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	500	500
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamplifier	off	off
Stablemode	Trace	Trace
Stablevalue	0.30 dB	0.30 dB
Run	5 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.14 dB	0.30 dB

FCC ID: 2AREB-AIRFLY

IC: 24385-AIRFLY

TEST REPORT

Report No. : AB0044478(5)


Date : 09 Sep 2022

Emission Bandwidth 20 dB (2402 MHz; 8DPSK; 3DH5)

20 dB Bandwidth

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2402.000000	1.260000	---	---	2401.375000	2402.635000

20 dB Bandwidth



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.40070 GHz	2.40070 GHz
Stop Frequency	2.40330 GHz	2.40330 GHz
Span	2.600 MHz	2.600 MHz
RBW	20.000 kHz	>= 13.000 kHz
VBW	100.000 kHz	>= 60.000 kHz
SweepPoints	260	~ 260
Sweeptime	94.727 μ s	AUTO
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	200	200
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	9 / max. 150	max. 150
Stable	5 / 5	5
Max Stable Difference	0.12 dB	0.50 dB

FCC ID: 2AREB-AIRFLY

IC: 24385-AIRFLY



TEST REPORT

Report No. : AB0044478(5)

Date : 09 Sep 2022

FCC ID: 2AREB-AIRFLY
IC: 24385-AIRFLY

TEST REPORT

Report No. : AB0044478(5)


Date : 09 Sep 2022

Occupied Channel Bandwidth 99% (2402 MHz; 8DPSK; 8DH5)

99 % Bandwidth

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2402.000000	1.160000	---	---	2401.435000	2402.595000

99 % Bandwidth



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.40070 GHz	2.40070 GHz
Stop Frequency	2.40330 GHz	2.40330 GHz
Span	2.600 MHz	2.600 MHz
RBW	20.000 kHz	>= 13.000 kHz
VBW	100.000 kHz	>= 60.000 kHz
SweepPoints	260	~ 260
SweepTime	94.727 µs	AUTO
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	500	500
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamplifier	off	off
Stablemode	Trace	Trace
Stablevalue	0.30 dB	0.30 dB
Run	7 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.24 dB	0.30 dB

FCC ID: 2AREB-AIRFLY

IC: 24385-AIRFLY

TEST REPORT

Report No. : AB0044478(5)


Date : 09 Sep 2022

Emission Bandwidth 20 dB (2441 MHz; 8DPSK; 3DH5)

20 dB Bandwidth

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2441.000000	1.260000	---	---	2440.375000	2441.635000

20 dB Bandwidth



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.43970 GHz	2.43970 GHz
Stop Frequency	2.44230 GHz	2.44230 GHz
Span	2.600 MHz	2.600 MHz
RBW	20.000 kHz	>= 13.000 kHz
VBW	100.000 kHz	>= 60.000 kHz
SweepPoints	260	~ 260
SweepTime	94.727 μ s	AUTO
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	200	200
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	13 / max. 150	max. 150
Stable	5 / 5	5
Max Stable Difference	0.00 dB	0.50 dB

FCC ID: 2AREB-AIRFLY

IC: 24385-AIRFLY



TEST REPORT

Report No. : AB0044478(5)

Date : 09 Sep 2022

FCC ID: 2AREB-AIRFLY
IC: 24385-AIRFLY

TEST REPORT

Report No. : AB0044478(5)


Date : 09 Sep 2022

Occupied Channel Bandwidth 99% (2441 MHz; 8DPSK; 3DH5)

99 % Bandwidth

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2441.000000	1.170000	---	---	2440.425000	2441.595000

99 % Bandwidth



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.43970 GHz	2.43970 GHz
Stop Frequency	2.44230 GHz	2.44230 GHz
Span	2.600 MHz	2.600 MHz
RBW	20.000 kHz	>= 13.000 kHz
VBW	100.000 kHz	>= 60.000 kHz
SweepPoints	260	~ 260
Sweeptime	94.727 μ s	AUTO
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	500	500
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.30 dB	0.30 dB
Run	8 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.07 dB	0.30 dB

FCC ID: 2AREB-AIRFLY

IC: 24385-AIRFLY

TEST REPORT

Report No. : AB0044478(5)


Date : 09 Sep 2022

Emission Bandwidth 20 dB (2480 MHz; 8DPSK; 3DH5)

20 dB Bandwidth

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2480.000000	1.260000	---	---	2479.375000	2480.635000

20 dB Bandwidth



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.47870 GHz	2.47870 GHz
Stop Frequency	2.48130 GHz	2.48130 GHz
Span	2.600 MHz	2.600 MHz
RBW	20.000 kHz	>= 13.000 kHz
VBW	100.000 kHz	>= 60.000 kHz
SweepPoints	260	~ 260
Sweeptime	94.727 μ s	AUTO
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	200	200
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	9 / max. 150	max. 150
Stable	5 / 5	5
Max Stable Difference	0.07 dB	0.50 dB

FCC ID: 2AREB-AIRFLY

IC: 24385-AIRFLY

TEST REPORT

Report No. : AB0044478(5)


Date : 09 Sep 2022

Occupied Channel Bandwidth 99% (2480 MHz; 8DPSK; 3DH5)

99 % Bandwidth

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2480.000000	1.160000	---	---	2479.435000	2480.595000

99 % Bandwidth



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.47870 GHz	2.47870 GHz
Stop Frequency	2.48130 GHz	2.48130 GHz
Span	2.600 MHz	2.600 MHz
RBW	20.000 kHz	>= 13.000 kHz
VBW	100.000 kHz	>= 60.000 kHz
SweepPoints	260	~ 260
SweepTime	94.727 µs	AUTO
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	500	500
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamplifier	off	off
Stablemode	Trace	Trace
Stablevalue	0.30 dB	0.30 dB
Run	6 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.19 dB	0.30 dB

FCC ID: 2AREB-AIRFLY

IC: 24385-AIRFLY

TEST REPORT

Report No. : AB0044478(5)


Date : 09 Sep 2022

Carrier Frequency Separation (2402 MHz; GFSK; DH5)

Result

DUT Frequency (MHz)	Frequency Separation (MHz)	Limit Min (MHz)	Limit Max (MHz)	Center Frequency low Channel (MHz)	Center Frequency high Channel (MHz)
2402.000000	1.009900	0.623333	---	2401.995050	2403.004950

CFS



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.40100 GHz	2.40100 GHz
Stop Frequency	2.40400 GHz	2.40400 GHz
Span	3.000 MHz	3.000 MHz
RBW	300.000 kHz	<= 300.000 kHz
VBW	300.000 kHz	>= 300.000 kHz
SweepPoints	101	~ 10
SweepTime	1.000 ms	AUTO
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	200	200
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	Sweep
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	20 / max. 150	max. 150
Stable	10 / 10	10
Max Stable Difference	0.11 dB	0.50 dB

FCC ID: 2AREB-AIRFLY

IC: 24385-AIRFLY



TEST REPORT

Report No. : AB0044478(5)

Date : 09 Sep 2022

FCC ID: 2AREB-AIRFLY
IC: 24385-AIRFLY

TEST REPORT

Report No. : AB0044478(5)


Date : 09 Sep 2022

Carrier Frequency Separation (2441 MHz; GFSK; DH5)

Result

DUT Frequency (MHz)	Frequency Separation (MHz)	Limit Min (MHz)	Limit Max (MHz)	Center Frequency low Channel (MHz)	Center Frequency high Channel (MHz)
2441.000000	1.009900	0.626667	---	2440.995050	2442.004950

CFS



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.44000 GHz	2.44000 GHz
Stop Frequency	2.44300 GHz	2.44300 GHz
Span	3.000 MHz	3.000 MHz
RBW	300.000 kHz	<= 300.000 kHz
VBW	300.000 kHz	>= 300.000 kHz
SweepPoints	101	~ 10
SweepTime	1.000 ms	AUTO
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	200	200
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	Sweep
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	14 / max. 150	max. 150
Stable	10 / 10	10
Max Stable Difference	0.17 dB	0.50 dB

FCC ID: 2AREB-AIRFLY

IC: 24385-AIRFLY



TEST REPORT

Report No. : AB0044478(5)

Date : 09 Sep 2022

FCC ID: 2AREB-AIRFLY
IC: 24385-AIRFLY

TEST REPORT

Report No. : AB0044478(5)


Date : 09 Sep 2022

Carrier Frequency Separation (2480 MHz; GFSK; DH5)

Result

DUT Frequency (MHz)	Frequency Separation (MHz)	Limit Min (MHz)	Limit Max (MHz)	Center Frequency low Channel (MHz)	Center Frequency high Channel (MHz)
2480.000000	0.980198	0.623333	---	2479.024752	2480.004950

CFS



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.47800 GHz	2.47800 GHz
Stop Frequency	2.48100 GHz	2.48100 GHz
Span	3.000 MHz	3.000 MHz
RBW	300.000 kHz	<= 300.000 kHz
VBW	300.000 kHz	>= 300.000 kHz
SweepPoints	101	~ 10
SweepTime	1.000 ms	AUTO
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	200	200
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	Sweep
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	15 / max. 150	max. 150
Stable	10 / 10	10
Max Stable Difference	0.00 dB	0.50 dB

FCC ID: 2AREB-AIRFLY

IC: 24385-AIRFLY



TEST REPORT

Report No. : AB0044478(5)

Date : 09 Sep 2022

FCC ID: 2AREB-AIRFLY
IC: 24385-AIRFLY



TEST REPORT

Report No. : AB0044478(5)

Date : 09 Sep 2022

Band Edge low (Hopping; GFSK; DH5)

Result

DUT Frequency (MHz)	Result
hopping	PASS

Inband Peak

Frequency (MHz)	Level (dBm)
2445.175000	-4.7

Measurements

Frequency (MHz)	Level (dBm)	Margin (dB)	Limit (dBm)	Result
2383.125000	-49.4	21.3	-28.1	PASS
2345.475000	-49.6	21.5	-28.1	PASS
2383.075000	-49.7	21.5	-28.1	PASS
2351.075000	-49.9	21.8	-28.1	PASS
2345.425000	-50.1	22.0	-28.1	PASS
2398.075000	-50.1	22.0	-28.1	PASS
2351.025000	-50.1	22.0	-28.1	PASS
2398.125000	-50.1	22.0	-28.1	PASS
2380.875000	-50.3	22.2	-28.1	PASS
2380.825000	-50.3	22.2	-28.1	PASS
2385.825000	-50.5	22.4	-28.1	PASS
2383.175000	-50.5	22.4	-28.1	PASS
2345.525000	-50.5	22.4	-28.1	PASS
2388.775000	-50.8	22.6	-28.1	PASS
2398.025000	-50.8	22.7	-28.1	PASS

FCC ID: 2AREB-AIRFLY
IC: 24385-AIRFLY




TEST REPORT

Report No. : AB0044478(5)

Date : 09 Sep 2022

Band Edge



FCC ID: 2AREB-AIRFLY
IC: 24385-AIRFLY



TEST REPORT

Report No. : AB0044478(5)

Date : 09 Sep 2022

Measurement 1

Setting	Instrument Value	Target Value
Start Frequency	2.31000 GHz	2.31000 GHz
Stop Frequency	2.40000 GHz	2.40000 GHz
Span	90.000 MHz	90.000 MHz
RBW	100.000 kHz	<= 100.000 kHz
VBW	300.000 kHz	>= 300.000 kHz
SweepPoints	1800	~ 1800
SweepTime	1.800 ms	AUTO
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	22 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.00 dB	0.50 dB

Measurement 2

Setting	Instrument Value	Target Value
Start Frequency	2.40000 GHz	2.40000 GHz
Stop Frequency	2.48350 GHz	2.48350 GHz
Span	83.500 MHz	83.500 MHz
RBW	100.000 kHz	<= 100.000 kHz
VBW	300.000 kHz	>= 300.000 kHz
SweepPoints	1670	~ 1670
SweepTime	1.670 ms	AUTO
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	66 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.00 dB	0.50 dB

FCC ID: 2AREB-AIRFLY
IC: 24385-AIRFLY



TEST REPORT

Report No. : AB0044478(5)

Date : 09 Sep 2022

Band Edge high (Hopping; GFSK; DH5)

Result

DUT Frequency (MHz)	Result
hopping	PASS

Inband Peak

Frequency (MHz)	Level (dBm)
2431.875000	0.4

Measurements

Frequency (MHz)	Level (dBm)	Margin (dB)	Limit (dBm)	Result
2484.475000	-47.9	18.3	-29.6	PASS
2484.525000	-48.7	19.1	-29.6	PASS
2491.075000	-49.0	19.4	-29.6	PASS
2484.425000	-49.0	19.4	-29.6	PASS
2491.125000	-49.0	19.4	-29.6	PASS
2493.025000	-50.2	20.6	-29.6	PASS
2489.425000	-50.3	20.7	-29.6	PASS
2492.975000	-50.4	20.8	-29.6	PASS
2495.975000	-50.4	20.8	-29.6	PASS
2489.475000	-50.4	20.8	-29.6	PASS
2483.875000	-50.6	21.0	-29.6	PASS
2496.025000	-50.7	21.1	-29.6	PASS
2485.775000	-50.7	21.1	-29.6	PASS
2490.525000	-50.8	21.2	-29.6	PASS
2490.075000	-50.8	21.2	-29.6	PASS


FCC ID: 2AREB-AIRFLY
IC: 24385-AIRFLY

TEST REPORT

Report No. : AB0044478(5)

Date : 09 Sep 2022

Band Edge



FCC ID: 2AREB-AIRFLY
IC: 24385-AIRFLY



TEST REPORT

Report No. : AB0044478(5)

Date : 09 Sep 2022

Measurement 1

Setting	Instrument Value	Target Value
Start Frequency	2.40000 GHz	2.40000 GHz
Stop Frequency	2.48350 GHz	2.48350 GHz
Span	83.500 MHz	83.500 MHz
RBW	100.000 kHz	<= 100.000 kHz
VBW	300.000 kHz	>= 300.000 kHz
SweepPoints	1670	~ 1670
SweepTime	1.670 ms	AUTO
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	81 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.00 dB	0.50 dB

Measurement 2

Setting	Instrument Value	Target Value
Start Frequency	2.48350 GHz	2.48350 GHz
Stop Frequency	2.50000 GHz	2.50000 GHz
Span	16.500 MHz	16.500 MHz
RBW	100.000 kHz	<= 100.000 kHz
VBW	300.000 kHz	>= 300.000 kHz
SweepPoints	330	~ 330
SweepTime	37.969 μ s	AUTO
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	6 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.00 dB	0.50 dB

FCC ID: 2AREB-AIRFLY
IC: 24385-AIRFLY



TEST REPORT

Report No. : AB0044478(5)

Date : 09 Sep 2022

Band Edge low (2402 MHz; GFSK; DH5)

Result

DUT Frequency (MHz)	Result
2402.000000	PASS

Inband Peak

Frequency (MHz)	Level (dBm)
2401.875000	2.1

Measurements

Frequency (MHz)	Level (dBm)	Margin (dB)	Limit (dBm)	Result
2381.375000	-47.1	19.2	-27.9	PASS
2381.275000	-47.2	19.3	-27.9	PASS
2381.425000	-47.4	19.5	-27.9	PASS
2380.325000	-47.5	19.6	-27.9	PASS
2341.075000	-47.7	19.9	-27.9	PASS
2380.675000	-47.8	19.9	-27.9	PASS
2380.725000	-47.8	19.9	-27.9	PASS
2380.925000	-47.8	19.9	-27.9	PASS
2382.025000	-47.9	20.0	-27.9	PASS
2380.875000	-47.9	20.0	-27.9	PASS
2381.975000	-47.9	20.1	-27.9	PASS
2381.075000	-48.0	20.1	-27.9	PASS
2343.675000	-48.2	20.3	-27.9	PASS
2381.125000	-48.3	20.4	-27.9	PASS
2380.375000	-48.3	20.4	-27.9	PASS

FCC ID: 2AREB-AIRFLY
IC: 24385-AIRFLY




TEST REPORT

Report No. : AB0044478(5)

Date : 09 Sep 2022

Band Edge



FCC ID: 2AREB-AIRFLY
IC: 24385-AIRFLY



TEST REPORT

Report No. : AB0044478(5)

Date : 09 Sep 2022

Measurement 1

Setting	Instrument Value	Target Value
Start Frequency	2.31000 GHz	2.31000 GHz
Stop Frequency	2.40000 GHz	2.40000 GHz
Span	90.000 MHz	90.000 MHz
RBW	100.000 kHz	<= 100.000 kHz
VBW	300.000 kHz	>= 300.000 kHz
SweepPoints	1800	~ 1800
SweepTime	1.800 ms	AUTO
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	37 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.00 dB	0.50 dB

Measurement 2

Setting	Instrument Value	Target Value
Start Frequency	2.40000 GHz	2.40000 GHz
Stop Frequency	2.48350 GHz	2.48350 GHz
Span	83.500 MHz	83.500 MHz
RBW	100.000 kHz	<= 100.000 kHz
VBW	300.000 kHz	>= 300.000 kHz
SweepPoints	1670	~ 1670
SweepTime	1.670 ms	AUTO
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	8 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.28 dB	0.50 dB

FCC ID: 2AREB-AIRFLY
IC: 24385-AIRFLY



TEST REPORT

Report No. : AB0044478(5)

Date : 09 Sep 2022

Band Edge high (2480 MHz; GFSK; DH5)

Result

DUT Frequency (MHz)	Result
2480.000000	PASS

Inband Peak

Frequency (MHz)	Level (dBm)
2479.875000	1.0

Measurements

Frequency (MHz)	Level (dBm)	Margin (dB)	Limit (dBm)	Result
2491.375000	-50.3	21.2	-29.0	PASS
2496.775000	-50.4	21.3	-29.0	PASS
2496.825000	-50.4	21.3	-29.0	PASS
2497.025000	-50.6	21.5	-29.0	PASS
2496.975000	-50.6	21.6	-29.0	PASS
2497.275000	-50.6	21.6	-29.0	PASS
2497.175000	-50.7	21.6	-29.0	PASS
2497.075000	-50.9	21.9	-29.0	PASS
2497.225000	-50.9	21.9	-29.0	PASS
2491.425000	-51.0	21.9	-29.0	PASS
2497.425000	-51.1	22.1	-29.0	PASS
2491.475000	-51.2	22.2	-29.0	PASS
2491.275000	-51.3	22.2	-29.0	PASS
2491.325000	-51.4	22.3	-29.0	PASS
2497.325000	-51.4	22.4	-29.0	PASS


FCC ID: 2AREB-AIRFLY
IC: 24385-AIRFLY

TEST REPORT

Report No. : AB0044478(5)

Date : 09 Sep 2022

Band Edge



FCC ID: 2AREB-AIRFLY
IC: 24385-AIRFLY



TEST REPORT

Report No. : AB0044478(5)

Date : 09 Sep 2022

Measurement 1

Setting	Instrument Value	Target Value
Start Frequency	2.40000 GHz	2.40000 GHz
Stop Frequency	2.48350 GHz	2.48350 GHz
Span	83.500 MHz	83.500 MHz
RBW	100.000 kHz	<= 100.000 kHz
VBW	300.000 kHz	>= 300.000 kHz
SweepPoints	1670	~ 1670
SweepTime	1.670 ms	AUTO
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	10 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.02 dB	0.50 dB

Measurement 2

Setting	Instrument Value	Target Value
Start Frequency	2.48350 GHz	2.48350 GHz
Stop Frequency	2.50000 GHz	2.50000 GHz
Span	16.500 MHz	16.500 MHz
RBW	100.000 kHz	<= 100.000 kHz
VBW	300.000 kHz	>= 300.000 kHz
SweepPoints	330	~ 330
SweepTime	37.969 μ s	AUTO
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	17 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.00 dB	0.50 dB

FCC ID: 2AREB-AIRFLY
IC: 24385-AIRFLY



TEST REPORT

Report No. : AB0044478(5)

Date : 09 Sep 2022

Tx Spurious Emission (2402 MHz; GFSK; DH5)

Result Inband Peak

Frequency (MHz)	Level (dBm)
2402.000	1.5

Final measurements

Frequency (MHz)	Level Pre Measurement (dBm)	level (dBm)	Limit (dBm)	Margin (dB)	Result
---	---	---	---	---	---

Pre Measurements

Frequency (MHz)	Level (dBm)	Margin (dB)	Limit (dBm)
7205.789099	-39.3	19.8	-19.5
4807.166065	-41.6	22.1	-19.5
2385.063025	-48.2	28.6	-19.5
2375.105042	-48.3	28.7	-19.5
2335.273109	-48.4	28.9	-19.5
2345.231092	-49.2	29.7	-19.5
2365.147059	-49.4	29.9	-19.5
2325.315126	-49.8	30.3	-19.5
2355.189076	-50.3	30.8	-19.5
2395.021008	-52.5	33.0	-19.5
2315.357143	-52.5	33.0	-19.5
2488.497131	-53.0	33.5	-19.5
2305.399160	-57.1	37.6	-19.5
9604.412133	-58.2	38.7	-19.5
2165.987395	-58.7	39.1	-19.5

Measurement Settings

Start Frequency (MHz)	Stop Frequency (MHz)	Pre Measurement	Final Measurement
30.000000	2400.000000	1	1
2400.000000	2483.500000	1	1
2483.500000	26000.000000	1	1


FCC ID: 2AREB-AIRFLY
IC: 24385-AIRFLY

TEST REPORT

Report No. : AB0044478(5)

Date : 09 Sep 2022

Spurious



— Limit — Sum Level - - - Threshold x Critical x Final Critical

Pre Measurement 1

Setting	Instrument Value	Target Value
RBW	100.000 kHz	<= 100.000 kHz
VBW	300.000 kHz	>= 300.000 kHz
SweepPoints	238	~ 238
SweepTime	23.700 ms	AUTO
Reference Level	-30.000 dBm	-30.000 dBm
Attenuation	0.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	3	3
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	12 / max. 40	max. 40
Stable	3 / 3	3
Max Stable Difference	0.00 dB	0.50 dB

FCC ID: 2AREB-AIRFLY
IC: 24385-AIRFLY



TEST REPORT

Report No. : AB0044478(5)

Date : 09 Sep 2022

Tx Spurious Emission (2441 MHz; GFSK;DH5)

Result Inband Peak

Frequency (MHz)	Level (dBm)
2441.000	1.3

Final measurements

Frequency (MHz)	Level Pre Measurement (dBm)	level (dBm)	Limit (dBm)	Margin (dB)	Result
---	---	---	---	---	---

Pre Measurements

Frequency (MHz)	Level (dBm)	Margin (dB)	Limit (dBm)
7325.720251	-38.9	19.2	-19.7
4887.120166	-42.7	23.0	-19.7
4877.125903	-43.5	23.8	-19.7
2488.497131	-46.5	26.8	-19.7
2498.491394	-47.0	27.3	-19.7
2508.485657	-47.4	27.7	-19.7
2518.479919	-47.6	27.9	-19.7
2375.105042	-49.0	29.3	-19.7
2385.063025	-49.6	29.9	-19.7
2395.021008	-49.9	30.2	-19.7
2365.147059	-50.2	30.5	-19.7
2355.189076	-52.9	33.2	-19.7
2528.474182	-53.0	33.3	-19.7
2345.231092	-57.3	37.6	-19.7
9764.320336	-58.1	38.4	-19.7

Measurement Settings

Start Frequency (MHz)	Stop Frequency (MHz)	Pre Measurement	Final Measurement
30.000000	2400.000000	1	1
2400.000000	2483.500000	1	1
2483.500000	26000.000000	1	1


FCC ID: 2AREB-AIRFLY
IC: 24385-AIRFLY

TEST REPORT

Report No. : AB0044478(5)

Date : 09 Sep 2022

Spurious



— Limit — Sum Level - - - Threshold × Critical × Final Critical

Pre Measurement 1

Setting	Instrument Value	Target Value
RBW	100.000 kHz	<= 100.000 kHz
VBW	300.000 kHz	>= 300.000 kHz
SweepPoints	238	~ 238
SweepTime	23.700 ms	AUTO
Reference Level	-30.000 dBm	-30.000 dBm
Attenuation	0.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	3	3
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	8 / max. 40	max. 40
Stable	3 / 3	3
Max Stable Difference	0.00 dB	0.50 dB

FCC ID: 2AREB-AIRFLY
IC: 24385-AIRFLY



TEST REPORT

Report No. : AB0044478(5)

Date : 09 Sep 2022

Tx Spurious Emission (2480 MHz; GFSK;DH5)

Result Inband Peak

Frequency (MHz)	Level (dBm)
2480.000	-5.9

Final measurements

Frequency (MHz)	Level Pre Measurement (dBm)	level (dBm)	Limit (dBm)	Margin (dB)	Result
---	---	---	---	---	---

Pre Measurements

Frequency (MHz)	Level (dBm)	Margin (dB)	Limit (dBm)
7435.657140	-40.2	10.6	-29.5
4957.080004	-44.4	14.8	-29.5
2538.468445	-46.5	17.0	-29.5
2528.474182	-48.0	18.5	-29.5
2548.462707	-48.3	18.8	-29.5
2518.479919	-48.5	18.9	-29.5
2558.456970	-49.0	19.4	-29.5
2488.497131	-50.9	21.4	-29.5
2498.491394	-51.6	22.0	-29.5
2508.485657	-53.0	23.5	-29.5
2395.021008	-53.4	23.9	-29.5
2568.451232	-54.6	25.0	-29.5
2385.063025	-56.5	27.0	-29.5
9924.228538	-57.7	28.2	-29.5
19838.537080	-57.9	28.4	-29.5

Measurement Settings

Start Frequency (MHz)	Stop Frequency (MHz)	Pre Measurement	Final Measurement
30.000000	2400.000000	1	1
2400.000000	2483.500000	1	1
2483.500000	26000.000000	1	1


FCC ID: 2AREB-AIRFLY
IC: 24385-AIRFLY

TEST REPORT

Report No. : AB0044478(5)

Date : 09 Sep 2022

Spurious



— Limit — Sum Level - - - Threshold x Critical x Final Critical

Pre Measurement 1

Setting	Instrument Value	Target Value
RBW	100.000 kHz	<= 100.000 kHz
VBW	300.000 kHz	>= 300.000 kHz
SweepPoints	238	~ 238
SweepTime	23.700 ms	AUTO
Reference Level	-30.000 dBm	-30.000 dBm
Attenuation	0.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	3	3
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	12 / max. 40	max. 40
Stable	3 / 3	3
Max Stable Difference	0.00 dB	0.50 dB

FCC ID: 2AREB-AIRFLY
IC: 24385-AIRFLY




TEST REPORT

Report No. : AB0044478(5)

Date : 09 Sep 2022

Conducted Emission

Test mode: Bluetooth + Charging



FCC ID: 2AREB-AIRFLY
IC: 24385-AIRFLY



TEST REPORT

Report No. : AB0044478(5)

Date : 09 Sep 2022

EDIT PEAK LIST (Final Measurement Results)				
Trace1:	FCC-QP			
Trace2:	FCC-AV			
Trace3:	---			
TRACE	FREQUENCY	LEVEL dBµV		DELTA LIMIT dB
1 Quasi Peak	249 kHz	42.66	N gnd	-19.12
2 Average	253.5 kHz	34.28	L1 gnd	-17.36
2 Average	379.5 kHz	34.37	L1 gnd	-13.91
1 Quasi Peak	384 kHz	41.03	L1 gnd	-17.15
1 Quasi Peak	630.5 kHz	36.63	L1 gnd	-19.36
2 Average	630.5 kHz	34.40	L1 gnd	-11.60
1 Quasi Peak	1.0085 MHz	33.92	L1 gnd	-22.07
2 Average	1.0085 MHz	25.02	L1 gnd	-20.97
1 Quasi Peak	1.517 MHz	33.14	L1 gnd	-22.85
2 Average	1.517 MHz	25.44	L1 gnd	-20.55
2 Average	2.282 MHz	24.47	L1 gnd	-21.52
1 Quasi Peak	2.7725 MHz	28.62	L1 gnd	-27.37
1 Quasi Peak	3.9065 MHz	24.46	L1 gnd	-31.53
2 Average	4.0595 MHz	21.49	L1 gnd	-24.50
1 Quasi Peak	10.1255 MHz	28.46	N gnd	-31.53
2 Average	10.229 MHz	17.56	N gnd	-32.43
2 Average	17.537 MHz	36.07	N gnd	-13.92
1 Quasi Peak	17.5775 MHz	47.58	L1 gnd	-12.41
2 Average	17.7395 MHz	36.12	N gnd	-13.87
1 Quasi Peak	17.8295 MHz	47.90	L1 gnd	-12.10

FCC ID: 2AREB-AIRFLY
IC: 24385-AIRFLY