


RF Exposure report

Report No.: HP190830DC001-FWL**FCC ID:** 2ARER-SA10**Product Name** Nooie Smart Power Strip**Test Model:** SA10**Received Date:** N/A**Test Date:** 2019-8-30~2019-9-18**Issued Date:** 2019-9-30**Applicant Name:** Shenzhen Apeman Innovations Technology Co.,Ltd**Applicant Address:** Building P11, Huanancheng, Longgang District, Shenzhen, China**Issued By:** Hwa-Hsing (Dongguan) Testing Co., Ltd.**Lab Address:** No.101, Bld N1, Yuyuan 2Rd, Yuyuan Industrial Park, HuangJiang Town, Dongguan, China**Test Location:** No.101, Bld N1, Yuyuan 2Rd, Yuyuan Industrial Park, HuangJiang Town, Dongguan, China**FCC Designation****Number:** CN1255**Standards:** FCC Part 2 (Section 2.1091)
KDB 447498 D01
IEEE C95.1

The above equipment has been tested by **Hwa-Hsing (Dongguan) Testing Co., Ltd.**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :

Tank Tan//Engineer

Date: Sep. 30, 2019**Approved by :**

Harry Li/ Supervisor

Date: Sep. 30, 2019

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by A2LA or any agency of the federal government. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of contents

Release control record	3
1. RF exposure limit.....	4
2. MPE calculation formula	4
3. Calculation result of maximum conducted power.....	5
4. Appendix – Information on the Testing Laboratories.....	6

Release control record

Issue No.	Reason for change	Date issued
HP190830DC001-FMP	Original release	Sep. 30, 2019

1. RF exposure limit

Limits for maximum permissible exposure (MPE)

Limits for general population / uncontrolled exposure				
Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Average time (minutes)
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30
Note: F = Frequency in MHz				

2. MPE calculation formula

$$Pd = (P_{out} * G) / (4 * \pi * r^2)$$

Where:

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Classification:

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user.

3. Calculation result of maximum conducted power

The antennas provided to the EUT, please refer to the following table:

Antenna No.	Function/ mode	Frequency Band	Antenna Gain (dBi)	Antenna Type	Transmit and Receive Chain
1	2.4GHz WLAN	2400~2483.5MHz	2.0	PCB Antenna	1TX,1RX

Frequency band (MHz)	Max power (mW)	Antenna gain (dBi)	Distance (cm)	Power density (mW/cm ²)	Limit (mW/cm ²)
2400~2483.5MHz	9.2470	2	20	0.02916	1.0

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

4. Appendix – Information on the Testing Laboratories

We, [Hwa-Hsing \(Dongguan\) Co., Ltd.](#), A global provider of TESTING and CERTIFICATION services for consumer products, electronic products and wireless information technology products. Adhering to the core values “HONEST and TRUSTWORTHY, OBJECTIVE and IMPARTIALITY, RIGOROUS and AFFICIENT”, commitment to provide professional, perfect and efficient comprehensive ONE-STOP solution of TESTING and CERTIFICATION services for Manufacturers, Buyers, Traders, Brands, Retailers. Assist client to better manage risk, protect their brands, reduce costs and cut time to over 150 markets in global. Our laboratories are FCC recognized accredited test firms and accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lab Address: [No.101, Bld N1, Yuyuan 2Rd, Yuyuan Industrial Park, HuangJiang Town, Dongguan, China](#)

Contact Tel: [0769-83078199](tel:0769-83078199)

Email: customerservice.dg@hwa-hsing.com

Web Site: www.hwa-hsing.com

--- END ---