

FCC Part 15C

Measurement and Test Report

For

LOWEX, LLC

FCC ID: 2AREV-LWXF18

FCC Rule(s):	<u>FCC Part 15.247</u>
Product Description:	<u>feature phone</u>
Tested Model:	<u>F18</u>
Report No.:	<u>BSL008390306RF</u>
Tested Date:	<u>November 12-November 15, 2018</u>
Issued Date:	<u>November 20, 2018</u>
Tested By:	<u>Messi Wang / Engineer</u>
Reviewed By:	<u>Lisa. Li / EMC Manager</u>
Approved & Authorized By:	<u>Mike mo / PSQ Manager</u>
Prepared By:	

Messi Wang

Lisa. Li

Mike mo

BSL Testing Co.,LTD.

NO. 24, ZH Park, Nantou, Shenzhen, 518000 China

Tel: 400-882-9628

Fax: 86- 755-26508703

TABLE OF CONTENTS

1. GENERAL INFORMATION.....	3
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	3
1.2 EUT SETUP AND TEST MODE.....	5
1.3 TEST STANDARDS.....	5
1.4 TEST METHODOLOGY.....	5
1.5 TEST FACILITY.....	5
1.6 MEASUREMENT UNCERTAINTY.....	6
1.7 TEST EQUIPMENT LIST AND DETAILS.....	6
2. SUMMARY OF TEST RESULTS.....	7
3. RF EXPOSURE.....	8
3.1 STANDARD APPLICABLE.....	8
3.2 TEST RESULT.....	8
4. ANTENNA REQUIREMENT.....	9
4.1 STANDARD APPLICABLE.....	9
4.2 EVALUATION INFORMATION.....	9
5. CONDUCTED EMISSIONS.....	10
6. CONDUCTED PEAK OUTPUT POWER.....	13
7. 20DB EMISSION BANDWIDTH.....	14
8. CARRIER FREQUENCIES SEPARATION.....	18
9. HOPPING CHANNEL NUMBER.....	20
10. DWELL TIME.....	22
11. PSEUDORANDOM FREQUENCY HOPPING SEQUENCE.....	25
12. BAND EDGE.....	26
14. SPURIOUS EMISSION.....	32
15. TEST SETUP PHOTO.....	43
16. EUT CONSTRUCTIONAL DETAILS.....	44

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Applicant:	LOWEX, LLC
Address of applicant:	739 NW 105th Pl, Miami, Florida 33172, USA
Manufacturer:	LuZhou XinYu Communication Technology Co., LTD
Address of manufacturer:	NO.19, Section 5, JiuGu Avenue, High Tech District, LuZhou City, SiChuan Provice, China
Product Name:	feature phone
Model No.:	F18
Test Model No:	F18
Remark: All above models are identical in the same PCB layout, interior structure and electrical circuits. The differences are color, appearance and model name for commercial purpose.	
Quantity of tested samples	1
Serial No.:	N/A
Description test modes:	SIM 1 and SIM 2 is a chipset unit,the wors case is SIM1.
Hardware Version:	DF600_PCB
Software Version:	DF600_DF600E_HC
Operation Frequency:	2402MHz~2480MHz
Channel numbers:	79
Channel separation:	1MHz
Modulation type:	GFSK, Pi/4 QPSK, 8DPSK
Antenna Type:	Internal antenna
Antenna gain:	1.2dBi
Power supply:	DC 3.7V by battery or DC 5V from adapter input AC 120V, 60Hz

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402MHz	21	2422MHz	41	2442MHz	61	2462MHz
2	2403MHz	22	2423MHz	42	2443MHz	62	2463MHz
3	2404MHz	23	2424MHz	43	2444MHz	63	2464MHz
4	2405MHz	24	2425MHz	44	2445MHz	64	2465MHz
5	2406MHz	25	2426MHz	45	2446MHz	65	2466MHz
6	2407MHz	26	2427MHz	46	2447MHz	66	2467MHz
7	2408MHz	27	2428MHz	47	2448MHz	67	2468MHz
8	2409MHz	28	2429MHz	48	2449MHz	68	2469MHz
9	2410MHz	29	2430MHz	49	2450MHz	69	2470MHz
10	2411MHz	30	2431MHz	50	2451MHz	70	2471MHz
11	2412MHz	31	2432MHz	51	2452MHz	71	2472MHz
12	2413MHz	32	2433MHz	52	2453MHz	72	2473MHz
13	2414MHz	33	2434MHz	53	2454MHz	73	2474MHz
14	2415MHz	34	2435MHz	54	2455MHz	74	2475MHz
15	2416MHz	35	2436MHz	55	2456MHz	75	2476MHz
16	2417MHz	36	2437MHz	56	2457MHz	76	2477MHz
17	2418MHz	37	2438MHz	57	2458MHz	77	2478MHz
18	2419MHz	38	2439MHz	58	2459MHz	78	2479MHz
19	2420MHz	39	2440MHz	59	2460MHz	79	2480MHz
20	2421MHz	40	2441MHz	60	2461MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test.

EUT Cable List and Details

Cable Description	Length (M)	Shielded/Unshielded	With Core/Without Core
Earphone	1.0	Unshielded	Without Ferrite

Auxiliary Equipment List and Details

Description	Manufacturer	Model	Serial Number
Adapter	JINFULIN	A01	/

Special Cable List and Details

Cable Description	Length (M)	Shielded/Unshielded	With Core/Without Core
/	/	/	/

1.2 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level.

Test Mode List			
Test Mode	Description	Channel	Frequency (MHz)
1	GFSK,	CH1	2402
		CH40	2441
		CH79	2480
2	Pi/4 QPSK	CH1	2402
		CH40	2441
		CH79	2480
3	8DPSK	CH1	2402
		CH40	2441
		CH79	2480

1.3 Test Standards

The following report accordance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 of the Federal Communication Commissions rules.

1.4 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard for Testing Unlicensed Wireless Devices, and ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

1.5 Test Facility

BSL Testing Co.,LTD.

NO. 24, ZH Park, Nantou, Shenzhen, 518000 China

Test Firm Registration Number: 866035

Designation Number: CN1217

Tel: 400-882-9628

Fax: 86-755-26508703

1.6 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
RF Output Power	Conducted	$\pm 0.42\text{dB}$
Occupied Bandwidth	Conducted	$\pm 1.5\%$
Power Spectral Density	Conducted	$\pm 1.8\text{dB}$
Conducted Spurious Emission	Conducted	$\pm 2.17\text{dB}$
Conducted Emissions	Conducted	$\pm 2.88\text{dB}$
Transmitter Spurious Emissions	Radiated	$\pm 5.1\text{dB}$

1.7 Test Equipment List and Details

Description	Manufacturer	Model	Serial No.	Cal Date	Due. Date
Communication Tester	Rohde & Schwarz	CMW500	100358	2018-11-08	2019-11-07
Spectrum Analyzer	R&S	FSP40	100550	2018-10-08	2019-10-07
Test Receiver	R&S	ESC17	US47140102	2018-10-08	2019-10-07
Signal Generator	HP	83630B	3844A01028	2018-10-08	2019-10-07
Test Receiver	R&S	ESPI-3	100180	2018-10-08	2019-10-07
Amplifier	Agilent	8449B	4035A00116	2018-10-08	2019-10-07
Amplifier	HP	8447E	2945A02770	2018-10-08	2019-10-07
Signal Generator	IFR	2023A	202307/242	2018-10-08	2019-10-07
Broadband Antenna	SCHAFFNER	2774	2774	2018-10-21	2019-10-20
Biconical and log periodic antennas	ELECTRO-METRIC CS	EM-6917B-1	171	2018-10-21	2019-10-20
Horn Antenna	R&S	HF906	100253	2018-10-21	2019-10-20
Horn Antenna	EM	EM-6961	6462	2018-10-21	2019-10-20
LISN	R&S	ESH3-Z5	100196	2018-10-08	2019-10-07
LISN	COM-POWER	LI-115	02027	2018-10-08	2019-10-07
3m Semi-Anechoic Chamber	Chengyu Electron	9 (L)*6 (W)* 6 (H)	BSL086	2018-10-08	2019-10-07
Horn Antenna	Schwarzbeck	BBHA9170	00814	2018-10-21	2019-10-20

2. SUMMARY OF TEST RESULTS

Test Item	Section in CFR 47	Result
RF Exposure (SAR)	Part 1.1307 Part 2.1093	Pass* (Please refer to SAR Report)
Antenna Requirement	15.203/15.247 (c)	Pass
AC Power Line Conducted Emission	15.207	Pass
Conducted Peak Output Power	15.247 (b)(1)	Pass
20dB Occupied Bandwidth	15.247 (a)(1)	Pass
Carrier Frequencies Separation	15.247 (a)(1)	Pass
Hopping Channel Number	15.247 (a)(1)	Pass
Dwell Time	15.247 (a)(1)	Pass
Pseudorandom Frequency Hopping Sequence	15.247(b)(4)	Pass
Radiated Emission	15.205/15.209	Pass
Band Edge	15.247(d)	Pass

Pass: The EUT complies with the essential requirements in the standard.

Remark: Test according to ANSI C63.10:2013

3. RF Exposure

3.1 Standard Applicable

According to § 1.1307 and § 2.1093, the portable transmitter must comply the RF exposure requirements.

3.2 Test Result

This product complied with the requirement of the RF exposure, please see the RF Exposure Report.

4. Antenna Requirement

4.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

4.2 Evaluation Information


This product has a internal permanent antenna(1.2dBi), fulfill the requirement of this section.

5. Conducted Emissions


Test Requirement:	FCC Part15 C Section 15.207														
Test Method:	ANSI C63.10:2013														
Test Frequency Range:	150KHz to 30MHz														
Class / Severity:	Class B														
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto														
Limit:	<table><tr><th rowspan="2">Frequency range (MHz)</th><th colspan="2">Limit (dBuV)</th></tr><tr><th>Quasi-peak</th><th>Average</th></tr><tr><td>0.15-0.5</td><td>66 to 56*</td><td>56 to 46*</td></tr><tr><td>0.5-5</td><td>56</td><td>46</td></tr><tr><td>5-30</td><td>60</td><td>50</td></tr></table> * Decreases with the logarithm of the frequency.	Frequency range (MHz)	Limit (dBuV)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
Frequency range (MHz)	Limit (dBuV)														
	Quasi-peak	Average													
0.15-0.5	66 to 56*	56 to 46*													
0.5-5	56	46													
5-30	60	50													
Test setup:	Reference Plane Test table/Insulation plane Remark: E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m														
Test procedure:	1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2013 on conducted measurement.														
Test Instruments:	Refer to section 1.7 for details														
Test mode:	Refer to section 1.2 for details														
Test results:	Pass														

Measurement data:

Line:




No.	Mk.	Freq.	Measure- ment	Limit	Over		
		MHz	dBuV	dBuV	dB	Detector	Comment
1		0.1565	59.65	65.64	-5.99	QP	
2		0.1565	41.10	55.64	-14.54	AVG	
3		0.2900	55.23	60.52	-5.29	QP	
4		0.2900	26.79	50.52	-23.73	AVG	
5	*	0.3832	54.03	58.21	-4.18	QP	
6		0.3832	37.69	48.21	-10.52	AVG	
7		0.9620	50.43	56.00	-5.57	QP	
8		0.9620	35.62	46.00	-10.38	AVG	
9		1.4660	50.46	56.00	-5.54	QP	
10		1.4660	28.37	46.00	-17.63	AVG	
11		2.3060	48.58	56.00	-7.42	QP	
12		2.3060	25.86	46.00	-20.14	AVG	

Neutral:

No.	Mk.	Freq.	Measure- ment	Limit	Over	Detector	Comment
		MHz	dBuV	dBuV	dB		
1		0.1900	58.99	64.03	-5.04	QP	
2		0.1900	35.61	54.03	-18.42	AVG	
3		0.2900	55.72	60.52	-4.80	QP	
4		0.2900	23.90	50.52	-26.62	AVG	
5	*	0.5020	53.05	56.00	-2.95	QP	
6		0.5020	31.21	46.00	-14.79	AVG	
7		0.9300	53.01	56.00	-2.99	QP	
8		0.9300	35.58	46.00	-10.42	AVG	
9		1.4780	52.33	56.00	-3.67	QP	
10		1.4780	33.49	46.00	-12.51	AVG	
11		1.9060	51.05	56.00	-4.95	QP	
12		1.9060	34.80	46.00	-11.20	AVG	


6. Conducted Peak Output Power

Test Requirement:	FCC Part15 C Section 15.247 (b)(3)
Test Method:	ANSI C63.10:2013
Limit:	30dBm(for GFSK),20.97dBm(for EDR)
Test setup:	 The diagram illustrates the test setup. A Power Meter is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Power Meter and the E.U.T. are placed on a Non-Conducted Table. The table is supported by two vertical legs. Below the table is a Ground Reference Plane.
Test Instruments:	Refer to section 1.7 for details
Test mode:	Refer to section 1.2 for details
Test results:	Pass

Measurement Data

Mode	Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
GFSK	Lowest	0.065	30.00	Pass
	Middle	0.652		
	Highest	0.958		
Pi/4QPSK	Lowest	-0.956	20.97	Pass
	Middle	0.068		
	Highest	0.095		
8DPSK	Lowest	-0.358	20.97	Pass
	Middle	0.352		
	Highest	0.245		

7. 20dB Emission Bandwidth


Test Requirement:	FCC Part15 C Section 15.247 (a)(2)
Test Method:	ANSI C63.10:2013
Limit:	N/A
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table. The table is supported by a Ground Reference Plane.
Test Instruments:	Refer to section 1.7 for details
Test mode:	Refer to section 1.2 for details
Test results:	Pass

Measurement Data


Mode	Test channel	20dB Emission Bandwidth (MHz)	Result
GFSK	Lowest	0.93	Pass
	Middle	0.93	
	Highest	0.93	
Pi/4QPSK	Lowest	1.29	Pass
	Middle	1.29	
	Highest	1.28	
8DPSK	Lowest	1.28	Pass
	Middle	1.28	
	Highest	1.28	

Test plot as follows:


Test mode:	GFSK mode
------------	-----------



Lowest channel




Middle channel




Highest channel

Test mode:


Pi/4QPSK mode



Lowest channel




Middle channel




Highest channel

Test mode:


8DPSK mode



Lowest channel




Middle channel



Highest channel

8. Carrier Frequencies Separation

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Receiver setup:	RBW=20KHz, VBW=62KHz, detector=Peak
Limit:	0.025MHz or 2/3 of the 20dB bandwidth (whichever is greater)
Test setup:	
Test Instruments:	Refer to section 1.7 for details
Test mode:	Refer to section 1.2 for details
Test results:	Pass

Measurement Data

Modulation type	Channel	Carrier Frequencies Separation (MHz)	Limit (MHz) *	Result
GFSK	39	1.00	≥ 0.93	Pass
$\pi/4$ DQPSK	39	1.00	≥ 0.86	Pass
8DPSK	39	1.00	≥ 0.85	Pass

Note:

*: GFSK limit = The maximum 20 dB Bandwidth for GFSK modulation on the section 7.4.


$\pi/4$ DQPSK limit = 2/3 * The maximum 20 dB Bandwidth for $\pi/4$ DQPSK modulation on the section 7.4.

8DPSK limit = 2/3 * The maximum 20 dB Bandwidth for 8DPSK modulation on the section 7.4


Test plot as follows:

Only show the worst case


GFSK




π /4DQPSK



8DPSK




9. Hopping Channel Number

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Receiver setup:	RBW=100kHz, VBW=300kHz, Frequency range=2400MHz-2483.5MHz, Detector=Peak
Limit:	15 channels
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table. The table is supported by a Ground Reference Plane.
Test Instruments:	Refer to section 1.7 for details
Test mode:	Refer to section 1.2 for details
Test results:	Pass


Measurement Data:

Mode	Hopping channel numbers	Limit	Result
GFSK	79	15	Pass
Pi/4QPSK	79	15	Pass
8DPSK	79	15	Pass


GFSK




$\pi/4$ DQPSK



8DPSK



10. Dwell Time

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Receiver setup:	RBW=1MHz, VBW=1MHz, Span=0Hz, Detector=Peak
Limit:	0.4 Second
Test setup:	
Test Instruments:	Refer to section 1.7 for details
Test mode:	Refer to section 1.2 for details
Test results:	Pass

Measurement Data



Modulation type	Test Mode	Channel	Pulse Time (ms)	Total of Dwell (ms)	Limit (ms)	Result
GFSK	DH1	2441	0.38	121.60	400	Pass
	DH3	2441	1.63	260.80		
	DH5	2441	2.88	307.20		
π/4DQPSK	2DH1	2441	0.38	121.60	400	Pass
	2DH3	2441	1.64	262.40		
	2DH5	2441	2.88	307.20		
8DPSK	3DH1	2441	0.38	121.60	400	Pass
	3DH3	2441	1.64	262.40		
	3DH5	2441	2.89	308.27		

The test period: $T = 0.4 \text{ Second/Channel} \times 79 \text{ Channel} = 31.6 \text{ s}$

Test plot as follows:



Dwell time

GFSK

 $\pi/4$ -DQPSK



Channel 39 / 2441 MHz - DH1

Channel 39 / 2441 MHz - 2DH1



Channel 39 / 2441 MHz - DH3

Channel 39 / 2441 MHz - 2DH3





Channel 39 / 2441 MHz - DH5

Channel 39 / 2441 MHz - 2DH5


Dwell time	
8DPSK Spectrum Ref Level 30.00 dBm Att 40 dB SGF TRG:VID RBW 1 MHz SWT 10 ms VBW 3 MHz 1AP Clrw M1[1] D1[1] -14.65 dBm 0.00000000 s 9.08 dB 385.00 μs 20 dBm 10 dBm 0 dBm -10 dBm -20 dBm -30 dBm -40 dBm TRG -24.500 dBm CF 2.441 GHz 8001 pts 1.0 ms/	
Channel 39 / 2441 MHz - 3DH1 Spectrum Ref Level 30.00 dBm Att 40 dB SGF TRG:VID RBW 1 MHz SWT 10 ms VBW 3 MHz 1AP Clrw M1[1] D1[1] -25.95 dBm -1.25 μs 8.76 dB 1.63500 ms 20 dBm 10 dBm 0 dBm -10 dBm -20 dBm -30 dBm -40 dBm TRG -24.500 dBm CF 2.441 GHz 8001 pts 1.0 ms/	
2 Channel 39 / 2441 MHz - 3DH3 Spectrum Ref Level 30.00 dBm Att 40 dB SGF TRG:VID RBW 1 MHz SWT 10 ms VBW 3 MHz 1AP Clrw M1[1] D1[1] -11.22 dBm 0.00000000 s 5.62 dB 2.88625 ms 20 dBm 10 dBm 0 dBm -10 dBm -20 dBm -30 dBm -40 dBm TRG -24.500 dBm CF 2.441 GHz 8001 pts 1.0 ms/	
Channel 39 / 2441 MHz - 3DH5 Spectrum Ref Level 30.00 dBm Att 40 dB SGF TRG:VID RBW 1 MHz SWT 10 ms VBW 3 MHz 1AP Clrw M1[1] D1[1] -11.22 dBm 0.00000000 s 5.62 dB 2.88625 ms 20 dBm 10 dBm 0 dBm -10 dBm -20 dBm -30 dBm -40 dBm TRG -24.500 dBm CF 2.441 GHz 8001 pts 1.0 ms/	

11. Pseudorandom Frequency Hopping Sequence

Test Requirement:	FCC Part15 C Section 15.247 (a)(1) requirement:
<i>Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.</i> <i>Alternatively. Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.</i>	
EUT Pseudorandom Frequency Hopping Sequence	
<i>The pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONES; i.e. the shift register is initialized with nine ones.</i> • Number of shift register stages: 9 • Length of pseudo-random sequence: $2^9 - 1 = 511$ bits • Longest sequence of zeros: 8 (non-inverted signal)  <i>Linear Feedback Shift Register for Generation of the PRBS sequence</i> <i>An example of Pseudorandom Frequency Hopping Sequence as follow:</i>  <i>Each frequency used equally on the average by each transmitter.</i> <i>The system receivers have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.</i>	


12. Band Edge

Conducted Emission Method


Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	ANSI C63.10:2013
Receiver setup:	RBW=100kHz, VBW=300kHz, Detector=Peak
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T are placed on a Non-Conducted Table. The table is supported by two vertical legs and sits on a Ground Reference Plane.
Test Instruments:	Refer to section 1.7 for details
Test mode:	Refer to section 1.2 for details
Test results:	Pass

Test plot as follows:

GFSK Mode:




Pi/4QPSK Mode:



No-hopping mode

Hopping mode



No-hopping mode


Hopping mode

8DPSK Mode:



No-hopping mode


Hopping mode



No-hopping mode

Hopping mode

Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209 and 15.205					
Test Method:	ANSI C63.10:2013					
Test Frequency Range:	All restriction band have been tested, and 2.31GHz to 2.5GHz band is the worse case					
Test site:	Measurement Distance: 3m					
Receiver setup:	Frequency	Detector	RBW	VBW	Remark	
	Above 1GHz	Peak	1MHz	3MHz	Peak Value	
		Peak	1MHz	10Hz	Average Value	
Limit:	Frequency		Limit (dBuV/m @3m)		Remark	
	Above 1GHz		54.00		Average Value	
			74.00		Peak Value	
Test setup:						
Test Procedure:	1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.					
Test Instruments:	Refer to section 1.7 for details					
Test mode:	Refer to section 1.2 for details					
Test results:	Pass					

Remark: During the test, pre-scan the GFSK, Pi/4QPSK, 8DPSK modulation, and found the GFSK modulation which it is worse case.

Test channel:	Lowest
---------------	--------

Peak value:

Frequency (MHz)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	52.52	74.00	-21.48	Horizontal
2400.00	54.54	74.00	-19.46	Horizontal
2390.00	52.84	74.00	-21.16	Vertical
2400.00	55.68	74.00	-18.32	Vertical

Average value:

Frequency (MHz)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	42.52	54.00	-11.48	Horizontal
2400.00	41.51	54.00	-12.49	Horizontal
2390.00	43.84	54.00	-10.16	Vertical
2400.00	44.95	54.00	-9.05	Vertical

Test channel:	Highest
---------------	---------

Peak value:

Frequency (MHz)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	55.35	74.00	-18.65	Horizontal
2500.00	52.24	74.00	-21.76	Horizontal
2483.50	55.52	74.00	-18.48	Vertical
2500.00	56.47	74.00	-17.53	Vertical

Average value:


Frequency (MHz)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	44.25	54.00	-9.75	Horizontal
2500.00	45.24	54.00	-8.76	Horizontal
2483.50	42.52	54.00	-11.48	Vertical
2500.00	42.57	54.00	-11.43	Vertical

Remark:

1. *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
2. *The emission levels of other frequencies are very lower than the limit and not show in test report.*

14. Spurious Emission


Conducted Emission Method

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	ANSI C63.10:2013
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table. The table is supported by two vertical legs and sits on a Ground Reference Plane.
Test Instruments:	Refer to section 1.7 for details
Test mode:	Refer to section 1.2 for details
Test results:	Pass


Remark:

During the test, pre-scan the GFSK, Pi/4QPSK, 8DPSK modulation, and found the GFSK modulation which it is worse case.


Test channel:	Lowest channel
---------------	----------------



Reference level




30MHz~1GHz




1GHz~25GHz


Test channel:	Middle channel
---------------	----------------



Reference level




30MHz~1GHz




1GHz~25GHz


Test channel:	Highest channel
---------------	-----------------



Reference level





30MHz~1GHz



1GHz~25GHz

Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	30MHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
		Peak	1MHz	10Hz	Average Value
Limit:	Frequency		Limit (dBuV/m @3m)		Remark
	30MHz-88MHz		40.0		Quasi-peak Value
	88MHz-216MHz		43.5		Quasi-peak Value
	216MHz-960MHz		46.0		Quasi-peak Value
	960MHz-1GHz		54.0		Quasi-peak Value
	Above 1GHz		54.0		Average Value
			74.0		Peak Value
Test setup:	Below 1GHz				
					
Test setup:	Above 1GHz				


	
Test Procedure:	1. The EUT was placed on the top of a rotating table (0.8 meters below 1G and 1.5 meters above 1G) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
Test Instruments:	Refer to section 1.7 for details
Test mode:	Refer to section 1.2 for details
Test results:	Pass

Remark:


1. During the test, pre-scan the GFSK, Pi/4QPSK, 8DPSK modulation, and found the GFSK modulation which it is worse case.
2. Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis which it is worse case.

Measurement data:

Vertical:



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB	Detector
1		71.3298	15.58	10.96	26.54	40.00	-13.46	QP
2		160.9088	23.82	12.38	36.20	43.50	-7.30	QP
3	*	193.7726	25.86	13.01	38.87	43.50	-4.63	QP
4		245.9507	22.87	13.67	36.54	46.00	-9.46	QP
5		300.3672	20.30	15.26	35.56	46.00	-10.44	QP
6		378.5842	19.21	16.02	35.23	46.00	-10.77	QP

Horizontal:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB Detector
1		32.7486	20.47	9.02	29.49	40.00	-10.51 QP
2		79.5209	18.92	9.82	28.74	40.00	-11.26 QP
3	*	160.9089	23.79	11.66	35.45	43.50	-8.05 QP
4		193.7728	18.87	12.01	30.88	43.50	-12.62 QP
5		360.4476	15.01	14.73	29.74	46.00	-16.26 QP
6		810.2653	15.61	22.14	37.75	46.00	-8.25 QP

■ Above 1GHz

Test channel:	Lowest
---------------	--------

Peak value:

Frequency (MHz)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4804.00	44.35	74.00	-29.65	Vertical
7206.00	46.62	74.00	-27.38	Vertical
9608.00	49.54	74.00	-24.46	Vertical
12010.00	*	74.00		Vertical
14412.00	*	74.00		Vertical
4804.00	48.35	74.00	-25.65	Horizontal
7206.00	46.62	74.00	-27.38	Horizontal
9608.00	47.54	74.00	-26.46	Horizontal
12010.00	*	74.00		Horizontal
14412.00	*	74.00		Horizontal

Average value:

Frequency (MHz)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4804.00	31.25	54.00	-22.75	Vertical
7206.00	33.62	54.00	-20.38	Vertical
9608.00	36.54	54.00	-17.46	Vertical
12010.00	*	54.00		Vertical
14412.00	*	54.00		Vertical
4804.00	37.58	54.00	-16.42	Horizontal
7206.00	38.94	54.00	-15.06	Horizontal
9608.00	36.52	54.00	-17.48	Horizontal
12010.00	*	54.00		Horizontal
14412.00	*	54.00		Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “*”, means this data is the too weak instrument of signal is unable to test.
3. The emission levels of other frequencies are very lower than the limit and not show in test report.

Test channel:	Middle
---------------	--------

Peak value:

Frequency (MHz)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4882.00	45.58	74.00	-28.42	Vertical
7323.00	47.65	74.00	-26.35	Vertical
9764.00	48.94	74.00	-25.06	Vertical
12205.00		74.00		Vertical
14646.00		74.00		Vertical
4882.00	47.58	74.00	-26.42	Horizontal
7323.00	48.95	74.00	-25.05	Horizontal
9764.00	46.62	74.00	-27.38	Horizontal
12205.00		74.00		Horizontal
14646.00		74.00		Horizontal

Average value:

Frequency (MHz)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4882.00	33.52	54.00	-20.48	Vertical
7323.00	34.54	54.00	-19.46	Vertical
9764.00	36.84	54.00	-17.16	Vertical
12205.00		54.00		Vertical
14646.00		54.00		Vertical
4882.00	38.95	54.00	-15.05	Horizontal
7323.00	36.63	54.00	-17.37	Horizontal
9764.00	37.25	54.00	-16.75	Horizontal
12205.00		54.00		Horizontal
14646.00		54.00		Horizontal

Remark:

1. *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
2. *“*”*, means this data is the too weak instrument of signal is unable to test.
3. *The emission levels of other frequencies are very lower than the limit and not show in test report.*

Test channel:

Highest

Peak value:



Frequency (MHz)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4960.00	44.58	74.00	-29.42	Vertical
7440.00	45.24	74.00	-28.76	Vertical
9920.00	48.51	74.00	-25.49	Vertical
12400.00		74.00		Vertical
14880.00		74.00		Vertical
4960.00	49.52	74.00	-24.48	Horizontal
7440.00	45.55	74.00	-28.45	Horizontal
9920.00	47.48	74.00	-26.52	Horizontal
12400.00		74.00		Horizontal
14880.00		74.00		Horizontal

Average value:


Frequency (MHz)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4960.00	34.58	54.00	-19.42	Vertical
7440.00	36.65	54.00	-17.35	Vertical
9920.00	38.25	54.00	-15.75	Vertical
12400.00		54.00		Vertical
14880.00		54.00		Vertical
4960.00	38.47	54.00	-15.53	Horizontal
7440.00	35.84	54.00	-18.16	Horizontal
9920.00	36.95	54.00	-17.05	Horizontal
12400.00		54.00		Horizontal
14880.00		54.00		Horizontal

15. Test Setup Photo

Radiated Emission



Conducted Emission

**16. EUT Constructional Details**

Please refer to report BSL008390305RF.

-----End-----