

4

3

2

1

NOTES:

1. INTERPRET DRAWING PER ASME Y14.5

2. LASER MARKING SETTINGS:

MARKING PARAMETERS: LASER POWER = 80%
SCAN SPEED = 1000mm/S
PULSE FREQUENCY = 60kHz
SPOT VARIABLE = 0
REPETITION = 1
FILL PATTERN = PATTERN 1
FILL INTERVAL = 0.080mm
SHRINK FILL = 0.00mm

3

QR CODE REQUIREMENTS:

QR CODE LABEL TO BE 12mm X 12mm SQUARE
QR CODE TO INCLUDE PART NUMBER AND SERIAL NUMBER
USE THE FOLLOWING FORMAT:

<https://qr.longviewiot.com/device/PN/SN

pn FORMAT = 000-0000000-000
sn FORMAT = 00000000000

4. FONTS:

4a

GT AMERICA BOLD, 6pt (2.12mm HT)

4b

GT AMERICA, 5.5pt (1.9mm HT)

5. ARTWORK:

5a

LOGO FOR REFERENCE ONLY. SCALE SUPPLIED ARTWORK
CAD FILE TO DIMENSIONS SHOWN AND MARK IN
LOCATION SHOWN, CENTER JUSTIFIED

LOGO PN: 710-000190-001

PRELIMINARY

REV

DESCRIPTION

DATE

INITIAL RELEASE

12/5/18

4b

LONGVIEW

Carnegie Technologies, LLC

WARNING - EXPLOSION HAZARD - BATTERIES
MUST ONLY BE CHANGED IN AN AREA FREE
OF IGNITABLE CONCENTRATIONS.
REPLACE BATTERY WITH LITHIUM AAA ONLY
TEMP: -20C TO +55C
MODEL: LV-PSH-173
CL I, DIV 2, GRP A,B,C,D, T6
FCC ID: 2ARIP-0015
IC: 24612-0015
COC: USA
IP68
support.longviewiot.com

DRAWN

DATE

TH

12/5/18

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN
MILLIMETERS

DIMENSION TOLERANCES

.X ± .5
.XX ± .10

ANGLE ± 1/2°

3.2

FINISH IN
MICRONS

THIRD ANGLE PROJECTION

THESE DRAWINGS AND SPECIFICATIONS ARE THE
EXCLUSIVE PROPERTY OF CARNEGIE TECHNOLOGIES.
ISSUED IN STRICT CONFIDENCE AND
D SHALL NOT, WITHOUT THE PRIOR WRITTEN
PERMISSION OF CARNEGIE TECHNOLOGIES, BE
REPRODUCED, COPIED OR USED FOR ANY PURPOSE
WHATSOEVER, EXCEPT THE MANUFACTURE
OF ARTICLES FOR CARNEGIE TECHNOLOGIES.

Title

THREE BUTTON, SPEC, LASER
ETCHING

Scale:

1,000

Size

D

Drawing No.

790-000031-104

Rev

Sheet

1 of 1

4

3

2

1