

FCC Part 15C

Measurement and Test Report

For

Shenzhen Hongjiayi Electronics Co., Ltd.

3rd Floor, Building B, Zone E, Shajing Democratic West Industrial Park,

Shajing Street, Bao'an District, Shenzhen

FCC ID: 2ARMWYTS-M501

FCC Rule(s): FCC Part 15.249

Product Description: mouse

Tested Model: YTS-M501

Report No.: STRD1808049I

Sample Receipt Date: 2018-08-16

Tested Date: 2018-08-17 to 2018-09-27


Issued Date: 2018-09-27

Tested By: Ray Yang / Engineer

Reviewed By: Silin Chen / EMC Manager

Approved & Authorized By: Jandy So / PSQ Manager

Prepared By:



Shenzhen SEM Test Technology Co., Ltd.

1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road,
Bao'an District, Shenzhen, P.R.C. (518101)

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen SEM Test Technology Co., Ltd.

TABLE OF CONTENTS

1. GENERAL INFORMATION.....	3
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	3
1.2 TEST STANDARDS.....	4
1.3 TEST METHODOLOGY	4
1.4 TEST FACILITY	4
1.5 EUT SETUP AND TEST MODE	5
1.6 MEASUREMENT UNCERTAINTY	5
1.7 TEST EQUIPMENT LIST AND DETAILS	6
2. SUMMARY OF TEST RESULTS	7
3. ANTENNA REQUIREMENTS.....	8
3.1 STANDARD APPLICABLE.....	8
3.2 TEST RESULT.....	8
4. RADIATED EMISSIONS.....	9
4.1 STANDARD APPLICABLE.....	9
4.2 TEST PROCEDURE.....	9
4.3 CORRECTED AMPLITUDE & MARGIN CALCULATION.....	11
4.4 SUMMARY OF TEST RESULTS/PLOTS	11
5. OUT OF BAND EMISSIONS.....	20
5.1 STANDARD APPLICABLE.....	20
5.2 TEST PROCEDURE.....	20
5.3 SUMMARY OF TEST RESULTS/PLOTS	20
6. EMISSION BANDWIDTH.....	23
6.1 STANDARD APPLICABLE.....	23
6.2 TEST PROCEDURE.....	23
6.3 SUMMARY OF TEST RESULTS/PLOTS	23
7. CONDUCTED EMISSIONS	25
7.1 TEST PROCEDURE.....	25
7.2 BASIC TEST SETUP BLOCK DIAGRAM.....	25
7.3 TEST RECEIVER SETUP	25
7.4 SUMMARY OF TEST RESULTS/PLOTS	25

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: Shenzhen Hongjiayi Electronics Co., Ltd.
Address of applicant: 3rd Floor, Building B, Zone E, Shajing Democratic West Industrial Park, Shajing Street, Bao'an District, Shenzhen

Manufacturer: Shenzhen Hongjiayi Electronics Co., Ltd.
Address of manufacturer: 3rd Floor, Building B, Zone E, Shajing Democratic West Industrial Park, Shajing Street, Bao'an District, Shenzhen

General Description of EUT	
Product Name:	mouse
Trade Name:	/
Model No.:	YTS-M501
Adding Model(s):	M502, M503, M504, M505, M506, M507, M508, M509, M510
Rated Voltage:	DC 1.5V
Power Adapter Model:	/
<i>Note: The test data is gathered from a production sample, provided by the manufacturer. The appearance of others models listed in the report is different from main-test model YTS-M501, but the circuit and the electronic construction do not change, declared by the manufacturer.</i>	

Technical Characteristics of EUT	
Frequency Range:	2402.6MHz-2480.6MHz
Max. Field Strength:	85.17dBuV/m
Modulation:	GFSK
Antenna Type:	PCB Antenna
Antenna Gain:	2.34dBi
Lowest Internal Frequency of EUT:	16MHz

1.2 Test Standards

The tests were performed according to following standards:

FCC Rules Part 15.249: Operation within the bands 902-928 MHz, 2400-2483.5 MHz, 5725-5875 MHz, and 24.0-24.25 GHz.

ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which results in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted accordingly in reference to the Operating Instructions.

1.4 Test Facility

FCC – Registration No.: 125990

Shenzhen SEM Test Technology Co., Ltd. Laboratory has been recognized to perform compliance testing on equipment subject to the Commissions Declaration Of Conformity (DOC). The Designation Number is CN5010, and Test Firm Registration Number is 125990.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Shenzhen SEM.Test Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	Low Channel	2402.6MHz
TM2	Middle Channel	2441.6MHz
TM3	High Channel	2480.6MHz

Test Conditions	
Temperature:	22~25 °C
Relative humidity	50~55 %.
ATM Pressure:	1019 mbar

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Special Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
/	/	/	/

1.6 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
RF Output Power	Conducted	±0.42dB
Occupied Bandwidth	Conducted	±1.5%
Conducted Spurious Emission	Conducted	±2.17dB
Conducted Emissions	Conducted	9-150kHz ±3.74dB
		0.15-30MHz ±3.34dB
Transmitter Spurious Emissions	Radiated	30-200MHz ±4.52dB
		0.2-1GHz ±5.56dB
		1-6GHz ±3.84dB
		6-18GHz ±3.92dB

1.7 Test Equipment List and Details

No.	Description	Manufacturer	Model	Serial No.	Cal Date	Due Date
SEMT-1072	Spectrum Analyzer	Agilent	E4407B	MY41440400	2018-05-22	2019-05-21
SEMT-1031	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2018-05-22	2019-05-21
SEMT-1007	EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2018-05-22	2019-05-21
SEMT-1008	Amplifier	Agilent	8447F	3113A06717	2018-05-22	2019-05-21
SEMT-1043	Amplifier	C&D	PAP-1G18	2002	2018-05-22	2019-05-21
SEMT-1011	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2017-06-08	2020-06-07
SEMT-1042	Horn Antenna	ETS	3117	00086197	2017-06-08	2020-06-07
SEMT-1121	Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170582	2017-06-08	2020-06-07
SEMT-1069	Loop Antenna	Schwarz beck	FMZB 1516	9773	2017-06-08	2020-06-07
SEMT-1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2018-05-22	2019-05-21
SEMT-1003	L.I.S.N	Schwarz beck	NSLK8126	8126-224	2018-05-22	2019-05-21
SEMT-1002	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2018-05-22	2019-05-21
SEMT-1168	Pre-amplifier	Direction Systems Inc.	PAP-0126	14141-12838	2018-05-22	2019-05-21
SEMT-1169	Pre-amplifier	Direction Systems Inc.	PAP-2640	14145-14153	2018-05-22	2019-05-21
SEMT-1163	Spectrum Analyzer	Rohde & Schwarz	FSP40	100612	2018-05-22	2019-05-21
SEMT-1170	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2018-03-19	2021-03-18
SEMT-1166	Power Limiter	Agilent	N9356B	MY45450376	2018-05-22	2019-05-21
SEMT-1048	RF Limiter	ATTEN	AT-BSF-2400~2500	/	2018-05-22	2019-05-21
SEMT-1076	RF Switcher	Top Precision	RCS03-A2	/	2018-05-22	2019-05-21
SEMT-C001	Cable	Zheng DI	LL142-07-07-10M(A)	/	2018-03-19	2019-03-18
SEMT-C002	Cable	Zheng DI	ZT40-2.92J-2.92J-6M	/	2018-03-19	2019-03-18
SEMT-C003	Cable	Zheng DI	ZT40-2.92J-2.92J-2.5M	/	2018-03-19	2019-03-18
SEMT-C004	Cable	Zheng DI	2M0RFC	/	2018-03-19	2019-03-18
SEMT-C005	Cable	Zheng DI	1M0RFC	/	2018-03-19	2019-03-18
SEMT-C006	Cable	Zheng DI	1M0RFC	/	2018-03-19	2019-03-18

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§ 15.203	Antenna Requirement	Compliant
§15.205	Restricted Band of Operation	Compliant
§ 15.207(a)	Conducted Emission	N/A
§ 15.209(a)(f)	Radiated Spurious Emissions	Compliant
§15.249(a)	Field Strength of Emissions	Compliant
§15.249(d)	Out of Band Emission	Compliant
§15.215 (c)	Emission Bandwidth	Compliant

N/A: not applicable

3. Antenna Requirements

3.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.2 Test Result

This product has an integral antenna, fulfill the requirement of this section.

4. Radiated Emissions

4.1 Standard Applicable

According to §15.249(a), the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental Frequency	Field strength of fundamental (milli-volts/meter)	Field strength of Harmonics (micro-volts/meter)
902-928 MHz	50	500
2400-2483.5 MHz	50	500
5725-5875 MHz	50	500
24.0-24.25 GHz	250	2500

(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.



The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

4.2 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.205 15.249(a) and FCC Part 15.209 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.



Frequency :9kHz-30MHz
 RBW=10KHz,
 VBW =30KHz
 Sweep time= Auto
 Trace = max hold
 Detector function = peak

Frequency :30MHz-1GHz
 RBW=120KHz,
 VBW=300KHz
 Sweep time= Auto
 Trace = max hold
 Detector function = peak, QP

Frequency :Above 1GHz
 RBW=1MHz,
 VBW=3MHz(Peak), 10Hz(AV)
 Sweep time= Auto
 Trace = max hold
 Detector function = peak, AV

4.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dB μ V means the emission is 6dB μ V below the maximum limit. The equation for margin calculation is as follows:


$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15C Limit}$$

4.4 Summary of Test Results/Plots

Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.


➤ Spurious Emissions Below 1GHz

Test Channel	Low	Polarity:	Horizontal
--------------	-----	-----------	------------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	49.3594	39.84	-13.61	26.23	40.00	-13.77	72	100	peak
2	108.2667	44.58	-15.57	29.01	43.50	-14.49	114	100	peak
3	290.0172	37.02	-9.65	27.37	46.00	-18.63	121	100	peak
4	381.2487	39.81	-8.70	31.11	46.00	-14.89	133	100	peak
5	631.6884	38.04	-6.15	31.89	46.00	-14.11	323	100	peak
6	878.3214	34.27	-1.45	32.82	46.00	-13.18	199	100	peak

Test Channel	Low	Polarity:	Vertical
--------------	-----	-----------	----------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	55.4147	39.46	-14.23	25.23	40.00	-14.77	342	100	peak
2	98.4866	39.51	-15.99	23.52	43.50	-19.98	224	100	peak
3	134.0882	42.41	-18.68	23.73	43.50	-19.77	73	100	peak
4	289.0021	38.39	-9.73	28.66	46.00	-17.34	192	100	peak
5	379.9141	38.36	-8.67	29.69	46.00	-16.31	102	100	peak
6	597.2234	37.47	-6.64	30.83	46.00	-15.17	200	100	peak

Test Channel	Middle	Polarity:	Horizontal
--------------	--------	-----------	------------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	50.9420	40.09	-13.60	26.49	40.00	-13.51	316	100	peak
2	70.0903	41.19	-17.95	23.24	40.00	-16.76	91	100	peak
3	104.9033	40.73	-15.32	25.41	43.50	-18.09	280	100	peak
4	206.3976	39.14	-13.73	25.41	43.50	-18.09	104	100	peak
5	345.5952	37.83	-8.50	29.33	46.00	-16.67	213	100	peak
6	578.6699	37.58	-6.99	30.59	46.00	-15.41	330	100	peak

Test Channel	Middle	Polarity:	Vertical
--------------	--------	-----------	----------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	51.3005	39.67	-13.60	26.07	40.00	-13.93	184	100	peak
2	98.4866	39.52	-15.99	23.53	43.50	-19.97	189	100	peak
3	215.2678	38.82	-13.63	25.19	43.50	-18.31	127	100	peak
4	334.8589	38.09	-8.82	29.27	46.00	-16.73	94	100	peak
5	489.0269	38.49	-8.36	30.13	46.00	-15.87	143	100	peak
6	584.7895	38.20	-6.79	31.41	46.00	-14.59	168	100	peak

Test Channel	High	Polarity:	Horizontal
--------------	------	-----------	------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	52.0251	38.64	-13.59	25.05	40.00	-14.95	309	100	peak
2	88.6524	39.07	-16.51	22.56	43.50	-20.94	171	100	peak
3	107.8877	40.49	-15.54	24.95	43.50	-18.55	93	100	peak
4	221.3921	38.07	-13.07	25.00	46.00	-21.00	94	100	peak
5	346.8092	37.81	-8.46	29.35	46.00	-16.65	242	100	peak
6	504.7062	39.39	-8.39	31.00	46.00	-15.00	224	100	peak

Test Channel	High	Polarity:	Vertical
--------------	------	-----------	----------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	51.8430	39.21	-13.59	25.62	40.00	-14.38	245	100	peak
2	93.7685	39.17	-16.18	22.99	43.50	-20.51	100	100	peak
3	134.5592	42.85	-18.70	24.15	43.50	-19.35	158	100	peak
4	236.6447	38.08	-11.89	26.19	46.00	-19.81	92	100	peak
5	307.8313	38.46	-9.35	29.11	46.00	-16.89	102	100	peak
6	562.6624	38.63	-7.57	31.06	46.00	-14.94	321	100	peak

Spurious Emissions Above 1GHz

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel-2402.6MHz							
2402.60	88.75	-3.59	85.16	114.00	-28.84	H	PK
2402.60	70.47	-3.59	66.88	94.00	-27.12	H	AV
4805.20	48.75	-3.59	45.16	74.00	-28.84	H	PK
4805.20	40.38	-3.59	36.79	54.00	-17.21	H	AV
7207.80	44.61	-0.52	44.09	74.00	-29.91	H	PK
7207.80	35.72	-0.52	35.20	54.00	-18.80	H	AV
2402.60	83.43	-3.59	79.84	114.00	-34.16	V	PK
2402.60	64.94	-3.59	61.35	94.00	-32.65	V	AV
4805.20	48.86	-3.59	45.27	74.00	-28.73	V	PK
4805.20	40.54	-3.59	36.95	54.00	-17.05	V	AV
7207.80	46.62	-0.52	46.10	74.00	-27.90	V	PK
7207.80	37.29	-0.52	36.77	54.00	-17.23	V	AV
Middle Channel-2441.6MHz							
2441.60	87.91	-3.59	84.32	114.00	-29.68	H	PK
2441.60	69.81	-3.59	66.22	94.00	-27.78	H	AV
4883.20	48.66	-3.49	45.17	74.00	-28.83	H	PK
4883.20	40.33	-3.49	36.84	54.00	-17.16	H	AV
7324.80	45.66	-0.47	45.19	74.00	-28.81	H	PK
7324.80	37.43	-0.47	36.96	54.00	-17.04	H	AV
2441.60	83.42	-3.59	79.83	114.00	-34.17	V	PK
2441.60	63.43	-3.59	59.84	94.00	-34.16	V	AV
4883.20	48.81	-3.49	45.32	74.00	-28.68	V	PK
4883.20	39.37	-3.49	35.88	54.00	-18.12	V	AV
7324.80	44.57	-0.47	44.10	74.00	-29.90	V	PK
7324.80	36.70	-0.47	36.23	54.00	-17.77	V	AV

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	H/V	
High Channel-2480.6MHz							
2480.60	88.76	-3.59	85.17	114.00	-28.83	H	PK
2480.60	70.11	-3.59	66.52	94.00	-27.48	H	AV
4961.20	48.64	-3.41	45.23	74.00	-28.77	H	PK
4961.20	39.82	-3.41	36.41	54.00	-17.59	H	AV
7441.80	46.17	-0.42	45.75	74.00	-28.25	H	PK
7441.80	37.27	-0.42	36.85	54.00	-17.15	H	AV
2480.60	83.76	-3.59	80.17	114.00	-33.83	V	PK
2480.60	64.82	-3.59	61.23	94.00	-32.77	V	AV
4961.20	49.14	-3.41	45.73	74.00	-28.27	V	PK
4961.20	39.85	-3.41	36.44	54.00	-17.56	V	AV
7441.80	45.62	-0.42	45.20	74.00	-28.80	V	PK
7441.80	35.91	-0.42	35.49	54.00	-18.51	V	AV

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, which above 5th Harmonics are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

The measurements greater than 20dB below the limit from 9kHz to 30MHz..

5. Out of Band Emissions

5.1 Standard Applicable

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

5.2 Test Procedure

As the radiation test, set the Lowest and Highest Transmitting Channel, observed the outside band of 2400MHz to 2483.5MHz, than mark the higher-level emission for comparing with the FCC rules.


5.3 Summary of Test Results/Plots

Test mode	Frequency	Limit	Result
	MHz	dBuV / dBc	
Lowest	2310.00	<54 dBuV	Pass
	2390.00	<54 dBuV	Pass
	2400.00	<54 dBuV	Pass
Highest	2483.50	<54 dBuV	Pass
	2500.00	<54 dBuV	Pass

The edge emissions are below the FCC 15.209 Limits or complies with the 15.249 requirements.

Please refer to the test plots as below.

Test Channel	Low	Polarity:	Vertical(worst case)
--------------	-----	-----------	----------------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	41.22	-7.78	33.44	54.00	-20.56	Ave Detector
	2310.000	53.75	-7.78	45.97	74.00	-28.03	Peak Detector
2	2390.000	40.77	-7.32	33.45	54.00	-20.55	Ave Detector
	2390.000	57.65	-7.32	50.33	74.00	-23.67	Peak Detector
3	2400.000	41.27	-7.26	34.01	54.00	-19.99	Ave Detector
	2400.000	72.29	-7.26	65.03	74.00	-8.97	Peak Detector
4	2402.454	74.11	-7.25	66.86	/	/	Ave Detector
	2401.843	89.98	-7.25	82.73	/	/	Peak Detector

6. Emission Bandwidth

6.1 Standard Applicable

According to 15.215 (c), intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

6.2 Test Procedure

According to the ANSI 63.10-2013, the emission bandwidth test method as follows.

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

Set span = 1MHz, centered on a transmitting channel

RBW $\geq$ 1% 20dB Bandwidth, VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold


All the trace to stabilize, use the marker-to-peak function to set the marker to the peak of the emission, use the marker-delta function to measure and record the 20dB down and 99% bandwidth of the emission.

6.3 Summary of Test Results/Plots

Test Channel	20dB Bandwidth(kHz)
Low Channel	2100
Middle Channel	2180
High Channel	2190


Please refer to the following test plots

Low Channel




Date: 21.SEP.2018 16:50:34

Middle Channel



Date: 21.SEP.2018 16:57:13

High Channel



Date: 21.SEP.2018 17:00:13


7. Conducted Emissions

7.1 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.

7.2 Basic Test Setup Block Diagram



7.3 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency 150 kHz
Stop Frequency 30 MHz
Sweep Speed Auto
IF Bandwidth..... 10 kHz
Quasi-Peak Adapter Bandwidth 9 kHz
Quasi-Peak Adapter Mode Normal

7.4 Summary of Test Results/Plots

Not applicable

***** END OF REPORT *****