TEST REPORT

Applicant:	Torro GmbH
Address of Applicant:	Am Roehrig 2 D-63762 Grossostheim Germany
Manufacturer/Factory:	TAIGEN TOYS FACTORY
Address of Manufacturer/Factory:	SHANGCUN INDUSTRIAL PARK ,LIANXIA TOWN,CHENGHAI DISTRICT,SHANTOU CITY,GUANGDONG PROVINCE,CHINA
Equipment Under Test (EUT)	
Product Name:	The model tank
Model No.:	See Section 5.1
FCC ID:	2ARN520211008
Applicable standards:	FCC CFR Title 47 Part 15 Subpart C Section 15.247
Date of sample receipt:	October 08, 2021
Date of Test:	October 08-25, 2021
Date of report issued:	October 25, 2021
Test Result :	PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

Robinson Luo
Laboratory Manager

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

2 Version

Version No.	Date	Description
00	*October 25, 2021*	*Original*

Prepared By: ***Date:*** *October 25, 2021*

Project Engineer

Check By: ***Date:*** *October 25, 2021*

Reviewer

3 Contents

Page

1 COVER PAGE 1

2 VERSION 2

3 CONTENTS 3

4 TEST SUMMARY 4

5 GENERAL INFORMATION 5

5.1 GENERAL DESCRIPTION OF EUT 5
5.2 TEST MODE 7
5.3 DESCRIPTION OF SUPPORT UNITS 7
5.4 DEVIATION FROM STANDARDS 7
5.5 ABNORMALITIES FROM STANDARD CONDITIONS 7
5.6 TEST FACILITY 7
5.7 TEST LOCATION 7
5.8 ADDITIONAL INSTRUCTIONS 7

6 TEST INSTRUMENTS LIST 8

7 TEST RESULTS AND MEASUREMENT DATA 10

7.1 ANTENNA REQUIREMENT 10
7.2 CONDUCTED OUTPUT POWER 11
7.3 CHANNEL BANDWIDTH 12
7.4 POWER SPECTRAL DENSITY 13
7.5 SPURIOUS EMISSION IN NON-RESTRICTED & RESTRICTED BANDS 14
7.5.1 Conducted Emission Method 14
7.5.2 Radiated Emission Method 15

8 TEST SETUP PHOTO 30

9 EUT CONSTRUCTIONAL DETAILS 30

4 Test Summary

Test Item	Section in CFR 47	Result
Antenna requirement	15.203/15.247 (c)	Pass
AC Power Line Conducted Emission	15.207	N/A
Conducted Output Power	15.247 (b)(3)	Pass
Channel Bandwidth	15.247 (a)(2)	Pass
Power Spectral Density	15.247 (e)	Pass
Band Edge	15.247(d)	Pass
Spurious Emission	15.205/15.209	Pass

Remarks:

1. *Pass: The EUT complies with the essential requirements in the standard.*
2. *N/A:Not applicable.*
3. *Test according to ANSI C63.10:2013*

Measurement Uncertainty

Test Item	Frequency Range	Measurement Uncertainty	Notes
Radiated Emission	30MHz-200MHz	3.8039dB	(1)
Radiated Emission	200MHz-1GHz	3.9679dB	(1)
Radiated Emission	1GHz-18GHz	4.29dB	(1)
Radiated Emission	18GHz-40GHz	3.30dB	(1)
AC Power Line Conducted Emission	0.15MHz ~ 30MHz	3.44dB	(1)
Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.			

5 General Information

5.1 General Description of EUT

Product Name:	The model tank
Model No.:	TG3841-10,15101-CA, 3818-A, 3818-A1, 3818-B, 3818-B1, 3818-C, 3818-C1, 3818-D, 3818-D1, 3818-E, 3818-E1, 3819-A, 3819-A1, 3819-B, 3819-B1, 3848-B, 3848-B1, 3859-B, 3859-B1, 3869C-B, 3869C-B1, 3879G-B, 3879G-B1, 3879F-B, 3879F-B1, 3909-B, 3909-B1, 3889-B, 3889-B1, 3928-B, 3928-B1, 3878-B, 3878-B1, 3888-C, 3888-C1, 3888-B, 3888-B1, 3898-B, 3898-B1, 3898-C, 3898-C1, 501, 502, 503, 504, 505, 506, 3929-B, 3929-B1, 3930-B, 3930-B1, 3931-B, 3931-B1
Test Model No:	TG3841-10
Remark: All above models are identical in the same PCB layout, interior structure and electrical circuits. The differences are appearance color and model name for commercial purpose.	
Test sample(s) ID:	GTS202110000007-1
Sample(s) Status:	Engineer sample
S/N:	N/A
Hardware Version:	V1.0.0
Software Version:	V1.0.0
Operation Frequency:	2420MHz~2460MHz
Channel Numbers:	41
Channel Separation:	1MHz
Modulation Type:	GFSK
Antenna Type:	Wire Antenna
Antenna Gain:	1.0dBi(declare by applicant)
Power Supply:	DC 4.5V, 3*1.5V size AAA battery

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2420 MHz	12	2431 MHz	23	2442 MHz	34	2453 MHz
2	2421 MHz	13	2432 MHz	24	2443 MHz	35	2454 MHz
3	2422 MHz	14	2433 MHz	25	2444 MHz	36	2455 MHz
4	2423 MHz	15	2434 MHz	26	2445 MHz	37	2456 MHz
5	2424 MHz	16	2435 MHz	27	2446 MHz	38	2457 MHz
6	2425 MHz	17	2436 MHz	28	2447 MHz	39	2458 MHz
7	2426 MHz	18	2437 MHz	29	2448 MHz	40	2459 MHz
8	2427 MHz	19	2438 MHz	30	2449 MHz	41	2460 MHz
9	2428 MHz	20	2439 MHz	31	2450 MHz		
10	2429 MHz	21	2440 MHz	32	2451 MHz		
11	2430 MHz	22	2441 MHz	33	2452 MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The lowest channel	2420MHz
The middle channel	2440MHz
The Highest channel	2460MHz

5.2 Test mode

Transmitting mode	Keep the EUT in continuously transmitting mode.
Remark: the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.	

5.3 Description of Support Units

None.

5.4 Deviation from Standards

None.

5.5 Abnormalities from Standard Conditions

None.

5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

● **FCC—Registration No.: 381383**

Designation Number: CN5029

Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files.

● **IC —Registration No.: 9079A**

CAB identifier: CN0091

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing

● **NVLAP (LAB CODE:600179-0)**

Global United Technology Services Co., Ltd., is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP).

5.7 Test Location

All tests were performed at:

Global United Technology Services Co., Ltd.
Address: No. 123-128, Tower A, Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102
Tel: 0755-27798480
Fax: 0755-27798960

5.8 Additional Instructions

Test Software	Special test software provided by manufacturer
Power level setup	Default

6 Test Instruments list

Radiated Emission:						
Item	**Test Equipment**	**Manufacturer**	**Model No.**	**Inventory No.**	**Cal.Date (mm-dd-yy)**	**Cal.Due date (mm-dd-yy)**
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	July. 02 2020	July. 01 2025
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	June. 24 2021	June. 23 2022
4	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	GTS214	June. 24 2021	June. 23 2022
5	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120 D	GTS208	June. 24 2021	June. 23 2022
6	Horn Antenna	ETS-LINDGREN	3160	GTS217	June. 24 2021	June. 23 2022
7	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
8	Coaxial Cable	GTS	N/A	GTS213	June. 24 2021	June. 23 2022
9	Coaxial Cable	GTS	N/A	GTS211	June. 24 2021	June. 23 2022
10	Coaxial cable	GTS	N/A	GTS210	June. 24 2021	June. 23 2022
11	Coaxial Cable	GTS	N/A	GTS212	June. 24 2021	June. 23 2022
12	Amplifier(100kHz-3GHz)	HP	8347A	GTS204	June. 24 2021	June. 23 2022
13	Amplifier(2GHz-20GHz)	HP	84722A	GTS206	June. 24 2021	June. 23 2022
14	Amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	June. 24 2021	June. 23 2022
15	Band filter	Amindeon	82346	GTS219	June. 24 2021	June. 23 2022
16	Power Meter	Anritsu	ML2495A	GTS540	June. 24 2021	June. 23 2022
17	Power Sensor	Anritsu	MA2411B	GTS541	June. 24 2021	June. 23 2022
18	Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	GTS575	June. 24 2021	June. 23 2022
19	Splitter	Agilent	11636B	GTS237	June. 24 2021	June. 23 2022
20	Loop Antenna	ZHINAN	ZN30900A	GTS534	June. 24 2021	June. 23 2022
21	Breitband hornantenne	SCHWARZBECK	BBHA 9170	GTS579	Oct. 17 2021	Oct. 16 2022
22	Amplifier	TDK	PA-02-02	GTS574	Oct. 17 2021	Oct. 16 2022
23	Amplifier	TDK	PA-02-03	GTS576	Oct. 17 2021	Oct. 16 2022
24	PSA Series Spectrum Analyzer	Rohde & Schwarz	FSP	GTS578	June. 24 2021	June. 23 2022

RF Conducted Test:						
Item	**Test Equipment**	**Manufacturer**	**Model No.**	**Serial No.**	**Cal.Date (mm-dd-yy)**	**Cal.Due date (mm-dd-yy)**
1	MXA Signal Analyzer	Agilent	N9020A	GTS566	June. 24 2021	June. 23 2022
2	EMI Test Receiver	R&S	ESCI 7	GTS552	June. 24 2021	June. 23 2022
3	Spectrum Analyzer	Agilent	E4440A	GTS533	June. 24 2021	June. 23 2022
4	MXG vector Signal Generator	Agilent	N5182A	GTS567	June. 24 2021	June. 23 2022
5	ESG Analog Signal Generator	Agilent	E4428C	GTS568	June. 24 2021	June. 23 2022
6	USB RF Power Sensor	DARE	RPR3006W	GTS569	June. 24 2021	June. 23 2022
7	RF Switch Box	Shongyi	RFSW3003328	GTS571	June. 24 2021	June. 23 2022
8	Programmable Constant Temp & Humi Test Chamber	WEWON	WHTH-150L-40-880	GTS572	June. 24 2021	June. 23 2022

General used equipment:						
Item	**Test Equipment**	**Manufacturer**	**Model No.**	**Inventory No.**	**Cal.Date (mm-dd-yy)**	**Cal.Due date (mm-dd-yy)**
1	Humidity/ Temperature Indicator	KTJ	TA328	GTS243	June. 24 2021	June. 23 2022
2	Barometer	ChangChun	DYM3	GTS255	June. 24 2021	June. 23 2022

7 Test results and Measurement Data

7.1 Antenna requirement

Standard requirement:	FCC Part15 C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. **15.247(c) (1)(i) requirement:** (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.	
E.U.T Antenna:	
The antenna is Wire antenna, the best case gain of the is 1.0dBi, reference to the appendix II for details	

7.2 Conducted Output Power

Test Requirement:	FCC Part15 C Section 15.247 (b)(3)
Test Method:	ANSI C63.10:2013 and KDB558074 D01 15.247 Meas Guidance v05r02
Limit:	30dBm
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data: The detailed test data see Appendix for 2.4G.

7.3 Channel Bandwidth

Test Requirement:	FCC Part15 C Section 15.247 (a)(2)
Test Method:	ANSI C63.10:2013 and KDB558074 D01 15.247 Meas Guidance v05r02
Limit:	>500KHz
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data: The detailed test data see Appendix for 2.4G.

7.4 Power Spectral Density

Test Requirement:	FCC Part15 C Section 15.247 (e)
Test Method:	ANSI C63.10:2013 and KDB558074 D01 15.247 Meas Guidance v05r02
Limit:	8dBm/3kHz
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data: The detailed test data see Appendix for 2.4G.

7.5 Spurious Emission in Non-restricted & restricted Bands

7.5.1 Conducted Emission Method

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	ANSI C63.10:2013 and KDB558074 D01 15.247 Meas Guidance v05r02
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data: The detailed test data see Appendix for 2.4G.

7.5.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209
Test Method:	ANSI C63.10:2013
Test Frequency Range:	9kHz to 25GHz
Test site:	Measurement Distance: 3m

Receiver setup:

Frequency	Detector	RBW	VBW	Value
9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak
Above 1GHz	Peak	1MHz	3MHz	Peak
	Peak	1MHz	10Hz	Average

Limit:

Frequency	Limit (uV/m)	Value	Measurement Distance
0.009MHz-0.490MHz	2400/F(KHz)	QP	300m
0.490MHz-1.705MHz	24000/F(KHz)	QP	30m
1.705MHz-30MHz	30	QP	30m
30MHz-88MHz	100	QP	3m
88MHz-216MHz	150	QP	
216MHz-960MHz	200	QP	
960MHz-1GHz	500	QP	
Above 1GHz	500	Average	
	5000	Peak	

Test setup:

For radiated emissions from 9kHz to 30MHz



For radiated emissions from 30MHz to1GHz



For radiated emissions above 1GHz



Test Procedure:

1. The EUT was placed on the top of a rotating table (0.8m for below 1G and 1.5m for above 1G) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Test Instruments:	Refer to section 6.0 for details					
Test mode:	Refer to section 5.2 for details					
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar
Test voltage:	DC 3.7V					
Test results:	Pass					

Measurement data:

Remark:
Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis which it is worse case.

■ **9kHz~30MHz**

The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

■ **Below 1GHz**

Pre-scan all test modes, found worst case at 2460MHz, and so only show the test result of 2460MHz

Horizontal:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
35.375	38.14	12.56	0.61	35.38	15.93	40.00	-24.07	QP
55.805	37.50	12.51	0.82	36.27	14.56	40.00	-25.44	QP
151.597	33.21	12.80	1.58	37.09	10.50	43.50	-33.00	QP
404.667	33.31	14.82	2.88	37.52	13.49	46.00	-32.51	QP
793.396	33.10	22.15	4.43	37.62	22.06	46.00	-23.94	QP
968.934	33.75	23.99	5.11	37.54	25.31	54.00	-28.69	QP

Vertical:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
36.381	38.04	12.71	0.62	35.45	15.92	40.00	-24.08	QP
47.826	37.27	13.01	0.75	36.08	14.95	40.00	-25.05	QP
109.796	40.61	9.96	1.28	36.80	15.05	43.50	-28.45	QP
170.195	33.82	12.42	1.69	37.19	10.74	43.50	-32.76	QP
796.183	33.67	22.19	4.45	37.62	22.69	46.00	-23.31	QP
979.180	32.52	23.99	5.14	37.53	24.12	54.00	-29.88	QP

- **Above 1GHz**
- **Unwanted Emissions in Restricted Frequency Bands**

Test channel:	Lowest	Polarization:	Horizontal



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4840.000	23.91	31.26	4.65	37.74	22.08	54.00	-31.92	Average
4840.000	39.49	31.26	4.65	37.74	37.66	74.00	-36.34	Peak
7260.000	16.85	36.30	6.55	35.62	24.08	54.00	-29.92	Average
7260.000	27.58	36.30	6.55	35.62	34.81	74.00	-39.19	Peak
9680.000	19.74	38.00	8.00	34.97	30.77	54.00	-23.23	Average
9680.000	28.07	38.00	8.00	34.97	39.10	74.00	-34.90	Peak

Test channel:	Lowest	Polarization:	Vertical



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4840.000	23.25	31.26	4.65	37.74	21.42	54.00	-32.58	Average
4840.000	35.72	31.26	4.65	37.74	33.89	74.00	-40.11	Peak
7260.000	17.29	36.30	6.55	35.62	24.52	54.00	-29.48	Average
7260.000	27.92	36.30	6.55	35.62	35.15	74.00	-38.85	Peak
9680.000	19.44	38.00	8.00	34.97	30.47	54.00	-23.53	Average
9680.000	26.94	38.00	8.00	34.97	37.97	74.00	-36.03	Peak

Test channel:	Middle	Polarization:	Horizontal



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4880.000	24.91	31.31	4.69	37.75	23.16	54.00	-30.84	Average
4880.000	37.78	31.31	4.69	37.75	36.03	74.00	-37.97	Peak
7320.000	17.53	36.43	6.63	35.60	24.99	54.00	-29.01	Average
7320.000	27.16	36.43	6.63	35.60	34.62	74.00	-39.38	Peak
9760.000	19.95	38.10	8.03	35.03	31.05	54.00	-22.95	Average
9760.000	27.09	38.10	8.03	35.03	38.19	74.00	-35.81	Peak

Test channel:	Middle	Polarization:	Vertical



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4880.000	27.25	31.31	4.69	37.75	25.50	54.00	-28.50	Average
4880.000	39.52	31.31	4.69	37.75	37.77	74.00	-36.23	Peak
7320.000	18.41	36.43	6.63	35.60	25.87	54.00	-28.13	Average
7320.000	28.94	36.43	6.63	35.60	36.40	74.00	-37.60	Peak
9760.000	19.82	38.10	8.03	35.03	30.92	54.00	-23.08	Average
9760.000	26.78	38.10	8.03	35.03	37.88	74.00	-36.12	Peak

Test channel:	Highest	Polarization:	Horizontal



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4920.000	25.77	31.37	4.75	37.77	24.12	54.00	-29.88	Average
4920.000	39.08	31.37	4.75	37.77	37.43	74.00	-36.57	Peak
7380.000	16.44	36.57	6.69	35.58	24.12	54.00	-29.88	Average
7380.000	28.55	36.57	6.69	35.58	36.23	74.00	-37.77	Peak
9840.000	18.84	38.20	8.06	35.09	30.01	54.00	-23.99	Average
9840.000	27.79	38.20	8.06	35.09	38.96	74.00	-35.04	Peak

Test channel:	Highest	Polarization:	Vertical



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4920.000	25.95	31.37	4.75	37.77	24.30	54.00	-29.70	Average
4920.000	41.90	31.37	4.75	37.77	40.25	74.00	-33.75	Peak
7380.000	16.61	36.57	6.69	35.58	24.29	54.00	-29.71	Average
7380.000	28.36	36.57	6.69	35.58	36.04	74.00	-37.96	Peak
9840.000	18.98	38.20	8.06	35.09	30.15	54.00	-23.85	Average
9840.000	26.70	38.20	8.06	35.09	37.87	74.00	-36.13	Peak

Remarks:

1. *Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
2. *The emission levels of frequencies range from 18GHz-25GHz are very lower than the limit and not show in test report.*

■ **Unwanted Emissions in Non-restricted Frequency Bands**

Test channel:	Lowest	Polarization:	Horizontal



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	30.68	27.14	2.81	38.64	21.99	54.00	-32.01	Average
2310.000	40.99	27.14	2.81	38.64	32.30	74.00	-41.70	Peak
2390.000	30.54	27.37	2.91	38.84	21.98	54.00	-32.02	Average
2390.000	43.79	27.37	2.91	38.84	35.23	74.00	-38.77	Peak

Test channel:	Lowest	Polarization:	Vertical



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	27.98	27.14	2.81	34.94	22.99	54.00	-31.01	Average
2310.000	38.83	27.14	2.81	34.94	33.84	74.00	-40.16	Peak
2390.000	26.45	27.37	2.91	34.78	21.95	54.00	-32.05	Average
2390.000	36.88	27.37	2.91	34.78	32.38	74.00	-41.62	Peak

Test channel:	Highest	Polarization:	Horizontal



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2483.500	27.49	27.66	2.99	34.60	23.54	54.00	-30.46	Average
2483.500	35.70	27.66	2.99	34.60	31.75	74.00	-42.25	Peak
2500.000	27.88	27.70	3.01	34.57	24.02	54.00	-29.98	Average
2500.000	37.95	27.70	3.01	34.57	34.09	74.00	-39.91	Peak

Test channel:	Highest	Polarization:	Vertical



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2483.500	28.87	27.66	2.99	34.60	24.92	54.00	-29.08	Average
2483.500	37.11	27.66	2.99	34.60	33.16	74.00	-40.84	Peak
2500.000	28.88	27.70	3.01	34.57	25.02	54.00	-28.98	Average
2500.000	37.52	27.70	3.01	34.57	33.66	74.00	-40.34	Peak

Remarks:

1. *Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
2. *The emission levels of other frequencies are very lower than the limit and not show in test report.*

8 Test Setup Photo

Reference to the **appendix I** for details.

9 EUT Constructional Details

Reference to the **appendix II** for details.

------End------