FCC TEST REPORT

Client Name	:	Shenzhen Qili Audio Application CO., Ltd.
Address	:	7F, Nanhang Buiding, No.7 Langshan Road, Hi-Tech Industrial Park (North), Nanshan district, Shenzhen, 518057 China
Product Name	:	qdc TWX
Date	:	May 25, 2022

Shenzhen Anbotek Compliance Laboratory Limited

Contents

1. General Information 5
1.1. Client Information 5
1.2. Description of Device (EUT) 5
1.3. Auxiliary Equipment Used During Test 6
1.4. Description of Test Modes 6
1.5. List of channels 7
1.6. Description Of Test Setup 8
1.7. Test Equipment List 9
1.8. Measurement Uncertainty 10
1.9. Description of Test Facility 10
2. Summary of Test Results 11
3. Conducted Emission Test 12
3.1. Test Standard and Limit 12
3.2. Test Setup 12
3.3. Test Procedure 12
3.4. Test Data 12
4. Radiation Spurious Emission and Band Edge 17
4.1. Test Standard and Limit 17
4.2. Test Setup 17
4.3. Test Procedure 18
4.4. Test Data 19
5. Maximum Peak Output Power Test 27
5.1. Test Standard and Limit 27
5.2. Test Setup 27
5.3. Test Procedure 27
5.4. Test Data 27
6. 20DB Occupy Bandwidth Test 28
6.1. Test Standard 28
6.2. Test Setup 28
6.3. Test Procedure 28
6.4. Test Data 28
7. Carrier Frequency Separation Test 29
7.1. Test Standard and Limit 29
7.2. Test Setup 29
7.3. Test Procedure 29
7.4. Test Data 29
8. Number of Hopping Channel Test 30
8.1. Test Standard and Limit 30

8.2. Test Setup 30
8.3. Test Procedure 30
8.4. Test Data 30
9. Dwell Time Test 31
9.1. Test Standard and Limit 31
9.2. Test Setup 31
9.3. Test Procedure 31
9.4. Test Data 31
10. 100kHz Bandwidth of Frequency Band Edge Requirement 32
10.1. Test Standard and Limit 32
10.2. Test Setup 32
10.3. Test Procedure 32
10.4. Test Data 32
11. Antenna Requirement 33
11.1. Test Standard and Requirement 33
11.2. Antenna Connected Construction 33
APPENDIX I -- TEST SETUP PHOTOGRAPH 34
APPENDIX II -- EXTERNAL PHOTOGRAPH 36
APPENDIX III -- INTERNAL PHOTOGRAPH 43
APPENDIX IV – Appendix Test Data 50

TEST REPORT

Applicant	:	Shenzhen Qili Audio Application CO., Ltd.
Manufacturer	:	CHANGSHU OBO SEAHORN ACOUSTICS ELECTRONIC Co.,Ltd.
Product Name	:	qdc TWX
Model No.	:	qdc TWX
Trade Mark	:	qdc
Rating(s)	:	Charging Box Input: DC 5V, 0.6A(with DC 3.7V, 700mAh Battery inside) Earphone Input: DC 5V, 60mA(with DC 3.7V, 222mAh Battery inside)
Test Standard(s)	**:**	**FCC Part15 Subpart C, Section 15.247**
Test Method(s)	**:**	**ANSI C63.10: 2020**

The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC Part 15 Subpart C requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited.

Date of receipt	Mar. 28, 2022
Date of Test	Mar. 28~Apr. 14, 2022
Prepared by	Nian xiu Chen (Nianxiu Chen)
Approved & Authorized Signer	Kingkongjin (Kingkong Jin)

1. General Information

1.1. Client Information

Applicant	:	Shenzhen Qili Audio Application CO., Ltd.
Address	:	7F, Nanhang Buiding, No.7 Langshan Road, Hi-Tech Industrial Park (North), Nanshan district, Shenzhen, 518057 China
Manufacturer	:	CHANGSHU OBO SEAHORN ACOUSTICS ELECTRONIC Co.,Ltd.
Address	:	Building F, No.15 , Dianchang Rd,Bad Dist.City Jiangsu Z15513 China
Factory	:	CHANGSHU OBO SEAHORN ACOUSTICS ELECTRONIC Co.,Ltd.
Address	:	Building F, No.15 , Dianchang Rd,Bad Dist.City Jiangsu Z15513 China

1.2. Description of Device (EUT)

Product Name	:	qdc TWX	
Model No.	:	qdc TWX	
Trade Mark	:	qdc	
Test Power Supply	:	AC 120V, 60Hz for adapter/ AC 240V, 60Hz for adapter/ DC 3.7V Battery inside	
Test Sample No.	:	1-2-1(Normal Sample), 1-2-2(Engineering Sample)	
Product Description	:	Operation Frequency:	2402-2480MHz
		Number of Channel:	79 Channels
		Modulation Type:	GFSK, π/4-DQPSK, 8-DPSK
		Antenna Type:	FPC Antenna
		Antenna Gain(Peak):	1.94 dBi (Provided by customer)
		Adapter:	N/A
Remark: 1) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual. 2) This report is for BDR+EDR module.			

1.3. Auxiliary Equipment Used During Test

Adapter	:	M/N: A2023 Input: AC 100-240V, 0.7A, 50-60Hz USB1 Output: DC 5V, 2.4A USB2 Output: DC 5V, 2.4A

1.4. Description of Test Modes

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

TEST MODE:

Mode 1	GFSK	CH00	TX+ Charging Mode/TX Only
Mode 2		CH39	
Mode 3		CH78	
Mode 4	π/4-DQPSK	CH00	
Mode 5		CH39	
Mode 6		CH78	
Mode 7	8-DPSK	CH00	
Mode 8		CH39	
Mode 9		CH78	

Note:

(1) The measurements are performed at the highest, middle, lowest available channels.

(2)The data rate was set in 1Mbps for radiated emission due to the highest RF output power.

1.5. List of channels

Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
00	2402	17	2419	34	2436	51	2453	68	2470
01	2403	18	2420	35	2437	52	2454	69	2471
02	2404	19	2421	36	2438	53	2455	70	2472
03	2405	20	2422	37	2439	54	2456	71	2473
04	2406	21	2423	38	2440	55	2457	72	2474
05	2407	22	2424	39	2441	56	2458	73	2475
06	2408	23	2425	40	2442	57	2459	74	2476
07	2409	24	2426	41	2443	58	2460	75	2477
08	2410	25	2427	42	2444	59	2461	76	2478
09	2411	26	2428	43	2445	60	2462	77	2479
10	2412	27	2429	44	2446	61	2463	78	2480
11	2413	28	2430	45	2447	62	2464		
12	2414	29	2431	46	2448	63	2465		
13	2415	30	2432	47	2449	64	2466		
14	2416	31	2433	48	2450	65	2467		
15	2417	32	2434	49	2451	66	2468		
16	2418	33	2435	50	2452	67	2469		

Note:

1. The engineering test program was provided and the EUT was programmed to be in continuously transmitting mode.
2. EUT built-in battery-powered, fully-charged battery use of the test battery.

1.6. Description Of Test Setup

CE



RE



1.7. Test Equipment List

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Three Phase V-type Artificial Power Network	CYBERTEK	EM5040DT	E215040DT001	Jul 05, 2021	1 Year
2.	EMI Test Receiver	Rohde & Schwarz	ESCI	100627	Oct. 22, 2021	1 Year
3.	EMI Test Receiver	Rohde & Schwarz	ESR26	101481	Oct. 22, 2021	1 Year
4.	RF Switching Unit	Compliance Direction	RSU-M2	38303	Oct. 22, 2021	1 Year
5.	MAX Spectrum Analysis	Agilent	N9020A	MY51170037	Oct. 22, 2021	1 Year
6.	Preamplifier	SKET Electronic	BK1G18G30D	KD17503	Oct. 22, 2021	1 Year
7.	Double Ridged Horn Antenna	Instruments corporation	GTH-0118	351600	Oct. 22, 2021	2 Year
8.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	VULB 9163-289	Oct. 22, 2021	2 Year
9.	Loop Antenna	Schwarzbeck	FMZB1519B	00053	Oct. 22, 2021	2 Year
10.	Horn Antenna	A-INFO	LB-180400-KF	J211060628	Oct. 22, 2021	2 Year
11.	Pre-amplifier	SONOMA	310N	186860	Oct. 22, 2021	1 Year
12.	EMI Test Software EZ-EMC	SHURPLE	N/A	N/A	N/A	N/A
13.	RF Test Control System	YIHENG	YH3000	2017430	Oct. 22, 2021	1 Year
14.	Power Sensor	DAER	RPR3006W	15I00041SN045	Oct. 22, 2021	1 Year
15.	Power Sensor	DAER	RPR3006W	15I00041SN046	Oct. 22, 2021	1 Year
16.	MXA Spectrum Analysis	KEYSIGHT	N9020A	MY53280032	Oct. 22, 2021	1 Year
17.	MXG RF Vector Signal Generator	Agilent	N5182A	MY48180656	Oct. 22, 2021	1 Year
18.	Signal Generator	Agilent	E4421B	MY41000743	Oct. 22, 2021	1 Year
19.	DC Power Supply	IVYTECH	IV3605	1804D360510	Oct. 22, 2021	1 Year
20.	Constant Temperature Humidity Chamber	ZHONGJIAN	ZJ-KHWS80B	N/A	Oct. 22, 2021	1 Year

1.8. Measurement Uncertainty

Radiation Uncertainty	:	Ur = 3.9 dB (Horizontal)
		Ur = 3.8 dB (Vertical)
Conduction Uncertainty	:	Uc = 3.4 dB

1.9. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 184111

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No. 184111.

ISED-Registration No.: 8058A

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (ISED) Innovation, Science and Economic Development Canada. The acceptance letter from the ISED is maintained in our files. Registration 8058A.

Test Location

Shenzhen Anbotek Compliance Laboratory Limited.
1/F, Building D, Sogood Science and Technology Park, Sanwei community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.518102

2. Summary of Test Results

Standard Section	Test Item	Result
15.203/15.247(c)	Antenna Requirement	PASS
15.207	Conducted Emission	PASS
15.205/15.209	Spurious Emission	PASS
15.247(b)(1)	Conducted Peak Output Power	PASS
15.247(a)(1)	20dB Occupied Bandwidth	PASS
15.247(a)(1)	Carrier Frequencies Separation	PASS
15.247(a)(1)	Hopping Channel Number	PASS
15.247(a)(1)	Dwell Time	PASS
15.247(d)	Band Edge	PASS
Remark: “N/A” is an abbreviation for Not Applicable.		

3. Conducted Emission Test

3.1. Test Standard and Limit

Test Standard	FCC Part15 Section 15.207		
Test Limit	Frequency	Maximum RF Line Voltage (dBuV)	
		Quasi-peak Level	Average Level
	150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
	500kHz~5MHz	56	46
	5MHz~30MHz	60	50
Remark: (1) *Decreasing linearly with logarithm of the frequency. (2) The lower limit shall apply at the transition frequency.			

3.2. Test Setup



3.3. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC ANSI C63.10: 2020 on Conducted Emission Measurement.

The bandwidth of test receiver (ESCI) set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.

3.4. Test Data

During the test, pre-scan all modes, only the worst case is recorded in the report.

Please to see the following pages.

Conducted Emission Test Data

Test Site: 1# Shielded Room
Operating Condition: Mode 1
Test Specification: AC 120V, 60Hz for adapter
Comment: Live Line
Tem.: 23.1℃ Hum.: 49%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBpW)	Limit (dBpW)	Over Limit (dB)	Detector	Remark
1	0.1500	49.44	0.11	49.55	65.99	-16.44	QP	
2	0.1500	30.63	0.11	30.74	55.99	-25.25	AVG	
3	0.1700	30.75	0.12	30.87	54.96	-24.09	AVG	
4	0.1940	46.06	0.12	46.18	63.86	-17.68	QP	
5	0.5340	41.99	0.15	42.14	56.00	-13.86	QP	
6	0.5340	28.65	0.15	28.80	46.00	-17.20	AVG	
7	0.9860	19.25	0.15	19.40	46.00	-26.60	AVG	
8	1.0420	34.63	0.15	34.78	56.00	-21.22	QP	
9	1.2980	34.35	0.14	34.49	56.00	-21.51	QP	
10	1.3540	19.00	0.14	19.14	46.00	-26.86	AVG	
11	1.6300	34.63	0.13	34.76	56.00	-21.24	QP	
12	1.6660	19.42	0.13	19.55	46.00	-26.45	AVG	

Conducted Emission Test Data

Test Site: 1# Shielded Room

Operating Condition: Mode 1

Test Specification: AC 120V, 60Hz for adapter

Comment: Neutral Line

Tem.: 23.1℃ Hum.: 49%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBpW)	Limit (dBpW)	Over Limit (dB)	Detector	Remark
1	0.1500	31.65	0.11	31.76	55.99	-24.23	AVG	
2	0.1660	48.81	0.12	48.93	65.15	-16.22	QP	
3	0.1900	29.30	0.12	29.42	54.03	-24.61	AVG	
4	0.2180	26.96	0.12	27.08	52.89	-25.81	AVG	
5	0.2700	23.19	0.13	23.32	51.12	-27.80	AVG	
6	0.2779	39.40	0.13	39.53	60.88	-21.35	QP	
7	0.5260	40.23	0.15	40.38	56.00	-15.62	QP	
8	0.5299	27.40	0.15	27.55	46.00	-18.45	AVG	
9	1.0660	31.76	0.15	31.91	56.00	-24.09	QP	
10	1.5820	17.70	0.13	17.83	46.00	-28.17	AVG	
11	1.6260	31.07	0.13	31.20	56.00	-24.80	QP	
12	3.6420	29.99	0.12	30.11	56.00	-25.89	QP	

Conducted Emission Test Data

Test Site: 1# Shielded Room

Operating Condition: Mode 1

Test Specification: AC 240V, 60Hz for adapter

Comment: Live Line

Tem.: 23.1℃ Hum.: 49%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBpW)	Limit (dBpW)	Over Limit (dB)	Detector	Remark
1	0.4140	26.50	0.12	26.62	47.57	-20.95	AVG	
2	0.4340	27.35	0.12	27.47	47.18	-19.71	AVG	
3	0.5420	31.62	0.15	31.77	46.00	-14.23	AVG	
4	0.5580	42.06	0.15	42.21	56.00	-13.79	QP	
5	0.9220	37.61	0.15	37.76	56.00	-18.24	QP	
6	1.0060	38.35	0.15	38.50	56.00	-17.50	QP	
7	1.0700	24.96	0.15	25.11	46.00	-20.89	AVG	
8	1.0820	38.66	0.15	38.81	56.00	-17.19	QP	
9	1.0940	39.12	0.15	39.27	56.00	-16.73	QP	
10	1.7580	24.03	0.13	24.16	46.00	-21.84	AVG	
11	1.8620	38.86	0.12	38.98	56.00	-17.02	QP	
12	2.6220	22.58	0.12	22.70	46.00	-23.30	AVG	

Conducted Emission Test Data

Test Site: 1# Shielded Room
Operating Condition: Mode 1
Test Specification: AC 240V, 60Hz for adapter
Comment: Neutral Line
Tem.: 23.1℃ Hum.: 49%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBpW)	Limit (dBpW)	Over Limit (dB)	Detector	Remark
1	0.1539	45.65	0.12	45.77	65.78	-20.01	QP	
2	0.1660	45.24	0.12	45.36	65.15	-19.79	QP	
3	0.2180	42.50	0.12	42.62	62.89	-20.27	QP	
4	0.4340	25.74	0.12	25.86	47.18	-21.32	AVG	
5	0.4540	25.35	0.13	25.48	46.80	-21.32	AVG	
6	0.5620	41.13	0.15	41.28	56.00	-14.72	QP	
7	0.5620	29.75	0.15	29.90	46.00	-16.10	AVG	
8	1.0580	36.30	0.15	36.45	56.00	-19.55	QP	
9	1.1340	36.66	0.15	36.81	56.00	-19.19	QP	
10	1.1500	24.15	0.15	24.30	46.00	-21.70	AVG	
11	1.6740	22.12	0.13	22.25	46.00	-23.75	AVG	
12	3.2460	20.65	0.12	20.77	46.00	-25.23	AVG	

4. Radiation Spurious Emission and Band Edge

4.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.209 and 15.205				
Test Limit	Frequency (MHz)	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz~0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz~88MHz	100	40.0	Quasi-peak	3
	88MHz~216MHz	150	43.5	Quasi-peak	3
	216MHz~960MHz	200	46.0	Quasi-peak	3
	960MHz~1000MHz	500	54.0	Quasi-peak	3
	Above 1000MHz	500	54.0	Average	3
		-	74.0	Peak	3

Remark:
(1)The lower limit shall apply at the transition frequency.
(2) 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

4.2. Test Setup



Figure 1. Below 30MHz



Figure 2. 30MHz to 1GHz



Figure 3. Above 1 GHz

4.3. Test Procedure

For below 1GHz: The EUT is placed on a turntable, which is 0.8m above the ground plane.
For above 1GHz: The EUT is placed on a turntable, which is 1.5m above the ground plane.
The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Rotated the EUT through three orthogonal axes to determine the maximum emissions, both horizontal and vertical polarization of the antenna are set on test. The EUT is tested in 9*6*6 Chamber. The device is evaluated in xyz orientation.
For the radiated emission test above 1GHz:

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

For 9kHz to 150kHz, Set the spectrum analyzer as:
RBW = 200Hz, VBW =1kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 150kHz to 30MHz, Set the spectrum analyzer as:
RBW = 9KHz, VBW =30kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 30MHz to 1000MHz, Set the spectrum analyzer as:
RBW = 120kHz, VBW =300kHz,Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For above 1GHz,Set the spectrum analyzer as:
RBW =1MHz, VBW =1MHz, Detector= Peak, Trace mode= Max hold, Sweep- auto couple.
For average measurement: use duty cycle correction factor method (DCCF)
Average level = Peak level + DCCF

4.4. Test Data

PASS

During the test, Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the X-axis is the worst case.

The test results of 9kHz-30MHz was attenuated more than 20dB below the permissible limits, so the results don't record in the report.

During the test, pre-scan all modes, only the worst case is recorded in the report.

Test Results (30~1000MHz)

Test Mode: Mode 1

Power Source: DC 3.7V battery inside

Polarization: Vertical

Temp.(℃)/Hum.(%RH): 22.7℃/49%RH



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	40.7730	28.97	-16.87	12.10	40.00	-27.90	QP			
2	52.1164	29.69	-17.29	12.40	40.00	-27.60	QP			
3	61.0245	30.80	-18.10	12.70	40.00	-27.30	QP			
4	125.2260	35.94	-20.21	15.73	43.50	-27.77	QP			
5	144.0819	35.33	-21.26	14.07	43.50	-29.43	QP			
6	639.4888	27.78	-7.92	19.86	46.00	-26.14	QP			

Test Results (30~1000MHz)

Test Mode: Mode 1

Power Source: DC 3.7V battery inside

Polarization: Horizontal

Temp.(℃)/Hum.(%RH): 22.7℃/49%RH

No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	43.3534	26.37	-16.95	9.42	40.00	-30.58	QP			
2	54.4516	26.98	-17.41	9.57	40.00	-30.43	QP			
3	107.8877	27.69	-17.97	9.72	43.50	-33.78	QP			
4	119.8556	29.27	-19.54	9.73	43.50	-33.77	QP			
5	308.9126	28.66	-14.63	14.03	46.00	-31.97	QP			
6	401.8385	28.78	-12.38	16.40	46.00	-29.60	QP			

Test Results (1GHz-25GHz)

Test Mode: CH00	Test channel: Lowest

Peak value:

Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4804.00	26.65	15.27	41.92	74.00	-32.08	Vertical
7206.00	27.90	18.09	45.99	74.00	-28.01	Vertical
9608.00	28.55	23.76	52.31	74.00	-21.69	Vertical
12010.00	*			74.00		Vertical
14412.00	*			74.00		Vertical
4804.00	27.07	15.27	42.34	74.00	-31.66	Horizontal
7206.00	27.88	18.09	45.97	74.00	-28.03	Horizontal
9608.00	28.01	23.76	51.77	74.00	-22.23	Horizontal
12010.00	*			74.00		Horizontal
14412.00	*			74.00		Horizontal

Average value:

Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4804.00	16.03	15.27	31.30	54.00	-22.70	Vertical
7206.00	16.93	18.09	35.02	54.00	-18.98	Vertical
9608.00	17.57	23.76	41.33	54.00	-12.67	Vertical
12010.00	*			54.00		Vertical
14412.00	*			54.00		Vertical
4804.00	15.42	15.27	30.69	54.00	-23.31	Horizontal
7206.00	16.94	18.09	35.03	54.00	-18.97	Horizontal
9608.00	17.32	23.76	41.08	54.00	-12.92	Horizontal
12010.00	*			54.00		Horizontal
14412.00	*			54.00		Horizontal

Test Results (1GHz-25GHz)

Test Mode: CH39	Test channel: Middle

Peak value:

Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4882.00	26.67	15.42	42.09	74.00	-31.91	Vertical
7323.00	27.75	18.02	45.77	74.00	-28.23	Vertical
9764.00	27.56	23.80	51.36	74.00	-22.64	Vertical
12205.00	*			74.00		Vertical
14646.00	*			74.00		Vertical
4882.00	26.77	15.42	42.19	74.00	-31.81	Horizontal
7323.00	27.87	18.02	45.89	74.00	-28.11	Horizontal
9764.00	27.71	23.80	51.51	74.00	-22.49	Horizontal
12205.00	*			74.00		Horizontal
14646.00	*			74.00		Horizontal

Average value:

Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4882.00	15.76	15.42	31.18	54.00	-22.82	Vertical
7323.00	17.03	18.02	35.05	54.00	-18.95	Vertical
9764.00	17.43	23.80	41.23	54.00	-12.77	Vertical
12205.00	*			54.00		Vertical
14646.00	*			54.00		Vertical
4882.00	15.33	15.42	30.75	54.00	-23.25	Horizontal
7323.00	16.50	18.02	34.52	54.00	-19.48	Horizontal
9764.00	17.83	23.80	41.63	54.00	-12.37	Horizontal
12205.00	*			54.00		Horizontal
14646.00	*			54.00		Horizontal

Test Results (1GHz-25GHz)

Test Mode: CH78	Test channel: Highest

Peak value:

Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4960.00	26.94	15.58	42.52	74.00	-31.48	Vertical
7440.00	27.76	17.93	45.69	74.00	-28.31	Vertical
9920.00	28.11	23.83	51.94	74.00	-22.06	Vertical
12400.00	*			74.00		Vertical
14880.00	*			74.00		Vertical
4960.00	26.84	15.58	42.42	74.00	-31.58	Horizontal
7440.00	27.90	17.93	45.83	74.00	-28.17	Horizontal
9920.00	28.39	23.83	52.22	74.00	-21.78	Horizontal
12400.00	*			74.00		Horizontal
14880.00	*			74.00		Horizontal

Average value:

Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4960.00	16.88	15.58	32.46	54.00	-21.54	Vertical
7440.00	18.04	17.93	35.97	54.00	-18.03	Vertical
9920.00	17.98	23.83	41.81	54.00	-12.19	Vertical
12400.00				54.00		Vertical
14880.00				54.00		Vertical
4960.00	16.77	15.58	32.35	54.00	-21.65	Horizontal
7440.00	17.87	17.93	35.80	54.00	-18.20	Horizontal
9920.00	17.73	23.83	41.56	54.00	-12.44	Horizontal
12400.00	*			54.00		Horizontal
14880.00	*			54.00		Horizontal

Remark:

1. During the test, pre-scan the GFSK, π/4QPSK, 8DPSK modulation, and found the GFSK modulation is worse case, the report only record this mode.
2. Result =Reading + Factor
3. "*" means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.

Radiated Band Edge:

Test Mode: CH00	Test channel: Lowest
	
Average Value(Vertical)	Average Value(Horizontal)
	
Peak Value(Vertical)	Peak Value(Horizontal)

Test Mode: CH78	Test channel: Highest
	
Average Value(Vertical)	Average Value(Horizontal)
	
Peak Value(Vertical)	Peak Value(Horizontal)

Remark:

1. During the test, pre-scan the GFSK, π/4QPSK, 8DPSK modulation, and found the GFSK modulation is worse case, the report only record this mode.

5. Maximum Peak Output Power Test

5.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (b)(1)
Test Limit	According to §15.247(b) (1), For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

5.2. Test Setup



5.3. Test Procedure

1. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above,
2. Spectrum Setting:
   RBW > the 20 dB bandwidth of the emission being measured
   Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel
   VBW ≥ RBW
   Sweep = auto
   Detector function = peak
   Trace = max hold

5.4. Test Data

Pass

Please refer to Appendix C of the Appendix Test Data.

6. 20DB Occupy Bandwidth Test

6.1. Test Standard

Test Standard	FCC Part15 C Section 15.247 (a)(1)

6.2. Test Setup



6.3. Test Procedure

Using the following spectrum analyzer settings:

1. Span= approximately 2 to 3 times the 20dB bandwidth, centered on a hopping channel.
2. Set the RBW ≥1% of the 20 dB bandwidth.
3. Set the VBW ≥RBW
4. Sweep time = auto couple.
5. Detector function = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.

6.4. Test Data

Pass

Please refer to Appendix A of the Appendix Test Data.

7. Carrier Frequency Separation Test

7.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (a)(1)
Test Limit	>25KHz or >two-thirds of the 20 dB bandwidth

7.2. Test Setup



7.3. Test Procedure

The EUT must have its hopping function enabled. Using the following spectrum analyzer settings:

1. Span= Wide enough to capture the peaks of two adjacent channels
2. Set the RBW =approximately 30% of the channel spacing.
3. Set the VBW ≥ RBW.
4. Sweep time = auto couple.
5. Detector function = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.

7.4. Test Data

Pass

Please refer to Appendix D of the Appendix Test Data.

8. Number of Hopping Channel Test

8.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (a)(1)
Test Limit	>15 channels

8.2. Test Setup



8.3. Test Procedure

The EUT must have its hopping function enabled. Using the following spectrum analyzer setting:

1. Span= the frequency band of operation
2. Set the RBW = less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
3. Set the VBW ≥ RBW.
4. Sweep time = auto couple.
5. Detector function = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.

8.4. Test Data

Pass

Please refer to Appendix F of the Appendix Test Data.