

FCC 47 CFR PART 15 SUBPART C

CERTIFICATION TEST REPORT for BLE

For

Product: Smart Lighting

MODEL No.: S7RN5S

FCC ID: 2AROU-7887

REPORT NO:ES190320988E02

ISSUE DATE:April 02, 2019

Prepared for

**Flying Basketball LLC
1560 Sawgrass Corporate Parkway, 4th Floor, Sunrise, Florida, United
States**

Prepared by

EMTEK(SHENZHEN) CO., LTD.

**Bldg 69, Majialong Industry Zone, Nanshan District, Shenzhen,
Guangdong, China
TEL: 86-755-26954280
FAX: 86-755-26954282**

Table of Contents

1	TEST RESULT CERTIFICATION	3
2	EUT TECHNICAL DESCRIPTION	4
3	SUMMARY OF TEST RESULT	5
4	TEST METHODOLOGY	6
4.1	GENERAL DESCRIPTION OF APPLIED STANDARDS	6
4.2	MEASUREMENT EQUIPMENT USED	6
4.3	DESCRIPTION OF TEST MODES	8
5	FACILITIES AND ACCREDITATIONS	9
5.1	FACILITIES	9
5.2	LABORATORY ACCREDITATIONS AND LISTINGS	9
6	TEST SYSTEM UNCERTAINTY	10
7	SETUP OF EQUIPMENT UNDER TEST	11
7.1	RADIO FREQUENCY TEST SETUP 1	11
7.2	RADIO FREQUENCY TEST SETUP 2	11
7.3	CONDUCTED EMISSION TEST SETUP	12
7.4	SUPPORT EQUIPMENT	13
8	TEST REQUIREMENTS	14
8.1	DTS 6DB BANDWIDTH	14
8.2	MAXIMUM PEAK CONDUCTED OUTPUT POWER	17
8.3	MAXIMUM POWER SPECTRAL DENSITY	18
8.4	UNWANTED EMISSIONS IN NON-RESTRICTED FREQUENCY BANDS	21
8.5	RADIATED SPURIOUS EMISSION	28
8.6	CONDUCTED EMISSIONS TEST	70
8.7	ANTENNA APPLICATION	73

1 TEST RESULT CERTIFICATION

Applicant:	Flying Basketball LLC 1560 Sawgrass Corporate Parkway, 4th Floor, Sunrise, Florida, United States
Manufacturer:	Flying Basketball LLC 1560 Sawgrass Corporate Parkway, 4th Floor, Sunrise, Florida, United States
Product Description:	Smart Lighting
Model Number:	S7RN5S
File Number:	ES190320988E02

Measurement Procedure Used:

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
FCC 47 CFR Part 2, Subpart J FCC 47 CFR Part 15, Subpart C ANSI C63.10-2013	PASS

The above equipment was tested by EMTEK(SHENZHEN) CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 2, Part 15.247

The test results of this report relate only to the tested sample identified in this report

Date of Test : March 15, 2018 to April 29, 2018

Prepared by:

Yaping Shen

Yaping Shen/Editor

Reviewer:

Sevin Li

Sevin Li /Supervisor

Approve & Authorized Signer :

Lisa Wang

Lisa Wang/Manager



2 EUT TECHNICAL DESCRIPTION

This product contains BT, WIFI, and this report only shows the test results for BT .

Characteristics	Description
Data Rate	1Mbps for GFSK modulation
Modulation	GFSK modulation (1Mbps)
Operating Frequency Range	2402-2480MHz
Number of Channels	40 channels
Antenna Type	PCB Antenna
Antenna Gain	5.2dBi
Transmit Power Max	9.84dBm
Power supply	AC100-240V 50/60Hz

Note: for more details, please refer to the User's manual of the EUT.

3 SUMMARY OF TEST RESULT

FCC Part Clause	Test Parameter	Verdict	Remark
15.247(a)(2)	DTS (6dB) Bandwidth	PASS	
15.247(b)(3)	Maximum Peak Conducted Output Power	PASS	
15.247(e)	Maximum Power Spectral Density Level	PASS	
15.247(d)	Unwanted Emission Into Non-Restricted Frequency Bands	PASS	
15.247(d) 15.209	Unwanted Emission Into Restricted Frequency Bands (conducted)	PASS	
15.247(d) 15.209	Radiated Spurious Emission	PASS	
15.207	Conducted Emission Test	PASS	
15.203	Antenna Application	PASS	
	NOTE1: N/A (Not Applicable) NOTE2: According to FCC OET KDB 558074, the report use radiated measurements in the restricted frequency bands. In addition, the radiated test is also performed to ensure the emissions emanating from the device cabinet also comply with the applicable limits.		

RELATED SUBMITTAL(S) / GRANT(S):

This submittal(s) (test report) is intended for FCC ID: 2AROU-7887 filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

4 TEST METHODOLOGY

4.1 GENERAL DESCRIPTION OF APPLIED STANDARDS

According to its specifications, the EUT must comply with the requirements of the following standards:

FCC 47 CFR Part 2, Subpart J

FCC 47 CFR Part 15, Subpart C

FCC KDB 558074 D01 DTS Meas Guidance v05r02

4.2 MEASUREMENT EQUIPMENT USED

4.2.1 Conducted Emission Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LASTCAL.	DUE CAL.
Test Receiver	Rohde & Schwarz	ESCI	26115-010-0027	May 20, 2018	May 19, 2019
L.I.S.N.	Rohde & Schwarz	ENV216	101161	May 20, 2018	May 19, 2019
50ΩCoaxial Switch	Anritsu	MP59B	6100175589	May 20, 2018	May 19, 2019

4.2.2 For 3m Radiated Emission Measurement 9K-30M (3m chamber 1#)

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
EMI Test Receiver	Rohde & Schwarz	ESU	1302.6005.26	May 20, 2018	May 19, 2019
Loop Antenna	Schwarzbeck	FMZB 1519	1519-012	May 20, 2018	May 19, 2019
Cable	/	3M SF104-26.5	295838/4	May 20, 2018	May 19, 2019
Cable	/	6M SF104-26.5	295840/4	May 20, 2018	May 19, 2019

4.2.3 For 3m Radiated Emission Measurement 30M-1G (3m chamber 1#)

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	DUE CAL.
EMI Test Receiver	Rohde & Schwarz	ESU	1302.6005.26	May 19, 2018	May 18, 2019
Pre-Amplifier	HP	8447F	2944A07999	May 19, 2018	May 18, 2019
Bilog Antenna	Schwarzbeck	VULB9163	142	May 20, 2018	May 19, 2019
Cable	Schwarzbeck	AK9513	ACRX1	May 20, 2018	May 19, 2019
Cable	Rosenberger	N/A	FP2RX2	May 20, 2018	May 19, 2019
Cable	Schwarzbeck	AK9513	CRPX1	May 20, 2018	May 19, 2019
Cable	Schwarzbeck	AK9513	CRRX2	May 20, 2018	May 19, 2019

4.2.4 For 3m Radiated Emission Measurement 1G-18G (3m chamber 1#)

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	DUE CAL.
EMI Test Receiver	Rohde & Schwarz	ESU	1302.6005.26	May 19, 2018	May 18, 2019
Pre-Amplifier	A.H.	PAM-0126	1415261	May 20, 2018	May 19, 2019
Horn Antenna	Schwarzbeck	BBHA 9120	707	May 20, 2018	May 19, 2019
Cable	H+B	0.5M SF104-26.5	289147/4	May 20, 2018	May 19, 2019
Cable	H+B	3M SF104-26.5	295838/4	May 20, 2018	May 19, 2019
Cable	H+B	6M SF104-26.5	295840/4	May 20, 2018	May 19, 2019

4.2.5 For 3m Radiated Emission Measurement 18G-26.5G (3m chamber 1#)

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	DUE CAL.
EMI Test Receiver	Rohde & Schwarz	ESU	1302.6005.26	May 19, 2018	May 18, 2019
Pre-Amplifier	A.H.	PAM-0126	1415261	May 20, 2018	May 19, 2019
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170399	May 20, 2018	May 19, 2019
Cable	H+B	0.5M SF104-26.5	289147/4	May 20, 2018	May 19, 2019
Cable	H+B	3M SF104-26.5	295838/4	May 20, 2018	May 19, 2019
Cable	H+B	6M SF104-26.5	295840/4	May 20, 2018	May 19, 2019

4.2.6 For 3m Radiated Emission Measurement 26.5G-40G (3m chamber 3#)

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	DUE CAL.
EMI Test Receiver	Rohde & Schwarz	FSV40	132.1-3008K39-100967-AP	May 19, 2018	May 18, 2019
Pre-Amplifier	Lunar EM	LNA26G40-40	J1013131028001	May 19, 2018	May 18, 2019
Horn Antenna	AHS/USA	SAS-573	184	May 20, 2018	May 19, 2019
Cable	A.H	SAC-40G-1	414	May 20, 2018	May 19, 2019
Cable	A.H	SAC-40G-1	413	May 20, 2018	May 19, 2019

4.2.7 Radio Frequency Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	DUE CAL.
Spectrum Analyzer	Agilent	E4407B	88156318	May 20, 2018	May 19, 2019
Signal Analyzer	Agilent	N9010A	My53470879	May 20, 2018	May 19, 2019
Power meter	Anritsu	ML2495A	0824006	May 20, 2018	May 19, 2019
Power sensor	Anritsu	MA2411B	0738172	May 20, 2018	May 19, 2019

Remark: Each piece of equipment is scheduled for calibration once a year.

4.3 DESCRIPTION OF TEST MODES

The EUT has been tested under its typical operating condition.

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Those data rates (Bluetooth with BLE mode: 1Mbps) were used for all test.

Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Frequency and Channel list for Bluetooth with BLE mode:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	19	2440	...	...
1	2404	20	2442	37	2476
2	2406	21	2444	38	2478
...	...	...	...	39	2480
Note: $f_c = 2402\text{MHz} + k \times 1\text{MHz}$ $k=1$ to 39					

Test Frequency and channel for Bluetooth with BLE mode:

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	19	2440	39	2480

5 FACILITIES AND ACCREDITATIONS

5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at

Bldg 69, Majialong Industry Zone District, Nanshan District, Shenzhen, China

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 and CISPR Publication 22.

5.2 LABORATORY ACCREDITATIONS AND LISTINGS

Site Description

- EMC Lab.
- : Accredited by CNAS, 2016.10.24
The certificate is valid until 2022.10.28
The Laboratory has been assessed and proved to be in compliance with CNAS-CL01: 2006(identical to ISO/IEC17025: 2005)
The Certificate Registration Number is L2291
 - : Accredited by TUV Rheinland Shenzhen, 2016.5.19
The Laboratory has been assessed according to the requirements ISO/IEC 17025.
 - : Accredited by FCC, August 06, 2018
The certificate is valid until August 07, 2020
Designation Number: CN1204
Test Firm Registration Number: 882943
 - : Accredited by Industry Canada, November 09, 2018
The Conformity Assessment Body Identifier is CN0008.

6 TEST SYSTEM UNCERTAINTY

The following measurement uncertainty levels have been estimated for tests performed on the apparatus:


Parameter	Uncertainty
Radio Frequency	$\pm 1 \times 10^{-5}$
Maximum Peak Output Power Test	$\pm 1.0\text{dB}$
Conducted Emissions Test	$\pm 2.0\text{dB}$
Radiated Emission Test	$\pm 2.0\text{dB}$
Power Density	$\pm 2.0\text{dB}$
Occupied Bandwidth Test	$\pm 1.0\text{dB}$
Band Edge Test	$\pm 3\text{dB}$
All emission, radiated	$\pm 3\text{dB}$
Antenna Port Emission	$\pm 3\text{dB}$
Temperature	$\pm 0.5^{\circ}\text{C}$
Humidity	$\pm 3\%$

Measurement Uncertainty for a level of Confidence of 95%

7 SETUP OF EQUIPMENT UNDER TEST

7.1 RADIO FREQUENCY TEST SETUP 1

The Bluetooth with BLE mode component's antenna ports(s) of the EUT are connected to the measurement instrument per an appropriate attenuator. The EUT is controlled by PC/software to emit the specified signals for the purpose of measurements.



7.2 RADIO FREQUENCY TEST SETUP 2

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10. The test distance is 3m. The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 and CAN/CSA-CEI/IEC CISPR 22.

Below 30MHz:

The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna (loop antenna). The Antenna should be positioned with its plane vertical at the specified distance from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. The center of the loop shall be 1 m above the ground. For certain applications, the loop antenna plane may also need to be positioned horizontally at the specified distance from the EUT.


30MHz-1GHz:

The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).


Above 1GHz:

The EUT is placed on a turntable 1.5 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).


(a) Radiated Emission Test Set-Up, Frequency Below 30MHz



(b) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(c) Radiated Emission Test Set-Up, Frequency above 1000MHz




7.3 CONDUCTED EMISSION TEST SETUP

The mains cable of the EUT (maybe per AC/DC Adapter) must be connected to LISN. The LISN shall be placed 0.8 m from the boundary of EUT and bonded to a ground reference plane for LISN mounted on top of the ground reference plane. This distance is between the closest points of the LISN and the EUT. All other units of the EUT and associated equipment shall be at least 0.8m from the LISN.

Ground connections, where required for safety purposes, shall be connected to the reference ground point of the LISN and, where not otherwise provided or specified by the manufacturer, shall be of same length as the mains cable and run parallel to the mains connection at a separation distance of not more than 0.1 m.

According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.



7.4 SUPPORT EQUIPMENT

Item	Equipment	Mfr/Brand	Model/Type No.	Note
1.	Notebook	Lenovo	WB0205140E	WB06355728

Notes:

- 1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.*
- 2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.*

8 TEST REQUIREMENTS

8.1 DTS 6DB BANDWIDTH

8.1.1 Applicable Standard

According to FCC Part 15.247(a)(2) and KDB 558074 DTS 01 Meas. Guidance v05r02

8.1.2 Conformance Limit

The minimum -6 dB bandwidth shall be at least 500 kHz.

8.1.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

8.1.4 Test Procedure

The EUT was operating in Bluetooth with BLE mode and controlled its channel. Printed out the test result from the spectrum by hard copy function.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously

Set RBW = 100 kHz.

Set the video bandwidth (VBW) =300 kHz.

Set Span=2 times OBW

Set Detector = Peak.

Set Trace mode = max hold.

Set Sweep = auto couple.

Allow the trace to stabilize.

Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Measure and record the results in the test report.


Test Results

Temperature :	28°C	Test Date :	March 20, 2019
Humidity :	55 %	Test By:	KK

Operation Mode	Channel Number	Channel Frequency (MHz)	Measurement Bandwidth (kHz)	Limit (kHz)	Verdict
Bluetooth with BLE mode	0	2402	703.3	>500	PASS
	19	2440	703.3	>500	PASS
	39	2480	703.3	>500	PASS


Test Model

DTS (6dB) Bandwidth
Bluetooth with BLE mode
Channel 0: 2402MHz




Test Model

DTS (6dB) Bandwidth
Bluetooth with BLE mode
Channel 19: 2440MHz



Test Model

DTS (6dB) Bandwidth
Bluetooth with BLE mode
Channel 39: 2480MHz



Date: 20.MAR.2019 17:59:51

8.2 MAXIMUM PEAK CONDUCTED OUTPUT POWER

8.2.1 Applicable Standard

According to FCC Part 15.247(b)(3) and KDB 558074 DTS 01 Meas. Guidance v05r02

8.2.2 Conformance Limit

FCC:

The maximum peak conducted output power of the intentional radiator for systems using digital modulation in the 2400 - 2483.5 MHz bands shall not exceed: 1 Watt (30dBm).

IC:

For DTSs employing digital modulation techniques operating in the bands 902-928 MHz and 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1 W. The e.i.r.p. shall not exceed 4 W.

8.2.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

8.2.4 Test Procedure

■ According to FCC Part 15.247(b)(3)

As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. For smart system, Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Set the RBW $\geq$ DTS bandwidth (about 1MHz).

Set VBW = 3*RBW (about 3MHz)

Set the span $\geq$ 3*RBW

Set Sweep time = auto couple.

Set Detector = peak.

Set Trace mode = max hold.

Allow trace to fully stabilize. Use peak marker function to determine the peak amplitude level.

■ According to FCC Part 15.247(b)(4):

Conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Test Results

Temperature :	28°C	Test Date :	March 21, 2019
Humidity :	55 %	Test By:	KK

Channel Number	Channel Frequency (MHz)	Measurement Level (dBm)	EIRP (dBm)	Limit for peak conducted output power (dBm)	Limit for EIRP (dBm)	Verdict
0	2402	4.64	9.84	30	36	PASS
19	2440	3.86	9.06	30	36	PASS
39	2480	3.44	8.64	30	36	PASS
Note: The antenna gain is 5.2dBi						

8.3 MAXIMUM POWER SPECTRAL DENSITY

8.3.1 Applicable Standard

According to FCC Part 15.247(e) and KDB 558074 DTS 01 Meas. Guidance v05r02

8.3.2 Conformance Limit

The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

8.3.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

8.3.4 Test Procedure

This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance

The transmitter output (antenna port) was connected to the spectrum analyzer

Set analyzer center frequency to DTS channel center frequency.

Set the span to 1.5 times the DTS bandwidth.

Set the RBW to: 3 kHz

Set the VBW to: 10 kHz.

Set Detector = peak.

Set Sweep time = auto couple.

Set Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level within the RBW.

8.3.5 Test Results


Temperature :	28°C	Test Date :	March 21, 2019
Humidity :	55 %	Test By:	KK

Operation Mode	Channel Number	Channel Frequency (MHz)	Measurement Level (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
Bluetooth with BLE mode	0	2402	-14.65	<8	PASS
	19	2440	-13.05	<8	PASS
	39	2480	-12.12	<8	PASS

Note: N/A


Test Model

Power Spectral Density
Bluetooth with BLE mode
Channel 0: 2402MHz




Test Model

Power Spectral Density
Bluetooth with BLE mode
Channel 19: 2440MHz



Test Model

Power Spectral Density
Bluetooth with BLE mode
Channel 39: 2480MHz



Date: 20.MAR.2019 18:05:44

8.4 UNWANTED EMISSIONS IN NON-RESTRICTED FREQUENCY BANDS

8.4.1 Applicable Standard

According to FCC Part 15.247(d) and KDB 558074 DTS 01 Meas. Guidance v05r02

8.4.2 Conformance Limit

According to FCC Part 15.247(d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

8.4.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

8.4.4 Test Procedure

The transmitter output (antenna port) was connected to the spectrum analyzer

■ Reference level measurement

Establish a reference level by using the following procedure:

Set instrument center frequency to DTS channel center frequency.

Set the span to = 1.5 times the DTS bandwidth.

Set the RBW = 100 kHz.

Set the VBW $\geq 3 \times$ RBW.

Set Detector = peak.

Set Sweep time = auto couple.

Set Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum PSD level.

Note that the channel found to contain the maximum PSD level can be used to establish the reference level.

■ Emission level measurement

Set the center frequency and span to encompass frequency range to be measured.

Set the RBW = 100 kHz.

Set the VBW = 300 kHz.

Set Detector = peak

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.


Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements. Report the three highest emissions relative to the limit.

8.4.5 Test Results


Test Model

PSD(Power Spectral Density) RBW=100kHz
Bluetooth with BLE mode
Channel 0: 2402MHz




Test Model

Unwanted Emissions in non-restricted frequency bands
Bluetooth with BLE mode
Channel 0: 2402MHz




Test Model

Band edge
Bluetooth with BLE mode
Channel 0: 2402MHz




Date: 20.MAR.2019 18:07:18



Date: 25.MAR.2019 16:14:03

Test Model


PSD(Power Spectral Density) RBW=100kHz
Bluetooth with BLE mode
Channel 19: 2440MHz




Date: 20.MAR.2019 18:08:42

Test Model

Band edge
Bluetooth with BLE mode
Channel 0: 2440MHz




Date: 25.MAR.2019 16:16:29



Date: 25.MAR.2019 16:17:13

Test Model


Unwanted Emissions In Non-Restricted Frequency Bands
Bluetooth with BLE mode
Channel 19: 2440MHz



Date: 20.MAR.2019 18:09:38

Test Model


PSD(Power Spectral Density) RBW=100kHz
Bluetooth with BLE mode
Channel 19: 2480MHz



Date: 20.MAR.2019 18:10:09

Test Model


Unwanted Emissions In Non-Restricted Frequency Bands
Bluetooth with BLE mode
Channel 39: 2480MHz




Date: 20.MAR.2019 18:11:22

Test Model

Band edge
Bluetooth with BLE mode
Channel 39: 2480MHz



Date: 25.MAR.2019 16:15:17



Date: 20.MAR.2019 18:10:55

8.5 RADIATED SPURIOUS EMISSION

8.5.1 Applicable Standard

According to FCC Part 15.247(d) and 15.209 and KDB 558074 DTS 01 Meas. Guidance v05r02
According to KDB 558074 DTS 01 Meas. Guidance v05r02

8.5.2 Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
According to FCC Part 15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

According to FCC Part 15.205, the level of any transmitter spurious emission in Restricted bands shall not exceed the level of the emission specified in the following table

Restricted Frequency(MHz)	Field Strength (μV/m)	Field Strength (dBμV/m)	Measurement Distance
0.009-0.490	2400/F(KHz)	20 log (uV/m)	300
0.490-1.705	2400/F(KHz)	20 log (uV/m)	30
1.705-30	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

8.5.3 Test Configuration

Test according to clause 7.2 radio frequency test setup 2

8.5.4 Test Procedure

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz (1GHz to 25GHz), 100 kHz for $f < 1$ GHz (30MHz to 1GHz)

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Follow the guidelines in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this test, in order to provide the measuring system with sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit specified in Section 15.35(b). Submit this data.

Now set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a "duty cycle correction factor", derived from $20\log(\text{dwell time}/100 \text{ ms})$, in an effort to demonstrate compliance with the 15.209 limit. Submit this data.


Repeat above procedures until all frequency measured was complete.

8.5.5 Test Results

■ Spurious Emission below 30MHz (9KHz to 30MHz)

Temperature: 27°C
Humidity: 49 %
Test mode: TX 2402

Test Date: March 29, 2019
Test By: KK



Site 3m Chamber 1#

Polarization: X

Temperature: 27 C

Limit: (RE)FCC PART 15.209(9K-30M)


Power: AC 120V/60Hz

Humidity: 49 %


Mode: BLE TX 2402

Note:


No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1	*	0.0290	35.19	20.92	56.11	118.34	-62.23	peak		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	0.5885	35.40	21.25	56.65	72.21	-15.56	peak		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1	*	0.0246	36.69	20.84	57.53	119.77	-62.24	peak		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1	*	0.5100	32.08	21.28	53.36	73.45	-20.09	peak		Comment



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1	*	0.7914	33.64	21.20	54.84	69.65	-14.81	peak		Comment




Site 3m Chamber 1# Polarization: **Z** Temperature: 27 C
 Limit: (RE)FCC PART 15.209(9K-30M) Power: AC 120V/60Hz Humidity: 49 %
 Mode:BLE TX 2402
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	0.0228	33.58	20.81	54.39	120.43	-66.04	peak		

Temperature: 27°C
Humidity: 49 %
Test mode: TX 2440

Test Date: March 29, 2019
Test By: KK



Site 3m Chamber 1#

Polarization: X

Temperature: 27 C

Limit: (RE)FCC PART 15.209(9K-30M)


Power: AC 120V/60Hz

Humidity: 49 %


Mode: BLE TX 2440

Note:


No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1	*	0.0466	27.01	21.22	48.23	114.22	-65.99	peak		Comment




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	0.5885	31.90	21.25	53.15	72.21	-19.06	peak		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1	*	0.0246	36.69	20.84	57.53	119.77	-62.24	peak		Comment




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	1.5683	27.91	21.06	48.97	63.72	-14.75	peak		



Site 3m Chamber 1# Polarization: **Z** Temperature: 27 C
 Limit: (RE)FCC PART 15.209(9K-30M) Power: AC 120V/60Hz Humidity: 49 %
 Mode:BLE TX 2440
 Note:


No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1	*	0.0724	29.56	20.58	50.14	110.40	-60.26	peak		Comment



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1	*	0.7914	32.14	21.20	53.34	69.65	-16.31	peak		Comment

Temperature: 27°C
Humidity: 49 %
Test mode: TX 2480

Test Date: March 29, 2019
Test By: KK



Site 3m Chamber 1#

Polarization: X

Temperature: 27 C

Limit: (RE)FCC PART 15.209(9K-30M)


Power: AC 120V/60Hz

Humidity: 49 %


Mode: BLE TX 2480

Note:


No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1	*	0.0627	25.62	20.88	46.50	111.65	-65.15	peak		Comment




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	0.5885	29.40	21.25	50.65	72.21	-21.56	peak		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	0.0383	31.80	21.07	52.87	115.93	-63.06	peak		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1	*	0.5100	30.08	21.28	51.36	73.45	-22.09	peak		Comment



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	0.0480	27.79	21.25	49.04	113.97	-64.93	peak		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1	*	0.7913	30.64	21.20	51.84	69.65	-17.81	peak		Comment

■ Spurious Emission Above 1GHz (1GHz to 25GHz)


Bluetooth with BLE mode have been tested, and the worst result was report as below:

Temperature : 28℃ Test Date : March 29, 2019
Humidity : 55 % Test By: KK
Test mode: Bluetooth with BLE mode Frequency: Channel 0: 2402MHz




Site 3m Chamber #1 Polarization: **Horizontal** Temperature: 27 C
Limit: (RE)FCC PART 15C Power: AC 120V/60Hz Humidity: 43 %
Mode: BLE 2402
Note:


No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
		MHz	Level	Factor	ment			Height	Degree	
			dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		2006.587	64.35	-19.49	44.86	74.00	-29.14	peak		
2		2006.587	55.90	-19.49	36.41	54.00	-17.59	AVG		
3		4045.053	61.17	-15.04	46.13	74.00	-27.87	peak		
4		4045.053	51.62	-15.04	36.58	54.00	-17.42	AVG		
5		7786.979	59.33	-6.72	52.61	74.00	-21.39	peak		
6	*	7786.979	43.95	-6.72	37.23	54.00	-16.77	AVG		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		1751.955	65.01	-19.39	45.62	74.00	-28.38	peak		
2		1751.955	55.82	-19.39	36.43	54.00	-17.57	AVG		
3		3908.852	62.02	-15.53	46.49	74.00	-27.51	peak		
4		3908.852	52.15	-15.53	36.62	54.00	-17.38	AVG		
5		7463.052	60.17	-7.73	52.44	74.00	-21.56	peak		
6	*	7463.052	44.85	-7.73	37.12	54.00	-16.88	AVG		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		25701.00	87.40	-36.15	51.25	74.00	-22.75	peak		
2	*	25701.00	71.79	-36.15	35.64	54.00	-18.36	AVG		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		26287.50	87.27	-35.44	51.83	74.00	-22.17	peak		
2	*	26287.50	72.39	-35.44	36.95	54.00	-17.05	AVG		

Temperature : 28°C Test Date : March 29, 2019
 Humidity : 55 % Test By: KK
 Test mode: Bluetooth with BLE mode Frequency: Channel 19: 2440MHz




Site 3m Chamber #1 Polarization: **Horizontal** Temperature: 27 C
 Limit: (RE)FCC PART 15C Power: AC 120V/60Hz Humidity: 43 %
 Mode: BLE 2440
 Note:


No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
		MHz	Level	Factor	ment			Height	Degree	
			dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		1716.864	65.72	-19.38	46.34	74.00	-27.66	peak		
2		1716.864	55.64	-19.38	36.26	54.00	-17.74	AVG		
3		3987.591	61.94	-15.17	46.77	74.00	-27.23	peak		
4		3987.591	51.91	-15.17	36.74	54.00	-17.26	AVG		
5		7655.312	60.17	-7.16	53.01	74.00	-20.99	peak		
6	*	7655.312	44.38	-7.16	37.22	54.00	-16.78	AVG		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		1741.856	64.49	-19.39	45.10	74.00	-28.90			peak
2		1741.856	55.81	-19.39	36.42	54.00	-17.58			AVG
3		4042.716	61.46	-15.05	46.41	74.00	-27.59			peak
4	*	4042.716	51.92	-15.05	36.87	54.00	-17.13			AVG
5		8039.699	59.32	-5.97	53.35	74.00	-20.65			peak
6		8039.699	42.53	-5.97	36.56	54.00	-17.44			AVG



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		24953.00	86.72	-37.02	49.70	74.00	-24.30	peak		
2	*	24953.00	71.38	-37.02	34.36	54.00	-19.64	AVG		




Site 3m Chamber #3
Limit: (RE)FCC PART 15 C
Mode:BLE 2440
Note:

Polarization: **Vertical**
Power: AC 120V/60Hz
Temperature: 24 C
Humidity: 53 %


No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1		24239.00	87.59	-37.10	50.49	74.00	-23.51	peak		
2	*	24239.00	72.52	-37.10	35.42	54.00	-18.58	AVG		

Temperature : 28°C Test Date : March 29, 2019
 Humidity : 55 % Test By: KK
 Test mode: Bluetooth with BLE mode Frequency: Channel 39: 2480MHz




Site 3m Chamber #1 Polarization: **Horizontal** Temperature: 27 C
 Limit: (RE)FCC PART 15C Power: AC 120V/60Hz Humidity: 43 %
 Mode: BLE 2480
 Note:


No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
		MHz	Level	Factor	ment			Height	Degree	
			dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		1912.583	64.87	-19.46	45.41	74.00	-28.59	peak		
2		1912.583	55.71	-19.46	36.25	54.00	-17.75	AVG		
3		3895.881	62.55	-15.59	46.96	74.00	-27.04	peak		
4		3895.881	52.16	-15.59	36.57	54.00	-17.43	AVG		
5		5503.938	60.41	-12.27	48.14	74.00	-25.86	peak		
6	*	5503.938	49.53	-12.27	37.26	54.00	-16.74	AVG		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		1714.385	65.75	-19.38	46.37	74.00	-27.63	peak		
2		1714.385	55.61	-19.38	36.23	54.00	-17.77	AVG		
3		5248.368	59.52	-12.63	46.89	74.00	-27.11	peak		
4	*	5248.368	49.86	-12.63	37.23	54.00	-16.77	AVG		
5		7980.660	59.90	-6.06	53.84	74.00	-20.16	peak		
6		7980.660	43.05	-6.06	36.99	54.00	-17.01	AVG		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		24230.50	86.78	-37.10	49.68	74.00	-24.32	peak		
2	*	24230.50	71.39	-37.10	34.29	54.00	-19.71	AVG		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		24171.00	87.62	-37.11	50.51	74.00	-23.49	peak		
2	*	24171.00	71.94	-37.11	34.83	54.00	-19.17	AVG		

■ Spurious Emission in Restricted Band 2310-2390MHz and 2483.5-2500MHz

Test Model	Spurious Emission in Restricted Band 2310-2390MHz Bluetooth with BLE mode Channel 0: 2402MHz	H
------------	--	---



Site 3m Chamber #1

Polarization: **Horizontal**

Temperature: 27 C

Limit: (RE)FCC PART 15C

Power: AC 120V/60Hz


Humidity: 43 %

Mode:BLE 2402

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		2343.608	63.71	-18.59	45.12	74.00	-28.88	peak		
2	*	2343.608	56.44	-18.59	37.85	54.00	-16.15	AVG		
3		2360.772	63.50	-18.54	44.96	74.00	-29.04	peak		
4		2360.772	55.49	-18.54	36.95	54.00	-17.05	AVG		
5		2389.208	64.65	-18.47	46.18	74.00	-27.82	peak		
6		2389.208	53.32	-18.47	34.85	54.00	-19.15	AVG		


Test Model	Spurious Emission in Restricted Band 2483.5-2500MHz		
	Bluetooth with BLE mode		
	Channel 0: 2402MHz		V



Site 3m Chamber #1 Polarization: **Vertical** Temperature: 27 C
 Limit: (RE)FCC PART 15C Power: AC 120V/60Hz Humidity: 43 %
 Mode:BLE 2402
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		2324.052	67.18	-18.64	48.54	74.00	-25.46	peak		
2		2324.052	57.55	-18.64	38.91	54.00	-15.09	AVG		
3		2346.424	66.57	-18.58	47.99	74.00	-26.01	peak		
4		2346.424	57.23	-18.58	38.65	54.00	-15.35	AVG		
5		2383.276	65.82	-18.49	47.33	74.00	-26.67	peak		
6	*	2383.276	58.09	-18.49	39.60	54.00	-14.40	AVG		

Test Model	Spurious Emission in Restricted Band 2310-2390MHz		
	Bluetooth with BLE mode		
	Channel 39: 2480MHz	H	



Site 3m Chamber #1 Polarization: **Horizontal** Temperature: 27 C
Limit: (RE)FCC PART 15C Power: AC 120V/60Hz Humidity: 43 %

Mode: BLE 2480
Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		2485.882	68.05	-18.21	49.84	74.00	-24.16	peak		
2	*	2485.882	55.06	-18.21	36.85	54.00	-17.15	AVG		
3		2488.575	68.20	-18.20	50.00	74.00	-24.00	peak		
4		2488.575	53.89	-18.20	35.69	54.00	-18.31	AVG		
5		2494.591	69.50	-18.19	51.31	74.00	-22.69	peak		
6		2494.591	54.73	-18.19	36.54	54.00	-17.46	AVG		


Test Model

Spurious Emission in Restricted Band 2483.5-2500MHz

Bluetooth with BLE mode

Channel 39: 2480MHz

V



Site 3m Chamber #1

Polarization: **Vertical**

Temperature: 27 C

Limit: (RE)FCC PART 15C

Power: AC 120V/60Hz


Humidity: 43 %

Mode: BLE 2480


Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		2485.238	66.94	-18.21	48.73	74.00	-25.27	peak		
2		2485.238	57.79	-18.21	39.58	54.00	-14.42	AVG		
3		2488.058	68.02	-18.20	49.82	74.00	-24.18	peak		
4		2488.058	55.09	-18.20	36.89	54.00	-17.11	AVG		
5		2495.062	69.47	-18.19	51.28	74.00	-22.72	peak		
6	*	2495.062	59.44	-18.19	41.25	54.00	-12.75	AVG		


■ Spurious Emission below 1GHz (30MHz to 1GHz)




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
		MHz	Level	Factor	ment			Height	Degree	
			dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		192.3537	36.10	-12.17	23.93	43.50	-19.57	QP		
2		240.3687	31.90	-10.15	21.75	46.00	-24.25	QP		
3		417.1512	30.51	-5.63	24.88	46.00	-21.12	QP		
4		599.9961	29.36	-2.15	27.21	46.00	-18.79	QP		
5		726.4600	29.28	-0.62	28.66	46.00	-17.34	QP		
6	*	759.3187	30.00	-0.04	29.96	46.00	-16.04	QP		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1		192.5961	29.94	-12.15	17.79	43.50	-25.71	QP		
2		323.5462	27.36	-7.79	19.57	46.00	-26.43	QP		
3		373.8650	27.77	-6.75	21.02	46.00	-24.98	QP		
4		462.1350	28.36	-5.30	23.06	46.00	-22.94	QP		
5		526.5187	29.08	-4.22	24.86	46.00	-21.14	QP		
6	*	618.9112	28.81	-1.92	26.89	46.00	-19.11	QP		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		191.9900	36.00	-12.21	23.79	43.50	-19.71	QP		
2		240.0050	31.59	-10.16	21.43	46.00	-24.57	QP		
3		477.0487	28.67	-5.08	23.59	46.00	-22.41	QP		
4		624.1250	29.82	-1.89	27.93	46.00	-18.07	QP		
5		688.8724	28.77	-1.17	27.60	46.00	-18.40	QP		
6	*	783.2050	29.20	0.14	29.34	46.00	-16.66	QP		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		192.1111	31.64	-12.20	19.44	43.50	-24.06	QP		
2		240.0050	30.65	-10.16	20.49	46.00	-25.51	QP		
3		400.0550	27.95	-6.02	21.93	46.00	-24.07	QP		
4		513.0600	28.14	-4.53	23.61	46.00	-22.39	QP		
5		736.6450	29.12	-0.42	28.70	46.00	-17.30	QP		
6	*	836.9187	28.65	0.73	29.38	46.00	-16.62	QP		



Site 3m Chamber 1#

Polarization: **Horizontal**

Temperature: 27 C

Limit: (RE)FCC PART 15 C


Power: AC 120V/60Hz

Humidity: 43 %

Mode: BLE TX 2480

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		191.8687	36.65	-12.22	24.43	43.50	-19.07	QP		
2		400.0550	31.37	-6.02	25.35	46.00	-20.65	QP		
3		596.6012	29.26	-2.28	26.98	46.00	-19.02	QP		
4		714.5774	29.41	-0.80	28.61	46.00	-17.39	QP		
5		813.0324	29.11	0.42	29.53	46.00	-16.47	QP		
6	*	925.0674	28.98	2.60	31.58	46.00	-14.42	QP		



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
		MHz	Level	Factor	ment			Height	Degree	
			dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		192.1111	32.09	-12.20	19.89	43.50	-23.61	QP		
2		416.4237	28.01	-5.64	22.37	46.00	-23.63	QP		
3		613.5762	27.52	-1.98	25.54	46.00	-20.46	QP		
4		739.9187	28.92	-0.35	28.57	46.00	-17.43	QP		
5		853.2875	27.76	1.02	28.78	46.00	-17.22	QP		
6	*	956.3500	29.70	3.11	32.81	46.00	-13.19	QP		

8.6 CONDUCTED EMISSIONS TEST

8.6.1 Applicable Standard

According to FCC Part 15.207(a)

8.6.2 Conformance Limit

Frequency(MHz)	Conducted Emission Limit	
	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

8.6.3 Test Configuration

Test according to clause 7.3 conducted emission test setup


8.6.4 Test Procedure

The EUT was placed on a table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Repeat above procedures until all frequency measured were complete.

8.6.5 Test Results



Site Conduction #1

Phase: **L1**

Temperature: 24.9C

Limit: (CE)FCC PART 15.207


Power: AC 120V/60Hz

Humidity: 54 %

Mode: BT ON+LED white

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV	dBuV	dB		
1		0.1580	30.74	19.76	50.50	65.57	-15.07	QP	
2		0.1580	12.06	19.76	31.82	55.57	-23.75	AVG	
3		0.4940	24.76	19.31	44.07	56.10	-12.03	QP	
4	*	0.4940	15.20	19.31	34.51	46.10	-11.59	AVG	
5		1.1220	18.66	19.22	37.88	56.00	-18.12	QP	
6		1.1220	6.21	19.22	25.43	46.00	-20.57	AVG	
7		2.7100	18.11	19.19	37.30	56.00	-18.70	QP	
8		2.7100	4.00	19.19	23.19	46.00	-22.81	AVG	
9		5.9060	15.21	19.23	34.44	60.00	-25.56	QP	
10		5.9060	1.14	19.23	20.37	50.00	-29.63	AVG	
11		17.6220	15.53	19.67	35.20	60.00	-24.80	QP	
12		17.6220	1.69	19.67	21.36	50.00	-28.64	AVG	



Site Conduction #1
 Limit: (CE)FCC PART 15.207
 Mode: BT ON+LED white
 Note:

Phase: **N**
 Power: AC 120V/60Hz

Temperature: 24.9C
 Humidity: 54 %

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1500	28.40	19.83	48.23	66.00	-17.77	QP	
2		0.1500	10.68	19.83	30.51	56.00	-25.49	AVG	
3		0.3620	22.00	19.38	41.38	58.68	-17.30	QP	
4	*	0.3620	13.11	19.38	32.49	48.68	-16.19	AVG	
5		1.1300	18.81	19.22	38.03	56.00	-17.97	QP	
6		1.1300	10.33	19.22	29.55	46.00	-16.45	AVG	
7		1.9700	17.85	19.18	37.03	56.00	-18.97	QP	
8		1.9700	8.14	19.18	27.32	46.00	-18.68	AVG	
9		3.6540	16.20	19.19	35.39	56.00	-20.61	QP	
10		3.6540	6.38	19.19	25.57	46.00	-20.43	AVG	
11		17.7260	12.39	19.67	32.06	60.00	-27.94	QP	
12		17.7260	-2.11	19.67	17.56	50.00	-32.44	AVG	

8.7 ANTENNA APPLICATION

8.7.1 Antenna Requirement

Standard	Requirement
FCC CRF Part 15.203	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

8.7.2 Result

PASS.

The EUT has 1 antenna: a PCB Antenna for BLE, the gain is 5.2 dBi;

- Note:
- ☒ Antenna use a permanently attached antenna which is not replaceable.
 - ☐ Not using a standard antenna jack or electrical connector for antenna replacement
 - ☐ The antenna has to be professionally installed (please provide method of installation)

which in accordance to section 15.203, please refer to the internal photos.