Wireless Indoor or Outdoor Humidity And Temperature Monitor User Guide

(WTH001)

Indoor temperature and humidity monitor main machine
(hereinafter called main machine)

Indoor/Outdoor wireless remote sensor auxiliary machine
(hereinafter called auxiliary machine)

Please read this manual carefully before usingthe product and keep it in a safe place for future reference.

Table of content

1.Introduction.....1
2.Precaution.....1
3.Main machine features.....2
4.Auxiliary machine features.....3
5.Battery replacement and product placement.....4
6.Main machine & auxiliary machine synchronization and installation.....6
7.Main machine & auxiliary machine placement.....7
8.Maximum & minimum recorded temperature & humidity.....8
9.Comfort level icon display.....9
10.Package list.....9
11.Specification.....9
12.Troubleshooting.....10
14.Certification.....11

Introduction

Thanks for your purchase of the Wireless Indoor or Outdoor Humidity And Temperature Monitor. You can place the auxiliary machine indoor or outdoor, and the collected data will be transmitted to the main machine indoor to let you know the indoor or outdoor temperature and humidity changes from the screen on the main machine.

Precaution

- Please take good care of the button battery to avoid accidental ingestion by children. For adult use only.
- The temperature of the product shall not exceed 60°C and shall not be lower than -20°C. Humidity must not be more than 99%, and not be less than 0%.
- This product is not fireproof, do not throw it into the fire or place it near any fire source.
- This product is not waterproof, do not immerse it into water in case of damage.
- Please remove the battery insulation sheet before using.

Main machine features

1 Comfort Level Icon
2 "SNP" Key icon
3 Temperature trend icon
4 "MAX/MIN" Icon
5 Main machine temperature/humidity/time/date/week/month/year
6 "+" Button to setting sign
7 Main machine temperature/humidity/time/date/week/month/year and humidity
8 "-" Button to setting sign
9 "SYNC/PAIR" Button
10 "MODE" Button
11 "DISPLAY" Button
12 Main machine temperature/humidity/time/date/week/month/year and humidity
13 "SYNC/PAIR" Button
14 "MAX/MIN" Button
15 Main machine temperature/humidity/time/date/week/month/year and humidity
16 Battery cover
17 Battery installation direction
18 Battery cover lock
19 Battery installation direction
20 Battery cover lock
21 Battery cover
22 Battery installation direction
23 Battery cover lock
24 Battery cover
25 Battery installation direction
26 Battery cover lock
27 Battery cover
28 Battery installation direction
29 Battery cover lock
30 "MODE" Indoor icon
31 Auxiliary machine temperature and humidity display
32 "MAX/MIN" Temperature/Humidity/Time/Date/Week/Month/Year
33 "C" Temperature and humidity indicator
34 "%" Temperature and humidity indicator
35 "C" Celsius icon
36 "%" Humidity icon
37 Communication signal icon
38 Low battery warning icon

1 "SYNC/PAIR"
2 Press to synchronize the data from the auxiliary machine
3 Press and hold to reset the pairing mode of the auxiliary machine
4 "+"
5 Press to enter the setting mode
6 "MAX/MIN/CLEAR"
7 Press to clear the maximum and min. value
8 "-"
9 Press to enter the setting mode
10 "C/°F"
11 Press to change the temperature Celsius/°C or °F

Back view

1 Tripod for placing the main machine on the desktop
2 Hole for hanging the main machine on the wall

Top view

1 Tripod stand

Bottom view

1 Tripod stand
2 Hole for hanging the main machine on the wall

Auxiliary machine features

1 Battery installation direction
2 Battery cover lock
3 Battery cover
4 Battery installation direction
5 Battery cover lock
6 Battery cover
7 Battery installation direction
8 Battery cover lock
9 Battery cover